



2018


**JCB HYDRAULIC EXCAVATOR  
JS 131**



**JCB, Inc. North American  
MACHINE PRICE LIST  
in U.S. Dollars**

**EFFECTIVE: April 1, 2018**

CHANGES TO SPECIFICATIONS AND/OR PRICES MAY OCCUR.  
PLEASE REFER TO THE PRODUCT MANAGER FOR UPDATES

	<b>JS131 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## STANDARD EQUIPMENT

<b>ENGINE</b>	JCB Ecomax 444, 74 HP at 1,800 RPM. Four-cylinder water cooled common rail direct injection diesel engine. Low emission engine, EPA Tier 4 Final compliant. Dual element air cleaner.
<b>HYDRAULICS</b>	Variable flow load sensing system with on demand and servo operated multi function open center control. Independent servo gear pump. Two main axial piston pumps yield combined flow of 68.6 GPM. Servo pump flow: 5.3 GPM.
<b>OPERATOR'S AREA</b>	Air conditioned cab, noise and vibration isolated by six hydraulically damped resilient mountings. Opening door window. Fan forced fresh air ventilation with defogger and washer/wiper. Fully adjustable suspension seat with seatbelt, headrest, armrests, and backrest recline. Two boom and one mainframe work light
<b>CONTROLS</b>	Excavator controls are ISO pattern, servo operated, with in cab 7" digital display and change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance and a console mounted switch.
<b>UPPER</b>	Monoboomb with choice of dipper arms to suit dig depth requirements. No reinforcing required for hammer operations. Boom: 15' 5" (4.7m). Dippers: 8' 2" (2.5m), 9' 10" (3.0m).
<b>UNDERCARRIAGE</b>	The undercarriage gives excellent stability, is a fully welded X-frame type with undercarriage center cover, engine undercover and travel drive motor, cover and shields. Twin top and seven bottom rollers are heat-treated, sealed and lubricated. Track idler is sealed and lubricated and incorporates spring cushion recoil.
<b>TRACK DRIVE</b>	Full hydrostatic, 2 speed, driven by two axial piston motors. Motors are guarded in undercarriage frame for protection from debris. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 4.1 MPH, low speed is 2.4 MPH. Parking brake is disc type, spring applied, hydraulic release.
<b>ELECTRICAL</b>	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 55 amp output alternator with 12 volt in-cab supply.
<b>LIVELINK</b>	3 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
<b>OPERATING WEIGHT</b>	Equipped with standard boom, dipper, 24" track shoes and excavator bucket: apprx. 30,350 lbs.
<b>WARRANTY</b>	3-year / 3,000 hour full coverage warranty (please see the machine warranty certificate for details)

### SECTIONS ARE ORGANIZED AS FOLLOWS:


**Section 1** - PACKAGE BUILDS

**Section 2** - CUSTOM BUILD - NEW FACTORY BUILT ORDERS

**Section 3** - OPTIONS - NEW FACTORY BUILT ORDERS

**Section 4** - ATTACHMENTS - NEW FACTORY BUILT ORDERS

**DEALER FIT - EXCAVATORS** (LISTED SEPARATELY FOR ALL EXCAVATORS)

	<b>JS131 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 1 - YELLOW SERIES

Select one of the following machine PACKAGE BUILD codes and ATTACHMENT(S) if required from the section at the bottom of this sheet. Package build configurations cannot normally be changed. If a Package Build does not meet your requirements please order a machine using the Custom Build, Attachments & Options Sections following.

### SALES

CODE	ITEM	JS131
9290	JS131 LC Primary Build Tier 4 Final	✓
900A448	Long Undercarriage 78" (1990mm) Gauge, Overall Length: 141" (3585mm)	✓
900B597	24" (600mm), Triple Grouser - 44 Link Tracks	✓
900C264	Monoboom with 9' 10" (3.0 m) Dipper. No HBCV	✓
900D396	Tipping Link with Lifting Shackle	✓
900E1U1	North American Manual Pack	✓
900KF09	Hammer/Auxiliary Prop Mono 3.0m Arm	✓
900M019	Quick Hitch Lite Installation Kit	✓
900R001	AM/FM Radio	✓


### SUGGESTED LIST PRICE

**\$133,178**

## ATTACHMENTS FOR YELLOW SERIES:

### SALES

CODE	U.S. LIST
<b>EXCAVATOR BUCKETS</b>	
YWSEA01 ADD 328/00500. 36" BUCKET	\$3,920
YWSEA02 ADD 980/A8250. HYDRAULIC COUPLER	\$5,811
YWSEA03 ADD 980/B0201. HM090T	\$18,348
YWSEA04 ADD 328/00498. 24" BUCKET	\$3,480

	<b>JS131 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS:

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each E (Essential) category below. Select Options and/or Attachments from Section 3 or 4.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	ITEM	U.S. LIST
<b>BASE UNIT (E)</b>		
9290	JS131 LC Primary Build Tier 4 Final	\$125,465
<b>UNDERCARRIAGE for 9290 BASE UNIT (E)</b>		
900A448	Long Undercarriage 78" (1990mm) Gauge, Overall Length: 141" (3585mm)	\$0
<b>TRACK PADS FOR 9290 BASE UNIT (E)</b>		
900B597	24" (600mm), Triple Grouser - 44 Link Tracks	\$2,970
900B598	28" (700mm), Triple Grouser - 44 Link Tracks	\$3,670
<b>MONO BOOM AND DIPPERS (E) Includes brackets for all attachment pipework</b>		
900C261	Monoboom with 8' 2" (2.5 m) Dipper. No HBCV	\$1,053
900C264	Monoboom with 9' 10" (3.0 m) Dipper. No HBCV	\$1,053
<b>TIPPING LINK (E)</b>		
900D396	Tipping Link with Lifting Shackle	\$477
<b>MANUAL PACK (E)</b>		
900E1U1	North American Manual Pack	\$0

**JS131 HYDRAULIC EXCAVATOR**U.S. DOLLAR  
PRICE PAGESF.O.B.  
SAVANNAH, GA

EFFECTIVE: April 1, 2018

**SECTION 3 - OPTIONS - NEW FACTORY BUILT ORDERS:**

SALES CODE	ITEM	U.S. LIST
HYDRAULIC ATTACHMENT PIPEWORK - NEW FACTORY BUILT ORDERS ONLY		
900KF08	Hammer/Auxilliary Prop Mono 2.5m Arm	\$1,523
900KF09	Hammer/Auxilliary Prop Mono 3.0m Arm	\$1,523
Notes:	• High flow circuit pipework is dual function. The merged circuit adds in up to 70% of the flow from the second main pump. When operator selects hammer function hydraulic flow is delivered in one direction to run hammer. Circuit is operated by foot pedal. When auxiliary function is selected the same pump flow is delivered bi-directionally to run tool. Circuit can be operated by the foot pedal, hand control buttons or slider depending on code available.	
	• For additional factory installed hydraulic pipework options call JCB Product Marketing.	
	• Shut-off ball valve for hammer and auxiliary pipework available through JCB Parts Dept.	
OPTIONS NEW FACTORY BUILT ORDERS ONLY		
900M108	Hydraulic Quick Hitch	\$5,811
900M019	Quick Hitch Lite Installation Kit	\$1,523
900P210	Scavenger Type Precleaner System	\$269
900R001	AM/FM Radio	\$169
900R011	Deluxe Seat - Air Suspension and Heated Base	\$726
900R035	Rainguard - Cab Mounted	\$484
900R130	Lower Level Windscreen Wiper	\$256
900S010	Vandal Cover Kit	\$2,282
900S020	FOPS Level 2 Guard - Front Windshield and Roof	\$5,618
900S025	Mesh Screen Guard for Front Windshield	\$1,477
900S034	LED Worklights	\$814
900S130	Additional Worklights	\$470
900S140	Amber Beacon - Cab Roof	\$182
900S253	Rear View Camera	\$698
900V001	HP32 Hydraulic Oil - for Cold Climate Operation	\$0
900V002	HP68 Hydraulic Oil - for Hot Climate Operation	\$0
900X040	Refueling Pump	\$590
900X381	Shut-off Valves For Auxiliary/Hammer Circuit (For 8' 2" (2.5m) Dipper)	\$723
900X382	Shut-off Valves For Auxiliary/Hammer Circuit (For 9' 10" (3.0mm) Dipper)	\$723
900X531	Twin Track Guides	\$1,404

**SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS:**

SALES CODE	ITEM	U.S. LIST
<b>EXCAVATOR BUCKETS</b>		
YWSEA01	ADD 328/00500. 36" BUCKET	\$3,920
YWSEA02	ADD 980/A8250. HYDRAULIC COUPLER	\$5,811
YWSEA03	ADD 980/B0201. HM090T	\$18,348
YWSEA04	ADD 328/00498. 24" BUCKET	\$3,480



2018


**JCB HYDRAULIC EXCAVATOR  
JZ141D**



**JCB, Inc. North American  
MACHINE PRICE LIST  
in U.S. Dollars**

**EFFECTIVE: April 1, 2018**

CHANGES TO SPECIFICATIONS AND/OR PRICES MAY OCCUR.  
PLEASE REFER TO THE PRODUCT MANAGER FOR UPDATES

	<b>JZ141D HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	-----------------------------------	----------------------------	------------------------	--------------------------

## STANDARD EQUIPMENT

<b>ENGINE</b>	JCB Ecomax 444, 74 HP at 1,800 RPM. Four-cylinder water cooled common rail direct injection diesel engine. Low emission engine, EPA Tier 4 Final compliant. Dual element air cleaner.
<b>HYDRAULICS</b>	Variable flow load sensing system with on demand and servo operated multi function open center control. Independent servo gear pump. Two main axial piston pumps yield combined flow of 68.6 GPM. Servo pump flow: 5.3 GPM.
<b>OPERATOR'S AREA</b>	Air conditioned cab, noise and vibration isolated by six hydraulically damped resilient mountings. Opening door window. Fan forced fresh air ventilation with defogger and washer/wiper. Fully adjustable suspension seat with seatbelt, headrest, armrests, and backrest recline. Two boom and one mainframe work light
<b>CONTROLS</b>	Excavator controls are ISO pattern, servo operated, with in cab 7" digital display and change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance and a console mounted switch.
<b>UPPER</b>	Monoboomb with choice of dipper arms to suit dig depth requirements. No reinforcing required for hammer operations. Boom: 15' 5" (4.7m). Dippers: 8' 2" (2.5m), 9' 10" (3.0m).
<b>UNDERCARRIAGE</b>	The undercarriage gives excellent stability, is a fully welded X-frame type with undercarriage center cover, engine undercover and travel drive motor, cover and shields. Twin top and seven bottom rollers are heat-treated, sealed and lubricated. Track idler is sealed and lubricated and incorporates spring cushion recoil.
<b>TRACK DRIVE</b>	Full hydrostatic, 2 speed, driven by two axial piston motors. Motors are guarded in undercarriage frame for protection from debris. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 4.1 MPH, low speed is 2.4 MPH. Parking brake is disc type, spring applied, hydraulic release.
<b>ELECTRICAL</b>	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 55 amp output alternator with 12 volt in-cab supply.
<b>LIVELINK</b>	3 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
<b>OPERATING WEIGHT</b>	Equipped with standard boom, dipper, 24" track shoes and excavator bucket: apprx. 35,280 lbs.
<b>WARRANTY</b>	3-year / 3,000 hour full coverage warranty (please see the machine warranty certificate for details)

### SECTIONS ARE ORGANIZED AS FOLLOWS:


**Section 1** - PACKAGE BUILDS

**Section 2** - CUSTOM BUILD - NEW FACTORY BUILT ORDERS

**Section 3** - OPTIONS - NEW FACTORY BUILT ORDERS

**Section 4** - ATTACHMENTS - NEW FACTORY BUILT ORDERS

**DEALER FIT - EXCAVATORS** (LISTED SEPARATELY FOR ALL EXCAVATORS)

	<b>JZ141D HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	-----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 1 - YELLOW SERIES

Select one of the following machine PACKAGE BUILD codes and ATTACHMENT(S) if required from the section at the bottom of this sheet. Package build configurations cannot normally be changed. If a Package Build does not meet your requirements please order a machine using the Custom Build, Attachments & Options Sections following.

### SALES

CODE	ITEM	JZ141D
9145	JZ141 LC T4F Monoboom With Dozer	✓
900A483	Long Undercarriage 78" (1990mm) Gauge, Overall Length: 141" (3585mm)	✓
900B614	24" (600mm), 44 Links, Triple Grouser - Dozer Width 103" (2610mm)	✓
900C393	Monoboom with 9' 10" (3.0 m) Dipper. No HBCV	✓
900D396	Tipping Link with Lifting Shackle	✓
900EC07	North American Manual Pack	✓
900KM24	Hammer/Auxilliary Prop Mono 3.0m Arm	✓
900M036	Quick Hitch Lite Installation Kit	✓
900R001	AM/FM Radio	✓

**SUGGESTED LIST PRICE**

**\$152,951**

## ATTACHMENTS FOR YELLOW SERIES:

### SALES

CODE	U.S. LIST
<b>EXCAVATOR BUCKETS</b>	
YWSEA01 ADD 328/00500. 36" BUCKET	\$3,920
YWSEA02 ADD 980/A8250. HYDRAULIC COUPLER	\$5,811
YWSEA03 ADD 980/B0201. HM090T	\$18,348
YWSEA04 ADD 328/00498. 24" BUCKET	\$3,480



	<b>JZ141D HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	-----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS:

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each E (Essential) category below. Select Options and/or Attachments from Section 3 or 4.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	ITEM	U.S. LIST
<b>BASE UNIT (E)</b>		
9145	JZ141 LC T4F MONOBOOM WITH DOZER	\$145,237
<b>UNDERCARRIAGE for 9290 BASE UNIT (E)</b>		
900A483	LONG UNDERCARRIAGE, 1990MM (78IN) GAUGE, 3585MM (141IN) LONG	\$0
<b>TRACK PADS FOR 9290 BASE UNIT (E)</b>		
900B614	600MM (24IN), 44 LINKS, TRIPLE GROUSER - DOZER WIDTH 2610MM (103IN)	\$2,970
900B615	700MM (28IN), 44 LINKS, TRIPLE GROUSER - DOZER WIDTH 2710MM (107IN)	\$3,670
<b>MONO BOOM AND DIPPERS (E) Includes brackets for all attachment pipework</b>		
900C392	MONOBOOM, 0 HBCV, 2.5M DIPPER	\$1,053
900C393	MONOBOOM, 0 HBCV, 3.0M DIPPER	\$1,053
<b>TIPPING LINK (E)</b>		
900D396	Tipping Link with Lifting Shackle	\$477
<b>MANUAL PACK (E)</b>		
900EC07	USA HOMOLOGATION PACK	\$0

**JZ141D HYDRAULIC EXCAVATOR**U.S. DOLLAR  
PRICE PAGESF.O.B.  
SAVANNAH, GA

EFFECTIVE: April 1, 2018

**SECTION 3 - OPTIONS - NEW FACTORY BUILT ORDERS:**

SALES CODE	ITEM	U.S. LIST
<b>HYDRAULIC ATTACHMENT PIPEWORK - NEW FACTORY BUILT ORDERS ONLY</b>		
900KM23	HAMMER/AUX PROP. CONTROLS - 2.5M DIPPER	\$1,523
900KM24	HAMMER/AUX PROP. CONTROLS - 3.0M DIPPER	\$1,523
<b>Notes:</b>		
<ul style="list-style-type: none"><li>• High flow circuit pipework is dual function. The merged circuit adds in up to 70% of the flow from the second main pump. When operator selects hammer function hydraulic flow is delivered in one direction to run hammer. Circuit is operated by foot pedal. When auxiliary function is selected the same pump flow is delivered bi-directionally to run tool. Circuit can be operated by the foot pedal, hand control buttons or slider depending on code available.</li><li>• For additional factory installed hydraulic pipework options call JCB Product Marketing.</li><li>• Shut-off ball valve for hammer and auxiliary pipework available through JCB Parts Dept.</li></ul>		
<b>OPTIONS NEW FACTORY BUILT ORDERS ONLY</b>		
900M106	HYDRAULIC QUICK HITCH	\$5,811
900M036	HYDRAULIC QUICK HITCH LITE INSTALLATION	\$1,523
900P210	Scavenger Type Precleaner System	\$269
900R001	AM/FM Radio	\$169
900R011	Deluxe Seat - Air Suspension and Heated Base	\$726
900R035	Rainguard - Cab Mounted	\$484
900R130	Lower Level Windscreen Wiper	\$256
900S010	Vandal Cover Kit	\$2,282
900S020	FOPS Level 2 Guard - Front Windshield and Roof	\$5,618
900S025	Mesh Screen Guard for Front Windshield	\$1,477
900S034	LED Worklights	\$814
900S130	Additional Worklights	\$470
900S140	Amber Beacon - Cab Roof	\$182
900S253	Rear View Camera	\$698
900V001	HP32 Hydraulic Oil - for Cold Climate Operation	\$0
900V002	HP68 Hydraulic Oil - for Hot Climate Operation	\$0
900X040	Refueling Pump	\$590
900X381	Shut-off Valves For Auxiliary/Hammer Circuit (For 8' 2" (2.5m) Dipper)	\$723
900X382	Shut-off Valves For Auxiliary/Hammer Circuit (For 9' 10" (3.0mm) Dipper)	\$723
900X531	Twin Track Guides	\$1,404

**SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS:**

SALES CODE	ITEM	U.S. LIST
<b>EXCAVATOR BUCKETS</b>		
YWSEA01	ADD 328/00500. 36" BUCKET	\$3,920
YWSEA02	ADD 980/A8250. HYDRAULIC COUPLER	\$5,811
YWSEA03	ADD 980/B0201. HM090T	\$18,348
YWSEA04	ADD 328/00498. 24" BUCKET	\$3,480



2018


**JCB HYDRAULIC EXCAVATOR**  
**JS 145 and**  
**JS 145 Dozer**



**JCB, Inc. North American**  
**MACHINE PRICE LIST**  
**in U.S. Dollars**

**EFFECTIVE: April 1, 2018**

CHANGES TO SPECIFICATIONS AND/OR PRICES MAY OCCUR.  
PLEASE REFER TO THE PRODUCT MANAGER FOR UPDATES

	<b>JS145 and JS145 with BLADE</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	-----------------------------------	----------------------------	------------------------	--------------------------

## STANDARD EQUIPMENT

<b>ENGINE</b>	JCB Ecomax 444, 109 HP at 2,050 RPM. Four-cylinder water cooled common rail direct injection diesel engine. Low emission engine, EPA Tier 4 Final compliant. Dual element air cleaner. Selective Catalytic Reduction (SCR) System.
<b>HYDRAULICS</b>	Variable flow load sensing system with on demand and servo operated multi function open center control. Independent servo gear pump. Two main axial piston pumps yield combined flow of 70.7 GPM. Servo pump flow: 5.5 GPM.
<b>OPERATOR'S AREA</b>	Air conditioned cab, noise and vibration isolated by six hydraulically damped resilient mountings. Opening door window. Fan forced fresh air ventilation with defogger and washer/wiper. Fully adjustable suspension seat with seatbelt, headrest, armrests, and backrest recline. Two boom and one mainframe work light
<b>CONTROLS</b>	Excavator controls are ISO pattern, servo operated, with in cab 3.5" digital display and change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance and a console mounted switch.
<b>UPPER</b>	Monoboam with choice of dipper arms to suit dig depth requirements. No reinforcing required for hammer operations. Boom: 15' 5" (4.7m). Dippers: 8' 2" (2.5m), 9' 10" (3.0m).
<b>UNDERCARRIAGE</b>	The undercarriage gives excellent stability, is a fully welded X-frame type with undercarriage center cover, engine undercover and travel drive motor, cover and shields. Twin top and seven bottom rollers are heat-treated, sealed and lubricated. Track idler is sealed and lubricated and incorporates spring cushion recoil.
<b>TRACK DRIVE</b>	Full hydrostatic, 2 speed, driven by two axial piston motors. Motors are guarded in undercarriage frame for protection from debris. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 3.5 MPH, low speed is 2.1 MPH. Parking brake is disc type, spring applied, hydraulic release.
<b>ELECTRICAL</b>	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 55 amp output alternator with 12 volt in-cab supply.
<b>LIVELINK</b>	3 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
<b>OPERATING WEIGHT</b>	Equipped with standard boom, dipper, 24" track shoes and excavator bucket: apprx. 32,250 lbs. Equipped with dozer blade, standard boom, dipper, 24" track shoes and excavator bucket: apprx. 34,000 lb
<b>WARRANTY</b>	3-year / 3,000 hour full coverage warranty (please see the machine warranty certificate for details)

### SECTIONS ARE ORGANIZED AS FOLLOWS:


**Section 1** - PACKAGE BUILDS

**Section 2** - CUSTOM BUILD - NEW FACTORY BUILT ORDERS

**Section 3** - OPTIONS - NEW FACTORY BUILT ORDERS

**Section 4** - ATTACHMENTS - NEW FACTORY BUILT ORDERS

**DEALER FIT - EXCAVATORS** (LISTED SEPARATELY FOR ALL EXCAVATORS)

	<b>JS145 and JS145 with BLADE</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	-----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 1 - PACKAGE BUILDS

Select one of the following machine PACKAGE BUILD codes and ATTACHMENT(S) if required from the section at the bottom of this sheet. Package build configurations cannot normally be changed. If a Package Build does not meet your requirements please order a machine using the Custom Build, Attachments & Options Sections following.

SALES		PACKAGE BUILD CODE:	<b>9271A</b>
CODE	ITEM		JS145 9-10 Monoboomb
9271	JS145 Primary Build Tier 4 Final		✓
900A114	Long Undercarriage, 78" (1990mm) Gauge, Overall Length: 142" (3605mm)		✓
900B521	24" (600mm), Triple Grouser - 44 Link Tracks		✓
900C264	Monoboomb with 9' 10" (3.0 m) Dipper. No HBCV		✓
900D396	Tipping Link with Lifting Shackle		✓
900E2B4	North American Manual Pack		✓
900KF09	Hammer/Auxilliary Prop Mono 3.0m Arm		✓
900M113	Quick Hitch Lite Installation Kit		✓
900R001	AM/FM Radio		✓

**SUGGESTED LIST PRICE**

**\$141,337**


SALES		PACKAGE BUILD CODE:	<b>9272A</b>
CODE	ITEM		JS145 With Blade
9272	JS145 with Dozer Primary Build Tier 4 Final		✓
900A115	Long Undercarriage, 78" (1990mm) Gauge, Overall Length: 142" (3605mm)		✓
900B526	24" (600mm), Triple Grouser - 44 Link Tracks, 103" Dozer Width		✓
900C264	Monoboomb with 9' 10" (3.0 m) Dipper. No HBCV		✓
900D396	Tipping Link with Lifting Shackle		✓
900E2B4	North American Manual Pack		✓
900KF09	Hammer/Auxilliary Prop Mono 3.0m Arm		✓
900M113	Quick Hitch Lite Installation Kit		✓
900R001	AM/FM Radio		✓

**SUGGESTED LIST PRICE**

**\$152,927**

## ATTACHMENTS FOR PACKAGE BUILDS:

SALES CODE	U.S. LIST
<b>EXCAVATOR BUCKETS</b>	
<b>HEAVY DUTY PLATE LIP</b>	
YWSEA01 ADD 328/00500. 36" BUCKET	\$3,920
YWSEA02 ADD 980/A8250. HYDRAULIC COUPLER	\$5,811
YWSEA03 ADD 980/B0201. HM090T	\$18,348
YWSEA04 ADD 328/00498. 24" BUCKET	\$3,480


	<b>JS145 and JS145 with BLADE</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	-----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS:

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each E (Essential) category below. Select Options and/or Attachments from Section 3 or 4.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	ITEM	U.S. LIST
<b>BASE UNIT (E)</b>		
9271	JS145 Primary Build Tier 4 Final	\$133,623
9272	JS145 with Dozer Primary Build Tier 4 Final	\$145,213
<b>UNDERCARRIAGE for 9271 BASE UNIT (E)</b>		
900A114	Long Undercarriage, 78" (1990mm) Gauge, Overall Length: 142" (3605mm)	\$0
<b>UNDERCARRIAGE for 9272 BASE UNIT with BLADE (E)</b>		
900A115	Long Undercarriage, 78" (1990mm) Gauge, Overall Length: 142" (3605mm)	\$0
<b>TRACK PADS FOR 9271 BASE UNIT (E)</b>		
900B521	24" (600mm), Triple Grouser - 44 Link Tracks	\$2,970
900B522	28" (700mm), Triple Grouser - 44 Link Tracks	\$3,670
<b>TRACK PADS FOR 9272 BASE UNIT with BLADE (E)</b>		
900B526	24" (600mm), Triple Grouser - 44 Link Tracks, 103" Dozer Width	\$2,970
900B527	28" (700mm), Triple Grouser - 44 Link Tracks, 107" Dozer Width	\$3,669
<b>MONO BOOM AND DIPPERS (E) Includes brackets for all attachment pipework</b>		
900C261	Monoboom with 8' 2" (2.5 m) Dipper. No HBCV	\$1,053
900C264	Monoboom with 9' 10" (3.0 m) Dipper. No HBCV	\$1,053
<b>TIPPING LINK (E)</b>		
900D396	Tipping Link with Lifting Shackle	\$477
<b>MANUAL PACK (E)</b>		
900E2B4	North American Manual Pack	\$0

	<b>JS145 and JS145 with BLADE</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	-----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 3 - OPTIONS - NEW FACTORY BUILT ORDERS:

SALES CODE	ITEM	U.S. LIST
HYDRAULIC ATTACHMENT PIPEWORK - NEW FACTORY BUILT ORDERS ONLY		
900KF08	Hammer/Auxilliary Prop Mono 2.5m Arm	\$1,523
900KF09	Hammer/Auxilliary Prop Mono 3.0m Arm	\$1,523
Notes:	<ul style="list-style-type: none"><li>• High flow circuit pipework is dual function. The merged circuit adds in up to 70% of the flow from the second main pump. When operator selects hammer function hydraulic flow is delivered in one direction to run hammer. Circuit is operated by foot pedal. When auxiliary function is selected the same pump flow is delivered bi-directionally to run tool. Circuit can be operated by the foot pedal, hand control</li><li>• Low flow circuit: separate pipework set delivers servo pump flow bi-directionally to run tool. Operated by hand control buttons or slider.</li><li>• For additional factory installed hydraulic pipework options call JCB Product Marketing.</li><li>• Shut-off ball valve for hammer and auxiliary pipework available through JCB Parts Dept.</li></ul>	
OPTIONS NEW FACTORY BUILT ORDERS ONLY		
900M108	Hydraulic Quick Hitch	\$5,811
900M113	Quick Hitch Lite Installation Kit	\$1,523
900P210	Scavenger Type Precleaner System	\$269
900R001	AM/FM Radio	\$169
900R011	Deluxe Seat - Air Suspension and Heated Base	\$726
900R035	Rainguard - Cab Mounted	\$484
900R130	Lower Level Windscreen Wiper	\$256
900S010	Vandal Cover Kit	\$2,282
900S020	FOPS Level 2 Guard - Front Windshield and Roof	\$5,618
900S025	Mesh Screen Guard for Front Windshield	\$1,477
900S034	LED Worklights	\$814
900S130	Additional Worklights	\$470
900S140	Amber Beacon - Cab Roof	\$182
900S253	Rear View Camera	\$698
900V001	HP32 Hydraulic Oil - for Cold Climate Operation	\$0
900V002	HP68 Hydraulic Oil - for Hot Climate Operation	\$0
900X040	Refueling Pump	\$590
900X381	Shut-off Valves For Auxiliary/Hammer Circuit (For 8' 2" (2.5m) Dipper)	\$723
900X382	Shut-off Valves For Auxiliary/Hammer Circuit (For 9' 10" (3.0mm) Dipper)	\$723
900X531	Twin Track Guides	\$1,404

## SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS:

SALES CODE	ITEM	U.S. LIST
<b>EXCAVATOR BUCKETS</b>		
YWSEA0	ADD 328/00500. 36" BUCKET	\$3,920
YWSEA0	ADD 980/A8250. HYDRAULIC COUPLER	\$5,811
YWSEA0	ADD 980/B0201. HM090T	\$18,348
YWSEA0	ADD 328/00498. 24" BUCKET	\$3,480



2018

**JCB HYDRAULIC EXCAVATOR**  
**JS160LC and**  
**JS160NLC**



**JCB, Inc. North American**  
**MACHINE PRICE LIST**  
**in U.S. Dollars**

**EFFECTIVE: April 1, 2018**

**CHANGES TO SPECIFICATIONS AND/OR PRICES MAY OCCUR.**  
**PLEASE REFER TO THE PRODUCT MANAGER FOR UPDATES**



	<b>JS160 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## STANDARD EQUIPMENT

<b>ENGINE</b>	JCB Ecomax 444, 125 net HP at 2200 RPM, Tier 4 Final. Water cooled 4 Cycle, 4 Cylinder, in-line, common rail, direct injection, variable geometry turbocharged, intercooled diesel. Low emission engine designed to comply with US EPA emission standard. Dual element air cleaner. Combined single face radiator and hydraulic oil cooler. Selective catalytic reduction (SCR) system
<b>HYDRAULICS</b>	Variable flow load sensing system with on demand and servo operated multi function open center control. Independent servo gear pump. Two main axial piston pumps yield combined flow of 86 GPM. Servo pump flow: 5.5 GPM.
<b>OPERATOR'S AREA</b>	Climate controlled, noise and vibration isolated by six hydraulically damped resilient mountings Full opening door window. Fan forced fresh air ventilation with defogger and washer/wiper. Fully adjustable, high back suspension seat with seatbelt, headrest, armrests, and backrest recline. Two boom and one mainframe work light.
<b>CONTROLS</b>	Excavator controls are ISO pattern, servo operated, with in cab 7" digital display and change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance and a console mounted switch. Rearview camera standard.
<b>UPPER</b>	Monoboam with choice of dipper arms to suit dig depth requirements. No reinforcing required for hammer operations. Boom: 16' 11" (5.15m). Dippers: 8' 10" (2.7m), 10' 0" (3.05m).
<b>UNDERCARRIAGE</b>	The long undercarriage gives excellent stability, is a fully welded X-frame type with undercarriage center cover, engine undercover and travel drive motor, cover and shields. Two top and seven bottom rollers are heat-treated, sealed and lubricated. Track idler is sealed and lubricated and incorporates spring cushion recoil.
<b>TRACK DRIVE</b>	Full hydrostatic, 2 speed, driven by two axial piston motors. Motors are guarded in undercarriage frame for protection from debris. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 3.4 MPH, low speed is 2.0 MPH. Parking brake is disc type, spring applied, hydraulic release.
<b>ELECTRICAL</b>	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 50 amp output alternator with 12 volt in-cab supply.
<b>LIVELINK</b>	3 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
<b>OPERATING WEIGHT</b>	Equipped with standard boom, dipper, 24" track shoes and excavator bucket: apprx. 38,500 lbs.
<b>WARRANTY</b>	3-year / 3,000 hour full coverage warranty (please see the machine warranty certificate for details)

### SECTIONS ARE ORGANIZED AS FOLLOWS:


**Section 1** - PACKAGE BUILDS

**Section 2** - CUSTOM BUILD - NEW FACTORY BUILT ORDERS

**Section 3** - OPTIONS - NEW FACTORY BUILT ORDERS

**Section 4** - ATTACHMENTS - NEW FACTORY BUILT ORDERS

**DEALER FIT - EXCAVATORS** (LISTED SEPARATELY FOR ALL EXCAVATORS)

	<b>JS160 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 1 - YELLOW SERIES

Select one of the following machine PACKAGE BUILD codes and ATTACHMENT(S) if required from the section at the bottom of this sheet. Package Build configurations cannot normally be changed. If a Package Build does not meet your requirements please order a machine using the Custom Build, Attachments & Options Sections following.

### SALES

CODE	ITEM	JS160NLC
9531	JS160 NLC Primary Build Tier 4 Final	✓
900A427	Narrow Long Undercarriage, 78" (1990mm) Gauge, 155" (3940mm) long	✓
900B574	24" (600mm), Triple Grouser - 43 Link Chain	✓
900C121	Monoboom with 10' 0" (3.05 m) Dipper	✓
900D403	Tipping Link with Lifting Shackle	✓
900E2E6	North American Manual Pack	✓
900KD09	Hammer/Aux Prop. Controls - 3.05M Dipper	✓
900M038	Quick Hitch Lite Installation Kit	✓
900R001	AM/FM Radio	✓


**SUGGESTED LIST PRICE**

**\$158,699**

## ATTACHMENTS FOR YELLOW SERIES:

### SALES

CODE	U.S. LIST
<b>EXCAVATOR BUCKETS</b>	
YWSEA05 ADD 328/00513. 42" BUCKET	\$5,030
YWSEA06 ADD 980/A8251. HYDRAULIC COUPLER	\$6,637
YWSEA07 ADD 980/B0204. HM120T	\$21,928


	<b>JS160 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS:

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each E (Essential) category below. Select Options and/or Attachments from Section 3 or 4.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	ITEM	U.S. LIST
<b>BASE UNIT (E)</b>		
9530	JS160 LC Primary Build Tier 4 Final	\$148,720
9531	JS160 NLC Primary Build Tier 4 Final	\$148,720
<b>UNDERCARRIAGE for 9530 BASE UNIT (E)</b>		
900A425	Long Undercarriage, 87" (2200mm) Gauge, 155" (3940mm) long	\$0
900A426	Extra Heavy Duty Undercarriage, 87" (2200mm) Gauge, 155" (3940mm) long	\$0
<b>UNDERCARRIAGE for 9531 BASE UNIT (E)</b>		
900A427	Extra Heavy Duty Undercarriage, 87" (2200mm) Gauge, 155" (3940mm) long	\$0
900A432	Narrow Long Undercarriage, 78" (1990mm) Gauge, 155" (3940mm) long for XHD 31.5" Shoe Only	\$0
<b>TRACK PADS</b>		
900B574	24" (600mm), Triple Grouser - 43 Link Chain	\$2,954
900B575	28" (700mm), Triple Grouser- 43 Link Chain	\$3,648
<b>MONO BOOM AND DIPPERS (E) Includes brackets for all attachment pipework</b>		
900C120	Monoboom with 8' 10" (2.7 m) Dipper	\$1,047
900C121	Monoboom with 10' 0" (3.05 m) Dipper	\$1,047
<b>TIPPING LINK (E)</b>		
900D403	Tipping Link with Lifting Shackle	\$467
<b>MANUAL PACK (E)</b>		
900E2E6	North American Manual Pack	\$0

	<b>JS160 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

### SECTION 3 - OPTIONS - NEW FACTORY BUILT ORDERS:

SALES CODE	ITEM	U.S. LIST
HYDRAULIC ATTACHMENT PIPEWORK - NEW FACTORY BUILT ORDERS ONLY		
900KD08	Hammer/Aux Prop. Controls - 2.7M Dipper	\$1,523
900KD09	Hammer/Aux Prop. Controls - 3.05M Dipper	\$1,523
Notes:	<ul style="list-style-type: none"><li>• High flow circuit pipework is dual function. The merged circuit adds in up to 70% of the flow from the second main pump. When operator selects hammer function hydraulic flow is delivered in one direction to run hammer. Circuit is operated by foot pedal. When auxiliary function is selected the same pump flow is delivered bi-directionally to run tool. Circuit can be operated by the foot pedal, hand control buttons or slider depending on code available.</li><li>• Low flow circuit: separate pipework set delivers servo pump flow bi-directionally to run tool. Operated by hand control buttons or slider.</li><li>• For additional factory installed hydraulic pipework options call JCB Product Marketing.</li><li>• Shut-off ball valve for hammer and auxiliary pipework available through JCB Parts Dept.</li></ul>	
OPTIONS NEW FACTORY BUILT ORDERS ONLY		
900M101	Hydraulic Quick Hitch	\$6,925
900M038	Quick Hitch Lite Installation Kit	\$1,523
900R001	AM/FM Radio	\$169
900R011	Deluxe Seat - Air Suspension and Heated Base	\$726
900R035	Rainguard - Cab Mounted	\$484
900R130	Lower Level Windscreen Wiper	\$256
900S010	Vandal Cover Kit	\$2,282
900S020	FOPS Level 2 Guard - Front Windshield and Roof	\$5,618
900S025	Mesh Screen Guard for Front Windshield	\$1,477
900S034	LED Worklights	\$814
900S130	Additional Worklights	\$470
900S140	Amber Beacon - Cab Roof	\$182
900S210	Top Around Handrail	\$1,411
900V005	HP32 Hydraulic Oil - for Cold Climate Operation	\$0
900V006	HP68 Hydraulic Oil - for Hot Climate Operation	\$0
900X076	Refueling Pump	\$590
900X386	Shut-off Valves For Auxiliary/Hammer Circuit (For 8' 10 " (2.7m) Dipper)	\$723
900X387	Shut-off Valves For Auxiliary/Hammer Circuit (For 10' 0" (3.05m) Dipper)	\$723
900X532	Twin Track Guides For Heavy Duty Machine	\$702
900X900	Counterweight with Red and White Chevrons	\$1,208

### SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS:

SALES CODE	ITEM	U.S. LIST
<b>EXCAVATOR BUCKETS</b>		
YWSEA05	ADD 328/00513. 42" BUCKET	\$5,030
YWSEA06	ADD 980/A8251. HYDRAULIC COUPLER	\$6,637
YWSEA07	ADD 980/B0204. HM120T	\$21,928



2018

**JCB HYDRAULIC EXCAVATOR**  
**JS 190LC and**  
**JS 190NLC**



**JCB, Inc. North American**  
**MACHINE PRICE LIST**  
**in U.S. Dollars**

**EFFECTIVE: April 1, 2018**

**CHANGES TO SPECIFICATIONS AND/OR PRICES MAY OCCUR.**  
**PLEASE REFER TO THE PRODUCT MANAGER FOR UPDATES**

	<b>JS190 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## STANDARD EQUIPMENT

<b>ENGINE</b>	JCB Ecomax 444, 125 net HP at 2200 RPM, Tier 4 Final. Water cooled 4 Cycle, 4 Cylinder, in-line, common rail, direct injection, variable geometry turbocharged, intercooled diesel. Low emission engine designed to comply with US EPA emission standard. Dual element air cleaner. Combined single face radiator and hydraulic oil cooler.
<b>HYDRAULICS</b>	Variable flow load sensing system with on demand and servo operated multi function open center control. Two variable displacement axial piston pumps yield combined flow of 86 GPM. Independent servo gear pump delivers 5.5 GPM.
<b>OPERATOR'S AREA</b>	Climate controlled, noise and vibration isolated by six hydraulically damped resilient mountings and lower windows. Full opening door window. Fan forced fresh air ventilation with defogger and Fully adjustable, high back suspension seat with seatbelt, headrest, armrests, and backrest recline Cigarette lighter and ashtray.
<b>CONTROLS</b>	Excavator controls are ISO pattern, servo operated, with in cab 7" digital display and change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance and a console mounted switch. Rearview camera standard.
<b>UPPER</b>	Monoboom with choice of dipper arms to suit dig depth requirements. No reinforcing required for hammer operations. Boom: 16' 11" (5.15m). Dippers: 8' 10" (2.7m), 10' 0" (3.05m).
<b>UNDERCARRIAGE</b>	The long undercarriage gives excellent stability, is a fully welded X-frame type with undercarriage center cover, engine undercover and travel drive motor, cover and shields. Two top and seven bottom rollers are heat-treated, sealed and lubricated. Track idler is sealed and lubricated and incorporates spring cushion recoil. Two track guides per side.
<b>TRACK DRIVE</b>	Full hydrostatic, 2 speed, driven by two axial piston motors. Motors are guarded in undercarriage frame for protection from debris. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 2.6 MPH, low speed is 1.5 MPH. Parking brake is disc type, spring applied, hydraulic release.
<b>ELECTRICAL</b>	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 40 amp output alternator with 12 volt in-cab supply.
<b>LIVELINK</b>	3 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
<b>OPERATING WEIGHT</b>	Equipped w/standard boom, dipper, 24" track shoes and excavator bucket: aprx. 43,750 lbs.
<b>WARRANTY</b>	3-year / 3,000 hour full coverage warranty (please see the machine warranty certificate for details)

### SECTIONS ARE ORGANIZED AS FOLLOWS:


**Section 1** - PACKAGE BUILDS

**Section 2** - CUSTOM BUILD - NEW FACTORY BUILT ORDERS

**Section 3** - OPTIONS - NEW FACTORY BUILT ORDERS

**Section 4** - ATTACHMENTS - NEW FACTORY BUILT ORDERS

**DEALER FIT - EXCAVATORS** (LISTED SEPARATELY FOR ALL EXCAVATORS)

	<b>JS190 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 1 - PACKAGE BUILDS

Select one of the following machine PACKAGE BUILD codes and ATTACHMENT(S) if required from the section at the bottom of this sheet. Package Build configurations cannot normally be changed. If a Package Build does not meet your requirements please order a machine using the Custom Build, Attachments & Options Sections following.


SALES		PACKAGE BUILD CODE:	<b>9542A</b>
CODE	ITEM		JS190NLC 10' DIPPER
9542	JS190 NLC Primary Build Tier 4 Final		✓
900A430	Long Undercarriage, 87" (2200mm), 164" (4170mm) long		✓
900B584	24" (600mm), Triple Grouser - 46 Link Chain		✓
900C121	Monoboom with 10' 0" (3.05 m) Dipper		✓
900D403	Tipping Link with Lifting Shackle		✓
900E2E6	North American Manual Pack		✓
900KD09	Hammer/Aux Prop. Controls - 3.05M Dipper		✓
900M038	Quick Hitch Lite Installation Kit		✓
900R001	AM/FM Radio		✓

**SUGGESTED LIST PRICE**

**\$177,067**

## ATTACHMENTS FOR PACKAGE BUILD:

SALES		U.S.
CODE		LIST
<b>EXCAVATOR BUCKETS</b>		
YWSEA05	ADD 328/00513. 42" BUCKET	\$5,030
YWSEA06	ADD 980/A8251. HYDRAULIC COUPLER	\$6,637
YWSEA07	ADD 980/B0204. HM120T	\$21,928

	<b>JS190 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------


## SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS:

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each E (Essential) category below. Select Options and/or Attachments from Section 3 or 4.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	ITEM	U.S. LIST
<b>BASE UNIT (E)</b>		
9541	JS190 LC Primary Build Tier 4 Final	\$166,816
9542	JS190 NLC Primary Build Tier 4 Final	\$166,816
<b>UNDERCARRIAGE for 9541 BASE UNIT (E)</b>		
900A431	Long Undercarriage, 87" (2200mm), 164" (4170mm) long	\$0
<b>UNDERCARRIAGE for 9542 BASE UNIT (E)</b>		
900A430	Long Undercarriage, 87" (2200mm), 164" (4170mm) long	\$0
<b>TRACK PADS</b>		
900B584	24" (600mm), Triple Grouser - 46 Link Chain	\$2,954
900B585	28" (700mm), Triple Grouser - 46 Link Chain	\$4,049
<b>MONO BOOM AND DIPPERS (E) Includes brackets for all attachment pipework</b>		
900C120	Monoboom with 8' 10" (2.7 m) Dipper	\$1,047
900C121	Monoboom with 10' 0" (3.05 m) Dipper	\$1,047
<b>TIPPING LINK (E)</b>		
900D403	Tipping Link with Lifting Shackle	\$467
<b>MANUAL PACK (E)</b>		
900E2E6	North American Manual Pack	\$0



	<b>JS190 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

### SECTION 3 - OPTIONS - NEW FACTORY BUILT ORDERS:

SALES CODE	ITEM	U.S. LIST
HYDRAULIC ATTACHMENT PIPEWORK - NEW FACTORY BUILT ORDERS ONLY		
900KD08	Hammer/Aux Prop. Controls - 2.7M Dipper	\$1,523
900KD09	Hammer/Aux Prop. Controls - 3.05M Dipper	\$1,523
Notes:	<ul style="list-style-type: none"><li>• High flow circuit pipework is dual function. The merged circuit adds in up to 70% of the flow from the second main pump. When operator selects hammer function hydraulic flow is delivered in one direction to run hammer. Circuit is operated by foot pedal. When auxiliary function is selected the same pump flow is delivered bi-directionally to run tool. Circuit can be operated by the foot pedal, hand control buttons or slider depending on code available.</li><li>• Low flow circuit: separate pipework set delivers servo pump flow bi-directionally to run tool. Operated by hand control buttons or slider.</li><li>• For additional factory installed hydraulic pipework options call JCB Product Marketing.</li><li>• Shut-off ball valve for hammer and auxiliary pipework available through JCB Parts Dept.</li></ul>	
OPTIONS NEW FACTORY BUILT ORDERS ONLY		
900M038	Quick Hitch Lite Installation Kit	\$1,523
900M101	Hydraulic Quick Hitch	\$6,925
900R001	AM/FM Radio	\$169
900R011	Deluxe Seat - Air Suspension and Heated Base	\$726
900R130	Lower Level Windscreen Wiper	\$256
900S001	Fire Extinguisher	\$336
900S010	Vandal Cover Kit	\$2,282
900S020	FOPS Level 2 Guard - Front Windshield and Roof	\$5,618
900S025	Mesh Screen Guard for Front Windshield	\$1,477
900S130	Additional Worklights	\$470
900S132	Additional Worklights (2 cab lights, 1 counter weight light - FOPS Compatible Only)	\$470
900S140	Amber Beacon - Cab Roof	\$182
900V005	HP32 Hydraulic Oil - for Cold Climate Operation	\$0
900V006	HP68 Hydraulic Oil - for Hot Climate Operation	\$0
900X076	Refueling Pump	\$590
900X387	Shut-off Valves For Auxiliary/Hammer Circuit (For 10' 0" (3.05m) Dipper)	\$723

### SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS:

SALES CODE	ITEM	U.S. LIST
<b>EXCAVATOR BUCKETS</b>		
YWSEA05	ADD 328/00513. 42" BUCKET	\$5,030
YWSEA06	ADD 980/A8251. HYDRAULIC COUPLER	\$6,637
YWSEA07	ADD 980/B0204. HM120T	\$21,928



2018


# **JCB HYDRAULIC EXCAVATOR JS220**



## **JCB, Inc. North American MACHINE PRICE LIST in U.S. Dollars**

**EFFECTIVE: April 1, 2018**

**CHANGES TO SPECIFICATIONS AND/OR PRICES MAY OCCUR.  
PLEASE REFER TO THE PRODUCT MANAGER FOR UPDATES**

	<b>JS220 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## STANDARD EQUIPMENT

<b>ENGINE</b>	JCB Ecomax 448, 173 Net HP at 2000 RPM, Tier 4 Final. 4-cycle, 4-cylinder in line, common rail, direct injection, variable geometry turbocharged, intercooled diesel. Low emission engine designed to comply with US EPA emission standard. Dual element air cleaner. Combined single face radiator and hydraulic oil cooler. Selective Catalytic Reduction (SCR) System.
<b>HYDRAULICS</b>	Variable flow load sensing system with on demand and servo operated multi function open center control. Independent servo gear pump. Two main axial piston pumps yield combined flow of 120 GPM. Servo pump flow: 4.8 GPM.
<b>OPERATOR'S AREA</b>	Climate controlled, noise and vibration isolated by six hydraulically damped resilient mountings. Full opening door window. Fan forced fresh air ventilation with defogger and washer/wiper. Fully adjustable, high back suspension seat with seatbelt, headrest, armrests and backrest recline. Two boom and one mainframe work light.
<b>CONTROLS</b>	Excavator controls are ISO pattern, servo operated, with in cab 7" digital display and change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance and a console mounted switch. Rearview camera standard.
<b>UPPER</b>	Monoboomb with choice of dipper arms to suit dig depth requirements. No dipper reinforcing required for hammer operations. Boom: 18' 8" (5.70m). Dipper Arms: 7' 10" (2.40m) or 9' 10" (3.0m). Electric refueling pump is situated in tool box.
<b>UNDERCARRIAGE</b>	The long undercarriage gives excellent stability, is a fully welded X-frame type with flush fitted, heavy duty swing turret cover and heavy duty undercover. Two top and eight bottom rollers are sealed and lubricated. Track idler is sealed and lubricated and incorporates spring cushion recoil.
<b>TRACK DRIVE</b>	Full hydrostatic, 3 speed, driven by two axial piston motors. Flush fitted heavy duty track motor guards. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 3.4 MPH, low speed is 2.1 MPH. Parking brake is disc type, spring applied, hydraulic release.
<b>ELECTRICAL</b>	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 40 amp output alternator with 12 volt in-cab supply.
<b>LIVELINK</b>	3 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
<b>OPERATING WEIGHT</b>	Equipped w/standard boom, dipper, 32" track shoes and excavator bucket: aprx. 51,000 lbs.
<b>WARRANTY</b>	3-year / 3,000 hour full coverage warranty (please see the machine warranty certificate for details)


### SECTIONS ARE ORGANIZED AS FOLLOWS:

**Section 1** - PACKAGE BUILDS

**Section 2** - CUSTOM BUILD - NEW FACTORY BUILT ORDERS

**Section 3** - OPTIONS - NEW FACTORY BUILT ORDERS

**Section 4** - ATTACHMENTS - NEW FACTORY BUILT ORDERS

	<b>JS220 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 1 - YELLOW SERIES

Select one of the following machine PACKAGE BUILD codes and ATTACHMENT(S) if required from the section at the bottom of this sheet. Package Build configurations cannot normally be changed. If a Package Build does not meet your requirements please order a machine using the Custom Build, Attachments & Options Sections following.

### SALES

CODE	ITEM	JS220
9557	JS220 LC Primary Build Tier 4 Final	✓
900A025	Long Undercarriage, 94" (2390mm), 176" (4460mm) long	✓
900B559	32" (800mm), Triple Grouser - 49 Link Chain	✓
900C402	Monoboom with 9' 10" (3.0 m) Dipper	✓
900D371	Tipping Link with Lifting Shackle	✓
900E2B2	North American Manual Pack	✓
900KC09	High flow pipework for Hammer/Auxiliary circuits for 9' 10" (3.0 m) dipper	✓
900M040	Hydraulic Quick Hitch Lite Installation Monoboom	✓
900R001	AM/FM Radio	✓


**SUGGESTED LIST PRICE**

**\$199,488**

## ATTACHMENTS FOR YELLOW SERIES:

### SALES

CODE		U.S. LIST
#REF!		
YWSEA08	ADD 328/00529. 48" BUCKET	\$6,288
YWSEA09	ADD 980/A8252. HYDRAULIC COUPLER	\$7,454
YWSEA10	ADD 980/B0210. HM180T	\$27,375


	<b>JS220 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS:

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each E (Essential) category below. Select Options and/or Attachments from Section 3 or 4.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	ITEM	U.S. LIST
<b>BASE MACHINE (E)</b>		
9557	JS220 LC Primary Build Tier 4 Final	\$185,904
<b>UNDERCARRIAGE (E)</b>		
900A025	Long Undercarriage, 94" (2390mm), 176" (4460mm) long	\$0
<b>TRACK PADS (E)</b>		
900B504	28" (700mm), Triple Grouser - 49 Link Chain	\$0
900B559	32" (800mm), Triple Grouser - 49 Link Chain	\$8,087
900B572	24" (600mm), Triple Grouser - 49 Link Chain, GeoGrip Rubber Tracks	\$20,761
<b>MONO BOOM AND DIPPERS (E) Includes brackets for all attachment pipework</b>		
900C401	Monoboam with 7' 10" (2.4 m) Dipper	\$1,801
900C402	Monoboam with 9' 10" (3.0 m) Dipper	\$1,801
<b>TIPPING LINK (E)</b>		
900D371	Tipping Link with Lifting Shackle	\$483
<b>MANUAL PACK (E)</b>		
900E2B2	North American Manual Pack	\$0

	<b>JS220 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

### SECTION 3 - OPTIONS - NEW FACTORY BUILT ORDERS:

SALES CODE	ITEM	U.S. LIST
HYDRAULIC ATTACHMENT PIPEWORK - NEW FACTORY BUILT ORDERS ONLY		
900KC08	High flow pipework for Hammer/Auxiliary circuits for 7' 10" (2.4 m) dipper	\$1,523
900KC09	High flow pipework for Hammer/Auxiliary circuits for 9' 10" (3.0 m) dipper	\$1,523
Notes:	<div>• High flow circuit pipework is dual function. The merged circuit adds in up to 70% of the flow from the second main pump. When operator selects hammer function hydraulic flow is delivered in one direction to run hammer. When auxiliary function is selected the same pump flow is delivered bi-directionally to run tool. Circuit can be operated by the foot pedal, hand control buttons or slider.</div> <div>• Low flow circuit: separate pipework set delivers flow bi-directionally to run tool. Operated by hand control buttons or slider.</div> <div>• For additional factory installed hydraulic pipework options call JCB Product Marketing.</div> <div>• Shut-off ball valve for hammer and auxiliary pipework available through JCB Parts Dept.</div>	
MISCELLANEOUS EXTRAS		
900M032	Hydraulic Quick Hitch	\$5,775
900M040	Hydraulic Quick Hitch Lite Installation Monoboom	\$1,523
900R001	AM/FM Radio	\$169
900R011	Deluxe Seat - Air Suspension and Heated Base	\$726
900R130	Lower Level Windscreen Wiper	\$256
900S001	Fire Extinguisher	\$336
900S010	Vandal Cover Kit	\$2,282
900S020	FOPS Level 2 Guard - Front Windshield and Roof	\$5,618
900S025	Mesh Screen Guard for Front Windshield	\$1,477
900S130	Additional Worklights	\$470
900S132	Additional Worklights (2 cab lights, 1 counter weight light - FOPS Compatible Only)	\$470
900S140	Amber Beacon - Cab Roof	\$182
900S205	Top Around Handrail	\$1,895
900V001	HP32 Hydraulic Oil - for Cold Climate Operation	\$0
900V002	HP68 Hydraulic Oil - for Hot Climate Operation	\$0

### SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS:

SALES CODE	ITEM	U.S. LIST
<b>YELLOW SERIES ATTACHMENTS</b>		
YWSEA08	ADD 328/00529. 48" BUCKET	\$6,288
YWSEA09	ADD 980/A8252. HYDRAULIC COUPLER	\$7,454
YWSEA10	ADD 980/B0210. HM180T	\$27,375




2018

**JCB HYDRAULIC EXCAVATOR  
220X**

**JCB, Inc. North American  
MACHINE PRICE LIST  
in U.S. Dollars**

**EFFECTIVE: April 1, 2018**

**CHANGES TO SPECIFICATIONS AND/OR PRICES MAY OCCUR.  
PLEASE REFER TO THE PRODUCT MANAGER FOR UPDATES**

	<b>220X HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	---------------------------------	----------------------------	------------------------	--------------------------

## STANDARD EQUIPMENT

<b>ENGINE</b>	JCB Ecomax 448, 173 Net HP at 2000 RPM, Tier 4 Final. 4-cycle, 4-cylinder in line, common rail, direct injection, variable geometry turbocharged, intercooled diesel. Low emission engine designed to comply with US EPA emission standard. Dual element air cleaner. Combined single face radiator and hydraulic oil cooler. Selective Catalytic Reduction (SCR) System.
<b>HYDRAULICS</b>	Variable flow load sensing system with on demand and servo operated multi function open center control. Independent servo gear pump. Two main axial piston pumps yield combined flow of 120 GPM. Servo pump flow: 4.2 GPM.
<b>OPERATOR'S AREA</b>	JCB Command Plus Cab. Climate controlled, noise and vibration isolated by four hydraulically damped resilient mountings. Full opening front window. Fan forced fresh air ventilation with defogger and washer/wiper. Fully adjustable, high back air suspension seat with seatbelt, headrest, armrests and backrest recline. Two boom and two mainframe work light.
<b>CONTROLS</b>	Excavator controls are ISO pattern, servo operated, with in cab 7" digital display and change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance. Rearview camera standard.
<b>UPPER</b>	Monoboam with choice of dipper arms to suit dig depth requirements. No dipper reinforcing required for hammer operations. Boom: 18' 8" (5.70m). Dipper Arms: 7' 10" (2.40m) or 9' 10" (3.0m).
<b>UNDERCARRIAGE</b>	The long undercarriage gives excellent stability, is a fully welded X-frame type with flush fitted, heavy duty swing turret cover and heavy duty undercover. Two top and eight bottom rollers are sealed and lubricated. Track idler is sealed and lubricated and incorporates spring cushion recoil.
<b>TRACK DRIVE</b>	Full hydrostatic, 2 speed, driven by two axial piston motors. Flush fitted heavy duty track motor guards. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 3.5 MPH, low speed is 2.0 MPH. Parking brake is disc type, spring applied, hydraulic release.
<b>ELECTRICAL</b>	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 100 amp output alternator with 12 volt in-cab supply.
<b>LIVELINK</b>	3 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
<b>OPERATING WEIGHT</b>	Equipped w/standard boom, dipper, 32" track shoes and excavator bucket: aprx. 52,450 lbs.
<b>WARRANTY</b>	3-year / 3,000 hour full coverage warranty (please see the machine warranty certificate for details)

### SECTIONS ARE ORGANIZED AS FOLLOWS:


**Section 1** - PACKAGE BUILDS

**Section 2** - CUSTOM BUILD - NEW FACTORY BUILT ORDERS

**Section 3** - OPTIONS - NEW FACTORY BUILT ORDERS

**Section 4** - ATTACHMENTS - NEW FACTORY BUILT ORDERS



	<b>220X HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	---------------------------------	----------------------------	------------------------	--------------------------

## SECTION 1 - YELLOW SERIES

Select one of the following machine PACKAGE BUILD codes and ATTACHMENT(S) if required from the section at the bottom of this sheet. Package Build configurations cannot normally be changed. If a Package Build does not meet your requirements please order a machine using the Custom Build, Attachments & Options Sections following.

### SALES

CODE	ITEM	220X
9282	220X LC MONO T4F	✓
900AB01	LONG CARRIAGE 2390MM (94IN) GAUGE 4460MM (176IN) LONG	✓
900BA07	800MM (31IN) TRACK PLATES, TRIPLE GROUSER, 49LINKS,STEP EXTENSIONS	✓
900CC01	MONOBOOM,0 HBCV, 3.0M DIPPER	✓
900DC11	TIPPING LINK- 17 TONNE LUG TIPPING LINK ONLY	✓
900ED02	US LANGUAGE PACK	✓
900KR16	HAMMER/AUX PROP.CONTROLS - 3.0M DIPPER	✓
900MA02	HYDRAULIC QUICK HITCH INSTALLATION FOR 3.0M MONO DIPPER	✓
900RB01	RADIO - BLUETOOTH COMPATIBLE	✓


**SUGGESTED LIST PRICE**

**\$207,315**

## ATTACHMENTS FOR YELLOW SERIES:

### SALES

CODE		U.S. LIST
<b>YELLOW SERIES ATTACHMENTS</b>		
YWSEA08	ADD 328/00529. 48" BUCKET	\$6,288
YWSEA09	ADD 980/A8252. HYDRAULIC COUPLER	\$7,454
YWSEA10	ADD 980/B0210. HM180T	\$27,375


	<b>220X HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	---------------------------------	----------------------------	------------------------	--------------------------

## SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS:

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each E (Essential) category below. Select Options and/or Attachments from Section 3 or 4.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	ITEM	U.S. LIST
	<b>BASE MACHINE (E)</b>	
9282	220X LC MONO T4F	\$192,521
9286	220X LCD MONO T4F	\$204,600
	<b>UNDERCARRIAGE for 9282 BASE UNIT (E)</b>	
900AB01	LONG CARRIAGE 2390MM (94IN) GAUGE 4460MM (176IN) LONG	\$0
	<b>UNDERCARRIAGE for 9286 BASE UNIT (E)</b>	
900AB04	LONG CARRIAGE 2390MM (94IN) GAUGE 4460MM (176IN) LONG - DOZER INCLUDED	\$0
	<b>TRACK PADS for 9282 BASE UNIT (E)</b>	
900BA05	700MM (28IN) TRACK PLATES TRIPLE GROUSER, 49 LINKS	\$5,580
900BA07	800MM (31IN) TRACK PLATES, TRIPLE GROUSER, 49LINKS,STEP EXTENSIONS	\$8,375
	<b>TRACK PADS for 9286 BASE UNIT (E)</b>	
900BA17	700MM DOZER BLADE TRACKS	\$5,580
	<b>MONO BOOM AND DIPPERS (E) Includes brackets for all attachment pipework</b>	
900CC01	MONOBOOM,0 HBCV, 3.0M DIPPER	\$1,865
900CC03	MONOBOOM,0 HBCV, 3.0M DIPPER HD	\$3,072
	<b>TIPPING LINK (E)</b>	
900DC11	TIPPING LINK- 17 TONNE LUG TIPPING LINK ONLY	\$500
	<b>MANUAL PACK (E)</b>	
900ED02	US LANGUAGE PACK	\$0
900ED03	FRENCH/CANADIAN LANGUAGE PACK	\$0

	<b>220X HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	---------------------------------	----------------------------	------------------------	--------------------------

### SECTION 3 - OPTIONS - NEW FACTORY BUILT ORDERS:

SALES CODE	ITEM	U.S. LIST
<b>GREASING</b>		
900G002	AUTOGREASING FOR 3M MONO DIPPER	\$9,399
<b>MACHINE PROTECTION</b>		
900J002	HEAVY DUTY REVOLVING FRAME WITH BOLT ON SIDE PROTECTION	\$2,073
900J005	LOWER FRAME UNDERCOVERS - 10MM SINGLE PIECE PLATE WITH X SHAPE STIFFENER	\$625
900J006	XD UNDERCOVERS - 10MM THICK	\$1,458
<b>HYDRAULIC ATTACHMENT PIPEWORK - NEW FACTORY BUILT ORDERS ONLY</b>		
900KR14	HAMMER/AUX/MERGED PROP.CONTROLS - 3.0M DIPPER	\$2,943
900KR16	HAMMER/AUX PROP.CONTROLS - 3.0M DIPPER	\$1,577
900KR19	HAMMER/AUX & LOW FLOW PROP. CONTROLS - 3.0M DIPPER	\$5,115
900KR22	HAMMER/AUX/MERGED & LOW FLOW PROP. CONTROLS - 3.0M DIPPER	\$6,484
<b>QUICKHITCH OPTIONS</b>		
900MA02	HYDRAULIC QUICK HITCH INSTALLATION FOR 3.0M MONO DIPPER	\$1,577
900MA05	HYDRAULIC QUICK HITCH	\$7,454
<b>FILTERS AND COOLING OPTIONS</b>		
900PA03	FLYSCREEN PLEATED	\$678
900PA04	AIR COMPRESSOR KIT	\$3,566
900PA07	REVERSING FAN	\$3,397
<b>CAB OPTIONS</b>		
900RB01	RADIO - BLUETOOTH COMPATIBLE	\$174
900RB02	DELUXE SEAT - AIR SUSPENSION AND HEATED BASE	\$726
900RB03	SUPER DELUXE SEAT - AIR SUSPENSION, HEATED BASE, VENTILATION AND AIR LUMBAR	\$2,089
900RB07	RAIN GUARD, CAB MOUNTED	\$516
900RB09	FRONT BLIND	\$83
900RB10	REAR BLIND	\$110
900RB11	RIGHT HAND SIDE BLIND	\$110
900RB17	FRONT TWIN WIPER	\$273
<b>SAFETY OPTIONS</b>		
900SC01	FIRE EXTINGUISHER	\$358
900SC03	FOPS FRONT GUARD	\$2,394
900SC04	FOPS ROOF GUARD	\$3,591
900SC05	MESH FULL FRONT GUARD	\$1,125
900SC06	MESH LOWER FRONT GUARD	\$835
900SC09	LEFT AND RIGHT FOLDING HAND RAILS	\$1,190
900SC11	ALL AROUND HANDRAILS (BOXING RING RAILS)	\$2,018
900SC12	HALOGEN AMBER BEACON	\$195
900SC14	2 X REAR HALOGEN BEACONS	\$272
900SC18	TWIN CAMERA	\$1,088
900SC22	WHITE NOISE ALARM	\$258
900SC23	SERVICE BAY & ACCESS LIGHTING	\$338
900SC27	LEVEL 2 - LIGHTING PACK HALOGEN	\$938
900SC29	LEVEL 3 - LIGHTING PACK HALOGEN	\$1,250
900SC30	LEVEL 2 - LIGHTING PACK LED	\$1,824
900SC32	LEVEL 3 - LIGHTING PACK LED	\$2,500
<b>OPTION PACKS</b>		
900TA01	SAFETY PACK	\$3,539
900TA05	SERVICE PACK FOR 3.0M ARM	\$7,775
<b>HYDRAULIC OIL OPTIONS</b>		
900VA01	HP68 HYDRAULIC OIL- FOR HOT CLIMATE OPERATION	\$0
900VA02	JCB BIO OIL	\$4,866
900VA03	PANOLIN HYDRAULIC OIL	\$7,960
900VA04	HP32 HYDRAULIC OIL - FOR COLD CLIMATE OPERATION	\$0
<b>MISCELLANEOUS EXTRAS</b>		
900XA01	SPADE STORAGE	\$115
900XA02	COUNTERWEIGHT WITH RED AND WHITE CHEVRONS	\$1,288
900XA10	BOOM FLOAT MONO	\$3,902
900XA12	REFUELLING PUMP	\$628
900XA14	TOOL KIT	\$24

### SECTION 4 - YELLOW SERIES ATTACHMENTS

SALES CODE	ITEM	U.S. LIST
<b>YELLOW SERIES ATTACHMENTS</b>		
YWSEA08	ADD 328/00529. 48" BUCKET	\$6,288
YWSEA09	ADD 980/A8252. HYDRAULIC COUPLER	\$7,454
YWSEA10	ADD 980/B0210. HM180T	\$27,375



2018


**JCB HYDRAULIC EXCAVATOR  
JS 300LC**



**JCB, Inc. North American  
MACHINE PRICE LIST  
in U.S. Dollars**

**EFFECTIVE: April 1, 2018**

**CHANGES TO SPECIFICATIONS AND/OR PRICES MAY OCCUR.  
PLEASE REFER TO THE PRODUCT MANAGER FOR UPDATES**

	<b>JS300 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## STANDARD EQUIPMENT

<b>ENGINE</b>	MTU 6R1000, 241 HP at 1,900 RPM. Six-cylinder water cooled common rail direct injection diesel engine. Low emission engine, EPA Tier 4 Final compliant. Dual element Powercore air cleaner.
<b>HYDRAULICS</b>	Variable flow load sensing system with on demand and servo operated multi function open center control. Independent servo gear pump. Two main axial piston pumps yield combined flow of 132 GPM. Servo pump flow: 4.8 GPM.
<b>OPERATOR'S AREA</b>	Air conditioned cab, noise and vibration isolated by six hydraulically damped resilient mountings. Opening door window. Fan forced fresh air ventilation with defogger and washer/wiper. Fully adjustable suspension seat with seatbelt, headrest, armrests, and backrest recline. Two boom and one mainframe work light
<b>CONTROLS</b>	Excavator controls are ISO pattern, servo operated, with in cab 7" digital display and change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance and a console mounted switch.
<b>UPPER</b>	Monoboomb with choice of dipper arms to suit dig depth requirements. No reinforcing required for hammer operations. Boom: 20' 4" (6.2m). Dippers: 8' 2" (2.5m), 10'2" (3.1m), 12'2" (3.7m).
<b>UNDERCARRIAGE</b>	The undercarriage gives excellent stability, is a fully welded X-frame type with undercarriage center cover, engine undercover and travel drive motor, cover and shields. Twin top and nine bottom rollers are heat-treated, sealed and lubricated. Track idler is sealed and lubricated and incorporates spring cushion recoil.
<b>TRACK DRIVE</b>	Full hydrostatic, 2 speed, driven by two axial piston motors. Motors are guarded in undercarriage frame for protection from debris. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 2.9 MPH, low speed is 1.7 MPH. Parking brake is disc type, spring applied, hydraulic release.
<b>ELECTRICAL</b>	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 100 amp output alternator with 12 volt in-cab supply.
<b>LIVELINK</b>	3 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
<b>OPERATING WEIGHT</b>	Equipped with standard boom, dipper, 32" track shoes and excavator bucket: apprx. 71,160 lbs.
<b>WARRANTY</b>	3-year / 3,000 hour full coverage warranty (please see the machine warranty certificate for details)

### SECTIONS ARE ORGANIZED AS FOLLOWS:


**Section 1** - PACKAGE BUILDS

**Section 2** - CUSTOM BUILD - NEW FACTORY BUILT ORDERS

**Section 3** - OPTIONS - NEW FACTORY BUILT ORDERS

**Section 4** - ATTACHMENTS - NEW FACTORY BUILT ORDERS

**DEALER FIT - EXCAVATORS** (LISTED SEPARATELY FOR ALL EXCAVATORS)

	<b>JS300 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 1 - YELLOW SERIES

Select one of the following machine PACKAGE BUILD codes and ATTACHMENT(S) if required from the section at the bottom of this sheet. Package build configurations cannot normally be changed. If a Package Build does not meet your requirements please order a machine using the Custom Build, Attachments & Options Sections following.

### PACKAGE BUILD CODE:

#### SALES

CODE	ITEM	JS300
9017	JS300 LC Primary Build Tier 4 Final	✓
900A003	Long Undercarriage, 2600mm (102") Gauge, 4810mm (189") long	✓
900B013	800mm (32"). Triple Grouser	✓
900C371	Monoboom, 0 HBCV, 10' 2" (3.1m) Heavy Duty Dipper	✓
900D010	Tipping Link: Max Capacity Lifting Shackle	✓
900EA67	North American Manual Pack: English	✓
900K294	Hammer/Aux/Merged - 10' 2" (3.1m) Dipper	✓
900R001	AM/FM Radio	✓
900R011	Deluxe Seat - Air Suspension And Heated Base	✓


### SUGGESTED LIST PRICE

**\$266,074**

## ATTACHMENTS FOR YELLOW SERIES:

#### SALES

CODE	U.S. LIST
<b>EXCAVATOR BUCKETS</b>	
YWSEA11 ADD 328/00571. 54" BUCKET	\$9,833
YWSEA12 ADD 980/A8254. HYDRAULIC COUPLER	\$9,445
YWSEA13 ADD 980/B0216. HM270T	\$40,196
YWSEA14 ADD 328/00572. 60" BUCKET	\$10,564

	<b>JS300 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS:

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each E (Essential) category below. Select Options and/or Attachments from Section 3 or 4.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	ITEM	U.S. LIST
<b>BASE UNIT (E)</b>		
9017	JS300 LC Primary Build Tier 4 Final	\$256,627
<b>UNDERCARRIAGE (E)</b>		
900A003	Long Undercarriage, 2600mm (102") Gauge, 4810mm (189") long	\$0
<b>TRACK PADS (E)</b>		
900B012	700mm(28"), Triple Grouser	\$4,977
900B013	800mm (32"). Triple Grouser	\$8,073
900B014	900mm (35"), Triple Grouser	\$12,019
<b>MONO BOOM AND DIPPERS (E) Includes brackets for all attachment pipework</b>		
900C371	Monoboom, 0 HBCV, 10' 2" (3.1m) Heavy Duty Dipper	\$480
900C372	Monoboom, 0 HBCV, 12' 2" (3.7m) Heavy Duty Dipper	\$961
<b>TIPPING LINK (E)</b>		
900D002	Tipping Link: Max Capacity Lifting Shackle	\$0
<b>MANUAL PACK (E)</b>		
900EA67	North American Manual Pack: English	\$0

**JS300 HYDRAULIC EXCAVATOR**U.S. DOLLAR  
PRICE PAGESF.O.B.  
SAVANNAH, GA

EFFECTIVE: April 1, 2018

**SECTION 3 - OPTIONS - NEW FACTORY BUILT ORDERS:**

SALES CODE	ITEM	U.S. LIST
HYDRAULIC ATTACHMENT PIPEWORK - NEW FACTORY BUILT ORDERS ONLY		
900K294	Hammer/Aux/Merged - 10' 2" (3.1m) Dipper	\$0
900K295	Hammer/Aux/Merged - 12' 2" (3.7m) Dipper	\$0
Notes:	• High flow circuit pipework is dual function. The merged circuit adds in up to 70% of the flow from the second main pump. When operator selects hammer function hydraulic flow is delivered in one direction to run hammer. Circuit is operated by foot pedal. When auxiliary function is selected the same pump flow is delivered bi-directionally to run tool. Circuit can be operated by the foot pedal, hand control buttons or slider depending on code available.	
	• Low flow circuit: separate pipework set delivers servo pump flow bi-directionally to run tool. Operated by hand control buttons or slider.	
	• For additional factory installed hydraulic pipework options call JCB Product Marketing.	
	• Shut-off ball valve for hammer and auxiliary pipework available through JCB Parts Dept.	
OPTIONS NEW FACTORY BUILT ORDERS ONLY		
900M105	Hydraulic Quick Hitch	\$9,445
900M026	Hydraulic Quick Hitch Lite Installation	\$1,523
900R001	AM/FM Radio	\$169
900R011	Deluxe Seat - Air Suspension and Heated Base	\$726
900R130	Lower Level Windscreen Wiper	\$256
900S001	Fire Extinguisher	\$336
900S010	Vandal Cover Kit	\$2,282
900S020	FOPS Level 2 Guard - Front Windshield and Roof	\$5,618
900S025	Mesh Screen Guard for Front Windshield	\$1,477
900S130	Additional Worklights	\$470
900S132	Additional Worklights (2 cab lights, 1 counter weight light - FOPS Compatible Only)	\$470
900S140	Amber Beacon - Cab Roof	\$182
900V001	HP32 Hydraulic Oil - for Cold Climate Operation	\$0
900V002	HP68 Hydraulic Oil - for Hot Climate Operation	\$0

**SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS:**

SALES CODE	ITEM	U.S. LIST
<b>EXCAVATOR BUCKETS</b>		
YWSEA11	ADD 328/00571. 54" BUCKET	\$9,833
YWSEA12	ADD 980/A8254. HYDRAULIC COUPLER	\$9,445
YWSEA13	ADD 980/B0216. HM270T	\$40,196
YWSEA14	ADD 328/00572. 60" BUCKET	\$10,564





2018


**JCB HYDRAULIC EXCAVATOR  
JS 330LC**



**JCB, Inc. North American  
MACHINE PRICE LIST  
in U.S. Dollars**

**EFFECTIVE: April 1, 2018**

**CHANGES TO SPECIFICATIONS AND/OR PRICES MAY OCCUR.  
PLEASE REFER TO THE PRODUCT MANAGER FOR UPDATES**

	<b>JS330 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## STANDARD EQUIPMENT

<b>ENGINE</b>	MTU 6R1000, 281 HP at 1,900 RPM. Six-cylinder water cooled common rail direct injection diesel engine. Low emission engine, EPA Tier 4 Final compliant. Dual element Powercore air cleaner.
<b>HYDRAULICS</b>	Variable flow load sensing system with on demand and servo operated multi function open center control. Independent servo gear pump. Two main axial piston pumps yield combined flow of 154 GPM. Servo pump flow: 7.5 GPM.
<b>OPERATOR'S AREA</b>	Air conditioned cab, noise and vibration isolated by six hydraulically damped resilient mountings. Opening door window. Fan forced fresh air ventilation with defogger and washer/wiper. Fully adjustable suspension seat with seatbelt, headrest, armrests, and backrest recline. Two boom and one mainframe work light
<b>CONTROLS</b>	Excavator controls are ISO pattern, servo operated, with in cab 7" digital display and change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance and a console mounted switch.
<b>UPPER</b>	Monoboam with choice of dipper arms to suit dig depth requirements. No reinforcing required for hammer operations. Boom: 21' 2" (6.45m). Dippers: 8' 8" (2.63m), 10' 7" (3.23m), 13' 3" (4.03m)
<b>UNDERCARRIAGE</b>	The undercarriage gives excellent stability, is a fully welded X-frame type with undercarriage center cover, engine undercover and travel drive motor, cover and shields. Twin top and nine bottom rollers are heat-treated, sealed and lubricated. Track idler is sealed and lubricated and incorporates spring cushion recoil.
<b>TRACK DRIVE</b>	Full hydrostatic, 2 speed, driven by two axial piston motors. Motors are guarded in undercarriage frame for protection from debris. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 3.2 MPH, low speed is 1.9 MPH. Parking brake is disc type, spring applied, hydraulic release.
<b>ELECTRICAL</b>	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 100 amp output alternator with 12 volt in-cab supply.
<b>LIVELINK</b>	3 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
<b>OPERATING WEIGHT</b>	Equipped with standard boom, dipper, 32" track shoes and excavator bucket: apprx. 75,350 lbs.
<b>WARRANTY</b>	3-year / 3,000 hour full coverage warranty (please see the machine warranty certificate for details)

### SECTIONS ARE ORGANIZED AS FOLLOWS:


**Section 1** - PACKAGE BUILDS

**Section 2** - CUSTOM BUILD - NEW FACTORY BUILT ORDERS

**Section 3** - OPTIONS - NEW FACTORY BUILT ORDERS

**Section 4** - ATTACHMENTS - NEW FACTORY BUILT ORDERS

**DEALER FIT - EXCAVATORS** (LISTED SEPARATELY FOR ALL EXCAVATORS)

	<b>JS330 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 1 - PACKAGE BUILDS

Select one of the following machine PACKAGE BUILD codes and ATTACHMENT(S) if required from the section at the bottom of this sheet. Package build configurations cannot normally be changed. If a Package Build does not meet your requirements please order a machine using the Custom Build, Attachments & Options Sections following.


SALES		PACKAGE BUILD CODE:	<b>9381A</b>
CODE	ITEM		<b>JS330</b>
			<b>Monoboom</b>
9381	JS330 LC Primary Build Tier 4 Final		✓
900A800	Long Undercarriage, 2600mm (102") Gauge, 4810mm (189") Long		✓
900B802	800mm (32"), Triple Grouser		✓
900C882	Monoboom, 0 HBCV, 10' 7" (3.23m) Dipper		✓
900D003	Tipping Link: Max Capacity Lifting Shackle		✓
900EA67	North American Manual Pack: English		✓
900K867	Hammer/Aux/Merged - 10' 7" (3.23m) Dipper		✓
900R001	AM/FM Radio		✓
900R011	Deluxe Seat - Air Suspension And Heated Base		✓

**SUGGESTED LIST PRICE**

**\$280,465**

## ATTACHMENTS FOR PACKAGE BUILDS:

SALES CODE		U.S. LIST
	<b>EXCAVATOR BUCKETS (E)</b>	
	<b>HEAVY DUTY PLATE LIP</b>	
YWSEA11	ADD 328/00571. 54" BUCKET	\$9,833
YWSEA12	ADD 980/A8254. HYDRAULIC COUPLER	\$9,445
YWSEA13	ADD 980/B0216. HM270T	\$40,196
YWSEA14	ADD 328/00572. 60" BUCKET	\$10,564

	<b>JS330 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS:

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each E (Essential) category below. Select Options and/or Attachments from Section 3 or 4.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	ITEM	U.S. LIST
<b>BASE UNIT (E)</b>		
9381	JS330 LC Primary Build Tier 4 Final	\$272,774
<b>UNDERCARRIAGE (E)</b>		
900A800	Long Undercarriage, 2600mm (102") Gauge, 4810mm (189") Long	\$0
<b>TRACK PADS (E)</b>		
900B801	700mm (28"), Triple Grouser	\$3,495
900B802	800mm (32"), Triple Grouser	\$5,835
900B803	900mm (35"), Triple Grouser	\$8,436
<b>MONO BOOM AND DIPPERS (E) Includes brackets for all attachment pipework</b>		
900C881	Monoboom, 0 HBCV, 8' 8" (2.63m) Dipper	\$480
900C882	Monoboom, 0 HBCV, 10' 7" (3.23m) Dipper	\$961
<b>TIPPING LINK (E)</b>		
900D003	Tipping Link: Max Capacity Lifting Shackle	\$0
<b>MANUAL PACK (E)</b>		
900EA67	North American Manual Pack: English	\$0

**JS330 HYDRAULIC EXCAVATOR**U.S. DOLLAR  
PRICE PAGESF.O.B.  
SAVANNAH, GA

EFFECTIVE: April 1, 2018

**SECTION 3 - OPTIONS - NEW FACTORY BUILT ORDERS:**

SALES CODE	ITEM	U.S. LIST
HYDRAULIC ATTACHMENT PIPEWORK - NEW FACTORY BUILT ORDERS ONLY		
900K866	Hammer/Aux/Merged - 8' 8" (2.63m) Dipper	\$0
900K867	Hammer/Aux/Merged - 10' 7" (3.23m) Dipper	\$0
Notes:	• High flow circuit pipework is dual function. The merged circuit adds in up to 70% of the flow from the second main pump. When operator selects hammer function hydraulic flow is delivered in one direction to run hammer. Circuit is operated by foot pedal. When auxiliary function is selected the same pump flow is delivered bi-directionally to run tool. Circuit can be operated by the foot pedal, hand control buttons or slider depending on code available.	
	• Low flow circuit: separate pipework set delivers servo pump flow bi-directionally to run tool. Operated by hand control buttons or slider.	
	• For additional factory installed hydraulic pipework options call JCB Product Marketing.	
	• Shut-off ball valve for hammer and auxiliary pipework available through JCB Parts Dept.	
OPTIONS NEW FACTORY BUILT ORDERS ONLY		
900M105	Hydraulic Quick Hitch	\$9,445
900M026	Hydraulic Quick Hitch Lite Installation	\$1,523
900R001	AM/FM Radio	\$169
900R011	Deluxe Seat - Air Suspension and Heated Base	\$726
900R130	Lower Level Windscreen Wiper	\$256
900S001	Fire Extinguisher	\$336
900S010	Vandal Cover Kit	\$2,282
900S020	FOPS Level 2 Guard - Front Windshield and Roof	\$5,618
900S025	Mesh Screen Guard for Front Windshield	\$1,477
900S130	Additional Worklights	\$470
900S132	Additional Worklights (2 cab lights, 1 counter weight light - FOPS Compatible Only)	\$470
900S140	Amber Beacon - Cab Roof	\$182
900V001	HP32 Hydraulic Oil - for Cold Climate Operation	\$0
900V002	HP68 Hydraulic Oil - for Hot Climate Operation	\$0

**SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS:**

SALES CODE	ITEM	U.S. LIST
<b>EXCAVATOR BUCKETS</b>		
YWSEA11	ADD 328/00571. 54" BUCKET	\$9,833
YWSEA12	ADD 980/A8254. HYDRAULIC COUPLER	\$9,445
YWSEA13	ADD 980/B0216. HM270T	\$40,196
YWSEA14	ADD 328/00572. 60" BUCKET	\$10,564



2018

**JCB HYDRAULIC EXCAVATOR  
JS 370LC**



**JCB, Inc. North American  
MACHINE PRICE LIST  
in U.S. Dollars**

**EFFECTIVE: April 1, 2018**

**CHANGES TO SPECIFICATIONS AND/OR PRICES MAY OCCUR.  
PLEASE REFER TO THE PRODUCT MANAGER FOR UPDATES**

	<b>JS370 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## STANDARD EQUIPMENT

<b>ENGINE</b>	MTU 6R1000, 281 HP at 1,900 RPM. Six-cylinder water cooled common rail direct injection diesel engine. Low emission engine, EPA Tier 4 Final compliant. Dual element Powercore air cleaner.
<b>HYDRAULICS</b>	Variable flow load sensing system with on demand and servo operated multi function open center control. Independent servo gear pump. Two main axial piston pumps yield combined flow of 160 GPM. Servo pump flow: 7.5 GPM.
<b>OPERATOR'S AREA</b>	Air conditioned cab, noise and vibration isolated by six hydraulically damped resilient mountings. Opening door window. Fan forced fresh air ventilation with defogger and washer/wiper. Fully adjustable suspension seat with seatbelt, headrest, armrests, and backrest recline. Two boom and one mainframe work light
<b>CONTROLS</b>	Excavator controls are ISO pattern, servo operated, with in cab 7" digital display and change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance and a console mounted switch.
<b>UPPER</b>	Monoboomb with choice of dipper arms to suit dig depth requirements. No reinforcing required for hammer operations. Boom: 21' 2" (6.45m). Dippers: 8' 8" (2.63m), 10' 7" (3.23m), 13' 3" (4.03m)
<b>UNDERCARRIAGE</b>	The undercarriage gives excellent stability, is a fully welded X-frame type with undercarriage center cover, engine undercover and travel drive motor, cover and shields. Twin top and nine bottom rollers are heat-treated, sealed and lubricated. Track idler is sealed and lubricated and incorporates spring cushion recoil.
<b>TRACK DRIVE</b>	Full hydrostatic, 2 speed, driven by two axial piston motors. Motors are guarded in undercarriage frame for protection from debris. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 3.2 MPH, low speed is 1.9 MPH. Parking brake is disc type, spring applied, hydraulic release.
<b>ELECTRICAL</b>	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 100 amp output alternator with 12 volt in-cab supply.
<b>LIVELINK</b>	3 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
<b>OPERATING WEIGHT</b>	Equipped with standard boom, dipper, 32" track shoes and excavator bucket: apprx. 81,800 lbs.
<b>WARRANTY</b>	3-year / 3,000 hour full coverage warranty (please see the machine warranty certificate for details)

### SECTIONS ARE ORGANIZED AS FOLLOWS:


**Section 1** - PACKAGE BUILDS

**Section 2** - CUSTOM BUILD - NEW FACTORY BUILT ORDERS

**Section 3** - OPTIONS - NEW FACTORY BUILT ORDERS

**Section 4** - ATTACHMENTS - NEW FACTORY BUILT ORDERS

**DEALER FIT - EXCAVATORS** (LISTED SEPARATELY FOR ALL EXCAVATORS)

	<b>JS370 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 1 - YELLOW SERIES

Select one of the following machine PACKAGE BUILD codes and ATTACHMENT(S) if required from the section at the bottom of this sheet. Package build configurations cannot normally be changed. If a Package Build does not meet your requirements please order a machine using the Custom Build, Attachments & Options Sections following.

### SALES

CODE	ITEM	JS370
9403	JS370 LC Primary Build Tier 4 Final	✓
900A006	Long Undercarriage, 2600mm (102") Gauge, 4947mm (195") long	✓
900B021	800mm (32") Track Plates	✓
900C157	Monoboom, 0 HBCV, 10' 7" (3.23m) Dipper	✓
900D003	Tipping Link: Max Capacity Lifting Shackle	✓
900EA67	North American Manual Pack: English	✓
900K755	Hammer/Aux/Merged - 10' 7" (3.23m) Dipper	✓
900R001	AM/FM Radio	✓
900R011	Deluxe Seat - Air Suspension And Heated Base	✓


**SUGGESTED LIST PRICE**

**\$296,265**

## ATTACHMENTS FOR YELLOW SERIES:

SALES CODE	U.S. LIST
<b>EXCAVATOR BUCKETS</b>	
YWSEA11 ADD 328/00571. 54" BUCKET	\$9,833
YWSEA12 ADD 980/A8254. HYDRAULIC COUPLER	\$9,445
YWSEA13 ADD 980/B0216. HM270T	\$40,196
YWSEA14 ADD 328/00572. 60" BUCKET	\$10,564



	<b>JS370 HYDRAULIC EXCAVATOR</b>	U.S. DOLLAR PRICE PAGES	F.O.B. SAVANNAH, GA	EFFECTIVE: April 1, 2018
---	----------------------------------	----------------------------	------------------------	--------------------------

## SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS:

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each E (Essential) category below. Select Options and/or Attachments from Section 3 or 4.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	ITEM	U.S. LIST
<b>BASE UNIT (E)</b>		
9403	JS370 LC Primary Build Tier 4 Final	\$288,575
<b>UNDERCARRIAGE (E)</b>		
900A006	Long Undercarriage, 2600mm (102") Gauge, 4947mm (195") long	\$0
<b>TRACK PADS (E)</b>		
900B020	700mm (28") Track Plates	\$3,495
900B021	800mm (32") Track Plates	\$5,835
900B022	900mm (35") Track Plates	\$8,435
<b>MONO BOOM AND DIPPERS (E) Includes brackets for all attachment pipework</b>		
900C156	Monoboom, 0 HBCV, 8' 8" (2.63m) Dipper	\$480
900C157	Monoboom, 0 HBCV, 10' 7" (3.23m) Dipper	\$961
<b>TIPPING LINK (E)</b>		
900D003	Tipping Link: Max Capacity Lifting Shackle	\$0
<b>MANUAL PACK (E)</b>		
900EA67	North American Manual Pack: English	\$0

**JS370 HYDRAULIC EXCAVATOR**U.S. DOLLAR  
PRICE PAGESF.O.B.  
SAVANNAH, GA

EFFECTIVE: April 1, 2018

**SECTION 3 - OPTIONS - NEW FACTORY BUILT ORDERS:**

SALES CODE	ITEM	U.S. LIST
HYDRAULIC ATTACHMENT PIPEWORK - NEW FACTORY BUILT ORDERS ONLY		
900K754	Hammer/Aux/Merged - 8' 8" (2.63m) Dipper	\$0
900K755	Hammer/Aux/Merged - 10' 7" (4.03m) Dipper	\$0
Notes:	• High flow circuit pipework is dual function. The merged circuit adds in up to 70% of the flow from the second main pump. When operator selects hammer function hydraulic flow is delivered in one direction to run hammer. Circuit is operated by foot pedal. When auxiliary function is selected the same pump flow is delivered bi-directionally to run tool. Circuit can be operated by the foot pedal, hand control buttons or slider depending on code available.	
	• Low flow circuit: separate pipework set delivers servo pump flow bi-directionally to run tool. Operated by hand control buttons or slider.	
	• For additional factory installed hydraulic pipework options call JCB Product Marketing.	
	• Shut-off ball valve for hammer and auxiliary pipework available through JCB Parts Dept.	
OPTIONS NEW FACTORY BUILT ORDERS ONLY		
900M105	Hydraulic Quick Hitch	\$9,445
900M026	Hydraulic Quick Hitch Lite Installation	\$1,523
900R001	AM/FM Radio	\$169
900R011	Deluxe Seat - Air Suspension and Heated Base	\$726
900R130	Lower Level Windscreen Wiper	\$256
900S001	Fire Extinguisher	\$336
900S010	Vandal Cover Kit	\$2,282
900S020	FOPS Level 2 Guard - Front Windshield and Roof	\$5,618
900S025	Mesh Screen Guard for Front Windshield	\$1,477
900S130	Additional Worklights	\$470
900S132	Additional Worklights (2 cab lights, 1 counter weight light - FOPS Compatible Only)	\$470
900S140	Amber Beacon - Cab Roof	\$182
900V001	HP32 Hydraulic Oil - for Cold Climate Operation	\$0
900V002	HP68 Hydraulic Oil - for Hot Climate Operation	\$0

**SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS:**

SALES CODE	ITEM	U.S. LIST
<b>EXCAVATOR BUCKETS</b>		
YWSEA11	ADD 328/00571. 54" BUCKET	\$9,833
YWSEA12	ADD 980/A8254. HYDRAULIC COUPLER	\$9,445
YWSEA13	ADD 980/B0216. HM270T	\$40,196
YWSEA14	ADD 328/00572. 60" BUCKET	\$10,564