



## **2019 MACHINE PRICE LIST**

519 Bonnie Valentine Way, Pendergrass, GA 30567

e-mail [sales@takeuchi-us.com](mailto:sales@takeuchi-us.com)  
[www.takeuchi-us.com](http://www.takeuchi-us.com)

Prices and specifications  
subject to change without notice

Prices are F.O.B. Pendergrass, GA  
Effective 1 January 2019



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

# TB210R

## Compact Excavator

### STANDARD EQUIPMENT

|                                  |  |
|----------------------------------|--|
| Operating Weight: 2,535 lbs.     | ROPS/TOPS 2 post foldable canopy                                 |
| Width: 29.5" / 40.2"             | Hydraulically retractable track frame                            |
| Maximum Dig Depth: 5' 9.1"       | Adjustable width dozer blade with 2 pin-on extensions            |
| Bucket Digging Force: 2,518 lbs. | Pilot operated joystick controls with safety lock out            |
| Horsepower / RPM: 11.7 / 2,200   | Pattern change valve   |
| Travel Speed: 1.2 / 2.3 mph      | Two-way auxiliary hydraulic circuit routed to the end of the arm |
| Auxiliary Flow: 5.9 gpm          | Adjustable seat with 2" retractable seat belt                    |
| Boom swing: Left 85° / Right 85° | Two speed travel   |
| 7.1" wide rubber tracks          | Travel alarm   |
|                                  | Boom mounted work light  |
|                                  | Horn   |
|                                  | Cast iron, wrap around counterweight                             |

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description  | Suggested List Price |
|--------------|--|----------------------|
| TB210R       | TB210R Equipped with ROPS/TOPS 2-post foldable canopy, Rubber tracks, Travel alarm, Auxiliary hydraulics | \$24,750             |

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

|          |   |       |
|----------|---|-------|
| BTB00708 | 8" Bucket with teeth, .8 cu. ft. capacity   | \$360 |
| BTB00712 | 12" Bucket with teeth, 1.1 cu. ft. capacity | \$380 |

### FIELD INSTALLED OPTIONS

|            |   |       |
|------------|---|-------|
| 0333400003 | 3" Retractable seat belt in lieu of standard 2" | \$157 |
|------------|---|-------|



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

# TB216

## Compact Excavator

### STANDARD EQUIPMENT

|   |   |
|---|---|
| Operating Weight: 3,900 lbs.  | ROPS/TOPS/OPG 4 post canopy                                       |
| Width: 38.6" / 51.2"  | LCD gauge panel with multi-functional operator information center |
| Maximum Dig Depth: 7' 10"   | Hydraulically retractable track frame                             |
| Bucket Digging Force: 4,250 lbs.  | Travel alarm  |
| Horsepower / RPM: 15 / 2,400  | Two-speed travel with automatic down shift                        |
| Travel Speed: 1.4 / 2.6 mph   | Pattern selector valve  |
| Auxiliary Flow: 8.9 gpm   | Pilot operated joystick controls with safety lock out             |
| Boom swing: Left 80° / Right 50°  | Cast iron, wrap around counterweight                              |
| 9" wide rubber tracks   | Adjustable suspension seat with 2" retractable seat belt          |
| Long Arm w/ integrated thumb mount  | Two-way auxiliary hydraulic circuit routed to the end of the arm  |
|   | Variable displacement axial piston main hydraulic pumps           |
| Electronic engine monitoring system   | Adjustable width dozer blade                                      |
| TFM hardware standard equipment, service included through the standard warranty period (sn 216101378 ~) |   |

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description   | Suggested List Price |
|--------------|---|----------------------|
| TB216        | TB216 Equipped with ROPS/TOPS/OPG canopy, Rubber tracks | \$32,526             |

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

|           |  |         |
|-----------|--|---------|
| BTB01608  | 8" Pin-On Bucket with teeth, 1.1 cu. ft. capacity                    | \$465   |
| BTB01612  | 12" Pin-On Bucket with teeth, 1.5 cu. ft. capacity                   | \$480   |
| BTB01618  | 18" Pin-On Bucket with teeth, 2.4 cu. ft. capacity                   | \$557   |
| BTB01624  | 24" Pin-On Bucket with teeth, 3.2 cu. ft. capacity                   | \$650   |
| BQC01600  | Quick Coupler  | \$785   |
| BQC01612  | 12" Quick Coupler Bucket with teeth, 1.5 cu. ft. capacity            | \$480   |
| BQC01618  | 18" Quick Coupler Bucket with teeth, 2.4 cu. ft. capacity            | \$557   |
| BQC01624  | 24" Quick Coupler Bucket with teeth, 3.2 cu. ft. capacity            | \$650   |
| BQC01624D | 24" Quick Coupler Ditch Bucket, 3.0 cu. ft. capacity                 | \$882   |
| ATH216I   | INSTALLED Hydraulic thumb (Only compatible w/ 12" or larger Buckets) | \$2,025 |

### FIELD INSTALLED OPTIONS

|            |   |         |
|------------|---|---------|
| 1914199048 | 3" Non-retractable seat belt in lieu of standard 2"           | \$73    |
| ATH216K    | Hydraulic thumb (Only compatible with 12" and larger buckets) | \$1,680 |



519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

# TB216H

## Hybrid Compact Excavator

### STANDARD EQUIPMENT

|   |   |
|---|---|
| Operating Weight: 4,277 lbs.  | LCD gauge panel with multi-functional operator information center |
| Width: 38.6" / 51.2"  | Hydraulically retractable track frame                             |
| Maximum Dig Depth: 7' 10"   | Travel alarm  |
| Bucket Digging Force: 4,250 lbs.  | Two-speed travel with automatic down shift                        |
| Horsepower / RPM: 15 / 2,400 (diesel)   | Pattern selector valve  |
| 14.2 / 2,400 (electric)   | Pilot operated joystick controls with safety lock out             |
| Travel Speed: 1.4 / 2.6 mph   | Cast iron, wrap around counterweight                              |
| Auxiliary Flow: 8.9 gpm   | Adjustable suspension seat with 2" retractable seat belt          |
| Boom swing: Left 80°/ Right 50°   | Two-way auxiliary hydraulic circuit routed to the end of the arm  |
| 9" wide rubber tracks   | Variable displacement axial piston main hydraulic pumps           |
| Long Arm w/ integrated thumb mount  | Adjustable width dozer blade                                      |
| ROPS/TOPS/OPG 4 post canopy   | Electronic engine monitoring system                               |
| TFM hardware standard equipment, service included through the standard warranty period (sn 216101378 ~) |   |

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description  | Suggested List Price |
|--------------|--|----------------------|
| TB216H       | TB216 Equipped with ROPS/TOPS/OPG canopy, Rubber tracks, diesel engine/electric motor, and 15' extension cable | \$52,260             |

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

|           |  |         |
|-----------|--|---------|
| BTB01608  | 8" Pin-On Bucket with teeth, 1.1 cu. ft. capacity                    | \$465   |
| BTB01612  | 12" Pin-On Bucket with teeth, 1.5 cu. ft. capacity                   | \$480   |
| BTB01618  | 18" Pin-On Bucket with teeth, 2.4 cu. ft. capacity                   | \$557   |
| BTB01624  | 24" Pin-On Bucket with teeth, 3.2 cu. ft. capacity                   | \$650   |
| BQC01600  | Quick Coupler  | \$785   |
| BQC01612  | 12" Quick Coupler Bucket with teeth, 1.5 cu. ft. capacity            | \$480   |
| BQC01618  | 18" Quick Coupler Bucket with teeth, 2.4 cu. ft. capacity            | \$557   |
| BQC01624  | 24" Quick Coupler Bucket with teeth, 3.2 cu. ft. capacity            | \$650   |
| BQC01624D | 24" Quick Coupler Ditch Bucket, 3.0 cu. ft. capacity                 | \$882   |
| ATH216I   | INSTALLED Hydraulic thumb (Only compatible w/ 12" or larger Buckets) | \$2,025 |

### FIELD INSTALLED OPTIONS

|            |   |         |
|------------|---|---------|
| 1914199048 | 3" Non-retractable seat belt in lieu of standard 2"           | \$73    |
| ATH216K    | Hydraulic thumb (Only compatible with 12" and larger buckets) | \$1,680 |

\*\* All TB216H's purchased for use in Canada must have a CSA (Canadian Standards Association) inspection on the electrical components prior to retail sale or rental. Canadian Dealer's and Direct Accounts are responsible for scheduling this inspection and any associated costs/fees. Inspection services are available throughout Canada. If you have questions concerning CSA inspections you may go to their website: <https://www.csagroup.org> or contact the CSA Group (Product Evaluation) at 888.273.3335. \*\*



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

# TB230

## Compact Excavator

### STANDARD EQUIPMENT

|  |  |
|--|--|
| Operating Weight: 6,360 lbs.   | TOPS/ROPS/OPG 4 post canopy  |
| Width: 4' 9.5"   | Color gauge panel with multi-function operator information center  |
| Maximum Dig Depth: 9' 3.6"   | High back adjustable suspension seat   |
| Bucket Digging Force: 6,471 lbs.   | Pilot operated joystick control with pattern change valve  |
| Horsepower / RPM: 24.4 / 2,400   | EPA Final Tier 4 compliant engine with engine monitoring system  |
| Travel Speed: 1.8 / 3.2 mph  | Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door   |
| Auxiliary Flow: 13.4 gpm   | High capacity radiator and hydraulic oil cooler  |
| Boom Swing: Left 79° / Right 58°   | Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode |
| Track Width: 11.8"   | Safety features include: Travel alarm, retractable seat belt control lockout, pilot accumulator, and lights                                    |
| Two speed travel with automatic shift down   | Variable displacement axial piston pump  |
| Reinforced arm w/ Integrated thumb mount   | Auto Idle  |
| Heavy duty dozer blade with float  |  |
| TFM hardware standard equipment, service included through the standard warranty period (sn 13000923 ~) |  |

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code           | Description  | Suggested List Price |
|------------------------|--|----------------------|
| TB230                  | TB230 Canopy Equipped with Rubber Tracks   | \$42,127             |
| TB230A (w/Angle Blade) | TB230 Canopy (above Equipped) with <b>Angle Blade</b><br>Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge | \$44,960             |

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

|           |  |         |
|-----------|--|---------|
| BTB12512  | 12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity                   | \$650   |
| BTB12518  | 18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity                   | \$675   |
| BTB12524  | 24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity                   | \$835   |
| BQC12500  | Quick Coupler  | \$785   |
| BQC12512  | 12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity            | \$650   |
| BQC12513  | 13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity            | \$675   |
| BQC12518  | 18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity            | \$675   |
| BQC12524  | 24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity            | \$835   |
| BQC12536D | 36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity                 | \$1,015 |
| ATH230I   | INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets) | \$1,920 |

### FIELD INSTALLED OPTIONS

|            |   |         |
|------------|---|---------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2"               | \$91    |
| ATH230K    | Hydraulic thumb (Only compatible with 13" and larger buckets) | \$1,575 |

### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

# TB235-2

## Compact Excavator

### STANDARD EQUIPMENT

|  |   |
|--|---|
| Operating Weight: 7,418 lbs.   | TOPS/ROPS/OPG 4 post canopy   |
| Width: 5' 2.2"   | Color gauge panel with multi-function operator information center   |
| Maximum Dig Depth: 10' 7.8"  | High back adjustable suspension seat  |
| Bucket Digging Force: 9,127 lbs.   | Pilot operated joystick control with pattern change valve   |
| Horsepower / RPM: 24.4 / 2,400   | EPA Final Tier 4 compliant engine and engine monitoring system  |
| Travel Speed: 1.7 / 2.8 mph  | Self bleeding fuel system with ground level fuel fill, sight gauge and lockable doo                         |
| Auxiliary Flow: 15.8 gpm   | Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system                                  |
| Boom Swing: Left 70° / Right 55°   | proportional slide switch, one-way mode and continous detent mode   |
| Track width: 11.8"   | Safety features include: travel alarm, retractable seat belt control lockout, pilot accumulator, and lights |
| Two speed travel with automatic shift down   | Varibale displacement axial piston pump   |
| Reinforced arm w/ Integrated thumb mount   | Auto Idle   |
| Heavy duty dozer blade with float  |   |
| TFM hardware standard equipment, service included through the standard warranty period |   |

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code                | Description  | Suggested List Price |
|-----------------------------|--|----------------------|
| TB235-2R                    | TB235-2 Canopy Equipped with Rubber Tracks   | \$47,500             |
| TB235-2RA (w/Angle Blade)   | TB235-2 Canopy (above Equipped) with <b>Angle Blade</b><br>Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge   | \$50,590             |
| TB235-2CR                   | TB235-2 Cab Equipped with Rubber<br>TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet | \$54,800             |
| TB235-2CRA (w/ Angle Blade) | TB235-2 Cab (above Equipped) with <b>Angle Blade</b><br>Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge  | \$57,890             |

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

|           |  |         |
|-----------|--|---------|
| BTB13512  | 12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity                   | \$650   |
| BTB13518  | 18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity                   | \$675   |
| BTB13524  | 24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity                   | \$835   |
| BQC13500  | Quick Coupler  | \$785   |
| BQC12512  | 12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity            | \$650   |
| BQC12513  | 13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity            | \$675   |
| BQC12518  | 18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity            | \$675   |
| BQC12524  | 24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity            | \$835   |
| BQC12536D | 36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity                 | \$1,015 |
| ATH235-2I | INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets) | \$1,920 |

### FIELD INSTALLED OPTIONS

|            |   |         |
|------------|---|---------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2"               | \$91    |
| ATH235-2K  | Hydraulic thumb (Only compatible with 13" and larger buckets) | \$1,575 |

### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

# TB240

## Compact Excavator

### STANDARD EQUIPMENT

|   |  |
|---|--|
| Operating Weight: 8,570 lbs.  | TOPS/ROPS/OPG 4 post canopy  |
| Width: 5' 8.5"  | Color gauge panel with multi-function operator information center  |
| Maximum Dig Depth: 11' 4.4"   | High back adjustable suspension seat   |
| Bucket Digging Force: 9,959 lbs.  | Pilot operated joystick control with pattern change valve  |
| Horsepower / RPM: 35.8 / 2,200  | EPA Final Tier 4 compliant engine with DPF and engine monitoring system  |
| Travel Speed: 1.8 / 3.3 mph   | Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door   |
| Auxiliary Flow: 17.1 gpm  | Side by side industrial type radiator and hydraulic oil cooler   |
| Boom Swing: Left 76° / Right 58°  | Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode |
| Track width: 13.8"  | Safety features include: Travel alarm, retractable seat belt, control lockout, pilot accumulator, and lights                                   |
| Two speed travel with automatic shift down  | Variable displacement axial piston pump  |
| Reinforced arm w/ Integrated thumb mount  | Auto Idle  |
| Heavy duty dozer blade with float   |  |
| TFM hardware standard equipment, service included through the standard warranty period (Canopy: sn 124001379~ / Cab: sn 124001483~) |  |

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code             | Description  | Suggested List Price |
|--------------------------|--|----------------------|
| TB240                    | TB240 Canopy Equipped with Rubber or Steel Tracks  | \$54,343             |
| TB240A (w/Angle Blade)   | TB240 Canopy (above Equipped) with <b>Angle Blade</b><br>Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge   | \$57,433             |
| TB240C                   | TB240 Cab Equipped with Rubber or Steel Tracks<br>TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet | \$61,903             |
| TB240CA (w/ Angle Blade) | TB240 Cab (above Equipped) with <b>Angle Blade</b><br>Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge  | \$64,993             |

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

|           |  |         |
|-----------|--|---------|
| BTB13512  | 12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity                   | \$650   |
| BTB13518  | 18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity                   | \$675   |
| BTB13524  | 24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity                   | \$835   |
| BQC13500  | Quick Coupler  | \$785   |
| BQC12512  | 12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity            | \$650   |
| BQC12513  | 13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity            | \$675   |
| BQC12518  | 18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity            | \$675   |
| BQC12524  | 24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity            | \$835   |
| BQC12536D | 36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity                 | \$1,015 |
| ATH240I   | INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets) | \$1,920 |

### FIELD INSTALLED OPTIONS

|             |   |         |
|-------------|---|---------|
| 1914199948  | 3" Retractable seat belt in lieu of standard 2"               | \$91    |
| ATH240K     | Hydraulic thumb (Only compatible with 13" and larger buckets) | \$1,575 |
| 1914054391A | Bolt on rubber pads for TB240 steel track unit                | \$3,480 |

### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

# TB250-2

## Compact Excavator

### STANDARD EQUIPMENT

|  |  |
|--|--|
| Operating Weight: 10,737 lbs.  | TOPS/ROPS/OPG 4 post canopy  |
| Width: 6' 0"   | Color gauge panel with multi-function operator information center  |
| Maximum Dig Depth: 12' 4.8"  | High back adjustable suspension seat   |
| Bucket Digging Force: 10,430 lbs.  | Pilot operated joystick control with pattern change valve  |
| Horsepower / RPM: 39 / 2,400   | EPA Final Tier 4 compliant engine with DPF and engine monitoring system  |
| Travel Speed: 1.6 / 2.6 mph  | Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door   |
| Auxiliary Flow: 24 gpm   | Side by side industrial type radiator and hydraulic oil cooler   |
| Track width: 15.7"   | Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode |
|  | Safety features include: Travel alarm, retractable seat belt, control lockout, pilot accumulator, and lights                                   |
| Two speed travel with automatic shift down   | Variable displacement axial piston pump  |
| Reinforced arm w/ integrated thumb mount   | Auto Idle  |
| Heavy duty dozer blade with float  |  |
| TFM hardware standard equipment, service included through the standard warranty period |  |

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code               | Description  | Suggested List Price |
|----------------------------|--|----------------------|
| TB250-2                    | TB250-2 Canopy Equipped with Rubber or Steel Tracks  | \$65,000             |
| TB250-2A (w/Angle Blade)   | TB250-2 Canopy (above Equipped) with Angle Blade<br>Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge  | \$68,100             |
| TB250-2C                   | TB250-2 Cab Equipped with Rubber or Steel Tracks<br>TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet | \$71,000             |
| TB250-2CA (w/ Angle Blade) | TB250-2 Cab (above Equipped) with Angle Blade<br>Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge   | \$74,100             |

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

|           |  |         |
|-----------|--|---------|
| BTB14512  | 12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity                   | \$945   |
| BTB14518  | 18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity                   | \$1,000 |
| BTB14524  | 24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity                   | \$1,080 |
| BTB14536  | 36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity                   | \$1,340 |
| BQC14500  | Quick Coupler  | \$800   |
| BQC14512  | 12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity            | \$945   |
| BQC14518  | 18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity            | \$1,000 |
| BQC14524  | 24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity            | \$1,080 |
| BQC14536  | 36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity            | \$1,340 |
| BQC14536D | 36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity                 | \$1,283 |
| ATH250-2I | INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets) | \$2,070 |

### FIELD INSTALLED OPTIONS

|            |   |         |
|------------|---|---------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2"               | \$91    |
| ATH250-2K  | Hydraulic Thumb (Only compatible with 18" and larger buckets) | \$1,722 |

### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard





519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

# TB260

## Compact Excavator

### STANDARD EQUIPMENT

|  |  |
|--|--|
| Operating Weight: 12,125 lbs.  | TOPS/ROPS/OPG 4 post canopy  |
| Width: 6' 6.7"   | Color gauge panel with multi-function operator information center                    |
| Maximum Dig Depth: 12' 9.4'  | Adjustable high back suspension seat   |
| Bucket Digging Force: 12,756 lbs   | Pilot operated joystick control with pattern change valve                            |
| Horsepower / RPM: 47.6 / 2,400   | Proportional slide switch control auxiliary hydraulic                                |
| Travel Speed: 1.7 / 3.0 mph  | EPA Final Tier 4 Turbocharged engine with DPF and engine monitoring system           |
| Primary Aux Flow: 27.0 gpm   | Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door |
| Second Aux Flow: 11.6 gpm  | Side by side radiator and hydraulic cooler   |
| Boom Swing: Left 78° / Right 55°   | Variable Displacement axial piston pump  |
| Track Width: 15.7"   | Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow           |
| Two speed travel with automatic shift down   | control system and proportional slide switch control                                 |
| Reinforced arm w/ Integrated thumb mount   | Primary auxiliary continuous mode and one-way mode                                   |
| Heavy duty dozer blade with float  | Safety features include: Travel alarm, retractable seat belt                         |
| Auto Idle  | control lockout, pilot accumulator, mirrors and lights                               |
| TFM hardware standard equipment, service included through the standard warranty period (Canopy: sn 1261001302~ / Cab: sn 1261001605- |  |

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code   | Description  | Suggested List Price |
|--|--|----------------------|
| TB260  | TB260 Equipped with ROPS/TOPS/FOPS canopy, Rubber or Steel Tracks  | \$71,807             |
| TB260A (w/Angle Blade)                                 | TB260 Canopy (above Equipped) with <b>Angle Blade</b><br>Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge   | \$74,897             |
| TB260L<br>(w/ Segmented Rubber Tracks)                 | TB260 Canopy (above Equipped with Segmented Rubber <b>Tracks</b> )   | \$76,957             |
| TB260LA<br>(w/ Angle Blade & Segmented Rubber Tracks)  | TB260 Canopy (above Equipped with Segmented Rubber <b>Tracks</b> ) w/ <b>Angle Blade</b> , Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge   | \$80,047             |
| TB260C   | TB260 Cab Equipped with Rubber or Steel Tracks<br>TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio 12v power outlet | \$78,605             |
| TB260CA (w/Angle Blade)                                | TB260 Cab (above Equipped) with <b>Angle Blade</b><br>Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge  | \$81,695             |
| TB260CL<br>(w/ Segmented Rubber Tracks)                | TB260 Cab (above Equipped with <b>Segmented Rubber Tracks</b> )  | \$83,755             |
| TB260CLA<br>(w/ Angle Blade & Segmented Rubber Tracks) | TB260 Cab (above Equipped with <b>Segmented Rubber Tracks</b> ) w/ <b>Angle Blade</b> , Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge  | \$86,845             |

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

|           |  |         |
|-----------|--|---------|
| BTB26012  | 12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity                   | \$945   |
| BTB26018  | 18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity                   | \$1,000 |
| BTB26024  | 24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity                   | \$1,080 |
| BTB26036  | 36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity                   | \$1,340 |
| BQC26000  | Quick Coupler  | \$800   |
| BQC14512  | 12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity            | \$945   |
| BQC14518  | 18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity            | \$1,000 |
| BQC14524  | 24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity            | \$1,080 |
| BQC14536  | 36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity            | \$1,340 |
| BQC14536D | 36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity                 | \$1,283 |
| ATH260I   | INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets) | \$2,070 |

### FIELD INSTALLED OPTIONS

|            |   |         |
|------------|---|---------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2"               | \$91    |
| ATH260K    | Hydraulic Thumb (Only compatible with 18" and larger buckets) | \$1,722 |

### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard

Prices and specifications  
subject to change without notice

P-7

Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA  
Effective 1 January 2019



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

# TB290

## Excavator

### STANDARD EQUIPMENT

|   |  |
|---|--|
| Operating Weight: 18,630 lbs.   | ROPS/OPG enclosed cab w/ air conditioner/heat, windshield wiper, 12v power outlet, and AM/FM/MP3 radio   |
| Width: 7' 7"  | Color 5.7" gauge panel with multi-function operator information center   |
| Maximum Dig Depth: 15'  | 10-way adjustable high back suspension seat  |
| Bucket Digging Force: 16,565 lbs.   | Pilot operated joystick control with pattern change valve  |
| Net Horsepower / RPM: 69.2 / 2,000  | EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system   |
| Travel Speed: 1.6 / 3.1 mph   | Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door   |
| Auxiliary Flow: 26.4 gpm  | Side by side radiator and hydraulic cooler   |
| Second Aux Flow: 14.5 gpm   | Load sensing variable displacement hydraulic system  |
| Boom Swing: Left 70° / Right 60°  | Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch  |
| Track Width: 17.7" Rubber / 21.7" Steel   | Primary auxiliary continuous mode and one-way mode   |
| Two speed travel with automatic shift down  | Safety features include: large skylight with sun shade, travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding, valve with lift alarm, mirrors and lights |
| Reinforced arm w/ Integrated thumb mount  |  |
| Heavy duty dozer blade with float   |  |
| Automatic track tensioner   |  |
| Auto Idle   |  |
| TFM hardware standard equipment, service included through the standard warranty period (sn 185102670 ~) |  |

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code   | Description  | Suggested List Price |
|--|--|----------------------|
| TB290C   | TB290 Cab Equipped with Rubber or Steel Tracks   | \$113,815            |
| TB290CA<br>(w/ Angle Blade)                            | TB290 Cab (above Equipped) with <b>Angle Blade</b><br>Angle Blade features 25 degree left and right angle, cylinder protective guards  | \$119,995            |
| TB290CL<br>(w/ Segmented Rubber Tracks)                | TB290 Cab (above Equipped except with <b>Segmented Rubber Tracks</b> )   | \$119,779            |
| TB290CLA<br>(w/ Angle Blade & Segmented Rubber Tracks) | TB290 Cab (above Equipped except with <b>Segmented Rubber Tracks</b> ) with <b>Angle Blade</b> , Angle Blade features 25 degree left and right angle, cylinder protective guards | \$125,959            |

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

|           |  |         |
|-----------|--|---------|
| BTB07018  | 18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity                   | \$1,080 |
| BTB07024  | 24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity                   | \$1,155 |
| BTB07036  | 36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity                  | \$1,445 |
| BQC07000  | Quick Coupler  | \$1,030 |
| BQC07018  | 18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity            | \$1,080 |
| BQC07024  | 24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity            | \$1,155 |
| BQC07036  | 36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity           | \$1,445 |
| BQC07036D | 36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity                 | \$1,420 |
| ATH290I   | INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets) | \$2,790 |

### FIELD INSTALLED OPTIONS

|            |   |         |
|------------|---|---------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2"               | \$91    |
| ATH290K    | Hydraulic thumb (Only compatible with 18" and larger buckets) | \$2,435 |

### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard



# TB280FR

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel: 706-693-3600 Fax: 706-693-3725  
 www.takeuchi-us.com

## Zero Swing Excavator

### STANDARD EQUIPMENT

|   |   |
|---|---|
| Operating Weight: 18,810 lbs.   | ROPS/OPG enclosed cab w/ air conditioner/heat, windshield wiper, 12v power outlet and AM/FM/MP3 radio                   |
| Width: 7' 7"  | Tilt-up operator's platform   |
| Maximum Dig Depth: 14' 11"  | Color 5.7" gauge panel with multi-function operator information center  |
| Bucket Digging Force: 16,335 lbs.   | 10-way adjustable high back suspension seat   |
| Horsepower / RPM: 69.2 / 2,000  | Pilot operated joystick control with pattern change valve   |
| Travel Speed: 1.7 / 3.2 mph   | EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system  |
| Auxiliary Flow: 39 gpm  | Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door                                    |
| Second Aux Flow: 15 gpm   | Side by side radiator and hydraulic cooler  |
| Boom swing: Left 30°/ Right 15°   | Variable displacement axial piston main hydraulic pumps   |
| Track Width: 17.7"  | Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch |
| Side-to-Side (STS) offset boom system   | Primary auxiliary continuous mode and one-way mode  |
| Two speed travel with automatic shift down  | Safety features include: large skylight with sun shade,   |
| Reinforced arm w/ Integrated thumb mount  | travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding                                   |
| Heavy duty dozer blade with float   | valve with lift alarm, mirrors and lights   |
| Auto idle   |   |
| TFM hardware standard equipment, service included through the standard warranty period (sn 178500473 ~) |   |

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code                              | Description  | Suggested List Price |
|---|--|----------------------|
| TB280FRC                                  | TB280FR Cab Equipped with Rubber or Steel Tracks         | \$117,420            |
| TB280FRCL<br>(w/ Segmented Rubber Tracks) | TB280FR Cab Equipped with <b>Segmented Rubber Tracks</b> | \$123,384            |

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

|             |  |         |
|-------------|--|---------|
| BTB07018    | 18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity                   | \$1,080 |
| BTB07024    | 24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity                   | \$1,155 |
| BTB07036 *  | 36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity                  | \$1,445 |
| BQC07000    | Quick Coupler  | \$1,030 |
| BQC07018    | 18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity            | \$1,080 |
| BQC07024    | 24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity            | \$1,155 |
| BQC07036 *  | 36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity           | \$1,445 |
| BQC07036D * | 36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity                 | \$1,420 |
| ATH280FRI   | INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets) | \$2,790 |

### FIELD INSTALLED OPTIONS

|             |  |         |
|-------------|--|---------|
| 1914199948  | 3" Retractable seat belt in lieu of standard 2" belt           | \$91    |
| ATH280FRK * | Hydraulic thumb ( Only compatible with 18" and larger buckets) | \$2,435 |

\* **NOTE:** The Zero Swing front radius feature is only available for the standard bucket attachment (30" or smaller)

### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard



# TB2150

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

## Excavator

### STANDARD EQUIPMENT

|  |   |
|--|---|
| Operating Weight: 34,480 lbs. (Rubber) | ROPS/OPG Level 2 cab  |
| Dozer Blade Width: 8' 6"               | Factory installed cab with automatic climate control, AM/FM/MP3 radio, wiper            |
| Maximum Dig Depth: 18'                 | Two speed travel with automatic shift down  |
| Bucket Digging Force: 22,190 lbs.      | Travel alarm  |
| Tail Swing Radius: 6' 6.7"             | Arm & Boom holding valve with lift alarm  |
| Horsepower / RPM: 114 / 2,000          | Pattern change valve  |
| EPA Final Tier 4 Compliant             | Pilot operated joystick controls with safety lock out                                   |
| Travel Speed: 1.9 / 3.4 mph            | Wrap around counterweight with towers   |
| Auxiliary Flow: (Primary) 59.0 gpm     | Adjustable air suspension seat with retractable seat belt                               |
| Auxiliary Flow: (Secondary) 14.5 gpm   | Primary and Secondary two-way auxiliary hydraulic circuits routed to the end of the arm |
| Boom Swing: Left 77° / Right 53°       | Proportional thumb wheel control of both auxiliary hydraulic circuits                   |
| 24" Wide Steel Tracks                  | Electrohydraulic push button controls of auxiliary hydraulic circuit (Primary Only)     |
| Optional: 20" Rubber Track             | Variable displacement axial piston main hydraulic pumps                                 |
| Optional: 20" Segmented Rubber Tracks  | Multi function color monitor panel  |
|  | Heavy duty dozer blade with Float   |

TFM hardware standard equipment, service included through the standard warranty period

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code                             | Description   | Suggested List Price |
|--|---|----------------------|
| TB2150                                   | TB2150 Equipped with CAB OPG, Rubber or Steel Tracks, Dozer blade with float, Auto Air Conditioner/Heat, Defroster, Windshield wiper and washer, Control pattern selector valve, Travel alarm, Cab light, Auxiliary hydraulics (primary and secondary), Slide back front window, AM/FM/MP3 radio, Air Suspension seat, Engine monitoring system | \$170,000            |
| TB2150CL<br>(w/ Segmented Rubber Tracks) | TB2150 Cab (above Equipped except with <b>Segmented Rubber Tracks</b> )   | \$178,948            |

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

|            |  |         |
|------------|--|---------|
| BMC1140    | Mechanical Coupler: Pin Grabber type with Pins (700 lbs)   | \$5,130 |
| BTB114018  | 18" Pin-On Bucket (Capacity 0.41) (875 lbs)  | \$2,745 |
| BTB114024  | 24" Pin-On Bucket (Capacity 0.57) (1025 lbs)   | \$2,825 |
| BTB114030  | 30" Pin-On Bucket (Capacity 0.73) (1110 lbs)   | \$3,385 |
| BTB114036  | 36" Pin-On Bucket (Capacity 0.89) (1295 lbs)   | \$3,660 |
| BTB114042D | 42" Pin-On Ditching Bucket (Capacity 0.50) (695 lbs)   | \$2,708 |
| BTB114048D | 48" Pin-On Ditching Bucket (Capacity 0.60) (800 lbs)   | \$2,915 |
| BTB114054D | 54" Pin-On Ditching Bucket (Capacity 0.70) (900 lbs)   | \$3,130 |
| BTB114060D | 60" Pin-On Ditching Bucket (Capacity 0.80) (970 lbs)   | \$3,335 |
| BTH1140I   | INSTALLED Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs)         | \$7,655 |
| BTH1140LI  | INSTALLED Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler) | \$7,655 |

### FIELD INSTALLED OPTIONS

|               |  |         |
|---------------|--|---------|
| K1573400001   | 3" Retractable seat belt in lieu of standard 2"  | \$123   |
| BTH1140K      | Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs)         | \$7,305 |
| BTH1140LK     | Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler) | \$7,305 |
| TB1140BKTPINS | Bucket Pin Kit (includes Hardware)   | \$482   |

### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard



# TL6

## Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

### STANDARD EQUIPMENT

|   |   |
|---|---|
| Operating Weight: 7485 lbs.                         | Radial boom design  |
| Overall Width Without Bucket: 5' 0.2"               | ROPS/FOPS tilt-up operators compartment w/ rearview mirrors                 |
| Tipping Load (SAE 732) 5,269 lbs.                   | Back-up alarm, Top and rear windows   |
| Rated Operating Capacity (ROC)(SAE J818): 1,841 lbs | Automatic fuel bleed system   |
| Bucket Digging Force: 5,930 lbs.                    | Pilot operated joystick controls  |
| Horsepower / RPM: 65.2 / 2700                       | Universal quick attach mounting bracket                                     |
| Travel Speed: 4 / 6mph                              | Suspension seat with retractable seatbelt                                   |
| Auxiliary Flow: 17.8 gpm                            | One and two way auxiliary hydraulics  |
| Ground Pressure: 4.8 psi                            | Electronic engine monitoring system   |
| Maximum Lift Height to Bucket Pin: 9' 6.4"          | Electrohydraulic push button controls of auxiliary hydraulic circuit        |
| Reach Fully Raised: 1' 10"                          | Proportional slide switch control auxiliary hydraulics with detent function |
| Canopy/Cab height: 6' 5"                            | Hydraulic self-leveling bucket  |
|   | Flat face, pressure releasing Hydraulic Couplers                            |
|   | Standard 14-pin connector with push button control                          |
|   | Dual element air cleaner  |
|   | Push button boom float with detent  |
|   | Foot Throttle   |

EPA Final Tier 4 Turbocharged Engine with DPF

TFM hardware standard equipment, service included through the standard warranty period

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description   | Suggested List Price |
|--------------|---|----------------------|
| TL6R         | TL6 with ROPS/FOPS Canopy, Rubber tracks  | \$46,791             |
| TL6CR        | TL6 with ROPS/FOPS Cab with Air Conditioning/Heat Defroster, Rubber Tracks, Hydraulic quick attach, Swing out door, AM/FM/MP3 Radio | \$52,213             |

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

### ATTACHMENTS

|              |   |            |
|--------------|---|------------|
| ABLU-60S-047 | 60" HD smooth dirt bucket with bolt-on edge, 12.7 cubic feet capacity | \$1,611.00 |
| ABLU-60T-047 | 60" HD dirt bucket with 7 teeth, 12.7 cubic feet capacity             | \$1,579.00 |
| BTL867       | 67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity | \$1,646.93 |
| BTL867T      | 67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity             | \$1,536.79 |
| BPL1200      | 7' six way dozer blade  | \$6,634.93 |
| BTLPF48      | HD 48" pallet forks and frame   | \$1,243.07 |

### FIELD INSTALLED OPTIONS

|            |   |      |
|------------|---|------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2' | \$91 |
|------------|---|------|

### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard



# TL8

## Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

### STANDARD EQUIPMENT

|  |  |
|--|--|
| Operating Weight: 8,445 lbs.   | Radial boom design   |
| Overall Width Without Bucket:(12"/15" Tracks) 62"/ 65.4'   | ROPS/FOPS tilt-up operators compartment w/ RH/LH rearview mirrors          |
| Tipping Load (SAE 732) 6,020 lbs   | Back-up alarm, Top and rear windows  |
| Rated Operating Capacity (ROC)(SAE J818): 2,105 lbs  | Automatic fuel bleed system  |
| Bucket Digging Force: 6,856 lbs  | Pilot operated joystick controls   |
| Horsepower / RPM: 74.3 / 2,600   | Universal quick attach mounting bracke                                     |
| Travel Speed: 4.6 / 6.8 mph  | Six-way adjustable suspension seat with retractable seatbel                |
| Auxiliary Flow: 18.4 gpm   | One and two way auxiliary hydraulics                                       |
| Ground Pressure: 4.4 psi   | Electronic engine monitoring system  |
| Maximum Lift Height to Bucket Pin: 9' 11"  | Electrohydraulic push button controls of auxiliary hydraulic circui        |
| Reach Fully Raised: 2' 4.7"  | Proportional slide switch control auxiliary hydraulics with detent functio |
| Canopy/Cab height: 6' 11.9" / 7' 4"  | Hydraulic self-leveling bucket   |
|  | Flat face, pressure releasing Hydraulic Couplers                           |
|  | Standard 14-pin connector with push button contrc                          |
| EPA Final Tier 4 Turbocharged Engine with DPF  | Dual element air cleaner with standard pre-cleaner                         |
|  | Push button boom float with detent   |
| Active Power Control (sn 200802489 ~ )   | Foot Throttle  |
| TFM hardware standard equipment, service included through the standard warranty period (Canopy: sn 200803984~/Cab: sn 200803863- |  |

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code    | Description   | Suggested List Price |
|-----------------|---|----------------------|
| TL8RW           | TL8 with ROPS/FOPS Canopy, 15" Rubber tracks  | \$53,303             |
| TL8RWP (w/ PC)  | TL8RW (above Equipped) with <b>Pattern Control*</b>   | \$54,281             |
| TL8CRW          | TL8 with ROPS/FOPS Cab with Air Conditioning/Heat Defroster, 15" Rubber Tracks, Hydraulic quick attach Roll up door | \$59,483             |
| TL8CRWP (w/ PC) | TL8CRW (above Equipped) with <b>Pattern Control*</b>  | \$60,461             |
| <hr/>           |   |                      |
| TL8RN           | TL8 with ROPS/FOPS Canopy, 12" Rubber tracks  | \$52,816             |
| TL8RNP (w/ PC)  | TL8RN (above Equipped) with <b>Pattern Control*</b>   | \$53,795             |
| TL8CRN          | TL8 with ROPS/FOPS Cab with Air Conditioning/Heat Defroster, 12" Rubber Tracks, Hydraulic quick attach Roll up door | \$58,996             |
| TL8CRNP (w/ PC) | TL8CRN (above Equipped) with <b>Pattern Control*</b>  | \$59,975             |

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC requires a minimum of 90 days delivery time for factory order

### ATTACHMENTS

NOTE: 67" and 76" buckets work with both 12" / 15" Track's

|              |   |            |
|--------------|---|------------|
| BTL867       | 67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity | \$1,646.93 |
| BTL867T      | 67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity             | \$1,536.79 |
| ABLU-72S-057 | 72" Low Profile Bucket - Smooth with Bolt on Cutting Edge             | \$1,690.99 |
| ABLU-72T-057 | 72" Low Profile Bucket - Tooth  | \$1,597.63 |
| BTL1076      | 76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity | \$2,139.96 |
| BTL1076T     | 76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity             | \$1,987.86 |
| BPL1200      | 7' six way dozer blade  | \$6,634.93 |
| BTLPF48      | HD 48" pallet forks and frame   | \$1,243.07 |
| K288547011   | Radio kit installed (AM/FM/MP3)                                       | \$500.00   |
| K488342041   | 3-point 2" seat belt kit Installed (in lieu of standard 2")           | \$190.00   |

### FIELD INSTALLED OPTIONS

|            |   |         |
|------------|---|---------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2"                     | \$91    |
| K48834204  | 3-point 2" seat belt kit in lieu of standard 2"                     | \$150   |
| K28833001  | Counter Weight Kit TL8 (350 lbs)(Increase ROC to 2,323 lb           | \$900   |
| K488710000 | H pattern fixed control kit for TL8                                 | \$353   |
| K48837001  | TL8 hydraulic quick attach coupler kit (for Canopy unit             | \$1,560 |
| K28854701  | Radio kit (AM/FM/MP3)   | \$421   |
| 1903908050 | Active Power Control Kit (Field Kit)( for SN 200800001 ~ 200802488) | \$300   |

### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription' | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription' | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription' | \$500 |

\* Added to the first 2 years that come standarc



# TL8

## Track Loader

### HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

#### STANDARD EQUIPMENT

|   |   |
|---|---|
| Operating Weight: 8,631 lbs.                        | Radial boom design  |
| Overall Width Without Bucket (w/ 15" Tracks): 65.4" | Tilt-up operators compartment w/ RH/LH rearview mirrors                     |
| Tipping Load (SAE 732): 6,020 lbs.                  | Back-up alarm, Top and rear windows   |
| Rated Operating Capacity (ROC)(SAE J818): 2,105 lbs | Automatic fuel bleed system   |
| Bucket Digging Force: 6,856 lbs.                    | Pilot operated joystick controls  |
| Horsepower / RPM: 74.3 / 2,600                      | Universal quick attach mounting bracket                                     |
| Travel Speed: 4.6 / 6.8 mph                         | Six-way adjustable suspension seat with retractable seatbelt                |
| Auxiliary Flow: 18.4 gpm STD / 33 gpm HF            | One and two way auxiliary hydraulics  |
| Ground Pressure: 4.5 psi                            | Electronic engine monitoring system   |
| Maximum Lift Height to Bucket Pin: 9' 11"           | Electrohydraulic push button controls of auxiliary hydraulic circuit        |
| Reach Fully Raised: 2' 4.7"                         | Proportional slide switch control auxiliary hydraulics with detent function |
| Cab height: 7' 4"                                   | Hydraulic self-leveling bucket  |
| 1/2" Lexan roll up door                             | 1/2" Flat face, pressure relieving Hydraulic Couplers                       |
| EPA Final Tier 4 turbocharged engine with DPF       | Standard 14-pin connector with push button control                          |
| ROPS/FOPS Level 2 on High Flow                      | Dual element air cleaner with standard pre-cleaner                          |
|   | Push button boom float with detent  |
|   | Foot throttle   |

TFM hardware standard equipment, service included through the standard warranty period (Cab: sn 200803863~)

#### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code     | Description   | Suggested List Price |
|------------------|---|----------------------|
| TL8CRWH          | TL8 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 15" Rubber Tracks, Hydraulic quick attach, Lexan Roll up door and HIGH FLOW auxiliary hydraulics (33 gpm) | \$62,315             |
| TL8CRWHP (w/ PC) | TL8CRW (above Equipped) with <b>Pattern Control*</b>  | \$63,294             |

#### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC requires a minimum of 90 days delivery time for factory order

#### ATTACHMENTS

|              |   |            |
|--------------|---|------------|
| BTL867       | 67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity | \$1,646.93 |
| BTL867T      | 67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity             | \$1,536.79 |
| ABLU-72S-057 | 72" Low Profile Bucket - Smooth with Bolt on Cutting Edge             | \$1,690.99 |
| ABLU-72T-057 | 72" Low Profile Bucket -Tooth   | \$1,597.63 |
| BTL1076      | 76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity | \$2,139.96 |
| BTL1076T     | 76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity             | \$1,987.86 |
| BPL1200      | 7' six way dozer blade  | \$6,634.93 |
| BTLPF48      | HD 48" pallet forks and frame   | \$1,243.07 |
| K288547011   | Radio kit installed (AM/FM/MP3)                                       | \$500.00   |
| K488342041   | 3-point 2" seat belt kit Installed (in lieu of standard 2")           | \$190.00   |

#### FIELD INSTALLED OPTIONS

|            |  |       |
|------------|--|-------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2"            | \$91  |
| K48834204  | 3-point 2" seat belt kit in lieu of standard 2"            | \$150 |
| K28833001  | Counter Weight Kit TL8 (350 lbs)(Increase ROC to 2,323 lb) | \$900 |
| K488710000 | H pattern fixed control kit for TL8                        | \$353 |
| K28854701  | Radio kit (AM/FM/MP3)                                      | \$421 |
| 1903908050 | Active Power Control Kit (Field Kit)                       | \$300 |

#### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard

Prices are F.O.B. Pendergrass, GA  
Effective 1 January 2019

Prices and specifications  
subject to change without notice

P-12-B  
Prices are in US Dollar



# TL10V2

## Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

### STANDARD EQUIPMENT

|   |  |
|---|--|
| Operating Weight: 9,950 lbs.                        | Vertical boom design   |
| Overall Width Without Bucket: 5' 8.5"               | Tilt-up operators compartment  |
| Tipping Load (SAE 732) 7,205 lbs.                   | Electronic dial type throttle and foot throttle                            |
| Rated Operating Capacity (ROC)(SAE J818): 2,522 lbs | Back-up alarm  |
| Bucket Digging Force: 6,520 lbs.                    | Top and rear windows   |
| Horsepower / RPM: 74.3 / 2,600                      | Automatic fuel bleed system  |
| Travel Speed: 4.8 / 7.0                             | Pilot operated joystick controls   |
| Auxiliary Flow: 18.8 gpm                            | Universal quick attach mounting bracket                                    |
| Ground Pressure: 4.9 PSI                            | Deluxe high back suspension seat with retractable seatbelt                 |
| Maximum Lift Height to Bucket Pin: 10' 4.8"         | One and two way auxiliary hydraulics                                       |
| Reach Fully Raised: 3' 1.4"                         | Electronic engine monitoring system  |
| Canopy/Cab height: 7' 5.4"                          | Electrohydraulic push button controls of auxiliary hydraulic circuit       |
| Selectable working modes                            | Proportional thumb wheel control auxiliary hydraulics with detent function |
| Front & rear LED working lights                     | Hydraulic self-leveling bucket   |
| ROPS/FOPS Level 1 operator protection               | Flat face, pressure relieving Hydraulic Couplers                           |
| Multi function color monitor                        | Standard 14-pin connector with push button control                         |
| Active power control power management system        | Dual element air cleaner   |
|   | Push button boom float with detent   |

TFM hardware standard equipment, service included through the standard warranty period

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code             | Description   | Suggested List Price |
|--------------------------|---|----------------------|
| TL10V2--R                | TL10 with ROPS/FOPS Canopy, 15.7" Rubber tracks   | \$65,100             |
| TL10V2-RR (w/ RC)        | TL10R (above Equipped) with <b>Ride Control*</b>  | \$65,800             |
| TL10V2-RP (w/ PC)        | TL10R (above Equipped) with <b>Pattern Control*</b>   | \$66,050             |
| TL10V2-RRP (w/ RC & PC)  | TL10R (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>  | \$66,750             |
| TL10V2-CR                | TL10 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster<br>15.7" Rubber Tracks, Hydraulic quick attach, Roll up door, AM/FM/MP3 Radio | \$71,500             |
| TL10V2-CRR (w/ RC)       | TL10CR (above Equipped) with <b>Ride Control*</b>   | \$72,200             |
| TL10V2-CRP (w/ PC)       | TL10CR (above Equipped) with <b>Pattern Control*</b>  | \$72,450             |
| TL10V2-CRRP (w/ RC & PC) | TL10CR (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>   | \$73,150             |

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

### ATTACHMENTS / OPTIONS

|          |   |            |
|----------|---|------------|
| BTL1076  | 76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity | \$2,139.96 |
| BTL1076T | 76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity             | \$1,987.86 |
| BPL1200  | 7' six way dozer blade  | \$6,634.93 |
| BTLPF48  | HD 48" pallet forks and frame   | \$1,243.07 |

### FIELD INSTALLED OPTIONS

|             |  |         |
|-------------|--|---------|
| 19141-99948 | 3" retractable seat belt in lieu of standard 2"      | \$91    |
| K48847001   | Hydraulic quick attach coupler kit (for Canopy unit) | \$1,980 |

### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard





# TL10V2

## Track Loader

### HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

#### STANDARD EQUIPMENT

|   |  |
|---|--|
| Operating Weight: 10,270 lbs.                       | Vertical boom design   |
| Overall Width Without Bucket: 5' 8.5"               | Tilt-up operators compartment  |
| Tipping Load (SAE 732) 7,205 lbs.                   | Electronic dial type throttle and foot throttle                            |
| Rated Operating Capacity (ROC)(SAE J818): 2,522 lbs | Back-up alarm  |
| Bucket Digging Force: 6,520 lbs.                    | Top and rear windows   |
| Horsepower / RPM: 74.3 / 2,600                      | Automatic fuel bleed system  |
| Travel Speed: 4.8 / 7.0                             | Pilot operated joystick controls   |
| Auxiliary Flow (SP1): 18.8 gpm STD / 32.8 gpm HF    | Universal quick attach mounting bracket                                    |
| Ground Pressure: 5.1 PSI                            | Deluxe high back suspension seat with retractable seatbelt                 |
| Maximum Lift Height to Bucket Pin: 10' 4.8"         | One and two way auxiliary hydraulics                                       |
| Reach Fully Raised: 3' 1.4"                         | Electronic engine monitoring system  |
| Cab height: 7' 6.9"                                 | Electrohydraulic push button controls of auxiliary hydraulic circuit       |
| Front & rear LED working lights                     | Proportional thumb wheel control auxiliary hydraulics with detent function |
| ROPS / FOPS Level 2 operator protection             | Hydraulic self-leveling bucket   |
| Multi function color monitor                        | Flat face, pressure relieving Hydraulic Couplers                           |
|   | Standard 14-pin connector with push button control                         |
|   | Dual element air cleaner   |
|   | Push button boom float with detent   |

TFM hardware standard equipment, service included through the standard warranty period

#### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code              | Description  | Suggested List Price |
|---------------------------|--|----------------------|
| TL10V2-CRH                | TL10 with Cab with Air Conditioning/Heat, Defroster, 15.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door, AM/FM/MP3 Radio, HIGH FLOW Auxiliary Hydraulics w/ second auxiliary line | \$74,550             |
| TL10V2-CRHR (w/ RC)       | TL10CRH (above Equipped) with <b>Ride Control*</b>   | \$75,250             |
| TL10V2-CRHP (w/ PC)       | TL10CRH (above Equipped) with <b>Pattern Control*</b>  | \$75,500             |
| TL10V2-CRHRP (w/ RC & PC) | TL10CRH (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>   | \$76,200             |

#### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

#### ATTACHMENTS / OPTIONS

|            |   |            |
|------------|---|------------|
| BTL1076    | 76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity | \$2,139.96 |
| BTL1076T   | 76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity             | \$1,987.86 |
| BPL1200    | 7' six way dozer blade  | \$6,634.93 |
| BTLPF48    | HD 48" pallet forks and frame   | \$1,243.07 |
| K288542041 | 3-point 2" seat belt kit Installed (in lieu of standard 2")           | \$190      |

#### FIELD INSTALLED OPTIONS

|             |   |      |
|-------------|---|------|
| 19141-99948 | 3" retractable seat belt in lieu of standard 2" | \$91 |
|-------------|---|------|

#### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard



# TL12R2

## Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

### STANDARD EQUIPMENT

|   |  |
|---|--|
| Operating Weight: 12,300 lbs.                       | Radial boom design   |
| Overall Width Without Bucket: 6' 5.2"               | Tilt-up operators compartment  |
| Tipping Load (SAE 732) 8,629 lbs.                   | Electronic dial type throttle and foot throttle                            |
| Rated Operating Capacity (ROC)(SAE J818): 2,975 lbs | Back-up alarm  |
| Bucket Digging Force: 8,210 lbs.                    | Top and rear windows   |
| Horsepower / RPM: 111.3 / 2,400                     | Automatic fuel bleed system  |
| Travel Speed: 5.0 / 7.8 mph                         | Pilot operated joystick controls   |
| Auxiliary Flow: 23.2 gpm                            | Universal quick attach mounting bracket                                    |
| Ground Pressure: 4.58 psi                           | Deluxe high back suspension seat with retractable seatbelt                 |
| Maximum Lift Height to Bucket Pin: 10' 6"           | One and two way auxiliary hydraulics                                       |
| Reach Fully Raised: 3' 1.8"                         | Electronic engine monitoring system  |
| Canopy/Cab height: 7' 7"                            | Electrohydraulic push button controls of auxiliary hydraulic circuit       |
| Active power control power management system        | Proportional thumb wheel control auxiliary hydraulics with detent function |
| Front & rear LED working lights                     | Hydraulic self-leveling bucket   |
| ROPS/FOPS Level 1 operator protection               | Flat face, pressure relieving Hydraulic Couplers                           |
| Multi function color monitor                        | Standard 14-pin connector with push button control                         |
| Selectable working modes                            | Dual element air cleaner   |
|   | Push button boom float with detent   |

TFM hardware standard equipment, service included through the standard warranty period

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code            | Description   | Suggested List Price |
|-------------------------|---|----------------------|
| TL12R2-R                | TL12 with Canopy, 17.7" Rubber tracks                       | \$80,500             |
| TL12R2-RR (w/ RC)       | TL12R (above Equipped) with Ride Control*                   | \$81,200             |
| TL12R2-RP (w/ PC)       | TL12R (above Equipped) with Pattern Control*                | \$81,450             |
| TL12R2-RRP (w/ RC & PC) | TL12R (above Equipped) with Ride Control & Pattern Control* | \$82,150             |

|                          |   |          |
|--------------------------|---|----------|
| TL12R2-CR                | TL12 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door, AM/FM/MP3 Radio | \$87,050 |
| TL12R2-CRR (w/ RC)       | TL12CR (above Equipped) with Ride Control*  | \$87,750 |
| TL12R2-CRP (w/ PC)       | TL12CR (above Equipped) with Pattern Control*   | \$88,000 |
| TL12R2-CRRP (w/ RC & PC) | TL12CR (above Equipped) with Ride Control & Pattern Control*  | \$88,700 |

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

### ATTACHMENTS / OPTIONS

|              |   |            |
|--------------|---|------------|
| BTL1280      | 80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity                 | \$2,381.23 |
| BTL1280T     | 80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity                              | \$2,197.66 |
| ABLU-84S-100 | 84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity | \$2,695.93 |
| ABLU-84T-100 | 84" High Capacity - HD Dirt Bucket - Tooth  | \$2,593.13 |
| BPL12008     | 8' six way dozer blade  | \$6,818.50 |
| BTLPF48      | HD 48" pallet forks and frame   | \$1,243.07 |

### FIELD INSTALLED OPTIONS

|             |  |         |
|-------------|--|---------|
| 19141-99948 | 3" retractable seat belt in lieu of standard 2"      | \$91    |
| 1914100145  | 3-point 2" seat belt kit in lieu of standard 2"      | \$260   |
| K48867001   | Hydraulic quick attach coupler kit (for Canopy unit) | \$1,980 |

### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard



# TL12R2

Track Loader

HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel: 706-693-3600 Fax: 706-693-3725

www.takeuchi-us.com

## STANDARD EQUIPMENT

|  |  |
|--|--|
| Operating Weight: 12,590 lbs.  | Radial boom design   |
| Overall Width Without Bucket: 6' 5.2"  | Tilt-up operators compartment  |
| Tipping Load (SAE 732) 8,629 lbs.  | Electronic dial type throttle and foot throttle                            |
| Rated Operating Capacity (ROC)(SAE J818): 2,975 lbs                                    | Back-up alarm  |
| Bucket Digging Force: 8,210 lbs.   | Top and rear windows   |
| Horsepower / RPM: 111.3 / 2,400  | Automatic fuel bleed system  |
| Travel Speed: 5.0 / 7.8 mph  | Pilot operated joystick controls   |
| Auxiliary Flow (SP1): 23.2 gpm STD / 40.4 gpm HF                                       | Universal quick attach mounting bracket                                    |
| Auxiliary Flow (SP2): 23.2 gpm   | Deluxe high back suspension seat with retractable seatbelt                 |
| Ground Pressure: 4.68 psi  | One and two way auxiliary hydraulics                                       |
| Maximum Lift Height to Bucket Pin: 10' 6"  | Electronic engine monitoring system  |
| Reach Fully Raised: 3' 1.8"  | Electrohydraulic push button controls of auxiliary hydraulic circuit       |
| Cab height: 7' 9.7"  | Proportional thumb wheel control auxiliary hydraulics with detent function |
| Active power control power management system   | Hydraulic self-leveling bucket   |
| Front & rear LED working lights  | Flat face, pressure relieving Hydraulic Couplers                           |
| ROPS / FOPS Level 2 operator protection  | Standard 14-pin connector with push button control                         |
| Multi function color monitor   | Dual element air cleaner   |
| Selectable working modes   | Push button boom float with detent   |
| TFM hardware standard equipment, service included through the standard warranty period |  |

## BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code              | Description  | Suggested List Price |
|---------------------------|--|----------------------|
| TL12R2-CRH                | TL12 with Cab with Air Conditioning/Heat, Defroster, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door, AM/FM/MP3 Radio, HIGH FLOW Auxiliary Hydraulics w/ second auxiliary line | \$90,050             |
| TL12R2-CRHR (w/ RC)       | TL12CRH (above Equipped) with <b>Ride Control*</b>   | \$90,750             |
| TL12R2-CRHP (w/ PC)       | TL12CRH (above Equipped) with <b>Pattern Control*</b>  | \$91,000             |
| TL12R2-CRHRP (w/ RC & PC) | TL12CRH (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>   | \$91,700             |

## BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

## ATTACHMENTS / OPTIONS

|              |   |            |
|--------------|---|------------|
| BTL1280      | 80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity                 | \$2,381.23 |
| BTL1280T     | 80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity                              | \$2,197.66 |
| ABLU-84S-100 | 84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity | \$2,695.93 |
| ABLU-84T-100 | 84" High Capacity - HD Dirt Bucket - Tooth  | \$2,593.13 |
| BPL12008     | 8' six way dozer blade  | \$6,818.50 |
| BTLPF48      | HD 48" pallet forks and frame   | \$1,243.07 |

## FIELD INSTALLED OPTIONS

|            |   |       |
|------------|---|-------|
| 1914199948 | 3" retractable seat belt in lieu of standard 2" | \$91  |
| 1914100145 | 3-point 2" seat belt kit in lieu of standard 2" | \$260 |

## TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard



# TL12V2

## Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

### STANDARD EQUIPMENT

|  |   |
|--|---|
| Operating Weight (Canopy/Cab): 12,860 lb / 13,190 lb | Vertical boom design  |
| Overall Width Without Bucket: 6' 5.2"                | Tilt-up operators compartment   |
| Tipping Load (SAE 732) 11,737 lbs.                   | Electronic dial type throttle and foot throttle                             |
| Rated Operating Capacity (ROC)(SAE J818): 4,107 lbs  | Back-up alarm   |
| Bucket Digging Force: 7,874 lbs.                     | Top and rear window   |
| Horsepower / RPM: 111.3 / 2,400                      | Automatic fuel bleed system   |
| Travel Speed: 5.0 / 7.8 mph                          | Pilot operated joystick controls  |
| Auxiliary Flow: 23.2 gpm                             | Universal quick attach mounting bracket                                     |
| Ground Pressure (Canopy / Cab): 4.8 psi / 4.9 psi    | Deluxe high back suspension seat with retractable seatbelt                  |
| Maximum Lift Height to Bucket Pin: 10' 10"           | One and two way auxiliary hydraulics  |
| Reach Fully Raised: 3' 0.4"                          | Electronic engine monitoring system   |
| Canopy/Cab height: 7' 7.7"                           | Electrohydraulic push button controls of auxiliary hydraulic circuit        |
| ROPS/FOPS Level 1 operators protection               | Proportional slide switch control auxiliary hydraulics with detent function |
| Front & rear LED working lights                      | Hydraulic self-leveling bucket  |
| Selectable working modes                             | Flat face, pressure relieving hydraulic couplers                            |
| Active power control power management system         | Standard 14-pin connector with push button control                          |
| Multi function color monitor                         | Dual element air cleaner  |
|  | Push button boom float with detent  |

TFM hardware standard equipment, service included through the standard warranty period

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code            | Description  | Suggested List Price |
|-------------------------|--|----------------------|
| TL12V2-R                | TL12V with Canopy, 17.7" Rubber tracks                       | \$83,500             |
| TL12V2-RR (w/ RC)       | TL12VR (above Equipped) with Ride Control*                   | \$84,200             |
| TL12V2-RP (w/ PC)       | TL12VR (above Equipped) with Pattern Control*                | \$84,450             |
| TL12V2-RRP (w/ RC & PC) | TL12VR (above Equipped) with Ride Control & Pattern Control* | \$85,150             |

|                          |  |          |
|--------------------------|--|----------|
| TL12V2-CR                | TL12V with ROPS/FOPS Cab, Air Conditioning/Heat, Defroster, AM/FM/MP3 Radio, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door | \$90,050 |
| TL12V2-CRR (w/ RC)       | TL12VCR (above Equipped) with Ride Control*  | \$90,750 |
| TL12V2-CRP (w/ PC)       | TL12VCR (above Equipped) with Pattern Control*   | \$91,000 |
| TL12V2-CRRP (w/ RC & PC) | TL12VCR (above Equipped) with Ride Control & Pattern Control*  | \$91,700 |

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

### ATTACHMENTS / OPTIONS

|              |   |            |
|--------------|---|------------|
| BTL1280      | 80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity                 | \$2,381.23 |
| BTL1280T     | 80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity                              | \$2,197.66 |
| ABLU-84S-100 | 84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity | \$2,695.93 |
| ABLU-84T-100 | 84" High Capacity - HD Dirt Bucket - Tooth - 27 cu.ft. capacity                   | \$2,593.13 |
| BPL12008     | 8' six way dozer blade  | \$6,818.50 |
| BTLPF48      | HD 48" pallet forks and frame   | \$1,243.07 |

### FIELD INSTALLED OPTIONS

|            |  |         |
|------------|--|---------|
| 1914199948 | 3" retractable seat belt in lieu of standard 2"      | \$91    |
| 1914100145 | 3-point 2" seat belt kit in lieu of standard 2"      | \$260   |
| K48857001  | Hydraulic quick attach coupler kit (for Canopy unit) | \$1,980 |

### TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard



# TL12V2

Track Loader

HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel: 706-693-3600 Fax: 706-693-3725

www.takeuchi-us.com

## STANDARD EQUIPMENT

|   |   |
|---|---|
| Operating Weight: 13,190 lbs.                         | Vertical boom design  |
| Overall Width Without Bucket: 6' 5.2"                 | ROPS/FOPS tilt-up operators compartment                                     |
| Tipping Load (SAE 732) 11,737 lbs.                    | Electronic dial type throttle and foot throttle                             |
| Rated Operating Capacity (ROC)(SAE J818): 4,107 lbs   | Back-up alarm   |
| Bucket Digging Force: 7,874 lbs.                      | Top and rear window   |
| Horsepower / RPM: 111.3 / 2,400                       | Automatic fuel bleed system   |
| Travel Speed: 5.0 / 7.8 mph                           | Pilot operated joystick controls  |
| Auxiliary Flow (Std / High Flow): 23.2 gpm / 40.4 gpm | Universal quick attach mounting bracket                                     |
| Ground Pressure: 4.9 psi                              | Deluxe high back suspension seat with retractable seatbelt                  |
| Maximum Lift Height to Bucket Pin: 10' 10"            | One and two way auxiliary hydraulics  |
| Reach Fully Raised: 3' 0.4"                           | Electronic engine monitoring system   |
| Cab height: 7' 9.7"                                   | Electrohydraulic push button controls of auxiliary hydraulic circuit        |
| ROPS/FOPS Level 2 operators protection                | Proportional slide switch control auxiliary hydraulics with detent function |
| Front & rear LED working lights                       | Hydraulic self-leveling bucket  |
| Selectable working modes                              | Flat face, pressure relieving hydraulic couplers                            |
| Active power control power management system          | Standard 14-pin connector with push button control                          |
| Multi function color monitor                          | Dual element air cleaner  |
|   | Push button boom float with detent  |

TFM hardware standard equipment, service included through the standard warranty period

## BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code              | Description  | Suggested List Price |
|---------------------------|--|----------------------|
| TL12V2-CRH                | TL12 with Cab with Air Conditioning/Heat, Defroster, AM/FM/MP3 Radio, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door<br>HIGH FLOW Auxiliary Hydraulics w/ second auxiliary line | \$93,050             |
| TL12V2-CRHR (w/ RC)       | TL12VCRH (above Equipped) with <b>Ride Control*</b>  | \$93,750             |
| TL12V2-CRHP (w/ PC)       | TL12VCRH (above Equipped) with <b>Pattern Control*</b>   | \$94,000             |
| TL12V2-CRHRP (w/ RC & PC) | TL12VCRH (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>  | \$94,700             |

## BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

## ATTACHMENTS / OPTIONS

|              |  |            |
|--------------|--|------------|
| BTL1280      | 80" HD smooth dirt bucket with bolt-on edge, 24.0 cu. ft. capacity                 | \$2,381.23 |
| BTL1280T     | 80" HD dirt bucket with 9 teeth 24.0 cu. ft. capacity                              | \$2,197.66 |
| ABLU-84S-100 | 84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu. ft. capacity | \$2,695.93 |
| ABLU-84T-100 | 84" High Capacity - HD Dirt Bucket - Tooth - 27 cu. ft. capacity                   | \$2,593.13 |
| BPL12008     | 8' six way dozer blade   | \$6,818.50 |
| BTLPF48      | HD 48" pallet forks and frame  | \$1,243.07 |

## FIELD INSTALLED OPTIONS

|            |   |       |
|------------|---|-------|
| 1914199948 | 3" retractable seat belt in lieu of standard 2" | \$91  |
| 1914100145 | 3-point 2" seat belt kit in lieu of standard 2" | \$260 |

## TAKEUCHI FLEET MANAGEMENT

|         |  |       |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

\* Added to the first 2 years that come standard



# TW40

## Wheel Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

### STANDARD EQUIPMENT

|   |  |
|---|--|
| Operating Weight: 7,275 lbs               | Back-Up Alarm  |
| Tip Load, Straight: 3,858 lbs             | Front Working Lights   |
| Bucket breakout force: 4,878 lbs          | Rear Working Lights  |
| Lift Arm Breakout Force: 4,181 lb         | Inching Pedal  |
| HP / RPM: 39.4 hp / 2,800 rpm             | Front Limited Slip Axle 45%                                    |
| Travel Speed (Max): 12.4 gpm              | Auxiliary Hydraulic Lines                                      |
| Auxiliary Flow: 10.3 gpm                  | Replaceable Bushings   |
| Maximum Height to Bucket pin: 9' 6.5"     | Bucket Float   |
| Height: (Canopy) 7' 10.5" / (Cab) 7' 6.1" | Automatic Bucket Positioning                                   |
| Articulation: 40 /40                      | Heavy Duty Hydraulic SSL Style Quick Attach Coupler            |
| Reach fully raised: 2' 8.2"               | Center Pivot Steering  |
|   | Heavy Duty 31x15.5-15 Construction Tire Assembly               |
|   | Optional heated Cab features front/rear wiper and rear defrost |

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description                                  | Suggested List Price |
|--------------|--|----------------------|
| TW40         | TW40 with Foldable ROPS/FOPS Guard and Tires | \$55,105             |
| TW40C        | TW40 with Cab with Heat and Tires            | \$59,740             |

### BASE MACHINE PRICE DOES NOT INCLUDE ATTACHMENTS

### ATTACHMENTS

|           |   |            |
|-----------|---|------------|
| BTW4060   | 60" General Purpose Bucket (0.66 cu. Yd) for TW40 with SSL Mount    | \$2,412.70 |
| BTW4060A  | 60" Bolt on Blade for BTW4060                                       | \$295.82   |
| BTW4060B  | 60" Tooth Bar for BTW4060 (note: not compatible with bolt on blade) | \$643.00   |
| BTW60-2PF | 48" Fork Assy for TW60-2 (Rated 6,000 lbs) (SSL Hookup)             | \$2,659.72 |

### FIELD INSTALLED OPTIONS

|             |                       |       |
|-------------|-----------------------|-------|
| TWFASTERKIT | TW Series Coupler Kit | \$132 |
|-------------|-----------------------|-------|



# TW60

## Wheel Loader

### SERIES 2

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

#### STANDARD EQUIPMENT

|  |  |
|--|--|
| Operating Weight: 10,692 lbs           | ROPS / FOPS Level 1 Cab  |
| Tip Load, Straight: 6,724 lbs          | Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost   |
| Bucket Breakout Force: 5,822 lbs       | LCD Gauge panel with multi-function operator information center  |
| Lift Arm Breakout Force: 6,675 lb      | Suspension Seat  |
| HP / RPM: 61 / 2300                    | Single control handle for direction (F/R) and loader functions   |
| Travel Speed (Max): 12.4 mph           | EPA Final Tier 4 Yanmar turbocharged, intercooled engine 4TNV86CHT-M   |
| Auxiliary Flow: 15.8 gpm               | 100% Front and rear differential lock  |
| Maximum Height to Bucket Pin: 10" 3.2" | Universal skid steer hydraulic coupler   |
| Height: 8' 1.4'                        | Bucket float   |
| Articulation: 40 / 40                  | Bucket level indicator   |
| Reach Fully Raised: 26.4"              | Mechanical bucket positioning  |
|  | Safety features include: back up alarm, lights, retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights), front driving lights, front and rear hazard and directional indicators |

#### ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

#### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description   | Suggested List Price |
|--------------|---|----------------------|
| TW60C2       | TW60-2 Cab  | \$79,032             |
| TW60C2HS     | TW60 Cab with High Speed Road Gear (24.8 mph max speed) | \$80,192             |

#### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES

#### TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

|             |   |            |
|-------------|---|------------|
| BTW65TIREHD | Heavy Duty Construction Tire Assy for TW602 / TW65 / TW80 (4 x Tire Assy) | \$3,395.00 |
|-------------|---|------------|

#### ATTACHMENTS

|            |  |            |
|------------|--|------------|
| BTW60-272  | Bucket (72" General Purpose) (1.11 cu. Yd) (SSL Hookup) for TW60-2 | \$2,750.00 |
| BTW60-272A | Blade, bolt-on (72") (For BTW60/271)                               | \$584.00   |
| BTW60-2PF  | 48" Fork Assy for TW60-2 (Rated 6,000 lbs) (SSL Hookup)            | \$2,659.72 |

#### FIELD INSTALLED OPTIONS

|            |   |         |
|------------|---|---------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2" | \$91.00 |
|------------|---|---------|



# TW65

## Wheel Loader

### SERIES 2

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

#### STANDARD EQUIPMENT

|  |  |
|--|--|
| Operating Weight: 11,354 lbs           | Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost   |
| Tip Load, Straight: 9,171 lbs          | LCD Gauge panel with multi-function operator information center with diagnostics and anti-theft capabilities   |
| Bucket Breakout Force: 11,600 lbs      | Deluxe suspension seat   |
| Lift Arm Breakout Force: 10,319 lb     | Pilot operator loader joystick control   |
| HP / RPM: 73 / 2200                    | EPA Final Tier 4 turbocharged engine with DOC and engine monitoring system   |
| Travel Speed (Max): 12.4 mph           | Side by side radiator and hydraulic oil cooler   |
| Auxiliary Flow: 16.4 gpm               | Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick   |
| Maximum Height to Bucket Pin: 10" 4.6" | 100% Front and rear differential lock  |
| Height: 8' 10"                         | Euro style attachment mount with hydraulic coupler   |
| Articulation: 40 / 40                  | Bucket float   |
| Reach Fully Raised: 24"                | Mechanical bucket positioning  |
| ROPS / FOPS Cab                        | Safety features include: back up alarm, lights, retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights), front driving lights, front and rear hazard and directional indicators |

#### ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

#### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|--------------|-------------|----------------------|
| TW65C2       | TW65 Cab    | \$83,420             |

#### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES

#### TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

|             |   |         |
|-------------|---|---------|
| BTW65TIREHD | Heavy Duty Construction Tire Assy for TW65 / TW80 (4 x Tire Assy) | \$3,395 |
|-------------|---|---------|

#### ATTACHMENTS

|           |   |            |
|-----------|---|------------|
| BTW5077   | 77" Construction Combo Bucket (1.05 cu. Yd) for TW65/TW80 | \$2,310    |
| BTW5077A  | 77" Bolt on Blade for BTW5077                             | \$360      |
| BTW8082   | 81.5" General Purpose Bucket (1.3 cu. Yd) for TW80        | \$2,520    |
| BTW8082A  | 82" Bolt-on Blade for BTW8082                             | \$370      |
| BTWPF48   | 48" Combo Fork Assy for all TW's (Rated 8000 lb)          | \$2,300    |
| BTWUNIADP | Combo Hitch to Universal SSL Adapter TW50/60/65/80        | \$2,307.80 |

#### FIELD INSTALLED OPTIONS

|              |   |       |
|--------------|---|-------|
| 1914199948   | 3" Retractable seat belt in lieu of standard 2" | \$91  |
| TWFASTERKIT  | TW Series Coupler Kit (Non Hig                  | \$132 |
| TWCOUPLERKIT | TW Series Coupler Kit for HIGH FLOW UNITS ONLY  | \$224 |





# TW80

Wheel Loader

SERIES 2

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

#### STANDARD EQUIPMENT

|                                      |  |
|--------------------------------------|--|
| Operating Weight: 12,700 lbs         | Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost   |
| Tip Load, Straight: 10,065 lbs       | LCD Gauge panel with multi-function operator information center with diagnostics and anti-theft capabilities   |
| Bucket Breakout Force: 13,690 lbs    | Deluxe suspension seat   |
| Lift Arm Breakout Force: 11,802 lb   | Pilot operator loader joystick control   |
| HP / RPM: 73 / 2200                  | EPA Final Tier 4 turbocharged engine with DOC and engine monitoring system   |
| Travel Speed (Max): 12.4 mph         | Side by side radiator and hydraulic oil cooler   |
| Auxiliary Flow: 16.4 gpm             | Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick   |
| Maximum Height to Bucket Pin: 11' 1" | 100% Front and rear differential lock  |
| Height: 8' 11.5"                     | Euro style attachment mount with hydraulic coupler   |
| Articulation: 40 / 40                | Bucket float   |
| Reach Fully Raised: 29"              | Mechanical bucket positioning  |
| ROPS / FOPS Cab                      | Safety features include: back up alarm, lights, retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights), front driving lights, front and rear hazard and directional indicators |

#### ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

#### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description  | Suggested List Price |
|--------------|--|----------------------|
| TW80C2       | TW80 Cab   | \$92,690             |
| TW80C2HS     | TW80 Cab, High Speed Road Gear (24.8 mph max speed), & Ride Control  | \$97,016             |
| TW80C2HH     | TW80 Cab, High Flow Auxiliary Hydraulics (26 gpm), High Speed Road Gear (24.8 mph max speed), & Ride Control | \$101,867            |

**BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES**

#### TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

|             |   |         |
|-------------|---|---------|
| BTW65TIREHD | Heavy Duty Construction Tire Assy for TW65 / TW80 (4 x Tire Assy) | \$3,395 |
|-------------|---|---------|

#### ATTACHMENTS

|           |  |            |
|-----------|--|------------|
| BTW8082   | 81.5" General Purpose Bucket (1.3 cu. Yd) for TW80 | \$2,520    |
| BTW8082A  | 82" Bolt-on Blade for BTW8082                      | \$370      |
| BTWPF48   | 48" Combo Fork Assy for all TW's (Rated 8000 lb)   | \$2,300    |
| BTWUNIADP | Combo Hitch to Universal SSL Adapter TW50/60/65/80 | \$2,307.80 |

#### FIELD INSTALLED OPTIONS

|              |   |       |
|--------------|---|-------|
| 1914199948   | 3" Retractable seat belt in lieu of standard 2" | \$91  |
| TWFASTERKIT  | TW Series Coupler Kit                           | \$132 |
| TWCOUPLERKIT | TW Series Coupler Kit for HIGH FLOW UNITS ONLY  | \$224 |



# TW95

## Wheel Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

### STANDARD EQUIPMENT

|   |  |
|---|--|
| Operating Weight: 17,417 lbs            | Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost   |
| Tip Load, Straight: 14,388 lbs          | LCD Gauge panel with multi-function operator information center with diagnostics and anti-theft capabilities   |
| Bucket Breakout Force: 16,186 lbs       | Deluxe suspension seat   |
| Lift Arm Breakout Force: 18,434 lbs     | Pilot operator loader joystick control   |
| HP / RPM: 114 / 2200                    | EPA Final Tier 4 turbocharged engine with DOC/SCR exhaust after treatment system   |
| Travel Speed (Max): 24.8 mph            | Side by side radiator and hydraulic oil cooler   |
| Auxiliary Flow: 26.4 gpm                | Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick   |
| Maximum Height to Bucket Pin: 11' 10.9" | 100% Front and rear differential lock  |
| Height: 9' 7.4"                         | Euro style attachment mount with hydraulic coupler   |
| Articulation: 40 /40                    | Bucket float   |
| Reach Fully Raised: 32.3"               | Return to dig  |
| ROPS / FOPS Level 2 Cab                 | Safety features include: back up alarm, lights, retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights), front driving lights, front and rear hazard and directional indicators |

### ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

### BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description                                    | Suggested List Price |
|--------------|--|----------------------|
| TW95C2HS     | TW95 Cab, High Speed Road Gear, & Ride Control | \$139,408            |

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES

### TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

|                |   |            |
|----------------|---|------------|
| BTW95TIREHDSET | Heavy Duty Radial Tire Assy for TW95 500/70R24 (Set of 4) | \$8,222.00 |
|----------------|---|------------|

### ATTACHMENTS

|                  |  |            |
|------------------|--|------------|
| BTW95952YDW-BOCE | Bucket (95" General Purpose) (W/BOCE) (2.00 cu. Yd) for TW95 | \$5,100.00 |
| BTW9595W-BOCE    | Bucket (95" Light Material) (W/BOCE) (2.75 cu. Yd) for TW95  | \$5,670.00 |
| BTW9595T         | Bucket (95" Light Material) (8 tooth) (2.62 cu. Yd) for TW95 | \$6,252.00 |
| BTW95PF          | 48" Fork Assy for TW95 (Rated 12,500 lbs)                    | \$3,280.00 |

### FIELD INSTALLED OPTIONS

|            |   |      |
|------------|---|------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2" | \$91 |
|------------|---|------|



## P3-Power Protection Plan + TFM\*

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

\* All P3 Extended warranties include the TFM monitoring service for models equipped with the TFM monitoring device.

### Excavators

| Model      |                         |             | TB210     | TB216     | TB216H     | TB230     | TB235/2   | TB240     |
|------------|-------------------------|-------------|-----------|-----------|------------|-----------|-----------|-----------|
| 2YR/2000HR | Full Machine            | Item #      | n/a       | n/a       | n/a        | n/a       | n/a       | n/a       |
| 2YR/2000HR | Full Machine            | List        | std       | std       | std        | std       | std       | std       |
| 3YR/3000HR | Power train             | Item Number | EW210P31  | EW216P31  | EW216HP31  | EW230P31  | EW235P31  | EW240P31  |
| 3YR/3000HR | Power train             | List        | \$524     | \$628     | \$1,048    | \$844     | 948       | 1157      |
| 3YR/3000HR | Power Train & Hydraulic | Item Number | EW210PH31 | EW216PH31 | EW216HPH31 | EW230PH31 | EW235PH31 | EW240PH31 |
| 3YR/3000HR | Power Train & Hydraulic | List        | \$874     | \$1,047   | \$1,747    | \$1,407   | 1581      | 1928      |
| 3YR/3000HR | Full Machine            | Item Number | EW210FM31 | EW216FM31 | EW216HPH31 | EW230FM31 | EW235FM31 | EW240FM31 |
| 3YR/3000HR | Full Machine            | List        | \$1,092   | \$1,308   | \$2,184    | \$1,759   | 1976      | 2410      |
| 4YR/4000HR | Power train             | Item Number | EW210P41  | EW216P41  | EW216HPH41 | EW230P41  | EW235P41  | EW240P41  |
| 4YR/4000HR | Power train             | List        | \$1,223   | \$1,465   | \$2,446    | \$1,970   | 2213      | 2699      |
| 4YR/4000HR | Power Train & Hydraulic | Item Number | EW210PH41 | EW216PH41 | EW216HPH41 | EW230PH41 | EW235PH41 | EW240PH41 |
| 4YR/4000HR | Power Train & Hydraulic | List        | \$1,878   | \$2,250   | \$3,756    | \$3,025   | 3399      | 4145      |
| 5YR/5000HR | Power train             | Item Number | EW210P51  | EW216P51  | EW216HPH51 | EW230P51  | EW235P51  | EW240P51  |
| 5YR/5000HR | Power train             | List        | \$1,398   | \$1,675   | \$2,796    | \$2,251   | 2529      | 3085      |
| 5YR/5000HR | Power Train & Hydraulic | Item Number | EW210PH51 | EW216PH51 | EW216HPH51 | EW230PH51 | EW235PH51 | EW240PH51 |
| 5YR/5000HR | Power Train & Hydraulic | List        | \$2,140   | \$2,564   | \$4,281    | \$3,447   | 3873      | 4723      |

|            |                   |        | TB250/2     | TB260     | TB290     | TB280FR   | TB2150     |
|------------|-------------------|--------|-------------|-----------|-----------|-----------|------------|
| 2YR/2000HR | Full Machine      | Item # | n/a         | n/a       | n/a       | n/a       | n/a        |
| 2YR/2000HR | Full Machine      | List   | std         | std       | std       | std       | std        |
| 3YR/3000HR | Power train       | Item # | EW250/2P31  | EW260P31  | EW280P31  | EW290P31  | EW2150P31  |
| 3YR/3000HR | Power train       | List   | \$1,418     | \$1,572   | \$2,276   | \$2,147   | \$3,494    |
| 3YR/3000HR | Power Train & Hyd | Item # | EW250/2PH31 | EW260PH31 | EW280PH31 | EW290PH31 | EW2150PH31 |
| 3YR/3000HR | Power Train & Hyd | List   | \$2,363     | \$2,621   | \$3,794   | \$3,578   | \$5,824    |
| 3YR/3000HR | Full Machine      | Item # | EW250/2FM31 | EW260FM31 | EW280FM31 | EW290FM31 | EW2150FM31 |
| 3YR/3000HR | Full Machine      | List   | \$2,954     | \$3,276   | \$4,742   | \$4,472   | \$7,280    |
| 4YR/4000HR | Power train       | Item # | EW250/2P41  | EW260P41  | EW280P41  | EW290P41  | EW2150P41  |
| 4YR/4000HR | Power train       | List   | \$3,308     | \$3,669   | \$5,311   | \$5,009   | \$8,154    |
| 4YR/4000HR | Power Train & Hyd | Item # | EW250/2PH41 | EW260PH41 | EW280PH41 | EW290PH41 | EW2150PH41 |
| 4YR/4000HR | Power Train & Hyd | List   | \$5,080     | \$5,635   | \$8,157   | \$7,692   | \$12,522   |
| 5YR/5000HR | Power train       | Item # | EW250/2P51  | EW260P51  | EW280P51  | EW290P51  | EW2150P51  |
| 5YR/5000HR | Power train       | List   | \$3,781     | \$4,193   | \$6,070   | \$5,724   | \$9,318    |
| 5YR/5000HR | Power Train & Hyd | Item # | EW250/2PH51 | EW260PH51 | EW280PH51 | EW290PH51 | EW2150PH51 |
| 5YR/5000HR | Power Train & Hyd | List   | \$5,789     | \$6,421   | \$9,295   | \$8,765   | \$14,269   |

For pricing on older models, please visit [www.takeuchi-us.com](http://www.takeuchi-us.com) under the P3 section



## P3-Power Protection Plan + TFM\*

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

\* All P3 Extended warranties include the TFM monitoring service for models equipped with the TFM monitoring device.

### Track Loaders

|            |                         |             | TL6      | TL8      | TL10V2     | TL12R2     | TL12V2     |
|------------|-------------------------|-------------|----------|----------|------------|------------|------------|
| 2YR/2000HR | Full Machine            | Item_Number | n/a      | n/a      | n/a        | n/a        | n/a        |
| 2YR/2000HR | Full Machine            | List        | std      | std      | std        | std        | std        |
| 3YR/3000HR | Power train             | Item_Number | EWL6P31  | EWL8P31  | EWL10VP31  | EWL12VP31  | EWL12VP31  |
| 3YR/3000HR | Power train             | List        | \$849    | \$1,033  | \$1,498    | \$1,947    | \$1,947    |
| 3YR/3000HR | Power Train & Hydraulic | Item_Number | EWL6PH31 | EWL8PH31 | EWL10VPH31 | EWL12VPH31 | EWL12VPH31 |
| 3YR/3000HR | Power Train & Hydraulic | List        | \$1,414  | \$1,722  | \$2,496    | \$3,245    | \$3,245    |
| 3YR/3000HR | Full Machine            | Item_Number | EWL6FM31 | EWL8FM31 | EWL10VFM31 | EWL12VFM31 | EWL12VFM31 |
| 3YR/3000HR | Full Machine            | List        | \$1,768  | \$2,153  | \$3,120    | \$4,056    | \$4,056    |
| 4YR/4000HR | Power train             | Item_Number | EWL6P41  | EWL8P41  | EWL10VP41  | EWL12VP41  | EWL12VP41  |
| 4YR/4000HR | Power train             | List        | \$1,980  | \$2,411  | \$3,494    | \$4,543    | \$4,543    |
| 4YR/4000HR | Power Train & Hydraulic | Item_Number | EWL6PH41 | EWL8PH41 | EWL10VPH41 | EWL12VPH41 | EWL12VPH41 |
| 4YR/4000HR | Power Train & Hydraulic | List        | \$3,041  | \$3,703  | \$5,366    | \$6,976    | \$6,976    |
| 5YR/5000HR | Power train             | Item_Number | EWL6P51  | EWL8P51  | EWL10VP51  | EWL12VP51  | EWL12VP51  |
| 5YR/5000HR | Power train             | List        | \$2,263  | \$2,756  | \$3,994    | \$5,192    | \$5,192    |
| 5YR/5000HR | Power Train & Hydraulic | Item_Number | EWL6PH51 | EWL8PH51 | EWL10VPH51 | EWL12VPH51 | EWL12VPH51 |
| 5YR/5000HR | Power Train & Hydraulic | List        | \$3,465  | \$4,219  | \$6,115    | \$7,950    | \$7,950    |

For pricing on older models, please visit [www.takeuchi-us.com](http://www.takeuchi-us.com) under the P3 section



## P3-Power Protection Plan + TFM\*

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

\* All P3 Extended warranties include the TFM monitoring service for models equipped with the TFM monitoring device.

### Wheel Loaders

|            |                         |             | TW 40    | TW 60/2    | TW 65    | TW80     | TW95/2   |
|------------|-------------------------|-------------|----------|------------|----------|----------|----------|
| 2YR/2000HR | Full Machine            | Item_Number | n/a      | n/a        | n/a      | n/a      | n/a      |
| 2YR/2000HR | Full Machine            | List        | std      | std        | std      | std      | std      |
| 3YR/3000HR | Power train             | Item_Number | EW40P32  | EW60/2P32  | EW65P32  | EW80P32  | EW95P32  |
| 3YR/3000HR | Power train             | List        | \$1,068  | \$1,523    | \$1,627  | \$1,825  | \$2,546  |
| 3YR/3000HR | Power Train & Hydraulic | Item_Number | EW40PH32 | EW60/2PH32 | EW65PH32 | EW80PH32 | EW95PH32 |
| 3YR/3000HR | Power Train & Hydraulic | List        | \$1,780  | \$2,538    | \$2,712  | \$3,041  | \$4,243  |
| 3YR/3000HR | Full Machine            | Item_Number | EW40FM32 | EW60/2FM32 | EW65FM32 | EW80FM32 | EW95FM32 |
| 3YR/3000HR | Full Machine            | List        | \$2,226  | \$3,172    | \$3,390  | \$3,801  | \$5,304  |
| 4YR/4000HR | Power train             | Item_Number | EW40P42  | EW60/2P42  | EW65P42  | EW80P42  | EW95P42  |
| 4YR/4000HR | Power train             | List        | \$2,493  | \$3,553    | \$3,797  | \$4,257  | \$5,940  |
| 4YR/4000HR | Power Train & Hydraulic | Item_Number | EW40PH42 | EW60/2PH42 | EW65PH42 | EW80PH42 | EW95PH42 |
| 4YR/4000HR | Power Train & Hydraulic | List        | \$3,828  | \$5,456    | \$5,831  | \$6,538  | \$9,123  |
| 5YR/5000HR | Power train             | Item_Number | EW40P52  | EW60/2P52  | EW65P52  | EW80P52  | EW95P52  |
| 5YR/5000HR | Power train             | List        | \$2,849  | \$4,060    | \$4,340  | \$4,866  | \$6,789  |
| 5YR/5000HR | Power Train & Hydraulic | Item_Number | EW40PH52 | EW60/2PH52 | EW65PH52 | EW80PH52 | EW95PH52 |
| 5YR/5000HR | Power Train & Hydraulic | List        | \$4,362  | \$6,217    | \$6,645  | \$7,450  | \$10,396 |

For pricing on older models, please visit [www.takeuchi-us.com](http://www.takeuchi-us.com) under the P3 section