

## 2018 Carbide Cutter Extreme Forestry Mulching Heads for Prime Movers



### Features

- Twin Hydraulic Drive Motors
- VOAC Bent-axis Variable Speed Piston Motors
- Heavy-duty Overhung Bearing Blocks
- 52-120 GPM / up to 6000 PSI
- 4 or 6-Groove Banded Belts
- Dual Belt Drive
- 1600-2150 rpm - 21 inch Diameter Rotor
- 3 in. Piloted, Double-tapered, Roller Bearings
- Machined Bearing Anti-wrap Protection
- Premium Strength Steel Body
- Quick Rotor Shutdown
- Adjustable 2nd Shear Bar
- Adjustable Tree-pusher Bar
- Claw Hooks on Pusher Bar
- Spring-loaded Belt Tensioner
- Skid Shoes - Adjustable 1-1/2 to 3 inches
- Spiral Carbide Tooth Pattern
- Steel Deflector Chains
- Optional Quadco Reversible Knives
- Optional Custom Mount Available

# 2018 Retail Pricing - *CARBIDE EXTREME HYDRAULIC*

<b>Specs</b>	Width of Cut in Inches	80
	Overall Width in Inches	106
	Number of Carbides	48
	Weight in Pounds	5000/6000/7000

Circle/select 1 item from each of 5 groups in the proper size/model column and code column.

Group	Carbide Extreme Hydraulic-driven	CODE	80
<b>1</b>	<b>Size &amp; Series</b>		
	80" 100 series 5000lbs	80XCH100	\$35,655
	80" 200 series 6000lbs	80XCH200	\$41,905
	80" 300 Series 7000lbs	80XCH300	\$46,065
<b>2</b>	<b>Teeth</b>		
	Standard Double Carbide	S	\$3,920
	Quadco Reversible Knives	Q	\$4,160
<b>3</b>	<b>Hydraulic Motor System</b>		
	Variable Displacement 60-80cc Hyd System	33	\$16,650
	Variable Displacement 90-110cc Hyd System	35	\$18,730
<b>4</b>	<b>Auxiliary Hydraulic Flow (GPM)</b>		
	52-58 (Variable Displacement 60-80CC Motor)	H	N/C
	59-63 (Variable Displacement 60-80CC Motor)	D	
	64-69 (Variable Displacement 60-80CC Motor)	C	
	70-77 (Variable Displacement 60-80CC Motor)	S	
	78-83 (Variable Displacement 60-80CC Motor)	E	
	84-88 (Variable Displacement 60-80CC Motor)	F	
	89-93 (Variable Displacement 60-80CC Motor)	G	
	65-72 (Variable Displacement 90-110CC Motor)	N	
	73-80 (Variable Displacement 90-110CC Motor)	O	
	81-88 (Variable Displacement 90-110CC Motor)	M	
	89-96 (Variable Displacement 90-110CC Motor)	P	
	97-104 (Variable Displacement 90-110CC Motor)	Q	
	104-112 (Variable Displacement 90-110CC Motor)	I	
	113-120 (Variable Displacement 90-110CC Motor)	L	
<b>5</b>	<b>Auxiliary Hydraulic Pressure (PSI)</b>		
	Non-adjustable (90-110CC Variable)	0	N/C
	4200-6000PSI (Variable Displacement Motor 60-80CC System)	4	

Product Code: \_\_\_\_\_ Total List Price \$ \_\_\_\_\_  
 Groups            1            2            3            4            5

**NOTE:** Units Ship via Flatbed Carriers Only - Please Call for Freight Quote.



**650 South Main Street  
 Hector, Minnesota 55342  
 loftness.com - 320.848.6266**