

2018 Flail Mowers for Skid-Steers For Standard or High-Flow Hydraulic Systems

Features

- **NEW** - High Pressure Gear-type Motor
- 28-43 GPM up to 4300 PSI
- Standard Gear Motor (with or without Case Drain)
- 10-28 GPM up to 3400 PSI
- Heavy-duty, Bearing Block
- 3-groove Banded Belt
- 0 - 4 1/2 inch Cutting Height (roller adjustment)
- 1/4 inch End Plates
- 5 1/2" OD x 1/4" Wall Roller Tube
- 1 1/2 inch Bearing on Gauge Roller
- 1900-2300 RPM Rotor Speed
- Structural Steel Frame, Front & Rear
- Spring-loaded Belt Tightener
- Full-width Gauge Roller w/Roller Scraper
- Fine-cut, Reversible Knives
- 1 3/4 inch Rotor Bearings
- 10 Gauge Hood
- Easy Access Vented Belt Shield
- Hoses are included (couplers are not).



L10020 - Printed 1.16.18 - Prices Effective 1.1.17 - Subject to Change - USD - FOB Factory - Uncrated

800.828.7624 - loftness.com - 320.848.6266

2018 Retail Pricing - *FLAIL MOWERS HYDRAULIC*

Specs	Cutting Width in Inches	60	72	90
	Overall Width in Inches	72	84	102
	Number of Knives	80	96	120
	Weight in Pounds	930	1008	1208
	Crated Weight in Pounds	1225	1275	1475
	Max Hydraulic Pressure (PSI) - Standard Gear Motor	3400	3400	3400
	Max Hydraulic Pressure (PSI) - High Pressure Gear Motor	4300	4300	4300
	Max Hydraulic HP Input (Hydraulic Horsepower = GPM x PSI / 1714)	90	90	90

Circle/select 1 item from each of 3 groups in the proper size/model column and code column.

Group	Flail	Code	60	72	90
1	Size				
	60 Inches	60HM	\$7,347		
	72 Inches	72HM		\$7,767	
	90 Inches	90HM			\$8,367
2	Hydraulic System				
	#1 - No Case Drain	1	\$2,870	\$2,870	\$2,870
	#2 - With Case Drain	2	\$2,220	\$2,220	\$2,220
3	Auxiliary Hydraulic Flow (GPM) & Pressure (PSI)				
	10-12 GPM (System #1)	3400 PSI max	01D	N/C	not available
	13-16 GPM (System #1)	3400 PSI max	02D	N/C	not available
	17-20 GPM (System #1)	3400 PSI max	03D	N/C	not available
	21-24 GPM (System #1 or #2)	3400 PSI max	04D	N/C	N/C
	25-28 GPM (System #1 or #2)	3400 PSI max	05D	N/C	N/C
	28-30 GPM (System #2)	4300 PSI max	31E	N/C	N/C
	31-34 GPM (System #2)	4300 PSI max	31A	N/C	N/C
	35-39 GPM (System #2)	4300 PSI max	31B	N/C	N/C
	40-43 GPM (System #2)	4300 PSI max	31C	N/C	N/C

Product Code: _____
Groups 1 2 3

Total List Price \$ _____

Hoses are included. - Couplers are NOT included.

System #1 Hoses: 3/4" x 102" #12 MORB - Male O-ring, NO Case Drain Line Required

System #2 Hoses: 3/4" x 102" #12 MORB - Male O-ring, Case Drain Line (required) : 1/2" x 126" - #8MORB

Crating Charge (net price) \$125 \$135 \$175

Other Related Products Auxiliary Hydraulic Oil Cooler, Skid-steer Mounted, Heavy-duty 120,000 BTU Cooler with Dual Fans For Heavy-duty Applications - Ask for the "Cool Flow" cooler from Loftness



**650 South Main Street
Hector, Minnesota 55342
loftness.com - 320.848.6266**