



## **2023 MACHINE PRICE LIST**

519 Bonnie Valentine Way, Pendergrass, GA 30567

e-mail [sales@takeuchi-us.com](mailto:sales@takeuchi-us.com)  
[www.takeuchi-us.com](http://www.takeuchi-us.com)

Prices and specifications  
subject to change without notice

Prices are F.O.B. Pendergrass, GA  
Effective 1 January 2023  
Revision 2



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

# TB210R

## Compact Excavator

### STANDARD EQUIPMENT

Operating Weight: 2,535 lbs.	ROPS/TOPS 2 post foldable canopy
Width: 29.5" / 40.2"	Hydraulically retractable track frame
Maximum Dig Depth: 5' 9.1"	Adjustable width dozer blade with 2 pin-on extensions
Bucket Digging Force: 2,518 lbs.	Pilot operated joystick controls with safety lock out
Horsepower / RPM: 11.7 / 2,200	Pattern change valve
Travel Speed: 1.2 / 2.3 mph	Two-way auxiliary hydraulic circuit routed to the end of the arm
Auxiliary Flow: 5.9 gpm	Adjustable seat with 2" retractable seat belt
Boom swing: Left 85° / Right 85°	Two speed travel
7.1" wide rubber tracks	Travel alarm
	Boom mounted work light
	Horn
	Cast iron, wrap around counterweight

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB210R	TB210R Equipped with ROPS/TOPS 2-post foldable canopy, Rubber tracks, Travel alarm, Auxiliary hydraulics	<b>\$27,027</b>

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB00708	8" Bucket with teeth, .8 cu. ft. capacity	<b>\$430.92</b>
BTB00712	12" Bucket with teeth, 1.1 cu. ft. capacity	<b>\$498.18</b>

### FIELD INSTALLED OPTIONS

0333400003	3" Non Retractable seat belt in lieu of standard 2"	<b>\$174.11</b>
------------	---	-----------------



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

# TB216

## Compact Excavator

### STANDARD EQUIPMENT

Operating Weight: 3,900 lbs.	ROPS/TOPS/OPG 4 post canopy
Width: 38.6" / 51.2"	LCD gauge panel with multi-functional operator information center
Maximum Dig Depth: 7' 10"	Hydraulically retractable track frame
Bucket Digging Force: 4,250 lbs.	Travel alarm
Horsepower / RPM: 15 / 2,400	Two-speed travel with automatic down shift
Travel Speed: 1.4 / 2.6 mph	Pattern selector valve
Auxiliary Flow: 8.9 gpm	Pilot operated joystick controls with safety lock out
Boom swing: Left 80°/ Right 50°	Cast iron, wrap around counterweight
9" wide rubber tracks	Adjustable suspension seat with 2" retractable seat belt
Long Arm w/ integrated thumb mount	Two-way auxiliary hydraulic circuit routed to the end of the arm
	Variable displacement axial piston main hydraulic pumps
Electronic engine monitoring system	Adjustable width dozer blade
TFM hardware standard equipment, service included through the standard warranty period (sn 216101378 ~)	

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB216R	TB216 Equipped with ROPS/TOPS/OPG canopy, Rubber tracks	<b>\$35,518</b>

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB01608	8" Pin-On Bucket with teeth, 1.1 cu. ft. capacity	<b>\$551.30</b>
BTB01612	12" Pin-On Bucket with teeth, 1.5 cu. ft. capacity	<b>\$688.90</b>
BTB01618	18" Pin-On Bucket with teeth, 2.4 cu. ft. capacity	<b>\$808.76</b>
BTB01624	24" Pin-On Bucket with teeth, 3.2 cu. ft. capacity	<b>\$852.15</b>
BQC01600	Quick Coupler	<b>\$1,073.88</b>
BQC01612	12" Quick Coupler Bucket with teeth, 1.5 cu. ft. capacity	<b>\$688.90</b>
BQC01618	18" Quick Coupler Bucket with teeth, 2.4 cu. ft. capacity	<b>\$808.76</b>
BQC01624	24" Quick Coupler Bucket with teeth, 3.2 cu. ft. capacity	<b>\$852.15</b>
BQC01624D	24" Quick Coupler Ditch Bucket, 3.0 cu. ft. capacity	<b>\$1,045.70</b>
ATH216I	INSTALLED Hydraulic thumb (Only compatible w/ 12" or larger Buckets)	<b>\$2,493.18</b>

### FIELD INSTALLED OPTIONS

1914199048	3" Non-retractable seat belt in lieu of standard 2"	<b>\$72.63</b>
ATH216K	Hydraulic thumb (Only compatible with 12" and larger buckets)	<b>\$2,243.18</b>



519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

# TB216H

## Hybrid Compact Excavator

### STANDARD EQUIPMENT

Operating Weight: 4,277 lbs.	LCD gauge panel with multi-functional operator information center
Width: 38.6" / 51.2"	Hydraulically retractable track frame
Maximum Dig Depth: 7' 10"	Travel alarm
Bucket Digging Force: 4,250 lbs.	Two-speed travel with automatic down shift
Horsepower / RPM: 15 / 2,400 (diesel)	Pattern selector valve
14.2 / 2,400 (electric)	Pilot operated joystick controls with safety lock out
Travel Speed: 1.4 / 2.6 mph	Cast iron, wrap around counterweight
Auxiliary Flow: 8.9 gpm	Adjustable suspension seat with 2" retractable seat belt
Boom swing: Left 80°/ Right 50°	Two-way auxiliary hydraulic circuit routed to the end of the arm
9" wide rubber tracks	Variable displacement axial piston main hydraulic pumps
Long Arm w/ integrated thumb mount	Adjustable width dozer blade
ROPS/TOPS/OPG 4 post canopy	Electronic engine monitoring system
TFM hardware standard equipment, service included through the standard warranty period (sn 216101378 ~)	

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB216RH	TB216 Equipped with ROPS/TOPS/OPG canopy, Rubber tracks, diesel engine/electric motor	<b>\$57,068</b>

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB01608	8" Pin-On Bucket with teeth, 1.1 cu. ft. capacity	<b>\$551.30</b>
BTB01612	12" Pin-On Bucket with teeth, 1.5 cu. ft. capacity	<b>\$688.90</b>
BTB01618	18" Pin-On Bucket with teeth, 2.4 cu. ft. capacity	<b>\$808.76</b>
BTB01624	24" Pin-On Bucket with teeth, 3.2 cu. ft. capacity	<b>\$852.15</b>
BQC01600	Quick Coupler	<b>\$1,073.88</b>
BQC01612	12" Quick Coupler Bucket with teeth, 1.5 cu. ft. capacity	<b>\$688.90</b>
BQC01618	18" Quick Coupler Bucket with teeth, 2.4 cu. ft. capacity	<b>\$808.76</b>
BQC01624	24" Quick Coupler Bucket with teeth, 3.2 cu. ft. capacity	<b>\$852.15</b>
BQC01624D	24" Quick Coupler Ditch Bucket, 3.0 cu. ft. capacity	<b>\$1,045.70</b>
ATH216I	INSTALLED Hydraulic thumb (Only compatible w/ 12" or larger Buckets)	<b>\$2,493.18</b>

### FIELD INSTALLED OPTIONS

1914199048	3" Non-retractable seat belt in lieu of standard 2"	<b>\$72.63</b>
ATH216K	Hydraulic thumb (Only compatible with 12" and larger buckets)	<b>\$2,243.18</b>
TP-84-MTF-0252-01	8/4 PLUG-CONNECTOR 25' Cable	<b>\$979.00</b>
TP-84-MTF-0502-01	8/4 PLUG-CONNECTOR 50' Cable	<b>\$1,155.00</b>

\*\* All TB216H's purchased for use in Canada must have a CSA (Canadian Standards Association) inspection on the electrical components prior to retail sale or rental. Canadian Dealer's and Direct Accounts are responsible for scheduling this inspection and any associated costs/fees. Inspection services are available throughout Canada. If you have questions concerning CSA inspections you may go to their website: <https://www.csagroup.org> or contact the CSA Group (Product Evaluation) at 888.273.3335. \*\*



519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel: 706-693-3600 Fax: 706-693-3725

www.takeuchi-us.com

# TB20e

## Battery Compact Excavator

### STANDARD EQUIPMENT

Operating Weight: 4,255 lb	High resolution multifunction color monitor
Width: 38.6" / 51.2"	Hydraulically retractable track frame
Maximum Dig Depth: 7' 10"	Travel alarm
Bucket Digging Force: 4,226 lb	Two-speed travel with automatic down shift
Lithium Ion Battery 24.7 kWh	Pattern selector via monitor panel
Travel Speed: 1.3 / 2.5 mph	EH joystick controls with safety lock out
Auxiliary Flow: 9.0 gpm	Cast iron, wrap around counterweight
Boom swing: Left 78°/ Right 49°	Adjustable suspension seat with 2" retractable seat belt
9" wide rubber tracks	Two-way auxiliary hydraulic circuit routed to the end of the arm
Long Arm w/ integrated thumb mount	Two Motor-linked fixed displacement gear pumps
Electronic monitoring system	Adjustable width dozer blade
ROPS/TOPS/OPG 4 post canopy	
TFM hardware standard equipment, service included through the standard warranty period (sn 120000010~)	

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB20e	TB20e Battery Excavator Equipped with ROPS/TOPS/OPG canopy, Rubber tracks	<b>\$79,000</b>

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB01608	8" Pin-On Bucket with teeth, 1.1 cu. ft. capacity	<b>\$551.30</b>
BTB01612	12" Pin-On Bucket with teeth, 1.5 cu. ft. capacity	<b>\$688.90</b>
BTB01618	18" Pin-On Bucket with teeth, 2.4 cu. ft. capacity	<b>\$808.76</b>
BTB01624	24" Pin-On Bucket with teeth, 3.2 cu. ft. capacity	<b>\$852.15</b>
BQC01600	Quick Coupler	<b>\$1,073.88</b>
BQC01612	12" Quick Coupler Bucket with teeth, 1.5 cu. ft. capacity	<b>\$688.90</b>
BQC01618	18" Quick Coupler Bucket with teeth, 2.4 cu. ft. capacity	<b>\$808.76</b>
BQC01624	24" Quick Coupler Bucket with teeth, 3.2 cu. ft. capacity	<b>\$852.15</b>
BQC01624D	24" Quick Coupler Ditch Bucket, 3.0 cu. ft. capacity	<b>\$1,045.70</b>
ATH216I	INSTALLED Hydraulic thumb (Only compatible w/ 12" or larger Buckets)	<b>\$2,493.18</b>

### FIELD INSTALLED OPTIONS

1914199048	3" Non-retractable seat belt in lieu of standard 2"	<b>\$72.63</b>
ATH216K	Hydraulic thumb (Only compatible with 12" and larger buckets)	<b>\$2,243.18</b>
TB20ECHR	480V Quick Charger	<b>\$6,400.00</b>
TP-103-PPT-0252-01	Charging Cable 25' with 110v plug	<b>\$518.82</b>

NOTE: TB20E is not available for Canada customers currently.



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

# TB225

## Compact Excavator

### STANDARD EQUIPMENT

Operating Weight: 4,993 lbs.	ROPS/FOPS/OPG Level 1
Width: 3' 7.3" / 4' 11"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 8' 5.5"	Suspension seat with fore/aft, tilt, and weight adjustments
Bucket Digging Force: 4,339 lbs.	Pilot operated joystick controls with pattern change valve
Horsepower / RPM: 19.6 / 2,400	EPA Tier 4 Final Engine
Travel Speed: 1.6 / 2.6 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 9.96 gpm	High capacity radiator and hydraulic oil cooler
Boom Swing: Left 75° / Right 55°	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system,
Track Width: 9.8"	proportional slide switch, one-way mode and continuous detent mode
	Safety features include: Travel alarm, retractable seat belt
Automatic load sensing two speed travel	control lockout, pilot accumulator, and lights
Reinforced arm w/ Integrated thumb mount	Variable displacement axial piston pump
Backfill blade with extensions	Auto Idle
TFM hardware standard equipment, service included through the standard warranty period	

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB225R	TB225 Canopy Equipped with Rubber	<b>\$41,878</b>

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB12512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	<b>\$778.05</b>
BTB12518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	<b>\$884.93</b>
BTB12524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	<b>\$999.50</b>
BQC12500	Quick Coupler	<b>\$1,073.88</b>
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	<b>\$778.05</b>
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	<b>\$807.98</b>
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	<b>\$884.93</b>
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	<b>\$999.50</b>
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	<b>\$1,503.44</b>
ATH225I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	<b>\$2,407.68</b>

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	<b>\$91.00</b>
ATH225K	Hydraulic thumb (Only compatible with 13" and larger buckets)	<b>\$2,157.68</b>



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

# TB230

## Compact Excavator

### STANDARD EQUIPMENT

Operating Weight: 6,360 lbs.	TOPS/ROPS/OPG 4 post canopy
Width: 4' 9.5"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 9' 3.6"	High back adjustable suspension seat
Bucket Digging Force: 6,471 lbs.	Pilot operated joystick control with pattern change valve
Horsepower / RPM: 24.4 / 2,400	EPA Final Tier 4 compliant engine with engine monitoring system
Travel Speed: 1.8 / 3.2 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 13.4 gpm	High capacity radiator and hydraulic oil cooler
Boom Swing: Left 79° / Right 58°	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode
Track Width: 11.8"	Safety features include: Travel alarm, retractable seat belt control lockout, pilot accumulator, and lights
Two speed travel with automatic shift down	Variable displacement axial piston pump
Reinforced arm w/ Integrated thumb mount	Auto Idle
Heavy duty dozer blade with float	
TFM hardware standard equipment, service included through the standard warranty period (sn 13000923 ~)	

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB230R	TB230 Canopy Equipped with Rubber Tracks	<b>\$46,003</b>
TB230S	TB230 Canopy Equipped with Steel Tracks	<b>\$46,876</b>
TB230RA (w/Angle Blade)	TB230 Canopy (Rubber Track) with <b>Angle Blade</b> *Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	<b>\$49,096</b>
TB230SA (w/Angle Blade)	TB230 Canopy (Steel Track) with <b>Angle Blade *</b>	<b>\$49,970</b>

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB12512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	<b>\$778.05</b>
BTB12518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	<b>\$884.93</b>
BTB12524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	<b>\$999.50</b>
BQC12500	Quick Coupler	<b>\$1,073.88</b>
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	<b>\$778.05</b>
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	<b>\$807.98</b>
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	<b>\$884.93</b>
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	<b>\$999.50</b>
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	<b>\$1,503.44</b>
ATH230I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	<b>\$2,407.68</b>

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	<b>\$91.00</b>
ATH230K	Hydraulic thumb (Only compatible with 13" and larger buckets)	<b>\$2,157.68</b>



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

# TB235-2

## Compact Excavator

### STANDARD EQUIPMENT

Operating Weight: 7,418 lbs.	TOPS/ROPS/OPG 4 post canopy
Width: 5' 2.2"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 10' 7.8"	High back adjustable suspension seat
Bucket Digging Force: 9,127 lbs.	Pilot operated joystick control with pattern change valve
Horsepower / RPM: 24.4 / 2,400	EPA Final Tier 4 compliant engine and engine monitoring system
Travel Speed: 1.7 / 2.8 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 15.8 gpm	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system,
Boom Swing: Left 70° / Right 55°	proportional slide switch, one-way mode and continuous detent mode
Track width: 11.8"	Safety features include: travel alarm, retractable seat belt,
	control lockout, pilot accumulator, and lights
Two speed travel with automatic shift down	Variable displacement axial piston pump
Reinforced arm w/ Integrated thumb mount	Auto Idle
Heavy duty dozer blade with float	
TFM hardware standard equipment, service included through the standard warranty period	

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB235-2R	TB235-2 Canopy Equipped with Rubber Tracks	\$51,870
TB235-2RA (w/Angle Blade)	TB235-2 Canopy (above Equipped) with <b>Angle Blade</b> Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$55,245

TB235-2CR	TB235-2 Cab Equipped with Rubber TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet	\$59,842
TB235-2CRA (w/ Angle Blade)	TB235-2 Cab (above Equipped) with <b>Angle Blade</b> Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$63,216

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB13512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	\$778.05
BTB13518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	\$884.93
BTB13524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	\$999.50
BQC13500	Quick Coupler	\$1,073.88
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	\$778.05
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	\$807.98
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	\$884.93
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	\$999.50
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	\$1,503.44
ATH235-2I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	\$2,407.68

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
ATH235-2K	Hydraulic thumb (Only compatible with 13" and larger buckets)	\$2,157.68





519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

# TB335R

## Compact Excavator

### STANDARD EQUIPMENT

Operating Weight: 7,970 lbs.	TOPS/ROPS/OPG 4 post canopy
Width: 5' 8.5"	Multifunction color display panel, 4.3" (Canopy) 7" (Cab)
Maximum Dig Depth: 10' 6.2"	High back adjustable suspension seat
Bucket Digging Force: 9,127 lbs.	Pilot operated joystick control with pattern change valve
Horsepower / RPM: 24.4 / 2,300	EPA Final Tier 4 compliant engine and engine monitoring system
Travel Speed: 1.9 / 2.5 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 17.0 gpm	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system,
Boom Swing: Left 70o/ Right 55o	proportional slide switch, one-way mode and continuous detent mode
Track width: 11.8"	Safety features include: travel alarm, retractable seat belt,
	control lockout, pilot accumulator, and LED work lights
Two speed travel with automatic shift down	Variable displacement axial piston pump
Reinforced arm w/ Integrated thumb mount	Auto Idle
Heavy duty dozer blade with float	
TFM hardware standard equipment, service included through the standard warranty period	

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB335R-R	TB335R Canopy Equipped with Rubber Tracks Four post TOPS/ROPS/OPG canopy, 12v power outlet, 1st aux circuit only	<b>\$54,982</b>
TB335R-RA (w/Angle Blade)	TB335R Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	<b>\$58,560</b>
TB335R-CR	TB335R Cab Equipped with Rubber TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet, 1st and 3rd aux circuits	<b>\$63,433</b>
TB335R-CRA (w/ Angle Blade)	TB335R Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	<b>\$67,009</b>

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB13512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	<b>\$778.05</b>
BTB13518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	<b>\$884.93</b>
BTB13524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	<b>\$999.50</b>
BQC13500	Quick Coupler	<b>\$1,073.88</b>
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	<b>\$778.05</b>
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	<b>\$807.98</b>
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	<b>\$884.93</b>
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	<b>\$999.50</b>
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	<b>\$1,503.44</b>
ATH235-2I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	<b>\$2,407.68</b>

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	<b>\$91.00</b>
ATH235-2K	Hydraulic thumb (Only compatible with 13" and larger buckets)	<b>\$2,157.68</b>



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

# TB240

## Compact Excavator

### STANDARD EQUIPMENT

Operating Weight: 8,570 lbs.	TOPS/ROPS/OPG 4 post canopy
Width: 5' 8.5"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 11' 4.4"	High back adjustable suspension seat
Bucket Digging Force: 9,959 lbs.	Pilot operated joystick control with pattern change valve
Horsepower / RPM: 35.8 / 2,200	EPA Final Tier 4 compliant engine with DPF and engine monitoring system
Travel Speed: 1.8 / 3.3 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 17.1 gpm	Side by side industrial type radiator and hydraulic oil cooler
Boom Swing: Left 76° / Right 58°	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode
Track width: 13.8"	Safety features include: Travel alarm, retractable seat belt control lockout, pilot accumulator, and lights
Two speed travel with automatic shift down	Variable displacement axial piston pump
Reinforced arm w/ Integrated thumb mount	Auto Idle
Heavy duty dozer blade with float	
TFM hardware standard equipment, service included through the standard warranty period (Canopy: sn 124001379~ / Cab: sn 124001483-	

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB240R	TB240 Canopy Equipped with Rubber Tracks	\$58,772
TB240S	TB240 Canopy Equipped with Steel Tracks	\$59,637
TB240RA (w/Angle Blade)	TB240 Canopy (Rubber Tracks) with <b>Angle Blade</b> *Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$62,114
TB240SA (w/Angle Blade)	TB240 Canopy (Steel Tracks) with <b>Angle Blade *</b>	\$62,969
TB240CR	TB240 Cab Equipped with Rubber Tracks ** TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet	\$66,948
TB240CS	TB240 Cab Equipped with Steel Tracks **	\$67,813
TB240CRA (w/ Angle Blade)	TB240 Cab (Rubber Tracks) with <b>Angle Blade</b> ***Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$70,290
TB240CSA (w/ Angle Blade)	TB240 Cab (Steel Tracks) with <b>Angle Blade</b>	\$71,155

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB13512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	\$778.05
BTB13518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	\$884.93
BTB13524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	\$999.50
BQC13500	Quick Coupler	\$1,073.88
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	\$778.05
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	\$807.98
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	\$884.93
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	\$999.50
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	\$1,503.44
ATH240I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	\$2,407.68

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
ATH240K	Hydraulic thumb (Only compatible with 13" and larger buckets)	\$2,157.68



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

# TB250-2

## Compact Excavator

### STANDARD EQUIPMENT

Operating Weight: 10,737 lbs.	TOPS/ROPS/OPG 4 post canopy
Width: 6' 0"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 12' 4.8"	High back adjustable suspension seat
Bucket Digging Force: 10,430 lbs.	Pilot operated joystick control with pattern change valve
Horsepower / RPM: 39 / 2,400	EPA Final Tier 4 compliant engine with DPF and engine monitoring system
Travel Speed: 1.6 / 2.6 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 24 gpm	Side by side industrial type radiator and hydraulic oil cooler
Track width: 15.7"	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode
Two speed travel with automatic shift down	Safety features include: Travel alarm, retractable seat belt, control lockout, pilot accumulator, and lights
Reinforced arm w/ Integrated thumb mount	Variable displacement axial piston pump
Heavy duty dozer blade with float	Auto Idle
TFM hardware standard equipment, service included through the standard warranty period	

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB250-2R	TB250-2 Canopy Equipped with Rubber Tracks	\$70,980
TB250-2S	TB250-2 Canopy Equipped with Steel Tracks	\$72,072
TB250-2RA (w/Angle Blade)	TB250-2 Canopy (Rubber Track) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$74,365
TB250-2SA (w/Angle Blade)	TB250-2 Canopy (Steel Track) with Angle Blade	\$75,457
TB250-2CR	TB250-2 Cab Equipped with Rubber Tracks TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet	\$77,532
TB250-2CS	TB250-2 Cab Equipped with Steel Tracks	\$78,624
TB250-2CRA (w/ Angle Blade)	TB250-2 Cab (Rubber Track) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$80,917
TB250-2CSA (w/ Angle Blade)	TB250-2 Cab (Steel Track) with Angle Blade	\$82,009

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB14512	12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity	\$1,131.17
BTB14518	18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity	\$1,254.00
BTB14524	24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity	\$1,354.32
BTB14536	36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity	\$1,680.36
BQC14500	Quick Coupler	\$1,094.40
BQC14512	12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity	\$1,120.39
BQC14518	18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity	\$1,185.60
BQC14524	24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity	\$1,280.45
BQC14536	36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity	\$1,588.70
BQC14536D	36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity	\$1,521.00
ATH250-2I	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,548.58

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
ATH250-2K	Hydraulic Thumb (Only compatible with 18" and larger buckets)	\$2,298.58



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

# TB350R

## Compact Excavator

### STANDARD EQUIPMENT

Operating Weight: 10,980 lbs.	TOPS/ROPS/OPG 4 post canopy
Width: 6' 6.7"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 11' 8.8"	High back adjustable suspension seat
Bucket Digging Force: 10,431 lb	Pilot operated joystick control with pattern change valve
Horsepower / RPM: 41.7 / 2,000	EPA Final Tier 4 compliant engine with DPF and engine monitoring system
Travel Speed: 1.7 / 3.1 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 24.6 gpm	Side by side industrial type radiator and hydraulic oil cooler
Track width: 15.7"	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode
Two speed travel with automatic shift down	Safety features include: Travel alarm, retractable seat belt, control lockout, pilot accumulator, and lights
Reinforced arm w/ Integrated thumb mount	Variable displacement axial piston pump
Heavy duty dozer blade with float	Auto Idle
TFM hardware standard equipment, service included through the standard warranty period	

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB350R-R	TB350R- Canopy Equipped with Rubber Tracks Four Post TOPS/ROPS/OPG Canopy, 12V Power Outlet, 1st Aux Circuit Only	<b>\$75,239</b>
TB350R-RA (w/Angle Blade)	TB350R- Canopy (Above Equipped) Rubber Track) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	<b>\$78,827</b>
TB350R-CR	TB350R- Cab Equipped with Rubber Tracks TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet	<b>\$82,184</b>
TB350R-CRA (w/ Angle Blade)	TB350R- Cab (Above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	<b>\$85,772</b>

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB14512	12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity	<b>\$1,131.17</b>
BTB14518	18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity	<b>\$1,254.00</b>
BTB14524	24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity	<b>\$1,354.32</b>
BTB14536	36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity	<b>\$1,680.36</b>
BQC14500	Quick Coupler	<b>\$1,094.40</b>
BQC14512	12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity	<b>\$1,120.39</b>
BQC14518	18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity	<b>\$1,185.60</b>
BQC14524	24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity	<b>\$1,280.45</b>
BQC14536	36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity	<b>\$1,588.70</b>
BQC14536D	36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity	<b>\$1,521.00</b>
ATH250-2I	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	<b>\$2,548.58</b>

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	<b>\$91.00</b>
ATH250-2K	Hydraulic Thumb (Only compatible with 18" and larger buckets)	<b>\$2,298.58</b>



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

## TB260

Compact Excavator

STANDARD EQUIPMENT		
Operating Weight: 12,125 lbs. Width: 6' 6.7" Maximum Dig Depth: 12' 9.4" Bucket Digging Force: 12,756 lbs. Horsepower / RPM: 47.6 / 2,400 Travel Speed: 1.7 / 3.0 mph Primary Aux Flow: 27.0 gpm Second Aux Flow: 11.6 gpm Boom Swing: Left 78° / Right 55° Track Width: 15.7" Two speed travel with automatic shift down Reinforced arm w/ Integrated thumb mount Heavy duty dozer blade with float Auto Idle	TOPS/ROPS/OPG 4 post canopy Color gauge panel with multi-function operator information center Adjustable high back suspension seat Pilot operated joystick control with pattern change valve Proportional slide switch control auxiliary hydraulics EPA Final Tier 4 Turbocharged engine with DPF and engine monitoring system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door Side by side radiator and hydraulic cooler Variable Displacement axial piston pump Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch controls Primary auxiliary continuous mode and one-way mode Safety features include: Travel alarm, retractable seat belt, control lockout, pilot accumulator, mirrors and lights	
TFM hardware standard equipment, service included through the standard warranty period (Canopy: sn 1261001302~ / Cab: sn 1261001605~)		
BASE MACHINE WITH STANDARD EQUIPMENT		
Factory Code	Description	Suggested List Price
TB260R	TB260 Equipped with ROPS/TOPS/FOPS canopy, Rubber Tracks	\$79,150
TB260S	TB260 Equipped with ROPS/TOPS/FOPS canopy, Steel Tracks	\$80,242
TB260RA (w/Angle Blade)	TB260 Canopy (Rubber Track) with <b>Angle Blade</b> Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$82,525
TB260SA (w/Angle Blade)	TB260 Canopy (Steel Track) with <b>Angle Blade</b>	\$83,617
TB260L (w/ Segmented Rubber Tracks)	TB260 Canopy (above Equipped with Segmented Rubber <b>Tracks</b> )	\$84,774
TB260LA (w/ Angle Blade & Segmented Rubber Tracks)	TB260 Canopy (above Equipped with Segmented Rubber <b>Tracks</b> ) w/ <b>Angle Blade</b> , Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$88,149
TB260CR	TB260 Cab Equipped with Rubber Tracks TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet	\$86,574
TB260CS	TB260 Cab Equipped with Steel Tracks	\$87,666
TB260CRA (w/Angle Blade)	TB260 Cab (Rubber Track) with <b>Angle Blade</b> Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$89,948
TB260CSA (w/Angle Blade)	TB260 Cab (Steel Track) with <b>Angle Blade</b>	\$91,040
TB260CL (w/ Segmented Rubber Tracks)	TB260 Cab (above Equipped Cab with <b>Segmented Rubber Tracks</b> )	\$92,197
TB260CLA (w/ Angle Blade & Segmented Rubber Tracks)	TB260 Cab (above Equipped Cab with <b>Segmented Rubber Tracks</b> ) w/ <b>Angle Blade</b> , Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$95,572
BASE MACHINE PRICE DOES NOT INCLUDE BUCKET		
ATTACHMENTS		
Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Thumb System		
AQC-PH260I	INSTALLED	Hydraulic Pin Grabber Coupler (TB260) - Includes set of dead pins & hoses (Installed)
AQC-PH260	Field Installed Kit	Hydraulic Pin Grabber Coupler (TB260) - Includes set of dead pins & hoses
ABE-260-PO12T		12" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)
ABE-260-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)
ABE-260-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)
ABE-260-PO36T		36" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)
ATE-260I	INSTALLED	Hydraulic Thumb (2-line) (Only compatible w/ 18" or larger Buckets)
ATE-260K	Field Installed Kit	Hydraulic Thumb (2-line) (Only compatible w/ 18" or larger Buckets)
DPK-260		Bucket Pin Kit (includes Hardware)
		\$363.00
Tag Branded Pin on Buckets, Manual Coupler		
BTB26012		12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity
BTB26018		18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity
BTB26024		24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity
BTB26036		36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity
BQC26000		Quick Coupler
BQC14512		12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity
BQC14518		18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity
BQC14524		24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity
BQC14536		36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity
BQC14536D		36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity
		\$1,094.40
		\$1,120.39
		\$1,185.60
		\$1,280.45
		\$1,588.70
		\$1,521.00
ATH260I	INSTALLED	Hydraulic thumb (Only compatible w/ 18" or larger Buckets) *
ATH260K	Field Installed Kit	Hydraulic Thumb (Only compatible with 18" and larger buckets)
		\$2,548.58
		\$2,298.58
FIELD INSTALLED OPTIONS		
1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00

Prices and specifications  
subject to change without notice

P-10  
Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA  
Effective 1 January 2023



519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

# TB257FR

## Zero Swing Excavator

### STANDARD EQUIPMENT

Operating Weight: 12,675 lbs.	ROPS/TOPS/OPG Level 1, 4 Post Canopy
Width: 6' 6.7"	Multifunction display
Maximum Dig Depth: 12' 9.4"	Deluxe High Back Suspension Seat
Bucket Digging Force: 10,431 lbs.	Pilot operated joystick controls with pattern change valve
Horsepower / RPM: 52.3 / 2,400	Proportional slide switch control auxiliary hydraulic
Travel Speed: 1.6 / 3.0 mph	EPA Tier 4 Final, Turbocharged engine with DOC/DPF exhaust aftertreatment system
Primary Aux Flow: 27.7 gpm	Self priming fuel system with ground level fuel fill, sight gauge and lockable door
Second Aux Flow: 11.8 gpm	Side by side radiator and hydraulic cooler
Boom Swing: Left 30°/ Right 16°	Variable Displacement axial piston pump
Track Width: 15.7"	Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch controls, third auxiliary circuit for hydraulic quick couple
Automatic Load Sensing Two Speed Travel	Primary auxiliary with detent and one way mode
Reinforced arm w/ Integrated thumb mount	Safety features include: Travel alarm, retractable seat belt, boom holding valve with lift alarm
Heavy duty backfill blade with float	control lockout, pilot accumulator, mirrors and LED working lights
Auto Idle	
TFM hardware standard equipment, service included through the standard warranty period	

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB257FRR	TB257FR Equipped with ROPS/TOPS/FOPS canopy, Rubber Tracks	\$81,218
TB257FRS	TB257FR Equipped with ROPS/TOPS/FOPS canopy, Steel Tracks	\$82,310

TB257FRCR	TB257FR Cab Equipped with Rubber Tracks TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio 12v power outlet	\$89,189
TB257FRCS	TB257FR Cab Equipped same as above with Steel Tracks	\$90,281

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

#### ATTACHMENTS

#### Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Hydraulic Thumb

AQC-PH257I	INSTALLED	Hydraulic Pin Grabber Coupler (TB257FR) (Installed)	\$4,713.56
AQC-PH257	Field Installed Kit	Hydraulic Pin Grabber Coupler (TB257FR) - Includes pins & hose	\$4,463.56
ABE-145-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,260.00
ABE-145-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,360.80
ATE-145I	INSTALLED	Hydraulic Thumb (2-tine) (Only compatible w/ 18" or larger Buckets)	\$2,848.75
ATE-145K	Field Installed Kit	Hydraulic Thumb (2-tine) (Only compatible w/ 18" or larger Buckets)	\$2,598.75
DPK-260		Bucket Pin Kit (includes Hardware)	\$363.00

#### Tag Manual Coupler / Pin on Buckets / Hydraulic Thumb

BTB14512		12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity	\$1,131.17
BTB14518		18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity	\$1,254.00
BTB14524		24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity	\$1,354.32
BTB14536		36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity	\$1,680.36
BQC14500		Quick Coupler	\$1,094.40
BQC14512		12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity	\$1,120.39
BQC14518		18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity	\$1,185.60
BQC14524		24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity	\$1,280.45
BQC14536		36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity	\$1,588.70
BQC14536D		36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity	\$1,521.00
ATH250-2I	INSTALLED	Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,548.58
ATH250-2K	Field Installed Kit	Hydraulic Thumb (2-tine) (Only compatible with 18" and larger buckets)	\$2,298.58

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
------------	---	---------



519 Bonnie Valentine Way, Pendergrass, GA 30561  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

# TB370

## Excavator

### STANDARD EQUIPMENT

Operating Weight: 14,850 lbs. Width: 6' 10.7" Maximum Dig Depth: 13' 4.7" Bucket Digging Force: 14,613 lbs. Net Horsepower / RPM: 56.9 / 2,000 Travel Speed: 1.6 / 2.9 mph Auxiliary Flow: 31.7 gpm Second Aux Flow: 12.3 gpm Boom Swing: Left 79° / Right 51° Track Width: 15.7" Automatic load sensing two speed travel Reinforced arm w/ Integrated thumb mount Heavy duty backfill blade with float Auto Idle	ROPS/OPG Level 1 climate control, jog dial, windshield wiper and washer, skylight, sunshade, radio with Bluetooth 8" Color touch screen multifunction display Deluxe high back suspension seat Pilot operated joystick controls EPA Tier 4 Final, Turbocharged engine with DOC/DPF exhaust aftertreatment system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door Side by side radiator and hydraulic cooler Closed center, load sensing hydraulic system Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch controls, third auxiliary circuit for hydraulic quick coupler Primary auxiliary with detent and one way mode. Safety features include: travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding, valve with lift alarm, mirrors and LED working lights
--	--

TFM hardware standard equipment, service included through the standard warranty period

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB370CR	TB370 Cab Equipped with 15.7" Rubber Tracks	\$107,798
TB370CS	TB370 Cab Equipped with 15.7" Steel Tracks	\$108,880
TB370CRA	(w/ Angle Blade) TB370 Cab with Rubber Tracks and Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards	\$112,800
TB370CSA	(w/ Angle Blade) TB370 Cab with Steel Tracks and Angle Blade (same as above)	\$113,882
TB370CL	TB370 Cab Equipped with Segmented 15.7" Rubber Tracks	\$113,504
TB370CLA	(w/ Angle Blade) TB370 Cab with Segmented Rubber Tracks and Angle Blade (same as above)	\$118,505

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

#### ATTACHMENTS

Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Hydraulic Thumb			
AQC-PH290I	INSTALLED	Hydraulic Pin Grabber Coupler (TB370) - Includes set of dead pins & hoses(Installed)	\$5,196.95
AQC-PH290	Field Installed Kit	Hydraulic Pin Grabber Coupler (TB370) - Includes set of dead pins & hoses	\$4,946.95
ABE-370-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,549.80
ABE-370-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,644.30
ABE-370-PO36T		36" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$2,009.70
ATE-370I	INSTALLED	Hydraulic Thumb (4-tine) (Only compatible w/ 18" or larger Buckets)	\$3,437.80
ATE-370K	Field Installed Kit	Hydraulic Thumb (4-tine) (Only compatible w/ 18" or larger Buckets)	\$3,187.80
DPK-290		Bucket Pin Kit (includes Hardware)	\$387.20

Tag Manual Coupler / Pin on Buckets / Hydraulic Thumb			
BTB07018		18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,329.70
BTB07024		24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,514.21
BTB07036		36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,894.40
BQC07000		Quick Coupler	\$1,350.33
BQC07018		18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,280.45
BQC07024		24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,382.54
BQC07036		36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,729.67
BQC07036D		36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,699.43
ATH290I	INSTALLED	Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$3,498.66
ATH290K	Field Installed Kit	Hydraulic thumb (Only compatible with 18" and larger buckets)	\$3,248.66

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
------------	---	---------



# TB290

## Excavator

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

### STANDARD EQUIPMENT

Operating Weight: 18,630 lbs.	ROPS/OPG enclosed cab w/ air conditioner/heat, windshield wiper,
Width: 7' 7"	12v power outlet, and AM/FM/MP3 radio
Maximum Dig Depth: 15'	Color 5.7" gauge panel with multi-function operator information center
Bucket Digging Force: 16,565 lbs.	10-way adjustable high back suspension seat
Net Horsepower / RPM: 69.2 / 2,000	Pilot operated joystick control with pattern change valve
Travel Speed: 1.6 / 3.1 mph	EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system
Auxiliary Flow: 26.4 gpm	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable doo
Second Aux Flow: 14.5 gpm	Side by side radiator and hydraulic cooler
Boom Swing: Left 70°/ Right 60°	Load sensing variable displacement hydraulic system
Track Width: 17.7" Rubber / 21.7" Steel	Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow
Two speed travel with automatic shift down	control system and proportional slide switch
Reinforced arm w/ Integrated thumb mount	Primary auxiliary continuous mode and one-way mode
Heavy duty dozer blade with float	Safety features include: large skylight with sun shade,
Automatic track tensioner	travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding
Auto Idle	valve with lift alarm, mirrors and lights
TFM hardware standard equipment, service included through the standard warranty period (sn 185102670 ~)	

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB290CR	TB290 Cab Equipped with Rubber Tracks	\$125,024
TB290CS	TB290 Cab Equipped with Steel Tracks	\$126,116
TB290CRA (w/ Angle Blade)	TB290 Cab (Rubber Tracks) with <b>Angle Blade</b> Angle Blade features 25 degree left and right angle, cylinder protective guards	\$131,772
TB290CSA	TB290 Cab (Steel Tracks) with <b>Angle Blade</b>	\$132,864
TB290CL (w/ Segmented Rubber Tracks)	TB290 Cab (above Equipped except with <b>Segmented Rubber Tracks</b> )	\$131,536
TB290CLA (w/ Angle Blade & Segmented Rubber Tracks)	TB290 Cab (above Equipped except with <b>Segmented Rubber Tracks</b> ) with <b>Angle Blade</b> , Angle Blade features 25 degree left and right angle, cylinder protective guards	\$138,284

**BASE MACHINE PRICE DOES NOT INCLUDE BUCKET**

### ATTACHMENTS

Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Hydraulic Thumb			
AQC-PH290I	INSTALLED	Hydraulic Pin Grabber Coupler (TB370) - Includes set of dead pins & hoses (Installed)	\$5,196.95
AQC-PH290	Field Installed	Hydraulic Pin Grabber Coupler (TB370) - Includes set of dead pins & hoses	\$4,946.95
ABE-290-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,549.80
ABE-290-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,644.30
ABE-290-PO36T		36" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$2,009.70
ATE-290I	INSTALLED	Hydraulic Thumb (4-tine) (Only compatible w/ 18" or larger Buckets	\$3,437.80
ATE-290K	Field Installed	Hydraulic Thumb (4-tine) (Only compatible w/ 18" or larger Buckets	\$3,187.80
DPK-290		Bucket Pin Kit (includes Hardware)	\$387.20

Tag Manual Coupler / Pin on Buckets / Hydraulic Thumb			
BTB07018		18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,329.70
BTB07024		24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,514.21
BTB07036		36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,894.40
BQC07000		Quick Coupler	\$1,350.33
BQC07018		18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,280.45
BQC07024		24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,382.54
BQC07036		36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,729.67
BQC07036D		36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,699.43
ATH290I	INSTALLED	Hydraulic thumb (Only compatible w/ 18" or larger Buckets	\$3,498.66
ATH290K	Field Installed	Hydraulic thumb (Only compatible with 18" and larger buckets	\$3,248.66

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
------------	---	---------





# TB280FR

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

## Zero Swing Excavator

### STANDARD EQUIPMENT

Operating Weight: 18,810 lbs.	ROPS/OPG enclosed cab w/ air conditioner/heat, windshield wiper, 12v power outlet and AM/FM/MP3 radio
Width: 7' 7"	Tilt-up operator's platform
Maximum Dig Depth: 14' 11"	Color 5.7" gauge panel with multi-function operator information center
Bucket Digging Force: 16,335 lbs.	10-way adjustable high back suspension seat
Horsepower / RPM: 69.2 / 2,000	Pilot operated joystick control with pattern change valve
Travel Speed: 1.7 / 3.2 mph	EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system
Auxiliary Flow: 39 gpm	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Second Aux Flow: 15 gpm	Side by side radiator and hydraulic cooler
Boom swing: Left 30°/ Right 15°	Variable displacement axial piston main hydraulic pump
Track Width: 17.7"	Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch
Side-to-Side (STS) offset boom system	Primary auxiliary continuous mode and one-way mode
Two speed travel with automatic shift down	Safety features include: large skylight with sun shade
Reinforced arm	travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding valve with lift alarm, mirrors and lights
Heavy duty dozer blade with float	
Auto idle	
TFM hardware standard equipment, service included through the standard warranty period (sn 178500473 ~	

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB280FRCR	TB280FR Cab Equipped with Rubber Tracks	\$128,960
TB280FRCS	TB280FR Cab Equipped with Steel Tracks	\$130,052
TB280FRCL (w/ Segmented Rubber Tracks)	TB280FR Cab Equipped with <b>Segmented Rubber Tracks</b>	\$135,472

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

#### Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Hydraulic Thumb

AQC-PH290I	INSTALLED	Hydraulic Pin Grabber Coupler (TB370) - Includes set of dead pins & hoses (Installed)	\$5,196.95
AQC-PH290	Field Installed Kit	Hydraulic Pin Grabber Coupler (TB370) - Includes set of dead pins & hose:	\$4,946.95
ABE-290-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,549.80
ABE-290-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,644.30
ABE-290-PO36T *		36" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$2,009.70
ATE-290I	INSTALLED	Hydraulic Thumb (4-tine) (Only compatible w/ 18" or larger Buckets)	\$3,437.80
ATE-290K	Field Installed Kit	Hydraulic Thumb (4-tine) (Only compatible w/ 18" or larger Buckets)	\$3,187.80
DPK-290		Bucket Pin Kit (includes Hardware)	\$387.20

#### Tag Manual Coupler / Pin on Buckets / Hydraulic Thumb

BTB07018		18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,329.70
BTB07024		24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,514.21
BTB07036 *		36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,894.40
BQC07000		Quick Coupler	\$1,350.33
BQC07018		18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,280.45
BQC07024		24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,382.54
BQC07036 *		36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,729.67
BQC07036D *		36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,699.43
ATH280FRI	INSTALLED	Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$3,498.66
ATH280FRK	Field Installed Kit	Hydraulic thumb (Only compatible with 18" and larger buckets)	\$3,248.66

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2" belt	\$91.00
------------	--	---------

\* **NOTE:** The Zero Swing front radius feature is only available for the standard bucket attachment (30" or smaller)



# TB2150

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

## Excavator

### STANDARD EQUIPMENT

Operating Weight: 34,480 lbs. (Rubber)	ROPS/OPG Level 2 cab
Dozer Blade Width: 8' 6"	Factory installed cab with automatic climate control, AM/FM/MP3 radio, wipe
Maximum Dig Depth: 18'	Two speed travel with automatic shift down
Bucket Digging Force: 22,190 lbs.	Travel alarm
Tail Swing Radius: 6' 6.7"	Arm & Boom holding valve with lift alarm
Horsepower / RPM: 114 / 2,000	Pattern change valve
EPA Final Tier 4 Compliant	Pilot operated joystick controls with safety lock out
Travel Speed: 1.9 / 3.4 mph	Wrap around counterweight with towers
Auxiliary Flow: (Primary) 59.0 gpm	Adjustable air suspension seat with retractable seat belt
Auxiliary Flow: (Secondary) 14.5 gpm	Primary and Secondary two-way auxiliary hydraulic circuits routed to the end of the arm
Boom Swing: Left 77° / Right 53°	Proportional thumb wheel control of both auxiliary hydraulic circuits
24" Wide Steel Tracks	Electrohydraulic push button controls of auxiliary hydraulic circuit (Primary Only)
Optional: 20" Rubber Track	Variable displacement axial piston main hydraulic pump
Optional: 20" Segmented Rubber Tracks	Multi function color monitor pane
	Heavy duty dozer blade with Floa

TFM hardware standard equipment, service included through the standard warranty period

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB2150CR	TB2150 Equipped with CAB OPG, Rubber Tracks, Dozer blade with float Auto Air Conditioner/Heat, Defroster, Windshield wiper and washer Control pattern selector valve, Travel alarm, Cab light, Auxiliary hydraulics (primary and secondary), Slide back front window, AM/FM/MP3 radio Air Suspension seat, Engine monitoring system	\$191,696
TB2150CS	TB2150 Equipped with CAB OPG, Steel Tracks, Dozer blade with float	\$193,643
TB2150CL (w/ Segmented Rubber Tracks)	TB2150 Cab (above Equipped except with <b>Segmented Rubber Tracks</b> )	\$201,761

**BASE MACHINE PRICE DOES NOT INCLUDE BUCKET**

### ATTACHMENTS

Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Hydraulic Thumb			
AQC-PH2150I	INSTALLED	Hydraulic Pin Grabber Coupler (TB2150) - Includes set of dead pins & hoses (Installed)	\$7,000.00
AQC-PH2150	Field Installed Kit	Hydraulic Pin Grabber Coupler (B2150) - Includes set of dead pins & hoses	\$6,750.00
ABE-2150-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$3,590.46
ABE-2150-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$3,864.60
ABE-2150-PO36T		36" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$4,787.28
ATE-2150LI	INSTALLED	Hyd Thumb LONG (4-tine) (Only compatible w/ 18" or larger Buckets)(for Hyd Coupler	\$8,283.03
ATE-2150LK	Field Installed Kit	Hyd Thumb LONG (4-tine) (Only compatible w/ 18" or larger Buckets)(for Hyd Coupler	\$8,033.03
ATE-2150I	INSTALLED	Hyd Thumb SHORT (4-tine) (Only compatible w/ 18" or larger Buckets)(for Pin on Bucket only	\$8,283.03
ATE-2150	Field Installed Kit	Hyd Thumb SHORT (4-tine) (Only compatible w/ 18" or larger Buckets)(for Pin on Bucket only	\$8,033.03

### Tag Manual Coupler / Pin on Buckets / Hydraulic Thumb

BTB114018		18" Pin-On Bucket (Capacity 0.41) (875 lbs)	\$3,598.70
BTB114024		24" Pin-On Bucket (Capacity 0.57) (1025 lbs)	\$3,864.60
BTB114030		30" Pin-On Bucket (Capacity 0.73) (1110 lbs)	\$4,437.74
BTB114036		36" Pin-On Bucket (Capacity 0.89) (1295 lbs)	\$4,798.26
BTB114042D		42" Pin-On Ditching Bucket (Capacity 0.50) (695 lbs)	\$3,395.83
BTB114048D		48" Pin-On Ditching Bucket (Capacity 0.60) (800 lbs)	\$3,655.41
BTB114054D		54" Pin-On Ditching Bucket (Capacity 0.70) (900 lbs)	\$3,925.02
BTB114060D		60" Pin-On Ditching Bucket (Capacity 0.80) (970 lbs)	\$4,562.28
BTH1140I	INSTALLED	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs	\$9,424.84
BTH1140K	Field Installed Kit	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs	\$9,174.84
BTH1140LI	INSTALLED	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler	\$9,424.84
BTH1140LK	Field Installed Kit	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler	\$9,174.84

### FIELD INSTALLED OPTIONS

K1573400001	3" Retractable seat belt in lieu of standard 2'	\$121.39
TB1140BKTPINS	Bucket Pin Kit (includes Hardware)	\$482.00

Prices and specifications  
subject to change without notice

P-15-A  
Prices are in US Dollar

Prices are F.O.B. Pendergrass,GA  
Effective 1 January 2023



# TB2150R

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

## Fixed Boom Excavator

### STANDARD EQUIPMENT

Operating Weight: 34,215 lbs. (Rubber)	ROPS/OPG Level 2 cab
Dozer Blade Width: 8' 6"	Factory installed cab with automatic climate control, AM/FM/MP3 radio, wipe
Maximum Dig Depth: 19' 9.4"	Two speed travel with automatic shift down
Bucket Digging Force: 22,256 lbs.	Travel alarm
Tail Swing Radius: 5' 7"	Arm & Boom holding valve with lift alarm
Horsepower / RPM: 114 / 2,000	Pattern change valve
EPA Final Tier 4 Compliant	Pilot operated joystick controls with safety lock out
Travel Speed: 1.9 / 3.4 mph	Wrap around counterweight
Auxiliary Flow: (Primary) 59.0 gpm	Adjustable air suspension seat with retractable seat belt
Auxiliary Flow: (Secondary) 14.5 gpm	Primary and Secondary two-way auxiliary hydraulic circuits routed to the end of the arm
20" Rubber Track	Proportional thumb wheel control of 1st and 2nd auxiliary hydraulic circuit
Optional: 20" Segmented Rubber Track	Electrohydraulic push button controls of primary auxiliary hydraulic circuit
Optional: 24" Steel Tracks	Variable displacement axial piston main hydraulic pump
Optional: 28" Wide Steel Tracks	Multi function color monitor pane
	Heavy duty dozer blade with float

TFM hardware standard equipment, service included through the standard warranty period

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB2150R-CR	TB2150R Equipped with CAB OPG, Rubber Tracks, Dozer Blade with Float Auto Air Conditioner/Heat, Defroster, Windshield Wiper and Washer Control Pattern Selector Valve, Travel Alarm, Cab Light, Auxiliary Hydraulics (primary and secondary), Slide Back Front Window, AM/FM/MP3 Radio Air Suspension Seat, Engine Monitoring System	\$186,900
TB2150R-CSS	TB2150R Equipped with CAB OPG, 24" Steel Tracks, Dozer blade with float	\$188,790
TB2150R-CWS	TB2150R Equipped with CAB OPG, 28" Steel Tracks, Dozer blade with float	\$191,415
TB2150R-CL (w/ Segmented Rubber Tracks)	TB2150R Cab (above Equipped except with 20" <b>Segmented Rubber Tracks</b> )	\$197,190

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Hydraulic Thumb			
AQC-PH2150I	INSTALLED	Hydraulic Pin Grabber Coupler (TB2150) - Includes set of dead pins & hoses (Installed)	\$7,000.00
AQC-PH2150	Field Installed Kit	Hydraulic Pin Grabber Coupler (B2150) - Includes set of dead pins & hose:	\$6,750.00
ABE-2150-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$3,590.46
ABE-2150-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$3,864.60
ABE-2150-PO36T		36" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$4,787.28
ATE-2150LI	INSTALLED	Hyd Thumb LONG (4-tine) (Only compatible w/ 18" or larger Buckets)(for Hyd Coupler	\$8,283.03
ATE-2150LK	Field Installed Kit	Hyd Thumb LONG (4-tine) (Only compatible w/ 18" or larger Buckets)(for Hyd Coupler	\$8,033.03
ATE-2150I	INSTALLED	Hyd Thumb SHORT (4-tine) (Only compatible w/ 18" or larger Buckets)(for Pin on Bucket only	\$8,283.03
ATE-2150	Field Installed Kit	Hyd Thumb SHORT (4-tine) (Only compatible w/ 18" or larger Buckets)(for Pin on Bucket only	\$8,033.03

Tag Manual Coupler / Pin on Buckets / Hydraulic Thumb			
BTB114018		18" Pin-On Bucket (Capacity 0.41) (875 lbs)	\$3,598.70
BTB114024		24" Pin-On Bucket (Capacity 0.57) (1025 lbs)	\$3,864.60
BTB114030		30" Pin-On Bucket (Capacity 0.73) (1110 lbs)	\$4,437.74
BTB114036		36" Pin-On Bucket (Capacity 0.89) (1295 lbs)	\$4,798.26
BTB114042D		42" Pin-On Ditching Bucket (Capacity 0.50) (695 lbs)	\$3,395.83
BTB114048D		48" Pin-On Ditching Bucket (Capacity 0.60) (800 lbs)	\$3,655.41
BTB114054D		54" Pin-On Ditching Bucket (Capacity 0.70) (900 lbs)	\$3,925.02
BTB114060D		60" Pin-On Ditching Bucket (Capacity 0.80) (970 lbs)	\$4,562.28
BTH1140I	INSTALLED	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs	\$9,424.84
BTH1140K	Field Installed Kit	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs	\$9,174.84
BTH1140LI	INSTALLED	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler	\$9,424.84
BTH1140LK	Field Installed Kit	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler	\$9,174.84

### FIELD INSTALLED OPTIONS

K1573400001	3" Retractable seat belt in lieu of standard 2'	\$121.39
TB1140BKTPINS	Bucket Pin Kit (includes Hardware)	\$482.00

Prices and specifications  
subject to change without notice

P-15-B  
Prices are in US Dollar

Prices are F.O.B. Pendergrass,GA  
Effective 1 January 2023



# TL6

## Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

### STANDARD EQUIPMENT

Operating Weight: 7485 lbs.	Radial boom design
Overall Width Without Bucket: 5' 0.2"	ROPS/FOPS tilt-up operators compartment w/ rearview mirrors
Tipping Load (SAE 732) 5,269 lbs.	Back-up alarm, Top and rear windows
Rated Operating Capacity (ROC)(SAE J818): 1,841 lbs	Automatic fuel bleed system
Bucket Digging Force: 5,930 lbs.	Pilot operated joystick controls
Horsepower / RPM: 65.2 / 2700	Universal quick attach mounting bracket
Travel Speed: 4 / 6mph	Suspension seat with retractable seatbelt
Auxiliary Flow: 17.8 gpm	One and two way auxiliary hydraulics
Ground Pressure: 4.8 psi	Electronic engine monitoring system
Maximum Lift Height to Bucket Pin: 9' 6.4"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Reach Fully Raised: 1' 10"	Proportional slide switch control auxiliary hydraulics with detent function
Canopy/Cab height: 6' 5"	Hydraulic self-leveling bucket
	Flat face, pressure releasing Hydraulic Couplers
	Standard 14-pin connector with push button control
	Dual element air cleaner
	Push button boom float with detent
	Foot Throttle

EPA Final Tier 4 Turbocharged Engine with DPF

TFM hardware standard equipment, service included through the standard warranty period

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL6R	TL6 with ROPS/FOPS Canopy, Rubber tracks	<b>\$52,629</b>
TL6CR	TL6 with ROPS/FOPS Cab with Air Conditioning/Heat Defroster, Rubber Tracks, Hydraulic quick attach, Swing out door, AM/FM/MP3 Radio	<b>\$58,727</b>

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

### ATTACHMENTS

ABLU-60S-047	60" HD smooth dirt bucket with bolt-on edge, 12.7 cubic feet capacity	<b>\$2,283.59</b>
ABLU-60T-047	60" HD dirt bucket with 7 teeth, 12.7 cubic feet capacity	<b>\$2,404.03</b>
BTL867	67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity	<b>\$2,420.99</b>
BTL867T	67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity	<b>\$2,349.06</b>
TDZR84	7' six way dozer blade	<b>\$9,893.66</b>
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	<b>\$1,227.87</b>

### FIELD INSTALLED OPTIONS

K28843001	Counter Weight Kit (332 lbs)(ROC: 2041 lbs)	<b>\$1,300.00</b>
1914199948	3" Retractable seat belt in lieu of standard 2'	<b>\$91.00</b>
K28843005	TL6 hydraulic quick attach coupler kit (for Canopy unit)	<b>\$1,800.15</b>



# TL8R2

## Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

### STANDARD EQUIPMENT

Operating Weight: 8,807 lbs.	Radial lift design
Overall Width Without Bucket:(15.7" Tracks) 65.5"	ROPS/FOPS tilt-up operators compartment w/ rear view camera
Tipping Load (SAE 732) 6,041 lbs.	Back-up alarm, Top and rear windows
Rated Operating Capacity (ROC)(SAE J818): 2,116 lbs	Automatic fuel bleed system
Bucket Digging Force: 6,204 lbs.	Pilot operated joystick controls
Horsepower / RPM: 73.2 / 2,600	Universal quick attach mounting bracket
Travel Speed: 4.7 / 7 mph	Deluxe high back suspension seat with retractable seatbelt
Auxiliary Flow: 19.1 gpm	One and two way auxiliary hydraulics
Ground Pressure: 4.5 psi	Electronic engine monitoring system
Maximum Lift Height to Bucket Pin: 10' 1.2"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Reach Fully Raised: 2' 4.3"	Proportional slide switch control auxiliary hydraulics with detent function
Canopy/Cab height: 7' 3.8"	Hydraulic self-leveling bucket
	Flat face, pressure releasing Hydraulic Couplers
	Standard 14-pin connector with push button control
	Dual element air cleaner with standard pre-cleaner
	Push button boom float with detent
	Foot Throttle

TFM hardware standard equipment, service included through the standard warranty period

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL8R2-R	TL8R2 with ROPS/FOPS Canopy, 15" Rubber tracks	<b>\$61,807</b>
TL8R2-CR	TL8R2 with ROPS/FOPS Cab with Air Conditioning/Heat Defroster, 15" Rubber Tracks, Hydraulic quick attach,AM/FM/MP3 Radio, Roll up door	<b>\$68,578</b>

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

#### ATTACHMENTS

BTL867	67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity	<b>\$2,420.99</b>
BTL867T	67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity	<b>\$2,349.06</b>
ABLU-72S-057	72" Low Profile Bucket - Smooth with Bolt on Cutting Edge	<b>\$2,485.76</b>
ABLU-72T-057	72" Low Profile Bucket -Tooth	<b>\$2,442.45</b>
BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	<b>\$2,808.70</b>
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	<b>\$2,817.79</b>
TDZR84	7' six way dozer blade	<b>\$9,893.66</b>
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	<b>\$1,227.87</b>

#### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2'	<b>\$91.00</b>
K48834204	3-point 2" seat belt kit in lieu of standard 2'	<b>\$150.00</b>
K28843001	Counter Weight Kit (332 lbs)(ROC: 2314 lbs)	<b>\$1,300.00</b>
K48800115	Level 2 Roof Guard Kit	<b>\$888.25</b>
K48887001	Hydraulic quick attach coupler kit (for Canopy unit)	<b>\$1,998.87</b>



# TL8R2

## Track Loader

### HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

#### STANDARD EQUIPMENT

Operating Weight: 9,182 lbs.	Radial lift design
Overall Width Without Bucket: (15.7" Tracks) 65.5"	ROPS/FOPS tilt-up operators compartment w/ rear view camera
Tipping Load (SAE 732) 6,041 lbs.	Back-up alarm, Top and rear windows
Rated Operating Capacity (ROC)(SAE J818): 2,116 lbs	Automatic fuel bleed system
Bucket Digging Force: 6,204 lbs.	Pilot operated joystick controls
Horsepower / RPM: 73.2 / 2,600	Universal quick attach mounting bracket
Travel Speed: 4.7 / 7 mph	Deluxe high back suspension seat with retractable seatbelt
Auxiliary Flow: 19.1 gpm STD / 33.8 gpm HF	One and two way auxiliary hydraulics
Ground Pressure: 4.5 psi	Electronic engine monitoring system
Maximum Lift Height to Bucket Pin: 10' 1.2"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Reach Fully Raised: 2' 4.3"	Proportional slide switch control auxiliary hydraulics with detent function
Cab height: 7' 6.1"	Hydraulic self-leveling bucket
1/2" Lexan roll up door	Flat face, pressure releasing Hydraulic Couplers
EPA Final Tier 4 turbocharged engine with DPF	Standard 14-pin connector with push button control
	Dual element air cleaner with standard pre-cleaner
	Push button boom float with detent
	Foot Throttle

TFM hardware standard equipment, service included through the standard warranty period

#### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL8R2-CRH	TL8R2 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, Rubber Tracks, Hydraulic quick attach, Lexan Roll up door and HIGH FLOW auxiliary hydraulics (33 gpm) AM/FM/MP3 Radio, 2-speed auto-shift with creep mode	<b>\$71,744</b>

#### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

#### ATTACHMENTS

BTL867	67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity	<b>\$2,420.99</b>
BTL867T	67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity	<b>\$2,349.06</b>
ABLU-72S-057	72" Low Profile Bucket - Smooth with Bolt on Cutting Edge	<b>\$2,485.76</b>
ABLU-72T-057	72" Low Profile Bucket -Tooth	<b>\$2,442.45</b>
BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	<b>\$2,808.70</b>
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	<b>\$2,817.79</b>
TDZR84	7' six way dozer blade	<b>\$9,893.66</b>
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	<b>\$1,227.87</b>

#### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	<b>\$91.00</b>
K48834204	3-point 2" seat belt kit in lieu of standard 2"	<b>\$150.00</b>
K28843001	Counter Weight Kit (332 lbs)(ROC: 2314 lbs)	<b>\$1,300.00</b>
K48800115	Level 2 Roof Guard Kit	<b>\$888.25</b>



# TL10V2

## Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

### STANDARD EQUIPMENT

Operating Weight: 9,950 lbs.	Vertical boom design
Overall Width Without Bucket: 5' 8.5"	Tilt-up operators compartment
Tipping Load (SAE 732) 7,205 lbs.	Electronic dial type throttle and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 2,522 lbs	Back-up alarm
Bucket Digging Force: 6,520 lbs.	Top and rear windows
Horsepower / RPM: 74.3 / 2,600	Automatic fuel bleed system
Travel Speed: 4.8 / 7.0	Pilot operated joystick controls
Auxiliary Flow: 18.8 gpm	Universal quick attach mounting bracket
Ground Pressure: 4.9 PSI	Deluxe high back suspension seat with retractable seatbelt
Maximum Lift Height to Bucket Pin: 10' 4.8"	One and two way auxiliary hydraulics
Reach Fully Raised: 3' 1.4"	Electronic engine monitoring system
Canopy/Cab height: 7' 5.4"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Selectable working modes	Proportional thumb wheel control auxiliary hydraulics with detent function
Front & rear LED working lights	Hydraulic self-leveling bucket
ROPS/FOPS Level 1 operator protection	Flat face, pressure relieving Hydraulic Couplers
Multi function color monitor	Standard 14-pin connector with push button control
Active power control power management system	Dual element air cleaner
	Push button boom float with detent

TFM hardware standard equipment, service included through the standard warranty period

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL10V2--R	TL10 with ROPS/FOPS Canopy, 15.7" Rubber tracks	<b>\$71,089</b>
TL10V2-RR (w/ RC)	TL10R (above Equipped) with <b>Ride Control*</b>	<b>\$71,854</b>
TL10V2-RP (w/ PC)	TL10R (above Equipped) with <b>Pattern Control*</b>	<b>\$72,127</b>
TL10V2-RRP (w/ RC & PC)	TL10R (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>	<b>\$72,891</b>

TL10V2-CR	TL10 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 15.7" Rubber Tracks, Hydraulic quick attach, Roll up door, AM/FM/MP3 Radio	<b>\$78,078</b>
TL10V2-CRR (w/ RC)	TL10CR (above Equipped) with <b>Ride Control*</b>	<b>\$78,842</b>
TL10V2-CRP (w/ PC)	TL10CR (above Equipped) with <b>Pattern Control*</b>	<b>\$79,115</b>
TL10V2-CRRP (w/ RC & PC)	TL10CR (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>	<b>\$79,880</b>

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

### ATTACHMENTS / OPTIONS

BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	<b>\$2,808.70</b>
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	<b>\$2,817.79</b>
TDZR84	7' six way dozer blade	<b>\$9,893.66</b>
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	<b>\$1,227.87</b>

### FIELD INSTALLED OPTIONS

K28843001	Counter Weight Kit (332 lbs)(ROC: 2718 lbs)	<b>\$1,300.00</b>
19141-99948	3" retractable seat belt in lieu of standard 2"	<b>\$91.00</b>
K48847001	Hydraulic quick attach coupler kit (for Canopy unit)	<b>\$1,998.87</b>



# TL10V2

## Track Loader

### HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

#### STANDARD EQUIPMENT

Operating Weight: 10,270 lbs.	Vertical boom design
Overall Width Without Bucket: 5' 8.5"	Tilt-up operators compartment
Tipping Load (SAE 732) 7,205 lbs.	Electronic dial type throttle and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 2,522 lbs	Back-up alarm
Bucket Digging Force: 6,520 lbs.	Top and rear windows
Horsepower / RPM: 74.3 / 2,600	Automatic fuel bleed system
Travel Speed: 4.8 / 7.0	Pilot operated joystick controls
Auxiliary Flow (SP1): 18.8 gpm STD / 32.8 gpm HF	Universal quick attach mounting bracket
Ground Pressure: 5.1 PSI	Deluxe high back suspension seat with retractable seatbelt
Maximum Lift Height to Bucket Pin: 10' 4.8"	One and two way auxiliary hydraulics
Reach Fully Raised: 3' 1.4"	Electronic engine monitoring system
Cab height: 7' 6.9"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Front & rear LED working lights	Proportional thumb wheel control auxiliary hydraulics with detent function
ROPS / FOPS Level 2 operator protection	Hydraulic self-leveling bucket
Multi function color monitor	Flat face, pressure relieving Hydraulic Couplers
	Standard 14-pin connector with push button control
	Dual element air cleaner
	Push button boom float with detent

TFM hardware standard equipment, service included through the standard warranty period

#### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL10V2-CRH	TL10 with Cab with Air Conditioning/Heat, Defroster, 15.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door, AM/FM/MP3 Radio, HIGH FLOW Auxiliary Hydraulics	\$81,409
TL10V2-CRHR (w/ RC)	TL10CRH (above Equipped) with <b>Ride Control*</b>	\$82,173
TL10V2-CRHP (w/ PC)	TL10CRH (above Equipped) with <b>Pattern Control*</b>	\$82,446
TL10V2-CRHRP (w/ RC & PC)	TL10CRH (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>	\$83,210

#### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

#### ATTACHMENTS / OPTIONS

BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	\$2,808.70
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	\$2,817.79
TDZR84	7' six way dozer blade	\$9,893.66
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	\$1,227.87

#### FIELD INSTALLED OPTIONS

19141-99948	3" retractable seat belt in lieu of standard 2"	\$91.00
K28843001	Counter Weight Kit (332 lbs)(ROC: 2718 lbs)	\$1,300.00





# TL12R2

## Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

### STANDARD EQUIPMENT

Operating Weight: 12,300 lbs.	Radial boom design
Overall Width Without Bucket: 6' 5.2"	Tilt-up operators compartment
Tipping Load (SAE 732) 8,629 lbs.	Electronic dial type throttle and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 2,975 lbs	Back-up alarm
Bucket Digging Force: 8,210 lbs.	Top and rear windows
Horsepower / RPM: 111.3 / 2,400	Automatic fuel bleed system
Travel Speed: 5.0 / 7.8 mph	Pilot operated joystick controls
Auxiliary Flow: 23.2 gpm	Universal quick attach mounting bracket
Ground Pressure: 4.58 psi	Deluxe high back suspension seat with retractable seatbelt
Maximum Lift Height to Bucket Pin: 10' 6"	One and two way auxiliary hydraulics
Reach Fully Raised: 3' 1.8"	Electronic engine monitoring system
Canopy/Cab height: 7' 7"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Active power control power management system	Proportional thumb wheel control auxiliary hydraulics with detent function
Front & rear LED working lights	Hydraulic self-leveling bucket
ROPS/FOPS Level 1 operator protection	Flat face, pressure relieving Hydraulic Couplers
Multi function color monitor	Standard 14-pin connector with push button control
Selectable working modes	Dual element air cleaner
	Push button boom float with detent

TFM hardware standard equipment, service included through the standard warranty period

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12R2-R	TL12 with Canopy, 17.7" Rubber tracks	<b>\$87,906</b>
TL12R2-RR (w/ RC)	TL12R (above Equipped) with Ride Control*	<b>\$88,670</b>
TL12R2-RP (w/ PC)	TL12R (above Equipped) with Pattern Control*	<b>\$88,943</b>
TL12R2-RRP (w/ RC & PC)	TL12R (above Equipped) with Ride Control & Pattern Control*	<b>\$89,708</b>

TL12R2-CR	TL12 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door, AM/FM/MP3 Radio	<b>\$95,059</b>
TL12R2-CRR (w/ RC)	TL12CR (above Equipped) with Ride Control*	<b>\$95,823</b>
TL12R2-CRP (w/ PC)	TL12CR (above Equipped) with Pattern Control*	<b>\$96,096</b>
TL12R2-CRRP (w/ RC & PC)	TL12CR (above Equipped) with Ride Control & Pattern Control*	<b>\$96,860</b>

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

### ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	<b>\$3,125.37</b>
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	<b>\$3,115.18</b>
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity	<b>\$3,538.41</b>
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth	<b>\$3,468.31</b>
TDZR96	8' six way dozer blade	<b>\$10,281.16</b>
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	<b>\$1,227.87</b>

### FIELD INSTALLED OPTIONS

19141-99948	3" retractable seat belt in lieu of standard 2"	<b>\$91.00</b>
1914100145	3-point 2" seat belt kit in lieu of standard 2"	<b>\$288.86</b>
K48867001	Hydraulic quick attach coupler kit (for Canopy unit)	<b>\$2,198.76</b>
K28863001	Counter Weight Kit (450 lbs) ( ROC: 3,291 lbs)	<b>\$1,875.00</b>
TBK56104	BUMPER KIT (TL12V/R ONLY)	<b>\$4,815.66</b>



# TL12R2

Track Loader

HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel: 706-693-3600 Fax: 706-693-3725

www.takeuchi-us.com

## STANDARD EQUIPMENT

Operating Weight: 12,590 lbs.	Radial boom design
Overall Width Without Bucket: 6' 5.2"	Tilt-up operators compartment
Tipping Load (SAE 732) 8,629 lbs.	Electronic dial type throttle and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 2,975 lbs	Back-up alarm
Bucket Digging Force: 8,210 lbs.	Top and rear windows
Horsepower / RPM: 111.3 / 2,400	Automatic fuel bleed system
Travel Speed: 5.0 / 7.8 mph	Pilot operated joystick controls
Auxiliary Flow (SP1): 23.2 gpm STD / 40.4 gpm HF	Universal quick attach mounting bracket
Auxiliary Flow (SP2): 23.2 gpm	Deluxe high back suspension seat with retractable seatbelt
Ground Pressure: 4.68 psi	One and two way auxiliary hydraulics
Maximum Lift Height to Bucket Pin: 10' 6"	Electronic engine monitoring system
Reach Fully Raised: 3' 1.8"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Cab height: 7' 9.7"	Proportional thumb wheel control auxiliary hydraulics with detent function
Active power control power management system	Hydraulic self-leveling bucket
Front & rear LED working lights	Flat face, pressure relieving Hydraulic Couplers
ROPS / FOPS Level 2 operator protection	Standard 14-pin connector with push button control
Multi function color monitor	Dual element air cleaner
Selectable working modes	Push button boom float with detent
TFM hardware standard equipment, service included through the standard warranty period	

## BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12R2-CRH	TL12 with Cab with Air Conditioning/Heat, Defroster, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door, AM/FM/MP3 Radio, HIGH FLOW Auxiliary Hydraulics	\$98,335
TL12R2-CRHR (w/ RC)	TL12CRH (above Equipped) with <b>Ride Control*</b>	\$99,099
TL12R2-CRHP (w/ PC)	TL12CRH (above Equipped) with <b>Pattern Control*</b>	\$99,372
TL12R2-CRHRP (w/ RC & PC)	TL12CRH (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>	\$100,136

## BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

## ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$3,125.37
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	\$3,115.18
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity	\$3,538.41
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth	\$3,468.31
TDZR96	8' six way dozer blade	\$12,281.16
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	\$1,227.87

## FIELD INSTALLED OPTIONS

1914199948	3" retractable seat belt in lieu of standard 2"	\$91.00
1914100145	3-point 2" seat belt kit in lieu of standard 2"	\$288.86
K28863001	Counter Weight Kit (450 lbs) ( ROC: 3,291 lbs)	\$1,875.00
TWK56088	BUMPER KIT, hydraulic winch (TL12V/R ONLY)	\$12,096.82
TBK56104	BUMPER KIT (TL12V/R ONLY)	\$4,815.66



# TL12V2

## Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

### STANDARD EQUIPMENT

Operating Weight (Canopy/Cab): 12,860 lb / 13,190 lb	Vertical boom design
Overall Width Without Bucket: 6' 5.2"	Tilt-up operators compartment
Tipping Load (SAE 732) 11,737 lbs.	Electronic dial type throttle and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 4,107 lbs	Back-up alarm
Bucket Digging Force: 7,874 lbs.	Top and rear window
Horsepower / RPM: 111.3 / 2,400	Automatic fuel bleed system
Travel Speed: 5.0 / 7.8 mph	Pilot operated joystick controls
Auxiliary Flow: 23.2 gpm	Universal quick attach mounting bracket
Ground Pressure (Canopy / Cab): 4.8 psi / 4.9 psi	Deluxe high back suspension seat with retractable seatbelt
Maximum Lift Height to Bucket Pin: 10' 10"	One and two way auxiliary hydraulics
Reach Fully Raised: 3' 0.4"	Electronic engine monitoring system
Canopy/Cab height: 7' 7.7"	Electrohydraulic push button controls of auxiliary hydraulic circuit
ROPS/FOPS Level 1 operators protection	Proportional slide switch control auxiliary hydraulics with detent function
Front & rear LED working lights	Hydraulic self-leveling bucket
Selectable working modes	Flat face, pressure relieving hydraulic couplers
Active power control power management system	Standard 14-pin connector with push button control
Multi function color monitor	Dual element air cleaner
	Push button boom float with detent

TFM hardware standard equipment, service included through the standard warranty period

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12V2-R	TL12V with Canopy, 17.7" Rubber tracks	<b>\$91,182</b>
TL12V2-RR (w/ RC)	TL12VR (above Equipped) with Ride Control*	<b>\$91,946</b>
TL12V2-RP (w/ PC)	TL12VR (above Equipped) with Pattern Control*	<b>\$92,219</b>
TL12V2-RRP (w/ RC & PC)	TL12VR (above Equipped) with Ride Control & Pattern Control*	<b>\$92,984</b>

TL12V2-CR	TL12V with ROPS/FOPS Cab, Air Conditioning/Heat, Defroster, AM/FM/MP3 Radio, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door	<b>\$98,335</b>
TL12V2-CRR (w/ RC)	TL12VCR (above Equipped) with Ride Control*	<b>\$99,099</b>
TL12V2-CRP (w/ PC)	TL12VCR (above Equipped) with Pattern Control*	<b>\$99,372</b>
TL12V2-CRRP (w/ RC & PC)	TL12VCR (above Equipped) with Ride Control & Pattern Control*	<b>\$100,136</b>

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

### ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	<b>\$3,125.37</b>
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	<b>\$3,115.18</b>
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity	<b>\$3,538.41</b>
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth - 27 cu.ft. capacity	<b>\$3,468.31</b>
TDZR96	8' six way dozer blade	<b>\$10,281.16</b>
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	<b>\$1,227.87</b>

### FIELD INSTALLED OPTIONS

1914199948	3" retractable seat belt in lieu of standard 2"	<b>\$91.00</b>
1914100145	3-point 2" seat belt kit in lieu of standard 2"	<b>\$288.86</b>
K48857001	Hydraulic quick attach coupler kit (for Canopy unit)	<b>\$2,298.70</b>
K28863001	Counter Weight Kit (450 lbs) ( ROC: 4,815 lbs)	<b>\$1,875.00</b>
TBK56104	BUMPER KIT (TL12V/R ONLY)	<b>\$4,815.66</b>

Prices and specifications  
subject to change without notice

P-20-A  
Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA  
Effective 1 January 2023



# TL12V2

Track Loader

HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel: 706-693-3600 Fax: 706-693-3725

www.takeuchi-us.com

## STANDARD EQUIPMENT

Operating Weight: 13,190 lbs.	Vertical boom design
Overall Width Without Bucket: 6' 5.2"	ROPS/FOPS tilt-up operators compartment
Tipping Load (SAE 732) 11,737 lbs.	Electronic dial type throttle and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 4,107 lbs	Back-up alarm
Bucket Digging Force: 7,874 lbs.	Top and rear window
Horsepower / RPM: 111.3 / 2,400	Automatic fuel bleed system
Travel Speed: 5.0 / 7.8 mph	Pilot operated joystick controls
Auxiliary Flow (Std / High Flow): 23.2 gpm / 40.4 gpm	Universal quick attach mounting bracket
Ground Pressure: 4.9 psi	Deluxe high back suspension seat with retractable seatbelt
Maximum Lift Height to Bucket Pin: 10' 10"	One and two way auxiliary hydraulics
Reach Fully Raised: 3' 0.4"	Electronic engine monitoring system
Cab height: 7' 9.7"	Electrohydraulic push button controls of auxiliary hydraulic circuit
ROPS/FOPS Level 2 operators protection	Proportional slide switch control auxiliary hydraulics with detent function
Front & rear LED working lights	Hydraulic self-leveling bucket
Selectable working modes	Flat face, pressure relieving hydraulic couplers
Active power control power management system	Standard 14-pin connector with push button control
Multi function color monitor	Dual element air cleaner
	Push button boom float with detent

TFM hardware standard equipment, service included through the standard warranty period

## BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12V2-CRH	TL12 with Cab with Air Conditioning/Heat, Defroster, AM/FM/MP3 Radio, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door HIGH FLOW Auxiliary Hydraulics	\$101,611
TL12V2-CRHR (w/ RC)	TL12VCRH (above Equipped) with <b>Ride Control*</b>	\$102,375
TL12V2-CRHP (w/ PC)	TL12VCRH (above Equipped) with <b>Pattern Control*</b>	\$102,648
TL12V2-CRHRP (w/ RC & PC)	TL12VCRH (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>	\$103,412

## BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

## ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$3,125.37
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	\$3,115.18
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity	\$3,538.41
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth - 27 cu.ft. capacity	\$3,468.31
TDZR96	8' six way dozer blade	\$10,281.16
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	\$1,227.87

## FIELD INSTALLED OPTIONS

1914199948	3" retractable seat belt in lieu of standard 2"	\$91.00
1914100145	3-point 2" seat belt kit in lieu of standard 2"	\$288.86
K28863001	Counter Weight Kit (450 lbs) ( ROC: 4,815 lbs)	\$1,875.00
TWK56088	BUMPER KIT, hydraulic winch (TL12V/R HF ONLY)	\$12,096.82
TBK56104	BUMPER KIT (TL12V/R ONLY)	\$4,815.66



# TW60

Wheel Loader

SERIES 2

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

## STANDARD EQUIPMENT

Operating Weight: 10,692 lbs	ROPS / FOPS Level 1 Cab
Tip Load, Straight: 6,724 lbs	Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost
Bucket Breakout Force: 5,822 lbs	LCD Gauge panel with multi-function operator information center
Lift Arm Breakout Force: 6,675 lb	Suspension Seat
HP / RPM: 61 / 2300	Single control handle for direction (F/R) and loader functions
Travel Speed (Max): 12.4 mph	EPA Final Tier 4 Yanmar turbocharged, intercooled engine 4TNV86CHT-M
Auxiliary Flow: 15.8 gpm	100% Front and rear differential lock
Maximum Height to Bucket Pin: 10" 3.2"	Universal skid steer hydraulic coupler
Height: 8' 1.4'	Bucket float
Articulation: 40 / 40	Bucket level indicator
Reach Fully Raised: 26.4"	Mechanical bucket positioning
	Safety features include: back up alarm, lights, retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights), front driving lights, front and rear hazard and directional indicators

## ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

## BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TW60C2	TW60-2 Cab	\$96,663
TW60C2HS	TW60 Cab with High Speed Road Gear (17 mph max speed)	\$98,000

**BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES**

## TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

BTW65TIREHD	Heavy Duty Construction Tire Assy for TW602 / TW65 / TW80 (4 x Tire Assy)	\$5,280.00
-------------	---	------------

## ATTACHMENTS

BTW60-276	Bucket (76" General Purpose) (1.11 cu. Yd) (SSL Hookup) for TW60-2	\$3,620.93
BTW60-276A	Blade, bolt-on (76") (For BTW60-276)	\$731.88
BTW60-2PF	48" Fork Assy for TW60-2 (Rated 6,000 lbs) (SSL Hookup)	\$2,792.71

## FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
------------	---	---------



# TW80

Wheel Loader

SERIES 3

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

#### STANDARD EQUIPMENT

Operating Weight: 12,700 lbs	Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost
Tip Load, Straight: 10,065 lbs	LCD Gauge panel with multi-function operator information center with diagnostics and anti-theft capabilities
Bucket Breakout Force: 13,690 lbs	Deluxe suspension seat
Lift Arm Breakout Force: 11,802 lb	Pilot operator loader joystick control
HP / RPM: 73 / 2200	EPA Final Tier 4 turbocharged engine with DOC and engine monitoring system
Travel Speed (Max): 12.4 mph	Side by side radiator and hydraulic oil cooler
Auxiliary Flow: 16.4 gpm	Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick
Maximum Height to Bucket Pin: 11' 1"	100% Front and rear differential lock
Height: 8' 11.5"	Euro style attachment mount with hydraulic coupler
Articulation: 40 / 40	Bucket float
Reach Fully Raised: 29"	Mechanical bucket positioning
ROPS / FOPS Cab	Safety features include: back up alarm, lights, retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights), front driving lights, front and rear hazard and directional indicators

#### ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

#### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TW80C3	TW80 Cab (requires 90 + days)	<b>\$109,722</b>
TW80C3HS	TW80 Cab, High Speed Road Gear (24.8 mph max speed), & Ride Control	<b>\$114,707</b>
TW80C3HH	TW80 Cab, High Flow Auxiliary Hydraulics (26 gpm), High Speed Road Gear (24.8 mph max speed), & Ride Control (Requires 90 + days)	<b>\$120,270</b>

**BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES**

#### TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

BTW65TIREHD	Heavy Duty Construction Tire Assy for TW65 / TW80 (4 x Tire Assy)	<b>\$5,280.00</b>
-------------	---	-------------------

#### ATTACHMENTS

BTW8082	81.5" General Purpose Bucket (1.3 cu. Yd) for TW80	<b>\$3,303.72</b>
BTW8082A	82" Bolt-on Blade for BTW8082	<b>\$421.80</b>
BTWPF48	48" Combo Fork Assy for all TW's (Rated 8000 lb)	<b>\$3,146.40</b>
BTWUNIADP	Combo Hitch to Universal SSL Adapter TW50/60/65/80	<b>\$2,630.89</b>

#### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	<b>\$91</b>
TWFASTERKIT	TW Series Coupler Kit	<b>\$205.65</b>
TWCOUPLERKIT	TW Series Coupler Kit for HIGH FLOW UNITS ONLY	<b>\$223.30</b>



# TW95

## Wheel Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel: 706-693-3600 Fax: 706-693-3725  
www.takeuchi-us.com

### STANDARD EQUIPMENT

Operating Weight: 17,417 lbs	Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost
Tip Load, Straight: 14,388 lbs	LCD Gauge panel with multi-function operator information center with diagnostics and anti-theft capabilities
Bucket Breakout Force: 16,186 lbs	Deluxe suspension seat
Lift Arm Breakout Force: 18,434 lbs	Pilot operator loader joystick control
HP / RPM: 114 / 2200	EPA Final Tier 4 turbocharged engine with DOC/SCR exhaust after treatment system
Travel Speed (Max): 24.8 mph	Side by side radiator and hydraulic oil cooler
Auxiliary Flow: 26.4 gpm	Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick
Maximum Height to Bucket Pin: 11' 10.9"	100% Front and rear differential lock
Height: 9' 7.4"	Euro style attachment mount with hydraulic coupler
Articulation: 40 /40	Bucket float
Reach Fully Raised: 32.3"	Return to dig
ROPS / FOPS Level 2 Cab	Safety features include: back up alarm, lights, retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights), front driving lights, front and rear hazard and directional indicators

### ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TW95C2HS	TW95 Cab, High Speed Road Gear, & Ride Control	<b>\$169,360</b>

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES

### TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

BTW95TIREHDSSET	Heavy Duty Radial Tire Assy for TW95 500/70R24 (Set of 4)	<b>\$12,452.00</b>
-----------------	---	--------------------

### ATTACHMENTS

BTW95952YDW-BOCE	Bucket (95" General Purpose) (W/BOCE) (2.00 cu. Yd) for TW95	<b>\$6,686.10</b>
BTW9595W-BOCE	Bucket (95" Light Material) (W/BOCE) (2.75 cu. Yd) for TW95	<b>\$7,433.37</b>
BTW9595T	Bucket (95" Light Material) (8 tooth) (2.62 cu. Yd) for TW95	<b>\$8,196.37</b>
BTW95PF	48" Fork Assy for TW95 (Rated 12,500 lbs)	<b>\$4,300.08</b>

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	<b>\$91.00</b>
------------	---	----------------



## P3-Power Protection Plan + TFM\*

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.  
\* All P3 Extended warranties include the TFM monitoring service for models equipped with the TFM monitoring device.

		3YR/3000HR			4YR/4000HR			5YR/5000HR		
Models	Details	Powertrain	Powertrain & Hydraulic	Full Machine	Powertrain	Powertrain & Hydraulic	Full Machine	Powertrain	Powertrain & Hydraulic	Full Machine
TB20E	Item Number	EW20EP31	EW20EPH31	EW20EFM31	EW20EP41	EW20EPH41	EW20EFM41	EW20EP51	EW20EPH51	EW20EFM51
	List Price	\$2,016.00	\$3,360.00	\$4,200.00	\$4,704.00	\$7,224.00	\$9,038.40	\$5,376.00	\$8,232.00	\$10,315.00
TB210	Item Number	EW210P31	EW210PH31	EW210FM31	EW210P41	EW210PH41	EW210FM41	EW210P51	EW210PH51	EW210FM51
	List Price	\$529.00	\$882.00	\$1,105.00	\$1,235.00	\$1,896.00	\$2,373.00	\$1,411.00	\$2,161.00	\$2,708.00
TB216	Item Number	EW216P31	EW216PH31	EW216FM31	EW216P41	EW216PH41	EW216FM41	EW216P51	EW216PH51	EW216FM51
	List Price	\$729.00	\$1,215.00	\$1,519.00	\$1,701.00	\$2,613.00	\$3,269.00	\$1,944.00	\$2,977.00	\$3,731.00
TB216H	Item Number	EW216HP31	EW216HPH31	EW216HFM31	EW216HP41	EW216HPH41	EW216HFM41	EW216HP51	EW216HPH51	EW216HFM51
	List Price	\$1,217.00	\$2,029.00	\$2,536.00	\$2,840.00	\$4,362.00	\$5,457.00	\$3,246.00	\$4,970.00	\$6,228.00
TB225	Item Number	EW225P31	EW225PH31	EW225FM31	EW225P41	EW225PH41	EW225FM41	EW225P51	EW225PH51	EW225FM51
	List Price	\$914.00	\$1,523.00	\$1,903.00	\$2,132.00	\$3,273.00	\$4,096.00	\$2,436.00	\$3,730.00	\$4,674.00
TB230	Item Number	EW230P31	EW230PH31	EW230FM31	EW230P41	EW230PH41	EW230FM41	EW230P51	EW230PH51	EW230FM51
	List Price	\$980.00	\$1,634.00	\$2,042.00	\$2,287.00	\$3,512.00	\$4,394.00	\$2,614.00	\$4,002.00	\$5,015.00
TB235-2	Item Number	EW235P31	EW235PH31	EW235FM31	EW235P41	EW235PH41	EW235FM41	EW235P51	EW235PH51	EW235FM51
	List Price	\$1,171.00	\$1,951.00	\$2,439.00	\$2,732.00	\$4,195.00	\$5,249.00	\$3,122.00	\$4,781.00	\$5,991.00
TB335R	Item Number	EW335P31	EW335PH31	EW335FM31	EW335P41	EW335PH41	EW335FM41	EW335P51	EW335PH51	EW335FM51
	List Price	\$1,591.00	\$2,651.00	\$3,314.00	\$3,712.00	\$5,700.00	\$7,132.00	\$4,242.00	\$6,496.00	\$8,139.00
TB350R	Item Number	EW350P31	EW350PH31	EW350FM31	EW350P41	EW350PH41	EW350FM41	EW350P51	EW350PH51	EW350FM51
	List Price	\$2,016.00	\$3,360.00	\$4,200.00	\$4,704.00	\$7,224.00	\$9,038.40	\$5,376.00	\$8,232.00	\$10,315.20
TB240	Item Number	EW240P31	EW240PH31	EW240FM31	EW240P41	EW240PH41	EW240FM41	EW240P51	EW240PH51	EW240FM51
	List Price	\$1,168.00	\$1,946.00	\$2,433.00	\$2,725.00	\$4,185.00	\$5,236.00	\$3,114.00	\$4,769.00	\$5,976.00
TB250-2	Item Number	EW250/2P31	EW250/2PH31	EW250/2FM31	EW250/2P41	EW250/2PH41	EW250/2FM41	EW250/2P51	EW250/2PH51	EW250/2FM51
	List Price	\$1,431.00	\$2,386.00	\$2,982.00	\$3,340.00	\$5,129.00	\$6,417.00	\$3,817.00	\$5,845.00	\$7,324.00
TB257FR	Item Number	EW257P31	EW257PH31	EW257FM31	EW257P41	EW257PH41	EW257FM41	EW257P51	EW257PH51	EW257FM51
	List Price	\$1,857.00	\$3,095.00	\$3,869.00	\$4,334.00	\$6,655.00	\$8,327.00	\$4,953.00	\$7,584.00	\$9,503.00
TB260	Item Number	EW260P31	EW260PH31	EW260FM31	EW260P41	EW260PH41	EW260FM41	EW260P51	EW260PH51	EW260FM51
	List Price	\$1,588.00	\$2,646.00	\$3,308.00	\$3,704.00	\$5,689.00	\$7,118.00	\$4,234.00	\$6,483.00	\$8,123.00
TB280FR	Item Number	EW280P31	EW280PH31	EW280FM31	EW280P41	EW280PH41	EW280FM41	EW280P51	EW280PH51	EW280FM51
	List Price	\$2,643.00	\$4,405.00	\$5,506.00	\$6,167.00	\$9,471.00	\$11,849.00	\$7,048.00	\$10,792.00	\$13,523.00
TB290	Item Number	EW290P31	EW290PH31	EW290FM31	EW290P41	EW290PH41	EW290FM41	EW290P51	EW290PH51	EW290FM51
	List Price	\$2,492.00	\$4,154.00	\$5,192.00	\$5,815.00	\$8,931.00	\$11,174.00	\$6,646.00	\$10,177.00	\$12,752.00
TB370	Item Number	EW370P31	EW370PH31	EW370FM31	EW370P41	EW370PH41	EW370FM41	EW370P51	EW370PH51	EW370FM51
	List Price	\$2,621.00	\$4,368.00	\$5,460.00	\$6,115.00	\$9,391.00	\$11,750.00	\$6,989.00	\$10,702.00	\$13,410.00
TB2150	Item Number	EW2150P31	EW2150PH31	EW2150FM31	EW2150P41	EW2150PH41	EW2150FM41	EW2150P51	EW2150PH51	EW2150FM51
	List Price	\$4,057.00	\$6,762.00	\$8,453.00	\$9,467.00	\$14,538.00	\$18,190.00	\$10,819.00	\$16,567.00	\$20,759.00

Takeuchi Fleet Management (TFM) Subscriptions	
Pricing is for Monitoring Only for All Takeuchi Models Equipped with a TFM Monitoring Device.	
1 Year TFM12 Months	Item Number List TFMS1YRS180
2 Year TFM24 Months	Item Number List TFMS2YRS340
3 Year TFM36 Months	Item Number List TFMS3YRS500

PLEASE NOTE:  
TFM Monitoring is included with all P3 Extended Warranties purchased for the duration of the extended warranty period, provided the Takeuchi Model is equipped with a TFM Monitoring Device.





## P3-Power Protection Plan + TFM\*

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

\* All P3 Extended warranties include the TFM monitoring service for models equipped with the TFM monitoring device.

		3YR/3000HR			4YR/4000HR			5YR/5000HR		
Models	Details	Powertrain	Powertrain & Hydraulic	Full Machine	Powertrain	Powertrain & Hydraulic	Full Machine	Powertrain	Powertrain & Hydraulic	Full Machine
TL6	Item Number	EWL6P31	EWL6PH31	EWL6FM31	EWL6P41	EWL6PH41	EWL6FM41	EWL6P51	EWL6PH51	EWL6FM51
	List Price	\$985.00	\$1,642.00	\$2,053.00	\$2,299.00	\$3,531.00	\$4,418.00	\$2,628.00	\$4,023.00	\$5,042.00
TL8R2	Item Number	EWL8/2P31	EWL8/2PH31	EWL8/2FM31	EWL8/2P41	EWL8/2PH41	EWL8/2FM41	EWL8/2P51	EWL8/2PH51	EWL8/2FM51
	List Price	\$1,285.00	\$2,142.00	\$2,678.00	\$2,999.00	\$4,605.00	\$5,762.00	\$3,427.00	\$5,248.00	\$6,576.00
TL8R2-H	Item Number	EWL8/2HP31	EWL8/2HHP31	EWL8/2HFM31	EWL8/2HP41	EWL8/2HHP41	EWL8/2HFM41	EWL8/2HP51	EWL8/2HHP51	EWL8/2HFM51
	List Price	\$1,436.00	\$2,394.00	\$2,993.00	\$3,352.00	\$5,147.00	\$6,440.00	\$3,830.00	\$5,865.00	\$7,350.00
TL10R	Item Number	EWL10P31	EWL10PH31	EWL10FM31	EWL10P41	EWL10PH41	EWL10FM41	EWL10P51	EWL10PH51	EWL10FM51
	List Price	\$1,559.00	\$2,599.00	\$3,248.00	\$3,638.00	\$5,587.00	\$6,990.00	\$4,158.00	\$6,366.00	\$7,978.00
TL10R-HF	Item Number	EWL10HP31	EWL10HHP31	EWL10HFM31	EWL10HP41	EWL10HHP41	EWL10HFM41	EWL10HP51	EWL10HHP51	EWL10HFM51
	List Price	\$1,710.00	\$2,850.00	\$3,562.00	\$3,990.00	\$6,127.00	\$7,666.00	\$4,560.00	\$6,982.00	\$8,749.00
TL10V2	Item Number	EWL10VP31	EWL10VPH31	EWL10VFM31	EWL10VP41	EWL10VPH41	EWL10VFM41	EWL10VP51	EWL10VPH51	EWL10VFM51
	List Price	\$1,739.00	\$2,898.00	\$3,623.00	\$4,057.00	\$6,231.00	\$7,796.00	\$4,637.00	\$7,100.00	\$8,897.00
TL12R	Item Number	EWL12P31	EWL12PH31	EWL12FM31	EWL12P41	EWL12PH41	EWL12FM41	EWL12P51	EWL12PH51	EWL12FM51
	List Price	\$1,858.00	\$3,096.00	\$3,870.00	\$4,334.00	\$6,656.00	\$8,328.00	\$4,954.00	\$7,585.00	\$9,505.00
TL12R-HF	Item Number	EWL12HP31	EWL12HHP31	EWL12HFM31	EWL12HP41	EWL12HHP41	EWL12HFM41	EWL12HP51	EWL12HHP51	EWL12HFM51
	List Price	\$2,029.00	\$3,381.00	\$4,226.00	\$4,733.00	\$7,269.00	\$9,095.00	\$5,410.00	\$8,283.00	\$10,380.00
TL12V2/R2	Item Number	EWL12VP31	EWL12VPH31	EWL12VFM31	EWL12VP41	EWL12VPH41	EWL12VFM41	EWL12VP51	EWL12VPH51	EWL12VFM51
	List Price	\$2,260.00	\$3,767.00	\$4,709.00	\$5,274.00	\$8,100.00	\$10,134.00	\$6,028.00	\$9,230.00	\$11,566.00

Takeuchi Fleet Management (TFM) Subscriptions			
Pricing is for Monitoring Only for All Takeuchi Models Equipped with a TFM Monitoring Device.			
1 Year TFM12 Months	Item Number List	TFMS1YR\$180	
2 Year TFM24 Months	Item Number List	TFMS2YR\$340	
3 Year TFM36 Months	Item Number List	TFMS3YR\$500	

### PLEASE NOTE:

TFM Monitoring is included with all P3 Extended Warranties purchased for the duration of the extended warranty period, provided the Takeuchi Model is equipped with a TFM Monitoring Device.



## P3-Power Protection Plan

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

		3YR/3000HR			4YR/4000HR			5YR/5000HR		
Models	Details	Powertrain	Powertrain & Hydraulic	Full Machine	Powertrain	Powertrain & Hydraulic	Full Machine	Powertrain	Powertrain & Hydraulic	Full Machine
TW60 Series II	Item Number	EW60/2P32	EW60/2PH32	EW60/2FM32	EW60/2P42	EW60/2PH42	EW60/2FM42	EW60/2P52	EW60/2PH52	EW60/2FM52
	List Price	1768	2946	3683	4125	6335	7926	4714	7218	9045
TW80 Series II/III	Item Number	EW80P32	EW80PH32	EW80FM32	EW80P42	EW80PH42	EW80FM42	EW80P52	EW80PH52	EW80FM52
	List Price	1825	3041	3801	4257	6538	8180	4866	7450	9336
TW95	Item Number	EW95P32	EW95PH32	EW95FM32	EW95P42	EW95PH42	EW95FM42	EW95P52	EW95PH52	EW95FM52
	List Price	2956	4927	6158	6897	10592	13253	7883	12070	15125

Takeuchi Fleet Management (TFM) Subscriptions		
Pricing is for Monitoring Only for All Takeuchi Models Equipped with a TFM Monitoring Device.		
1 Year TFM12 Months	Item Number List	TFMS1YR\$180
2 Year TFM24 Months	Item Number List	TFMS2YR\$340
3 Year TFM36 Months	Item Number List	TFMS3YR\$500

### PLEASE NOTE:

TFM Monitoring is included with all P3 Extended Warranties purchased for the duration of the extended warranty period, provided the Takeuchi Model is equipped with a TFM Monitoring Device.