



Website WWW.KENSTRUCKREPAIR.com

Email Sales@KENSTRUCKREPAIR.com

Truck Repair, Inc.

Office 815•697•2361

Fax 815•697•2522

Interstate-57 Exit 302 ◀ 400 North Oak - P.O. Box 37 ▶ Chebanse, Illinois 60922

**Quote, Specification, Price on
2020 Titan 53' 2 Axle TW Dropframe Walking Floor**

Customer Application	Garbage
Base Model	53-2-TW-DF-WF-Dropframe (OPEN TOP)
Style	Drop style – See Note #3
Wall Configuration	
Front	To suit garbage application
Sides	To suit garbage application
Rear Door	SDSWG, Door in Door, Air Release, Lights in Door, Compactor Posts, with reinforced bottom lock finger – See Note #5
Overall Length	53 ft
Overall Width	102" nominal
Overall Height	13' 3 3/4" approx.
King Pin Location	36" WELD IN
Upper Coupler	5/16" THK Steel– Set @ 49" high
Number of Axles	
Primary	Two (2)
Lift	None (0)
Axles	SAF-Straight Spindle – See Note #1
Axle Track	77"
Suspension	SAF CBX25U 342 Fusion Beam
Location of Spreads	84" From Rear
Hub/Drum Assembly	10 Stud Duralite-Hub Pilot / Centrifuse Drum
Disc Wheel Size	8.25 x 22.5
Rims	STEEL – Std. Duty-Pre-painted white
Tires	
Brand	Goodyear
Size	255/70R22.5
Tread	Endurance RSA
Ply	16
Quantity	8
Axle Layout	FRONT-Primary-50-Primary-84-REAR
Oil Seals	Stemco Voyageur
Lubricants	Oil 80W-90
Brakes	
ABS	2S/2M Meritor Wabco – See Note #1
Slack adj.	Haldex Auto – See Note #1
Cam Enclos	All axles – c/w Dust Shields – See Note #1
Lift Kits	None
Lift Controls	None
Frame Width	48"
Rear Bumper	None-bottom of light bar is less than 22" from ground – bumper not required

	Option #1	None
	Option #2	1 pc D Ring style tow hook-mounted left hand side (roadside)
	Option #3	4 x 4 bumper blocks w/ grove to bumper uprights
Tire Carrier		None
Landing Gear		Inboard Jost Landing Gear-w/ cushion foot #A401-G3-14
Top Rail		Titan Tapered V1
Top Cross Tube (less rear)		Qty 1 – spring steel (two piece style)
Floor Crossmembers		12” Centers
Keith Walking Floor Kit		Running floor II – 3 1/2” dia cylinders – 6” stroke
Slat Model & Width		2299 (1914 C.W.S.) 3 1/2”- 1212 seals - T-blocks Rear-with drop – See Note #3
Slat Wear Strips		24” at rear of trailer floor
Continuous Bearing		Continuous splash/hold down
Side Wall Wear Plates		None
Front Access Door		STD-35w x 37.5h sealed-curb side hinge with flip step over air & electrical
Tarp Style		None – See Note # 7
Tarp Header		Flat – front & rear
Tarp Basket		None
Tarp Hooks		None
Axle Fender		None
Hyd Fitting	Pressure	1” – Quick coupler –Male with 9’ hose attached
	Return	1” – Quick coupler – Female with 9’ hose attached
Mud Flaps	Style	Titan Black Rubber
	Location	Rear off light bar
Mud Flap – Landing Gear		None
Paint	Body – Color	Natural Aluminum
	Run – Gear	Titan Black
	Hub / Drum	Same as Running Gear
	Rims or Disc	Pre-painted white
Light package (Plug Form)		3 markers per side (including corner, mitre & midturn) At rear: 3 per side 4” dia in door & 2 rect outer clearance at top – See Note #6
	Option #1	Add (3) 1x4 lights to the center of the light bar on door
	Option #2	Add 9 marker lights per side for a total of 11 at bottom per side
Access	Catwalk	None
	J-Ladder Front	2 pc ladder on front wall with one section on man door & one section above it w/ 10” stand offs
	J-Ladder Rear	None
	Steps-Front - Out	Use flip up step below ladder
	Steps-Front In	None
	Steps-Rear	None

Additional specifications:

- 1) Long stroke Haldex brake chambers. Suspension plumbed to deflate when brakes are set (auto dump). No trailer mounted dump control. No control box needed.
- 2) Install grab handle on roadside of front wall.
- 3) Charge to make trailer a drop deck including trailer drop, extra sidewall material, drop floor kit, & 1914 CWS upcharge. Trailer floor to have 12 ½" drop.
- 4) 2" liquid filled air gauge on driverside front corner mitre at eye level.
- 5) Door pusher bar/prop to be installed, attached to rear air door. Special cone locks to operate from outside of sidewall. Tailgate release mount on plate roadside just ahead of subframe.
- 6) Mount license plate in light bar on door.
- 7) Tarp support rod with standoffs to be added to rear side of top rear header tube. Add (5) tarp ratchet holders on driverside of trailer to suit Deroche tarp.

Volume: 150.2 cu yds

Estimated weight, 19,718 lbs +/- 3%

List Price

\$ 108,189.64

No FET Included, FOB Chebanse, IL

No state or local tax included

No license or title fees included