



Website WWW.KENSTRUCKREPAIR.com

Email Sales@KENSTRUCKREPAIR.com

Truck Repair, Inc.

Office 815•697•2361

Fax 815•697•2522

Interstate-57 Exit 302 ◀ 400 North Oak - P.O. Box 37 ▶ Chebanse, Illinois 60922

**Quote, Specification, Price on
2020 Titan 48ft Thinwall Walking Floor Trailer
Spring Ride – Keith Floor**

Customer application	To Suit Garbage Application
Base model	48-2-TW-WF – Open Top
Style	Straight
Wall configuration	
Front	To Suit Garbage Application
Sides	7-14" + 1-6" to Suit Garbage Application
Rear Door	Side Swing, Door in Door, Lights in Door, Air Release w/ reinforced lock finger – See Note #4
Overall length	48ft
Overall width	102" Nominal
Overall height	13' 1 ¼" Approx
King pin location	36" WELD IN
Upper coupler	5/16" THK Steel– Set @ 48" high
Number of Axles	
Primary	Two (2)
Axles	IMT - 5" round - .580 wall - Straight Spindle - See Note #2
Axle track	77"
Suspension	Reyco 21B w/ inner wear plates & 3 leaf springs
Location of spreads	See axle layout
Hub/drum assembly	10 Stud Duralite – Hub Pilot/Centrifuse Drum
Disc wheel size	8.25 x 22.5
Rims	STEEL- Std. Duty – Pre-painted White
Tires	
Brand	Goodyear
Size	11R22.5
Tread	Endurance RSA
Ply	14
Quantity	8
Axle layout	FRONT -Prim -50 - Prim -28 - REAR
Oil seals	SKF
Lubricants	Oil-Std 80W-90
Brakes	
ABS	2S/1M Meritor Wabco
Slack adj.	Meritor Auto
Cam Enclos	All Axles – C/W Dust Shields
Lift kits	None
Lift controls	None
Frame width	48"
Rear bumper	Alum, offset, push

	Option #1	Tow shackles
	Option #2	Alum vertical blocks bolted to bumper
	Option #3	None
Tire carrier		None
Landing gear		Standard Jost Landing Gear – low pro cushion foot
Top rail		Titan Tapered, V1
Top cross tube		Qty 1 – Spring Steel (two piece style)
Floor crossmembers		12” Centers – Cross Bracing Required
Keith walking floor kit		Running floor II – 3.5” Dia Cylinders – 10” stroke
Slat model & width		2299 (1914 C.W.S.) 3 ½”, 1212 seals, T-blocks rear
Slat wear strips		None
Continuous bearing		Continuous Splash/Hold Down Bearings
Side wall wear plates		Boomerang style
Front access door		STD 35 x 37.5h Sealed – Curbside Hinge W/Flip Step Over Air & Electrical
Tarp style		None
Tarp header		None
Tarp basket		Tarp hoops front & rear – shipped loose
Tarp hooks		Tarp Hooks on 48” o/c with 4 Hooks on Rear Door
Axle fender		None
Hyd fitting	Pressure	1” quick coupler – Male – See Note #3
	Return	1” quick coupler – Female – See Note #3
Mud flaps	Style	Titan black rubber
	Location	Rear
Mud flap – Landing gear		None
Paint	Body – color	Natural aluminum
	Run – gear	Titan black
	Hub / drum	Same as running gear
	Rims or Disc	Pre-painted White
Light package		3 markers per side (includes corner, mitre, & midturn)
		At Rear: 3 per side, 4” dia in door, & 5 rect. clearance at top
	Option #1	Rear lights upper to be in top of door-due to roller style rear header
	Option #2	Install rear taillights & license plate in rear door
Access	Catwalk	STD 24” Catwalk
	J-Ladder Frt	Roadside To Catwalk w/ Two Rung Style Hand Holds Above
	J-Ladder Rear	Located In Center of Rear Door
	Steps Frt out	None
	Steps Frt in	None
	Steps Rear	None

Additional specifications:

- 1) KP To Center of Tandem Must Be 41' or Less
- 2) Invert axles
- 3) Add 9' hoses and hose hanger bracket
- 4) Top rear header to be Steel Roller Style

Estimated weight: 17,901 lbs +/- 3%

Estimated volume: 123 cu yds

List Price

\$ 85,636.25

No FET Included, FOB Chebanse, IL

No State Or Local Tax Included

No License Or Title Fees Included