

Product Code	Description	Bid Price As of 02/01/25
<b>F. Portable "Self-Priming" Trash Pumps</b>		
<b>B. Gorman-Rupp</b>		
CM21FB01	Model 12D-GX160, 2" x 2" Heavy Duty Trash Pump, Double Grease Seal, Gasoline Engine, Passes a 1-3/16" Solid, Shut-Off Head is 116', 185 GPM Flow Rate	\$3,615.00
CM21FB02	Model 13D-GX270, 3" x 3" Heavy Duty Trash Pump, Double Grease Seal, Gasoline Engine, Passes a 1-1/2" Solid, Shut-Off Head is 102', 400 GPM Flow Rate	\$4,647.00
CM21FB03	Model T4A60S-4LE2T FT4 Isuzu, 4" x 4" Heavy Duty Trash Pump, Mechanical Oil Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes 3" Solid, Shut-Off Head 145', 810 GPM Max Flow Rate. Options Available: DOT Wheel-Kit and Eradicator® Solids Management System	\$51,474.00
CM21FB04	Model T4A60S-4LE2T FT4-ESP (Enclosed Silent Package) Isuzu, 4" x 4" Heavy Duty Trash Pump, Mechanical Oil Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes 3" Solid, Shut-Off Head 145', 810 GPM Max Flow Rate. Pump & Engine mounted on a full containment base with a "sound-attenuated" aluminum enclosure. Options Available: DOT Wheel-Kit and Eradicator® Solids Management System	\$79,661.00
CM21FB05	Model T6A60S-4LE2X FT4 Isuzu, 6" x 6" Heavy Duty Trash Pump, Mechanical Oil Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes 3" Solid, Shut-Off Head 152', 1650 GPM Flow Rate. Options Available: DOT Wheel-Kit and Eradicator® Solids Management System	\$62,812.00
CM21FB06	Model T6A60S-4045T <b>S5</b> John Deere, 6" x 6" Heavy Duty Trash Pump, Mechanical Oil Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes 3" Solid, Shut-Off Head 152', 1650 GPM Flow Rate. Options Available: DOT Wheel-Kit and Eradicator® Solids Management System	\$75,503.00
CM21FB07	Model T6A60S-4045T <b>S5</b> -ESP (Enclosed Silent Package) John Deere, 6" x 6" Heavy Duty Trash Pump, Mechanical Oil Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes 3" Solid, Shut-Off Head 152', 1650 GPM Max Flow Rate. Pump & Engine mounted on a full containment base with a "sound-attenuated" aluminum enclosure. Options Available: DOT Wheel-Kit and Eradicator® Solids Management System	\$107,450.00
<b>Q. AMT Pump</b>		
CM21FQ02	Model 2S5XHR-GX160, 2" x 2" Self-Priming Trash Pump, cast aluminum housing, viton mechanical seal, Honda GX160 5HP Gasoline engine, passes a 1-1/4" solid, Shut-off head is 125', 230 GPM flow rate	\$1,866.00
CM21FQ03	Model <b>3</b> S5XHR-GX200, 3" x 3" Self-Priming Trash Pump, cast aluminum housing, viton mechanical seal, Honda GX200 5HP Gasoline engine, passes a 1-1/4" solid, Shut-off head is 110', 290 GPM flow rate	\$1,983.00
CM21FQ04	Model 3S9XHR-GX270, 3" x 3" Self-Priming Trash Pump, cast aluminum housing, viton mechanical seal, Honda GX270 8HP Gasoline engine, passes a 2" solid, Shut-off head is 110', 370 GPM flow rate	\$3,116.00
CM21FQ05	Model 4S13XHR-GX390, 4" x 4" Self-Priming Trash Pump, cast aluminum housing, viton mechanical seal, Honda GX390 13HP Gasoline engine, passes a 2" solid, Shut-off head is 105', 530 GPM flow rate	\$5,676.00
CM21FQ06	Model 338G-96-GX120, 2" x 2" Self-Priming Diaphragm Pump, cast aluminum housing, Honda GX120 4HP Gasoline engine, passes a 1-5/8" solid, Shut-off head is 25', 50 GPM flow rate	\$3,271.00
CM21FQ07	Model 337H-96-GX160, 3" x 3" Self-Priming Diaphragm Pump, cast aluminum housing, Honda GX160 4HP Gasoline engine, passes a 1-5/8" solid, Shut-off head is 25', 88 GPM flow rate	\$3,500.00
<b>G. Portable "Priming-Assisted" Trash Pumps</b>		
<b>C. Gorman-Rupp</b>		
CM21GC01	Model PAV3B60C-3TNV80F FT4, 3" X 3" Heavy Duty Priming Assisted Trash Pump, Mechanical Oil Lube Seal, Skid-Mounted Final Tier 4 Yanmar Engine, Auto-Start Controls, Passes 3" Solid, Shut-Off Head 136', 450 GPM Max Flow Rate. Options Available: Wheel-Kit.	\$46,826.00
CM21GC02	Model PA4A60C-4LE2T FT4 Isuzu, 4" X 4" Heavy Duty Priming Assisted Trash Pump, Mechanical Oil-Lube Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes a 3" Solid, Shut-Off Head is 135', 925 GPM Flow Rate. Options Available: DOT Wheel-Kit	\$62,722.00
CM21GC03	Model PA4A60C-4LE2T FT4-ESP (Enclosed Silent Pump) Isuzu, 4" X 4" Heavy Duty Priming Assisted Trash Pump, Mechanical Oil-Lube Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes a 3" Solid, Shut-Off Head is 135', 925 GPM Flow Rate. Pump & Engine mounted on a full containment base with a "sound-attenuated" aluminum enclosure. Options Available: DOT Wheel-Kit	\$95,227.00
CM21GC04	Model VPA4A60C-3CH1 FT4, 4" x 4" Heavy Duty Priming Assisted Trash Pump, Mechanical Oil Lube Seal, Skid mounted Final Tier 4 Isuzu Diesel Engine, Autostart Controls, Passes 3" solid, Shut off Head is 150', 850 GPM Flow Rate, Options Available: DOT Wheel kit.	\$40,133.00

CM21GC05	Model PA6C60-4045T <b>S5</b> John Deere, 6" X 6" Heavy Duty Priming Assisted Trash Pump, Mechanical Oil-Lube Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes a 3" Solid, Shut-Off Head is 158', 2300 GPM Flow Rate. Options Available: DOT Wheel-Kit	\$76,015.00
CM21GC06	Model PA6C60-4045T <b>S5-ESP</b> (Enclosed Silent Pump) John Deere, 6" X 6" Heavy Duty Priming Assisted Trash Pump, Mechanical Oil-Lube Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes a 3" Solid, Shut-Off Head is 158', 2300 GPM Flow Rate. Pump & Engine mounted on a full containment base with a "sound-attenuated" aluminum enclosure. Options Available: DOT Wheel-Kit	\$110,554.00
CM21GC09	Model VPA6A60C- <b>4LE2T FT4</b> Isuzu, 10" X 10" Heavy Duty Priming Assisted Trash Pump, Mechanical Oil-Lube Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes a 3" Solid, Shut-Off Head is 114', 1520 GPM Flow Rate. Options Available: DOT Wheel-Kit	\$46,968.00
CM21GC10	Model PA8E60-4045H FT 4 John Deere, 8" X 8" Heavy Duty Priming Assisted Trash Pump, Mechanical Oil-Lube Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes a 3" Solid, Shut-Off Head is 200', 3750 GPM Flow Rate. Options Available: DOT Wheel-Kit	\$113,083.00
CM21GC11	Model PA8E60-4045H FT 4-ESP(Enclosed Silent Pump) John Deere, 8" X 8" Heavy Duty Priming Assisted Trash Pump, Mechanical Oil-Lube Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes a 3" Solid, Shut-Off Head is 200', 3750 GPM Flow Rate. Options Available: DOT Wheel-Kit	\$148,992.00
CM21GC12	Model PA10A60-4045H <b>FT4</b> John Deere, 10" X 10" Heavy Duty Priming Assisted Trash Pump, Mechanical Oil-Lube Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes a 3" Solid, Shut-Off Head is 156', 3920 GPM Flow Rate. Options Available: DOT Wheel-Kit	\$116,112.00
CM21GC13	Model PA12A60- <b>B-4045H FT4</b> John Deere, 12" X 12" Heavy Duty Priming Assisted Trash Pump, Mechanical Oil-Lube Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes a 3" Solid, Shut-Off Head is 108', 6200 GPM Flow Rate. Options Available: DOT Wheel-Kit	\$143,693.00
CM21GC14	Model PA12A60- <b>B-4045H FT4-ESP</b> (Enclosed Silent Pump) John Deere, 12" X 12" Heavy Duty Priming Assisted Trash Pump, Mechanical Oil-Lube Seal, Skid-Mounted Final Tier 4 Diesel Engine, Auto-Start Controls, Passes a 3" Solid, Shut-Off Head is 108', 6200 GPM Flow Rate. Options Available: DOT Wheel-Kit	\$204,375.00
CM21GC15	Model PAH6B60-6068H FT4 John Deere 10" x 6" Heavy Duty High Pressure Priming Assisted Final Tier 4 Diesel Engine-Driven Pump. Auto-Start Controls, Mechanical Oil-Lube Seal Mounted on Steel Skid, Passes 3" Solids, Shut-Off Head is 250'. Max Flow is 4445 GPM. Options Available: Wheel Kit	\$150,846.00
CM21GC16	Model PAH8A60-6090H FT4 John Deere 10" x 8" Heavy Duty High Pressure Priming Assisted Final Tier 4 Diesel Engine-Driven Pump. Auto-Start Controls, Mechanical Oil-Lube Seal Mounted on Steel Skid, Passes 3" Solids, Shut-Off Head is 344. Max Flow is 5250 GPM. Options Available: DOT Highway Trailer	\$198,204.00
CM21GC17	Model PAH10B60-6136H FT4 John Deere 12" X 10" Heavy Duty High Pressure Priming Assisted Final Tier 4 Diesel Engine-Driven Pump. Auto-Start Controls, Mechanical Oil-Lube Seal Mounted on Steel Skid. Passes a 2" Solid, Shut-Off is 380' Max Flow is 6,100 gpm. Options Available: DOT Highway Trailer	\$274,146.00
<b>I. Electric Submersible Pumps</b>		
<b>B. Gorman-Rupp</b>		
CM21IB01	Model S2A1- <b>E2 230/1</b> , 2" Electric Submersible Pump 230Volt <b>1</b> Phase 2HP, NEMA Control Panel w/Standard 50' Cable	\$8,436.00
CM21IB02	Model S3A1- <b>E5 230/3</b> , 3" Electric Submersible Pump 230 Volt 3 Phase 5 HP, NEMA Control Panel w/Standard 50' Cable	\$9,249.00
CM21IB03	Model S4A1-E25 <b>460/3</b> , 4" Electric Submersible Pump 460 Volt 3 Phase 25 HP, NEMA Control Panel w/Standard 50' Cable	\$22,698.00
CM21IB04	Model S6A1-E60 <b>460/3</b> , 6" Electric Submersible Pump 460Volt 3 Phase 60 HP, NEMA Control Panel w/ Standard 50' Cable	\$34,770.00
CM21IB05	Model S8A1-E95 <b>460/3</b> , 8" Electric Submersible Pump 460 Volt 3 Phase 95 HP, NEMA Control Panel w/Standard 50' Cable	\$39,139.00
CM21IB06	Model S12A1-E140 <b>460/3</b> , 12" Electric Submersible Pump 460 Volt 3 Phase 140 HP, NEMA Control Panel w/Standard 50' Cable	\$51,767.00
<b>L. AMT Pump</b>		
CM21II01	Model 5891-DC, 1-1/2" 12 Volt Electric Submersible Pump 1/3HP, on/off switch w/Standard 30' Power Cord, comes with metal carry case	\$2,169.00
CM21II02	Model 5811-99, 1-1/2" Electric Submersible Pump 1/2HP, single phase, 115v, plastic housing, automatic float switch w/Standard Power Cord, solids handling clog resistant impellers. Shut-off head 21', Flows up to 47 GPM.	\$485.00
CM21II03	Model 5780-98, 2" Electric Submersible Pump 1/2HP, single phase, 115v, stainless steel housing, automatic float switch w/Standard Power Cord, solids handling clog resistant impellers. Shut-off head 32', Flows up to 57 GPM.	\$1,306.00
CM21II04	Model 5792-95, 2" Electric Submersible Pump 1/2HP, single phase, 115v, Cast Iron Housing, automatic float switch w/Standard Power Cord, solids handling clog resistant impellers. Shut-off head 37', Flows to 64 GPM.	\$780.00