



2024 PRODUCT CATALOG



[AMKUS.COM](https://www.amkus.com)



IN THE MOMENT FIRST RESPONDERS TRUST AMKUS FOR THE **MOST VERSATILE LIFESAVING** RESCUE TOOLS.

RACING PARTNERSHIPS


For more than 40 years, AMKUS Rescue Systems has supplied rescue tools to NASCAR. Over the years, our partnership has expanded to include NHRA, IMSA and World of Outlaws. When incidents occur on the track, first responders are equipped with the most reliable rescue tools to ensure driver safety.



OFFICIAL RESCUE TOOL

STAR AWARDS

The AMKUS Star Awards honors our heroic first responders and the work they do to save lives every day. From the bottom of our hearts, we thank each individual for their commitment to saving others. Share your story at amkus.com/star-awards.



SIMPLE. RUGGED. RELIABLE.

SPREADERS

iS290 Midsize Spreader



With a 12 second open/close rate, the iS290 Spreader is our most compact spreader. Using a four-stage pump, it maximizes speed regardless of load conditions. Designed with a short profile, which allows users to better perform the most complicated extrication techniques.

PART NUMBER: IS290LB

Length	35.2 in (894 mm)
Weight	47.3 lbs (21.5 kg)
Spreading distance (with ERTs)	37 in (940 mm)
Highest Spreading Force (HSF)	9,640 lbs (42.9 kN)
Lowest Spreading Force (LSF)	6,040 lbs (26.9 kN)
Highest Pulling Force (HPF)	5,890 lbs (26.2 kN)
Lowest Pulling Force (LPF)	3,910 lbs (17.4 kN)



iS320 Large Spreader



Our largest and most powerful spreader is the iS320 Spreader, featuring a solid aluminum body with a compact tool design that allows access to tight areas other tools can't reach. Our Gator Tips are standard and include an aggressive tooth pattern that won't slip and the beveled edges don't rip sheet metal.

PART NUMBER: IS320LB

Length	38.1 in (968 mm)
Weight	54.3 lbs (24.6 kg)
Spreading Distance (with ERTs)	39.1 in (993 mm)
Highest Spreading Force (HSF)	15,100 lbs (67.2 kN)
Lowest Spreading Force (LSF)	10,530 lbs (46.9 kN)
Highest Pulling Force (HPF)	11,500 lbs (51.1 kN)
Lowest Pulling Force (LPF)	7,580 lbs (33.7 kN)





CUTTERS

iC650 Midsize Cutter



The iC650 Cutter features a 15 second open/close rate, long runtimes, and a short profile to maximize maneuverability in confined spaces.

PART NUMBER: IC650LB

Length	33.5 in (851 mm)
Height	11.2 in (285 mm)
Weight	49.5 lbs (22.4 kg)
Cutter Opening	6.2 in (158 mm)
Cutter Rating	A6/B8/C6/D7/E7/F4



iC700 Short Blade Cutter



The iC700 Cutter uses durable blades that reduce twist and torque when faced with harder materials. The speed of this cutter allows users to make two cuts in the same amount of time large blade cutters take to make one.

PART NUMBER: IC700LB

Length	32.7 inches (830 mm)
Height	11.6 inches (294 mm)
Weight	53.8 lbs (24.4 kg)
Cutter Opening	5.8 inches (147 mm)
Cutter Rating	A7/B8/C7/D9/E8/F4



iC750 Large Blade Cutter



The iC750 Cutter is our largest cutter ready for the most complicated rescue situations. The blade and center bolt are designed to allow access to the most difficult cuts.

PART NUMBER: IC750LB

Length	33.7 inches (856 mm)
Height	11.6 inches (294 mm)
Weight	54.7 lbs (24.8 kg)
Cutter Opening	7 in (178 mm)
Cutter Rating	A8/B9/C7/D9/E9/F4



COMBIS & RAM

iCT614 Midsize Combi Tool



The iCT614 Combi Tool features a short profile, it maximizes vulnerability during tight vehicle extraction and can easily be used during forcible entry situations. With a 15 second open/close rate, this is one of the best “first on the scene” rescue tools.

PART NUMBER: ICT614LB

Length (with spreading tips)	35.3 in (897 mm)
Length (without spreading tips)	34 in (864 mm)
Height	11.2 in (285 mm)
Weight	47.2 lbs (21.4 kg)
Max Spreading Distance	14.0 in (356 mm)
Highest Spreading Force (HSF)	8,010 lbs (35.6 kN)
Cutter Opening	13.8 in (351 mm)
Cutter Rating	A6/B6/C5/D6/E7/F4



iCT716 Large Combi Tool



The iCT716 Combi Tool is our largest combi tool, combining the capabilities of a cutter and spreader. It is another perfect “first on the scene” rescue tool. The rotating handle allows the tool to easily be repositioned for your rescue operation.

PART NUMBER: ICT716LB

Length (with spreading tips)	36 in (915 mm)
Length (without spreading tips)	34.8 in (885 mm)
Height	11.6 in (294 mm)
Weight	58.7 lbs (26.6 kg)
Max Spreading Distance	15.6 in (396 mm)
Highest Spreading Force (HSF)	7,830 lbs (34.8 kN)
Cutter Opening	13.8 in (351 mm)
Cutter Rating	A7/B8/C7/D9/E8/F5



iTR500 RAM



When fully extended, it reaches 50 inches. With an all-aluminum body, the ram is ready for use in any rescue situation. The motor and valve assembly can easily rotate so they stay protected, so you can better position yourself for a successful rescue.

PART NUMBER: ITR500LB

Length, extended	50.5 inches (1283 mm)
Length, retracted	21.9 inches (556 mm)
Weight	54.8 lbs (24.9 kg)
Highest spreading force, Piston 1	48,540 lbs (215.9 kN)
Highest spreading force, Piston 2	22,390 lbs (99.6 kN)





ACCESSORIES

Increase the reach of your spread by 8 inches with our optional Extended Reach Tips (ERTs). There are more than 16 ways to configure the ERTs and standard Gator Tips to create the exact angle needed in different rescue scenarios. With a push button release, Gator Tips and ERTs can be added or removed in seconds.



Spreader Extended Reach Tips (ERT)

PART NUMBER: KS0029-KIT



Combi Extended Reach Tips (ERTs)

PART NUMBER: KN0194-KIT



Tip Gator Grip

PART NUMBER: KS0017G-KIT

DEWALT BATTERIES & CHARGERS

6/2 AMP-HR 60V Batteries & Single Charger

Includes 2 batteries and chargers.

PART NUMBER: BATT6-KIT

9/3 AMP-HR 60V Batteries & Single Charger

Includes 2 batteries and chargers.

PART NUMBER: BATT9-KIT

12/4 AMP-HR 60V Batteries & Single Charger

Includes 2 batteries and chargers.

PART NUMBER: BATT12-KIT

60V Battery (6/2 AMP-HR)

PART NUMBER: IBATTFV-6

60V Battery (9/3 AMP-HR)

PART NUMBER: IBATTFV-9

60V Battery (12/4 AMP-HR)

PART NUMBER: IBATTFV-12

Flexvolt Battery Charger - 120V

Single charger

PART NUMBER: ICHRG120

Flexvolt Battery Charger - 120V

4 bay fast charger

PART NUMBER: ICHRG-4FAST

Flexvolt Battery Charger - 220V

Single charger

PART NUMBER: ICHRG220

DEWALT FLEXVOLT FIRE-RESCUE KITS



WINDSHIELD REMOVAL KIT | WNDREM-KIT

Windshield Removal Kit

PART NUMBER: WNDREM-KIT

60V Reciprocating Saw Kit

PART NUMBER: RECSAW-KIT

Scene Lighting Kit

PART NUMBER: SCNLGHT-KIT

Cutoff Saw Kit

PART NUMBER: CUTSAW2-KIT

Chainsaw Kit

PART NUMBER: CHNSAW-KIT

20" Chainsaw Kit

PART NUMBER: CHNSAW20-KIT

Blower Kit

PART NUMBER: BLOWER-KIT

Portable Bandsaw Kit

PART NUMBER: BANDSAW-KIT

60V Grinder Kit With 4.5" Diamond Rescue Blade

PART NUMBER: GRINDER-KIT

Hammer Drill & Impact Driver Kit

PART NUMBER: DRILL-KIT

60V Cordless Circular Saw Kit

PART NUMBER: CIRCSAW-KIT



CUTOFF SAW KIT | CUTSAW2-KIT



4201 Montdale Drive
Valparaiso, IN 46383
800-592-6587
experts@amkus.com

[amkus.com](https://www.amkus.com)



AMKUS Rescue Systems reserves the right to make changes
in design and specifications without notice.

© Copyright AMKUS Rescue Systems 2024

APRIL 2024

