


QAS 625 T4F

Mobile Generator



Standard Scope of Supply

The Atlas Copco **QAS 625 T4F** generator is a prime power, multi-voltage, sound attenuated, mobile generator. It is powered by a Volvo T4 Final liquid-cooled, six cylinder diesel engine.

The units consist of an alternator, diesel engine, cooling system, electrical distribution and control systems - all enclosed within a sound attenuated enclosure fabricated from powder coated steel.

Special attention has been given to the overall product quality, user friendliness, ease of serviceability, and economical operation to ensure best in class total cost of ownership.

Available Models

QAS 625 VD

Multiple voltage – 625kVA prime power – Volvo engine

Standard Features

- Compact, sound attenuated, corrosion resistant, with single point lifting and 110% fluid containment
- Tri axle trailer as standard, available as a skid mounted unit with forklift pockets as an option
- Heavy Duty alternator with AREP excitation and marine grade protection
- Single side service with long run filters and 500 hour service intervals
- Extremely reliable and durable Volvo TWD1672GE T4F engine
- Voltage selector switch
- Emergency Stop
- Remote signal Start / Stop

Benefits

- Extremely durable and environmentally sensitive, designed to be used for everything from the oil patch to special event power
- Versatility, giving you the flexibility to match your machine to the correct application
- Start-up power for the most demanding sites with 300% over load starting capabilities
- Heavy duty oil, air and fuel filters extend the maintenance interval to 500 hours for reduced total cost of ownership
- Reduces maintenance costs with long intervals easy access for mechanics
- Proven engine platform with high reliability
- Simple voltage change within seconds
- Ability to provide extended running hours
- External, recessed emergency stop for increased safety
- Allows connection as a critical back-up unit via a 2 wire dry contact connection in the distribution panel

Technical Data¹

Generator	Units	QAS 625 VD
Rated Prime Power 3Ø @ 400V 50hz	kW / kVA	500/ 625
Rated Standby Power 3Ø	kW / kVA	550/ 688
3Ø Power Factor		0.8
3Ø Voltage In 480V Switch Position (Series Star w/ Neutral)	V	480Y/277
Amp Capacity @ 480V / 60Hz	A	750
3Ø Voltage In 240-208V Switch Position (Parallel Star w/ Neutral)	V	240YY/139 – 208YY/120
Amp Capacity @ 240V / 60Hz	A	1500
Amp Capacity @ 208V / 60Hz	A	1600
1Ø Power Factor		1
1Ø Voltage In 120-240V Switch Position (Zig-Zag)	V	120-240
Amp Capacity @ 240V	A	1000
Amp Capacity @ 120V	A	2 x 1000
Performance class (acc.ISO 8528-5:1993)		G2*
Single step load acceptance (0-PRP) @60Hz	kW- %	TBD
Alternator (4 Pole, 12 Wire)	Leroy Somer	LSA47.2 M8
Excitation		AREP
Automatic Voltage Regulator (+/- 0.5%)	Leroy Somer	DVC310
Insulation		Class H
Frequency	Hz	60
Main Breaker - Shunt Trip	A	1600
Power Distribution – Terminal Board		5 Wire (L1, L2, L3, N, Ground)
Terminal Board Connections		Bare Wire Terminals
Maximum Terminal Cable Size		350MCM
Convenience Receptacles ²		2 x NEMA 5-20R, 3 x 125/250V 50A CS6364

Engine	Units	QAS 625 VD
Model		Volvo TWD1672GE
US EPA Tier		T4F
Displacement	l	16
Cylinders	#	6
Continuous Engine Power Output (@ 1800 RPM)	HP (kW)	724 (532)
Rated Speed	RPM	1800
Engine Control		ECU
Aspiration		Turbocharged
Engine oil capacity ³	Gal (l)	12.7 *
Engine coolant capacity	Gal (l)	TBD
Maximum Ambient Temperature (@ Sea Level) ⁴	°F (°C)	122°F (50°C)
Minimum Starting Temperature (Without cold weather options)	°F (°C)	14°F (-10°C)
Minimum Starting Temperature (With cold weather kit)	°F (°C)	-4°F (-20°C)
Electrical System (Negative Ground)	V	24
Engine Alternator Output	A	TBD
Battery Capacity (Cold Cranking Amps)	A	TBD
Sound Pressure Level @ 23'(7 m) @ 75% Load ⁶	dB(A)	73


Fuel System	Units	QAS 625 VD
Fuel Consumption @ 0% load	Gal/h (l /h)	TBD
Fuel Consumption @ 50% load	Gal/h (l /h)	16.8 (63.7)*
Fuel Consumption @ 75% load	Gal/h (l /h)	24.6 (93.0)*
Fuel Consumption @ 100% load	Gal/h (l /h)	32.2 (122.0)*
Fuel Type		Diesel
Fuel Tank Capacity	Gal/h (l /h)	700
Fuel Autonomy @ 75% load ⁵	Hr	28*
DEF Tank Capacity	Gal/h (l /h)	39.5 (149)

*TBD

¹ All ratings are at a reference condition of 0' altitude and 20°C (68°F)² Please see receptacle voltage configuration in Power Distribution section on page #5³ Engine oil to meet CJ-4 (low ash oil)⁴ Please see "Derate Table" for altitude and temperature calculations on⁶ Measured in accordance with ISO 2151 under free field conditions @ 7m distance⁷ Engine and emissions require the use of Ultra Low Sulfur Diesel in accordance to ASTM-D975 Grade No.1-D S15 & No.2-D S15⁸ TBC⁹ Only at 60 Hz

Dimensions

Trailer Mounted



Weight - Wet (ready to operate)	Units	QAS625 VD
Trailer Mounted	lbs (kg)	24,000 (10,886) *
Skid Mounted	lbs (kg)	19,000 (8618) *
Dimensions		
Trailer Mounted (L x W x H)	Inches	260 x 102 x 118
Skid Mounted (L x W x H)	Inches	215 x 70 x 110 *

*TBD

Main Data

Alternator



The Leroy Somer LSA alternators are designed for heavy duty continuous applications, with marine winding protection and Leroy Somer's AREP excitation system.

- AREP Excitation for superior motor starting capabilities
- Marine grade (relative humidity >95%) protection
- External multi-voltage selector switch (3 – position)
- 4 pole brushless design with single bearing, Class H insulation and IP23 rating
- Voltage regulation +/- 0.5%
- Full Load acceptance of prime power rating

The AREP system uses 2 independent auxiliary windings located in the main stator to send supply voltage to the AVR:

- The voltage delivered by the first auxiliary winding H1 is proportional to the alternator output voltage (shunt characteristic).
- The voltage delivered by the second auxiliary winding H3 is proportional to the current drawn by the alternator and is a function of the applied load (compound characteristic – booster effect).
- The resulting phase-to-phase voltage supplies power to the AVR.

This power supply to the AVR power circuit is independent of the voltage sensing measured on the alternator output terminals. Therefore, the excitation current delivered by the AVR to the alternator exciter is independent of any voltage distortions (harmonics) due to the load. The AREP system gives the alternator a high overload capacity (load impact or starting electric motors) and a short-circuit capability (300% - 10 s) in order to provide discriminating protection: the alternator with AREP excitation is shorter than the one with PMG excitation. It is particularly suitable for demanding applications.



Performance @ Altitude and High Ambient Conditions (TBD)

When using at altitude and high ambient conditions the engine and alternator will de-rate as per chart below.
















		Temperature °C (°F)										
		0 (32)	5 (41)	10 (50)	15 (59)	20 (68)	25 (77)	30 (86)	35 (95)	40 (104)	45 (113)	50 (122)
Height m (ft)	0	-	-	-	-	-	-	-	-	-	-	-
	500 (1640)	-	-	-	-	-	-	-	-	-	-	-
	1000 (3280)	-	-	-	-	-	-	-	-	-	-	-
	1500 (4921)	-	-	-	-	-	-	-	-	-	-	-
	2000 (6561)	-	-	-	-	-	-	-	-	-	-	-
	2500 (8202)	-	-	-	-	-	-	-	-	-	-	-
	3000 (9842)	-	-	-	-	-	-	-	-	-	-	-
	3500 (11482)	-	-	-	-	-	-	-	-	-	-	-
	4000 (13123)	-	-	-	-	-	-	-	-	-	-	-
	4500 (14764)	-	-	-	-	-	-	-	-	-	-	-
	5000 (16404)	-	-	-	-	-	-	-	-	-	-	-

Power Distribution

The main power is connected from the alternator through a 3-position voltage selector switch to the main power cubicle. The cubicle incorporates all power distribution, controls, sensing and protection devices.

- ✓ 3-position Voltage Selector Switch (VSS)
- ✓ Current transformer x 3 (1 each leg)
- ✓ Single main breaker w/shunt trip
- ✓ Individual breakers for each receptacle
- ✓ Convenience receptacles located on outside of unit for easy access
- ✓ Terminal board for hard wiring
- ✓ Cam-Lock external quick connect (available as option)
- ✓ External emergency stop switch (recessed)
- ✓ Neutral bonded to Ground with a removable bonding link accessible in the control cubicle

Please refer to the chart below for power distribution and voltages. NOTE: All voltages below are subject to change, depending on set point of “Fine Voltage Adjustment” potentiometer and Voltage Selector Switch.

		120V Receptacle NEMA 20-5R	125/250V Receptacle CS6364	Terminal Board
Fine Voltage Adjustment ↓	Voltage Selector Switch Position ↓			
	 240/120V 1Ø	120V	240/120V	
	 240/139V 3Ø	139V	240/139V	
	 240/139V 3Ø	120V	208/120V	
	 480V 3Ø	139V	240/139V	

- All voltages are adjustable with the “Fine Voltage Adjustment” potentiometer located on the control panel. Therefore, voltage may be different then what is shown in the above table. All voltages should be verified before connection to the unit.

Controller

The QAS 625come equipped with a DeepSea 7310 control module. This is a fully diagnostic ECU controller with large 3" display, that is intuitive and easy to operate with all functions conveniently at your fingertips. The controller also manages the engine ECU operating system, and a number of safety warnings and shut downs on various parameters (listed below).

The controller is powered by a main On/Off switch located next to unit.

DeepSea 7310 Controller Functionality:

Home Page (displayed while running, scrolling every 3seconds)

- ✓ Generator voltage (ph-ph)

Status Page

- ✓ Generator voltage (ph-N)
- ✓ Generator voltage (ph-ph)
- ✓ Generator frequency
- ✓ Generator kw
- ✓ Generator power factor
- ✓ Generator amperage

Generator Page

- ✓ Generator current (A)
- ✓ Generator earth current
- ✓ Generator load (kw)
- ✓ Generator load (kVA)
- ✓ Generator power factor
- ✓ Generator load (kVAh)
- ✓ Generator load (kWh, kVAh, kVArh)
- ✓ Generator phase sequence
- ✓ Dual mutual status

Event Page

- ✓ Displays the last 15 events

Remote Start/Stop

- ✓ Automatic start/stop via 2 wire dry contact connection

Operational Buttons

- ✓ Start button
- Stop button
- Automatic mode (external remote start)
- Up/Down arrows

Info Page

- ✓ Model number
- ✓ USB identification number
- ✓ Configured engine type
- ✓ Module's date and time
- ✓ Scheduler setting

Engine Page

- ✓ Engine speed
- ✓ Oil pressure
- ✓ Coolant temperature
- ✓ Engine battery volts
- ✓ Run Time
- ✓ Oil Temperature
- ✓ Fuel Temperature
- ✓ Turbo Pressure
- ✓ Fuel Pressure
- ✓ Fuel Consumption
- ✓ Fuel Used
- ✓ Fuel Level
- ✓ Auxiliary Sensors
- ✓ Engine Maintenance Due
- ✓ Engine ECU Link

Engine DTC Page

- ✓ This page contains any active Diagnostic Trouble Codes that the engine ECU is currently generating. These alarms are conditions detected by the engine ECU and displayed on the DSE controller.



Engine

Volvo

Volvo Tier 4 Final, turbo charged, intercooled, six-cylinder, liquid-cooled diesel engine provides ample power to operate the generator continuously at full-load.

Meets all US EPA, CARB and Environment Canada exhaust legislations with Tier 4 Final compliance. The engine utilizes a Selective Catalytic Reduction (SCR) and Diesel Exhaust Fluid (DEF) to meet final Tier 4 emissions. All functionality of the engine is monitored automatically on the controller.

The engine has the capability to start the generator at 14°F (-10°C) with standard glow-plug aid. Cold start options are available for machine starting for down to -13°F (-25°C).

The 700 Gal (2,646 l) fuel tank is sufficiently sized to operate the unit at full-load condition for long run times (see chart on page 2 for specifications).

The engine operates on a 24V negative ground electrical system with a charging alternator and lockable battery cutoff switch.

The cooling system is suitably designed for continuous operation in ambient conditions up to 122°F (50°C), with canopy door closed.

Fuel System

A large 700 US Gal (2,646 l) fuel tank provides safe diesel storage while eliminating tank corrosion contaminants from being introduced to your fuel system. With integrated fuel water separator and filter, the system is designed to help maintain clean and trouble-free diesel supply to the engine for reliable trouble-free operation.

- ✓ Pad-lockable diesel fill cap
- ✓ Fuel / Water separator
- ✓ Inline priming pump (w/ filter)
- ✓ Fuel pre-filter
- ✓ Fuel supply pump (w/ strainer)
- ✓ Fuel level sensor
- ✓ Low fuel shut down feature (programmable level)

Scheduled maintenance

Standard equipped with filters sized and designed to allow 500-hour service intervals under normal operating conditions. Extended time between services reduces down time and total cost of ownership of the unit over its lifetime.

- | | |
|------------------------------|-------------------------------|
| • 500 Hour Service Interval: | • 1000 Hour Service Interval: |
| ✓ Oil filter | ✓ Air filter |
| ✓ Fuel filter | ✓ Oil filter |
| ✓ Fuel / water separator | ✓ Fuel filter |
| | ✓ Fuel / water separator |

NOTE: Site specific operating conditions such as; poor fuel quality and low load profile may require more frequent service intervals.

Enclosure & Frame

The generator enclosure is designed for extreme applications to provide superior performance and reliability.

The enclosure is fabricated from coated steel which is powder coated for corrosion resistance. The enclosure and frame are fully sealed from the radiator to the back of the unit, providing a true 110% containment of all fluids.

- ✓ Zink rich primer, powder coated enclosure
- ✓ Heavy duty base frame
- ✓ 110% fluid containment
- ✓ Superior level of rain ingress protection and design features
- ✓ Pad-lockable doors and fuel cap
- ✓ Engine fluid plumbed to exterior of frame for ease of service
- ✓ Central lifting point
- ✓ Sound dampening material and design to allow quiet operation at 73 dB(A)

Undercarriage

The QAS 625 is available with two undercarriage alternatives, providing utmost flexibility in installation, site handling or towing. Both the skid frame and the trailer mount the same way and can be interchanged for versatility.

- Trailer mounted:
 - ✓ Triple axle trailer
 - ✓ Available with hydraulic or electric brakes
 - ✓ DOT/Federal approved light package and 6 pin plug
 - ✓ Adjustable height pintle hitch (3" lunette)
 - ✓ 17.5" Rims with 215/75R LR H Tires for trailer use
 - ✓ Heavy Duty torsion axles
 - ✓ Safety chains
 - ✓ Screw jack leveling, with pad foot
 - ✓ Single point lifting structure
 - ✓ Tie down points x4
- Skid mounted:
 - ✓ Sub-frame skid with integrated forklift pockets
 - ✓ Heavy duty design for use in extreme conditions
 - ✓ Built-in locations for straps or chains to secure the unit for transport
 - ✓ Single point lifting structure

Factory Options Available

- Skid mounted
- Paralleling controller
- Cold Weather Kit
- Battery charger
- Spare tire
- Stabilizer jacks
- Toolbox
- CSA Kit
- Battery Charger
- Camlocks
- External Fuel Tank Valves

Manufacturing & Environmental Standards

The **QAS 625 VD** are manufactured following stringent ISO 9001 regulations, and by a fully implemented Environmental Management System fulfilling ISO 14001 requirements.

Attention has been given to ensure minimum negative impact to the environment.

The **QAS625 VD T4F** meets all current US EPA, CARB and Environment Canada exhaust and noise emission directives.

Supplied Documentation

The unit is delivered with documentation regarding:

- Hard copies of the Atlas Copco Operators Safety and Instruction Manual, Atlas Copco Parts Book, Volvo Engine Manual and Parts book, in English as well as electronic copies available on request.
- Warranty Registration card for engine and Atlas Copco Generators (Units must be registered upon receipt).

Warranty Coverage

Atlas Copco Generator: Warrantied to be free from defects with regard to material and workmanship for the period of eighteen (18) months from date of shipment from the factory, or twelve (12) months from date of initial startup, whichever occurs first, without limitation of running hours.

Volvo Engine: Twenty four (24) months or a maximum of three thousand (3000) hours of operation whichever occurs first (with the first twelve (12) months at unlimited running hours).

Leroy Somer Alternator: Warrantied to be free from defects with regard to material and workmanship for the period of twenty-seven (27) months from date of shipment from the factory, or twenty-four (24) months from date of initial startup or 10,000 hours, whichever occurs first.