

DLX Enterprises LLC 2026 HGAC Buy Retail Pricing Spreadsheet			
Solicitation: GE08-26			
E: Miscellaneous			
Item #	Name	Description	MSRP
246	HC382524 Earth	Best Case by DLX™ Earth 38 x 25 x 24 in (96.52 x 63.50 x 60.96 cm)	\$ 2,055.63
263	HC752524 Earth	Best Case by DLX™ Earth 75 x 25 x 24 in (194.63 x 63.50 x 60.96 cm)	\$ 2,709.06
351	PLPD200	POWER DISTRIBUTION PANEL - HIGH POWER	\$ 5,579.73
		• Six Position // (6) 50 A	
		• 200 A distribution panel	
		• (5) 200 A female Cam-Lok tail set, 10 ft (3 m)	
364	PLPC15A50	POWER CABLE 120V // 15A // 50 ft	\$ 86.47
		• 120 volt	
		• 15 A	
		• 50 ft (15.2 m)	
366	PLPC30A50	POWER CABLE 230V // 30A // 50 ft	\$ 513.35
		• 230 volt	
		• 30 A	
		• 50 ft (15.2 m)	
367	PLPC50A50	POWER CABLE 230V // 50A // 50 ft	\$ 210.00
		• 230 volt	
		• 50 A	
		• 50 ft (15.2 m)	
432	PLPS50	50 AMP POWER DISTRIBUTION PANEL	\$ 1,141.18
		• 50 A temporary power box w/ 50 A feed-thru (Spider Box)	
		• (6) 20 A GFCI L5-20R	
		• (1) 30 A 250V L6-30R	
		• (1) 50 A California Style Plug (power input)	
		• (1) 50 A California Style Receptacle (passthrough)	
		• NEMA 3R & UL 1640	
568	PLPS50K	50 AMP POWER DISTRIBUTION PANEL KIT	\$ 3,347.93
		• 50 A temporary power box w/ 50 A feed-thru - (6) 20 A GFCI duplex receptacle	
		• (1) 230V // 50 A Power cable, 50 ft	
		• (6) 120V // 15 A Power cable, 50 ft	
		• (1) Best Case by DLX™ Red 38 x 25 x 24 in (96.52 x 63.50 x 60.96 cm)	
578	PLPD200K	POWER DISTRIBUTION PANEL - HIGH POWER KIT 3 PH WITH CASE	\$ 7,437.85
		• Six Position // (6) 50 A	
		• (5) 200A female Cam-Lok tail set, 10 ft (3 m)	
		• (1) Best Case by DLX™ Red 50 x 25 x 25 in (127.33 x 63.50 x 63.50 cm)	
740	PLGRK	GENERATOR GROUNDING ROD KIT	\$ 236.25
		• (1) Copper grounding rod // 4 ft (1.2 m)	
		• 10-14 grounding wire with terminal // 25 ft (7.6 m)	
		• ABS storage and transport pipe // 50 in (127 cm)	
748	TGDLX1	DLX TRAINING 1 Day • (1) DLX trainer • (1) Day (up to 8 Hrs) DLX equipment instruction on setup/ takedown/ packing/ care & maintenance	\$ 2,929.00
2095	TLGET1	GET-HX Single Axle Flat Deck Trailer ONLY	\$ 39,909.00
2106	PLGPC	Generator Power Cord 50-Amp 50ft. 125/250-volt 14-50p To Cs6364 Locking Connector	\$ 447.00
2129	PLSLPOLE	SOLAR LIGHT POLE	\$ 3,900.86
		• Solar powered LED light	
		• 4' -10' telescoping pole	
2216	PL15GENVC	• Powder coated base plate	
		Vinyl Cover for 15KVA Shindaiwa Generator	\$ 253.00
2266	TGDLX2	DLX TRAINING 2 Day	\$ 5,282.35
		• (1) DLX trainer	
		• (2) Days (Up to 8 Hrs / Day) DLX equipment instruction on setup/ takedown/ packing/ care & maintenance	
2310	PLYA50	POWER LOGIX // 50-A SPLITTER	\$ 425.50
		Kit Contents	
		(1) Y Adapter, 50A Comment end	
		• 6/3-8/1 SOW Rubber Jacket, 50A “Y” Adapter	
		• Input (1) 50A Twist-Lock CS63 Plug	
		• Output (2) 50A Twist-Lock CS63 Receptacle	
		• Weight - 6 lbs	

2400	TGIMB	INSPECTION AND MAINTENANCE, BASIC [ADD CUSTOMER-SPECIFIC MAINTENANCE ITEMS] • Performance of scheduled maintenance • Diagnosis and isolation of customer identified and traced equipment malfunctions • Replacement/ Repair of minor assemblies/modular components that can be readily removed/installed and do not require critical adjustment. • Provide guidance for servicing of any items out of, or not covered under the manufacturer warranty.	\$ 2,929.00
2431	PLPX1000GZK	POWER LOGIX // OFF GRID POWER KIT // 1000W W/ SOLAR • (2) GZ Yeti 500X Battery Banks • (2) GZ Nomad 100 Solar Panel • (2) 8mm Input Extension Cable, 30ft • (1) Wheeled Stackable Hard Case, IP67 , 33" x 25" x 19", Waterproof	\$ 3,572.00
2432	PLPX2000GZK	POWER LOGIX // OFF GRID POWER KIT // 2000W W/ SOLAR • (2) GZ Yeti 1000x Battery Banks • (4) GZ Nomad 100 Solar Panel • (2) 4X 8mm Combiner to HPP Connector • (4) 8mm Input Extension Cable, 30ft • (1) Wheeled Stackable Hard Case, IP67 , 32.95" x 24.96" x 18.74" w/ Foam insert	\$ 6,745.00
2460	PLGZHPP30	HIGH POWER PORT 30 FT EXTENSION CABLE	\$ 59.95
2497	PLPD400K	POWER DISTRIBUTION PANEL - 400 AMP • (2) 200 amp power panels • (10) 200A female Cam-Lok tail set, 10 ft (3 m) • (1) Best Case by DLX™ Red 50 x 25 x 25 in (127.33 x 63.50 x 63.50 cm)	\$ 13,116.00
2579	Plug Adapter L6-30P to 6-30R 30A	1.5 ft. L6-30P 3-Prong 250-Volt Locking Plug to 6-30R 3-Prong 30 Amp 250-Volt HVAC Female Adapter	\$ 107.73
2603	Plug Adapter, Generator plug to CA receptacle	10' Plug Adapter, 8/6 SEOW Black Amperage: 30A Voltage: 125/250V Plug: 14-50P Connector: 50A CA Twist	\$ 513.00
3194	GET-HX Strap Kit	GET-HX Trailer Strap Kit 10) 12" short straps with Ratchet and Single Stud L-Track fitting 10) 135.75" Long straps with Single Stud L-Track Fitting	\$ 265.50
3444	TLGET2	GET-HX Tandem Axle Flat Deck Trailer ONLY Trailer Dimensions (LxW) 264 x 96 in (6.7 x 2.43 m) Tandem 8,000 lb Axle *See Technical Data Sheet for full specifications. *Replaces DLX p/n GET-HX TANDEM	\$ 49,600.00
3391	PLPS50KEXM	50 AMP POWER DISTRIBUTION PANEL KIT • 50 A temporary power box w/ 50 A feed-thru - (6) 20 A GFCI duplex receptacle • (1) 230V // 50 A Power cable, 50 ft • (6) 120V // 15 A Power cable, 50 ft Extreme Weather • (1) Best Case by DLX™ Red 38 x 25 x 24 in (96.52 x 63.50 x 60.96 cm)	\$ 3,946.00
3420	PLR100SP40	BATTERY UNIT - DANGEROUS GOODS UN3480 Power: 100W Capacity:146Wh/39600mAh USB-A Output: 5V/3.1A, 5V/3A, 9V/2A Type-C Output: 5V/3A, 9V/2A DC Output: 9~12.6V/10A Max AC Output: 220-240V 50Hz EU Socket Size: 19.2*15.6*9.4cm N.W: 1.5kg SOLAR PANEL Power: 40W DC Output:15V/2.66A USB-A Output:5V/3A, 9V/2A, 12V/1.5A Type-C Output: 5V/3A 9V/3A 12V/2.5A, 15V/2A Folding Size: 30.4*22*4cm N.W: 2.1kg Unfolding Size:88.2*30.4*2cm	\$ 330.00
4093	PVC Flex Duct 12" x 15' Tan	12" dia x 15' long Tan ABC Enviroduct 1399 tan, 4" pitch, belt cuffs each end	\$ 367.00
4094	PVC Flex Duct 14" x 15' Tan	14" dia x 15' long Tan ABC Enviroduct 1399 tan, 6" pitch, belt cuffs each end	\$ 335.00
4095	PLIP165	Victron Blue Smart IP165 Charger 120V 12V/4 Trickle charger used for generators PowerLogix 440 Solar Charging Array	\$ 120.00

4105	PLSCA440	440W, 4 Panel Solar Charger	\$ 1,534.00
		Shelter Roof and Ground Mount Compatible	
		Panel Dimension - 39.8 x 23.6 in. (101 x 60 cm)	
		Deployed Dimension - 91 x 49 in. (231.1 x 124.5 cm)	
		Packed Dimension - 45.5 x 24 x 4 (115.6 x 60.9 x 10.2 cm)	
		Weight - 31 lbs. (14 kg)	
		Contents	
		(2) Dual Solar Array Mounting Panel	
		(1) Array Panel Connector	
		(1) Array Connection Cable, 20ft (6.1 m)	
		(4) 110W Flexible Solar Panels, OD Green	
4257	PLHQCH50Z	Power Logix PLEx-HQcase 50 Hz	\$ 11,704.00
		3000VA 5.12kWh 1450W Solar Charger Gray Metal, Earth Case	
		1 Phase, 50 Hz 230VAC	
		Unit Dimensions - 38" W x 25" D x 16" H	
		Weight - 240lbs (108.6 kg)	
		Contents	
		(1) Power System Installed in a 38" Short Best Case	
		(1) Array Cable Adapter for PLEx-Convoy, 1.0 ft (0.3 m)	
		(1) Quick Start Guide	
		(1) Equipment Manual packet	
		(1) Extra Set of fuses	
4407	PLGM440	Ground Mount Frame Kit for 440 Solar Charging Array	\$ 1,426.00
		Collapsible Expeditionary Mounting system for PowerLogix Solar Charging Arrays	
		Deployed Dimensions - 96.5 x 49 x 36 in. (245.1 x 124.5 x 91.4 cm)	
		Packed Dimension - 47 x 4 x 8.5 in. (119.4 x 10.2 x 21.6 cm)	
		System Weight - 22 lbs. (9.95 kg)	
		Contents	
		(1) Complete Ground Mount Frame Assembly	
		(1) Carry Bag	
		(1) Stake and Repair Kit	
4412	PLRFSS5954	RF/EMI Shielding Enclosure for ASAP® Shelters	\$ 55,200.00
		Effectiveness - Up to 95dB from 30MHz - 18GHz	
		Deployed Dimensions 59 x 54 x 87 in (149.9 x 137.2 x 220.9 cm)	
		Single RF Secure Entry Door	
		Power Supply & Climate Control Waveguides	
		AC/ 0-250V, 20A Filter Box, 10KHz-1GHz, Type B	
		Removable I/O Plate w/ cover. (4) Cat6 RJ45, (2) FC/FC Fiber Optic Couplers	
		6" (127mm) 12VDC or 24VDC Intake/Exhaust Ventilation Fans w/ assembly kit	
4415	PLRFSSA12	RF/EMI Shielding Enclosure for ASAP®	\$ 92,870.00
		Fits ASAP® Models 12,18, 24	
		Effectiveness - Up to 95dB 30MHz - 18GHz	
		Deployed Dimensions 131 x 120 x 87 in (332.7 x 304.8 x 220.9 cm)	
		Single RF Secure Entry Door	
		Power Supply & Climate Control Waveguides	
		AC/ 0-250V, 20A Filter Box, 10KHz-1GHz, Type B	
		Removable I/O Plate w/ cover. (4) Cat6 RJ45, (2) FC/FC Fiber Optic Couplers	
		6" (127mm) 12VDC or 24VDC Intake/Exhaust Ventilation Fans w/ assembly kit	
4605	PLSW30AD	20A CIRCUIT BREAKER ON BOTH ENDS PROTECTS THE UNIT FROM OVERCURRENT	\$ 677.00
		125/250V 30A inlet, L14-30P, Twist-to-lock	
		(4) 125V 20A duplex receptacles, NEMA 5-20R	
		(2) Class "A" ground-fault circuit-interrupters (GFCI)	
		(2) Circuit Breakers, Single-Pole 20A	
		10" x 10" x 6.75"	
		10.8 lbs	
4657	PLSW30ADK	20A CIRCUIT BREAKER KIT	\$ 2,957.00
		BOTH ENDS PROTECTS THE UNIT FROM OVERCURRENT	
		125/250V 30A inlet, L14-30P, Twist-to-lock	
		Kit Contents:	
		• 20A Circuit Breaker	
		• Power cable 30A	
		• (4) Power cables 15A	
		• Best Case by DLX™ Red 38 x 25 x 16 in (94.90 x 63.50 x 40.64 cm)	
		20W folding panel - Portable Solar Charger	
		Ports and quantities – 1x USB-A 5V, 1x USB-C 5V	
		Deployed: 17.5x12.8x0.5"	

4815	PLDS20	Folded 8.7x12.8x0.7"	\$ 62.00
		weight 1.385 lb	
		Charge time to 100W = 2 days	
		Cell Type - MonocrCharging Cordystalline	
		2x Carabiners, Manual	
4854	PLMLDLT18HD	Diesel LED Light Tower Flood Lights	\$ 39,412.00
		Floodlights 4x32 W LED	
		Total Lumen 166,200	
		L x W x H 122 x 57.5 x 95 "	
		Total Weight 2645 Lb	
		Mast Height 8.5 M 27.8ft	
		Max Wind Rating 110 KPH (68mph)	
		Power 15kW	
		Electrical Receptacles (4) 20 Amp/120V GFI Duplex, (2) 30 Amp Twist Lock, (1) 50 Amp Twist Lock	
		Interior Compartment Work Lights 2x LED	
		Generator End Linz SLS18 MD	
		Engine Model Kohler KDI 1903 M	
		Sound Level 68dBA	
		Fuel Diesel	
		Fuel Tank Capacity 240 Liters / 63 US Gal	
4927	PLPD17843	Fuel Consumption 2.8 Liters per hour at 50%, 4.0 Liters at 75%, 5.4 Liters at 100% load.	\$ 955.00
		Run Time (75% Load) 62.5 hrs	
		Secondary Fluid Containment 110%	
		DLX Power Distribution Kit REF#DZ17843	
		(1) PCE IMST Distribution Box 32Amp 230V IP44	
		Incoming Circuit: 32A 230V 2P+E IP44	
		Through Socket: 32A 230V 2P+E IP44 Panel Socket	
		Outgoing Circuits: 2 x 16A 1P+N+E 230V CEE Panel Sockets IP44, 2 x 16A 1P+N+E 230V Schuko Panel Sockets IP44	
		Outgoing protection: 4 x 16A 2P 30mA RCBO Type A	
		(1) Power Cable, 10m, H07RN-F 6mm2, Rubber, 32A 2P+E 230V Plug & Connector IP44, Black	
4952	PLPD17850	DLX Power Distribution Kit REF#17850	\$ 1,177.00
		(1) PCE IMST Distribution Box 32Amp 230V IP65	
		Incoming Circuit: 32A 230V 2P+E IP67 Flanged Plug	
		Through Socket: 32A 230V 2P+E IP67 Panel Socket	
		Outgoing Circuits: 2 x 16A 1P+N+E 230V CEE Panel Sockets IP44, 2 x 16A 1P+N+E 230V Schuko Panel Sockets IP54	
		Outgoing protection: 4 x 16A 2P 30mA RCBO Type A	
		(1) Power Cable, 15m, H07RN-F 6mm2, Rubber, 32A 2P+E 230V Plug & Connector IP67, Black	
5165	PLRFSS5954-BAA	RF/EMI Shielding Enclosure for ASAP® Shelters	\$ 62,544.00
		**Berry Amendment Compliant	
		Effectiveness - Up to 95dB from 30MHz - 18GHz	
		Deployed Dimensions 59 x 54 x 87 in (149.9 x 137.2 x 220.9 cm)	
		Single RF Secure Entry Door	
		Power Supply & Climate Control Waveguides	
		AC/ 0-250V, 20A Filter Box, 10KHz-1GHz, Type B	
		Removable I/O Plate w/ cover. (4) Cat6 RJ45, (2) FC/FC Fiber Optic Couplers	
		6" (127mm) 12VDC or 24VDC Intake/Exhaust Ventilation Fans w/ assembly kit	
5166	PLRFSSA12-BAA	RF/EMI Shielding Enclosure for ASAP®	\$ 108,907.00
		**Berry Amendment Compliant	
		Fits ASAP® Models 12,18, 24	
		Effectiveness - Up to 95dB 30MHz - 18GHz	
		Deployed Dimensions 131 x 120 x 87 in (332.7 x 304.8 x 220.9 cm)	
		Single RF Secure Entry Door	
		Power Supply & Climate Control Waveguides	
		AC/ 0-250V, 20A Filter Box, 10KHz-1GHz, Type B	
		Removable I/O Plate w/ cover. (4) Cat6 RJ45, (2) FC/FC Fiber Optic Couplers	
		6" (127mm) 12VDC or	
5255	CCYDCT14	Y Duct, 14 x 14 x 14 in.	\$ 350.00
5256	CCYDCT12	Y Duct, 12 x 12 x 12 in.	\$ 350.00
		Soft Collapsing Y Duct Adapter with Metal Attachment Rings	
		Power Logix Alternator Add-on for PLEx-HQcase	

5390	PLHQC-ALT	12V or 24V Alternator Charger, Charging up to 50A (700W)	\$ 740.00
		Compatible with Smart Alternators	
		Additional Weight - 3lbs	
		Contents	
		(1) 12/24V Alternator Charging Sub-System	
		(1) Equipment Manual	
5501	PLDS40	(1) Extra Set of fuses	\$ 121.00
		40W folding panel - Portable Solar Charger Ports: 1x USB-A 5V, 1x USB-C 5V Deployed: 17.5x36.22x0.12" Folded 17.5x12.8x1.45" weight 1.385 lbs, Cell Type - Monocrystalline 2x Carabiners, Manual, Olive Green	
5528	CCHVAC5TVC	Vinyl cover 5T HVAC	\$ 228.00
5725	PLPD18620	Power Distribution Unit	\$ 1,082.00
		32amp 1PH+N+E 230V Rubber box	
		Incoming:	
		32A 3p 6h 230V IP67 PCE Black Appliance Inlet.	
		Outgoing:	
		32A 3p 6h 230V IP67 PCE Black Panel Socket Loop	
		2 x 16A 3p 6h 230V IP67 PCE Black Panel Socket	
		2 x 16A 3p 6h 230V IP54 PCE Schuko Panel Socket	
		Protection:	
		2 x RCBO C16 1pN 4,50kA ldn 0,03A A 1M Din (Siemens, 5SV1313-7KK16).	
		2 x RCBO C16 1pN 4,50kA ldn 0,03A A 1M Din (Siemens, 5SV1313-7KK16).	
		Installed accessories: 1 red led (IN / LOOP), 4 green leds (OUT).	
		Box dimensions W230 x D230 x H270mm	
		Weight 6.50kg	
		Technical Data & Compliance Info: IEC 61439-1 & 2 / PSC, CE & UKCA marking, Un 230V 1PH+N+E fn 50Hz, InA 32A, lcc 4.500A, RDF 50/100,	
		Electrical insulation class I (first).	
		PBF32M 2M1 2M1S RT-S.	
		Power Cable	
		10 Metre H07RN-F 6mm2 Rubber Cable 3 Core	
		32A 2P+E 230V IP67 PCE Plug & Connector, Black	
		Included Attachments:	
		20W USB 2 Socket Extension	
		13A, Schuko Earthed Plug	
		1x Type A, 1x Type C	
		IP20	
5750	14W Folding Solar Panel	14W Folding Solar Panel	\$ 40.00
		SOLAR-SG014-FOLD	
5751	20W Folding Solar Panel	20W Folding Solar Panel	\$ 62.00
		SOLAR-SG020-FOLD	