

1250-2000kW Aluminum Enclosure & UL Sub Base Tank Packages

Table of Contents

Page Numbers

Selection Guide for Package Enclosures

2-3

1250-2000kW Weather Enclosure with External Silencer

Standard Features

4

Enclosure & Tank Packages

5

Options

6-7

1250-2000kW Sound Enclosure Level 1 with External Silencer

Standard Features

8

Enclosure & Tank Packages

9

Options

10-11

1250-2000kW Sound Enclosure Level 2 with External Silencer

Standard Features

12

Enclosure & Tank Packages

13

Options

14-15

1250-2000kW Weather Enclosure with Internal Silencer

Standard Features

16

Enclosure & Tank Packages

17

Options

18-19

1250-2000kW Sound Enclosure Level 1 with Internal Silencer

Standard Features

20

Enclosure & Tank Packages

21

Options

22-23

1250-2000kW Sound Enclosure Level 2 with Internal Silencer

Standard Features

24

Enclosure & Tank Packages

25

Options

26-27

Note: "Package" enclosures/tanks are only available with radiator cooled applications.

Selection Guide for Aluminum Enclosure & Sub Base Tank “Packages”

Weather & Sound Level 1 Enclosures with External Silencer

When a “package” weather enclosure or sound enclosure level 1 with external silencer is selected, you will be required to make a loose critical silencer selection (due to multiple silencer options available)

The following items are automatically selected for you:

- Loose flex exhaust & weld on flange. These will be installed before shipment.
- Installed flex fuel lines (if tank is selected).
- Loose inner tank leak alarm (if a tank is selected). This will be installed before shipment.
- Spring isolators (for solid mount applications). These will be installed before shipment.
- Battery charger installation (when a battery charger and “package” enclosure are both chosen)

Note: battery chargers must be ordered loose, they will be installed for shipment

Sound Level 2 Enclosures with External Silencer

When a “package” sound enclosure level 2 with external silencer is selected, you will be required to make a loose hospital silencer selection (due to multiple silencer options available)

The following items are automatically selected for you:

- Loose flex exhaust & weld on flange. These will be installed before shipment.
- Installed flex fuel lines (if tank is selected).
- Loose inner tank leak alarm (if a tank is selected). This will be installed before shipment.
- Spring isolators (for solid mount applications). These will be installed before shipment.
- Battery charger installation (when a battery charger and “package” enclosure are both selected)

Note: battery chargers must be ordered loose, they will be installed for shipment

Weather, Sound Level 1 & Sound Level 2 Enclosures with Internal Silencer

When a “package” weather, sound level 1 or sound level 2 enclosure with internal silencer are selected, **the following items are automatically selected for you”**

- Installed flex fuel lines (if tank is selected).
- Loose inner tank leak alarm (if tank is selected). This will be installed before shipment.
- Spring isolators (for solid mount applications). These will be installed before shipment.
- Battery charger installation (when a battery charger and “package” enclosure are both selected)

Note: weather and sound level 1 enclosures with internal silencers include a critical silencer

Sound level 2 enclosures with internal silencers include a hospital silencer

Selection Guide for Aluminum Enclosure & Sub Base Tank “Packages” Cont’d

“Package” enclosures/tanks are only offered for radiator cooled applications.

When a “package” enclosure is selected, the system will display the following additional characteristics:

- Enclosure Silencer (External or Internal)
- Enclosure Material (Aluminum)
- Enclosure Subbase Tank
- Enclosure Basic Electrical Package
- Enclosure Electrical Accessories
- Enclosure Accessories

When a tank is selected, the system will display the following additional characteristic:

- Enclosure Tank Accessories

A selection in the “Enclosure Subbase Tank” characteristic is required. If you do not want a tank, choose the option “Lift Base Only”.

Characteristic “Enclosure Tank Acc.” is not available when “Lift Base Only” (Value 0000) is selected from the characteristic “Enclosure Subbase Tank”.

Enclosure electrical accessory “Basic Electrical Package” of a “Load Center” is a prerequisite for selecting any of the following options:

- Wiring of block heater
- Wiring of battery charger
- Enclosure heater
- Exhaust fan
- Emergency lights
- Motorized louvers
- Transformer
- Supply fuel transfer system for tank

Only enclosure accessories and sub-base fuel tanks from this bulletin can be ordered with these “package” enclosures.

Ordering Block Heaters with Enclosure Packages

When ordering single phase or three phase block heaters the following enclosure options selections must match the phase of the block heater:

Basic Electrical Package
Load Center
Enclosure Heater

Standard Features

Aluminum Weather Enclosures for External Silencers & UL Tank Packages

► **Weather Enclosures with External Silencer designs require Kohler critical external silencer, flex exhaust & weld-on flange (these options will be auto-selected in the quotation system)**

Weather Enclosure Features:

► **Available in Aluminum (.080) formed panel, solid construction**

Pre-assembled package offers a corrosion resistant aluminum, dent resilient structure that mounts directly to lift base or tank.

► **Polyurethane Enamel Paint**

Superior finish, durability and appearance.

► **Interchangeable Modular panel construction**

Allows complete serviceability or replacement without compromising enclosure design.

► **Service Access**

External radiator fill, six personnel doors for easy access to generator set control and servicing of fuel fill, fuel gauge, oil fill & battery.

► **Turning of Control Panel**

If generator has a single circuit breaker then the control panel is turned to opposite side of the breaker. If dual breaker consult factory.

Cooling/Combustion Air Intake:

► **Fixed air inlet louvers**

Sized for maximum cooling airflow constructed of same material as housing

Cooling Air Discharge:

► **Alternator cooling**

Punched air louvers provide cooling air for alternator.

► **Punched air Gravity Outlet 90° grid**

Accommodates largest generator set radiator within the gen-set group.

Standard Sub-Base Tank Features:

► **Extended Operation**

Usable tank capacity offers full load standby operation of up to 48 hours through 2000 kW

► **UL Listed**

Secondary containment generator base tank meets UL 142 special purpose tank requirements.

► **NFPA compliant**

Designed to comply with the installation standards of NFPA 30, NFPA 37 and NFPA 110

► **Integral external lift lugs**

Enables crane with spreader-bar lifting of complete package (empty tank, mounted gen-set and enclosure) to ensure safety.

► **Emergency pressure relief vent caps**

Meets UL requirements - insures adequate venting of inner and outer tank under extreme pressure and/or emergency conditions

► **Atmospheric vent cap**

Oversized 2" vent is raised above lockable fuel fill

► **Low fuel level and leak detection switch**

Annunciates a contained primary tank fuel leak or a 50% low fuel level condition at Generator Set Control

► **Full width electrical stub-up**

Easy access via removable end channel.

► **Fuel transfer system**

Tank top mounting bracket offers location for (optional) fuel transfer system for extended generator set operation or for customer specified tank monitoring

► **Rain runoff**

Included when tanks extend beyond the enclosure, ensures rain run-off.

Options:

See Weather Enclosure for External Silencer list of options

Pricing

Aluminum Weather Enclosures for External Silencer & UL Tank Packages

Kohler Package Part Numbers	Secondary Cont. UL Tank Gallon Capacity	Estimated fuel supply hours at 60hz with full load	Package Dimensions¹ Inches			Shipping Weight lbs.	Elec. Stub Up L x W	List Price
			Length	Width	Height			2024
1250 REOZMD ADV-7775 40°C & 50°C ADV-8551 SEISMIC GM72613-TPG								
GM72661-TAG	Lift Base		282	102	129	32310	37 x 90	\$163,321
GM72662-TAG	1350	13	302	102	137	35170	37 x 90	\$191,086
GM72663-TAG	1600	15	302	102	140	35530	37 x 90	\$193,588
GM72664-TAG	2100	20	302	102	145	36270	37 x 90	\$197,768
GM72665-TAG	2600	25	302	102	150	36960	37 x 90	\$201,953
GM72666-TAG	3130	30	302	102	155	37630	37 x 90	\$206,141
GM72667-TAG	4150	40	332	102	161	39360	37 x 90	\$217,590
GM72668-TAG	5150	50	390	102	163	41220	37 x 90	\$250,425
GM72669-TAG	6160	60	450	102	163	43000	37 x 90	\$265,153
GM72670-TAG	7700	74	550	102	163	45960	37 x 90	\$289,733
1600 REOZMD ADV-7778 40°C & 50°C ADV-8551 SEISMIC GM72616-TPG								
GM72691-TAG	Lift Base		310	108	133	38300	37 x 96	\$183,180
GM72692-TAG	1350	10	330	108	139	41400	37 x 96	\$211,207
GM72693-TAG	1600	12	330	108	141	41725	37 x 96	\$213,096
GM72694-TAG	2100	16	330	108	145	42350	37 x 96	\$216,879
GM72695-TAG	2600	20	330	108	150	43070	37 x 96	\$221,598
GM72696-TAG	3130	24	330	108	154	43650	37 x 96	\$225,343
GM72697-TAG	4150	32	330	108	163	44960	37 x 96	\$233,788
GM72698-TAG	5150	40	382	108	165	46875	37 x 96	\$265,126
GM72699-TAG	6160	48	426	108	167	48545	37 x 96	\$278,469
GM72700-TAG	7700	60	518	108	167	51460	37 x 96	\$302,259
1750/2000 REOZMD ADV-7779 40°C ADV-8551 SEISMIC GM72617-TPG								
GM72701-TAG	Lift Base		320	114	139	41020	39 x 102	\$192,884
GM72702-TAG	1350	10/8	342	114	144	44280	39 x 102	\$220,938
GM72703-TAG	1600	11/10	342	114	146	44610	39 x 102	\$222,919
GM72704-TAG	2100	15/13	342	114	150	45210	39 x 102	\$226,849
GM72705-TAG	2600	18/16	342	114	154	45840	39 x 102	\$230,770
GM72706-TAG	3130	22/20	342	114	158	46445	39 x 102	\$234,696
GM72707-TAG	4150	29/26	342	114	166	47840	39 x 102	\$242,565
GM72708-TAG	5150	36/32	364	114	171	49310	39 x 102	\$271,074
GM72709-TAG	6160	44/38	406	114	181	53990	39 x 102	\$317,773
GM72710-TAG	7900	54/48	504	114	181	57160	39 x 102	\$343,723
1750/2000 REOZMD ADV-7780 50°C ADV-8551 SEISMIC GM72618-TPG								
GM72711-TAG	Lift Base		320	126	155	43570	39 x 114	\$211,195
GM72712-TAG	1350	10/8	342	126	159	46950	39 x 114	\$239,523
GM72713-TAG	1600	11/10	342	126	161	47270	39 x 114	\$241,602
GM72714-TAG	2100	15/13	342	126	164	47940	39 x 114	\$244,723
GM72715-TAG	2600	18/16	342	126	168	48590	39 x 114	\$248,891
GM72716-TAG	3130	22/20	342	126	171	49105	39 x 114	\$252,020
GM72717-TAG	4150	29/26	438	126	171	51710	39 x 114	\$270,398
GM72718-TAG	5150	36/32	360	126	191	55030	39 x 114	\$272,146
GM72719-TAG	6160	44/38	382	126	195	56470	39 x 114	\$282,993
GM72720-TAG	7900	54/48	454	126	197	59240	39 x 114	\$306,299

¹ Package dimensions are overall length, width and height. Overall length includes tank length.

Options

Aluminum Weather Enclosures for External Silencer & UL Tank Packages

Option	Description	Kohler Part #	List Price
Electrical			
DC Light Package	Two-(2) quantity DC interior lights powered by the starting battery on a fused circuit with a 0-60 minute "No-Lock-On" timer, 24 VDC standard.	GM73237-TAG	\$ 2,624
Additional DC Lights	Two additional DC Lights; only available when DC light package is ordered	GM73238-TAG	\$ 1,520
Basic Electrical Package 200 Amp Max (only one can be selected and cannot be ordered with Load Center)	Load center 120/208/240VAC single phase, 200 amp max w/ main and 12 branch circuits. (1) switch control (3) AC lights vapor tight and gasketed wiring of jacket water heater (2) duplex GFI receptacles.	GM76027-TAG	\$ 6,487
	Load center 120/208/240VAC 3 phase, 200 amp max w/ main and 12 branch circuits. (1) switch control (3) AC lights vapor tight and gasketed wiring of jacket water heater (2) duplex GFI receptacles.	GM76028-TAG	\$ 8,376
	Load center 120/240VAC, single phase, 200 amp max with main and 12 branch circuits. One-(1) switch control and <u>Two-(2) four foot LED lights</u> . Block heater wiring included. Two-(2) quantity duplex GFI receptacles.	GM76029-TAG	\$ 6,742
	Load center 120/208/240VAC, three phase, 200 amp max with main and 12 branch circuits. One-(1) switch control and Two-(2) four foot LED lights. Block heater wiring included. Two-(2) quantity duplex GFI receptacles.	GM76030-TAG	\$ 8,631
Additional Lights & Receptacles	Two Additional AC lights	GM73243-TAG	\$ 2,389
(only available with BEP or Load Center is ordered)	Additional duplex GFI receptacles (2 included - internal mounted)	GM73244-TAG	\$ 969
	Additional duplex GFI receptacles (2 included - external mounted)	GM73245-TAG	\$ 1,938
Load Center - 200 Amp Max (only one can be selected and cannot be orderd with BEP)	Load center 120/208/240VAC, single phase, 200 amp max with main and 12 branch circuits and wiring of the block heater	GM76025-TAG	\$ 2,278
	Load center 120/208/240VAC, 3 phase, 200 amp max with main and 12 branch circuits and wiring of the block heater	GM76026-TAG	\$ 4,167
Transformer Single Phase	Single Phase 37.5 kVA 480 primary /208/120 secondary Transformer; available only when BEP or Load Center is ordered	GM73248-TAG	\$ 12,656
Disconnect Switch (For 1-phase)	Disconnect Switch for Single phase 37.5 kVA Transformer; available only when Transformer is ordered	GM73249-TAG	\$ 3,449
Transformer 3 Phase	3 Phase 37.5 kVA 480 primary /208/120 secondary Transformer; available only when BEP or Load Bank is ordered.	GM73250-TAG	\$ 13,464
Disconnect Switch (For 3-phase)	Disconnect Switch for 3-phase 37.5 kVA Transformer; available only when Transformer is ordered.	GM73251-TAG	\$ 3,960
Emergency Lights	Dual head battery powered emergency lights includes batteries (qty 2) mounted inside enclosure; available only when BEP or Load Center is ordered	GM73252-TAG	\$ 1,556
Enclosure Heater	Single Phase - 208VAC 5kW thermostatically controlled heater	GM73253-TAG	\$ 6,564
(If block heater is ordered, a 3 phase block heater must be matched with 3 phase enclosure heater, must be	Single Phase - 240VAC 5kW thermostatically controlled heater	GM73254-TAG	\$ 6,564
	3 phase - 208VAC 5kW thermostatically controlled heater	GM73255-TAG	\$ 6,564
	3 phase - 240VAC 5kW thermostatically controlled heater	GM73256-TAG	\$ 6,564
Exhaust Fan	800 CFM Shutter-Mounted Exhaust Fan (Wall mounted); available only when BEP or Load Center is ordered	GM73257-TAG	\$ 2,762
Miscellaneous			
Battery Charger	Provide bracket mount & wire customer supplied battery charger to DC side of generator; can only be ordered with loose battery charger and either a BEP or Load Center	GM73258-TAG	\$ 1,933
Battery Charger With Alarms	Provide bracket mount & wire customer supplied battery charger with alarm to DC side of generator; can only be ordered with loose battery charger w/alarms and either a BEP or Load Center	GM73259-TAG	\$ 2,418
Viewing Window	Control Panel Viewing Window	GM73260-TAG	\$ 1,667
Alarm	High fuel level float switch; available only with a tank	GM73261-TAG	\$ 249
Alarm	Economical 3 alarm panel for high, low, and fuel leak (mounted inside enclosure); available only with a tank	GM73262-TAG	\$ 2,669
Alarm	Economical 3 alarm panel for high, low, and fuel leak (mounted outside enclosure); available only with a tank	GM73263-TAG	\$ 2,669
Fill/Spill	Above ground 5 gallon fill/spill containment, piping from fill to outside of enclosure. (External enclosure wall mount) Spill/fill to ship loose for field install or may be attached when it does not effect shipping; available only with a tank	GM73264-TAG	\$ 871
Emergency Stop	Emergency Stop Button - externally mounted	GM73265-TAG	\$ 1,547
Seismic Bracing	Necessary bracing and upgrades to the enclosures and tanks when IBC or OSHPD is selected (OSHPD only available on REOZMD models)	GM87027-TAG	\$ 27,281
ULC-S601 Listing	Canada Option	GM78723-TAG	\$ 667
Pad Lockable - now standard			
Automatic Door Holder - now standard			
Internal Release Handle			
Internal Release Handles	Internal Release Handles - 1 per door	GM73266-TAG	\$ 2,447
Supply Fuel Transfer Systems - only available with BEP or Load Center			
1250 kW through 1600 kW	Series 400 Electronic Control Module (ECM) with 4 GPM pump and 1/3 HP motor, solenoid valve, fuel strainer and critical high shutdown. Mounted, plumbed and wired as a Modular Fuel Transfer System; available only with a tank	GM73267-TAG	\$ 12,776

Options

Aluminum Weather Enclosures for External Silencer & UL Tank Packages

Option	Description	Kohler Part #	List Price
1750 kW through-2000kW	Series 400 Electronic Control Module (ECM) with 7 GPM pump and 1/2 HP motor, solenoid valve, fuel strainer and critical high shutdown. Mounted, plumbed and wired as a Modular Fuel Transfer System; available only with a tank	GM73268-TAG	\$ 13,898
Return Fuel Transfer Systems (MUST order Supply fuel transfer system)			
1250 kW through 1600 kW	A 7 GPM pump returns fuel to the main tank	GM73269-TAG	\$ 4,616
1750 kW through-2000kW	A 10 GPM pump returns fuel to the main tank.	GM73270-TAG	\$ 5,738
Motorized Discharge Louvers - only available with BEP or Load Center			
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1250 REOZMD	GM73271-TAG	\$ 9,849
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1600 REOZMD	GM73272-TAG	\$ 13,540
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73275-TAG	\$ 13,744
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73276-TAG	\$ 20,013
Motorized Intake Louvers - only available with BEP or Load Center			
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1250 REOZMD	GM73279-TAG	\$ 41,702
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1600 REOZMD	GM73280-TAG	\$ 41,702
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73283-TAG	\$ 48,736
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73284-TAG	\$ 55,467
Gravity Discharge			
Gravity Discharge	Gravity Discharge (Aluminum) - 1250REOZMD	GM73287-TAG	\$ 7,422
Gravity Discharge	Gravity Discharge (Aluminum) - 1600 REOZMD	GM73288-TAG	\$ 7,904
Gravity Discharge	Gravity Discharge (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73291-TAG	\$ 8,064
Gravity Discharge	Gravity Discharge (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73292-TAG	\$ 13,298
State Tank Accessories			
Fuel Fill Options	Fill pipe extension to within 6" of bottom	GM77856-TAG	\$ 556
	5 Gal. Spill Containment	GM77857-TAG	\$ 1,278
	5 Gal. Spill Containment w/ 95% shutoff	GM77858-TAG	\$ 1,833
	5 Gal. Spill Containment w/ fill to within 6" of tank bottom	GM77859-TAG	\$ 2,778
Normal Vent Options	12' above grade (without spill containment)	GM77860-TAG	\$ 778
	12' above grade (with spill containment)	GM77861-TAG	\$ 2,000
High Fuel Switch	High Fuel switch (set at 90%)	GM77862-TAG	\$ 278
	High Fuel switch (set at 90%) FDEP Approved	GM77863-TAG	\$ 1,167
Fuel in Basin Options	Fuel in Basin Switch, top mount (FDEP approved)	GM77864-TAG	\$ 556
Fuel Supply Options	Fire safety valve (installed on fuel supply)	GM77865-TAG	\$ 833
	Ball valve (installed on fuel supply)	GM77866-TAG	\$ 333
Bottom Clearance/Coating	C8 x 11.5 channels (provide 2" ground clearance)	GM77867-TAG	\$ 7,222
	Epoxy, Mastic Coating	GM77868-TAG	\$ 4,889
Tank Marking Options	Combustible Liquids - Keep Fire Away (2 decals provided)	GM77869-TAG	\$ 278
	NFPA 704 identification (2 decals provided)	GM77870-TAG	\$ 278
	Tank number and safe fill height (2 decals provided)	GM77871-TAG	\$ 278

Standard Features

Aluminum Sound Enclosures Level 1 for External Silencer & UL Tank Packages

► **Sound Enclosure Level 1 with External Silencer designs require Kohler critical external silencer, flex exhaust & weld-on flange (these options will be auto-selected in the quotation system). Design drops-over to mount to tank or lift base.**

Sound Enclosure Level 1 Features:

► **Available in Aluminum (.080), formed panel, solid construction**

Pre-assembled package offers a corrosion resistant aluminum, dent resilient structure that mounts directly to lift base or tank.

► **Polyurethane Enamel Paint**

Superior finish, durability and appearance.

► **Interchangeable modular panel construction**

Allows complete serviceability or replacement without compromising enclosure design.

► **-Attenuated design**

Offers reduction up to -15 dBA @ 7 meters, average of 8 readings. Acoustic insulation is UL-94 HF1 listed for flame resistance. The -15 dBA design offers 2" mechanically restrained acoustic insulation in enclosure only.

► **Service access**

External radiator fill, six personnel doors for easy access to generator set control and servicing of fuel fill, fuel gauge, oil fill & battery.

► **Turning of Control Panel**

If generator has a single circuit breaker then the control panel is turned to opposite side of the breaker. If dual breaker consult factory.

Cooling/Combustion Air Intake:

► **-attenuated models offer 90° vertical air inlet hood**

The -15 dBA models include acoustic insulation lining with urethane film.

Cooling Air Discharge:

► **-attenuated models offer 90° vertical air Gravity Outlet 90° internal plenum**

Redirects cooling air up and above enclosure to reduce noise ambient. -15 dBA models include acoustic insulation with urethane film.

Standard Sub-Base Tank Features:

► **Extended Operation**

Usable tank capacity offers full load standby operation of up to 48 hours through 2000 kW

► **UL Listed**

Secondary containment generator base tank meets UL 142 special purpose tank requirements.

► **NFPA compliant**

Designed to comply with the installation standards of NFPA 30, NFPA 37 and NFPA 110.

► **Integral external tank lift lugs**

Enables a crane with spreader-bar lifting of complete package (empty tank, mounted gen-set and enclosure) to ensure safety.

► **Emergency pressure relief vent caps**

Meets UL requirements - insures adequate venting of inner and outer tank under extreme pressure and/or emergency conditions.

► **Atmospheric vent cap**

Oversized 2" vent is raised above lockable fuel fill.

► **Low fuel level and leak detection switch**

Annunciates a contained primary tank fuel leak or a 50% low fuel level condition and the Generator Set Control.

► **Full width electrical stub-up**

Easy access via removable end channel.

► **Fuel transfer System**

Tank top mounting bracket offers location for (optional) fuel transfer system for extended generator set operation of for customer specified tank monitoring.

► **Rain runoff**

Included when tanks extend beyond the enclosure, ensures rain run-off.

Options:

See SL1 with External Silencer list of options

Pricing								
Aluminum Sound Enclosures Level 1 for External Silencer & UL Tank Packages								
Kohler Package Part Numbers	Secondary Cont. UL Tank Gallon Capacity	Estimated fuel supply hours at 60hz with full load	Package Dimensions ¹ Inches			Shipping Weight lbs.	Elec. Stub Up L x W	List Price
			Length	Width	Height			2024
1250 REOZMD ADV-7791 40°C & 50°C ADV-8551 SEISMIC GM72621-TPG								
GM72741-TAG	Lift Base		444	114	129	34350	41 x 102	\$226,970
GM72742-TAG	1350	13	444	114	133	37500	41 x 102	\$250,768
GM72743-TAG	1600	15	444	114	135	37810	41 x 102	\$252,817
GM72744-TAG	2100	20	444	114	139	38450	41 x 102	\$256,889
GM72745-TAG	2600	25	444	114	143	39080	41 x 102	\$260,965
GM72746-TAG	3130	30	444	114	143	39880	41 x 102	\$266,072
GM72747-TAG	4150	40	444	114	148	40985	41 x 102	\$273,235
GM72748-TAG	5150	50	444	114	163	42255	41 x 102	\$299,931
GM72749-TAG	6160	60	498	114	163	44050	41 x 102	\$313,620
GM72750-TAG	7700	74	584	114	163	46780	41 x 102	\$336,998
1600 REOZMD ADV-7794 40°C & 50°C ADV-8551 SEISMIC GM72624-TPG								
GM72771-TAG	Lift Base		485	114	139	40835	41 x 102	\$251,852
GM72772-TAG	1350	10	485	114	143	44090	41 x 102	\$275,911
GM72773-TAG	1600	12	485	114	144	44490	41 x 102	\$276,990
GM72774-TAG	2100	16	485	114	148	45180	41 x 102	\$281,316
GM72775-TAG	2600	20	485	114	151	45750	41 x 102	\$284,565
GM72776-TAG	3130	24	503	114	153	46535	41 x 102	\$289,889
GM72777-TAG	4150	32	485	114	161	47810	41 x 102	\$295,425
GM72778-TAG	5150	40	485	114	168	48705	41 x 102	\$322,449
GM72779-TAG	6160	48	521	114	171	50400	41 x 102	\$335,496
GM72780-TAG	7700	60	589	114	173	52910	41 x 102	\$355,622
1750/2000 REOZMD ADV-7795 40°C ADV-8551 SEISMIC GM72625-TPG								
GM72781-TAG	Lift Base		485	114	143	43335	41 x 102	\$255,840
GM72782-TAG	1350	10/8	485	114	147	46590	41 x 102	\$279,899
GM72783-TAG	1600	11/10	485	114	148	46990	41 x 102	\$280,978
GM72784-TAG	2100	15/13	485	114	152	47680	41 x 102	\$285,304
GM72785-TAG	2600	18/16	485	114	155	48095	41 x 102	\$288,553
GM72786-TAG	3130	22/20	485	114	159	48650	41 x 102	\$292,891
GM72787-TAG	4150	29/26	485	114	166	49975	41 x 102	\$299,412
GM72788-TAG	5150	36/32	485	114	173	51200	41 x 102	\$326,437
GM72789-TAG	6160	44/38	521	114	184	56575	41 x 102	\$380,558
GM72790-TAG	7900	54/48	589	114	185	59095	41 x 102	\$400,686
1750/2000 REOZMD ADV-7796 50°C ADV-8551 SEISMIC GM72626-TPG								
GM72791-TAG	Lift Base		511	124	155	45755	41 x 112	\$286,321
GM72792-TAG	1350	10/8	511	124	157	49490	41 x 112	\$308,741
GM72793-TAG	1600	11/10	511	124	159	49715	41 x 112	\$311,111
GM72794-TAG	2100	15/13	511	124	162	50295	41 x 112	\$314,669
GM72795-TAG	2600	18/16	511	124	165	50875	41 x 112	\$318,232
GM72796-TAG	3130	22/20	511	124	168	51575	41 x 112	\$321,798
GM72797-TAG	4150	29/26	511	124	171	53200	41 x 112	\$332,832
GM72798-TAG	5150	36/32	511	124	188	57725	41 x 112	\$403,541
GM72799-TAG	6160	44/38	511	124	194	58875	41 x 112	\$411,163
GM72800-TAG	7900	54/48	575	124	197	61625	41 x 112	\$432,679
¹ Package dimensions are overall length, width and height. Overall length includes tank length.								

Options

Aluminum Sound Enclosures Level 1 for External Silencer & UL Tank Packages

Option	Description	Kohler Part #	List Price
Electrical			
DC Light Package	Two-(2) quantity DC interior lights powered by the starting battery on a fused circuit with a 0-60 minute "No-Lock-On" timer, 24 VDC standard.	GM73237-TAG	\$ 2,624
Additional DC Lights	Two additional DC Lights; only available when DC light package is ordered	GM73238-TAG	\$ 1,520
Basic Electrical Package 200 Amp Max (only one can be selected and cannot be ordered with Load Center)	Load center 120/208/240VAC single phase, 200 amp max w/ main and 12 branch circuits. (1) switch control (3) AC lights vapor tight and gasketed wiring of jacket water heater (2) duplex GFI receptacles.	GM76027-TAG	\$ 6,487
	Load center 120/208/240VAC 3 phase, 200 amp max w/ main and 12 branch circuits. (1) switch control (3) AC lights vapor tight and gasketed wiring of jacket water heater (2) duplex GFI receptacles.	GM76028-TAG	\$ 8,376
	Load center 120/240VAC, single phase, 200 amp max with main and 12 branch circuits. One-(1) switch control and <u>Two-(2) four foot LED lights</u> . Block heater wiring included. Two-(2) quantity duplex GFI receptacles.	GM76029-TAG	\$ 6,742
	Load center 120/208/240VAC, three phase, 200 amp max with main and 12 branch circuits. One-(1) switch control and Two-(2) four foot LED lights. Block heater wiring included. Two-(2) quantity duplex GFI receptacles.	GM76030-TAG	\$ 8,631
Additional Lights & Receptacles (only available with BEP or Load Center is ordered)	Two Additional AC lights	GM73243-TAG	\$ 2,389
	Additional duplex GFI receptacles (2 included - internal mounted)	GM73244-TAG	\$ 969
	Additional duplex GFI receptacles (2 included - external mounted)	GM73245-TAG	\$ 1,938
Load Center - 200 Amp Max (only one can be selected and cannot be orderd with BEP)	Load center 120/208/240VAC, single phase, 200 amp max with main and 12 branch circuits and wiring of the block heater	GM76025-TAG	\$ 2,278
	Load center 120/208/240VAC, 3 phase, 200 amp max with main and 12 branch circuits and wiring of the block heater	GM76026-TAG	\$ 4,167
Transformer Single Phase	Single Phase 37.5 kVA 480 primary /208/120 secondary Transformer; available only when BEP or Load Center is ordered	GM73248-TAG	\$ 12,656
Disconnect Switch (For 1-phase)	Disconnect Switch for Single phase 37.5 kVA Transformer; available only when Transformer is ordered	GM73249-TAG	\$ 3,449
Transformer 3 Phase	3 Phase 37.5 kVA 480 primary /208/120 secondary Transformer; available only when BEP or Load Bank is ordered.	GM73250-TAG	\$ 13,464
Disconnect Switch (For 3-Ph)	Disconnect Switch for 3-phase 37.5 kVA Transformer; available only when Transformer is ordered.	GM73251-TAG	\$ 3,960
Emergency Lights	Dual head battery powered emergency lights includes batteries (qty 2) mounted inside enclosure; available only when BEP or Load Center is ordered	GM73252-TAG	\$ 1,556
Enclosure Heater (If block heater is ordered, a 3 phase block heater must be matched with 3 phase enclosure heater, must be ordered with either BEP or load center)	Single Phase - 208VAC 5kW thermostatically controlled heater	GM73253-TAG	\$ 6,564
	Single Phase - 240VAC 5kW thermostatically controlled heater	GM73254-TAG	\$ 6,564
	3 phase - 208VAC 5kW thermostatically controlled heater	GM73255-TAG	\$ 6,564
	3 phase - 240VAC 5kW thermostatically controlled heater	GM73256-TAG	\$ 6,564
Exhaust Fan	800 CFM Shutter-Mounted Exhaust Fan (Wall mounted); available only when BEP or Load Center is ordered	GM73257-TAG	\$ 2,762
Miscellaneous			
Battery Charger	Provide bracket mount & wire customer supplied battery charger to DC side of generator; can only be ordered with loose battery charger and either a BEP or Load Center	GM73258-TAG	\$ 1,933
Battery Charger With Alarms	Provide bracket mount & wire customer supplied battery charger with alarm to DC side of generator; can only be ordered with loose battery charger w/alarms and either a BEP or Load Center	GM73259-TAG	\$ 2,418
Viewing Window	Control Panel Viewing Window	GM73260-TAG	\$ 1,667
Alarm	High fuel level float switch; available only with a tank	GM73261-TAG	\$ 249
Alarm	Economical 3 alarm panel for high, low, and fuel leak (mounted inside enclosure); available only with a tank	GM73262-TAG	\$ 2,669
Alarm	Economical 3 alarm panel for high, low, and fuel leak (mounted outside enclosure); available only with a tank	GM73263-TAG	\$ 2,669
Fill/Spill	Above ground 5 gallon fill/spill containment, piping from fill to outside of enclosure. (External enclosure wall mount) Spill/fill to ship loose for field install or may be attached when it does not effect shipping; available only with a tank	GM73264-TAG	\$ 871
Emergency Stop	Emergency Stop Button - externally mounted	GM73265-TAG	\$ 1,547
Seismic Bracing	Necessary bracing and upgrades to the enclosures and tanks when IBC or OSHPD is selected (OSPHD only available on REOZMD models)	GM87028-TAG	\$ 27,281
ULC-S601 Listing	Canada Option	GM78723-TAG	\$ 667
Pad Locks Std with Global Design			
Automatic Door Holder Std with Global Design			
Internal Release Handle			
Internal Release Handles	Internal Release Handles - 1 per door	GM73266-TAG	\$ 2,447

Options

Aluminum Sound Enclosures Level 1 for External Silencer & UL Tank Packages

Option	Description	Kohler Part #	List Price
Supply Fuel Transfer Systems - only available with BEP or Load Center			
1250 kW through 1600 kW	Series 400 Electronic Control Module (ECM) with 4 GPM pump and 1/3 HP motor, solenoid valve, fuel strainer and critical high shutdown. Mounted, plumbed and wired as a Modular Fuel Transfer System; available only with a tank	GM73267-TAG	\$ 12,776
1750 kW through 2000 kW	Series 400 Electronic Control Module (ECM) with 7 GPM pump and 1/2 HP motor, solenoid valve, fuel strainer and critical high shutdown. Mounted, plumbed and wired as a Modular Fuel Transfer System; available only with a tank	GM73268-TAG	\$ 13,898
Return Fuel Transfer Systems (MUST order Supply fuel transfer system)			
1250 kW through 1600 kW	A 7 GPM pump returns fuel to the main tank.	GM73269-TAG	\$ 4,616
1750 kW through 2000 kW	A 10 GPM pump returns fuel to the main tank.	GM73270-TAG	\$ 5,738
Motorized Discharge Louvers - only available with BEP or Load Center			
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1250 REOZMD	GM73295-TAG	\$ 9,849
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1600 REOZMD	GM73296-TAG	\$ 13,540
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73299-TAG	\$ 13,744
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73300-TAG	\$ 20,013
Motorized Intake Louvers - only available with BEP or Load Center			
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1250 REOZMD	GM73303-TAG	\$ 14,531
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1600 REOZMD	GM73304-TAG	\$ 16,402
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73307-TAG	\$ 14,867
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73308-TAG	\$ 21,640
Gravity Discharge			
Gravity Discharge	Gravity Discharge (Aluminum) - 1250REOZMD	GM73311-TAG	\$ 7,422
Gravity Discharge	Gravity Discharge (Aluminum) - 1600 REOZMD	GM73312-TAG	\$ 7,904
Gravity Discharge	Gravity Discharge (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73315-TAG	\$ 8,064
Gravity Discharge	Gravity Discharge (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73316-TAG	\$ 13,298
State Tank Accessories			
Fuel Fill Options	Fill pipe extension to within 6" of bottom	GM77856-TAG	\$ 556
	5 Gal. Spill Containment	GM77857-TAG	\$ 1,278
	5 Gal. Spill Containment w/ 95% shutoff	GM77858-TAG	\$ 1,833
	5 Gal. Spill Containment w/ fill to within 6" of tank bottom	GM77859-TAG	\$ 2,778
Normal Vent Options	12' above grade (without spill containment)	GM77860-TAG	\$ 778
	12' above grade (with spill containment)	GM77861-TAG	\$ 2,000
High Fuel Switch	High Fuel switch (set at 90%)	GM77862-TAG	\$ 278
	High Fuel switch (set at 90%) FDEP Approved	GM77863-TAG	\$ 1,167
Fuel in Basin Options	Fuel in Basin Switch, top mount (FDEP approved)	GM77864-TAG	\$ 556
Fuel Supply Options	Fire safety valve (installed on fuel supply)	GM77865-TAG	\$ 833
	Ball valve (installed on fuel supply)	GM77866-TAG	\$ 333
Bottom Clearance/Coating	C8 x 11.5 channels (provide 2" ground clearance)	GM77867-TAG	\$ 7,222
	Epoxy, Mastic Coating	GM77868-TAG	\$ 4,889
Tank Marking Options	Combustible Liquids - Keep Fire Away (2 decals provided)	GM77869-TAG	\$ 278
	NFPA 704 identification (2 decals provided)	GM77870-TAG	\$ 278
	Tank number and safe fill height (2 decals provided)	GM77871-TAG	\$ 278

Standard Features

Aluminum Sound Enclosures Level 2 for External Silencer & UL Tank Packages

► Sound Enclosure Level 2 with External Silencer designs require Kohler hospital external silencer, flex exhaust & weld-on flange (these options will be auto-selected in the quotation system). Design drops-over to mount to tank or lift base.

Sound Enclosure Level 2 Features:

► Available in Aluminum (.080), formed panel, solid construction

Pre-assembled package offers a corrosion resistant aluminum, dent resilient structure that mounts directly to lift base or tank.

► Polyurethane Enamel Paint

Superior finish, durability and appearance.

► Interchangeable modular panel construction

Allows complete serviceability or replacement without compromising enclosure design.

► -Attenuated design

Offers reduction up to -25 dBA @ 7 meters, average of 8 readings. Acoustic insulation is UL-94 HF1 listed for flame resistance. The -25 dBA design features 3" acoustic insulation with aluminum perforated interior liner in the enclosure and 2" insulation mechanically restrained in hoods.

► Service access

External radiator fill, six personnel doors for easy access to generator set control and servicing of fuel fill, fuel gauge, oil fill & battery.

► Turning of Control Panel

If generator has a single circuit breaker then the control panel is turned to opposite side of the breaker. If dual breaker consult factory.

Cooling/Combustion Air Intake:

► -attenuated models offer 90° vertical air inlet hood

The -25 dBA models include acoustic insulation lining with urethane film.

Cooling Air Discharge:

► -attenuated models offer 90° vertical air Gravity Outlet 90° internal plenum

Redirects cooling air up and above enclosure to reduce noise ambient. -25 dBA models include acoustic insulation with urethane film.

Standard Sub-Base Tank Features:

► Extended Operation

Usable tank capacity offers full load standby operation of up to 48 hours through 2000 kW

► UL Listed

Secondary containment generator base tank meets UL 142 special purpose tank requirements.

► NFPA compliant

Designed to comply with the installation standards of NFPA 30, NFPA 37 and NFPA 110.

► Integral external tank lift lugs

Enables a crane with spreader-bar lifting of complete package (empty tank, mounted gen-set and enclosure) to ensure safety.

► Emergency pressure relief vent caps

Meets UL requirements - insures adequate venting of inner and outer tank under extreme pressure and/or emergency conditions.

► Atmospheric vent cap

Oversized 2" vent is raised above lockable fuel fill.

► Low fuel level and leak detection switch

Annunciates a contained primary tank fuel leak or a 50% low fuel level condition and the Generator Set Control.

► Full width electrical stub-up

Easy access via removable end channel.

► Fuel transfer System

Tank top mounting bracket offers location for (optional) fuel transfer system for extended generator set operation of for customer specified tank monitoring.

► Rain runoff

Included when tanks extend beyond the enclosure, ensures rain run-off.

Options:

See SL2 with External Silencer list of options

Pricing

Aluminum Sound Enclosures Level 2 for External Silencer & UL Tank Packages

Kohler Package Part Numbers	Secondary Cont. UL Tank Gallon Capacity	Estimated fuel supply hours at 60hz with full load	Package Dimensions¹ Inches			Shipping Weight lbs.	Elec. Stub Up L x W	List Price
			Length	Width	Height			2024
1250 REOZMD ADV-7807 40°C & 50°C ADV-8551 SEISMIC GM72629-TPG								
GM72821-TAG	Lift Base		444	114	129	35800	41 x 102	\$238,319
GM72822-TAG	1350	13	444	114	133	38950	41 x 102	\$263,306
GM72823-TAG	1600	15	444	114	135	39260	41 x 102	\$265,458
GM72824-TAG	2100	20	444	114	139	39900	41 x 102	\$269,733
GM72825-TAG	2600	25	444	114	143	40530	41 x 102	\$274,014
GM72826-TAG	3130	30	444	114	143	41330	41 x 102	\$279,375
GM72827-TAG	4150	40	444	114	148	42435	41 x 102	\$286,896
GM72828-TAG	5150	50	444	114	163	43705	41 x 102	\$314,927
GM72829-TAG	6160	60	498	114	163	45500	41 x 102	\$329,301
GM72830-TAG	7700	74	584	114	163	48230	41 x 102	\$353,847
1600 REOZMD ADV-7810 40°C & 50°C ADV-8551 SEISMIC GM72632-TPG								
GM72851-TAG	Lift Base		485	114	139	42355	41 x 102	\$264,444
GM72852-TAG	1350	10	485	114	143	45610	41 x 102	\$289,707
GM72853-TAG	1600	12	485	114	144	46010	41 x 102	\$290,840
GM72854-TAG	2100	16	485	114	148	46700	41 x 102	\$295,382
GM72855-TAG	2600	20	485	114	151	47270	41 x 102	\$298,794
GM72856-TAG	3130	24	503	114	153	48055	41 x 102	\$304,383
GM72857-TAG	4150	32	485	114	161	49330	41 x 102	\$310,196
GM72858-TAG	5150	40	485	114	168	50225	41 x 102	\$338,572
GM72859-TAG	6160	48	521	114	171	51920	41 x 102	\$352,271
GM72860-TAG	7700	60	589	114	173	54430	41 x 102	\$373,403
1750/2000 REOZMD ADV-7811 40°C ADV-8551 SEISMIC GM72633-TPG								
GM72861-TAG	Lift Base		485	114	143	44535	41 x 102	\$268,631
GM72862-TAG	1350	10/8	485	114	147	47790	41 x 102	\$293,894
GM72863-TAG	1600	11/10	485	114	148	48190	41 x 102	\$295,027
GM72864-TAG	2100	15/13	485	114	152	48880	41 x 102	\$299,569
GM72865-TAG	2600	18/16	485	114	155	49295	41 x 102	\$302,981
GM72866-TAG	3130	22/20	485	114	159	49850	41 x 102	\$307,536
GM72867-TAG	4150	29/26	485	114	166	51175	41 x 102	\$314,383
GM72868-TAG	5150	36/32	485	114	173	52400	41 x 102	\$342,759
GM72869-TAG	6160	44/38	521	114	184	57775	41 x 102	\$399,586
GM72870-TAG	7900	54/48	589	114	185	60295	41 x 102	\$420,721
1750/2000 REOZMD ADV-7812 50°C ADV-8551 SEISMIC GM72634-TPG								
GM72871-TAG	Lift Base		511	124	155	46955	41 x 112	\$300,637
GM72872-TAG	1350	10/8	511	124	157	50690	41 x 112	\$324,178
GM72873-TAG	1600	11/10	511	124	159	50915	41 x 112	\$326,667
GM72874-TAG	2100	15/13	511	124	162	51495	41 x 112	\$330,403
GM72875-TAG	2600	18/16	511	124	165	52075	41 x 112	\$334,144
GM72876-TAG	3130	22/20	511	124	168	52775	41 x 112	\$337,887
GM72877-TAG	4150	29/26	511	124	171	54400	41 x 112	\$349,474
GM72878-TAG	5150	36/32	511	124	188	58925	41 x 112	\$423,718
GM72879-TAG	6160	44/38	511	124	194	60075	41 x 112	\$431,721
GM72880-TAG	7900	54/48	575	124	197	62825	41 x 112	\$454,313

¹ Package dimensions are overall length, width and height. Overall length includes tank length.

Options

Aluminum Sound Enclosures Level 2 for External Silencer & UL Tank Packages

Option	Description	Kohler Part #	List Price
Electrical			
DC Light Package	Two-(2) quantity DC interior lights powered by the starting battery on a fused circuit with a 0-60 minute "No-Lock-On" timer, 24 VDC standard.	GM73237-TAG	\$ 2,624
Additional DC Lights	Two additional DC Lights; only available when DC light package is ordered	GM73238-TAG	\$ 1,520
Basic Electrical Package 200 Amp Max (only one can be selected and cannot be ordered with Load Center)	Load center 120/208/240VAC single phase, 200 amp max w/ main and 12 branch circuits. (1) switch control (3) AC lights vapor tight and gasketed wiring of jacket water heater (2) duplex GFI receptacles.	GM76027-TAG	\$ 6,487
	Load center 120/208/240VAC 3 phase, 200 amp max w/ main and 12 branch circuits. (1) switch control (3) AC lights vapor tight and gasketed wiring of jacket water heater (2) duplex GFI receptacles.	GM76028-TAG	\$ 8,376
	Load center 120/240VAC, single phase, 200 amp max with main and 12 branch circuits. One-(1) switch control and <u>Two-(2) four foot LED lights</u> . Block heater wiring included. Two-(2) quantity duplex GFI receptacles.	GM76029-TAG	\$ 6,742
	Load center 120/208/240VAC, three phase, 200 amp max with main and 12 branch circuits. One-(1) switch control and Two-(2) four foot LED lights. Block heater wiring included. Two-(2) quantity duplex GFI receptacles.	GM76030-TAG	\$ 8,631
Additional Lights & Receptacles (only available with BEP or Load Center is ordered)	Two Additional AC lights	GM73243-TAG	\$ 2,389
	Additional duplex GFI receptacles (2 included - internal mounted)	GM73244-TAG	\$ 969
	Additional duplex GFI receptacles (2 included - external mounted)	GM73245-TAG	\$ 1,938
Load Center - 200 Amp Max (only one can be selected and cannot be order with BEP)	Load center 120/208/240VAC, single phase, 200 amp max with main and 12 branch circuits and wiring of the block heater	GM76025-TAG	\$ 2,278
	Load center 120/208/240VAC, 3 phase, 200 amp max with main and 12 branch circuits and wiring of the block heater	GM76026-TAG	\$ 4,167
Transformer Single Phase	Single Phase 37.5 kVA 480 primary /208/120 secondary Transformer; available on when BEP or Load Center is ordered	GM73248-TAG	\$ 12,656
Disconnect Switch (For 1-phase)	Disconnect Switch for Single phase 37.5 kVA Transformer; available only when transformer is ordered	GM73249-TAG	\$ 3,449
Transformer 3 Phase	3 Phase 37.5 kVA 480 primary /208/120 secondary Transformer; available only when BEP or Load Center is ordered	GM73250-TAG	\$ 13,464
Disconnect Switch (For 3-Ph)	Disconnect Switch for 3-phase 37.5 kVA Transformer; available only when transformer is ordered	GM73251-TAG	\$ 3,960
Emergency Lights	Dual head battery powered emergency lights includes batteries (qty 2) mounted inside enclosure; available only when BEP or Load Center is ordered	GM73252-TAG	\$ 1,556
Enclosure Heater (If block heater is ordered, a 3 phase block heater must be matched with 3 phase enclosure heater, must be ordered with either BEP or load center)	Single Phase - 208VAC 5kW thermostatically controlled heater	GM73253-TAG	\$ 6,564
	Single Phase - 240VAC 5kW thermostatically controlled heater	GM73254-TAG	\$ 6,564
	3 phase - 208VAC 5kW thermostatically controlled heater	GM73255-TAG	\$ 6,564
	3 phase - 240VAC 5kW thermostatically controlled heater	GM73256-TAG	\$ 6,564
Exhaust Fan	800 CFM Shutter-Mounted Exhaust Fan (Wall mounted); available only when BEP or Load Center is ordered	GM73257-TAG	\$ 2,762
Miscellaneous			
Battery Charger	Provide bracket mount & wire customer supplied battery charger to DC side of generator; can only be ordered with loose battery charger and either a BEP or Load Center	GM73258-TAG	\$ 1,933
Battery Charger With Alarms	Provide bracket mount & wire customer supplied battery charger with alarm to DC side of generator; can only be ordered with loose battery charger w/alarms and either a BEP or Load Center	GM73259-TAG	\$ 2,418
Viewing Window	Control Panel Viewing Window	GM73260-TAG	\$ 1,667
Alarm	High fuel level float switch; available only with a tank	GM73261-TAG	\$ 249
Alarm	Economical 3 alarm panel for high, low, and fuel leak (mounted inside enclosure); available only with a tank	GM73262-TAG	\$ 2,669
Alarm	Economical 3 alarm panel for high, low, and fuel leak (mounted outside enclosure); available only with a tank	GM73263-TAG	\$ 2,669
Fill/Spill	Above ground 5 gallon fill/spill containment, piping from fill to outside of enclosure. (External enclosure wall mount) Spill/fill to ship loose for field install or may be attached when it does not effect shipping; available only with a tank	GM73264-TAG	\$ 871
Emergency Stop	Emergency Stop Button - externally mounted	GM73265-TAG	\$ 1,547
Seismic Bracing	Necessary bracing and upgrades to the enclosures and tanks when IBC or OSHPD is selected (OSHPD only available on REOZMD models)	GM87029-TAG	\$ 27,281
ULC-S601 Listing	Canada Option	GM78723-TAG	\$ 667
Pad Lock Std with Global Design			
Automatic Door Holder Std with Global Design			
Internal Release Handle			
Internal Release Handles	Internal Release Handles - 1 per door	GM73266-TAG	\$ 2,447

Options

Aluminum Sound Enclosures Level 2 for External Silencer & UL Tank Packages

Option	Description	Kohler Part #	List Price
Supply Fuel Transfer Systems - only available with BEP or Load Center			
1250 kW through 1600 kW	Series 400 Electronic Control Module (ECM) with 4 GPM pump and 1/3 HP motor, solenoid valve, fuel strainer and critical high shutdown. Mounted, plumbed and wired as a Modular Fuel Transfer System; available only with tank	GM73267-TAG	\$ 12,776
1750 kW through 2000 kW	Series 400 Electronic Control Module (ECM) with 7 GPM pump and 1/2 HP motor, solenoid valve, fuel strainer and critical high shutdown. Mounted, plumbed and wired as a Modular Fuel Transfer System; available only with tank	GM73268-TAG	\$ 13,898
Return Fuel Transfer Systems (MUST order Supply fuel transfer system)			
1250 kW through 1600 kW	A 7 GPM pump returns fuel to the main tank.	GM73269-TAG	\$ 4,616
1750 kW through 2000 kW	A 10 GPM pump returns fuel to the main tank.	GM73270-TAG	\$ 5,738
Motorized Discharge Louvers - only available with BEP or Load Center			
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1250 REOZMD	GM73319-TAG	\$ 9,849
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1600 REOZMD	GM73320-TAG	\$ 13,540
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73323-TAG	\$ 13,744
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73324-TAG	\$ 20,013
Motorized Intake Louvers - only available with BEP or Load Center			
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1250 REOZMD	GM73327-TAG	\$ 14,531
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1600 REOZMD	GM73328-TAG	\$ 16,402
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73331-TAG	\$ 14,867
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73332-TAG	\$ 21,640
Gravity Discharge			
Gravity Discharge	Gravity Discharge (Aluminum) - 1250REOZMD	GM73335-TAG	\$ 7,422
Gravity Discharge	Gravity Discharge (Aluminum) - 1600 REOZMD	GM73336-TAG	\$ 7,904
Gravity Discharge	Gravity Discharge (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73339-TAG	\$ 8,064
Gravity Discharge	Gravity Discharge (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73340-TAG	\$ 13,298
State Tank Accessories			
Fuel Fill Options	Fill pipe extension to within 6" of bottom	GM77856-TAG	\$ 556
	5 Gal. Spill Containment	GM77857-TAG	\$ 1,278
	5 Gal. Spill Containment w/ 95% shutoff	GM77858-TAG	\$ 1,833
	5 Gal. Spill Containment w/ fill to within 6" of tank bottom	GM77859-TAG	\$ 2,778
Normal Vent Options	12' above grade (without spill containment)	GM77860-TAG	\$ 778
	12' above grade (with spill containment)	GM77861-TAG	\$ 2,000
High Fuel Switch	High Fuel switch (set at 90%)	GM77862-TAG	\$ 278
	High Fuel switch (set at 90%) FDEP Approved	GM77863-TAG	\$ 1,167
Fuel in Basin Options	Fuel in Basin Switch, top mount (FDEP approved)	GM77864-TAG	\$ 556
Fuel Supply Options	Fire safety valve (installed on fuel supply)	GM77865-TAG	\$ 833
	Ball valve (installed on fuel supply)	GM77866-TAG	\$ 333
Bottom Clearance/Coating	C8 x 11.5 channels (provide 2" ground clearance)	GM77867-TAG	\$ 7,222
	Epoxy, Mastic Coating	GM77868-TAG	\$ 4,889
Tank Marking Options	Combustible Liquids - Keep Fire Away (2 decals provided)	GM77869-TAG	\$ 278
	NFPA 704 identification (2 decals provided)	GM77870-TAG	\$ 278
	Tank number and safe fill height (2 decals provided)	GM77871-TAG	\$ 278

Standard Features

Aluminum Weather Enclosures with Internal Silencers & UL Tank Packages

► **Weather Enclosure with Internal Silencer Design** includes internal critical silencer. Design drops-over to mount to tank or lift base.

Weather Enclosure for internal silencers include an internal critical silencer.

Weather Enclosure with Internal Silencer Features:

► **Available in Aluminum (.080), formed panel, solid construction**

Pre-assembled package offers a corrosion resistant aluminum, dent resilient structure that mounts directly to lift base or tank.

► **Polyurethane Enamel Paint**

Superior finish, durability and appearance.

► **Interchangeable Modular panel construction**

Allows complete serviceability or replacement without compromising enclosure design.

► **Internal Critical Exhaust Silencer (Standard)**

Offers maximum component life, operator safety and includes rain shield and cap.

► **Service Access**

External radiator fill, six personnel doors for easy access to generator set control and servicing of fuel fill, fuel gauge, oil fill & battery.

► **Turning of Control Panel**

If generator has a single circuit breaker then the control panel is turned to opposite side of the breaker. If dual breaker consult factory.

Cooling/Combustion Air Intake:

► **Weather protective designs use fixed air inlet louvers**

Sized for maximum cooling airflow constructed of same material as Enclosure

Cooling Air Discharge:

► **Weather Protective design features horizontal air discharge**

Exhausts air through removable punched air Gravity Outlet 90° grille.

Standard Sub-Base Tank Features:

► **Extended Operation**

Usable tank capacity offers full load standby operation of up to 48 hours through 2000 kW

► **UL Listed**

Secondary containment generator base tank meets UL 142 special purpose tank requirements.

► **NFPA compliant**

Designed to comply with the installation standards of NFPA 30, NFPA 37 and NFPA 110

► **Integral external lift lugs**

Enables crane with spreader-bar lifting of complete package (empty tank, mounted gen-set and enclosure) to ensure safety.

► **Emergency pressure relief vent caps**

Meets UL requirements - insures adequate venting of inner and outer tank under extreme pressure and/or emergency conditions

► **Atmospheric vent cap**

Oversized 2" vent is raised above lockable fuel fill

► **Low fuel level and leak detection switch**

Annunciates a contained primary tank fuel leak or a 50% low fuel level condition at Generator Set Control

► **Full width electrical stub-up**

Easy access via removable end channel.

► **Fuel transfer system**

Tank top mounting bracket offers location for (optional) fuel transfer system for extended generator set operation or for customer specified tank monitoring

► **Rain runoff**

Included when tanks extend beyond the enclosure, ensures rain run-off.

Options:

See Weather Enclosure with Internal Silencer list of options

Pricing

Aluminum Weather Enclosures for Internal Silencer & UL Tank Packages

Kohler Package Part Numbers	Secondary Cont. UL Tank Gallon Capacity	Estimated fuel supply hours at 60hz with full load	Package Dimensions ¹			Shipping Weight lbs.	Elec. Stub Up L x W	List Price
			Length	Width	Height			2024
1250 REOZMD ADV-7783 40°C & 50°C ADV-8551 SEISMIC GM72637-TPG								
GM72901-TAG	Lift Base		282	102	146	32400	37 x 90	\$205,506
GM72902-TAG	1350	13	302	102	154	35260	37 x 90	\$233,272
GM72903-TAG	1600	15	302	102	157	35620	37 x 90	\$235,773
GM72904-TAG	2100	20	302	102	162	36360	37 x 90	\$239,953
GM72905-TAG	2600	25	302	102	167	37050	37 x 90	\$244,138
GM72906-TAG	3130	30	320	102	170	37910	37 x 90	\$250,059
GM72907-TAG	4150	40	408	102	170	40125	37 x 90	\$266,565
GM72908-TAG	5150	50	364	102	172	42050	37 x 90	\$299,832
GM72909-TAG	6160	60	450	102	188	45640	37 x 90	\$338,494
GM72910-TAG	7700	74	550	102	188	45410	37 x 90	\$363,074
1600 REOZMD ADV-7786 40°C & 50°C ADV-8551 SEISMIC GM72640-TPG								
GM72931-TAG	Lift Base		310	108	159	38300	37 x 96	\$240,477
GM72932-TAG	1350	10	330	108	165	41400	37 x 96	\$268,504
GM72933-TAG	1600	12	330	108	167	41725	37 x 96	\$270,393
GM72934-TAG	2100	16	330	108	171	42350	37 x 96	\$274,175
GM72935-TAG	2600	20	364	108	173	43430	37 x 96	\$281,395
GM72936-TAG	3130	24	426	108	173	44850	37 x 96	\$291,647
GM72937-TAG	4150	32	552	108	173	47700	37 x 96	\$312,731
GM72938-TAG	5150	40	380	108	199	50480	37 x 96	\$358,983
GM72939-TAG	6160	48	424	108	201	52150	37 x 96	\$372,323
GM72940-TAG	7700	60	518	108	201	55100	37 x 96	\$396,519
1750/2000 REOZMD ADV-7787 40°C ADV-8551 SEISMIC GM72641-TPG								
GM72941-TAG	Lift Base		320	114	161	41500	39 x 114	\$256,195
GM72942-TAG	1350	10/8	342	114	166	44760	39 x 114	\$284,249
GM72943-TAG	1600	11/10	342	114	168	45090	39 x 114	\$286,230
GM72944-TAG	2100	15/13	342	114	172	45690	39 x 114	\$290,160
GM72945-TAG	2600	18/16	380	114	173	46880	39 x 114	\$297,558
GM72946-TAG	3130	22/20	444	114	173	48340	39 x 114	\$308,193
GM72947-TAG	4150	29/26	390	114	191	51820	39 x 114	\$343,965
GM72948-TAG	5150	36/32	390	114	198	53040	39 x 114	\$371,551
GM72949-TAG	6160	44/38	406	114	203	54470	39 x 114	\$381,084
GM72950-TAG	7900	54/48	504	114	203	57610	39 x 114	\$407,035
1750/2000 REOZMD ADV-7788 50°C ADV-8551 SEISMIC GM72642-TPG								
GM72951-TAG	Lift Base		320	126	161	43800	39 x 114	\$267,793
GM72952-TAG	1350	10/8	342	126	165	47260	39 x 114	\$296,121
GM72953-TAG	1600	11/10	342	126	167	47580	39 x 114	\$298,200
GM72954-TAG	2100	15/13	342	126	170	48250	39 x 114	\$301,321
GM72955-TAG	2600	18/16	344	126	173	48915	39 x 114	\$304,775
GM72956-TAG	3130	22/20	402	126	173	48340	39 x 114	\$315,254
GM72957-TAG	4150	29/26	518	126	173	51820	39 x 114	\$336,084
GM72958-TAG	5150	36/32	360	126	197	53040	39 x 114	\$379,563
GM72959-TAG	6160	44/38	382	126	201	54470	39 x 114	\$390,410
GM72960-TAG	7900	54/48	454	126	203	57610	39 x 114	\$413,716

¹ Package dimensions are overall length, width and height. Overall length includes tank length.

Options

Aluminum Weather Enclosures for Internal Silencer & UL Tank Packages

Option	Description	Kohler Part #	List Price
Electrical			
DC Light Package	Two-(2) quantity DC interior lights powered by the starting battery on a fused circuit with a 0-60 minute "No-Lock-On" timer.	GM73237-TAG	\$ 2,624
Additional DC Lights	Two additional DC Lights; only available when DC light package is ordered	GM73238-TAG	\$ 1,520
Basic Electrical Package 200 Amp Max (only one can be selected and cannot be ordered with Load Center)	Load center 120/208/240VAC single phase, 200 amp max w/ main and 12 branch circuits. (1) switch control (3) AC lights vapor tight and gasketed wiring of jacket water heater (2) duplex GFI receptacles.	GM76027-TAG	\$ 6,487
	Load center 120/208/240VAC 3 phase, 200 amp max w/ main and 12 branch circuits. (1) switch control (3) AC lights vapor tight and gasketed wiring of jacket water heater (2) duplex GFI receptacles.	GM76028-TAG	\$ 8,376
	Load center 120/240VAC, single phase, 200 amp max with main and 12 branch circuits. One-(1) switch control and <u>Two-(2) four foot LED lights</u> . Block heater wiring included. Two-(2) quantity duplex GFI receptacles.	GM76029-TAG	\$ 6,742
	Load center 120/208/240VAC, three phase, 200 amp max with main and 12 branch circuits. One-(1) switch control and Two-(2) four foot LED lights. Block heater wiring included. Two-(2) quantity duplex GFI receptacles.	GM76030-TAG	\$ 8,631
Additional Lights & Receptacles	Two Additional AC lights	GM73243-TAG	\$ 2,389
(only available with BEP or Load Center is ordered)	Additional duplex GFI receptacles (2 included - internal mounted)	GM73244-TAG	\$ 969
	Additional duplex GFI receptacles (2 included - external mounted)	GM73245-TAG	\$ 1,938
Load Center - 200 Amp Max	Load center 120/208/240VAC, single phase, 200 amp max with main and 12 branch circuits and wiring of the block heater	GM76025-TAG	\$ 2,278
	Load center 120/208/240VAC, 3 phase, 200 amp max with main and 12 branch circuits and wiring of the block heater	GM76026-TAG	\$ 4,167
Transformer Single Phase	Single Phase 37.5 kVA 480 primary /208/120 secondary Transformer; available on when BEP or Load Center is ordered	GM73248-TAG	\$ 12,656
Disconnect Switch (For 1-phase)	Disconnect Switch for Single phase 37.5 kVA Transformer; available only when transformer is ordered	GM73249-TAG	\$ 3,449
Transformer 3 Phase	3 Phase 37.5 kVA 480 primary /208/120 secondary Transformer; available only when BEP or Load Center is ordered	GM73250-TAG	\$ 13,464
Disconnect Switch (For 3-phase)	Disconnect Switch for 3-phase 37.5 kVA Transformer; available only when transformer is ordered	GM73251-TAG	\$ 3,960
Emergency Lights	or Load Center is ordered	GM73252-TAG	\$ 1,556
Enclosure Heater	Single Phase - 208VAC 5kW thermostatically controlled heater	GM73253-TAG	\$ 6,564
(If block heater is ordered, a 3 phase block heater must be matched with 3 phase enclosure heater, must be	Single Phase - 240VAC 5kW thermostatically controlled heater	GM73254-TAG	\$ 6,564
	3 phase - 208VAC 5kW thermostatically controlled heater	GM73255-TAG	\$ 6,564
	3 phase - 240VAC 5kW thermostatically controlled heater	GM73256-TAG	\$ 6,564
Exhaust Fan	800 CFM Shutter-Mounted Exhaust Fan (Wall mounted); available only when BEP or Load Center is ordered	GM73257-TAG	\$ 2,762
Miscellaneous			
Battery Charger	Provide bracket mount & wire customer supplied battery charger to DC side of generator; can only be ordered with loose battery charger and either a BEP or Load Center	GM73258-TAG	\$ 1,933
Battery Charger With Alarms	Provide bracket mount & wire customer supplied battery charger with alarm to DC side of generator; can only be ordered with loose battery charger w/alarms and either a BEP or Load Center	GM73259-TAG	\$ 2,418
Viewing Window	Control Panel Viewing Window	GM73260-TAG	\$ 1,667
Alarm	High fuel level float switch; available only with a tank	GM73261-TAG	\$ 249
Alarm	Economical 3 alarm panel for high, low, and fuel leak (mounted inside enclosure); available only with a tank	GM73262-TAG	\$ 2,669
Alarm	Economical 3 alarm panel for high, low, and fuel leak (mounted outside enclosure); available only with a tank	GM73263-TAG	\$ 2,669
Fill/Spill	Above ground 5 gallon fill/spill containment, piping from fill to outside of enclosure. (External enclosure wall mount) Spill/fill to ship loose for field install or may be attached when it does not effect shipping; available only with a tank	GM73264-TAG	\$ 871
Emergency Stop	Emergency Stop Button - externally mounted	GM73265-TAG	\$ 1,547
Seismic Bracing	Necessary bracing and upgrades to the enclosures and tanks when IBC or OSHPD is selected (OSPHD only available on REOZMD models)	GM87030-TAG	\$ 27,281
ULC-S601 Listing	Canada Option	GM78723-TAG	\$ 667
Pad Lock Std with Global Design			
Automatic Door Holder Std with Global Design			
Internal Release Handles			
Internal Release Handles	Internal Release Handles - 1 per door	GM73266-TAG	\$ 2,447
Supply Fuel Transfer Systems - only available with BEP or Load Center			
1250 kW through 1600 kW	Series 400 Electronic Control Module (ECM) with 4 GPM pump and 1/3 HP motor, solenoid valve, fuel strainer and critical high shutdown. Mounted, plumbed and wired as a Modular Fuel Transfer System; available only with tank	GM73267-TAG	\$ 12,776
1750 kW through 2000 kW	Series 400 Electronic Control Module (ECM) with 7 GPM pump and 1/2 HP motor, solenoid valve, fuel strainer and critical high shutdown. Mounted, plumbed and wired as a Modular Fuel Transfer System; available only with tank	GM73268-TAG	\$ 13,898
Return Fuel Transfer Systems (MUST order Supply fuel transfer system)			
1250 kW through 1600 kW	A 7 GPM pump returns fuel to the main tank.	GM73269-TAG	\$ 4,616
1750 kW through 2000 kW	A 10 GPM pump returns fuel to the main tank.	GM73270-TAG	\$ 5,738
Motorized Discharge Louvers - only available with BEP or Load Center			
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1250 REOZMD	GM73271-TAG	\$ 9,849

Options

Aluminum Weather Enclosures for Internal Silencer & UL Tank Packages

Option	Description	Kohler Part #	List Price
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1600 REOZMD	GM73272-TAG	\$ 13,540
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73275-TAG	\$ 13,744
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73276-TAG	\$ 20,013
Motorized Intake Louvers - only available with BEP or Load Center			
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1250 REOZMD	GM73279-TAG	\$ 41,702
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1600 REOZMD	GM73280-TAG	\$ 41,702
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73283-TAG	\$ 48,736
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73284-TAG	\$ 55,467
Gravity Discharge			
Gravity Discharge	Gravity Discharge (Aluminum) - 1250REOZMD	GM73287-TAG	\$ 7,422
Gravity Discharge	Gravity Discharge (Aluminum) - 1600 REOZMD	GM73288-TAG	\$ 7,904
Gravity Discharge	Gravity Discharge (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73291-TAG	\$ 8,064
Gravity Discharge	Gravity Discharge (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73292-TAG	\$ 13,298
State Tank Accessories			
Fuel Fill Options	Fill pipe extension to within 6" of bottom	GM77856-TAG	\$ 556
	5 Gal. Spill Containment	GM77857-TAG	\$ 1,278
	5 Gal. Spill Containment w/ 95% shutoff	GM77858-TAG	\$ 1,833
	5 Gal. Spill Containment w/ fill to within 6" of tank bottom	GM77859-TAG	\$ 2,778
Normal Vent Options	12' above grade (without spill containment)	GM77860-TAG	\$ 778
	12' above grade (with spill containment)	GM77861-TAG	\$ 2,000
High Fuel Switch	High Fuel switch (set at 90%)	GM77862-TAG	\$ 278
	High Fuel switch (set at 90%) FDEP Approved	GM77863-TAG	\$ 1,167
Fuel in Basin Options	Fuel in Basin Switch, top mount (FDEP approved)	GM77864-TAG	\$ 556
Fuel Supply Options	Fire safety valve (installed on fuel supply)	GM77865-TAG	\$ 833
	Ball valve (installed on fuel supply)	GM77866-TAG	\$ 333
Bottom Clearance/Coating	C8 x 11.5 channels (provide 2" ground clearance)	GM77867-TAG	\$ 7,222
	Epoxy, Mastic Coating	GM77868-TAG	\$ 4,889
Tank Marking Options	Combustible Liquids - Keep Fire Away (2 decals provided)	GM77869-TAG	\$ 278
	NFPA 704 identification (2 decals provided)	GM77870-TAG	\$ 278
	Tank number and safe fill height (2 decals provided)	GM77871-TAG	\$ 278

Standard Features

Aluminum Sound Enclosures Level 1 with Internal Silencer & UL Tank Packages

► **Sound Enclosure Level 1 with Internal Silencer Design** includes internal critical silencer. Design drops-over to mount to tank or lift base.

Sound Enclosure Level 1 with Internal Silencer Features:

► **Available in Aluminum (.080), formed panel, solid construction**

Pre-assembled package offers a corrosion resistant aluminum, dent resilient structure that mounts directly to lift base or tank.

► **Polyurethane Enamel Paint**

Superior finish, durability and appearance.

► **Interchangeable modular panel construction**

Allows complete serviceability or replacement without compromising enclosure design.

► **Internal Critical Exhaust Silencer (Standard)**

Offers maximum component life, operator safety and includes rain shield and cap.

► **-Attenuated design**

Offers reduction up to -15 dBA @ 7 meters, average of 8 readings. Acoustic insulation is UL-94 HF1 listed for flame resistance. The -15 dBA design offers 2" mechanically restrained acoustic insulation in enclosure only.

► **Service access**

External radiator fill, six personnel doors for easy access to generator set control and servicing of fuel fill, fuel gauge, oil fill & battery.

► **Turning of Control Panel**

If generator has a single circuit breaker then the control panel is turned to opposite side of the breaker. If dual breaker consult factory.

Cooling/Combustion Air Intake:

► **-attenuated models offer 90° vertical air inlet hood**

The -15 dBA models include acoustic insulation lining with urethane film.

Cooling Air Discharge:

► **-attenuated models offer 90° vertical air Gravity Outlet 90° internal plenum**

Redirects cooling air up and above enclosure to reduce noise ambient. -15 dBA models include acoustic insulation with urethane film.

Standard Sub-Base Tank Features:

► **Extended Operation**

Usable tank capacity offers full load standby operation of up to 48 hours through 2000 kW

► **UL Listed**

Secondary containment generator base tank meets UL 142 special purpose tank requirements.

► **NFPA compliant**

Designed to comply with the installation standards of NFPA 30, NFPA 37 and NFPA 110.

► **Integral external tank lift lugs**

Enables a crane with spreader-bar lifting of complete package (empty tank, mounted gen-set and enclosure) to ensure safety.

► **Emergency pressure relief vent caps**

Meets UL requirements - insures adequate venting of inner and outer tank under extreme pressure and/or emergency conditions.

► **Atmospheric vent cap**

Oversized 2" vent is raised above lockable fuel fill.

► **Low fuel level and leak detection switch**

Annunciates a contained primary tank fuel leak or a 50% low fuel level condition and the Generator Set Control.

► **Full width electrical stub-up**

Easy access via removable end channel.

► **Fuel transfer System**

Tank top mounting bracket offers location for (optional) fuel transfer system for extended generator set operation of for customer specified tank monitoring.

► **Rain runoff**

Included when tanks extend beyond the enclosure, ensures rain run-off.

Options:

See SL1 with Internal Silencer list of options

Pricing

Aluminum Sound Enclosures Level 1 with Internal Silencer & UL Tank Packages

Kohler Package Part Numbers	Secondary Cont. UL Tank Gallon Capacity	Estimated fuel supply hours at 60hz with full load	Package Dimensions ¹ Inches			Shipping Weight lbs.	Elec. Stub Up L x W	List Price
			Length	Width	Height			2024
1250 REOZMD ADV-7799 40°C & 50°C ADV-8551 SEISMIC GM72645-TPG								
GM72981-TAG	Lift Base		444	114	165	34955	41 x 102	\$291,393
GM72982-TAG	1350	13	444	114	169	38105	41 x 102	\$315,190
GM72983-TAG	1600	15	444	114	171	38415	41 x 102	\$317,240
GM72984-TAG	2100	20	444	114	175	39055	41 x 102	\$321,311
GM72985-TAG	2600	25	514	114	175	40645	41 x 102	\$332,472
GM72986-TAG	3130	30	588	114	175	42305	41 x 102	\$344,528
GM72987-TAG	4150	40	444	114	199	44905	41 x 102	\$381,160
GM72988-TAG	5150	50	444	114	207	46115	41 x 102	\$407,857
GM72989-TAG	6160	60	502	114	207	47995	41 x 102	\$423,358
GM72990-TAG	7700	74	590	114	207	50775	41 x 102	\$446,237
1600 REOZMD ADV-7802 40°C & 50°C ADV-8551 SEISMIC GM72648-TPG								
GM73011-TAG	Lift Base		485	114	165	40710	41 x 102	\$320,121
GM73012-TAG	1350	10	485	114	169	43965	41 x 102	\$344,180
GM73013-TAG	1600	12	485	114	170	44365	41 x 102	\$345,259
GM73014-TAG	2100	16	485	114	174	45055	41 x 102	\$349,585
GM73015-TAG	2600	20	565	114	174	46665	41 x 102	\$362,378
GM73016-TAG	3130	24	643	114	174	48370	41 x 102	\$374,763
GM73017-TAG	4150	32	485	114	195	51750	41 x 102	\$406,035
GM73018-TAG	5150	40	485	114	202	52965	41 x 102	\$433,025
GM73019-TAG	6160	48	521	114	205	54660	41 x 102	\$446,170
GM73020-TAG	7700	60	589	114	207	57170	41 x 102	\$466,299
1750/2000 REOZMD ADV-7803 40°C ADV-8551 SEISMIC GM72649-TPG								
GM73021-TAG	Lift Base		485	114	165	43545	41 x 102	\$329,183
GM73022-TAG	1350	10/8	485	114	169	46800	41 x 102	\$353,242
GM73023-TAG	1600	11/10	485	114	170	47200	41 x 102	\$354,321
GM73024-TAG	2100	15/13	485	114	174	47890	41 x 102	\$358,647
GM73025-TAG	2600	18/16	565	114	174	49500	41 x 102	\$371,440
GM73026-TAG	3130	22/20	643	114	174	51205	41 x 102	\$383,825
GM73027-TAG	4150	29/26	485	114	195	54585	41 x 102	\$413,765
GM73028-TAG	5150	36/32	485	114	202	55800	41 x 102	\$440,756
GM73029-TAG	6160	44/38	521	114	205	57495	41 x 102	\$453,901
GM73030-TAG	7900	54/48	589	114	207	60005	41 x 102	\$474,030
1750/2000 REOZMD ADV-7804 50°C ADV-8551 SEISMIC GM72650-TPG								
GM73031-TAG	Lift Base		511	124	165	45620	41 x 112	\$351,427
GM73032-TAG	1350	10/8	511	124	167	49355	41 x 112	\$373,847
GM73033-TAG	1600	11/10	511	124	169	49580	41 x 112	\$376,217
GM73034-TAG	2100	15/13	511	124	172	50160	41 x 112	\$379,775
GM73035-TAG	2600	18/16	511	124	175	50740	41 x 112	\$383,338
GM73036-TAG	3130	22/20	511	124	178	51440	41 x 112	\$386,904
GM73037-TAG	4150	29/26	617	124	178	54090	41 x 112	\$405,748
GM73038-TAG	5150	36/32	511	124	198	57595	41 x 112	\$468,647
GM73039-TAG	6160	44/38	511	124	204	58740	41 x 112	\$476,269
GM73040-TAG	7900	54/48	575	124	207	61490	41 x 112	\$497,785

¹ Package dimensions are overall length, width and height. Overall length includes tank length.

Options

Aluminum Sound Enclosures Level 1 for Internal Silencer & UL Tank Packages

Option	Description	Kohler Part #	List Price
Electrical			
DC Light Package	Two-(2) quantity DC interior lights powered by the starting battery on a fused circuit with a 0-60 minute "No-Lock-On" timer, 24 VDC standard.	GM73237-TAG	\$ 2,624
Additional DC Lights	Two additional DC Lights; only available when DC light package is ordered	GM73238-TAG	\$ 1,520
Basic Electrical Package 200 Amp Max (only one can be selected and cannot be ordered with Load Center)	Load center 120/208/240VAC single phase, 200 amp max w/ main and 12 branch circuits. (1) switch control (3) AC lights vapor tight and gasketed wiring of jacket water heater (2) duplex GFI receptacles.	GM76027-TAG	\$ 6,487
	Load center 120/208/240VAC 3 phase, 200 amp max w/ main and 12 branch circuits. (1) switch control (3) AC lights vapor tight and gasketed wiring of jacket water heater (2) duplex GFI receptacles.	GM76028-TAG	\$ 8,376
	Load center 120/240VAC, single phase, 200 amp max with main and 12 branch circuits. One-(1) switch control and <u>Two-(2) four foot LED lights</u> . Block heater wiring included. Two-(2) quantity duplex GFI receptacles.	GM76029-TAG	\$ 6,742
	Load center 120/208/240VAC, three phase, 200 amp max with main and 12 branch circuits. One-(1) switch control and Two-(2) four foot LED lights. Block heater wiring included. Two-(2) quantity duplex GFI receptacles.	GM76030-TAG	\$ 8,631
Additional Lights & Receptacles	Two Additional AC lights	GM73243-TAG	\$ 2,389
(only available with BEP or Load Center is ordered)	Additional duplex GFI receptacles (2 included - internal mounted)	GM73244-TAG	\$ 969
	Additional duplex GFI receptacles (2 included - external mounted)	GM73245-TAG	\$ 1,938
Load Center - 200 Amp Max (only one can be selected and cannot be ordered with BEP)	Load center 120/208/240VAC, single phase, 200 amp max with main and 12 branch circuits and wiring of the block heater	GM76025-TAG	\$ 2,278
	Load center 120/208/240VAC, 3 phase, 200 amp max with main and 12 branch circuits and wiring of the block heater	GM76026-TAG	\$ 4,167
Transformer Single Phase	Single Phase 37.5 kVA 480 primary /208/120 secondary Transformer; available on when BEP or Load Center is ordered	GM73248-TAG	\$ 12,656
Disconnect Switch (For 1-phase)	Disconnect Switch for Single phase 37.5 kVA Transformer; available only when transformer is ordered	GM73249-TAG	\$ 3,449
Transformer 3 Phase	3 Phase 37.5 kVA 480 primary /208/120 secondary Transformer; available only when BEP or Load Center is ordered	GM73250-TAG	\$ 13,464
Disconnect Switch (For 3-phase)	Disconnect Switch for 3-phase 37.5 kVA Transformer; available only when transformer is ordered	GM73251-TAG	\$ 3,960
Emergency Lights	Dual head battery powered emergency lights includes batteries (qty 2) mounted inside enclosure; available only when BEP or Load Center is ordered	GM73252-TAG	\$ 1,556
Enclosure Heater	Single Phase - 208VAC 5kW thermostatically controlled heater	GM73253-TAG	\$ 6,564
(If block heater is ordered, a 3 phase block heater must be matched with 3 phase enclosure heater, must be	Single Phase - 240VAC 5kW thermostatically controlled heater	GM73254-TAG	\$ 6,564
	3 phase - 208VAC 5kW thermostatically controlled heater	GM73255-TAG	\$ 6,564
	3 phase - 240VAC 5kW thermostatically controlled heater	GM73256-TAG	\$ 6,564
Exhaust Fan	800 CFM Shutter-Mounted Exhaust Fan (Wall mounted); available only when BEP or Load Center is ordered	GM73257-TAG	\$ 2,762
Miscellaneous			
Battery Charger	Provide bracket mount & wire customer supplied battery charger to DC side of generator; can only be ordered with loose battery charger and either a BEP or Load Center	GM73258-TAG	\$ 1,933
Battery Charger With Alarms	Provide bracket mount & wire customer supplied battery charger with alarm to DC side of generator; can only be ordered with loose battery charger w/alarms and either a BEP or Load Center	GM73259-TAG	\$ 2,418
Viewing Window	Control Panel Viewing Window	GM73260-TAG	\$ 1,667
Alarm	High fuel level float switch; available only with a tank	GM73261-TAG	\$ 249
Alarm	Economical 3 alarm panel for high, low, and fuel leak (mounted inside enclosure); available only with a tank	GM73262-TAG	\$ 2,669
Alarm	Economical 3 alarm panel for high, low, and fuel leak (mounted outside enclosure); available only with a tank	GM73263-TAG	\$ 2,669
Fill/Spill	Above ground 5 gallon fill/spill containment, piping from fill to outside of enclosure. (External enclosure wall mount) Spill/fill to ship loose for field install or may be attached when it does not effect shipping; available only with a tank	GM73264-TAG	\$ 871
Emergency Stop	Emergency Stop Button - externally mounted	GM73265-TAG	\$ 1,547
Seismic Bracing	Necessary bracing and upgrades to the enclosures and tanks when IBC or OSHPD is selected (OSPHD only available on REOZMD models)	GM87031-TAG	\$ 27,281
ULC-S601 Listing	Canada Option	GM78723-TAG	\$ 667
Pad Lock Std with Global Design			
Automatic Door Holder Std with Global Design			
Internal Release Handles			
Internal Release Handles	Internal Release Handles - 1 per door	GM73266-TAG	\$ 2,447
Supply Fuel Transfer Systems - only available with BEP or Load Center			
1250 kW through 1600 kW	Series 400 Electronic Control Module (ECM) with 4 GPM pump and 1/3 HP motor, solenoid valve, fuel strainer and critical high shutdown. Mounted, plumbed and wired as a Modular Fuel Transfer System; available only with tank	GM73267-TAG	\$ 12,776
1750 kW through 2000 kW	Series 400 Electronic Control Module (ECM) with 7 GPM pump and 1/2 HP motor, solenoid valve, fuel strainer and critical high shutdown. Mounted, plumbed and wired as a Modular Fuel Transfer System; available only with tank	GM73268-TAG	\$ 13,898
Return Fuel Transfer Systems (MUST order Supply fuel transfer system)			
1250 kW through 1600 kW	A 7 GPM pump returns fuel to the main tank.	GM73269-TAG	\$ 4,616

Options			
Aluminum Sound Enclosures Level 1 for Internal Silencer & UL Tank Packages			
Option	Description	Kohler Part #	List Price
1750 kW through 2000 kW	A 10 GPM pump returns fuel to the main tank.	GM73270-TAG	\$ 5,738

Options

Aluminum Sound Enclosures Level 1 for Internal Silencer & UL Tank Packages

Option	Description	Kohler Part #	List Price
Motorized Discharge Louvers - only available with BEP or Load Center			
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1250 REOZMD	GM73295-TAG	\$ 9,849
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1600 REOZMD	GM73296-TAG	\$ 13,540
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73299-TAG	\$ 13,744
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73300-TAG	\$ 20,013
Motorized Intake Louvers - only available with BEP or Load Center			
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1250 REOZMD	GM73303-TAG	\$ 14,531
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1600 REOZMD	GM73304-TAG	\$ 16,402
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73307-TAG	\$ 14,867
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73308-TAG	\$ 21,640
Gravity Discharge			
Gravity Discharge	Gravity Discharge (Aluminum) - 1250 REOZMD	GM73311-TAG	\$ 7,422
Gravity Discharge	Gravity Discharge (Aluminum) - 1600 REOZMD	GM73312-TAG	\$ 7,904
Gravity Discharge	Gravity Discharge (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73315-TAG	\$ 8,064
Gravity Discharge	Gravity Discharge (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73316-TAG	\$ 13,298
State Tank Accessories			
Fuel Fill Options	Fill pipe extension to within 6" of bottom	GM77856-TAG	\$ 556
	5 Gal. Spill Containment	GM77857-TAG	\$ 1,278
	5 Gal. Spill Containment w/ 95% shutoff	GM77858-TAG	\$ 1,833
	5 Gal. Spill Containment w/ fill to within 6" of tank bottom	GM77859-TAG	\$ 2,778
Normal Vent Options	12' above grade (without spill containment)	GM77860-TAG	\$ 778
	12' above grade (with spill containment)	GM77861-TAG	\$ 2,000
High Fuel Switch	High Fuel switch (set at 90%)	GM77862-TAG	\$ 278
	High Fuel switch (set at 90%) FDEP Approved	GM77863-TAG	\$ 1,167
Fuel in Basin Options	Fuel in Basin Switch, top mount (FDEP approved)	GM77864-TAG	\$ 556
Fuel Supply Options	Fire safety valve (installed on fuel supply)	GM77865-TAG	\$ 833
	Ball valve (installed on fuel supply)	GM77866-TAG	\$ 333
Bottom Clearance/Coating	C8 x 11.5 channels (provide 2" ground clearance)	GM77867-TAG	\$ 7,222
	Epoxy, Mastic Coating	GM77868-TAG	\$ 4,889
Tank Marking Options	Combustible Liquids - Keep Fire Away (2 decals provided)	GM77869-TAG	\$ 278
	NFPA 704 identification (2 decals provided)	GM77870-TAG	\$ 278
	Tank number and safe fill height (2 decals provided)	GM77871-TAG	\$ 278

Standard Features

Aluminum Sound Enclosures Level 2 with Internal Silencer & UL Tank Packages

► **Sound Enclosure Level 2 with Internal Silencer Design** includes internal hospital silencer. Design drops-over to mount to tank or lift base.

Sound Enclosure Level 2 with Internal Silencer Features:

► **Available in Aluminum (.080), formed panel, solid construction**

Pre-assembled package offers a corrosion resistant aluminum, dent resilient structure that mounts directly to lift base or tank.

► **Polyurethane Enamel Paint**

Superior finish, durability and appearance.

► **Interchangeable modular panel construction**

Allows complete serviceability or replacement without compromising enclosure design.

► **-Attenuated design**

Offers reduction up to -25 dBA @ 7 meters, average of 8 readings. Acoustic insulation is UL-94 HF1 listed for flame resistance. The -25 dBA design features 3" acoustic insulation with aluminum perforated interior liner in the enclosure and 2" insulation mechanically restrained in hoods.

► **Internal Hospital Exhaust Silencer (Standard)**

Offers maximum component life, operator safety and includes rain shield and cap.

► **Service access**

External radiator fill, six personnel doors for easy access to generator set control and servicing of fuel fill, fuel gauge, oil fill & battery.

► **Turning of Control Panel**

If generator has a single circuit breaker then the control panel is turned to opposite side of the breaker. If dual breaker consult factory.

Cooling/Combustion Air Intake:

► **-attenuated models offer 90° vertical air inlet hood**

The -25 dBA models include acoustic insulation lining with urethane film.

Cooling Air Discharge:

► **-attenuated models offer 90° vertical air Gravity Outlet 90° internal plenum**

Redirects cooling air up and above enclosure to reduce noise ambient. -25 dBA models include acoustic insulation with urethane film.

Standard Sub-Base Tank Features:

► **Extended Operation**

Usable tank capacity offers full load standby operation of up to 48 hours through 2000 kW

► **UL Listed**

Secondary containment generator base tank meets UL 142 special purpose tank requirements.

► **NFPA compliant**

Designed to comply with the installation standards of NFPA 30, NFPA 37 and NFPA 110.

► **Integral external tank lift lugs**

Enables a crane with spreader-bar lifting of complete package (empty tank, mounted gen-set and enclosure) to ensure safety.

► **Emergency pressure relief vent caps**

Meets UL requirements - insures adequate venting of inner and outer tank under extreme pressure and/or emergency conditions.

► **Atmospheric vent cap**

Oversized 2" vent is raised above lockable fuel fill.

► **Low fuel level and leak detection switch**

Annunciates a contained primary tank fuel leak or a 50% low fuel level condition and the Generator Set Control.

► **Full width electrical stub-up**

Easy access via removable end channel.

► **Fuel transfer System**

Tank top mounting bracket offers location for (optional) fuel transfer system for extended generator set operation of for customer specified tank monitoring.

► **Rain runoff**

Included when tanks extend beyond the enclosure, ensures rain run-off.

Options:

See SL1 with Internal Silencer list of options

Pricing

Aluminum Sound Enclosures Level 2 with Internal Silencer & UL Tank Packages

Kohler Package Part Numbers	Secondary Cont. UL Tank Gallon Capacity	Estimated fuel supply hours at 60hz with full load	Package Dimensions ¹ Inches			Shipping Weight lbs.	Elec. Stub Up L x W	List Price
			Length	Width	Height			2024
1250 REOZMD ADV-7815 40°C & 50°C ADV-8551 SEISMIC GM72653-TPG								
GM73061-TAG	Lift Base		444	114	165	35370	41 x 102	\$305,962
GM73062-TAG	1350	13	444	114	169	38520	41 x 102	\$330,950
GM73063-TAG	1600	15	444	114	171	38830	41 x 102	\$333,101
GM73064-TAG	2100	20	444	114	175	39470	41 x 102	\$337,377
GM73065-TAG	2600	25	514	114	175	41060	41 x 102	\$349,095
GM73066-TAG	3130	30	588	114	175	42720	41 x 102	\$361,755
GM73067-TAG	4150	40	444	114	199	45320	41 x 102	\$400,219
GM73068-TAG	5150	50	444	114	207	46530	41 x 102	\$428,250
GM73069-TAG	6160	60	502	114	207	48410	41 x 102	\$444,526
GM73070-TAG	7700	74	590	114	207	51190	41 x 102	\$468,549
1600 REOZMD ADV-7818 40°C & 50°C ADV-8551 SEISMIC GM72656-TPG								
GM73091-TAG	Lift Base		485	114	165	41125	41 x 102	\$336,127
GM73092-TAG	1350	10	485	114	169	44380	41 x 102	\$361,389
GM73093-TAG	1600	12	485	114	170	44780	41 x 102	\$362,522
GM73094-TAG	2100	16	485	114	174	45470	41 x 102	\$367,064
GM73095-TAG	2600	20	565	114	174	47080	41 x 102	\$380,497
GM73096-TAG	3130	24	643	114	174	48785	41 x 102	\$393,501
GM73097-TAG	4150	32	485	114	195	52165	41 x 102	\$426,336
GM73098-TAG	5150	40	485	114	202	53380	41 x 102	\$454,676
GM73099-TAG	6160	48	521	114	205	55075	41 x 102	\$468,479
GM73100-TAG	7700	60	589	114	207	57585	41 x 102	\$489,614
1750/2000 REOZMD ADV-7819 40°C ADV-8551 SEISMIC GM72657-TPG								
GM73101-TAG	Lift Base		485	114	165	43920	41 x 102	\$345,642
GM73102-TAG	1350	10/8	485	114	169	47175	41 x 102	\$370,904
GM73103-TAG	1600	11/10	485	114	170	47575	41 x 102	\$372,037
GM73104-TAG	2100	15/13	485	114	174	48265	41 x 102	\$376,579
GM73105-TAG	2600	18/16	565	114	174	49875	41 x 102	\$390,011
GM73106-TAG	3130	22/20	643	114	174	51580	41 x 102	\$403,016
GM73107-TAG	4150	29/26	485	114	195	54960	41 x 102	\$434,454
GM73108-TAG	5150	36/32	485	114	202	56175	41 x 102	\$462,793
GM73109-TAG	6160	44/38	521	114	205	57870	41 x 102	\$476,596
GM73110-TAG	7900	54/48	589	114	207	60380	41 x 102	\$497,731
1750/2000 REOZMD ADV-7820 50°C ADV-8551 SEISMIC GM72658-TPG								
GM73111-TAG	Lift Base		511	124	165	46220	41 x 112	\$368,999
GM73112-TAG	1350	10/8	511	124	167	49950	41 x 112	\$392,539
GM73113-TAG	1600	11/10	511	124	169	50180	41 x 112	\$395,028
GM73114-TAG	2100	15/13	511	124	172	50760	41 x 112	\$398,764
GM73115-TAG	2600	18/16	511	124	175	51340	41 x 112	\$402,505
GM73116-TAG	3130	22/20	511	124	178	52040	41 x 112	\$406,249
GM73117-TAG	4150	29/26	617	124	178	54690	41 x 112	\$426,036
GM73118-TAG	5150	36/32	511	124	198	58195	41 x 112	\$492,079
GM73119-TAG	6160	44/38	511	124	204	59340	41 x 112	\$500,083
GM73120-TAG	7900	54/48	575	124	207	62090	41 x 112	\$522,674

¹ Package dimensions are overall length, width and height. Overall length includes tank length.

Options

Aluminum Sound Enclosures Level 2 for Internal Silencer & UL Tank Packages

Option	Description	Kohler Part #	List Price
Electrical			
DC Light Package	Two-(2) quantity DC interior lights powered by the starting battery on a fused circuit with a 0-60 minute "No-Lock-On" timer, 24 VDC standard.	GM73237-TAG	\$ 2,624
Additional DC Lights	Two additional DC Lights; only available when DC light package is ordered	GM73238-TAG	\$ 1,520
Basic Electrical Package 200 Amp Max (only one can be selected and cannot be ordered with Load Center)	Load center 120/208/240VAC single phase, 200 amp max w/ main and 12 branch circuits. (1) switch control (3) AC lights vapor tight and gasketed wiring of jacket water heater (2) duplex GFI receptacles.	GM76027-TAG	\$ 6,487
	Load center 120/208/240VAC 3 phase, 200 amp max w/ main and 12 branch circuits. (1) switch control (3) AC lights vapor tight and gasketed wiring of jacket water heater (2) duplex GFI receptacles.	GM76028-TAG	\$ 8,376
	Load center 120/240VAC, single phase, 200 amp max with main and 12 branch circuits. One-(1) switch control and <u>Two-(2) four foot LED lights</u> . Block heater wiring included. Two-(2) quantity duplex GFI receptacles.	GM76029-TAG	\$ 6,742
	Load center 120/208/240VAC, three phase, 200 amp max with main and 12 branch circuits. One-(1) switch control and Two-(2) four foot LED lights. Block heater wiring included. Two-(2) quantity duplex GFI receptacles.	GM76030-TAG	\$ 8,631
Additional Lights & Receptacles (only available with BEP or Load Center is ordered)	Two Additional AC lights	GM73243-TAG	\$ 2,389
	Additional duplex GFI receptacles (2 included - internal mounted)	GM73244-TAG	\$ 969
	Additional duplex GFI receptacles (2 included - external mounted)	GM73245-TAG	\$ 1,938
Load Center - 200 Amp Max (only one can be selected and cannot be orderd with BEP)	Load center 120/208/240VAC, single phase, 200 amp max with main and 12 branch circuits and wiring of the block heater	GM76025-TAG	\$ 2,278
	Load center 120/208/240VAC, 3 phase, 200 amp max with main and 12 branch circuits and wiring of the block heater	GM76026-TAG	\$ 4,167
Transformer Single Phase	Single Phase 37.5 kVA 480 primary /208/120 secondary Transformer; available on when BEP or Load Center is ordered	GM73248-TAG	\$ 12,656
Disconnect Switch (For 1-phase)	Disconnect Switch for Single phase 37.5 kVA Transformer; available only when transformer is ordered	GM73249-TAG	\$ 3,449
Transformer 3 Phase	3 Phase 37.5 kVA 480 primary /208/120 secondary Transformer; available only when BEP or Load Center is ordered	GM73250-TAG	\$ 13,464
Disconnect Switch (For 3-phase)	Disconnect Switch for 3-phase 37.5 kVA Transformer; available only when transformer is ordered	GM73251-TAG	\$ 3,960
Emergency Lights	Dual head battery powered emergency lights includes batteries (qty 2) mounted inside enclosure; available only when BEP or Load Center is ordered	GM73252-TAG	\$ 1,556
Enclosure Heater (If block heater is ordered, a 3 phase block heater must be matched with 3 phase enclosure heater, must be Exhaust Fan	Single Phase - 208VAC 5kW thermostatically controlled heater	GM73253-TAG	\$ 6,564
	Single Phase - 240VAC 5kW thermostatically controlled heater	GM73254-TAG	\$ 6,564
	3 phase - 208VAC 5kW thermostatically controlled heater	GM73255-TAG	\$ 6,564
	3 phase - 240VAC 5kW thermostatically controlled heater	GM73256-TAG	\$ 6,564
	800 CFM Shutter-Mounted Exhaust Fan (Wall mounted); available only when BEP or Load Center is ordered	GM73257-TAG	\$ 2,762
Miscellaneous			
Battery Charger	Provide bracket mount & wire customer supplied battery charger to DC side of generator; can only be ordered with loose battery charger and either a BEP or Load Center	GM73258-TAG	\$ 1,933
Battery Charger With Alarms	Provide bracket mount & wire customer supplied battery charger with alarm to DC side of generator; can only be ordered with loose battery charger w/alarms and either a BEP or Load Center	GM73259-TAG	\$ 2,418
Viewing Window	Control Panel Viewing Window	GM73260-TAG	\$ 1,667
Alarm	High fuel level float switch; available only with a tank	GM73261-TAG	\$ 249
Alarm	Economical 3 alarm panel for high, low, and fuel leak (mounted inside enclosure); available only with a tank	GM73262-TAG	\$ 2,669
Alarm	Economical 3 alarm panel for high, low, and fuel leak (mounted outside enclosure); available only with a tank	GM73263-TAG	\$ 2,669
Fill/Spill	Above ground 5 gallon fill/spill containment, piping from fill to outside of enclosure. (External enclosure wall mount) Spill/fill to ship loose for field install or may be attached when it does not effect shipping; available only with a tank	GM73264-TAG	\$ 871
Emergency Stop	Emergency Stop Button - externally mounted	GM73265-TAG	\$ 1,547
Seismic Bracing	Necessary bracing and upgrades to the enclosures and tanks when IBC or OSHPD is selected (OSPHD only available on REOZMD models)	GM87032-TAG	\$ 27,281
ULC-S601 Listing	Canada Option	GM78723-TAG	\$ 667
Pad Lock Std with Global Design			
Automatic Door Holder Std with Global Design			
Internal Release Handles			
Internal Release Handles	Internal Release Handles - 1 per door	GM73266-TAG	\$ 2,447
Supply Fuel Transfer Systems - only available with BEP or Load Center			
1250 kW through 1600 kW	Series 400 Electronic Control Module (ECM) with 4 GPM pump and 1/3 HP motor, solenoid valve, fuel strainer and critical high shutdown. Mounted, plumbed and wired as a Modular Fuel Transfer System; availavle with tank only	GM73267-TAG	\$ 12,776

Options

Aluminum Sound Enclosures Level 2 for Internal Silencer & UL Tank Packages

Option	Description	Kohler Part #	List Price
1750 kW through 2000 kW	Series 400 Electronic Control Module (ECM) with 7 GPM pump and 1/2 HP motor, solenoid valve, fuel strainer and critical high shutdown. Mounted, plumbed and wired as a Modular Fuel Transfer System; available with tank only	GM73268-TAG	\$ 13,898
Return Fuel Transfer Systems (MUST order Supply fuel transfer system)			
1250 kW through 1600 kW	A 7 GPM pump returns fuel to the main tank.	GM73269-TAG	\$ 4,616
1750 kW through 2000 kW	A 10 GPM pump returns fuel to the main tank.	GM73270-TAG	\$ 5,738
Motorized Discharge Louvers - only available with BEP or Load Center			
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1250 REOZMD	GM73319-TAG	\$ 9,849
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1600 REOZMD	GM73320-TAG	\$ 13,540
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73323-TAG	\$ 13,744
Motorized Discharge	Motorized Discharge Louvers (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73324-TAG	\$ 20,013
Motorized Intake Louvers - only available with BEP or Load Center			
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1250 REOZMD	GM73327-TAG	\$ 14,531
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1600 REOZMD	GM73328-TAG	\$ 16,402
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73331-TAG	\$ 14,867
Motorized Intake	Motorized Intake Louvers (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73332-TAG	\$ 21,640
Gravity Discharge			
Gravity Discharge	Gravity Discharge (Aluminum) - 1250REOZMD	GM73335-TAG	\$ 7,422
Gravity Discharge	Gravity Discharge (Aluminum) - 1600 REOZMD	GM73336-TAG	\$ 7,904
Gravity Discharge	Gravity Discharge (Aluminum) - 1750/2000 REOZMD 40°C Radiator	GM73339-TAG	\$ 8,064
Gravity Discharge	Gravity Discharge (Aluminum) - 1750/2000 REOZMD 50°C Radiator	GM73340-TAG	\$ 13,298
State Tank Accessories			
Fuel Fill Options	Fill pipe extension to within 6" of bottom	GM77856-TAG	\$ 556
	5 Gal. Spill Containment	GM77857-TAG	\$ 1,278
	5 Gal. Spill Containment w/ 95% shutoff	GM77858-TAG	\$ 1,833
	5 Gal. Spill Containment w/ fill to within 6" of tank bottom	GM77859-TAG	\$ 2,778
Normal Vent Options	12' above grade (without spill containment)	GM77860-TAG	\$ 778
	12' above grade (with spill containment)	GM77861-TAG	\$ 2,000
High Fuel Switch	High Fuel switch (set at 90%)	GM77862-TAG	\$ 278
	High Fuel switch (set at 90%) FDEP Approved	GM77863-TAG	\$ 1,167
Fuel in Basin Options	Fuel in Basin Switch, top mount (FDEP approved)	GM77864-TAG	\$ 556
Fuel Supply Options	Fire safety valve (installed on fuel supply)	GM77865-TAG	\$ 833
	Ball valve (installed on fuel supply)	GM77866-TAG	\$ 333
Bottom Clearance/Coating	C8 x 11.5 channels (provide 2" ground clearance)	GM77867-TAG	\$ 7,222
	Epoxy, Mastic Coating	GM77868-TAG	\$ 4,889
Tank Marking Options	Combustible Liquids - Keep Fire Away (2 decals provided)	GM77869-TAG	\$ 278
	NFPA 704 identification (2 decals provided)	GM77870-TAG	\$ 278
	Tank number and safe fill height (2 decals provided)	GM77871-TAG	\$ 278