

**T5 DUAL COMMAND  
US PRICE LIST**

## Standard Equipment

### KEY SELLING POINTS:

- CommandArc# ergonomically places most frequently used controls to operator's right
- High visibility panel provides a better view of loader when at full height
- Ten repositionable vents for heating and air conditioning
- Full-size instructor seat
- Electro Hydraulic shuttle lever
- 24x24 Dual Command# transmission
- Power clutch to allow for gear changes without the use of the foot clutch
- 3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- Factory Installed Loader available

#### T5.90 DC

86 Gross Engine hp  
73 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### T5.100 DC

99 Gross Engine hp  
85 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### T5.110 DC

107 Gross Engine hp  
93 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### T5.120 DC

117 Gross Engine hp  
100 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

### ALL MODELS:

Tier 4B Emissions Compliant:  
(SCR + CEGR)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Constant Engine RPM

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Dual Element Air Filter

Vertical Exhaust

30.3 gal Fuel Tank with Guard

2.8 gal AdBLUE DEF Tank

Front Axle Support with access for

Front Pump

Parking brake

### TRANSMISSION:

LH side steering column mounted

Power Shuttle

24 Forward X 24 Reverse Speeds

(4) Synchronized Gears with a

HiLo in each Gear

Power clutch button on Gear lever

to allow for gear changes without the use of the foot clutch

(3) Non-synchronized Ranges

Forward Reverse Synchronized Shuttle

25 mph (40 kph)

Speed varies with tire selection

### STEERING/BRAKES:

Hydrostatic Power Steering

Brakes-

Wet disk brakes

Hydraulically assisted

### AXLES:

FRONT

Heavy Duty 4WD

Electrohydraulic FWD Engagement

Adjustable Tread Width

**T5 DUAL COMMAND  
US PRICE LIST**

## Standard Equipment

### REAR

Heavy Duty Flange Type  
Adjustable Tread Width

### HYDRAULIC SYSTEM:

Open Center System  
Dual Gear Pumps with Cooler  
Implement Pump: 16.9 gpm (63.8 L)  
Steering Pump: 9.7 gpm (37.0 L)  
Total Flow: 26.6 gpm (100.8 L)  
(2) Open Center Remote Valves with  
detent

REAR DIFFERENTIAL LOCK:  
Electronically Engaged

### PTO:

Fully Independent  
Hydraulic Engagement  
Flip-up PTO Shaft Guard  
540/1000 rpm  
Wet Clutch

### 3-POINT LIFT SYSTEM:

Right hand console mounted control  
Cab - Electronic Draft Control with  
Fender mounted controls  
ROPS - Mechanical Draft Control with  
Lift-O-Matic Plus  
5,620 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

### ELECTRICAL:

(1) 800 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
3-pin Power Outlet (30 amp)  
Single Pin (8 amp) Accessory Power  
outlet  
CAB - 2 - 12V power sockets  
ROPS - 1 - 12V power socket

### LIGHTING:

#### CAB

Front: (2) Halogen Headlights and  
(2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

#### ROPS

Front: (2) Halogen Headlights  
Rear: (1) Worklight  
Turn Signals/Flashers/Rear Lights

### INSTRUMENTATION:

Analog Instrumentation with warning  
lights for air cleaner service,  
alternator, oil pressure, fuel  
sediment/water sensor, PTO  
engagement, head light high beam,  
low fuel and parking brake,  
advanced instrument cluster,  
digital speed readout, gauges  
for fuel level, engine temperature,  
tachometer and hour meter

### OPERATOR PROTECTIVE STRUCTURE:

#### CAB MODELS

ROPS protected, flat deck platform  
with heat and air conditioning, tinted  
windshield, retractable sun screen,  
front and rear wiper / washer,  
instructor seat, two doors with locks,  
one internal & two external mirrors,  
openable side windows, hinged rear  
window (opens completely)

Steering Wheel - tilt & telescope  
Seat - Cloth covered air suspension  
seat with 10 degrees swivel,  
operator's presence sensor,  
retractable seat belt and arm rests  
Suspended pedals  
Radio, speakers, and antenna

**T5 DUAL COMMAND  
US PRICE LIST****Standard Equipment****ROPS MODELS**

2-Post Foldable ROPS with ISO-  
mounted flat deck platform  
Steering Wheel - adjustable tilt  
Seat - Vinyl covered with mechanical  
suspension, operator's presence  
sensor, retractable seat belts and  
arm rests  
Suspended pedals  
Locking brake pedals

**MISCELLANEOUS:**

Pivoting Engine Hood  
SMV Emblem  
Toolbox

**WARRANTY:**

New Holland Standard Warranty Applies

**LOADER:****665TL/720LU NON SELF-LEVELING**

Maximum Lift Height @ pivot pin: 134"  
Dump Clearance: 101.4"  
Digging Depth: 7"  
Lift Capacity  
Max Height @ 800mm: 2,632 LBS  
59" high @ 800mm: 3,638 LBS  
Breakout Force @ 800mm: 4,455 LBS  
Reach @ Max Lift Height: 43"  
Reach @ Ground Level: 91"  
Bucket Rollback Angle: 44 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style Loader  
bucket attach

**665TL/725LU SELF-LEVELING**

Maximum Lift Height @ pivot pin: 135"  
Dump Clearance: 102.2"  
Digging Depth: 6.4"  
Lift Capacity  
Max Height @ 800mm: 3,428 LBS  
59" high @ 800mm: 5,549 LBS  
Breakout Force @ 800mm: 5,661 LBS  
Reach @ Max Lift Height: 43"  
Reach @ Ground Level: 93  
Bucket Rollback Angle: 40 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style Loader  
bucket attach

**T5 DUAL COMMAND  
US PRICE LIST**
**Models**

| COMMERCIAL MODEL                 | VERSION    | Weight    | Factory Data | List Price  |
|----------------------------------|------------|-----------|--------------|-------------|
| T5.90 DC                         | Cab        | 8,157 LB  |              | \$80,293.00 |
| Includes the following Equipment |            |           |              |             |
| 14.9R24 R1W (8239404)            | \$2,162.00 |           |              |             |
| 18.4R34 R1W (8365404)            | \$3,833.00 |           |              |             |
| T5.90 DC                         | Rops       | 8,157 LB  |              | \$67,557.00 |
| Includes the following Equipment |            |           |              |             |
| 14.9R24 R1W (8239404)            | \$2,162.00 |           |              |             |
| 18.4R34 R1W (8365404)            | \$3,833.00 |           |              |             |
| T5.100 DC                        | Cab        | 8,157 LB  |              | \$82,753.00 |
| Includes the following Equipment |            |           |              |             |
| 14.9R24 R1W (8239404)            | \$2,162.00 |           |              |             |
| 18.4R34 R1W (8365404)            | \$3,833.00 |           |              |             |
| T5.100 DC                        | Rops       | 8,157 LB  |              | \$70,017.00 |
| Includes the following Equipment |            |           |              |             |
| 14.9R24 R1W (8239404)            | \$2,162.00 |           |              |             |
| 18.4R34 R1W (8365404)            | \$3,833.00 |           |              |             |
| T5.110 DC                        | Cab        | 8,157 LB  |              | \$85,452.00 |
| Includes the following Equipment |            |           |              |             |
| 14.9R24 R1W (8239404)            | \$2,162.00 |           |              |             |
| 18.4R34 R1W (8365404)            | \$3,833.00 |           |              |             |
| T5.110 DC                        | Rops       | 8,157 LB  |              | \$72,716.00 |
| Includes the following Equipment |            |           |              |             |
| 14.9R24 R1W (8239404)            | \$2,162.00 |           |              |             |
| 18.4R34 R1W (8365404)            | \$3,833.00 |           |              |             |
| T5.120 DC                        | Cab        | 10,031 LB |              | \$87,883.00 |
| Includes the following Equipment |            |           |              |             |
| 14.9R24 R1W (8239404)            | \$2,162.00 |           |              |             |
| 18.4R34 R1W (8365404)            | \$3,833.00 |           |              |             |
| T5.120 DC                        | Rops       | 8,157 LB  |              | \$75,147.00 |
| Includes the following Equipment |            |           |              |             |
| 14.9R24 R1W (8239404)            | \$2,162.00 |           |              |             |
| 18.4R34 R1W (8365404)            | \$3,833.00 |           |              |             |

**T5 DUAL COMMAND  
US PRICE LIST**

## Factory Supplied Options

| Order Code | Description | Weight | Factory Data | List Price |
|------------|-------------|--------|--------------|------------|
|------------|-------------|--------|--------------|------------|

**OPERATOR PLATFORM**

## SD T9200 OPERATOR STRUCTURE #1

| ROPS |        |  |  |            |
|------|--------|--|--|------------|
|      | 392315 | Platform w/Foldable ROPS<br><b>Includes tilt column</b>  |  | No Charge  |
|      | 334190 | Deluxe Platform w/FOPS<br><b>Includes tilt column, FOPS canopy, noise reduction kit and 12V power outlet</b>                           |  | \$1,661.00 |
| Cab  |        |  |  |            |
|      | 744588 | Deluxe Cab<br><b>Includes instructor seat, rear wiper and washer, radio &amp; internal mirror</b>                                      |  | No Charge  |
|      | 334183 | Deluxe Cab w/HiVis Panel<br><b>Includes high visibility panel, instructor seat, rear wiper and washer, radio &amp; internal mirror</b> |  | \$557.00   |

**POWER TRAIN**

## TRANSMISSION

## SD T2820 PARK LOCK

|  |        |   |  |           |
|--|--------|---|--|-----------|
|  | 743551 | Parking Lock  |  | \$53.00   |
|  | 759176 | Hand Brake<br><b>Hand operated parking brake lever<br/>Standard Equipment</b> |  | No Charge |

**TIRES**

## FRONT

## SD T4940 FRONT WHEELS AND TIRES

| Ag Front Tires        |         |                    |  |            |
|-----------------------|---------|--------------------|--|------------|
|                       | 8232404 | 11.2R24 R1W        |  | \$1,203.00 |
|                       | 8235404 | 12.4R24 R1W        |  | \$1,436.00 |
|                       | 8236404 | 13.6R24 R1W        |  | \$1,757.00 |
|                       | 8239404 | 14.9R24 R1W        |  | \$2,162.00 |
| Specialty Front Tires |         |                    |  |            |
|                       | 8290904 | 12.5/80-18 10PR R4 |  | \$1,717.00 |

**T5 DUAL COMMAND  
US PRICE LIST**

|  |  |         |  |  |  |            |
|--|--|---------|--|--|--|------------|
|  |  | 8873402 | 360/80R20 TRI 2 HD<br><b>Municipal tread</b> |  |  | \$1,956.00 |
|  |  | 8247404 | 11.2R28 R1W                                  |  |  | \$1,484.00 |

**REAR**

## SD T4950 REAR WHEELS AND TIRES

**Ag Rear Tires**

|  |  |         |  |  |  |            |
|--|--|---------|--|--|--|------------|
|  |  | 8355404 | 16.9R30 R1W<br><b>4WD Front Tire - 11.2R24 (8232404)</b> |  |  | \$2,609.00 |
|  |  | 8357404 | 18.4R30 R1W<br><b>4WD Front Tire - 12.4R24 (8235404)</b> |  |  | \$3,480.00 |
|  |  | 8302804 | 16.9R34 R1W<br><b>Front Tire - 13.6R24 (8236404)</b>     |  |  | \$2,505.00 |
|  |  | 8365404 | 18.4R34 R1W<br><b>4WD Front Tire - 14.9R24 (8239404)</b> |  |  | \$3,833.00 |

**Specialty Rear Tires**

|  |  |         |   |  |  |            |
|--|--|---------|---|--|--|------------|
|  |  | 8391904 | 19.5L-24 10 PR R4<br><b>4WD Front Tire - 12.5/80-18 (8290904)</b>             |  |  | \$2,658.00 |
|  |  | 8906401 | 440/80 R30<br><b>Municipal tread<br/>4WD Front Tire - 360/80R20 (8873402)</b> |  |  | \$3,644.00 |
|  |  | 8372404 | 13.6R38 R1W 8372404<br><b>4WD Front Tire - 11.2R28 (8247404)</b>              |  |  | \$2,338.00 |

**HYDRAULICS**
**MID-MOUNT**

## SD T8280 MID-MOUNT VALVES

|  |  |        |  |  |  |            |
|--|--|--------|--|--|--|------------|
|  |  | 338125 | 2Mid-Mount w/Mec Joystick<br><b>2 function mid-mount valve and joystick</b>  |  |  | \$1,484.00 |
|  |  | 336780 | 2Mid-Mount w/Mec Joystick +Div<br><b>2 function mid-mount valve and joystick with 3rd function diverter<br/>Requires a Loader<br/>Bucket with Grapple NOT AVAILABLE as Factory Installed</b> |  |  | \$2,227.00 |

**LOADER**
**LOADER**

## SD T8110 LOADER BRACKETS

|  |  |        |   |  |  |            |
|--|--|--------|---|--|--|------------|
|  |  | 336740 | HD Non Self Leveling Ldr +SSQA<br><b>665TL Non Self Leveling with Skid Steer Style Attachment</b> |  |  | \$7,025.00 |
|  |  | 336742 | HD Non Self Leveling Ldr +Euro<br><b>665TL Non Self Leveling with Euro Style Attachment</b>       |  |  | \$7,025.00 |

**T5 DUAL COMMAND  
US PRICE LIST**

|  |  |        |  |  |  |            |
|--|--|--------|--|--|--|------------|
|  |  | 336744 | HD Self Leveling Ldr +SSQA<br><b>665TL Mechanical Self Leveling with Skid Steer Style Attachment</b> |  |  | \$8,138.00 |
|  |  | 336746 | HD Self Leveling Ldr +Euro<br><b>665TL Mechanical Self Leveling with Euro Style Attachment</b>       |  |  | \$8,138.00 |

## SD T8140 BUCKET

|  |  |        |            |  |  |          |
|--|--|--------|------------|--|--|----------|
|  |  | 336750 | 84" Bucket |  |  | \$942.00 |
|--|--|--------|------------|--|--|----------|

**HITCH**

## REAR 3 POINT HITCH

## SD T8130 3 POINT HITCH CONTROL

|  |  |        |                                |  |  |          |
|--|--|--------|--------------------------------|--|--|----------|
|  |  | 332035 | Mech 3 Pt Hitch Ground Control |  |  | \$261.00 |
|--|--|--------|--------------------------------|--|--|----------|

## SD T8200 HITCH

|  |  |        |   |  |  |            |
|--|--|--------|---|--|--|------------|
|  |  | 758931 | MDC HPL+LOM+2AUX<br><b>2 auxiliary lift rams for ROPS<br/>8,000 lbs lift capacity</b> |  |  | \$1,071.00 |
|  |  | 758932 | EDC HPL + 2 AUX<br><b>2 auxiliary lift rams for Cab<br/>8,000 lbs lift capacity</b>   |  |  | \$1,071.00 |

**CAB OR ROPS PLATFORM**

## OTHER

## SD T6730 PIN CONNECTOR

|  |  |        |   |  |  |         |
|--|--|--------|---|--|--|---------|
|  |  | 334994 | STD+30+HRN+ACS+MON<br><b>Monitor mounting bracket, 30Ah socket &amp; 2-12V power outlets<br/>Cab ONLY</b> |  |  | \$78.00 |
|--|--|--------|---|--|--|---------|

**WEIGHTS**

## FRONT

## SD T2150 FRONT BALLAST

|  |  |        |  |  |  |            |
|--|--|--------|--|--|--|------------|
|  |  | 333215 | Front Carrier +6 88 lb Weights<br><b>Total weight - 661 lbs (300 kg)</b> |  |  | \$819.00   |
|  |  | 335215 | 8 WEIGHTS 40 KG - CA<br><b>Total weight - 837 lbs (380 kg)</b>           |  |  | \$1,036.00 |

**T5 DUAL COMMAND  
US PRICE LIST**

**REAR**

SD T4961 REAR BALLAST

|  |  |        |   |  |  |          |
|--|--|--------|---|--|--|----------|
|  |  | 330470 | 4 x 110 lb Rear Wheel Weights<br><b>Total weight - 440 lbs (200 kg)</b><br><b>NOT compatible with 24" rear tires option</b> |  |  | \$639.00 |
|--|--|--------|---|--|--|----------|

**MISCELLANEOUS**

**FENDERS FRONT**

SD T8700 FENDERS

|  |  |        |                           |  |  |          |
|--|--|--------|---------------------------|--|--|----------|
|  |  | 744599 | Rear Fenders w/Extensions |  |  | \$166.00 |
|--|--|--------|---------------------------|--|--|----------|

**FENDERS REAR**

SD T8740 FRONT FENDERS

|  |  |        |                 |  |  |          |
|--|--|--------|-----------------|--|--|----------|
|  |  | 744674 | Dynamic Fenders |  |  | \$716.00 |
|--|--|--------|-----------------|--|--|----------|

**OPERATOR'S MANUALS**

SD T9840 COUNTRY CONFIGURATION

|  |  |        |   |  |  |           |
|--|--|--------|---|--|--|-----------|
|  |  | 334256 | Canada (FR) Config ROPS<br><b>French operator manual</b>    |  |  | No Charge |
|  |  | 334257 | USA Spanish Configuration<br><b>Spanish operator manual</b> |  |  | No Charge |



## T5 TIER 4B ELECTRO COMMAND SERIES US PRICE LIST

### Standard Equipment

KEY SELLING POINTS (some features are optional equipment):

- 16 x 16 Electro Command semi-powershift transmission now with optional Auto Shift feature
- Comfort Ride# cab suspension for a smoother ride - Optional
- Auto PTO manages PTO engagement in relation to the rear hitch position
- Engine Speed Management (constant engine RPM) - 2 settings
- Terralock# automatic traction system
- Terraglide# opt. front axle suspension
- Opt TerraGlide# class 1.5 HD front axle
- CommandArc# ergonomics
- Optional LED work lights
- 200 degree windshield wiper
- Standard high visibility panel (opening)
- (10) repositionable AC/heater vents
- Full-size instructor seat
- Electrohydraulic armrest-mntd joystick
- Hydraulic shuttle lever -finger control
- 3.4L, 4-cylinder, F5G engines with 4 valves per cylinder common rail fuel injection systems
- 8,084 lb. 3-point lift capacity
- Tier 4B/final emissions compliant ECOBlue Compact HI-eSCR (Selective Catalytic Reduction) after-treatment with low rate Cooled Exhaust Gas Recirculation (CEGR); no diesel particulate filter, no regeneration req.

#### MODELS:

T5.110  
107 gross engine HP  
93 PTO HP @ 2300 rpm  
4-cyl. turbocharged and intercooled  
207 cu. in. (3.4 L) displacement  
4 valves per cylinder

#### T5.120

117 gross engine HP  
100 PTO HP @ 2300 rpm  
4-cyl. turbocharged and intercooled

207 cu. in. (3.4 L) displacement  
4 Valves per cylinder

#### KEY COMMON FEATURES & OPTIONS:

- 16X16 Electro Command transmission with optional Auto Shift feature
- Optional Suspended cab w/HiVis panel
- Heavy-duty class 1.5 front axle with optional hydraulic differential lock
- Opt. premium air suspension seat with armrests, backrest, and heated cushion
- Full-size, deluxe radio with Bluetooth#
- Telescopic rearview mirror option
- (3) closed center rear remotes option
- Electrohydraulic mid-mount valve and armrest-mounted elec. joystick option
- Auto PTO option
- Engine block heater option

#### ENGINE:

- Tier 4B emissions: Compact HI-eSCR SCR with low rate CEGR
- Electronic injection Bosch high-pressure common rail system
- Engine Speed Management
- Electric engine shutoff
- Grid heater starting Aid
- Dual element air filter
- Vertical exhaust
- 43.6 gallon (165 L) fuel tank with guard
- 3.2 gallon (12 L) DEF (diesel exhaust fluid) tank

#### TRANSMISSION:

- 16 x 16 semi-powershift
- 8 push button powershift speeds
- Control buttons on gear shift lever and on CommandArc#
- Electrohydraulic shuttle
- 25-mph (40-kph) road speed
- 16th gear (32nd w/creeper) is an economy gear that operates the engine at a lower RPM to save fuel
- Multi-disk cerametallic clutch

**T5 TIER 4B ELECTRO COMMAND SERIES  
US PRICE LIST**

## Standard Equipment

### STEERING/BRAKES:

- Hydrostatic power steering
- Hydraulic wet brakes (equalizing and self-adjusting)
- Park brake

### FRONT AXLE:

- Class 1.5 w/Auto 4WD management
- Limited slip differential
- Opt. electrohydraulic FWD engagement
- Opt. suspended front axle

### -REAR AXLE:

- Heavy-duty flange
- Dog clutch differential lock
- Auto differential lock management
- Electrohydraulic rear differential lock

### HYDRAULIC SYSTEM:

- Fixed displacement pumps
- Tandem gear pumps
- Maximum flow at rated engine speed:
  - Implement pump: 21.1 gpm (80 l/m)
  - Steering pump: 11.4 gpm (43 l/m)
- (2) closed center rear remote valves configurable detent w/ quick release couplers

### PTO:

- Fully independent
- Flip-up PTO shaft guard
- 540/1000 rpm interchangeable shaft
- Electrohydraulic engagement
- Multi-plate clutch
- Fender-mounted EDC / PTO switches

### 3-POINT LIFT SYSTEM:

- Right hand console-mounted mouse
- Electronic Draft Control (EDC)
- Fast raise/lower control
- 8,084 lb. lift cap (OECD, 90% psi at 24" rear of lower link balls)
- Category II flexible lower link ends
- Telescopic stabilizers

### INSTRUMENTATION:

- Analog/digital instrument panel with:
  - Integrated warning lights
  - Analog fuel, temp., and temp. gauges
  - Digital hour meter, direction display, ground speed, and PTO speed

### ELECTRICAL:

- (1) 12-volt, 800 CCA battery
- 120-amp alternator
- 7-pin outlet for implement lighting
- 3-pin connector (TYCO CPC)
- Single pin (8-amp) power outlet
- Detusch diagnostic port

### LIGHTING:

- (2) Halogen front hood headlights
- (2) Front and (2) rear cab work lights
- Turn signals, flashers, and brake lights

### OPERATOR'S STATION:

- Flat deck platform and integral ROPS
- Heater and air conditioner
- "A" pillar exhaust
- (2) tinted doors with locks
- Partially opening tinted side windows
- Hinged tinted rear window
- Rear cab access plug for imp. wires
- Front and rear wipers and washers
- Tilt and telescoping steering wheel
- Fixed external mirrors
- Radio and speakers
- Deluxe air suspension seat with operator's presence and seat belt
- Instructor's seat with seat belt
- HiVis panel (overhead window-opens)

### MISCELLANEOUS:

- One-piece hood with gas strut
- Swinging drawbar
- SMV emblem
- Toolbox

### WARRANTY:

New Holland standard warranty applies

**T5 TIER 4B ELECTRO COMMAND SERIES  
US PRICE LIST**

## Models

| COMMERCIAL MODEL                     | Weight     | Factory Data | List Price  |
|--------------------------------------|------------|--------------|-------------|
| T5.110 ELEC COM T4B                  | 8,157 LB   |              | \$97,312.00 |
| Includes the following Equipment     |            |              |             |
| 14.9R24 A8 HD Rim (8242301)          | \$2,161.00 |              |             |
| 460/85(18.4)R34 A8 FI,MI,C (8365401) | \$3,834.00 |              |             |
| T5.120 ELEC COM T4B                  | 8,157 LB   |              | \$99,361.00 |
| Includes the following Equipment     |            |              |             |
| 14.9R24 A8 HD Rim (8242301)          | \$2,161.00 |              |             |
| 460/85(18.4)R34 A8 FI,MI,C (8365401) | \$3,834.00 |              |             |

## Factory Supplied Options

| Order Code | Description | Weight | Factory Data | List Price |
|------------|-------------|--------|--------------|------------|
|------------|-------------|--------|--------------|------------|

### TIRES

#### BRAND CHOICE

#### SD\_T4900 TIRE CATEGORY CHOICE

|  |        |                          |  |  |            |
|--|--------|--------------------------|--|--|------------|
|  | 330438 | No tire brand preference |  |  | No Charge  |
|  | 330447 | Alliance                 |  |  | \$444.00   |
|  | 330439 | Continental              |  |  | \$444.00   |
|  | 330418 | Trelleborg               |  |  | \$444.00   |
|  | 330444 | Nokian                   |  |  | \$777.00   |
|  | 330442 | Michelin                 |  |  | \$1,108.00 |

#### FRONT

#### SD\_T4940 FRONT WHEELS AND TIRES

##### Ag Front Tires

|  |         |  |  |  |            |
|--|---------|--|--|--|------------|
|  | 8235401 | 12.4R24 A8<br><b>R1W, Adjustable Rim,<br/>Match w/ 8357401 rear tire/wheel</b>         |  |  | \$1,435.00 |
|  | 8242301 | 14.9R24 A8 HD Rim<br><b>R1W, adjustable rim<br/>Match with 8365401 rear tire/wheel</b> |  |  | \$2,161.00 |
|  | 8838501 | 13.6-R28 6PR<br><b>Match with 8376701 rear tire/wheel<br/>R1W, adjustable rim</b>      |  |  | \$2,840.00 |

**T5 TIER 4B ELECTRO COMMAND SERIES  
 US PRICE LIST**
**REAR**
**SD T4950 REAR WHEELS AND TIRES**
**Ag Rear Tires**

|  |  |         |  |  |  |            |
|--|--|---------|--|--|--|------------|
|  |  | 8357401 | 18.4R30 R1W<br><b>Matching front tire/whl is 8235401, 12.4R24 (320/85R24)</b><br><b>R1W, adjustable rim</b><br><b>Not compatible with narrow rear fenders</b><br><b>option code: 331870</b>                    |  |  | \$3,480.00 |
|  |  | 8365401 | 460/85(18.4)R34 A8 FI,MI,CO,TR<br><b>Matching front tire/whl is 8242301, 14.9R24 (380/85R24)</b><br><b>R1W, adjustable rim</b><br><b>Not compatible with narrow rear fenders</b><br><b>option code: 331870</b> |  |  | \$3,834.00 |
|  |  | 8376701 | 16.9R38 R1W<br><b>Matching front tire is 8838501, 13.6R28 (340/85R28)</b><br><b>R1W, adjustable rim</b><br><b>Not compatible with narrow rear fenders</b><br><b>option code: 331870</b>                        |  |  | \$2,824.00 |

**HYDRAULICS**
**REAR REMOTES**
**SD T8270 REAR REMOTES**

|  |  |        |   |  |  |            |
|--|--|--------|---|--|--|------------|
|  |  | 330849 | 2 MRRV (2C) Fixed Pump,EDC<br><b>2 closed center mechanical hydraulic remote valves both with configurable detent</b>                             |  |  | No Charge  |
|  |  | 331844 | 3 MRRV (1NC+2C)Fixed Pump,EDC<br><b>3 mechanical rear hydraulic remote valves, 2 with configurable detents and 1 with non-configurable detent</b> |  |  | \$1,496.00 |

**ENGINE**
**AIR INTAKE**
**SD T1910 AIR CLEANER**

|  |  |        |  |  |  |           |
|--|--|--------|--|--|--|-----------|
|  |  | 330200 | Air Filter w/Dust Ejector<br><b>Engine air cleaner with dust ejector</b>         |  |  | \$121.00  |
|  |  | 390200 | Air Cleaner w/ Pre-Cleaner<br><b>Standare engine air cleaner with precleaner</b> |  |  | No Charge |

**T5 TIER 4B ELECTRO COMMAND SERIES  
US PRICE LIST**

**CAB OR ROPS PLATFORM**

OTHER

SD T9360 RR MIRRORS

|  |  |        |  |  |  |           |
|--|--|--------|--|--|--|-----------|
|  |  | 392428 | 2 Fixed Wide Angle Mirrors   |  |  | No Charge |
|  |  | 341852 | 2 External Wide Angle Mirrors  |  |  | \$401.00  |
|  |  |        | <b>2 Telescopic Rear Wide Angle Mirrors With Mechanical Adjustment</b> |  |  |           |

**LIGHTS**

ROTARY BEACON

SD T9146 ROTARY BEACON

|  |  |        |   |  |  |          |
|--|--|--------|---|--|--|----------|
|  |  | 759160 | ROTARY BEACON 759160                      |  |  | \$111.00 |
|  |  | 335916 | 2 Beacons RH and LH Side                  |  |  | \$220.00 |
|  |  |        | <b>Left and right side safety beacons</b> |  |  |          |

**WEIGHTS**

FRONT

SD T2150 FRONT BALLAST

|  |  |        |   |  |  |            |
|--|--|--------|---|--|--|------------|
|  |  | 331759 | 10 Weights<br><b>Qty. 10, 88 lb. (40 Kg) weights<br/>totaling 882 lb. (400 Kg)<br/>Requires a front axle support with weight carrier (335156 or<br/>758385)</b> |  |  | \$1,164.00 |
|--|--|--------|---|--|--|------------|

REAR

SD T4961 REAR BALLAST

|  |  |        |   |  |  |          |
|--|--|--------|---|--|--|----------|
|  |  | 330471 | 6 Rear Wheel Weights<br><b>6, 110 lb. (50 kg.) rear disc weights<br/>totaling 661 lb. (300Kg)</b> |  |  | \$975.00 |
|--|--|--------|---|--|--|----------|

**MANUALS**

OPERATORS

SD T9840 COUNTRY CONFIGURATION

|  |  |        |  |  |  |           |
|--|--|--------|--|--|--|-----------|
|  |  | 335148 | USA Spanish Config<br><b>Spanish Operator Manual</b> |  |  | No Charge |
|  |  | 335151 | Canada (FR) Config<br><b>French Operator Manual</b>  |  |  | No Charge |



**T5 TIER 4B ELECTRO COMMAND SERIES  
US PRICE LIST**

**MISCELLANEOUS**

**FENDERS FRONT**

**SD T8740 FRONT FENDERS**

|  |  |        |  |  |  |          |
|--|--|--------|--|--|--|----------|
|  |  | 758330 | Dynamic Front Fenders 480mm<br><b>18.9 inch (480 mm) dynamic front fenders</b> |  |  | \$743.00 |
|--|--|--------|--|--|--|----------|

**FENDERS REAR**

**SD T8700 FENDERS**

|  |  |        |   |  |  |           |
|--|--|--------|---|--|--|-----------|
|  |  | 331870 | Narrow Rear Fenders 331870<br><b>Not compatible with front fender options</b><br><b>Requires 8201801 9.5R28 front tires/wheels and</b><br><b>8369501 12.4R38 rear tire/wheels</b> |  |  | No Charge |
|--|--|--------|---|--|--|-----------|

**REVERSE ALARM**

**SD T9249 REVERSE ALARM**

|  |  |        |                            |  |  |          |
|--|--|--------|----------------------------|--|--|----------|
|  |  | 332692 | Reverse Alarm w/Work Light |  |  | \$245.00 |
|--|--|--------|----------------------------|--|--|----------|

## T5 ELECTRO COMMAND - STANDARD FASTPICK US PRICE LIST

### Standard Equipment

KEY SELLING POINTS (some features are optional equipment):

- 16 x 16 Electro Command semi-powershift transmission
- Auto PTO manages PTO engagement in relation to the rear hitch position
- Engine Speed Management (constant engine RPM) - 2 settings
- Terralock# automatic traction system
- CommandArc# ergonomics
- 200 degree windshield wiper
- Standard high visibility panel (opening)
- (10) repositionable AC/heater vents
- Full-size instructor seat
- Hydraulic shuttle lever -finger control
- 3.4L, 4-cylinder, F5G engines with 4 valves per cylinder common rail fuel injection systems
- 8,084 lb. 3-point lift capacity
- Tier 4B/final emissions compliant ECOBlue Compact HI-eSCR (Selective Catalytic Reduction) after-treatment with low rate Cooled Exhaust Gas Recirculation (CEGR); no diesel particulate filter, no regeneration req.

#### MODELS:

T5.110

107 gross engine HP  
93 PTO HP @ 2300 rpm  
4-cyl. turbocharged and intercooled  
207 cu. in. (3.4 L) displacement  
4 valves per cylinder

T5.120

117 gross engine HP  
100 PTO HP @ 2300 rpm  
4-cyl. turbocharged and intercooled  
207 cu. in. (3.4 L) displacement  
4 Valves per cylinder

#### ENGINE:

- Tier 4B emissions: Compact HI-eSCR SCR with low rate CEGR
- Electronic injection Bosch high-pressure common rail system
- Engine Speed Management
- Electric engine shutoff
- Grid heater starting Aid
- Engine block heater
- Dual element air filter
- Vertical exhaust
- 43.6 gallon (165 L) fuel tank with guard
- 3.2 gallon (12 L) DEF (diesel exhaust fluid) tank

#### TRANSMISSION:

- 16 x 16 semi-powershift
- 8 push button powershift speeds
- Control buttons on gear shift lever and on CommandArc#
- Electrohydraulic shuttle
- 25-mph (40-kph) road speed
- 16th gear (32nd w/creeper) is an economy gear that operates the engine at a lower RPM to save fuel
- Multi-disk cerametallic clutch
- Transmission heater

#### STEERING/BRAKES:

- Hydrostatic power steering
- Hydraulic wet brakes (equalizing and self-adjusting)
- Park brake

#### FRONT AXLE:

- Class 1.5 w/Auto 4WD management
- Electrohydraulic FWD engagement

#### -REAR AXLE:

- Heavy-duty flange
- Dog clutch differential lock
- Auto differential lock management
- Electrohydraulic rear differential lock

**T5 ELECTRO COMMAND - STANDARD FASTPICK  
US PRICE LIST**

## Standard Equipment

### HYDRAULIC SYSTEM:

- Fixed displacement pumps
- Tandem gear pumps
- Maximum flow at rated engine speed:
  - Implement pump: 21.1 gpm (80 l/m)
  - Steering pump: 11.4 gpm (43 l/m)
- (2) closed center rear remote valves configurable detent w/ quick release couplers
- 2 function mechanical mid mount valve and joystick
- Complete loader ready

### PTO:

- Fully independent
- Flip-up PTO shaft guard
- 540/1000 rpm interchangeable shaft
- Electrohydraulic engagement
- Multi-plate clutch
- Fender-mounted EDC / PTO switches

### 3-POINT LIFT SYSTEM:

- Right hand console-mounted mouse
- Electronic Draft Control (EDC)
- Fast raise/lower control
- 8,084 lb. lift cap (OECD, 90% psi at 24" rear of lower link balls)
- Category II flexible lower link ends
- Telescopic stabilizers

### INSTRUMENTATION:

- Analog/digital instrument panel with:
  - Integrated warning lights
  - Analog fuel, temp., and temp. gauges
  - Digital hour meter, direction display, ground speed, and PTO speed

### ELECTRICAL:

- (1) 12-volt, 800 CCA battery
- 120-amp alternator
- 7-pin outlet for implement lighting
- 3-pin connector (TYCO CPC)
- Single pin (8-amp) power outlet
- Detusch diagnostic port

### LIGHTING:

- (2) Halogen front hood headlights
- (2) Front and (2) rear cab work lights
- Turn signals, flashers, and brake lights

### OPERATOR'S STATION:

- Flat deck platform and integral ROPS
- Heater and air conditioner
- "A" pillar exhaust
- (2) tinted doors with locks
- Partially opening tinted side windows
- Hinged tinted rear window
- Rear cab access plug for imp. wires
- Front and rear wipers and washers
- Tilt and telescoping steering wheel
- Fixed external mirrors
- Radio and speakers
- Deluxe air suspension seat with operator's presence and seat belt
- Instructor's seat with seat belt
- HiVis panel (overhead window-opens)

### MISCELLANEOUS:

- One-piece hood with gas strut
- Swinging drawbar
- SMV emblem
- Toolbox
- 6 rear wheel weights

### WARRANTY:

New Holland standard warranty applies



**T5 ELECTRO COMMAND - STANDARD FASTPICK  
US PRICE LIST**

## Models

| COMMERCIAL MODEL                     | Weight     | Factory Data | List Price  |
|--------------------------------------|------------|--------------|-------------|
| T5.110 ELEC COM T4B                  | 8,157 LB   |              | \$97,312.00 |
| Includes the following Equipment     |            |              |             |
| 14.9R24 A8 HD Rim (8242301)          | \$2,161.00 |              |             |
| 460/85(18.4)R34 A8 FI,MI,C (8365401) | \$3,834.00 |              |             |
| T5.120 ELEC COM T4B                  | 8,157 LB   |              | \$99,361.00 |
| Includes the following Equipment     |            |              |             |
| 14.9R24 A8 HD Rim (8242301)          | \$2,161.00 |              |             |
| 460/85(18.4)R34 A8 FI,MI,C (8365401) | \$3,834.00 |              |             |

## Factory Supplied Options

| Order Code | Description | Weight | Factory Data | List Price |
|------------|-------------|--------|--------------|------------|
|------------|-------------|--------|--------------|------------|

### FAST PICK CONFIGURATION

#### SD\_T9980 PACKAGING

|   |                  |  |  |            |
|---|------------------|--|--|------------|
| X0474XX   | NAR NH PCK C STD |  |  | \$7,108.00 |
| <b>Standard Fastpick Package includes:</b><br><b>330849 2 Mechanical Rear Remotes</b><br><b>392428 2 Fixed Wide Angle Mirrors</b><br><b>390430 16 x 16 SPS 40 KPH</b><br><b>758820 2 Slice Mech CC MMV</b><br><b>332850 Deluxe Fabric Seat w/Air Suspension</b><br><b>339434 Deluxe Cab with HiVis Panel and A/C</b><br><b>330308 HD MFD Axle w/ Hydraulic Diff Lock</b><br><b>758980 Complete Loader Ready</b><br><b>744982 Engine Block and Transmission Heaters</b><br><b>330471 6 Rear Wheel Weights</b><br><b>8242301 14.9R24 R1W Front Tires</b><br><b>8365401 18.4R34 R1W Rear Tires</b> |                  |  |  |            |

### PTO

#### REAR PTO

#### SD\_T8010 PTO

|        |                   |  |  |          |
|--------|-------------------|--|--|----------|
| 331729 | 540/540E/1000 RPM |  |  | \$798.00 |
|--------|-------------------|--|--|----------|

**T5 ELECTRO COMMAND - STANDARD FASTPICK  
US PRICE LIST**

**CAB OR ROPS PLATFORM**

MONITOR MOUNTING

SD T7612 BRACKET MONITOR

|  |  |        |                          |  |  |          |
|--|--|--------|--------------------------|--|--|----------|
|  |  | 338761 | Monitor Mounting Bracket |  |  | \$139.00 |
|--|--|--------|--------------------------|--|--|----------|

**ELECTRICAL/CONNECTORS**

BATTERY

SD T7420 BATTERY

|  |  |        |   |  |  |          |
|--|--|--------|---|--|--|----------|
|  |  | 334774 | Batt. 140 AH W/B.IS.<br><b>Battery Isolator</b> |  |  | \$388.00 |
|--|--|--------|---|--|--|----------|

**LIGHTS**

ROTARY BEACON

SD T9146 ROTARY BEACON

|  |  |        |   |  |  |          |
|--|--|--------|---|--|--|----------|
|  |  | 759160 | ROTARY BEACON 759160  |  |  | \$111.00 |
|  |  | 335916 | 2 Beacons RH and LH Side<br><b>Left and right side safety beacons</b> |  |  | \$220.00 |

**MANUALS**

OPERATORS

SD T9840 COUNTRY CONFIGURATION

|  |  |        |  |  |  |           |
|--|--|--------|--|--|--|-----------|
|  |  | 335148 | USA Spanish Config<br><b>Spanish Operator Manual</b> |  |  | No Charge |
|  |  | 335151 | Canada (FR) Config<br><b>French Operator Manual</b>  |  |  | No Charge |

**MISCELLANEOUS**

FENDERS FRONT

SD T8740 FRONT FENDERS

|  |  |        |  |  |  |          |
|--|--|--------|--|--|--|----------|
|  |  | 758330 | Dynamic Front Fenders 480mm<br><b>18.9 inch (480 mm) dynamic front fenders</b> |  |  | \$743.00 |
|--|--|--------|--|--|--|----------|

**T5 ELECTRO COMMAND - DELUXE FASTPICK  
US PRICE LIST**

## Standard Equipment

KEY SELLING POINTS (some features are optional equipment):

- 16 x 16 Electro Command semi-powershift transmission with Auto Shift feature
- Auto PTO manages PTO engagement in relation to the rear hitch position
- Engine Speed Management (constant engine RPM) - 2 settings
- Terralock# automatic traction system
- CommandArc# ergonomics
- 200 degree windshield wiper
- Standard high visibility panel (opening)
- (10) repositionable AC/heater vents
- Full-size instructor seat
- Hydraulic shuttle lever -finger control
- 3.4L, 4-cylinder, F5G engines with 4 valves per cylinder common rail fuel injection systems
- 8,084 lb. 3-point lift capacity
- Tier 4B/final emissions compliant ECOBlue Compact HI-eSCR (Selective Catalytic Reduction) after-treatment with low rate Cooled Exhaust Gas Recirculation (CEGR); no diesel particulate filter, no regeneration req.

**MODELS:**

T5.110

- 107 gross engine HP
- 93 PTO HP @ 2300 rpm
- 4-cyl. turbocharged and intercooled
- 207 cu. in. (3.4 L) displacement
- 4 valves per cylinder

T5.120

- 117 gross engine HP
- 100 PTO HP @ 2300 rpm
- 4-cyl. turbocharged and intercooled
- 207 cu. in. (3.4 L) displacement
- 4 Valves per cylinder

**ENGINE:**

- Tier 4B emissions: Compact HI-eSCR SCR with low rate CEGR
- Electronic injection Bosch high-pressure common rail system
- Engine Speed Management
- Electric engine shutoff
- Grid heater starting Aid
- Engine block heater
- Dual element air filter
- Vertical exhaust
- 43.6 gallon (165 L) fuel tank with guard
- 3.2 gallon (12 L) DEF (diesel exhaust fluid) tank

**TRANSMISSION:**

- 16 x 16 semi-powershift with Auto Shift
- 8 push button powershift speeds
- Control buttons on gear shift lever and on CommandArc#
- Electrohydraulic shuttle
- 25-mph (40-kph) road speed
- 16th gear (32nd w/creeper) is an economy gear that operates the engine at a lower RPM to save fuel
- Multi-disk cerametallic clutch
- Transmission heater

**STEERING/BRAKES:**

- Hydrostatic power steering
- Hydraulic wet brakes (equalizing and self-adjusting)
- Park brake

**FRONT AXLE:**

- Class 1.5 w/Auto 4WD management
- Electrohydraulic FWD and differential lock engagement

**-REAR AXLE:**

- Heavy-duty flange
- Dog clutch differential lock
- Auto differential lock management
- Electrohydraulic rear differential lock

**T5 ELECTRO COMMAND - DELUXE FASTPICK  
US PRICE LIST**

## Standard Equipment

### HYDRAULIC SYSTEM:

- Fixed displacement pumps
- Tandem gear pumps
- Maximum flow at rated engine speed:
  - Implement pump: 21.1 gpm (80 l/m)
  - Steering pump: 11.4 gpm (43 l/m)
- (3) closed center rear remote valves configurable detent w/ quick release couplers
- 2 function mid mount valve with electronic arm-rest mounted joystick
- Complete loader ready

### PTO:

- Fully independent
- Flip-up PTO shaft guard
- 540/1000 rpm interchangeable shaft
- Electrohydraulic engagement
- Multi-plate clutch
- Fender-mounted EDC / PTO switches

### 3-POINT LIFT SYSTEM:

- Right hand console-mounted mouse
- Electronic Draft Control (EDC)
- Fast raise/lower control
- 8,084 lb. lift cap (OECD, 90% psi at 24" rear of lower link balls)
- Category II flexible lower link ends
- Telescopic stabilizers

### INSTRUMENTATION:

- Analog/digital instrument panel with:
  - Integrated warning lights
  - Analog fuel, temp., and temp. gauges
  - Digital hour meter, direction display, ground speed, and PTO speed

### ELECTRICAL:

- (1) 12-volt, 800 CCA battery
- 120-amp alternator
- 7-pin outlet for implement lighting
- 3-pin connector (TYCO CPC)
- Single pin (8-amp) power outlet
- Detusch diagnostic port

### LIGHTING:

- (2) Halogen front hood headlights
- (2) Front and (2) rear cab work lights
- Turn signals, flashers, and brake lights

### OPERATOR'S STATION:

- Flat deck platform and integral ROPS
- Cab suspension
- Heater and air conditioner
- "A" pillar exhaust
- (2) tinted doors with locks
- Partially opening tinted side windows
- Hinged tinted rear window
- Rear cab access plug for imp. wires
- Front and rear wipers and washers
- Tilt and telescoping steering wheel
- Telescopic external mirrors
- Monitor mounting bracket
- Radio and speakers
- Premium air suspension seat with operator's presence and seat belt
- Instructor's seat with seat belt
- HiVis panel (overhead window-opens)

### MISCELLANEOUS:

- One-piece hood with gas strut
- Swinging drawbar
- SMV emblem
- Toolbox
- 6 rear wheel weights

### WARRANTY:

New Holland standard warranty applies

**T5 ELECTRO COMMAND - DELUXE FASTPICK  
US PRICE LIST**

## Models

| COMMERCIAL MODEL                     | Weight     | Factory Data | List Price  |
|--------------------------------------|------------|--------------|-------------|
| T5.110 ELEC COM T4B                  | 8,157 LB   |              | \$97,312.00 |
| Includes the following Equipment     |            |              |             |
| 14.9R24 A8 HD Rim (8242301)          | \$2,161.00 |              |             |
| 460/85(18.4)R34 A8 FI,MI,C (8365401) | \$3,834.00 |              |             |
| T5.120 ELEC COM T4B                  | 8,157 LB   |              | \$99,361.00 |
| Includes the following Equipment     |            |              |             |
| 14.9R24 A8 HD Rim (8242301)          | \$2,161.00 |              |             |
| 460/85(18.4)R34 A8 FI,MI,C (8365401) | \$3,834.00 |              |             |

## Factory Supplied Options

| Order Code | Description | Weight | Factory Data | List Price |
|------------|-------------|--------|--------------|------------|
|------------|-------------|--------|--------------|------------|

### FAST PICK CONFIGURATION

#### SD\_T9980 PACKAGING

|         |  |  |  |             |
|---------|--|--|--|-------------|
| X0473XX | NAR NH PCK B DELUXE<br><b>Deluxe Fastpick Package Includes:</b><br>331844 3 Mechanical Rear Remotes<br>341852 2 External Telescopic Wide Angle Mirrors<br>330471 6 Rear Wheel Weights<br>744982 Engine Block and Transmission Heaters<br>334775 40 KPH W/Autofunction<br>330308 HD MFD Axle w/ Hydraulic Diff Lock<br>338761 Monitor Mounting Bracket<br>758980 Complete Loader Ready<br>758821 2 MMV CC w/EH Joystick<br>758312 Premium Air Seat<br>336730 Cab Suspension with HiVis panel & A/C<br>8242301 14.9R24 R1W Front Tires<br>8365401 18.4R34 R1W Rear Tires |  |  | \$11,864.00 |
|---------|--|--|--|-------------|

### PTO

#### REAR PTO

#### SD\_T8010 PTO

|        |                   |  |  |          |
|--------|-------------------|--|--|----------|
| 331729 | 540/540E/1000 RPM |  |  | \$798.00 |
|--------|-------------------|--|--|----------|

**T5 ELECTRO COMMAND - DELUXE FASTPICK  
 US PRICE LIST**
**ELECTRICAL/CONNECTORS**
**BATTERY**

## SD\_T7420 BATTERY

|  |  |        |   |  |  |          |
|--|--|--------|---|--|--|----------|
|  |  | 334774 | Batt. 140 AH W/B.IS.<br><b>Battery Isolator</b> |  |  | \$388.00 |
|--|--|--------|---|--|--|----------|

**LIGHTS**
**ROTARY BEACON**

## SD\_T9146 ROTARY BEACON

|  |  |        |   |  |  |          |
|--|--|--------|---|--|--|----------|
|  |  | 759160 | ROTARY BEACON 759160  |  |  | \$111.00 |
|  |  | 335916 | 2 Beacons RH and LH Side<br><b>Left and right side safety beacons</b> |  |  | \$220.00 |

**MANUALS**
**OPERATORS**

## SD\_T9840 COUNTRY CONFIGURATION

|  |  |        |  |  |  |           |
|--|--|--------|--|--|--|-----------|
|  |  | 335148 | USA Spanish Config<br><b>Spanish Operator Manual</b> |  |  | No Charge |
|  |  | 335151 | Canada (FR) Config<br><b>French Operator Manual</b>  |  |  | No Charge |

**MISCELLANEOUS**
**FENDERS FRONT**

## SD\_T8740 FRONT FENDERS

|  |  |        |  |  |  |          |
|--|--|--------|--|--|--|----------|
|  |  | 758330 | Dynamic Front Fenders 480mm<br><b>18.9 inch (480 mm) dynamic front fenders</b> |  |  | \$743.00 |
|--|--|--------|--|--|--|----------|

## T5 ELECTRO COMMAND - LESS FASTPICK US PRICE LIST

### Standard Equipment

KEY SELLING POINTS (some features are optional equipment):

- 16 x 16 Electro Command semi-powershift transmission now with optional Auto Shift feature
- Comfort Ride# cab suspension for a smoother ride - Optional
- Auto PTO manages PTO engagement in relation to the rear hitch position
- Engine Speed Management (constant engine RPM) - 2 settings
- Terralock# automatic traction system
- Terraglide# opt. front axle suspension
- Opt TerraGlide# class 1.5 HD front axle
- CommandArc# ergonomics
- Optional LED work lights
- 200 degree windshield wiper
- Standard high visibility panel (opening)
- (10) repositionable AC/heater vents
- Full-size instructor seat
- Electrohydraulic armrest-mntd joystick
- Hydraulic shuttle lever -finger control
- 8,084 lb. 3-point lift capacity
- Tier 4B/final emissions compliant ECOBlue Compact HI-eSCR (Selective Catalytic Reduction) after-treatment with low rate Cooled Exhaust Gas Recirculation (CEGR); no diesel particulate filter, no regeneration req.

#### MODELS:

T5.110  
107 gross engine HP  
93 PTO HP @ 2300 rpm  
4-cyl. turbocharged and intercooled  
207 cu. in. (3.4 L) displacement  
4 valves per cylinder

T5.120  
117 gross engine HP  
100 PTO HP @ 2300 rpm  
4-cyl. turbocharged and intercooled  
207 cu. in. (3.4 L) displacement  
4 Valves per cylinder

#### KEY COMMON FEATURES & OPTIONS:

- 16X16 Electro Command transmission with optional Auto Shift feature
- Optional Suspended cab w/HiVis panel
- Heavy-duty class 1.5 front axle with optional hydraulic differential lock
- Opt. premium air suspension seat with armrests, backrest, and heated cushion
- Full-size, deluxe radio with Bluetooth#
- Telescopic rearview mirror option
- (3) closed center rear remotes option
- Electrohydraulic mid-mount valve and armrest-mounted elec. joystick option
- Auto PTO option
- Engine block heater option

#### ENGINE:

- Tier 4B emissions: Compact HI-eSCR SCR with low rate CEGR
- Electronic injection Bosch high-pressure common rail system
- Engine Speed Management
- Electric engine shutoff
- Grid heater starting Aid
- Dual element air filter
- Vertical exhaust
- 43.6 gallon (165 L) fuel tank with guard
- 3.2 gallon (12 L) DEF (diesel exhaust fluid) tank

#### TRANSMISSION:

- 16 x 16 semi-powershift
- 8 push button powershift speeds
- Control buttons on gear shift lever and on CommandArc#
- Electrohydraulic shuttle
- 25-mph (40-kph) road speed
- 16th gear (32nd w/creeper) is an economy gear that operates the engine at a lower RPM to save fuel
- Multi-disk cerametallic clutch

## T5 ELECTRO COMMAND - LESS FASTPICK US PRICE LIST

### Standard Equipment

#### STEERING/BRAKES:

- Hydrostatic power steering
- Hydraulic wet brakes (equalizing and self-adjusting)
- Park brake

#### FRONT AXLE:

- Class 1.5 w/Auto 4WD management
- Limited slip differential
- Opt. electrohydraulic FWD engagement
- Opt. suspended front axle

#### -REAR AXLE:

- Heavy-duty flange
- Dog clutch differential lock
- Auto differential lock management
- Electrohydraulic rear differential lock

#### HYDRAULIC SYSTEM:

- Fixed displacement pumps
- Tandem gear pumps
- Maximum flow at rated engine speed:
  - Implement pump: 21.1 gpm (80 l/m)
  - Steering pump: 11.4 gpm (43 l/m)
- (2) closed center rear remote valves configurable detent w/ quick release couplers

#### PTO:

- Fully independent
- Flip-up PTO shaft guard
- 540/1000 rpm interchangeable shaft
- Electrohydraulic engagement
- Multi-plate clutch
- Fender-mounted EDC / PTO switches

#### 3-POINT LIFT SYSTEM:

- Right hand console-mounted mouse
- Electronic Draft Control (EDC)
- Fast raise/lower control
- 8,084 lb. lift cap (OECD, 90% psi at 24" rear of lower link balls)
- Category II flexible lower link ends
- Telescopic stabilizers

#### INSTRUMENTATION:

- Analog/digital instrument panel with:
  - Integrated warning lights
  - Analog fuel, temp., and temp. gauges
  - Digital hour meter, direction display, ground speed, and PTO speed

#### ELECTRICAL:

- (1) 12-volt, 800 CCA battery
- 120-amp alternator
- 7-pin outlet for implement lighting
- 3-pin connector (TYCO CPC)
- Single pin (8-amp) power outlet
- Detusch diagnostic port

#### LIGHTING:

- (2) Halogen front hood headlights
- (2) Front and (2) rear cab work lights
- Turn signals, flashers, and brake lights

#### OPERATOR'S STATION:

- Flat deck platform and integral ROPS
- Heater and air conditioner
- "A" pillar exhaust
- (2) tinted doors with locks
- Partially opening tinted side windows
- Hinged tinted rear window
- Rear cab access plug for imp. wires
- Front and rear wipers and washers
- Tilt and telescoping steering wheel
- Fixed external mirrors
- Radio and speakers
- Deluxe air suspension seat with operator's presence and seat belt
- Instructor's seat with seat belt
- HiVis panel (overhead window-opens)

#### MISCELLANEOUS:

- One-piece hood with gas strut
- Swinging drawbar
- SMV emblem
- Toolbox

#### WARRANTY:

New Holland standard warranty applies



**T5 ELECTRO COMMAND - LESS FASTPICK  
US PRICE LIST**

## Models

| COMMERCIAL MODEL                     | Weight     | Factory Data | List Price  |
|--------------------------------------|------------|--------------|-------------|
| T5.110 ELEC COM T4B                  | 8,157 LB   |              | \$97,312.00 |
| Includes the following Equipment     |            |              |             |
| 14.9R24 A8 HD Rim (8242301)          | \$2,161.00 |              |             |
| 460/85(18.4)R34 A8 FI,MI,C (8365401) | \$3,834.00 |              |             |
| T5.120 ELEC COM T4B                  | 8,157 LB   |              | \$99,361.00 |
| Includes the following Equipment     |            |              |             |
| 14.9R24 A8 HD Rim (8242301)          | \$2,161.00 |              |             |
| 460/85(18.4)R34 A8 FI,MI,C (8365401) | \$3,834.00 |              |             |

## Factory Supplied Options

| Order Code | Description | Weight | Factory Data | List Price |
|------------|-------------|--------|--------------|------------|
|------------|-------------|--------|--------------|------------|

### FAST PICK CONFIGURATION

#### SD\_T9980 PACKAGING

|  |         |                |  |           |
|--|---------|----------------|--|-----------|
|  | X0475XX | LESS PACKAGING |  | No Charge |
|--|---------|----------------|--|-----------|

### OPERATOR PLATFORM

#### SD\_T9200 OPERATOR STRUCTURE #1

|  |        |   |  |            |
|--|--------|---|--|------------|
|  | 336730 | Susp HiVis A/C<br><b>Cab Suspension</b> |  | \$1,440.00 |
|--|--------|---|--|------------|

### POWER TRAIN

#### TRANSMISSION

#### SD\_T2810 TRANSMISSION

|  |        |  |  |            |
|--|--------|--|--|------------|
|  | 390430 | 16x16 SPS 40KPH                                    |  | No Charge  |
|  | 334775 | 40KPH W/AutoFunction<br><b>Auto Shift</b>          |  | \$726.00   |
|  | 334114 | 16x16 40KPH W/Creep<br><b>Creeper</b>              |  | \$792.00   |
|  | 334779 | 40KPH W/AutoF+Creep<br><b>Auto Shift + Creeper</b> |  | \$1,518.00 |

**T5 ELECTRO COMMAND - LESS FASTPICK  
US PRICE LIST**

**AXLES**

**SD T4010 FRONT AXLE**

|  |  |        |                                |  |  |           |
|--|--|--------|--------------------------------|--|--|-----------|
|  |  | 337707 | Suspended Front Axle Less Brks |  |  | No Charge |
|--|--|--------|--------------------------------|--|--|-----------|

**TIRES**

**BRAND CHOICE**

**SD T4900 TIRE CATEGORY CHOICE**

|  |  |        |                          |  |  |            |
|--|--|--------|--------------------------|--|--|------------|
|  |  | 330438 | No tire brand preference |  |  | No Charge  |
|  |  | 330447 | Alliance                 |  |  | \$444.00   |
|  |  | 330439 | Continental              |  |  | \$444.00   |
|  |  | 330418 | Trelleborg               |  |  | \$444.00   |
|  |  | 330444 | Nokian                   |  |  | \$777.00   |
|  |  | 330442 | Michelin                 |  |  | \$1,108.00 |

**FRONT**

**SD T4940 FRONT WHEELS AND TIRES**

| Ag Front Tires |  |         |  |  |  |            |
|----------------|--|---------|--|--|--|------------|
|                |  | 8235401 | 12.4R24 A8<br><b>R1W, Adjustable Rim,<br/>Match w/ 8357401 rear tire/wheel</b>         |  |  | \$1,435.00 |
|                |  | 8242301 | 14.9R24 A8 HD Rim<br><b>R1W, adjustable rim<br/>Match with 8365401 rear tire/wheel</b> |  |  | \$2,161.00 |
|                |  | 8201801 | 9.5R28<br><b>R1W, Adjustable Rim,<br/>Match w/ 8369501 rear tire/wheel</b>             |  |  | \$1,769.00 |

**REAR**

**SD T4950 REAR WHEELS AND TIRES**

| Ag Rear Tires |  |         |   |  |  |            |
|---------------|--|---------|---|--|--|------------|
|               |  | 8357401 | 18.4R30 R1W<br><b>Matching front tire/whl is 8235401, 12.4R24<br/>(320/85R24)<br/>R1W, adjustable rim<br/>Not compatible with narrow rear fenders<br/>option code: 331870</b> |  |  | \$3,480.00 |

**T5 ELECTRO COMMAND - LESS FASTPICK  
 US PRICE LIST**

|                      |  |         |   |  |  |            |
|----------------------|--|---------|---|--|--|------------|
|                      |  | 8365401 | 460/85(18.4)R34 A8 FI,MI,CO,TR<br><b>Matching front tire/whl is 8242301, 14.9R24 (380/85R24)</b><br><b>R1W, adjustable rim</b><br><b>Not compatible with narrow rear fenders</b><br><b>option code: 331870</b>  |  |  | \$3,834.00 |
| Specialty Rear Tires |  |         |   |  |  |            |
|                      |  | 8369501 | 12.4R38 ) W11 x 38<br><b>Matching front tire/wheel is 9.5R28</b><br><b>Not compatible with front fender options 758329 and 758330</b><br><b>Row Crop with adjustable rim</b><br><b>Required when selecting narrow rear fender</b><br><b>option 331870</b> |  |  | \$2,049.00 |

**HYDRAULICS**
**REAR REMOTES**
**SD\_T8270 REAR REMOTES**

|  |  |        |   |  |  |            |
|--|--|--------|---|--|--|------------|
|  |  | 330849 | 2 MRRV (2C) Fixed Pump,EDC<br><b>2 closed center mechanical hydraulic remote valves both with configurable detent</b>                             |  |  | No Charge  |
|  |  | 331844 | 3 MRRV (1NC+2C)Fixed Pump,EDC<br><b>3 mechanical rear hydraulic remote valves, 2 with configurable detents and 1 with non-configurable detent</b> |  |  | \$1,496.00 |

**MID-MOUNT**
**SD\_T8280 MID-MOUNT VALVES**

|  |  |        |  |  |  |            |
|--|--|--------|--|--|--|------------|
|  |  | 758820 | 2 Slice Mech CC MMV<br><b>2 function mid mount valve with mechanical joystick</b>                  |  |  | \$1,440.00 |
|  |  | 758821 | 2 MMV CC w/EH Joystk<br><b>2 function mid mount valve with armrest mounted electronic joystick</b> |  |  | \$1,994.00 |

**T5 ELECTRO COMMAND - LESS FASTPICK  
 US PRICE LIST**
**LOADER**

## LOADER BRACKETS

## SD T8110 LOADER BRACKETS

|  |  |        |   |  |  |            |
|--|--|--------|---|--|--|------------|
|  |  | 758980 | Loader Ready.<br><b>Complete loader ready</b><br><b>Includes:</b><br>- Complete TPS mounting brackets<br>- Hose kit from mid mount valve to vertical brackets<br>- Multi-coupler base<br><br>Requires a mid mount valve selection |  |  | \$4,586.00 |
|--|--|--------|---|--|--|------------|

**ENGINE**

## AIR INTAKE

## SD T1910 AIR CLEANER

|  |  |        |  |  |  |          |
|--|--|--------|--|--|--|----------|
|  |  | 330200 | Air Filter w/Dust Ejector<br><b>Engine air cleaner with dust ejector</b> |  |  | \$121.00 |
|--|--|--------|--|--|--|----------|

## SD T1931 COLD WEATHER STARTI

|  |  |        |                   |  |  |          |
|--|--|--------|-------------------|--|--|----------|
|  |  | 744982 | Block Heater 120V |  |  | \$107.00 |
|--|--|--------|-------------------|--|--|----------|

**PTO**

## REAR PTO

## SD T8010 PTO

|  |  |        |                   |  |  |          |
|--|--|--------|-------------------|--|--|----------|
|  |  | 331729 | 540/540E/1000 RPM |  |  | \$798.00 |
|--|--|--------|-------------------|--|--|----------|

**CAB OR ROPS PLATFORM**

## MONITOR MOUNTING

## SD T7612 BRACKET MONITOR

|  |  |        |                          |  |  |          |
|--|--|--------|--------------------------|--|--|----------|
|  |  | 338761 | Monitor Mounting Bracket |  |  | \$139.00 |
|--|--|--------|--------------------------|--|--|----------|

## OTHER

## SD T9360 RR MIRRORS

|  |  |        |   |  |  |          |
|--|--|--------|---|--|--|----------|
|  |  | 341852 | 2 External Wide Angle Mirrors<br><b>2 Telescopic Rear Wide Angle Mirrors With Mechanical Adjustment</b> |  |  | \$401.00 |
|--|--|--------|---|--|--|----------|

**T5 ELECTRO COMMAND - LESS FASTPICK  
 US PRICE LIST**
**ELECTRICAL/CONNECTORS**
**BATTERY**

## SD T7420 BATTERY

|  |  |        |   |  |  |          |
|--|--|--------|---|--|--|----------|
|  |  | 334774 | Batt. 140 AH W/B.IS.<br><b>Battery Isolator</b> |  |  | \$388.00 |
|--|--|--------|---|--|--|----------|

**LIGHTS**
**ROTARY BEACON**

## SD T9146 ROTARY BEACON

|  |  |        |   |  |  |          |
|--|--|--------|---|--|--|----------|
|  |  | 759160 | ROTARY BEACON 759160  |  |  | \$111.00 |
|  |  | 335916 | 2 Beacons RH and LH Side<br><b>Left and right side safety beacons</b> |  |  | \$220.00 |

**WEIGHTS**
**FRONT**

## SD T2150 FRONT BALLAST

|  |  |        |   |  |  |            |
|--|--|--------|---|--|--|------------|
|  |  | 331759 | 10 Weights<br><b>Qty. 10, 88 lb. (40 Kg) weights<br/>totaling 882 lb. (400 Kg)<br/>Requires a front axle support with weight carrier (335156 or<br/>758385)</b> |  |  | \$1,164.00 |
|--|--|--------|---|--|--|------------|

## SD T8100 FRONT THREE POINT HITCH

|  |  |        |   |  |  |           |
|--|--|--------|---|--|--|-----------|
|  |  | 335156 | L/FHPL L/FPTO-STD<br><b>Standard front axle support with weight carrier.<br/>Not compatible with suspended front axle.</b>            |  |  | \$359.00  |
|  |  | 758385 | L/FHPL L/FPTO-MULTI<br><b>Suspended axle front axle support with weight carrier<br/>Not compatible with non suspended front axle.</b> |  |  | No Charge |

**REAR**

## SD T4961 REAR BALLAST

|  |  |        |   |  |  |          |
|--|--|--------|---|--|--|----------|
|  |  | 330471 | 6 Rear Wheel Weights<br><b>6, 110 lb. (50 kg.) rear disc weights<br/>totaling 661 lb. (300Kg)</b> |  |  | \$975.00 |
|--|--|--------|---|--|--|----------|



**T5 ELECTRO COMMAND - LESS FASTPICK  
US PRICE LIST**

**MISCELLANEOUS**

**FENDERS FRONT**

**SD T8740 FRONT FENDERS**

|  |  |        |  |  |  |          |
|--|--|--------|--|--|--|----------|
|  |  | 758330 | Dynamic Front Fenders 480mm<br><b>18.9 inch (480 mm) dynamic front fenders</b> |  |  | \$743.00 |
|--|--|--------|--|--|--|----------|

**REVERSE ALARM**

**SD T9249 REVERSE ALARM**

|  |  |        |                            |  |  |          |
|--|--|--------|----------------------------|--|--|----------|
|  |  | 332692 | Reverse Alarm w/Work Light |  |  | \$245.00 |
|--|--|--------|----------------------------|--|--|----------|