

**TK4.80V  
US PRICE LIST**

## Standard Equipment

### DIESEL ENGINE

74 Gross Engine hp  
65 PTO hp @ 2300 rpm  
207 cu. in. (3.4L) Displacement  
4 Cyl Turbocharged Intercooled Eng  
Common Rail Fuel Injection  
Under Hood Muffler  
Horizontal Exhaust  
Dual Element Air Filter  
24.3-gallon Fuel Tank  
Fuel System Water Separator  
Electric Engine Shutoff  
Grid Heater Starting Aid  
Tier 4A Emissions Compliant  
CEGR+DOC+DPF

### TRACTOR CLUTCH/TRANSMISSION

Hand Lever Activated, Single Plate \  
11.5 in. Diameter Organic Driveline  
Clutch  
8 x 8 (2 ranges of 4 gears) Transmission  
and Non-Synchronized Mechanical  
Forward-Reverse Shuttle

### STEERING SYSTEM

Steering-O-Matic# Plus  
Hand Rail Support  
Hydraulic Controlled Steering Clutch  
Packs for Each Side  
(9) 9 in. Diameter Clutch Disks per Pack  
Running in Oil

### PTO

11 in. Organic PTO Clutch  
Independent, 540 rpm  
Mechanical Engagement  
PTO Shaft Guard

### BRAKES

Foot Actuated, Mechanical Controlled  
Band Brakes  
Parking Brake - hand operated

### HYDRAULIC SYSTEM

Open Center System  
Dual Gear Pumps  
Maximum flow at Rated Engine Speed  
Implement Pump: 9.2 gpm  
Steering Pump: 5.4 gpm  
Three Rear Open Center Remote Valves  
with Quick Release Couplers:  
(1) Valve Self-Centering with Float  
Position  
(1) Detented Valve with Flow Control  
(1) Single/double acting Valve

### 3-POINT LIFT SYSTEM

Two Lever Controls (one for position,  
one for draft)  
Lift-O-Matic Plus  
4,265 lbs. Lift Capacity (OECD rated  
with top link in top hole)  
Category I/ II Fixed Link Ends  
Adjustable Chain Stabilizers  
Top Link Draft Sensing

### ELECTRICAL

One 12-volt, 800 cca Battery  
120 amp Alternator  
7-Pin Outlet for Trailer/Implement  
lighting  
Single Pin (8 amp) Accessory Power  
outlet

### LIGHTING

(2) Halogen Front Headlights  
One Rear Worklight  
Turn Signals and Flashers

### INSTRUMENTATION

Analog Instrument Panel with Warning  
Lights plus Engine Temperature and  
Fuel Level Gauges

**TK4.80V**  
**US PRICE LIST**

## Standard Equipment

**\*MANUFACTURER'S RATING**

**OPERATOR'S STATION**

53.3 in. (1354 mm) Height at Top of Dash

91.4 in. (2321 mm) Height at Top of Rollbar

Isolation Mounted Operator's Seat, Footrest and Fenders

Foldable Mid-Mounted Rollbar

Deluxe Vinyl Seat with Operator's Presence Sensor

Seat Belts

**MISCELLANEOUS**

121.3 in. (3080 mm) Maximum Length with Rollbar Folded

Pivoting Engine Hood

Swinging Drawbar with Clevis Hitch

SMV Emblem

Toolbox

4 Front Ballasts (440 lbs)

**WARRANTY**

New Holland Standard Warranty Applies

**TRACKS AND UNDERCARRIAGE**

35.4 in. (900 mm) Track Setting (center to center)

10.6 in. (270 mm) Track Shoe Width equals 46.1 in. (1170 mm) overall width

Heavy-duty Dry Track Chain

(4) Track Rollers per side

Front Leaf Spring Controls Track Oscillation

Track Assemblies Mounted Independent to Driveline

**TK4.80V  
US PRICE LIST**

## Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
TK4.80V	Rops	4,300 LB		\$79,656.00

## Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

### TRANSMISSION

#### TRANSMISSION

##### SD T2810 TRANSMISSION

		759191	16+8 GEARBOX W/CREEP			\$690.00
--	--	--------	----------------------	--	--	----------

### WEIGHTS

#### FRONT WEIGHTS

##### SD T2150 FRONT BALLAST

		759224	FRONT HOOK 759224			(\$543.00)
		759225	THREE FRONT BALLAST 198 lbs (3 x 66lb weights)			(\$125.00)
		759504	FOUR FRONT BALLASTS 440 lbs (4 x 88lb weights + 2 x 44lb supports)			No Charge

### OPERATORS MANUAL

##### SD T9807 OPERATOR MANUAL

		759242	AMERICAN ENGLISH OM			No Charge
		759243	AMERICAN SPANISH OM			No Charge

**TK4.80F**  
**US PRICE LIST**

## Standard Equipment

### DIESEL ENGINE

74 Gross Engine hp  
65 PTO hp @ 2300 rpm  
207 cu. in. (3.4L) Displacement  
4 Cyl Turbocharged Intercooled Eng  
Common Rail Fuel Injection  
Under Hood Muffler  
Horizontal Exhaust  
Dual Element Air Filter  
24.3-gallon Fuel Tank  
Fuel System Water Separator  
Electric Engine Shutoff  
Grid Heater Starting Aid  
Tier 4A Emissions Compliant  
CEGR+DOC+DPF

### TRACTOR CLUTCH/TRANSMISSION

Hand Lever Activated, Single Plate \  
11.5 in. Diameter Organic Driveline  
Clutch  
8 x 8 (2 ranges of 4 gears) Transmission  
and Non-Synchronized Mechanical  
Forward-Reverse Shuttle

### STEERING SYSTEM

Steering-O-Matic# Plus  
Hand Rail Support  
Hydraulic Controlled Steering Clutch  
Packs for Each Side  
(9) 9 in. Diameter Clutch Disks per Pack  
Running in Oil

### PTO

11 in. Organic PTO Clutch  
Independent, 540 rpm  
Mechanical Engagement  
PTO Shaft Guard

### BRAKES

Foot Actuated, Mechanical Controlled  
Band Brakes  
Parking Brake - hand operated

### HYDRAULIC SYSTEM

Open Center System  
Dual Gear Pumps  
Maximum flow at Rated Engine Speed  
Implement Pump: 9.2 gpm  
Steering Pump: 5.4 gpm  
Three Rear Open Center Remote Valves  
with Quick Release Couplers:  
(1) Valve Self-Centering with Float  
Position  
(1) Detented Valve with Flow Control  
(1) Single/double acting Valve

### 3-POINT LIFT SYSTEM

Two Lever Controls (one for position,  
one for draft)  
Lift-O-Matic Plus  
4,265 lbs. Lift Capacity (OECD rated  
with top link in top hole)  
Category I/ II Fixed Link Ends  
Adjustable Chain Stabilizers  
Top Link Draft Sensing

### ELECTRICAL

One 12-volt, 800 cca Battery  
120 amp Alternator  
7-Pin Outlet for Trailer/Implement  
lighting  
Single Pin (8 amp) Accessory Power  
outlet

### LIGHTING

(2) Halogen Front Headlights  
One Rear Worklight  
Turn Signals and Flashers

### INSTRUMENTATION

Analog Instrument Panel with Warning  
Lights plus Engine Temperature and  
Fuel Level Gauges

**TK4.80F**  
**US PRICE LIST**

## Standard Equipment

**\*MANUFACTURER'S RATING**

**OPERATOR'S STATION**

53.3 in. (1354 mm) Height at Top of Dash

91.4 in. (2321 mm) Height at Top of Rollbar

Isolation Mounted Operator's Seat, Footrest and Fenders

Foldable Mid-Mounted Rollbar

Deluxe Vinyl Seat with Operator's Presence Sensor

Seat Belts

**TRACKS AND UNDERCARRIAGE**

SmartTrax® Rubber Tracks

43.3 in. (1100 mm) Track Setting (center to center)

11.8 in. (300 mm) Track Shoe Width equals 55.1 in. (1400 mm) overall width

Heavy-duty Dry Track Chain

(4) Track Rollers per side

Front Leaf Spring Controls Track Oscillation

Track Assemblies Mounted Independent to Driveline

**MISCELLANEOUS**

121.3 in. (3080 mm) Maximum Length with Rollbar Folded

Pivoting Engine Hood

Swinging Drawbar with Clevis Hitch

SMV Emblem

Toolbox

4 Front Ballasts (440 lbs)

**WARRANTY**

New Holland Standard Warranty Applies

**TK4.80F  
US PRICE LIST**

## Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
TK4.80F	Rops	4,300 LB		\$87,485.00

## Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

### TRANSMISSION

#### TRANSMISSION

##### SD T2810 TRANSMISSION

		759191	16+8 GEARBOX W/CREEP			\$690.00
--	--	--------	----------------------	--	--	----------

### WEIGHTS

#### FRONT WEIGHTS

##### SD T2150 FRONT BALLAST

		759224	FRONT HOOK 759224			(\$543.00)
		759225	THREE FRONT BALLAST 198 lbs (3 x 66lb weights)			(\$125.00)
		759504	FOUR FRONT BALLASTS 440 lbs (4 x 88lb weights + 2 x 44lb supports)			No Charge

### OPERATORS MANUAL

##### SD T9807 OPERATOR MANUAL

		759242	AMERICAN ENGLISH OM			No Charge
		759243	AMERICAN SPANISH OM			No Charge

**TK4.100**  
**US PRICE LIST**

## Standard Equipment

**DIESEL ENGINE**

98 Gross Engine hp\*  
 86 PTO hp @ 2300 rpm\*  
 207 cu. in. (3.4L) Displacement  
 4 Cyl Turbocharged Intercooled Eng  
 Common Rail Fuel Injection  
 Under Hood Muffler  
 Horizontal Exhaust  
 Dual Element Air Filter  
 24.3-gallon Fuel Tank  
 Fuel System Water Separator  
 Electric Engine Shutoff  
 Grid Heater Starting Aid  
 Tier 4A Emissions Compliant  
 CEGR+DOC+DPF

**TRACTOR CLUTCH/TRANSMISSION**

Hand Lever Activated, Double Plate  
 11.5 in. Diameter Organic Driveline  
 Clutch  
 8 x 8 (2 ranges of 4 gears) Transmission  
 and Non-Synchronized Mechanical  
 Forward-Reverse Shuttle

**STEERING SYSTEM**

Steering-O-Matic# Plus  
 Hand Rail Support  
 Hydraulic Controlled Steering Clutch  
 Packs for Each Side  
 Six 10 in. Diameter Clutch Disks per  
 pack running in Oil

**PTO**

11 in. Organic PTO Clutch  
 Independent, 540/1000 rpm, Manual  
 Shift  
 Double Lever, Mechanical Engagement  
 PTO Shaft Guard

**BRAKES**

Foot Actuated, Mechanical Controlled  
 and Steering-O-Matic™ Controlled  
 Wet Disc Brakes  
 Parking Brake - hand operated

**HYDRAULIC SYSTEM**

Open Center System  
 Triple Gear Pumps  
 Oil Cooler  
 Maximum flow at Rated Engine Speed  
 Implement Pump: 11.9 gpm  
 Steering Pump: 5.8 gpm  
 Oil Cooler Pump x.x gpm  
 Three Rear Open Center Remote Valves  
 with Quick Release Couplers:  
 (1) Valve Self-Centering with Float  
 Position  
 (1) Detented Valve  
 (1) Valve Self-Centering

**3-POINT LIFT SYSTEM**

Two Lever Controls (one for position,  
 one for draft)  
 Lift-O-Matic Plus  
 4,078 lbs. Lift Capacity  
 (OECD rated with top link in top hole)  
 Category I/ II Fixed Link Ends  
 Adjustable Chain Stabilizers  
 Top Link Draft Sensing

**ELECTRICAL**

One 12-volt, 800 cca Battery  
 120 amp Alternator  
 7-Pin Outlet for Trailer/Implement  
 lighting  
 Single Pin (8 amp) Accessory Power  
 outlet

**LIGHTING**

(2) Halogen Front Headlights  
 One Rear Worklight  
 Turn Signals and Flashers

**INSTRUMENTATION**

Analog/Digital Instrument Panel with  
 Warning Lights plus Engine  
 Temperature and Fuel Level Gauges

\*MANUFACTURER'S RATING

**TK4.100**  
**US PRICE LIST**

## Standard Equipment

OPERATOR'S STATION: (less cab)  
54.5 in. (1384 mm) Height at Top of Dash  
92.9 in. (2361 mm) Height at Top of Rollbar  
Isolation Mounted Operator's Seat, Footrest and Fenders  
Foldable Mid-Mounted Rollbar  
Deluxe Vinyl Seat with Operator's Presence Sensor  
Retractable Seat Belts

OPERATOR'S STATION: CAB  
Deluxe Cab with Heater and Air Conditioner  
Isolation Mounted Cab Structure  
Integral ROPS  
(2) Doors with Locks  
Tinted Glass  
Hinged Rear Window (fully opens)  
Front and Rear Wiper and Washer  
Horn  
Interior Mirror  
2 external mirrors  
Radio Ready  
Deluxe Cloth Air Suspension Seat with Operator's Presence Sensor

TRACKS AND UNDERCARRIAGE  
43.3 in. (1100 mm) Track Setting (center to center)  
12.2 in. (310 mm) Track Shoe Width equals 55.5 in. (1410 mm) overall width  
Heavy-duty Dry Track Chain  
(6) Track Rollers per side  
Front Leaf Spring Controls Track Oscillation  
Track Assemblies Mounted Independent to Driveline

MISCELLANEOUS  
132.5 in. (3365 mm) Maximum Length with Rollbar Folded  
Pivoting Engine Hood  
Swinging Drawbar with Clevis Hitch  
SMV Emblem  
Toolbox  
Front Tow Hook

WARRANTY  
New Holland Standard Warranty Applies



**TK4.100  
US PRICE LIST**

## Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
TK4.100	Cab	4,300 LB		\$99,566.00
TK4.100	Rops	4,300 LB		\$86,865.00

## Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

### TRANSMISSION

#### TRANSMISSION

##### SD T2810 TRANSMISSION

		759191	16+8 GEARBOX W/CREEP			\$690.00
--	--	--------	----------------------	--	--	----------

### HYDRAULICS

#### HYDRAULIC PUMP

##### SD T8230 HYD PUMP

		759194	HYDRAULIC PUM759194 <b>12.0 gpm</b>			No Charge
		762084	HYDR.PUMP 80l/min <b>21.1 gpm</b>			\$1,500.00

#### REAR REMOTE VALVES

##### SD T8270 REAR REMOTES

		759205	4REAR REMOTES W/FLOW <b>First valve detented with flow control</b> <b>Second valve self-centering w/ float</b> <b>third and fourth valve self centering</b>			\$1,187.00
--	--	--------	--	--	--	------------

### OTHER EQUIPMENT

#### ADDITIONAL EQUIPMENT

##### SD T8500 SEAT

		759506	PREMIUM PNEUMAT.SEAT			\$998.00
--	--	--------	----------------------	--	--	----------



**TK4.100  
US PRICE LIST**

**WEIGHTS**

**FRONT WEIGHTS**

**SD\_T2150 FRONT BALLAST**

		759225	THREE FRONT BALLAST 198 lbs (3 x 66lb weights)			\$418.00
--	--	--------	---	--	--	----------

**OPERATORS MANUAL**

**SD\_T9807 OPERATOR MANUAL**

		759242	AMERICAN ENGLISH OM			No Charge
		759243	AMERICAN SPANISH OM			No Charge

**TK4.100M  
US PRICE LIST**

## Standard Equipment

### DIESEL ENGINE

98 Gross Engine hp\*  
86 PTO hp @ 2300 rpm\*  
207 cu. in. (3.4L) Displacement  
4 Cyl Turbocharged Intercooled Eng  
Common Rail Fuel Injection  
Under Hood Muffler  
Horizontal Exhaust  
Dual Element Air Filter  
24.3-gallon Fuel Tank  
Fuel System Water Separator  
Electric Engine Shutoff  
Grid Heater Starting Aid  
Tier 4A Emissions Compliant  
CEGR+DOC+DPF

### TRACTOR CLUTCH/TRANSMISSION

Hand Lever Activated, Double Plate  
11.5 in. Diameter Organic Driveline  
Clutch  
8 x 8 (2 ranges of 4 gears) Transmission  
and Non-Synchronized Mechanical  
Forward-Reverse Shuttle

### STEERING SYSTEM

Steering-O-Matic# Plus  
Hand Rail Support  
Hydraulic Controlled Steering Clutch  
Packs for Each Side  
Six 10 in. Diameter Clutch Disks per  
pack running in Oil

### PTO

11 in. Organic PTO Clutch  
Independent, 540/1000 rpm, Manual  
Shift  
Double Lever, Mechanical Engagement  
PTO Shaft Guard

### BRAKES

Foot Actuated, Mechanical Controlled  
and Steering-O-Matic# Controlled  
Wet Disc Brakes  
Parking Brake - hand operated  
\* MANUFACTURER'S RATING

### HYDRAULIC SYSTEM

Open Center System  
Triple Gear Pumps  
Maximum flow at Rated Engine Speed  
Implement Pump: 11.9 gpm  
Steering Pump: 5.8 gpm  
Oil Cooler Pump X.X gpm  
Three Rear Open Center Remote Valves  
with Quick Release Couplers:  
(1) Valve Self-Centering with Float  
Position  
(1) Detented Valve  
(1) Valve Self-Centering

### 3-POINT LIFT SYSTEM

Two Lever Controls (one for position,  
one for draft)  
Lift-O-Matic Plus  
4078 lbs. Lift Capacity  
(OECD rated with top link in top hole)  
Category I/II Fixed Link Ends  
Adjustable Chain Stabilizers  
Top Link Draft Sensing

### ELECTRICAL

One 12-volt, 800 cca Battery  
120 amp Alternator  
7-Pin Outlet for Trailer/Implement  
lighting  
Single Pin (8 amp) Accessory Power  
outlet

### LIGHTING

(2) Halogen Front Headlights  
One Rear Worklight  
Turn Signals and Flashers

### INSTRUMENTATION

Analog/Digital Instrument Panel with  
Warning Lights plus Engine  
Temperature and Fuel Level Gauges

\*MANUFACTURER'S RATING

**TK4.100M**  
**US PRICE LIST**

## Standard Equipment

OPERATOR'S STATION: (less cab)  
54.5 in. (1384 mm) Height at Top of Dash  
92.9 in. (2361 mm) Height at Top of Rollbar  
Isolation Mounted Operator's Seat, Footrest and Fenders  
Foldable Mid-Mounted Rollbar  
Deluxe Vinyl Seat with Operator's Presence Sensor  
Retractable Seat Belts

OPERATOR'S STATION: CAB  
Deluxe Cab with Heater and Air Conditioner  
Isolation Mounted Cab Structure  
Integral ROPS  
(2) Doors with Locks  
Tinted Glass  
Hinged Rear Window (fully opens)  
Front and Rear Wiper and Washer  
Horn  
Interior Mirror  
2 external mirrors  
Radio Ready  
Deluxe Cloth Air Suspension Seat with Operator's Presence Sensor

TRACKS AND UNDERCARRIAGE  
51.2 in. (1300 mm) Track Setting (center to center)  
15.7 in. (400 mm) Track Shoe Width equals 67 in. (1700 mm) overall width, with Heavy-duty lubricated track chain  
17.7 in. (450 mm) Track Shoe Width equals 68.9 in. (1750 mm) overall width, with Heavy-duty lubricated track chain  
(6) Track Rollers per side  
Front Leaf Spring Controls Track Oscillation  
Track Assemblies Mounted Independent to Driveline

MISCELLANEOUS  
132.5 in. (3365 mm) Maximum Length with Rollbar Folded  
Pivoting Engine Hood  
Swinging Drawbar with Clevis Hitch  
SMV Emblem  
Toolbox  
Front Tow Hook

WARRANTY  
New Holland Standard Warranty Applies

TK4.100M  
US PRICE LIST

## Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
TK4.100M	Cab	4,300 LB		\$102,470.00
TK4.100M	Rops	4,300 LB		\$89,769.00

## Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

### TRANSMISSION

#### TRANSMISSION

##### SD T2810 TRANSMISSION

		759191	16+8 GEARBOX W/CREEP			\$690.00
--	--	--------	----------------------	--	--	----------

### HYDRAULICS

#### HYDRAULIC PUMP

##### SD T8230 HYD PUMP

		759194	HYDRAULIC PUM759194 <b>12.0 gpm</b>			No Charge
		762084	HYDR.PUMP 80l/min <b>21.1 gpm</b>			\$1,500.00

#### REAR REMOTE VALVES

##### SD T8270 REAR REMOTES

		759205	4REAR REMOTES W/FLOW <b>First valve detented with flow control</b> <b>Second valve self-centering w/ float</b> <b>third and fourth valve self centering</b>			\$1,187.00
--	--	--------	--	--	--	------------

### TRACKS

##### SD T5000 TRACKS

#### Steel Tracks

		759251	450mm SHOES-140mm CH <b>17.1 inch wide tracks</b>			No Charge
--	--	--------	--	--	--	-----------

**TK4.100M  
US PRICE LIST**

		759259	400mm SHOES-140 LUBR <b>15.7 inch wide tracks</b>			(\$1,932.00)
Rubber Tracks						
		759261	RUBBER TRACKS 450MM <b>SmartTrax# - 17.1 inch wide</b> <b>Includes Heavy Duty Cast Iron Guard Cover</b>			\$7,503.00

**OTHER EQUIPMENT**

## ADDITIONAL EQUIPMENT

## SD T8500 SEAT

		759506	PREMIUM PNEUMAT.SEAT			\$998.00
--	--	--------	----------------------	--	--	----------

**WEIGHTS**

## FRONT WEIGHTS

## SD T2150 FRONT BALLAST

		759225	THREE FRONT BALLAST <b>198 lbs (3 x 66lb weights)</b>			\$418.00
		759316	10FRONT BALLASTS 500 <b>1,100 lbs (10 x 88lb weights + 2 x 110lb supports)</b> <b>TK4.100M ONLY</b>			\$1,357.00

**OPERATORS MANUAL**

## SD T9807 OPERATOR MANUAL

		759242	AMERICAN ENGLISH OM			No Charge
		759243	AMERICAN SPANISH OM			No Charge