

**POWERSTAR 65-75 STANDARD FASTPICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- CommandArc# ergonomically places most frequently used controls to operator's right
- Ten repositionable vents for heating and air conditioning
- 12x12 Transmission
- Hydraulic shuttle lever
- Full-size instructor seat
- Hi Visibility Panel
- Lift-O-Matic Plus
- Tier 4B EPA emissions compliant
- Factory Installed Loader

DIESEL ENGINE

PowerStar 65
64 Gross Engine hp
50 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 75

74 Gross Engine hp
65 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

ALL MODELS

US EPA Tier 4B Emissions Compliant
Bosch Fuel Injection Pump
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Air Cleaner: Dry Type with Safety Element
Under Hood Muffler
Vertical Exhaust
Fuel Sediment Filter with Water Sensor
23.8 gal Fuel Tank w/ Protection Shield
Parking brake

TRANSMISSION

Wet Clutch
LH side steering column mounted shuttle
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
Forward Reverse Power Shuttle
FWD - 25 mph (40 kph)
Speed varies with tire selection

AXLES

FWD FRONT AXLE
Electro-Hydraulic engagement standard
Adjustable Tread Width from 60.8 in. to 76.6 in.
Limited Slip Differential Lock
Standard FAS Ready

REAR AXLE

Flange Type
Adjustable Tread Width 52.2 in. to 76.0 in.
Rear Differential Lock - FWD mechanically engaged.

HYDRAULIC SYSTEM

Open Center System
(2) Open Center Valves with detent
2 Function mid mount valve and joystick
Dual Gear Pumps
Implement Pump: 12.5 gpm (47.5 L)
Steering Pump: 7.3 gpm (27.5 L)
Total Flow: 19.8 gpm (75 L)

PTO

540 rpm Hydraulic PTO
(1-3/8 in. 6 splines)
Fully Independent, wet clutch
Hydraulic engagement
Flip-up PTO Shaft Guard

**POWERSTAR 65-75 STANDARD FASTPICK
US PRICE LIST**

Standard Equipment

HITCH

3-point Category II with flex lower links
and telescoping stabilizers
Lift-O-Matic Plus rear hitch control
3664 lbs. Lift Capacity (SAE)
Swinging Drawbar
Mechanical Draft Control
Upper Link Draft Sensing
3-Point Hitch Ground Control

STEERING/BRAKES

Hydrostatic Power Steering
Brakes-
Wet disk brakes
Hydraulically assisted

INSTRUMENTATION

Analog Instrumentation with warning
lights for air cleaner service,
alternator, oil pressure, fuel
sediment/water sensor, PTO
engagement, head light high beam,
low fuel and parking brake, digital
speed readout, gauges for fuel level,
engine temperature, tachometer and
hour meter

ELECTRICAL

(1) 800 cca Heavy-duty Battery
Alternator: 120 amp
7-pin Outlet for trailer/implement lighting
and signals
4-pin Power Outlet (30 amp)
8 amp single pole
2 Auxiliary power sockets
(cigarette lighter)

LIGHTING

Front: (2) Halogen Headlights and
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE

ROPS protected, flat deck platform with
heat and air conditioning, tinted
windshield, retractable sun screen,
front and rear wiper and washer,
two doors with locks, two external
mirrors, openable side windows,
hinged rear window (fully opens)
High Visibility Panel
Steering Wheel - adjustable tilt
Seat - Cloth covered with air
suspension and 10 degrees of swivel,
operator's presence sensor, retractable
seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

MISCELLANEOUS

Pivoting Engine Hood
SMV Emblem
Rear wheel weights
Toolbox

WARRANTY

New Holland Standard Warranty Applies

**POWERSTAR 65-75 STANDARD FASTPICK
US PRICE LIST**

Standard Equipment

LOADER:

655TL/710LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 127.2"

Dump Clearance: 94.4"

Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 2,478 LBS

59" high @ 800mm: 3,080 LBS

Breakout Force @ 800mm: 3,739 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 45 degrees

Bucket Dump Angle: 60 degrees

Skid Steer style bucket attach

655TL/715LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 127.2"

Dump Clearance: 94.4"

Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 3,179 LBS

59" high @ 800mm: 4,665 LBS

Breakout Force @ 800mm: 3,860 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style bucket attach

**POWERSTAR 65-75 STANDARD FASTPICK
US PRICE LIST****Models**

COMMERCIAL MODEL	VERSION	ENGINE POWER	Weight	Factory Data	List Price
POWERSTAR 65	Cab	65 HP	6,239 LB		\$61,501.00
Includes the following Equipment					
11.2R24 R1W (8232404) \$1,161.00					
16.9R30 R1W (8355404) \$2,530.00					
POWERSTAR 75	Cab	75 HP	7,996 LB		\$64,760.00
Includes the following Equipment					
11.2R24 R1W (8232404) \$1,161.00					
16.9R30 R1W (8355404) \$2,530.00					

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

	X99803X	STANDARD PACKAGING Standard Package and Pricing Includes: 84 inch bucket 4 x 110 lb Rear Wheel Weights Requires one selection for each of the following: Mid mount valve and joystick: 2 Function mid mount valve and joystick or 2 Function mid mount valve and joystick + 3rd function diverter Loader: 655TL loader (select one)			\$1,597.00
--	---------	--	--	--	------------

HYDRAULICS

MID-MOUNT

SD_T8280 MID-MOUNT VALVES

	338125	2Mid-Mount w/Mec Joystick 2 function mid-mount valve and joystick.			No Charge
--	--------	---	--	--	-----------

**POWERSTAR 65-75 STANDARD FASTPICK
US PRICE LIST**

		336780	2Mid-Mount w/Mec Joystick +Div 2 function mid-mount valve and joystick with 3rd function diverter. Requires a 655TL Loader. Bucket with Grapple NOT AVAILABLE as Factory Installed.			\$750.00
--	--	--------	---	--	--	----------

LOADER

LOADER

SD_T8110 LOADER BRACKETS

		336914	if PACKAGING is STANDARD PACKAGING 655TL/710LU Non Self Leveling with Skid Steer Attachment			No Charge
		336734	if PACKAGING is STANDARD PACKAGING 655TL/715LU Mechanical Self Leveling with Skid Steer Style Attachment			\$1,119.00
		336736	if PACKAGING is STANDARD PACKAGING 655TL/715LU Mechanical Self Leveling with Euro Style Attachment			\$1,119.00

OPERATOR'S MANUALS

SD_T9840 COUNTRY CONFIGURATION

		334256	Canada (FR) Config ROPS			No Charge
		334257	USA Spanish Configuration			No Charge

**POWERSTAR 65-75 A LA CARTE CAB
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- CommandArc# ergonomically places most frequently used controls to operator's right
- Ten repositionable vents for heating and air conditioning
- 12x12 Transmission
- Mechanical or hydraulic shuttle lever
- Full-size instructor seat option
- Hi Visibility Panel Option
- Tier 4B EPA emissions compliant
- Factory Installed Loader

DIESEL ENGINE

PowerStar 65
64 Gross Engine hp
50 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 75
74 Gross Engine hp
65 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

ALL MODELS

US EPA Tier 4B Emissions Compliant
Bosch Fuel Injection Pump
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Air Cleaner: Dry Type with Safety Element
Under Hood Muffler
Vertical Exhaust
Fuel Sediment Filter with Water Sensor
23.8 gal Fuel Tank w/ Protection Shield
Parking brake

TRANSMISSION

Wet Clutch
LH side steering column mounted shuttle
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
Forward Reverse Power Shuttle
FWD - 25 mph (40 kph)
Speed varies with tire selection

AXLES

2WD HD FRONT AXLE - PowerStar 75
Inverted U-section type
Adjustable Tread Width from 57.0 in. to 79.7 in.

FWD FRONT AXLE

Electro-Hydraulic engagement standard
Adjustable Tread Width from 60.8 in. to 76.6 in.
Limited Slip Differential Lock

REAR AXLE

Flange Type
Adjustable Tread Width 52.2 in. to 76.0 in.
Rear Differential Lock - 2WD and FWD mechanically engaged.

HYDRAULIC SYSTEM

Open Center System
(2) Open Center Valves with detent
2 Function mid mount valve and joystick
Dual Gear Pumps
Implement Pump: 12.5 gpm (47.5 L)
Steering Pump: 7.3 gpm (27.5 L)
Total Flow: 19.8 gpm (75 L)

PTO

540 rpm Mechanical PTO
(1-3/8 in. 6 splines)
Fully Independent, wet clutch
Hydraulic Engagement
Flip-up PTO Shaft Guard

**POWERSTAR 65-75 A LA CARTE CAB
 US PRICE LIST**

Standard Equipment

HITCH

3-point Category II with flex lower links
 and telescoping stabilizers
 3664 lbs. Lift Capacity (SAE)
 Lift-O-Matic Plus
 3-Point Hitch Ground Control
 Swinging Drawbar
 Mechanical Draft Control
 Upper Link Draft Sensing

STEERING/BRAKES

Hydrostatic Power Steering
 Brakes-
 Wet disk brakes
 Hydraulically assisted

INSTRUMENTATION

Analog Instrumentation with warning
 lights for air cleaner service,
 alternator, oil pressure, fuel
 sediment/water sensor, PTO
 engagement, head light high beam,
 low fuel and parking brake, digital
 speed readout
 Gauges for fuel level, engine
 temperature, tachometer and hour
 meter

ELECTRICAL

(1) 800 cca Heavy-duty Battery
 Alternator: 120 amp
 7-pin Outlet for trailer/implement lighting
 and signals
 4-pin Power Outlet (30 amp)
 8 amp single pole
 Auxiliary power socket (cigarette lighter)

LIGHTING

Front: (2) Halogen Headlights and
 (2) cab mounted worklights
 Rear: (2) cab mounted worklights
 Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE

ROPS protected, flat deck platform with
 heat and air conditioning, tinted
 windshield, retractable sun screen,
 front wiper and washer, two doors
 with locks, two external mirrors,
 openable side windows, hinged rear
 window (fully opens)
 High Visibility Pane
 Steering Wheel - adjustable tilt
 Seat - Cloth covered with air
 suspension and 10 degrees of swivel,
 operator's presence sensor, retractable
 seat belt and arm rests
 Instructor Seat
 Suspended pedals
 Radio, speakers, and antenna

MISCELLANEOUS

Pivoting Engine Hood
 SMV Emblem
 Toolbox
 Toolbox on ROPS unit located in fenders

WARRANTY

New Holland Standard Warranty Applies

**POWERSTAR 65-75 A LA CARTE CAB
US PRICE LIST**

Standard Equipment

LOADER:

655TL/710LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 127.2"

Dump Clearance: 94.4"

Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 2,478 LBS

59" high @ 800mm: 3,080 LBS

Breakout Force @ 800mm: 3,739 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 45 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style bucket attach

655TL/715LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 127.2"

Dump Clearance: 94.4"

Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 3,179 LBS

59" high @ 800mm: 4,665 LBS

Breakout Force @ 800mm: 3,860 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style bucket attach

**POWERSTAR 65-75 A LA CARTE CAB
US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	ENGINE POWER	Weight	Factory Data	List Price
POWERSTAR 65	Cab	65 HP	6,239 LB		\$61,501.00
Includes the following Equipment					
11.2R24 R1W (8232404) \$1,161.00					
16.9R30 R1W (8355404) \$2,530.00					
POWERSTAR 75	Cab	75 HP	7,996 LB		\$64,760.00
Includes the following Equipment					
11.2R24 R1W (8232404) \$1,161.00					
16.9R30 R1W (8355404) \$2,530.00					

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

	X99801X	LESS PACKAGING			No Charge
--	---------	----------------	--	--	-----------

POWER TRAIN

AXLES

SD_T4010 FRONT AXLE

	336858	2WD Standard Axle Heavy Duty Requires 20 MPH (30 KPH) Compatible with 655TL Requires rear wheel weights (330470) ONLY when ordered with 655TL PowerStar 75 ONLY			(\$1,105.00)
	744580	4WD Electro Hyd Limited Slip Electro-hydraulic 4WD engagement			No Charge

**POWERSTAR 65-75 A LA CARTE CAB
US PRICE LIST**

TIRES
FRONT

SD_T4940 FRONT WHEELS AND TIRES

2WD Front Tires

		8125801	7.50-16 8 PLY HD			\$473.00
		8126601	9.5L15 4 RIB 8 PLY			\$619.00

4WD Radial Tires

		8232404	11.2R24 R1W			\$1,161.00
--	--	---------	-------------	--	--	------------

4WD Specialty Tires

		8290904	12.5/80-18 10PR R4			\$1,662.00
--	--	---------	--------------------	--	--	------------

4WD Front Shipping Wheels

		8299801	Non-Return Ship Wheels - 4WD			\$95.00
--	--	---------	------------------------------	--	--	---------

REAR

SD_T4950 REAR WHEELS AND TIRES

Radial Tires

		8355404	16.9R30 R1W 4WD Front Tire - 11.2R24 (8232404) 2WD Front Tire - 9.5L15 4 Rib (8126601) or 7.5-16 (8125801)			\$2,530.00
--	--	---------	--	--	--	------------

Specialty Tires

		8391904	19.5L-24 10 PR R4 4WD Front Tire - 12.5/80-18 (8290904)			\$2,573.00
--	--	---------	---	--	--	------------

Rear Shipping Wheels

		8399801	Non-Returnable Shipping Wheel			\$568.00
--	--	---------	-------------------------------	--	--	----------

HYDRAULICS
MID-MOUNT

SD_T8280 MID-MOUNT VALVES

		338125	2Mid-Mount w/Mec Joystick 2 function mid-mount valve and joystick.			No Charge
		336780	2Mid-Mount w/Mec Joystick +Div 2 function mid-mount valve and joystick with 3rd function diverter. Requires a 655TL Loader. Bucket with Grapple NOT AVAILABLE as Factory Installed.			\$750.00

**POWERSTAR 65-75 A LA CARTE CAB
 US PRICE LIST**
LOADER

LOADER

SD_T8110 LOADER BRACKETS

Standard Duty Loader

		336914	Non Self Leveling Ldr +SSQA 655TL/710LU Non Self Leveling with Skid Steer Attachment			No Charge
		336732	Non Self Leveling Ldr +Euro 655TL/710LU Non Self Leveling with Euro Style Attachment			No Charge
		336734	Mech Self Leveling Ldr +SSQA 655TL/715LU Mechanical Self Leveling with Skid Steer Style Attachment			\$1,119.00
		336736	Mech Self Leveling Ldr +Euro 655TL/715LU Mechanical Self Leveling with Euro Style Attachment			\$1,119.00
		743593	Less Front Loader			(\$6,120.00)

SD_T8140 BUCKET

		XT8140X	Less Bucket			No Charge
		336750	84" Bucket			\$952.00

WEIGHTS

REAR

SD_T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights			\$645.00
--	--	--------	-------------------------------	--	--	----------

OPERATOR'S MANUALS

SD_T9840 COUNTRY CONFIGURATION

		334256	Canada (FR) Config ROPS			No Charge
		334257	USA Spanish Configuration			No Charge

**POWERSTAR 90-120 PS UTILITY FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- CommandArc# ergonomically places most frequently used controls to operator's right
- Ten repositionable vents for heating and air conditioning
- Full-size instructor seat
- Hydraulic shuttle lever
- 3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- Factory Installed NSL SSL Loader

PowerStar 90

86 Gross Engine hp
73 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 100

99 Gross Engine hp
85 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 110

107 Gross Engine hp
93 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 120

117 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

ALL MODELS:

Tier 4B Emissions Compliant:
(SCR + CEGR)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Dual Element Air Filter

Constant Engine RPM

Vertical Exhaust

30.3 gal Fuel Tank with Guard

2.8 gal AdBlue DEF Tank

Parking brake

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

Forward Reverse Synchronized Shuttle

19 mph (30 kph)

Speed varies with tire selection

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes-

Wet disk brakes

Hydraulically assisted

AXLES:

FRONT - 4WD

Limited Slip

- PowerStar 90, 100 & 110:

Electrohydraulic FWD Engagement

Adjustable Tread Width from

56.6 in to 76.6 in.

- PowerStar 120:

Heavy Duty Electrohydraulic FWD

Engagement

Adjustable Tread Width from

56.6 in. to 76.6 in.

**POWERSTAR 90-120 PS UTILITY FAST PICK
US PRICE LIST**

Standard Equipment

AXLES Continued:

REAR

- PowerStar 90, 100 & 110:
Flange Type
Adjustable Tread Width 55.5 in to 76.2 in.
- PowerStar 120:
Heavy Duty Flange Type
Adjustable Tread Width 55.5 in. to 76.2 in.
- 4 x 110 lb Rear Wheel Weights

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

- Implement Pump: 16.9 gpm (63.9 L)
- Steering Pump: 9.7 gpm (37.0 L)
- Total Flow: 26.6 gpm (100.8 L)
- (2) Open Center Remote Valves with detent
- 2 Function Mid Mount Valve and Joystick

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

- Fully Independent
- Flip-up PTO Shaft Guard
- PowerStar 90, 100 & 110:
540 rpm Hydraulic
- PowerStar 120:
540/1000 rpm Hydraulic
- Electronic engagement
- Wet clutch
- 1-3/8 in. 6 splines

3-POINT LIFT SYSTEM:

- Right hand console mounted lever control
- Mechanical Draft Control
- Rear 3 Point Hitch Control
- 5,620 Pounds Lift Capacity
- Category II Ends
- Telescopic Stabilizers
- Flexible Lower Link Ends

ELECTRICAL:

- (1) 800 cca Heavy-Duty Battery - Cab
- 120 amp Alternator
- 7-pin Outlet for trailer/implement lighting and signals
- 3-pin Power Outlet (30 amp)
- Single Pin (8 amp) Accessory Power outlet
- 12V power socket

INSTRUMENTATION:

- Analog Instrumentation with warning lights for air cleaner service, alternator, oil pressure, fuel sediment/water sensor, PTO engagement, head light high beam, low fuel and parking brake, digital speed readout
- Gauges for fuel level, engine temperature, tachometer and hour meter

LIGHTING:

- Front: (2) Halogen Headlights and (2) cab mounted worklights
- Rear: (2) cab mounted worklights
- Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

- ROPS protected, flat deck platform with heat and air conditioning, tinted windshield, retractable sun screen, front and rear wiper and washer, two doors with locks, two external mirrors, openable side windows, hinged rear window (opens completely)
- Steering Wheel - adjustable tilt
- Seat - Cloth covered with air suspension and 10 degrees of swivel, operator's presence sensor, retractable seat belt and arm rests
- Instructor Seat
- Suspended pedals
- Radio, speakers, and antenna



**POWERSTAR 90-120 PS UTILITY FAST PICK
US PRICE LIST**

Standard Equipment

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

655TL/710LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 126"

Dump Clearance: 93.6"

Digging Depth: 8.2"

Lift Capacity

Max Height @ 800mm: 2,478 LBS

59" high @ 800mm: 3,080 LBS

Breakout Force @ 800mm: 3,739 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 45 degrees

Bucket Dump Angle: 60 degrees

Skid Steer Loader bucket attach

**POWERSTAR 90-120 PS UTILITY FAST PICK
 US PRICE LIST**
Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
POWERSTAR 90	Cab	8,157 LB		\$71,065.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 100	Cab	10,031 LB		\$73,525.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 110	Cab	8,157 LB		\$76,196.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 120	Cab	8,158 LB		\$80,157.00
Includes the following Equipment				
4WD+EH Engage+Limited Slip (744581) \$277.00				
Heavy Duty Rear Axle (333411) \$665.00				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
540/1000 RPM PTO (743594) \$560.00				

**POWERSTAR 90-120 PS UTILITY FAST PICK
 US PRICE LIST**
Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

	759310	UTILITY PACKAGE UTILITY Package and Pricing Includes: UTILITY package discount 12x12 Power shuttle transmission (330276) Deluxe cab with instructor seat (744588) 25 mph (40 kph) transmission speed (759059) 2 Function mid mount valve and joystick (338125) 655TL Non Self Leveling loader with SSL attachment (336914) 84" Bucket (336750) Rear 3 point hitch ground control (332035) Allows for choice of the following tires: 18.4-30 Rear with 12.4R24 Front R1 Bias ply OR 18.4-34 Rear with 14.9R24 Front R1 Bias ply Radial			\$8,207.00
--	--------	--	--	--	------------

POWER TRAIN
AXLES

SD_T4010 FRONT AXLE

	744581	4WD+EH Engage+Limited Slip+HD Heavy-Duty Limited Slip Base equipment on PowerStar 120 Requires Heavy-Duty rear axle (333411)			\$277.00
--	--------	--	--	--	----------

SD_T4810 REAR AXLE

	333411	Heavy Duty Rear Axle Heavy-Duty Rear Axle Base Equipment on PowerStar 120 Required for 34 & 38 inch rear tires NOT compatible with Standard-Duty 4WD front axles (743559 or 744580) NOT compatible with 30 inch or smaller rear tires on PowerStar 90, 100 or 110			\$665.00
--	--------	---	--	--	----------

**POWERSTAR 90-120 PS UTILITY FAST PICK
US PRICE LIST**

TIRES
FRONT

SD T4940 FRONT WHEELS AND TIRES

4WD Bias Front Tires

		8235601	12.4-24 8PR			\$1,075.00
		8240604	14.9-24 8PR R1			\$1,622.00

REAR

SD T4950 REAR WHEELS AND TIRES

Bias Rear Tires

		8363801	18.4-30 12PR R1 FLAN 4WD Front Tire - 12.4-24 (8235601) 2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)			\$2,609.00
		8365501	18.4-34 10PR 4WD Front Tire - 14.9-24 (8240604) 2WD Front Tire - 10.00-16 (8125901)			\$2,875.00

PTO
REAR PTO

SD T8010 PTO

		743594	540/1000 RPM PTO			\$560.00
--	--	--------	------------------	--	--	----------

WEIGHTS
REAR

SD T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights Total weight - 440 lbs (200 kg) NOT compatible with 24" rear tires option Required with 2WD HD front axle			\$639.00
--	--	--------	---	--	--	----------

OPERATOR'S MANUALS

SD T9840 COUNTRY CONFIGURATION

		334256	Canada (FR) Config ROPS French operator manual			No Charge
		334257	USA Spanish Configuration Spanish operator manual			No Charge

**POWERSTAR 90-120 PS STANDARD FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- CommandArc# ergonomically places most frequently used controls to operator's right
- Ten repositionable vents for heating and air conditioning
- High visibility panel for better view of loader when at full height
- Full-size instructor seat
- Hydraulic shuttle lever
- 3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- Factory Installed Loader

PowerStar 90

86 Gross Engine hp
73 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 100

98 Gross Engine hp
85 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 110

107 Gross Engine hp
93 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 120

117 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

ALL MODELS:

Tier 4B Emissions Compliant:
(SCR + CEGR)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Dual Element Air Filter

Constant Engine RPM

Vertical Exhaust

30.3 gal Fuel Tank with Guard

2.8 gal AdBlue DEF Tank

Parking brake

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

Forward Reverse Synchronized Shuttle

25 mph (40 kph)

Speed varies with tire selection

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes-

Wet disk brakes

Hydraulically assisted

AXLES:

FRONT - 4WD

Limited Slip

Heavy Duty Electrohydraulic

FWD Engagement

Adjustable Tread Width from

56.6 in. to 76.6 in.

REAR

Heavy Duty Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

**POWERSTAR 90-120 PS STANDARD FAST PICK
US PRICE LIST**

Standard Equipment

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (63.9 L)

Steering Pump: 9.7 gpm (37.0 L)

Total Flow: 26.6 gpm (100.8 L)

(2) Open Center Remote Valves with
detent

2 Function Mid Mount Valve and Joystick

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

540/1000 rpm Hydraulic

-Electronic engagement

-Wet clutch

1-3/8 in. 6 splines

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control

Lift-O-Matic Plus single lever control

3 Point Hitch Ground Control

Mechanical Draft Control

5,620 Pounds Lift Capacity

Category II Ends

Telescopic Stabilizers

Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - Cab

120 amp Alternator

7-pin Outlet for trailer/implement lighting
and signals

3-pin Power Outlet (30 amp)

Single Pin (8 amp) Accessory Power
outlet

(2) - 12V power sockets

INSTRUMENTATION:

Analog Instrumentation with warning

lights for air cleaner service,

alternator, oil pressure, fuel

sediment/water sensor, PTO

engagement, head light high beam,

low fuel and parking brake,

digital speed readout

Gauges for fuel level, engine

temperature, tachometer and hour

meter

CAB LIGHTING:

Front: (2) Halogen Headlights and

(2) cab mounted worklights

Rear: (2) cab mounted worklights

Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, flat deck platform

with heat and air conditioning, tinted

windshield, retractable sun screen,

front and rear wiper and washer, two

doors with locks, two external mirrors,

openable side windows, hinged rear

window, high visibility panel

Steering Wheel - adjustable tilt

Seat - Cloth covered with air

suspension and 10 degrees of swivel,

operator's presence sensor, retractable

seat belt and arm rests

Instructor Seat

Suspended pedals

Radio, speakers, and antenna

MISCELLANEOUS:

Pivoting Engine Hood

SMV Emblem

Toolbox

WARRANTY:

New Holland Standard Warranty Applies

**POWERSTAR 90-120 PS STANDARD FAST PICK
US PRICE LIST**

Standard Equipment

LOADER:

665TL/720LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 134"

Dump Clearance: 101.4"

Digging Depth: 7"

Lift Capacity

Max Height @ 800mm: 2,632 LBS

59" high @ 800mm: 3,638 LBS

Breakout Force @ 800mm: 4,455 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 91"

Bucket Rollback Angle: 44 degrees

Bucket Dump Angle: 60 degrees

Skid Steer style Loader bucket attach

665TL/725LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 135"

Dump Clearance: 102.2"

Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 3,428 LBS

59" high @ 800mm: 5,549 LBS

Breakout Force @ 800mm: 5,661 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 93

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

**POWERSTAR 90-120 PS STANDARD FAST PICK
 US PRICE LIST**
Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
POWERSTAR 90	Cab	8,157 LB		\$71,065.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 100	Cab	10,031 LB		\$73,525.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 110	Cab	8,157 LB		\$76,196.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 120	Cab	8,158 LB		\$80,157.00
Includes the following Equipment				
4WD+EH Engage+Limited Slip (744581) \$277.00				
Heavy Duty Rear Axle (333411) \$665.00				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
540/1000 RPM PTO (743594) \$560.00				

**POWERSTAR 90-120 PS STANDARD FAST PICK
US PRICE LIST****Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

	X99803X	STANDARD PACKAGING Standard Package and Pricing Includes: 12x12 Power shuttle transmission (330276) Deluxe cab with instructor seat and hi-vis panel (334183) 25mph (40 kph) speed (759059) Heavy Duty 4WD front axle (744581) Heavy Duty rear axle (333411) 84" Bucket (336750) 540/1000 RPM PTO (743594) Rear 3 point hitch ground control (332035) Lift-O-Matic Plus (743595) 4 x 110 lb Rear wheel weights (330470) Requires one selection for each of the following: Mid mount valve and joystick: 2 Function mid mount valve and joystick or 2 Function mid mount valve and joystick + 3rd function diverter Loader: 665TL loader (select one) Tires: 18.4R30 Rear with 12.4R24 Front R1W Radial OR 18.4R34 Rear with 14.9R24 Front R1W Radial			\$12,940.00
--	---------	--	--	--	-------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Radial Tires					
	8235404	12.4R24 R1W			\$1,436.00
4WD Radial Front Tires					
	8239404	14.9R24 R1W			\$2,162.00

**POWERSTAR 90-120 PS STANDARD FAST PICK
US PRICE LIST**

REAR

SD T4950 REAR WHEELS AND TIRES

Radial Rear Tires

		8357404	18.4R30 R1W 4WD Front Tire - 12.4R24 (8235404) 2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)			\$3,480.00
		8365404	18.4R34 R1W 4WD Front Tire - 14.9R24 (8239404) 2WD Front Tire - 10.00-16 (8125901)			\$3,768.00

HYDRAULICS

MID-MOUNT

SD T8280 MID-MOUNT VALVES

		338125	2Mid-Mount w/Mec Joystick 2 function mid-mount valve and joystick			No Charge
		336780	2Mid-Mount w/Mec Joystick +Div 2 function mid-mount valve and joystick with 3rd function diverter Requires a Loader Bucket with Grapple NOT AVAILABLE as Factory Installed			\$765.00

LOADER

LOADER

SD T8110 LOADER BRACKETS

Heavy Duty Loader

		336740	HD Non Self Leveling Ldr +SSQA 665TL/720LU Non Self Leveling with Skid Steer Style Attachment			No Charge
		336744	HD Self Leveling Ldr +SSQA 665TL/725LU Mechanical Self Leveling with Skid Steer Style Attachment			\$1,147.00
		336746	HD Self Leveling Ldr +Euro 665TL/725LU Mechanical Self Leveling with Euro Style Attachment			\$1,147.00

OPERATOR'S MANUALS

SD T9840 COUNTRY CONFIGURATION

		334256	Canada (FR) Config ROPS French operator manual			No Charge
--	--	--------	--	--	--	-----------



**POWERSTAR 90-120 PS STANDARD FAST PICK
US PRICE LIST**

		334257	USA Spanish Configuration Spanish operator manual			No Charge
--	--	--------	---	--	--	-----------

**POWERSTAR 90-120 PS KLASIK FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- CommandArc# ergonomically places most frequently used controls to operator's right
- Ten repositionable vents for heating and air conditioning
- High visibility panel for better view of loader when at full height
- Full-size instructor seat
- Hydraulic shuttle lever
- 3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- Factory Installed Loader available

PowerStar 90

86 Gross Engine hp
73 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 100

98 Gross Engine hp
85 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 110

107 Gross Engine hp
93 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 120

117 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

ALL MODELS:

Tier 4B Emissions Compliant:

- (SCR + CEGR)
- Electronic Injection Bosch
- High-pressure Common Rail System
- Electric Engine Shutoff
- Hand and Foot Throttle Controls
- Grid Heater Starting Aid
- Dual Element Air Filter
- Constant Engine RPM
- Vertical Exhaust
- 30.3 gal Fuel Tank with Guard
- 2.8 gal AdBlue DEF Tank
- Parking brake

TRANSMISSION:

- LH side steering column mounted
- Power Shuttle
- 12 Forward and 12 Reverse Speeds
- (4) Synchronized Gears
- (3) Non-synchronized Ranges
- Forward Reverse Synchronized Shuttle
- 25 ph (40 kph)
- Speed varies with tire selection

STEERING/BRAKES:

- Hydrostatic Power Steering
- Brakes-
- Wet disk brakes
- Hydraulically assisted

AXLES:

- FRONT - 4WD
- Limited Slip
- Heavy Duty Electrohydraulic
- FWD Engagement
- Adjustable Tread Width from
- 56.6 in. to 76.6 in.

REAR

- Heavy Duty Flange Type
- Adjustable Tread Width 55.5 in.
- to 76.2 in.
- 4 Wheel Weights (2 x 110lb per side)

**POWERSTAR 90-120 PS KLASIK FAST PICK
US PRICE LIST**

Standard Equipment

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (63.9 L)

Steering Pump: 9.7 gpm (37.0 L)

Total Flow: 26.6 gpm (100.8 L)

(2) Open Center Remote Valves with
detent

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

540/1000 rpm Hydraulic

-Electronic engagement

-Wet clutch

1-3/8 in. 6 splines

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control

Mechanical Draft Control

Rear 3 Point Hitch Control

Lift-O-Matic Plus

5,620 Pounds Lift Capacity

Category II Ends

Telescopic Stabilizers

Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - Cab

120 amp Alternator

7-pin Outlet for trailer/implement lighting
and signals

3-pin Power Outlet (30 amp)

Single Pin (8 amp) Accessory Power
outlet

(2) - 12V power sockets

INSTRUMENTATION:

Analog Instrumentation with warning

lights for air cleaner service,

alternator, oil pressure, fuel

sediment/water sensor, PTO

engagement, head light high beam,

low fuel and parking brake,

digital speed readout

Gauges for fuel level, engine

temperature, tachometer and hour

meter

CAB LIGHTING:

Front: (2) Halogen Headlights and

(2) cab mounted worklights

Rear: (2) cab mounted worklights

Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, flat deck platform

with heat and air conditioning, tinted

windshield, retractable sun screen,

front and rear wiper and washer, two

doors with locks, two external mirrors,

openable side windows, hinged rear

window, high visibility panel

Steering Wheel - adjustable tilt

Seat - Cloth covered with air

suspension and 10 degrees of swivel,

operator's presence sensor, retractable

seat belt and arm rests

Instructor Seat

Suspended pedals

Radio, speakers, and antenna

MISCELLANEOUS:

Pivoting Engine Hood

SMV Emblem

Toolbox

WARRANTY:

New Holland Standard Warranty Applies

**POWERSTAR 90-120 PS KLASSIC FAST PICK
US PRICE LIST**

Standard Equipment

LOADER:

665TL/720LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 134"

Dump Clearance: 101.4"

Digging Depth: 7"

Lift Capacity

Max Height @ 800mm: 2,632 LBS

59" high @ 800mm: 3,638 LBS

Breakout Force @ 800mm: 4,455 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 91"

Bucket Rollback Angle: 44 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

**POWERSTAR 90-120 PS KLASSIC FAST PICK
 US PRICE LIST**
Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
POWERSTAR 90	Cab	8,157 LB		\$71,065.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 100	Cab	10,031 LB		\$73,525.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 110	Cab	8,157 LB		\$76,196.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 120	Cab	8,158 LB		\$80,157.00
Includes the following Equipment				
4WD+EH Engage+Limited Slip (744581) \$277.00				
Heavy Duty Rear Axle (333411) \$665.00				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
540/1000 RPM PTO (743594) \$560.00				

POWERSTAR 90-120 PS KLASIK FAST PICK
US PRICE LIST
Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

	X99804X	KLASSIC PACKAGING Klassik Package and Pricing Includes: 12x12 Power shuttle transmission (330276) Deluxe cab with instructor seat and hi-vis panel (334183) 25mph (40 kph) speed (759059) Heavy Duty 4WD front axle (744581) Heavy Duty rear axle (333411) 2 Function mid mount valve and joystick (338125) 540/1000 RPM PTO (743594) Rear 3 point hitch ground control (332035) Lift-O-Matic Plus (743595) 4 x 110 lb Rear wheel weights (330470) Allows for choice of the following tires: 18.4-30 Rear with 12.4R24 Front R1 BiasI ply OR 16.4R34 Rear with 13.6R24 Front R1W Radial			\$3,488.00
--	---------	--	--	--	------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Bias Front Tires					
	8235601	12.4-24 8PR			\$1,075.00
4WD Radial Front Tires					
	8236404	13.6R24 R1W			\$1,757.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Bias Rear Tires					
	8363801	18.4-30 12PR R1 FLAN			\$2,609.00
4WD Front Tire - 12.4-24 (8235601) 2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)					

**POWERSTAR 90-120 PS KLASSIC FAST PICK
US PRICE LIST**

Radial Rear Tires

		8302804	16.9R34 R1W 4WD Front Tire - 13.6R24 (8236404) 2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)			\$2,505.00
--	--	---------	---	--	--	------------

LOADER

LOADER

SD T8110 LOADER BRACKETS

Heavy Duty Loader

		336740	HD Non Self Leveling Ldr +SSQA 665TL/720LU Non Self Leveling with Skid Steer Style Attachment			\$7,025.00
		336742	HD Non Self Leveling Ldr +Euro 665TL/720LU Non Self Leveling with Euro Style Attachment			\$7,025.00
		743593	Less Front Loader			No Charge

SD T8140 BUCKET

		336750	84" Bucket			\$942.00
--	--	--------	------------	--	--	----------

WEIGHTS

FRONT

SD T2150 FRONT BALLAST

		333215	Front Carrier +6 88 lb Weights Total weight - 661 lbs (300 kg)			\$819.00
		335215	8 WEIGHTS 40 KG - CA Total weight - 837 lbs (380 kg)			\$1,036.00

OPERATOR'S MANUALS

SD T9840 COUNTRY CONFIGURATION

		334256	Canada (FR) Config ROPS French operator manual			No Charge
		334257	USA Spanish Configuration Spanish operator manual			No Charge

**POWERSTAR 90-120 PS A LA CARTE CAB
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- CommandArc# ergonomically places most frequently used controls to operator's right
- High visibility panel option for better view of loader when at full height
- Ten repositionable vents for heating and air conditioning
- Full-size instructor seat option
- Hydraulic shuttle lever
- Creeper transmission option
- 3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- Factory Installed Loader available

PowerStar 90

86 Gross Engine hp
73 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 100

98 Gross Engine hp
85 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 110

107 Gross Engine hp
93 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 120

117 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

ALL MODELS:

Tier 4B Emissions Compliant:

(SCR + CEGR)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Dual Element Air Filter

Constant Engine RPM

Vertical Exhaust

30.3 gal Fuel Tank with Guard

2.8 gal AdBlue DEF Tank

Parking brake

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

Forward Reverse Synchronized Shuttle

19 mph (30 kph)

Speed varies with tire selection

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (63.9 L)

Steering Pump: 9.7 gpm (37.0 L)

Total Flow: 26.6 gpm (100.8 L)

(2) Open Center Remote Valves with detent

3-POINT LIFT SYSTEM:

Right hand console mounted lever control

Mechanical Draft Control

5,620 Pounds Lift Capacity

Category II Ends

Telescopic Stabilizers

Flexible Lower Link Ends

**POWERSTAR 90-120 PS A LA CARTE CAB
US PRICE LIST**

Standard Equipment

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes-

Wet disk brakes

Hydraulically assisted

AXLES:

FRONT - 2WD (19 mph, 30 kph)

Inverted U-section type

Adjustable Tread Width from 57.0 in.

to 79.7 in.

FRONT - 4WD

Limited Slip

- PowerStar 90, 100 & 110:

Electrohydraulic FWD Engagement

Adjustable Tread Width from

56.6 in. to 76.6 in.

- PowerStar 120:

Heavy Duty Electrohydraulic FWD

Engagement

Adjustable Tread Width from

56.6 in. to 76.6 in.

REAR

- PowerStar 90, 100 & 110:

Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

- PowerStar 120:

Heavy Duty Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

PowerStar 90, 100 & 110:

540 rpm Hydraulic

PowerStar 120:

540/1000 rpm Hydraulic

-Electronic engagement

-Wet clutch

1-3/8 in. 6 splines

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - Cab

120 amp Alternator

7-pin Outlet for trailer/implement lighting
and signals

3-pin Power Outlet (30 amp)

Single Pin (8 amp) Accessory Power

outlet

12V power socket

INSTRUMENTATION:

Analog Instrumentation with warning

lights for air cleaner service,

alternator, oil pressure, fuel

sediment/water sensor, PTO

engagement, head light high beam,

low fuel and parking brake,

digital speed readout

Gauges for fuel level, engine

temperature, tachometer and hour

meter

LIGHTING:

Front: (2) Halogen Headlights and

(2) cab mounted worklights

Rear: (2) cab mounted worklights

Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, flat deck platform

with heat and air conditioning, tinted

windshield, retractable sun screen,

front and rear wiper and washer, two

doors with locks, two external mirrors,

openable side windows, hinged rear

window (opens completely)

Steering Wheel - adjustable tilt

Seat - Cloth covered with air

suspension and 10 degrees of swivel,

operator's presence sensor, retractable

seat belt and arm rests

Instructor seat

Suspended pedals

Radio, speakers, and antenna

**POWERSTAR 90-120 PS A LA CARTE CAB
US PRICE LIST**

Standard Equipment

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

655TL/710LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 126"
Dump Clearance: 93.6"
Digging Depth: 8.2"
Lift Capacity
Max Height @ 800mm: 2,478 LBS
59" high @ 800mm: 3,080 LBS
Breakout Force @ 800mm: 3,739 LBS
Reach @ Max Lift Height: 39.5"
Reach @ Ground Level: 90.7"
Bucket Rollback Angle: 45 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro Style Loader
bucket attach

655TL/715LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 125"
Dump Clearance: 93"
Digging Depth: 8"
Lift Capacity
Max Height @ 800mm: 3,179 LBS
59" high @ 800mm: 4,665 LBS
Breakout Force @ 800mm: 3,860 LBS
Reach @ Max Lift Height: 39.4"
Reach @ Ground Level: 90.5"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro style Loader
bucket attach

665TL/720LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 134"
Dump Clearance: 101.4"
Digging Depth: 7"
Lift Capacity
Max Height @ 800mm: 2,632 LBS
59" high @ 800mm: 3,638 LBS
Breakout Force @ 800mm: 4,455 LBS
Reach @ Max Lift Height: 43"
Reach @ Ground Level: 91"
Bucket Rollback Angle: 44 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro style Loader
bucket attach

665TL/725LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 135"
Dump Clearance: 102.2"
Digging Depth: 6.4"
Lift Capacity
Max Height @ 800mm: 3,428 LBS
59" high @ 800mm: 5,549 LBS
Breakout Force @ 800mm: 5,661 LBS
Reach @ Max Lift Height: 43"
Reach @ Ground Level: 93
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro style Loader
bucket attach

**POWERSTAR 90-120 PS A LA CARTE CAB
 US PRICE LIST**
Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
POWERSTAR 90	Cab	8,157 LB		\$71,065.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 100	Cab	10,031 LB		\$73,525.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 110	Cab	8,157 LB		\$76,196.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 120	Cab	8,158 LB		\$80,157.00
Includes the following Equipment				
4WD+EH Engage+Limited Slip (744581) \$277.00				
Heavy Duty Rear Axle (333411) \$665.00				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
540/1000 RPM PTO (743594) \$560.00				

**POWERSTAR 90-120 PS A LA CARTE CAB
US PRICE LIST****Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

	X99801X	LESS PACKAGING			No Charge
--	---------	----------------	--	--	-----------

OPERATOR PLATFORM

SD_T9200 OPERATOR STRUCTURE #1

Cab					
	744588	Deluxe Cab Includes instructor seat, rear wiper and washer, radio & internal mirror			No Charge
	334183	Deluxe Cab w/HiVis Panel Includes high visibility panel, instructor seat, rear wiper and washer, radio & internal mirror			\$557.00

POWER TRAIN

TRANSMISSION

SD_T2800 SPEED

	759059	40KPH - REAL ALL TYR 25 MPH (40 KPH) Transmission for 4WD			\$264.00
--	--------	--	--	--	----------

AXLES

SD_T4010 FRONT AXLE

	336858	2WD Standard Axle Heavy Duty Requires 20 MPH (30 KPH) Compatible with 655TL Requires rear wheel weights (330470) ONLY when ordered with 655TL NOT compatible with 665TL			(\$1,105.00)
	744581	4WD+EH Engage+Limited Slip+HD Heavy-Duty Limited Slip Base equipment on PowerStar 120 Requires Heavy-Duty rear axle (333411)			\$277.00

**POWERSTAR 90-120 PS A LA CARTE CAB
 US PRICE LIST**

SD_T4810 REAR AXLE

		333411	Heavy Duty Rear Axle Heavy-Duty Rear Axle Base Equipment on PowerStar 120 Required for 34 & 38 inch rear tires NOT compatible with Standard-Duty 4WD front axles (743559 or 744580) NOT compatible with 30 inch or smaller rear tires on PowerStar 90, 100 or 110			\$665.00
--	--	--------	---	--	--	----------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

2WD Front Tires						
		8126601	9.5L15 4 RIB 8 PLY			\$641.00
		8125801	7.50-16 8 PLY HD			\$489.00
		8125901	10.00-16 8 PLY HD			\$914.00
4WD Bias Front Tires						
		8235601	12.4-24 8PR			\$1,075.00
		8236501	13.6-24 8PR R1 FLANG			\$1,317.00
		8240604	14.9-24 8PR R1			\$1,622.00
4WD Radial Tires						
		8235404	12.4R24 R1W			\$1,436.00
4WD Radial Front Tires						
		8236404	13.6R24 R1W			\$1,757.00
		8239404	14.9R24 R1W			\$2,162.00
4WD Specialty Front Tires						
		8290904	12.5/80-18 10PR R4			\$1,717.00
		8247404	11.2R28 R1W			\$1,484.00
		8873402	360/80R20 TRI 2 HD Municipal tread			\$1,956.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Bias Rear Tires						
		8363801	18.4-30 12PR R1 FLAN 4WD Front Tire - 12.4-24 (8235601) 2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)			\$2,609.00
		8364604	16.9-34 8PR R1 4WD Front Tire - 13.6-24 (8236501) 2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)			\$1,878.00

**POWERSTAR 90-120 PS A LA CARTE CAB
US PRICE LIST**

		8365501	18.4-34 10PR 4WD Front Tire - 14.9-24 (8240604) 2WD Front Tire - 10.00-16 (8125901)			\$2,875.00
Radial Rear Tires						
		8357404	18.4R30 R1W 4WD Front Tire - 12.4R24 (8235404) 2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)			\$3,480.00
		8302804	16.9R34 R1W 4WD Front Tire - 13.6R24 (8236404) 2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)			\$2,505.00
		8365404	18.4R34 R1W 4WD Front Tire - 14.9R24 (8239404) 2WD Front Tire - 10.00-16 (8125901)			\$3,768.00
Specialty Rear Tires						
		8391904	19.5L-24 10 PR R4 4WD Front Tire - 12.5/80-18 (8290904)			\$2,658.00
		8372404	13.6R38 R1W 8372404 4WD Front Tire - 11.2R28 (8247404) 2WD Front Tire - 7.50-16 (8125801)			\$2,338.00
		8906401	440/80 R30 Municipal tread 4WD Front Tire - 360/80R20 (8873402)			\$3,644.00

HYDRAULICS

MID-MOUNT

SD_T8280 MID-MOUNT VALVES

		338125	2Mid-Mount w/Mec Joystick 2 function mid-mount valve and joystick			\$1,484.00
		336780	2Mid-Mount w/Mec Joystick +Div 2 function mid-mount valve and joystick with 3rd function diverter Requires a Loader Bucket with Grapple NOT AVAILABLE as Factory Installed			\$2,227.00

LOADER

LOADER

SD_T8110 LOADER BRACKETS

Standard Duty Loader

		336914	Non Self Leveling Ldr +SSQA 655TL/710LU Non Self Leveling with Skid Steer Attachment NOT compatible with 38" rear tires			\$6,062.00
--	--	--------	---	--	--	------------

**POWERSTAR 90-120 PS A LA CARTE CAB
 US PRICE LIST**

		336732	Non Self Leveling Ldr +Euro 655TL/710LU Non Self Leveling with Euro Style Attachment NOT compatible with 38" rear tires			\$6,062.00
		336734	Mech Self Leveling Ldr +SSQA 655TL/715LU Mechanical Self Leveling with Skid Steer Style Attachment NOT compatible with 38" rear tires			\$7,170.00
		336736	Mech Self Leveling Ldr +Euro 655TL/715LU Mechanical Self Leveling with Euro Style Attachment NOT compatible with 38" rear tires			\$7,170.00
Heavy Duty Loader						
		336740	HD Non Self Leveling Ldr +SSQA 665TL/720LU Non Self Leveling with Skid Steer Style Attachment			\$7,025.00
		336742	HD Non Self Leveling Ldr +Euro 665TL/720LU Non Self Leveling with Euro Style Attachment			\$7,025.00
		336744	HD Self Leveling Ldr +SSQA 665TL/725LU Mechanical Self Leveling with Skid Steer Style Attachment			\$8,138.00
		336746	HD Self Leveling Ldr +Euro 665TL/725LU Mechanical Self Leveling with Euro Style Attachment			\$8,138.00

SD T8140 BUCKET

		336750	84" Bucket			\$942.00
--	--	--------	------------	--	--	----------

PTO

REAR PTO

SD T8010 PTO

		743594	540/1000 RPM PTO			\$560.00
--	--	--------	------------------	--	--	----------

HITCH

REAR 3 POINT HITCH

SD T8130 3 POINT HITCH CONTROL

		332035	Mech 3 Pt Hitch Ground Control			\$261.00
--	--	--------	--------------------------------	--	--	----------

SD T8200 HITCH

		743595	Lift-O-Matic Plus Lift-O-Matic Plus			\$265.00
--	--	--------	---	--	--	----------

**POWERSTAR 90-120 PS A LA CARTE CAB
 US PRICE LIST**
WEIGHTS
FRONT

SD T2150 FRONT BALLAST

		333215	Front Carrier +6 88 lb Weights Total weight - 661 lbs (300 kg)			\$819.00
		335215	8 WEIGHTS 40 KG - CA Total weight - 837 lbs (380 kg)			\$1,036.00

REAR

SD T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights Total weight - 440 lbs (200 kg) NOT compatible with 24" rear tires option Required with 2WD HD front axle			\$639.00
--	--	--------	---	--	--	----------

OPERATOR'S MANUALS

SD T9840 COUNTRY CONFIGURATION

		334256	Canada (FR) Config ROPS French operator manual			No Charge
		334257	USA Spanish Configuration Spanish operator manual			No Charge

**POWERSTAR 90-120 PS A LA CARTE ROPS
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- CommandArc# ergonomically places most frequently used controls to operator's right
- Hydraulic shuttle lever
- 3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- Factory Installed Loader available

PowerStar 90

86 Gross Engine hp
73 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 100

98 Gross Engine hp
85 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 110

107 Gross Engine hp
93 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

PowerStar 120

117 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207 cu in (3.4 L) Displacement

ALL MODELS:

Tier 4B Emissions Compliant:

(SCR + CEGR)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Dual Element Air Filter

Constant Engine RPM

Vertical Exhaust

30.3 gal Fuel Tank with Guard

2.8 gal AdBlue DEF Tank

Parking brake

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

Forward Reverse Synchronized Shuttle

19 mph (30 kph)

Speed varies with tire selection

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (63.9 L)

Steering Pump: 9.7 gpm (37.0 L)

Total Flow: 26.6 gpm (100.8 L)

(2) Open Center Remote Valves with detent

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control

Mechanical Draft Control

5,620 Pounds Lift Capacity

Category II Ends

Telescopic Stabilizers

Flexible Lower Link Ends

**POWERSTAR 90-120 PS A LA CARTE ROPS
US PRICE LIST**

Standard Equipment

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes-

Wet disk brakes

Hydraulically assisted

AXLES:

FRONT - 2WD (19 mph, 30 kph)

Inverted U-section type

Adjustable Tread Width from 57.0 in.

to 79.7 in.

FRONT - 4WD

Limited Slip

- PowerStar 90, 100 & 110:

Electrohydraulic FWD Engagement

Adjustable Tread Width from

56.6 in. to 76.6 in.

- PowerStar 120:

Heavy Duty Electrohydraulic FWD

Engagement

Adjustable Tread Width from

56.6 in. to 76.6 in.

REAR

- PowerStar 90, 100 & 110:

Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

- PowerStar 120:

Heavy Duty Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

PowerStar 90, 100 & 110:

540 rpm Hydraulic

PowerStar 120:

540/1000 rpm Hydraulic

-Electronic engagement

-Wet clutch

1-3/8 in. 6 splines

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - ROPS

120 amp Alternator

7-pin Outlet for trailer/implement lighting
and signals

3-pin Power Outlet (30 amp)

Single Pin (8 amp) Accessory Power

outlet

12V power socket

INSTRUMENTATION:

Analog Instrumentation with warning

lights for air cleaner service,

alternator, oil pressure, fuel

sediment/water sensor, PTO

engagement, head light high beam,

low fuel and parking brake,

digital speed readout

Gauges for fuel level, engine temp,

tachometer and hour meter

LIGHTING:

ROPS

Front: (2) Halogen Headlights

Rear: (1) ROPS mounted worklight

Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISO-

mounted flat deck platform

Steering Wheel - adjustable tilt

Seat - Vinyl covered with mechanical

suspension, operator's presence

sensor, retractable seat belts and

arm rests

Suspended pedals

Locking brake pedals

MISCELLANEOUS:

Pivoting Engine Hood

SMV Emblem

Toolbox

**POWERSTAR 90-120 PS A LA CARTE ROPS
US PRICE LIST**

Standard Equipment

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

LOADER:

655TL/710LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 126"

Dump Clearance: 93.6"

Digging Depth: 8.2"

Lift Capacity

Max Height @ 800mm: 2,478 LBS

59" high @ 800mm: 3,080 LBS

Breakout Force @ 800mm: 3,739 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 45 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro Style Loader

bucket attach

665TL/720LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 134"

Dump Clearance: 101.4"

Digging Depth: 7"

Lift Capacity

Max Height @ 800mm: 2,632 LBS

59" high @ 800mm: 3,638 LBS

Breakout Force @ 800mm: 4,455 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 91"

Bucket Rollback Angle: 44 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

655TL/715LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 125"

Dump Clearance: 93"

Digging Depth: 8"

Lift Capacity

Max Height @ 800mm: 3,179 LBS

59" high @ 800mm: 4,665 LBS

Breakout Force @ 800mm: 3,860 LBS

Reach @ Max Lift Height: 39.4"

Reach @ Ground Level: 90.5"

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

665TL/725LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 135"

Dump Clearance: 102.2"

Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 3,428 LBS

59" high @ 800mm: 5,549 LBS

Breakout Force @ 800mm: 5,661 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 93"

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

**POWERSTAR 90-120 PS A LA CARTE ROPS
 US PRICE LIST**
Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
POWERSTAR 90	Rops	8,157 LB		\$60,161.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 100	Rops	8,157 LB		\$62,621.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 110	Rops	8,157 LB		\$65,292.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 120	Rops	8,157 LB		\$69,253.00
Includes the following Equipment				
4WD+EH Engage+Limited Slip (744581) \$277.00				
Heavy Duty Rear Axle (333411) \$665.00				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
540/1000 RPM PTO (743594) \$560.00				

**POWERSTAR 90-120 PS A LA CARTE ROPS
US PRICE LIST****Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

	X99801X	LESS PACKAGING			No Charge
--	---------	----------------	--	--	-----------

OPERATOR PLATFORM

SD_T9200 OPERATOR STRUCTURE #1

ROPS

	392315	Platform w/Foldable ROPS Includes tilt column			No Charge
	334190	Deluxe Platform w/FOPS Includes tilt column, FOPS canopy, noise reduction kit and 12V power outlet			\$1,661.00

POWER TRAIN

TRANSMISSION

SD_T2800 SPEED

	759059	40KPH - REAL ALL TYR 25 MPH (40 KPH) Transmission for 4WD			\$264.00
--	--------	---	--	--	----------

AXLES

SD_T4010 FRONT AXLE

	336858	2WD Standard Axle Heavy Duty Requires 20 MPH (30 KPH) Compatible with 655TL Requires rear wheel weights (330470) ONLY when ordered with 655TL NOT compatible with 665TL			(\$1,105.00)
	744581	4WD+EH Engage+Limited Slip+HD Heavy-Duty Limited Slip Base equipment on PowerStar 120 Requires Heavy-Duty rear axle (333411)			\$277.00

**POWERSTAR 90-120 PS A LA CARTE ROPS
US PRICE LIST**

SD T4810 REAR AXLE

		333411	Heavy Duty Rear Axle Heavy-Duty Rear Axle Base Equipment on PowerStar 120 Required for 34 & 38 inch rear tires NOT compatible with Standard-Duty 4WD front axles (743559 or 744580) NOT compatible with 30 inch or smaller rear tires on PowerStar 90, 100 or 110			\$665.00
--	--	--------	---	--	--	----------

TIRES

FRONT

SD T4940 FRONT WHEELS AND TIRES

2WD Front Tires						
		8126601	9.5L15 4 RIB 8 PLY			\$641.00
		8125801	7.50-16 8 PLY HD			\$489.00
		8125901	10.00-16 8 PLY HD			\$914.00
4WD Bias Front Tires						
		8235601	12.4-24 8PR			\$1,075.00
		8236501	13.6-24 8PR R1 FLANG			\$1,317.00
		8240604	14.9-24 8PR R1			\$1,622.00
4WD Radial Tires						
		8235404	12.4R24 R1W			\$1,436.00
4WD Radial Front Tires						
		8236404	13.6R24 R1W			\$1,757.00
		8239404	14.9R24 R1W			\$2,162.00
4WD Specialty Front Tires						
		8290904	12.5/80-18 10PR R4			\$1,717.00
		8247404	11.2R28 R1W			\$1,484.00
		8873402	360/80R20 TRI 2 HD Municipal tread			\$1,956.00

REAR

SD T4950 REAR WHEELS AND TIRES

Bias Rear Tires						
		8363801	18.4-30 12PR R1 FLAN 4WD Front Tire - 12.4-24 (8235601) 2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)			\$2,609.00
		8364604	16.9-34 8PR R1 4WD Front Tire - 13.6-24 (8236501) 2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)			\$1,878.00

**POWERSTAR 90-120 PS A LA CARTE ROPS
US PRICE LIST**

		8365501	18.4-34 10PR 4WD Front Tire - 14.9-24 (8240604) 2WD Front Tire - 10.00-16 (8125901)			\$2,875.00
Radial Rear Tires						
		8357404	18.4R30 R1W 4WD Front Tire - 12.4R24 (8235404) 2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)			\$3,480.00
		8302804	16.9R34 R1W 4WD Front Tire - 13.6R24 (8236404) 2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)			\$2,505.00
		8365404	18.4R34 R1W 4WD Front Tire - 14.9R24 (8239404) 2WD Front Tire - 10.00-16 (8125901)			\$3,768.00
Specialty Rear Tires						
		8391904	19.5L-24 10 PR R4 4WD Front Tire - 12.5/80-18 (8290904)			\$2,658.00
		8372404	13.6R38 R1W 8372404 4WD Front Tire - 11.2R28 (8247404) 2WD Front Tire - 7.50-16 (8125801)			\$2,338.00
		8906401	440/80 R30 Municipal tread 4WD Front Tire - 360/80R20 (8873402)			\$3,644.00

HYDRAULICS

MID-MOUNT

SD_T8280 MID-MOUNT VALVES

		338125	2Mid-Mount w/Mec Joystick 2 function mid-mount valve and joystick			\$1,484.00
		336780	2Mid-Mount w/Mec Joystick +Div 2 function mid-mount valve and joystick with 3rd function diverter Requires a Loader Bucket with Grapple NOT AVAILABLE as Factory Installed			\$2,227.00

LOADER

LOADER

SD_T8110 LOADER BRACKETS

Standard Duty Loader

		336914	Non Self Leveling Ldr +SSQA 655TL/710LU Non Self Leveling with Skid Steer Attachment NOT compatible with 38" rear tires			\$6,062.00
--	--	--------	---	--	--	------------

**POWERSTAR 90-120 PS A LA CARTE ROPS
 US PRICE LIST**

		336732	Non Self Leveling Ldr +Euro 655TL/710LU Non Self Leveling with Euro Style Attachment NOT compatible with 38" rear tires			\$6,062.00
		336734	Mech Self Leveling Ldr +SSQA 655TL/715LU Mechanical Self Leveling with Skid Steer Style Attachment NOT compatible with 38" rear tires			\$7,170.00
		336736	Mech Self Leveling Ldr +Euro 655TL/715LU Mechanical Self Leveling with Euro Style Attachment NOT compatible with 38" rear tires			\$7,170.00
Heavy Duty Loader						
		336740	HD Non Self Leveling Ldr +SSQA 665TL/720LU Non Self Leveling with Skid Steer Style Attachment			\$7,025.00
		336742	HD Non Self Leveling Ldr +Euro 665TL/720LU Non Self Leveling with Euro Style Attachment			\$7,025.00
		336744	HD Self Leveling Ldr +SSQA 665TL/725LU Mechanical Self Leveling with Skid Steer Style Attachment			\$8,138.00
		336746	HD Self Leveling Ldr +Euro 665TL/725LU Mechanical Self Leveling with Euro Style Attachment			\$8,138.00

SD T8140 BUCKET

		336750	84" Bucket			\$942.00
--	--	--------	------------	--	--	----------

PTO

REAR PTO

SD T8010 PTO

		743594	540/1000 RPM PTO			\$560.00
--	--	--------	------------------	--	--	----------

HITCH

REAR 3 POINT HITCH

SD T8130 3 POINT HITCH CONTROL

		332035	Mech 3 Pt Hitch Ground Control			\$261.00
--	--	--------	--------------------------------	--	--	----------

SD T8200 HITCH

		743595	Lift-O-Matic Plus Lift-O-Matic Plus			\$265.00
--	--	--------	---	--	--	----------

POWERSTAR 90-120 PS A LA CARTE ROPS
US PRICE LIST
WEIGHTS
FRONT

SD T2150 FRONT BALLAST

		333215	Front Carrier +6 88 lb Weights Total weight - 661 lbs (300 kg)			\$819.00
		335215	8 WEIGHTS 40 KG - CA Total weight - 837 lbs (380 kg)			\$1,036.00

REAR

SD T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights Total weight - 440 lbs (200 kg) NOT compatible with 24" rear tires option Required with 2WD HD front axle			\$639.00
--	--	--------	---	--	--	----------

OPERATOR'S MANUALS

SD T9840 COUNTRY CONFIGURATION

		334256	Canada (FR) Config ROPS French operator manual			No Charge
		334257	USA Spanish Configuration Spanish operator manual			No Charge