

PERFORMANCE TRUCK - CLEVELAND (C359)
1287 HIGHWAY 59 NORTH
CLEVELAND, TEXAS 77328

HGAC BUY
3555 TIMMONS LANE, STE 120
HOUSTON, TEXAS 77027
USA

DREW VEST
CELL PHONE: 281-610-8007
OFFICE PHONE: 713-844-7111
EMAIL: AVEST@PERFORMANCETRUCK.COM

Vehicle Summary

Unit		Chassis	
Model:	Model L770	Fr Axle Load (lbs):	20000
Type:	Full Truck	Rr Axle Load (lbs):	22700
Description 1:	Spec for Cody	G.V.W.R. (lbs):	42700
Description 2:	ASL LH	G.C.W. (lbs):	62000
Application		Road Conditions:	
Intended Serv.:	Refuse/On-Highway	Class A (Highway)	94
Commodity:	Refuse, Scrap, Recycling	Class B (Hwy/Mtn)	6
Body		Class C (Off-Hwy)	0
Type:	Automated Side Loader / Push-Out	Class D (Off-Road)	0
Length (ft):	30	Maximum Grade:	6
Height (ft):	13	Wheelbase (in):	195
Max Laden Weight (lbs):	10000	Overhang (in):	54
Trailer		Fr Axle to BOC (in):	0.1
No. of Trailer Axles:	0	Cab to Axle (in):	194.9
Type:		Cab to EOF (in):	248.9
Length (ft):	0	Overall Comb. Length (in):	306.3
Height (ft):	0	Special Req.	
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

Price Level: January 1, 2026

100% Complete

Date: March 20, 2026

Deal: Spec for Cody

Quote Number: QUO-1247926-L2Z1P3

Printed On: 3/20/2026 10:49:41 AM

Sales Code	Std/ Opt	Description	\$ List	Weight
Base Model				
0005201	S	Model L770 Kenworth's Model L770 is built to withstand the harsh demands of the refuse industry. The rugged, aluminum cab delivers best-in-class durability for increased uptime and lap seam construction on a zinc-coated steel sub-frame for corrosion resistance. Bulkhead-style doors provide years of watertight performance. This low-cab forward vehicle adds a new dimension of productivity and versatility. An industry-leading, 65-degree cab tilt enhances maintenance and serviceability. Body installation is cost effective and efficient and the center console provides convenient access to body control integration points.		
0091180	S	Refuse, Scrap, Recycling	0	0
0093035	S	Refuse/On-Highway Truck or tractor which hauls refuse, recycled material, etc. Includes roll-on/roll-off container movement, as well as hauling refuse from transfer stations to, but not into, landfills.	0	0
0095220	O	Automated Side Loader / Push-Out	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0514150	S	10-3/4" Steel Rails To 305" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	0	87
0644090	S	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	0	0
0651090	S	Omit Rear Mudflaps and Hangers	0	0
Front Axle & Equipment				
1011890	S	PACCAR FX-20 Steer Axle 20,000 lbs. 4" Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Front axle is designed for demanding applications such as construction, heavy haul, refuse, and other vocational uses. Robust forged steel beam construction for long-lasting performance. It utilizes innovative tapered kingpin roller bearings for more efficient operation and improved steering efficiency. The PACCAR Steer Axle comes standard with the PACCAR warranty of 5 years, 750,000 miles.	0	0

Price Level: January 1, 2026

Deal: Spec for Cody

Printed On: 3/20/2026 10:49:41 AM

100% Complete

Date: March 20, 2026

Quote Number: QUO-1247926-L2Z1P3

Sales Code	Std/ Opt	Description	\$ List	Weight
1114030	S	Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	0	0
1243010	S	Power Steering Sheppard M100 Dual Gear For use with 16,000 to 20,000 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	0	0
1354850	S	PHP10 Iron PreSet PLUS Hubs - Air Disc Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	0	0
1354870	S	Severe Service Disc Brake Rotor For refuse applications, providing the braking torque necessary to slow or stop the vehicle.	0	0
1380400	O	Meritor Refuse Air Disc Front Brakes		0

Rear Axle & Equipment

1511440	O	Meritor RS23-161 23,000 lb Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.		-2,391
1616290	O	PHP10 Aluminum PreSet PLUS Hubs		0
1680440	O	Refuse Service Brakes, Steer And Drive Axles Designed for heavy-duty applications for refuse industry, providing long brake life, safety and performance.	0	0
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680525	O	Pneumatic Park Brake	0	0
1680760	O	Meritor Q+ Air Cam Rear Drum Brakes 16.5x8.625		0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the	0	0

Price Level: January 1, 2026

100% Complete

Date: March 20, 2026

Deal: Spec for Cody

Quote Number: QUO-1247926-L2Z1P3

Printed On: 3/20/2026 10:49:41 AM

Sales Code	Std/ Opt	Description	\$ List	Weight
		lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.		
1704890	O	Ratio 4.89 Rear Axle	0	0
1816090	O	Reyco 102CC 23,000 lb Single Drive		-770
1911010	S	Steel Suspension Insert Up To 77" Overhang	0	-130
Engine & Equipment				
2074806	O	PACCAR PX-9 350@2000 GOV@2200 1050@1200 Productivity (2024 Emissions)		0
		N21350 C121 64....Maximum Accelerator Pedal Ve N21370 C128 64....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 5.....Timer Setting (P030) N21610 C188 39....Low Ambient Temperature Thre N21620 C189 60....Intermediate Ambient Tempera N21630 C190 80....High Ambient Temperature Thr N21550 C206 35....Engine Load Threshold (P516) N21340 C209 120...Hard Maximum Speed Limit (P1 N21510 C225 YES...Enable Idle Shutdown Park Br N21450 C231 NO....Gear Down Protection (P026) N21570 C233 NO....Idle Shutdown Manual Overrul N21440 C234 NO....Engine Protection Shutdown (N21480 C238 NO....Auto Engine Brake in Cruise N21470 C239 NO....Cruise Control Auto Resume (N21430 C333 0.....Reserve Speed Limit Offset (N21410 C334 0.....Maximum Cycle Distance (N202 N21590 C382 YES...Enable Hot Ambient Automatic N21500 C395 0.....Expiration Distance (N209) N21530 C396 YES...Enable Impending Shutdown Wa N21540 C397 60....Timer For Impending Shutdown N21320 C399 100...Standard Maximum Speed Limit N21400 C400 252...Reserve Speed Function Reset N21420 C401 10....Maximum Active Distance (N20 N21330 C402 0.....Expiration Distance (N207)		
2091120	S	EMUX Electronics Architecture	0	0
2091305	O	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Override	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0
2092016	O	Typical Operating Speed 62 MPH	0	0

Price Level: January 1, 2026

100% Complete

Date: March 20, 2026

Deal: Spec for Cody

Quote Number: QUO-1247926-L2Z1P3

Printed On: 3/20/2026 10:49:41 AM

Sales Code	Std/ Opt	Description	\$ List	Weight
2092031	S	Powertrain Optimized for Fuel Economy Best analysis for vehicles which operate at or near cruise speed 90 plus percent of time.	0	0
2140200	O	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140450	O	Remote PTO/Throttle, 12-Pin Eng Bay Remote Control Provision		0
2140660	O	CARB Emission Compliant Engine	0	0
2140700	S	EPA Engine Idling Compliance	0	0
2147460	S	Bed Plate for PX-9, L9N Engines Designed to increase engine longevity by incorporating a stiffener bracket on the bottom side of the engine, inside the oil pan, for additional reinforcement. Required for all PX-9/L9N refuse applications and recommended for other high load 9-liter applications.	0	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2522110	O	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0	0
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2621000	S	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	0	0
2723210	S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2921110	S	PACCAR Fuel/Water Separator Standard Service PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo	0	0

Price Level: January 1, 2026

100% Complete

Date: March 20, 2026

Deal: Spec for Cody

Quote Number: QUO-1247926-L2Z1P3

Printed On: 3/20/2026 10:49:41 AM

Sales Code	Std/ Opt	Description	\$ List	Weight
		Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 520 1242 sq in, 579 1325 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 567 1440 sq in, 589 1604 sq in.		
3120450	S	Stainless Steel Grille	0	0
3261980	S	Heavy Duty Air Cleaner Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3367200	S	Exhaust Vertical LH DPF/SCR LH Back of Cab Vertical, Single Module	0	0
3387870	S	24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	0	0
Transmission & Equipment				
4052920	S	Allison 3000 RDS-P Transmission, Gen 6 Rugged Duty Series	0	0
4210080	O	1710 HD Driveline, 1 Midship Bearing		-20
4252940	S	Allison Neutral At Stop Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0	0
4253160	S	Allison Fuelsense Dynactive With Dynamic Shift Sensing	0	0
4256020	S	Console Mounted Push Button Shifter	0	0
4256640	O	Allison 6-Speed Configuration, Close Ratio Gears 3000 Series Transmissions.	0	0
4256870	O	Allison Output Function S Neutral Indicator Allison output function S Neutral Indicator for PTO. Required on Refuse Packer Applications. With this configuration NEUTRAL only, PTO engagement is permitted only when the transmission is in Neutral. Once the transmission is in Neutral, the PTO is automatically engaged and fast idle is initiated when the PTO switch is on. In addition with this configuration Pack-on-the-fly, the PTO is automatically engaged and fast idle is initiated when the PTO switch is On concurrently with shifting of the transmission to Neutral.	0	0
Air & Trailer Equipment				
4510210	S	Bendix AD-HF EP Air Dryer, Heater Coalescing filter, extended purge. Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0	0

Price Level: January 1, 2026

100% Complete

Date: March 20, 2026

Deal: Spec for Cody

Quote Number: QUO-1247926-L2Z1P3

Printed On: 3/20/2026 10:49:41 AM

Sales Code	Std/ Opt	Description	\$ List	Weight
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0

Tires & Wheels

5004040	S	FF: CN 20ply 315/80R22.5 HAU3 WT Efficiency Rating: Fair Waste transportation and other high scrub, urban applications.	0	0
5104770	S	RR: CN 14Ply 295/75R22.5 HDL3 ECO+	0	0
5190004	O	Code-rear Tire Qty 04	0	0
5210550	S	FF: Accur Stl Armor 29039PK 22.5X9.00 PHP10-5 Hand Holes	0	0
5310610	O	RR: Accur Steel Armor 50344PK 22.5X8.25 Heavy Duty, 5 Hand Holes		8
5390004	O	Code-rear Rim Qty 04	0	0

Fuel Tanks

5532040	S	23" Aluminum 50 Gallon Fuel Tank RH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	0	0
5603050	S	Location RH BOC 50 Gallon	0	0
5650490	S	Fuel Cooler Required with single fuel tank	0	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	O	DEF To Fuel Ratio 2:1 Or Greater	0	0
5655069	S	DEF Tank 520, 7.3 Gal	0	0

Battery Box & Bumper

6021500	S	Steel Space Saver Battery Box LH Back Of Cab	0	0
6121700	S	Steel Bumper Channel Painted Includes two front tow eyes with pins	0	0

Cab & Equipment

Price Level: January 1, 2026

100% Complete

Date: March 20, 2026

Deal: Spec for Cody

Quote Number: QUO-1247926-L2Z1P3

Printed On: 3/20/2026 10:49:41 AM

Sales Code	Std/ Opt	Description	\$ List	Weight
6501080	S	53" LCF ProBilt Cab LH Drive Includes steel frames with alum and fiberglass panels, all alum doors, dual door stops, door locks, tinted safety glass thru-out, cab and door mounted entry grab handles, 65 degree hydraulic tilt, stainless steel grille, dual rear cab fenders, service module BOC (cab tilt pump, oil fill and dipstick, coolant fill and check, fluid fill and dipstick for auto trans), door mounted armrests, power windows, doghousefull insulation, rubber floor mats, ergonomic center control console, removable instrument panel, Driver Information Display, LED backlit gauges, adjustable side flip-down interior sunvisor, 16" steering wheel with integrated horn button, tilt/telescopic adjustable column, over-door storage, driver and passenger side cup holders, USB charging port and 12VDC charging outlet, header includes HVAC controls and 12V power connection behind header cover, rear cab corner windows, 18" bolt-on step each side, self-canceling turn signals and front directional and side mounted turn signals.	0	0
6540160	S	Thermal Insulation Package in Cab The thermal insulation package is designed to make the cab thermally efficient in extreme temperatures. The model 520 adds insulation surrounding the doghouse to reduce engine heat transmitted to the cab.	0	0
6800500	S	4.5" Rubber Flares On Cab And wheel well fenders	0	0
6911720	S	Peterbilt Driver Seat	0	0
6921720	S	Peterbilt Passenger Seat	0	0
6939410	S	Non-Air Ride Driver	0	0
6939440	S	Low Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939510	S	Non-Air Ride Passenger	0	0
6939540	S	Low Back Passenger	0	0
6939570	S	Vinyl Passenger	0	0
7000000	S	Gray Interior Color Includes ABS Gray Headliner & Rear Cab Panel, Gray Vinyl Engine Tunnel Cover. For LH, RH, and Dual Steer Dual Seated Power Windows are standard on both doors. For Dual Steer RH stand-up the LH Window is Power and the RH Window is a Manual Sliding window.	0	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	0
7001620	S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7110680	S	Exterior Cab Entry Grabhandle	0	0

Price Level: January 1, 2026

100% Complete

Date: March 20, 2026

Deal: Spec for Cody

Quote Number: QUO-1247926-L2Z1P3

Printed On: 3/20/2026 10:49:41 AM

Sales Code	Std/ Opt	Description	\$ List	Weight
		Textured; NFPA compliant. Available on Day Cab specifications only.		
7220130	S	Rear Window Back of Cab Standard Tint 18.5in X 54in	0	0
7230350	S	2-Piece Flat Windshield	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7561260	S	Black LH/RH Tri-plane Mirrors, Heated, Motorized, Mounted to Doors. Features: Heated on All Three Surfaces, Upper/Lower Mirrors are Convex and Middle is a Flat Pane Motorized Mirror.	0	0
7610020	S	(1) Air Horn 15" Painted Mounted under cab.	0	0
7725720	S	No Head Unit or Audio Speakers Selected	0	0
7788335	S	Global Telematics Hardware	0	0
7852150	S	Peterbilt Pantograph Windshield Wipers With intermittent feature.	0	0
7900970	S	Backup Alarm Wiring To EOF	0	0
8011850	S	Transmission Oil Temperature (Main) Located in Digital Cluster Display.	0	0
8021315	S	Air Restriction Indicator Mounted on exhaust stanchion	0	0
8070860	O	Main Instrumentation Panel Digital Cluster 7" Display includes: Physical (Analog) - Speedometer, Tachometer, Oil Pressure, Coolant Temp and Display Gauges - Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure for air brake trucks.	0	0
8110090	S	Headlights Single Rectangular Halogen	0	0
8120570	S	(5) LED Clearance With (2) LED Marker Lights Includes (5) lights mounted on roof of cab and (1) cab side marker light mounted in front of each cab door	0	0
8133900	S	None Furnished Stop/Tail/Backup Lights Available with full truck only, not available with tractor	0	0
8134160	O	Self-Canceling Turn Signal	0	2
Paint				
8500710	S	Standard Paint Color Selection		0
8530770	O	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85700 BUMPER L0001EA BLACK N85500 CAB ROOF L0006EY WHITE	0	0

Price Level: January 1, 2026

100% Complete

Date: March 20, 2026

Deal: Spec for Cody

Quote Number: QUO-1247926-L2Z1P3

Printed On: 3/20/2026 10:49:41 AM

Sales Code	Std/ Opt	Description	\$ List	Weight
		N85200 FRAME L0001EA BLACK		

Shipping Destination

Options Not Subject To Discount

9400090	S	Kenworth Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0
9400094	S	PACCAR PX-9 Standard Coverage 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0	0
9407147	O	Fuel Price Index Factor \$0 NET	0	0
9408634	O	SmartLINQ RD - 5YR Sub PACCAR PX Engines		0
9408701	O	Base Warr: Emissions (CARB Operation) 5YR/150K MI - PX-9 Engine		0

Miscellaneous

9409097	O	State Of Registry: Washington	0	0
9409641	O	Model Year 2026 Engine	0	0
9409749	O	2024 Series Emissions Engine	0	0

Promotions

Special Requirements

- Special Requirement 1 0098170
- Special Requirement 2
- Special Requirement 3
- Special Requirement 4

Order Comments

Total Weight (lbs)

13,261

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------