



PERFORMANCE TRUCK - CLEVELAND (C359)
1287 HIGHWAY 59 NORTH
CLEVELAND, Texas 77328

HGAC BUY
3555 TIMMONS LANE, STE 120
HOUSTON, Texas 77027
United States of America

Drew Vest
Cell Phone: 281-610-8007
Office Phone: 713-844-7111
Email: avest@performancetruck.com

Vehicle Summary

Unit		Chassis	
Model:	T380 Series Conventional	Fr Axle Load (lbs):	10000
Type:	Full Truck	Rr Axle Load (lbs):	17000
Description 1:	KW Model T380 Trk	G.V.W.R. (lbs):	27000
Description 2:	HT07-26	G.C.W. (lbs):	27000
Application		Road Conditions:	
Intended Serv.:	Local Pickup & Delivery	Class A (Highway)	90
Commodity:	General Freight	Class B (Hwy/Mtn)	10
Body		Class C (Off-Hwy)	0
Type:	Van	Class D (Off-Road)	0
Length (ft):	10	Maximum Grade:	6
Height (ft):	12	Wheelbase (in):	157
Max Laden Weight (lbs):	4000	Overhang (in):	33
Trailer		Fr Axle to BOC (in):	67.5
No. of Trailer Axles:	0	Cab to Axle (in):	89.5
Type:		Cab to EOF (in):	122.5
Length (ft):	0	Overall Comb. Length (in):	230
Height (ft):	0	Special Req.	
Kingpin Inset (in):	0	U.S. Domestic Registry, 50-state.	
Corner Radius (in):	0		
Restrictions			
Length (ft):	75		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

Std/ Opt	Description	Weight
Model		
S	T380 Series Conventional	9,930
S	T380 Aero Hood	0
O	CARB Low NOX Omnibus Registration Guidelines Dealer/Customer acknowledges that this vehicle is NOT intended for registration or domicile/primary use in the State of California.	0
O	EPA Clean Idle Label - PACCAR PX Engines	0
O	T380 Manual	0
O	State of Registry: Texas	0
Engine & Equipment		
S	PACCAR PX-7 200 200@2400 600@1300, 2024 With Turbo Exhaust Brake (VGT Brake) N09420 C333 0.....Reserve Speed Limit Offset (N09380 C334 0.....Maximum Cycle Distance (C334 N09360 C400 252...Reserve Speed Function Reset N09200 C399 100...Standard Maximum Speed Limit N09400 C401 10....Maximum Active Distance (C40 N09220 C402 0.....Expiration Distance (C402) N09540 C395 0.....Expiration Distance (C395) N09260 C121 64....Max Vehicle Speed in Top Gea N09440 C234 NO....Engine Protection Shtdwn N09460 C231 NO....Gear Down Protection N09580 C133 5.....Idle Shtdwn Time N09680 C233 NO....Idle Shtdwn Override N09480 C132 1400..Max PTO Speed N09300 C128 64....Max Cruise Control Speed N09500 C239 NO....Cruise Control Auto Resume N09520 C238 NO....Auto Engine Brake in Cruise N09780 C190 80....High Ambient Temperature Thr N09740 C188 40....Low Ambient Temperature Thre N09760 C189 60....Intermediate Ambient Tempera N09720 C382 YES...Enable Hot Ambient Automatic N09600 C396 YES...Enable Impending Shutdown Wa N09620 C397 60....Timer For Impending Shutdown N09640 C206 35....Engine Load Threshold N09560 C225 YES...Enable Idle Shutdown Park Br	0
O	EPA Emissions Compliant Engine	0
S	PremierSpec	0
O	Gearing Analysis: Fuel Economy fuel efficiency results.	0
O	Customer's Typical Operating Spd: 60 MPH	0

Std/ Opt	Description	Weight
O	EWI Tracking - A2 Engine Module Chassis	0
	RegistrationYear Year of Registration: 2026	0
	Effective VSL Setting NA	0
O	Engine Idle Shutdown Timer Enabled	0
O	Enable EIST Ambient Temp Overrule	0
	Eff EIST NA Expiration Miles Use only with MX and Cummins engines	0
S	Air Compressor: Cummins 18.7 CFM - Cummins and PX	0
S	Air Cleaner: MD Composite Engine Mounted	0
S	Fan Hub: Horton On/Off for PX-7 or B6.7N	0
S	Cooling Module: 2.1M MD - Aero Hood 1000 Square Inches	0
S	EXH: Single Can 2024 PX-7 Horizontal Under Rail With Horizontal Tailpipe Below Rail RH Rail Back-of-Cab	0
S	Fuel Filter: PACCAR 2.1M MD for PX-7 or PX-9 Fuel/water separator for 2021 and later engines.	0
S	Run Aid:None *For Fuel Filter	0
S	Start Aid:None *For Fuel Filter	0
O	Alternator: 160 amp Brush Type T3	0
S	Batteries: 2 PACCAR GP31 Threaded Post (700-730) 1400-1460 CCA dual purpose.	0
S	Starter: PACCAR 90P47 12V with PACCAR PX-7	0
S	12V Low Voltage Disconnect for Battery Protection	0
Transmission & Clutch		
O	Transmission: Fuller FS6406A 6-speed synchro. *Torque Limit: 660 pound-feet.	152
O	Clutch: Eaton 14in 1 Plate Ceramic Dampened Up to 660 LBFT Engine torque	0
O	Clutch: Hydraulic Assist For use with 2.1M Medium Duty only	10
O	Driveline: 2 Dana Standard-Duty; 1 Centerbearing *Standard duty is 1710 series.	67

Front Axle & Equipment

Std/ Opt	Description	Weight
O	Hendrickson Steertek Front Axle rated 10k Standard Track 3.32 in. drop.	-13
S	Front Brakes: 14.6K Bendix ES S-Cam 16.5x5 in.	0
S	Front Brake Drums: 14.6K 16.5x5 in. cast.	0
S	Front Hub: Iron Hub Pilot 14,600 lbs. 11-1/4 in. bolt circle. For use w/ air disc brakes. Consider wheelguards (5850002) w/ aluminum wheels.	0
S	ConMet PreSet Plus Hub Package; Front Axle.	0
S	Hubcap: Front Vented.	0
S	Front Auto Slack Adjuster for Drum Brakes.	0
O	Front Springs: Mono-leaf 10K W/ Shock Absorbers With maintenance-free elastomer spring pin bushings.	-4
S	Single Power Steering Gear: 13.2K for Air Brakes.	0
O	5 mm Front Suspension Spacer Block	0
Rear Axle & Equipment		
O	Single Meritor MS17-13X3 Rear Axle rated at 17K with air brakes.	-102
O	Rear Axle Ratio - 3.90.	0
S	Single Rear Brakes 16-1/2x7 in. Bendix ES- extended service S-cam.	0
S	Single Rear Brake Drums: Cast S-Cam Single For use with 15x8.625", 16.5X7" or 16.5X8.625" brake.	0
S	Single Rear Hubs: Iron Hub Pilot 26k; 11.25" Bolt circle. Requires "R" series outer ends.	0
S	ConMet PreSet Plus Hub Package; Single Rear Axle.	0
S	Single Rear Axle Automatic Slack Adjusters. For use with drum brakes.	0
S	Spring Brake: 3030 Long Stroke Single 3 in. travel. For drum brakes. Helps keep brakes in adjustment longer.	0
S	Bendix 4S/4M Anti-Lock Brake System.	0
O	Air Operated Park Brake	0
S	Rear suspension: single Reyco 79KB taperleaf 21K. Medium-duty. Unladen Height: 9 in. Laden Height: 7.5 in. Not rear air disc brake compatible.	0
Tires & Wheels		
O	Front Tires: Yokohama RY617 11R22.5 14PR	-6

Std/ Opt	Description	Weight
O	Rear Tires: Yokohama RY617 11R22.5 14PR	-12
S	Tire pressure monitoring system for tire/wheel count: 6.	0
O	Rear Tire Quantity: 4	0
O	Front Wheel: Maxion 91262 22.5x8.25 Steel Steel Armor[™] powder coat, hub-pilot mount. 7400 lb. maximum rating. 5-hand holes. Air disc brake compatible.	128
O	Rear Wheel: Maxion 91262 22.5x8.25 Steel Steel Armor[™] powder coat, hub-pilot mount. 7400 lb. maximum rating. 5-hand holes. Air disc brake compatible. Code is priced per pair of wheels.	256
O	Powder Coat White Steel Wheel. Use in Conjunction with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color.	0
O	Rear Wheel/Rim Quantity: 4	0

Frame & Equipment

S	Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to 308 in. Truck frame weight is 2.91 lb.-in. per pair of rails. Section modulus is 14.80 cu.in., RBM is 1,776,000 in.-lbs per rail. 120,000 PSI yield. Heat treated. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required, Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	-56
O	Delete bumper: Requires a bumper setting code.	-27
S	40 in. Bumper Setting. Requires a Bumper Code.	0
S	Front Tow Loops: Two	0
S	Battery Box: Steel Parallel Module under W/Step, plastic cover. Use with 2 or 3 batteries. Up to 2 air tanks may be mounted to bottom of box. Batteries will be oriented perpendicular to the frame rail in a single row.	0
S	Battery Box Location: RH Side.	0
S	Stamped Steel Intermediate/ Fill-In Crossmember.	0
S	Welded Rear Cab Support.	0
O	Component Restriction: Do Not Drive- Unit May be decked.	0
S	Square End-of-Frame W/O Crossmember; Non-Towing.	0

Fuel Tanks & Equip

Price Level: January 1, 2026

Deal: KW Model T380 Trk

Printed On: 4/8/2026 3:58:18 PM

100% Complete

Date: April 08, 2026

Quote Number: QUO-1173074-P7R7J5

Std/ Opt	Description	Weight
S	50 US Gallon D-Shape Rectangular Aluminum Under fuel tank, replace. With non-slip step.	0
S	Small DEF Tank, 5.5 Gallons.	0
O	DEF to Fuel Fill Ratio 2:1 or Greater.	0
S	DEF Tank Location is LH Under Cab.	0
S	Location: 50 gal fuel tank LH under cab.	0
Cab & Equipment		
S	Cab: Stamped Aluminum with Curved Windshield LED markers. Requires separate roof code.	0
S	Hood: Short Aero w/ Dark Gray Crown In-Mold Color	0
S	Cab HVAC - Day Cab and 40 in. Sleeper System With Defrost, A/C, and 48,000 BTU/hr Heater. Includes automatic temperature control with one touch defrost operation and dash mounted cab temperature and solar intensity sensors. Pleated fresh air filter and cabin recirculation air filter standard. The Kenworth HVAC system is designed to provide optimal heating and cooling in all operating environments without need for additional insulation. Cab HVAC without sleeper heater AC is available with 40in sleeper.	0
S	Steering Wheel: 18 in. 4-Spoke.	0
S	Adjustable Telescoping Tilt Steering Column.	0
O	Gauge: DD Virtual Gauge - Air Filter Restriction	0
O	Gauge: DD Virtual Gauge - Manifold Pressure Boost	0
O	Gauge: DD Virtual Gauge - Engine Percent Torque	0
O	Gauge: DD Virtual Gauge - Engine Hours Instrument Cluster	0
O	Gauge: DD Virtual Gauge - Volts Instrument Cluster	0
S	Main Instrument Package: 7" Digital Display Cluster. Includes Physical (Analog): Speedometer, Tachometer, Oil Pressure, and Coolant Temp; and Digital: Fuel Level #1, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure, and Air Application for air brake trucks.	0

Std/ Opt	Description	Weight
S	Interior Trim Package: 2.1M MD Gray Foam Backing/Cloth Headliner W/Gray Sunvisor & Seat Color Three Underdash Center Console Cupholders (Two If Allison Transmission Is Selected).	0
S	Driver Seat: KW Air Seat IB Vinyl W/O Armrests /Susp Cover	0
O	Delete Standard Rider Seat.	-30
S	No Radio Or Speakers Selected: No Prewire & No Antenna Wiring. Not w/ Smart Wheel.	0
S	Turn Signal: Self-Cancelling	0
S	LH and RH Trip Ledge Rain Deflectors	0
S	Global Telematics Unit	0
S	Sensata Tire pressure monitoring system Requires 48991XX tire/wheel count code for sensors.	0
S	Dual Cab Interior Grabhandles: A Pillar Mounted Dash Wrap and B Pillar Mounted Grabhandles	0
S	Kenworth Daylite Door With Standard LH/RH electric door locks and LH/RH electric window controls.	0
S	Look-Down, Pass. Door, Black 11x6	0
S	Mirror Shell: Dual Aero In-Mold Black	0
S	Mirror: Dual KW Aero Rear View Non-Motor, Non-Heated with Integral CX	0
S	Rear Cab Stationary Window 19in x 36in	0
S	One-Piece Bonded-In Windshield With Curved Glass. Standard.	0
S	Direct Mount, Rubber Isolated Cab Suspension.	0
S	Roof: Low Profile Stamped Steel	0
Lights & Instruments		
S	Headlamps: Single Halogen Complex Reflector w/ Turn Indicator, Reflector and DRL. Fender Mtd.	0
S	14-Pin RP170 Body Lighting Connector.	0
S	Marker Lights: Five Rectangular LED.	0
S	LED Stop,Turn,Tail: With Two LED Backup Lights and With An LED License Plate.	0
Air Equipment		
S	Air Dryer: Bendix AD-HF Puraguard Heated	0

Std/ Opt	Description	Weight
S	Moisture Ejection Valve W/ Pull Cable Drain.	0
S	Nylon Air Tubing in Frame & Cab, Excluding Hoses subject to excessive heat or flexing.	0
Extended Warranty		
S	Base Warranty - PACCAR PX-7 Engine 36 months / Unlimited miles & km / Unlimited hours.	0
S	Base Warranty - Standard Service Medium Duty 12 months / Unlimited miles & km	0
O	TruckTech+ RD - 5YR Sub PACCAR PX Engines	0
O	Base Warranty: Emissions 5YR/100K MI	0
Miscellaneous		
O	GHG Secondary Manufacturer: Does Not Apply	0
S	EMUX Architecture	0
Promotions		
O	Model Year 2026 Engine	0
Paint		
O	Paint Color Number(s). N9702 A - L0006 WHITE N9720 FRAME N0001 BLACK	0
S	Bumper Unpainted	0
O	Day Cab Bulk Paint	0
S	Day Cab Standard Paint	0
S	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0
S	Base Coat/ Clear Coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0

<i>Std/ Opt</i>	<i>Description</i>	<i>Weight</i>
---------------------	--------------------	---------------

Special Requirements

Special Requirement 1 0098025
Special Requirement 2
Special Requirement 3
Special Requirement 4

Fuel Efficiency Score:**Order Comments**

Total Weight (lbs)

10,293

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information