



PERFORMANCE TRUCK - CLEVELAND (C359)  
1287 HIGHWAY 59 NORTH  
CLEVELAND, Texas 77328

HGAC BUY  
3555 TIMMONS LANE, STE 120  
HOUSTON, Texas 77027  
United States of America

Drew Vest  
Cell Phone: 281-610-8007  
Office Phone: 713-844-7111  
Email: avest@performancetruck.com

## Vehicle Summary

| Unit                    |                          | Chassis                           |       |
|-------------------------|--------------------------|-----------------------------------|-------|
| Model:                  | T680 Series Conventional | Fr Axle Load (lbs):               | 12000 |
| Type:                   | Full Truck               | Rr Axle Load (lbs):               | 23000 |
| Description 1:          | KW Model T680 Trk        | G.V.W.R. (lbs):                   | 35000 |
| Description 2:          | HT07-26                  | G.C.W. (lbs):                     | 35000 |
| Application             |                          | Road Conditions:                  |       |
| Intended Serv.:         | Local Pickup & Delivery  | Class A (Highway)                 | 90    |
| Commodity:              | General Freight          | Class B (Hwy/Mtn)                 | 10    |
| Body                    |                          | Class C (Off-Hwy)                 | 0     |
| Type:                   | Van                      | Class D (Off-Road)                | 0     |
| Length (ft):            | 12                       | Maximum Grade:                    | 6     |
| Height (ft):            | 13.5                     | Wheelbase (in):                   | 132   |
| Max Laden Weight (lbs): | 4000                     | Overhang (in):                    | 33    |
| Trailer                 |                          | Fr Axle to BOC (in):              | 68    |
| No. of Trailer Axles:   | 0                        | Cab to Axle (in):                 | 64    |
| Type:                   |                          | Cab to EOF (in):                  | 97    |
| Length (ft):            | 0                        | Overall Comb. Length (in):        | 215.4 |
| Height (ft):            | 0                        | Special Req.                      |       |
| Kingpin Inset (in):     | 0                        | U.S. Domestic Registry, 50-state. |       |
| Corner Radius (in):     | 0                        |                                   |       |
| Restrictions            |                          |                                   |       |
| Length (ft):            | 75                       |                                   |       |
| Width (in):             | 102                      |                                   |       |
| Height (ft):            | 13.5                     |                                   |       |

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

Note: All sales are F.O.B. designated plant of manufacture.

| Std/<br>Opt                   | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Weight |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| <b>Model</b>                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |        |
| S                             | <b>T680 Series Conventional</b><br>Primarily for On-highway tractor applications, it features superior aerodynamics, excellent forward lighting and advanced ergonomics. Elastomer bushed front spring pins & heavy-duty shock absorber brackets. 16mm fasteners from rear cab support to end-of-frame, except tractor taper crossmember. Three vinyl inside sunvisors for LH, RH, and center. Under-dash center console with (2) cup holders, (2) 12V outlets & a storage compartment. Glove box door with locking latch.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 14,892 |
| S                             | <b>T680</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0      |
| O                             | <b>CARB Low NOX Omnibus Registration Guidelines</b><br>Dealer/Customer acknowledges that this vehicle is NOT intended for registration or domicile/primary use in the State of California.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 0      |
| O                             | <b>EPA Clean Idle Label - PACCAR PX Engines</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0      |
| O                             | <b>T680 With PX-9, Next Gen</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0      |
| O                             | <b>State of Registry: Texas</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0      |
| <b>Engine &amp; Equipment</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |        |
| O                             | <b>PACCAR PX-9 350 350@1750 1050@1200, 2024</b><br>With Turbo Exhaust Brake (VGT Brake)<br>N09420 C333 0.....Reserve Speed Limit Offset (N09380 C334 0.....Maximum Cycle Distance (C334 N09360 C400 252...Reserve Speed Function Reset N09200 C399 100...Standard Maximum Speed Limit N09400 C401 10....Maximum Active Distance (C40 N09220 C402 0.....Expiration Distance (C402) N09540 C395 0.....Expiration Distance (C395) N09260 C121 68....Max Vehicle Speed in Top Gea N09440 C234 YES...Engine Protection Shtdwn N09460 C231 NO....Gear Down Protection N09580 C133 5.....Idle Shtdwn Time N09680 C233 NO....Idle Shtdwn Override N09480 C132 1400..Max PTO Speed N09300 C128 68....Max Cruise Control Speed N09500 C239 NO....Cruise Control Auto Resume N09520 C238 NO....Auto Engine Brake in Cruise N09780 C190 80....High Ambient Temperature Thr N09740 C188 40....Low Ambient Temperature Thre N09760 C189 60....Intermediate Ambient Tempera N09720 C382 YES...Enable Hot Ambient Automatic N09600 C396 YES...Enable Impending Shutdown Wa N09620 C397 60....Timer For Impending Shutdown N09640 C206 35....Engine Load Threshold N09560 C225 YES...Enable Idle Shutdown Park Br | -761   |
| O                             | <b>EPA Emissions Compliant Engine</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 0      |

| Std/<br>Opt | Description                                                                                                                                                                                                                                                                                                         | Weight |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| S           | <b>PremierSpec</b>                                                                                                                                                                                                                                                                                                  | 0      |
| O           | <b>Gearing Analysis: Balance</b><br>power/economy blend results.                                                                                                                                                                                                                                                    | 0      |
| O           | <b>Customer's Typical Operating Spd: 60 MPH</b>                                                                                                                                                                                                                                                                     | 0      |
| O           | <b>EWI Tracking - A2 Engine Module Chassis</b>                                                                                                                                                                                                                                                                      | 0      |
|             | <b>RegistrationYear</b><br>Year of Registration: 2026                                                                                                                                                                                                                                                               | 0      |
|             | <b>Effective VSL Setting 65.0 MPH or Greater (USA)</b>                                                                                                                                                                                                                                                              | 0      |
| O           | <b>Engine Idle Shutdown Timer Disabled</b>                                                                                                                                                                                                                                                                          | 0      |
|             | <b>Eff EIST NA Expiration Miles</b><br>Use only with MX and Cummins engines                                                                                                                                                                                                                                         | 0      |
| O           | <b>Air Compressor: Cummins 18.7 CFM - Cummins and PX</b>                                                                                                                                                                                                                                                            | 0      |
| S           | <b>Air Cleaner: Engine Mounted</b>                                                                                                                                                                                                                                                                                  | 0      |
| O           | <b>Fan Hub: Horton On/Off for PX-9 or L9N</b>                                                                                                                                                                                                                                                                       | 0      |
| S           | <b>Cooling Module: 1456 Square Inches</b>                                                                                                                                                                                                                                                                           | 0      |
| O           | <b>EXH: Single Can 2024 RH Under with RH Horizontal</b><br>Tailpipe Below Rail                                                                                                                                                                                                                                      | 20     |
| O           | <b>Fuel Filter:PACCAR Standard Service Interval</b><br>Fuel/Water Separator. 2017 and Later Emissions                                                                                                                                                                                                               | 0      |
| O           | <b>Run Aid:None</b><br>*For Fuel Filter                                                                                                                                                                                                                                                                             | 0      |
| O           | <b>Start Aid:None</b><br>*For Fuel Filter                                                                                                                                                                                                                                                                           | 0      |
| O           | <b>Kenworth Fuel Cooler</b><br>Required for Cummins engines with a single fuel tank. Required for PACCAR MX-13 engine with a single fuel tank and stationary use: High RPM, low vehicle speed, sustained for longer than 1 hour. Optional for all other applications.                                               | 6      |
| S           | <b>Alternator: PACCAR HDS 160 AMP Brushed</b>                                                                                                                                                                                                                                                                       | 0      |
| S           | <b>Batteries: 2 PACCAR GP31 Threaded Post (700-730)</b><br>1400-1460 CCA dual purpose.                                                                                                                                                                                                                              | 0      |
| O           | <b>Mitsubishi 105P55 12V Starter with Cummins and PX</b><br>PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded. Only for Cummins or PX engines. | 0      |
| S           | <b>12V Low Voltage Disconnect for Battery Protection</b>                                                                                                                                                                                                                                                            | 0      |

| Std/<br>Opt                       | Description                                                                                                                                                                                             | Weight |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| <b>Transmission &amp; Clutch</b>  |                                                                                                                                                                                                         |        |
| O                                 | <b>Transmission: Fuller FRM15210B 10-speed</b><br>w/pump & external oil cooler. Includes severe-duty pilot bearing on all class 8 models. *Torque Limit: 1550 pound-feet.                               | 93     |
| O                                 | <b>Clutch: Eaton 15-1/2 in. Advantage Self-Adjust</b><br>to 1750 ft-lb, Ceramic, 4-Paddle, Predamper                                                                                                    | 0      |
| O                                 | <b>Air-Assisted Hydraulic Clutch</b>                                                                                                                                                                    | 0      |
| O                                 | <b>Driveline: 1 Meritor RPL25; No Centerbearing Bearing</b>                                                                                                                                             | -8     |
| S                                 | <b>Aluminum Clutch Housing</b>                                                                                                                                                                          | 0      |
| <b>Front Axle &amp; Equipment</b> |                                                                                                                                                                                                         |        |
| S                                 | <b>Meritor MFS12E PLUS 12.5K 3.5in. Drop Standard Track</b>                                                                                                                                             | 0      |
| O                                 | <b>Front Brakes: 14.6K Meritor Q-Plus 16.5x5 in.</b><br>Not for fire truck/EMT/rescue service.                                                                                                          | -44    |
| O                                 | <b>Front Brake Drums: 14.6K 16.5x5 in. cast.</b>                                                                                                                                                        | 78     |
| O                                 | <b>Drum Brake Knuckle for Use on Meritor MFS Plus Steer Axle</b>                                                                                                                                        | 20     |
| S                                 | <b>Front Hub: Aluminum Hub Pilot 13,200 lbs.</b><br>10-Bolt, 11-1/4 in. bolt circle .                                                                                                                   | 0      |
| S                                 | <b>ConMet PreSet Plus Hub Package; Front Axle.</b>                                                                                                                                                      | 0      |
| S                                 | <b>Hubcap: Front Vented.</b>                                                                                                                                                                            | 0      |
| O                                 | <b>Front Auto Slack Adjuster for Drum Brakes.</b>                                                                                                                                                       | 0      |
| S                                 | <b>Front Springs: Taperleaf 12K W/ Shock Absorbers</b><br>w/ maintenance-free elastomer spring pin bushings. Standard with rubber pins except for C500 which has threaded pins. Not available on W900L. | 0      |
| O                                 | <b>Single Power Steering Gear: 13.2K Sheppard HD94.</b>                                                                                                                                                 | 0      |
| <b>Rear Axle &amp; Equipment</b>  |                                                                                                                                                                                                         |        |
| O                                 | <b>Single Meritor RS23-160 Rear Axle rated at 23K.</b>                                                                                                                                                  | -575   |
| O                                 | <b>Rear Axle Ratio - 3.58.</b>                                                                                                                                                                          | 0      |
| O                                 | <b>Single Rear Brakes 16-1/2x7 in., 23K. Meritor Q-Plus extended service S-cam.</b>                                                                                                                     | -12    |
| O                                 | <b>RR BRK DRUM: CENTRIFUSE SING</b><br>FOR USE W/16.5X7" BRK                                                                                                                                            | 60     |
| O                                 | <b>Single Rear Hubs: Aluminum Hub Pilot 23K;</b><br>11.25" bolt circle. Requires "R" series outer ends.                                                                                                 | 0      |

| Std/<br>Opt                  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Weight |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| O                            | <b>Single Rear Axle Automatic Slack Adjusters.</b><br>For use with drum brakes.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 0      |
| O                            | <b>Spring Brake: 3030 Long Stroke Single 3 in.</b><br>travel. For drum brakes. Helps keep brakes in adjustment longer.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 44     |
| O                            | <b>Bendix 4S/4M Anti-Lock Brake System.</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 0      |
| O                            | <b>Delete Bendix Wingman Advanced ACB / Fusion</b><br>Adaptive CC W/ ACB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 0      |
| O                            | <b>Air Operated Park Brake</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 0      |
| O                            | <b>Rear suspension: single Reyco 79KB taperleaf 23K.</b><br>Steel crossmembers & gussets, Kenworth longlife spring w/helper.<br>Unladen Height: 11.0 in. Laden Height: 9.3 in. Not available with shocks<br>or swaybars.                                                                                                                                                                                                                                                                                                                                                                                       | -190   |
| <b>Tires &amp; Wheels</b>    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |        |
| O                            | <b>Front Tires: Yokohama RY617 11R22.5 14PR</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 2      |
| O                            | <b>Rear Tires: Yokohama RY617 11R22.5 14PR</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 4      |
| O                            | <b>Rear Tire Quantity: 4</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 0      |
| O                            | <b>Front Wheel: Maxion 91262 22.5x8.25 Steel</b><br>Steel Armor[™] powder coat, hub-pilot mount. 7400 lb. maximum<br>rating. 5-hand holes. Air disc brake compatible.                                                                                                                                                                                                                                                                                                                                                                                                                                          | 128    |
| O                            | <b>Rear Wheel: Maxion 91262 22.5x8.25 Steel</b><br>Steel Armor[™] powder coat, hub-pilot mount. 7400 lb. maximum<br>rating. 5-hand holes. Air disc brake compatible. Code is priced per pair<br>of wheels.                                                                                                                                                                                                                                                                                                                                                                                                     | 256    |
| O                            | <b>Powder Coat White Steel Wheel. Use in Conjunction</b><br>with front, dual front, rear, spare or lift axle wheel code(s). All wheels<br>on chassis must have same finish color.                                                                                                                                                                                                                                                                                                                                                                                                                              | 0      |
| O                            | <b>Rear Wheel/Rim Quantity: 4</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 0      |
| <b>Frame &amp; Equipment</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |        |
| S                            | <b>Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to</b><br>284 in. Truck frame weight is 2.91 lb.-in. per pair of rails. Section<br>modulus is 14.80, RBM is 1,776,000 in.-lbs per rail. Frame rail<br>availability may be restricted based upon application, axle/suspension<br>capacity, fifth wheel setting, or component/dimensional specifications.<br>The results of the engineering review may result in a change to the<br>requested frame rail. If a change is required Kenworth Application<br>Engineering will advise the dealer of the appropriate material<br>specification for a substitute rail. | -175   |
| S                            | <b>Bumper: Aerodynamic, Unpainted, In-Mold Color.</b><br>With air dams, tow hook covers. Requires a bumper setting code.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 0      |
| O                            | <b>50.4 in. Bumper Setting. Requires a Bumper Code.</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 0      |
| O                            | <b>Battery Box Module: Short Length Aluminum</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 0      |

| Std/<br>Opt | Description                                                                                                                                                                                                                                                                                | Weight |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
|             | parallel under cab, aluminum diamond plate cover w/ step. Up to 2 air tanks may mount to bottom of box. Batteries will be oriented perpendicular on rail.                                                                                                                                  |        |
| S           | <b>Battery Box Location: LH Side.</b>                                                                                                                                                                                                                                                      | 0      |
| O           | <b>C5, T6, T8 diamond plate cover and black end</b> plates with access step for right hand under DPF/SCR or CNG. For T8, use extended length non-polished battery box on opposite rail to match the length of under cab components. End plates will be painted standard black frame color. | 0      |
| O           | <b>Delete Standard Fifth Wheel</b>                                                                                                                                                                                                                                                         | -362   |
| O           | <b>Delete Mudflap Arms: Dealer/ Customer Responsible</b> for installation of arms.                                                                                                                                                                                                         | -12    |
| O           | <b>Delete Mudflap Shields-Dealer/Customer</b> responsible for installation of shields.                                                                                                                                                                                                     | -8     |
| O           | <b>Square End-of-Frame W/O Crossmember; Non-Towing.</b>                                                                                                                                                                                                                                    | 0      |

### Fuel Tanks & Equip

|   |                                                                                                                                                                                                                                                                                                                                                                                           |     |
|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| O | <b>Fuel Tank: 45 US Gallon 24.5 in. Aluminum BOC</b> replace. Class 8 fuel tanks w/ o locking caps include an anti-siphon device on the filler neck.                                                                                                                                                                                                                                      | -22 |
| O | <b>Small Round DEF Tank, 14 Gallons.</b><br>The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204. | -9  |
| O | <b>Minimum Required DEF to Fuel Fill Ratio 1:1.</b>                                                                                                                                                                                                                                                                                                                                       | 0   |
| O | <b>DEF capacity ratio - Truck to be centrally fueled</b>                                                                                                                                                                                                                                                                                                                                  | 0   |
| O | <b>Delete Anti-Siphon Device Swaged in Place for Any</b> number of fuel tanks.                                                                                                                                                                                                                                                                                                            | -1  |
| O | <b>DEF Tank Location is RH.</b>                                                                                                                                                                                                                                                                                                                                                           | 0   |
| O | <b>Location: 45 Gal Fuel Tank LH Behind Cab.</b>                                                                                                                                                                                                                                                                                                                                          | 0   |

### Cab & Equipment

|   |                                                                                                                                                                                                                                                                                               |     |
|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| S | <b>Cab: Stamped Aluminum Cab with Panoramic Curved</b> glass windshield. Standard with stamped aluminum doors, heavy duty in-swinging hinges, and triple sealed doors. Manufactured using self-piercing rivets and structural adhesive. Includes LED exterior marker lights and turn signals. | 0   |
| O | <b>Hood: T680 Next Gen MX 119" BBC W/ Split Fender &amp; W/O Chassis Fairings.</b> *Requires 8829661                                                                                                                                                                                          | -70 |
| S | <b>Cab HVAC - Day Cab and 40 in. Sleeper</b> System With Defrost, A/C, and 48,000 BTU/hr Heater. Includes automatic temperature control with one touch defrost operation and dash mounted cab temperature and solar intensity sensors. Pleated                                                | 0   |

| Std/<br>Opt | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Weight |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
|             | fresh air filter and cabin recirculation air filter standard. The Kenworth HVAC system is designed to provide optimal heating and cooling in all operating environments without need for additional insulation. Cab HVAC without sleeper heater AC is available with 40in sleeper.                                                                                                                                                                                                                                                           |        |
| S           | <b>Kenworth Smartwheel: 18 in. Non-Leather With</b><br>Integrated Radio and Cruise Controls.                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 0      |
| O           | <b>Column Mtd Retarder Control, RH Side</b><br>Use with Manual & Allison Transmissions Only.                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 0      |
| S           | <b>Adjustable Telescoping Tilt Steering Column.</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 0      |
| S           | <b>Gauge: DD Virtual Gauge - Air Filter</b><br>Restriction                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 0      |
| S           | <b>Gauge: DD Virtual Gauge - Manifold</b><br>Pressure Boost                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0      |
| S           | <b>Gauge: DD Virtual Gauge - Engine Percent</b><br>Torque                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 0      |
| S           | <b>Main Instrument Package: 15" Digital Display.</b><br>Includes Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level #1, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, OAT and Voltmeter, and Air Application.                                                                                                                                                                                                                                                                       | 0      |
| S           | <b>Interior Color: Slate Gray</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 0      |
| S           | <b>Interior Package: Vantage Daycab</b><br>Includes durable headliner and vinyl sidewalls with geometric patterned trim and anodized aluminum accents throughout. Convenient overhead storage cubbies, full size glove box, two center console cupholders, and large door pad map pocket. Standard LH/RH power windows, electric door locks, interior LED lighting, nighttime-friendly red ambient lighting for dash and footwell, and door mounted courtesy light. Includes two standard 12V power outlets. Driver sunvisor includes strap. | 0      |
| S           | <b>Rubber Floormat</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 0      |
| O           | <b>Driver Seat: GT701 IB with Vinyl material.</b><br>The GT701 is standard with a single air bag, scissor linkage seat suspension. It includes a single chamber lumbar support, 10in Fore/Aft adjustment, 7in Up/Down adjustment, 2.5in pan extension, 51 degree seat back recline, and 16 degree full seat tilt. Includes 3-point matching seat belts. DR seat standard w/ dual armrests.                                                                                                                                                   | 0      |
| O           | <b>Delete Standard Rider Seat.</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | -58    |
| S           | <b>Seat Color: Black</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 0      |
| O           | <b>Kenworth Radio DEA700 AM/FM/WB</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 0      |
| S           | <b>Base Level Audio System - Daycab:High Performance</b><br>Door Speakers.                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 0      |
| S           | <b>Turn Signal: Non-Self Cancelling</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0      |



| Std/<br>Opt                     | Description                                                                                                                                                                                                                                                                                 | Weight |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| O                               | <b>LH and RH Trip Ledge Rain Deflectors</b>                                                                                                                                                                                                                                                 | 0      |
| S                               | <b>Global Telematics Unit</b>                                                                                                                                                                                                                                                               | 0      |
| S                               | <b>Dual Cab Interior Grabhandles: A Pillar Mounted Dash Wrap and B Pillar Mounted Grabhandles</b>                                                                                                                                                                                           | 0      |
| O                               | <b>Delete Standard Side Extenders.</b>                                                                                                                                                                                                                                                      | -46    |
| O                               | <b>Split Fender Without Under Cab Fairings.</b><br>Use With T680 Split Fenders.                                                                                                                                                                                                             | -60    |
| S                               | <b>Kenworth Daylite Door With Standard LH/RH</b><br>electric door locks and LH/RH electric window controls.                                                                                                                                                                                 | 0      |
| S                               | <b>Single Air Horn Under Cab.</b>                                                                                                                                                                                                                                                           | 0      |
| S                               | <b>Look-Down, Pass. Door, Black 11x6</b>                                                                                                                                                                                                                                                    | 0      |
| S                               | <b>Aero Mirror: Dual Kenworth Aerodynamic Motorized</b><br>heated mirrors, 7in X 13in with cab color mirror shell and black mirror arms. Also includes LH/RH heated 6in X 7in convex mirrors. Mirror brackets set for 8-1/2 ft load width. Mirror controls located on driver side door pad. | 0      |
| S                               | <b>Rear Cab Stationary Window 19in x 36in</b>                                                                                                                                                                                                                                               | 0      |
| S                               | <b>One-Piece Bonded-In Windshield With Curved Glass.</b><br>Standard.                                                                                                                                                                                                                       | 0      |
| O                               | <b>Opt Out - Wheel Well Closeouts</b><br>Rubber Shields That Close Out The Front Wheel Well.                                                                                                                                                                                                | 0      |
| S                               | <b>Kenworth Cab/Sleeper Air Suspension.</b>                                                                                                                                                                                                                                                 | 0      |
| <b>Lights &amp; Instruments</b> |                                                                                                                                                                                                                                                                                             |        |
| S                               | <b>Headlamps: Halogen Projector Low Beam, Halogen</b><br>Complex Reflector High Beam w/ Integral DRL.                                                                                                                                                                                       | 0      |
| O                               | <b>Marker Lights: Five Rectangular LED.</b>                                                                                                                                                                                                                                                 | 0      |
| S                               | <b>Turn Signal Lights: LED Side Turn Indicator, Hood</b><br>mounted.                                                                                                                                                                                                                        | 0      |
| S                               | <b>LED Stop,Turn,Tail: With Two LED</b><br>Backup Lights and With An LED License Plate.                                                                                                                                                                                                     | 0      |
| S                               | <b>Marker Lights: Interrupter Switch.</b><br>Included in Turn Signal For All Models Except T3. The T3 Switch Is In The Dash.                                                                                                                                                                | 0      |
| S                               | <b>Omit Brake Light with Engine Brake.</b><br>Can only be selected when chassis also has engine brake. Cannot be used with options to delete engine brake.                                                                                                                                  | 0      |
| <b>Air Equipment</b>            |                                                                                                                                                                                                                                                                                             |        |
| S                               | <b>Air Dryer: Bendix AD-HF Puraguard Heated</b>                                                                                                                                                                                                                                             | 0      |



| <i>Std/<br/>Opt</i>      | <i>Description</i>                                                                                                                                                                                                                      | <i>Weight</i> |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| S                        | <b>Moisture Ejection Valve W/ Pull Cable Drain.</b>                                                                                                                                                                                     | 0             |
| O                        | <b>Delete Standard Tractor Kit</b>                                                                                                                                                                                                      | -24           |
| S                        | <b>Nylon Air Tubing in Frame &amp; Cab, Excluding Hoses</b><br>subject to excessive heat or flexing.                                                                                                                                    | 0             |
| <b>Extended Warranty</b> |                                                                                                                                                                                                                                         |               |
| O                        | <b>Base Warranty - PACCAR PX-9 Engine</b><br>24 months / 250,000 miles / 402,336 km / 6250 hours.                                                                                                                                       | 0             |
| S                        | <b>Base Warranty - Standard Service Heavy Duty</b><br>12 months / 100,000 miles / 160,000 km.                                                                                                                                           | 0             |
| O                        | <b>TruckTech+ RD - 5YR Sub PACCAR PX Engines</b>                                                                                                                                                                                        | 0             |
| O                        | <b>Base Warranty: Emissions</b><br>5YR/100K MI                                                                                                                                                                                          | 0             |
| <b>Miscellaneous</b>     |                                                                                                                                                                                                                                         |               |
| S                        | <b>GHG Secondary Manufacturer: Does Not Apply</b>                                                                                                                                                                                       | 0             |
| S                        | <b>EMUX Architecture</b>                                                                                                                                                                                                                | 0             |
| <b>Promotions</b>        |                                                                                                                                                                                                                                         |               |
| O                        | <b>Model Year 2026 Engine</b>                                                                                                                                                                                                           | 0             |
| <b>Paint</b>             |                                                                                                                                                                                                                                         |               |
| O                        | <b>Paint Color Number(s).</b><br><br>N9702 A - L0006 WHITE<br>N9720 FRAME N0001 BLACK                                                                                                                                                   | 0             |
| S                        | <b>Bumper Unpainted</b>                                                                                                                                                                                                                 | 0             |
| O                        | <b>Day Cab Bulk Paint</b>                                                                                                                                                                                                               | 0             |
| O                        | <b>Day Cab Standard Paint</b>                                                                                                                                                                                                           | 0             |
| S                        | <b>1 - Color Paint - Day Cab</b><br>Color will be White if no other color is specified.                                                                                                                                                 | 0             |
| O                        | <b>Base Coat/ Clear Coat.</b><br>The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint. | 0             |

| <i>Std/<br/>Opt</i> | <i>Description</i> | <i>Weight</i> |
|---------------------|--------------------|---------------|
|---------------------|--------------------|---------------|

**Special Requirements**

Special Requirement 1 0098025

Special Requirement 2

Special Requirement 3

Special Requirement 4

**Fuel Efficiency Score:****Order Comments**

**Total Weight (lbs)**

13,166

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

## **Prices and Specifications Subject to Change Without Notice.**

---

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

### **PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*