

**Prepared For:**

HOUSTON-GALVESTON AREA C  
 Neal Witty  
 3555 TIMMONS  
 HOUSTON,, TX 77227-2777  
 (713)627 - 3200  
 Reference ID: N/A

**Presented By:**

HOLT TRK CTRS OF TX, LLC  
 Carlos Weeber  
 8900 NORTH LOOP E  
 HOUSTON TX 77029 - 1218  
 (713)674-3444

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.



**Model Profile**  
**2027 MV607 SBA (MV607)**

|                                  |                                                                                                                                                                                                                |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>AXLE CONFIG:</b>              | 4X2                                                                                                                                                                                                            |
| <b>APPLICATION:</b>              | Stake Flat                                                                                                                                                                                                     |
| <b>MISSION:</b>                  | Requested GVWR: 25500. Calc. GVWR: 23500. Calc. GCWR: 35000<br>Calc. Start / Grade Ability: 26.09% / 2.44% @ 55 MPH<br>Calc. Geared Speed: 64.6 MPH                                                            |
| <b>DIMENSION:</b>                | Wheelbase: 236.00, CA: 168.90, Axle to Frame: 53.00                                                                                                                                                            |
| <b>ENGINE, DIESEL:</b>           | {Cummins B6.7 200} EPA 2024, 200HP @ 2400 RPM, 600 lb-ft Torque @ 1600 RPM, 2600 RPM<br>Governed Speed, 200 Peak HP (Max)                                                                                      |
| <b>TRANSMISSION, MANUAL:</b>     | {Fuller FS-5406N} 6-Speed Manual, Direct Drive, Fully Synchronized, Short Shift Stroke                                                                                                                         |
| <b>CLUTCH:</b>                   | {Eaton Fuller Solo 1402} Self-Adjusting, 14" Dia Two-Plate, Stamped Angle Spring, Ceramic, 3-Super Button, 7+1 Low Rate Damper, 1.75"-10 Tooth Spline, Mechanical Pull Type Control, 860 lb-ft Torque Capacity |
| <b>AXLE, FRONT NON-DRIVING:</b>  | {Meritor MFS-08-153B} I-Beam Type, 8,000-lb Capacity                                                                                                                                                           |
| <b>AXLE, REAR, SINGLE:</b>       | {Dana Spicer S16-130} Single Reduction, 15,500-lb Capacity, 190 Wheel Ends Gear Ratio: 4.30                                                                                                                    |
| <b>CAB:</b>                      | Conventional, Day Cab                                                                                                                                                                                          |
| <b>TIRE, FRONT:</b>              | (2) 255/70R22.5 Load Range H AH37 (HANKOOK), 562 rev/mile, 75 MPH, All-Position                                                                                                                                |
| <b>TIRE, REAR:</b>               | (4) 255/70R22.5 Load Range H AH37 (HANKOOK), 562 rev/mile, 75 MPH, All-Position                                                                                                                                |
| <b>SUSPENSION, REAR, SINGLE:</b> | 15,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs                                                                                                                          |
| <b>PAINT:</b>                    | Cab schematic 100WP<br>Location 1: 9219, Winter White (Std)<br>Chassis schematic N/A                                                                                                                           |

| <b>Code</b> | <b>Description</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MV60700     | Base Chassis, Model MV607 SBA with 236.00 Wheelbase, 168.90 CA, and 53.00 Axle to Frame.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 1ANA        | AXLE CONFIGURATION 4x2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|             | <u>Notes</u><br>: Pricing may change if axle configuration is changed.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| 1CAC        | FRAME RAILS High Strength Low Alloy Steel (50,000 PSI Yield); 10.125" x 3.062" x 0.312" (257.2mm x 77.8mm x 8.0mm); 489.2" (12425mm) Maximum OAL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| 1LEG        | LICENSE PLATE HOLDER Includes Upper & Lower Mounting Plate Hardware, Mounted in Existing Holes in Front Bumper                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| 1LNG        | BUMPER, FRONT Contoured, Steel, Painted Gloss Black                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 1WEJ        | WHEELBASE RANGE 199" (505cm) Through and Including 254" (645cm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 2ATK        | AXLE, FRONT NON-DRIVING {Meritor MFS-08-153B} I-Beam Type, 8,000-lb Capacity                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 3ADA        | SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 8,000-lb Capacity, with Shock Absorbers                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|             | <u>Includes</u><br>: SPRING PINS Rubber Bushings, Maintenance-Free                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|             | <u>Notes</u><br>: In combinations where chassis component weights may cause a chassis lean, a spring is used in front left spring pack to offset this imbalance & provide a level chassis, within 3/8", with body installed.                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 4100        | BRAKE SYSTEM, HYDRAULIC {Wabco} Split System, with Automatic Adjustment and Four Channel ABS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 4GAR        | BRAKE, PARKING {Bosch} DSSA Type, 12" x 3"; for Hydraulic Brake Chassis; Activated by Lever in Cab; Differential Mounted                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 4XCW        | BRAKES, FRONT {Meritor Quadrauc} Hydraulic Disc Type, with Four 70mm Diameter Pistons, 12,000-lb Capacity                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| 4XCX        | BRAKES, REAR {Meritor Quadrauc} Hydraulic Disc Type, with Four 70mm Diameter Pistons, 21,000-lb Capacity per Axle                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 5AAA        | STEERING COLUMN Stationary                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 5CAW        | STEERING WHEEL 4-Spoke; 18" Dia., Black                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 5PRG        | STEERING GEAR {TRW TAS40} Power                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 6DGA        | DRIVELINE SYSTEM {Dana Spicer} SPL100, for 4x2/6x2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| 7BME        | EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Under Right Rail Back of Cab, Includes Single Short Horizontal Tail Pipe                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 8000        | ELECTRICAL SYSTEM 12-Volt, Standard Equipment                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|             | <u>Includes</u><br>: DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab<br>: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel<br>: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever<br>: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light<br>: STARTER SWITCH Electric, Key Operated<br>: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector<br>: TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature<br>: TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted |

| <b><u>Code</u></b> | <b><u>Description</u></b>                                                                                                                                                                                                                                                                                           |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                    | : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever                                                                                                                                                                                            |
|                    | : WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted                                                                                                                                                                                                                                                            |
|                    | : WIRING, CHASSIS Color Coded and Continuously Numbered                                                                                                                                                                                                                                                             |
| 8GXD               | ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount, with Remote Sense                                                                                                                                                                                                          |
| 8MJP               | BATTERY SYSTEM {Fleetrite} Maintenance-Free, (2) 12-Volt 1320CCA Total, Top Threaded Stud                                                                                                                                                                                                                           |
| 8RMS               | SPEAKERS Omit                                                                                                                                                                                                                                                                                                       |
| 8RMX               | RADIO Omit, Includes Wiring and Antenna                                                                                                                                                                                                                                                                             |
| 8RPR               | ANTENNA for Increased Roof Clearance Applications                                                                                                                                                                                                                                                                   |
| 8VBE               | HORN, ELECTRIC (1) Trumpet Style                                                                                                                                                                                                                                                                                    |
| 8VUX               | BATTERY BOX Steel, with Plastic Cover, 25" Wide, 2-3 Battery Capacity, Mounted Right Side Under Cab                                                                                                                                                                                                                 |
| 8WWJ               | INDICATOR, LOW COOLANT LEVEL with Audible Alarm                                                                                                                                                                                                                                                                     |
| 8XAH               | CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses                                                                                                                                                                                                                    |
| 8XKL               | STARTING MOTOR {Mitsubishi Electric Automotive America 90P47} 12-Volt, with Soft-Start                                                                                                                                                                                                                              |
| 8XNY               | HEADLIGHTS Halogen                                                                                                                                                                                                                                                                                                  |
| 9AAB               | LOGOS EXTERIOR Model Badges                                                                                                                                                                                                                                                                                         |
| 9AAE               | LOGOS EXTERIOR, ENGINE Badges                                                                                                                                                                                                                                                                                       |
| 9HCW               | GRILLE Molded in Black                                                                                                                                                                                                                                                                                              |
| 9WBN               | FENDER EXTENSIONS Painted                                                                                                                                                                                                                                                                                           |
| 9WBW               | FRONT END Tilting, Fiberglass, with Three Piece Construction, Dual Air Intakes                                                                                                                                                                                                                                      |
| 10060              | PAINT SCHEMATIC, PT-1 Single Color, Design 100                                                                                                                                                                                                                                                                      |
|                    | <b><u>Includes</u></b>                                                                                                                                                                                                                                                                                              |
|                    | : PAINT SCHEMATIC ID LETTERS "WP"                                                                                                                                                                                                                                                                                   |
| 10761              | PAINT TYPE Base Coat/Clear Coat, 1-2 Tone                                                                                                                                                                                                                                                                           |
| 10AGB              | CONNECTED PLATFORM Includes Connectivity Module and Five Year Data Plan                                                                                                                                                                                                                                             |
| 10UAV              | VEHICLE REGISTRATION IDENTITY ID for Non-CARB Omnibus and/or Non-ACT Adopting State or Exempt Vehicle. Not for use on vehicles registering in CA. Contains non-mitigated legacy engine & cannot be registered in CA unless exempt. You may be held liable under state law for failure to properly register vehicle. |
|                    | <b><u>Notes</u></b>                                                                                                                                                                                                                                                                                                 |
|                    | : CANNOT BE REGISTERED IN CA. For vehicles that will be registered in States other than CA.                                                                                                                                                                                                                         |
| 11LGB              | CLUTCH {Eaton Fuller Solo 1402} Self-Adjusting, 14" Dia Two-Plate, Stamped Angle Spring, Ceramic, 3-Super Button, 7+1 Low Rate Damper, 1.75"-10 Tooth Spline, Mechanical Pull Type Control, 860 lb-ft Torque Capacity                                                                                               |
| 12703              | ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection                                                                                                                                                                                                                          |
| 12EXR              | ENGINE, DIESEL {Cummins B6.7 200} EPA 2024, 200HP @ 2400 RPM, 600 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 200 Peak HP (Max)                                                                                                                                                                               |
| 12TSY              | FAN DRIVE {Borg-Warner SA85} Viscous Type, Screw On                                                                                                                                                                                                                                                                 |
|                    | <b><u>Includes</u></b>                                                                                                                                                                                                                                                                                              |
|                    | : FAN Nylon                                                                                                                                                                                                                                                                                                         |
| 12VCE              | AIR CLEANER Single Element, Fire Retardant Media                                                                                                                                                                                                                                                                    |

| <b><u>Code</u></b> | <b><u>Description</u></b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 12VKM              | EMISSION, CALENDAR YEAR {Cummins B6.7} EPA, OBD and GHG Certified for Calendar Year 2026                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| 12VXT              | THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| 12VYP              | ENGINE CONTROL, REMOTE MOUNTED No Provision for Remote Mounted Engine Control                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 12WPV              | OIL PAN 15 Quart Capacity, For Cummins ISB/B6.7 Engines                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| 12WVG              | EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| 12WZE              | CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| 12XCB              | RADIATOR Aluminum, 2-Row, Down Flow, Front to Back System, 640 SqIn Louvered, with 383 SqIn Charge Air Cooler                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 12XCS              | CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 13GNG              | TRANSMISSION, MANUAL {Fuller FS-5406N} 6-Speed Manual, Direct Drive, Fully Synchronized, Short Shift Stroke                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 13XAM              | PTO LOCATION Dual, Customer Intends to Install PTO at Left and/or Right Side of Transmission                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| 14AJE              | AXLE, REAR, SINGLE {Dana Spicer S16-130} Single Reduction, 15,500-lb Capacity, 190 Wheel Ends . Gear Ratio: 4.30                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| 14VAC              | SUSPENSION, REAR, SINGLE 15,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| 15LMR              | FUEL/WATER SEPARATOR {Racor 400 Series,} with Primer Pump, Includes Water-in-Fuel Sensor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| 15LRE              | LOCATION FUEL/WATER SEPARATOR Mounted Under Hood, Left Side, Above Front Axle                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 15SWU              | FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 16" Tank Depth, 40 US Gal (151L), Mounted Left Side, Under Cab                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 15WDG              | DEF TANK 7 US Gal (26L) Capacity, Frame Mounted Outside Left Rail, Under Cab                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| 16030              | CAB Conventional, Day Cab                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|                    | <u>Includes</u><br>: CLEARANCE/MARKER LIGHTS (5) Flush Mounted                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| 16400              | SEAT, PASSENGER Omit Item                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 16BAM              | AIR CONDITIONER with Integral Heater and Defroster                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 16GED              | GAUGE CLUSTER Base Level; English with English Electronic Speedometer                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                    | <u>Includes</u><br>: GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for<br>: GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure or Auxiliary Air Pressure (if Air Equipped)<br>: WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure, Primary and Secondary (if Air Equipped) |
| 16HKT              | IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| 16KAV              | SEAT, DRIVER {National} Non-Suspension, High Back with Integral Head Rest, Vinyl, with Fixed Back                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 16SNL              | MIRRORS (2) C-Loop, Black Heads and Arms, 7.5" x 14" Flat Glass, Includes 7.5" x 7" Convex Mirrors, for 102" Load Width                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

Notes

| <b><u>Code</u></b>       | <b><u>Description</u></b>                                                                                                                                |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
|                          | : Mirror Dimensions are Rounded to the Nearest 0.5"                                                                                                      |
| 16VKB                    | CAB INTERIOR TRIM Classic, for Day Cab                                                                                                                   |
|                          | <u>Includes</u>                                                                                                                                          |
|                          | : CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger                      |
|                          | : DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Overhead Console, Center Mounted                      |
|                          | : SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap                                              |
| 16VLM                    | CAB REAR SUSPENSION Rubber Suspension, for Low Cab Height                                                                                                |
| 16XCK                    | WINDOW, MANUAL (2) and Manual Door Locks, Left and Right Doors                                                                                           |
| 16XJN                    | INSTRUMENT PANEL Flat Panel                                                                                                                              |
| 16ZBT                    | ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab and Extended Cab                                                   |
| 27DTU                    | WHEELS, FRONT {Accuride 29001} DISC; 22.5x7.50 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs     |
| 28DTU                    | WHEELS, REAR {Accuride 29001} DUAL DISC; 22.5x7.50 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs |
| 7752525809               | (2) TIRE, FRONT 255/70R22.5 Load Range H AH37 (HANKOOK), 562 rev/mile, 75 MPH, All-Position                                                              |
| 7752525809               | (4) TIRE, REAR 255/70R22.5 Load Range H AH37 (HANKOOK), 562 rev/mile, 75 MPH, All-Position                                                               |
| <b>Services Section:</b> |                                                                                                                                                          |
| 40129                    | WARRANTY Standard for MV Series, Effective with Vehicles Built July 1, 2017 or Later, CTS-2020A                                                          |

| <u>Description</u> | (US DOLLAR) | <u>Price</u> |
|--------------------|-------------|--------------|
| Net Sales Price:   |             | \$75,995.00  |

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an International vehicle.

Approved by Seller:

Accepted by Purchaser:

\_\_\_\_\_  
Official Title and Date

\_\_\_\_\_  
Firm or Business Name

\_\_\_\_\_  
Authorized Signature

\_\_\_\_\_  
Authorized Signature and Date

This proposal is not binding upon the seller without  
Seller's Authorized Signature

\_\_\_\_\_  
Official Title and Date

If you haven't added a planned maintenance service contract to your proposal yet, please get in touch with your local dealer, International or IC Bus Sales Representative to learn more about the benefits when ordering together with the vehicle.

International® Financial offers loans, a full line up of lease options, and can establish a line of credit for use towards the purchase of International and IC Bus vehicles. Ask your dealer, International® or IC Bus® Sales Representative about completing an International Financial credit application and any promotional offers that may be available. International Financial services are provided by Navistar Financial Corporation.

The TOPS FET Calculation is an estimate for reference purposes only. The seller is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described here in are International Motors, LLC\* standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.

International Motors, LLC d/b/a International Motors USA LLC in Illinois and Ohio.