



2027 HGAC - ISUZU NPR 132"WB - GAS

INDUSTRIAL POWER ISUZU TRUCK FORT WORTH
712 N. BEACH STREET
FORT WORTH, TX 76111-5943
817-834-7473

Window Sticker

Code	Model	MSRP
1C204	NPR Gas Cab Chassis 132.5"WB, 110"CA	\$69,164.00
04	White, Standard model specifications with power windows and power door locks, air conditioning, rear body dome lamp switch, and an AM/FM radio with Bluetooth	\$0.00
Options		
Standard Equipment		
RQ2	Vehicle Application, Truck Application	Inc.
KNX	Air Cleaner, Dry paper single element. Air cleaner canister standard with air restriction gauge.	Inc.
IL3	Battery, Single Delco 12-V maintenance free 750 CCA frame mounted battery box	Inc.
I41	Exhaust, Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.	Inc.
AQB	Seat, Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	Inc.
C60	Air Conditioning, Air conditioner	Inc.
IL0	Power Windows & Door Locks, Yes	Inc.
I5H	Tires, LRR (low rolling resistance)	Inc.
ID3	Rear Axle, Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	Inc.
IX2	Accessories, Rear body dome lamp switch	Inc.
A17	Fuel Tank, 38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.	Inc.
8VN	Accessories, AM/FM stereo with auxiliary input, USB port, and Bluetooth.	Inc.
ID2	Front Axle, "I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	Inc.
I8J	Rear Suspension, 12,900 lbs. Capacity semi elliptical; main and auxiliary multi- leaf spring. Includes shock absorbers.	Inc.
RBV	Front Wheels, 16" X 6", 6-hole disc, painted white.	Inc.
I53I69	Front Tires, 215/85R16E (10 ply) tubeless Radial, all season tread.	Inc.
RBZ	Rear Wheels, 16" X 6", 6-hole disc, painted white.	Inc.
I53I34	Rear Tires, 215/85R16E (10 ply) tubeless Radial, all season tread.	Inc.
ID4	Front Suspension, 6,830 lb. capacity. Semi-elliptical tapered leaf springs. Includes shock absorbers and stabilizer bar.	Inc.
L8T	Engine, GMPT 6.6L (400 CID) V8 gasoline engine; 350 HP at 4500 RPM; 425 lb-ft torque at 3800 RPM; precise fuel control direct injection technology; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads; forged steel crankshaft; stainless steel exhaust manifold.	Inc.
KW7	Alternator, 170 Amp. output with integral regulator.	Inc.
IE1	Brakes, Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard.	Inc.
N8X	Transmission, 8L90-E Hydra-Matic, 8-speed automatic with lock-up converter and overdrive. Gear Ratios: 4.56, 2.97, 2.08, 1.69, 1.27, 1.00, 0.85, 0.65, Rev. 3.82:1	Inc.
071	Ratio, 3.91:1	Inc.
IA9	Wheelbase, 132.5 inches 110"CA	Inc.
SUBTOTAL		\$69,164.00
DEF Fill Charge		\$0.00
Tire Weight Tax		\$0.00
Destination Charge		\$2,275.00
Surcharge		\$0.00
TOTAL MSRP PRICE		\$71,439.00