



Product Specifications

Load Capacity	Trailer Weight	Overall Length	Overall Width	Deck Width	Deck Length
12,000 lbs.	3,250 lbs.	24'3"	8'6"	82" between fenders	18'0" 16'0" flat deck + 2'0" beavertail

Frame Construction	<u>Mainbeams:</u> W6" x 12lbs. per ft., grade A36 hi-tensile <u>Crossmembers:</u> 4" channel, run between mainrails on 22" centers
Ramps	60" x 21.5" traction
Decking	2" nominal oak
Headboard	5" channel, full width of trailer
Tie Downs	(6) heavy duty D-rings, 3 per side
Suspension	Multi-point spring with equalizers

Axles	(2) 6,000 lb. capacity
Brakes	12" x 2" electric with integral break-away system
Tires	215/75R, x 17.5, (H)
Wheels	8 hole steel disc
Jack	12,000 lb. dropleg
Hitch	4 position cast steel pintle eye, 1- 5/8" stock, 2 5/8" I.D.
Lights	12 volt DOT & ICC approved. All lights are LED type and flush
Paint	Black urethane Rust prohibitive undercoating Available: Black, White, Red, Yellow, or Gray



Options

- Ramps (wood/traction, upright)
- Additional deck lengths
- Gooseneck
- Paint color matching or galvanizing
- Polished aluminum wheels
- Hydraulic jacks
- Toolbox lid or enclosure
- Tire upgrade
- Additional D-rings
- Apitong decking
- Hubodometer
- Spare tire/carrier