



Product Specifications

Load Capacity	Trailer Weight	Overall Length	Deck Width	Deck Length
24,000 lbs.	6,250 lbs.	29'0"	8'6"	24'0" (19'0" flat deck + 5'0" beavertail)

Frame Construction	Pierced mainbeam construction with one piece interlocking crossmembers <u>Mainbeams:</u> W12" x 16 lbs. per ft., grade 50 Hi-tensile <u>Crossmembers:</u> 6" I-beam x 3.9 lbs per ft., 80 KSI tensile strength on 22" centers <u>Siderails:</u> C8" x 11.5 lbs. per ft., grade 50 Hi-tensile
Ramps	60" x 21.5" traction with spring assist
Decking	2" nominal oak
Headboard	8" channel, full width of trailer
Tie Downs	(8) heavy duty D-rings, 4 per side

Suspension	Hutch 9700 multi-point spring with radius rod axle tracking adjustment, 44,000 lb. capacity.
Axles	(2) 12,000 lb. capacity with oil bath hubs
Brakes	12-1/4" x 5" electric with integral break-away system
Tires	(8) 235/80R16 (E)
Wheels	8 hole steel disc
Jack	12,000 lb. dropleg, side crank
Hitch	4 position cast steel pintle eye, 1-5/8" stock, 2-7/8" I.D.
Lights	Flush mounted LED in rubber grommets Modular wiring harness with 7-way plug
Paint	Black Urethane Rust prohibitive undercoating Available: Black, White, Red, Yellow, Gray



Options

- Ramps (Air, hydraulic, bi-fold, wood-filled)
- Additional deck lengths
- Gooseneck
- Paint color matching or galvanizing
- Spare tire/carrier
- Polished aluminum wheels
- Dual 2-speed jacks
- Hydraulic jacks
- Toolbox lid or enclosure
- Tire upgrade
- Additional D-rings
- Apitong decking
- Double break beavertail
- Bucket plate/well
- Hubodometer