



Vehicle: [Fleet] 2026 Chevrolet 4500 XD LCF Diesel (CT42003) 2WD Reg Cab 132.5" (  Complete )

## Price Summary

| PRICE SUMMARY      |                    |
|--------------------|--------------------|
|                    | MSRP               |
| Base Price         | \$73,745.00        |
| Total Options      | \$0.00             |
| Vehicle Subtotal   | \$73,745.00        |
| Destination Charge | \$1,975.00         |
| <b>Grand Total</b> | <b>\$75,720.00</b> |

This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided.  
Data Version: 28181. Data Updated: Apr 7, 2026 1:47:00 AM UTC.



Vehicle: [Fleet] 2026 Chevrolet 4500 XD LCF Diesel (CT42003) 2WD Reg Cab 132.5" ( Complete )

## Technical Specifications

### Powertrain

#### Transmission

|                               |                  |                                |           |
|-------------------------------|------------------|--------------------------------|-----------|
| Drivetrain                    | Rear Wheel Drive | Trans Order Code               | IR7       |
| Trans Type                    | 6                | Trans Description Cont.        | Automatic |
| Trans Description Cont. Again | N/A              | First Gear Ratio (:1)          | 3.742     |
| Second Gear Ratio (:1)        | 2.003            | Third Gear Ratio (:1)          | 1.343     |
| Fourth Gear Ratio (:1)        | 1.000            | Fifth Gear Ratio (:1)          | 0.773     |
| Sixth Gear Ratio (:1)         | 0.634            | Reverse Ratio (:1)             | N/A       |
| Clutch Size                   | N/A              | Trans Power Take Off           | N/A       |
| Final Drive Axle Ratio (:1)   | N/A              | Transfer Case Model            | N/A       |
| Transfer Case Power Take Off  | N/A              | Second Reverse Gear Ratio (:1) | N/A       |
| Third Reverse Gear Ratio (:1) | N/A              | Fourth Reverse Gear Ratio (:1) | N/A       |
| Fifth Reverse Gear Ratio (:1) | N/A              | Sixth Reverse Gear Ratio (:1)  | N/A       |
| Transmission Manufacturer     | Aisin A465       | Transmission Type              | N/A       |

#### Engine

|                          |            |                             |                        |
|--------------------------|------------|-----------------------------|------------------------|
| Engine Order Code        | I1B        | Engine Type                 | Turbocharged Diesel I4 |
| Displacement             | 5.2L/317   | Fuel System                 | Direct Injection       |
| SAE Net Horsepower @ RPM | 215 @ 2500 | SAE Net Torque @ RPM        | 452 @ 1850-2750        |
| Engine Oil Cooler        | N/A        | Governed Engine Speed (RPM) | N/A                    |
| Engine Series            | 4HK1-TC    |                             |                        |

#### Electrical

|                                     |     |                                    |     |
|-------------------------------------|-----|------------------------------------|-----|
| Cold Cranking Amps @ 0° F (Primary) | 750 | Cold Cranking Amps @ 0° F (2nd)    | N/A |
| Cold Cranking Amps @ 0° F (3rd)     | N/A | Maximum Alternator Capacity (amps) | 140 |

#### Cooling System

|                               |          |
|-------------------------------|----------|
| Total Cooling System Capacity | 20.8 qts |
|-------------------------------|----------|

This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided.  
Data Version: 28181. Data Updated: Apr 7, 2026 1:47:00 AM UTC.



Vehicle: [Fleet] 2026 Chevrolet 4500 XD LCF Diesel (CT42003) 2WD Reg Cab 132.5" ( Complete )

Vehicle

Vehicle

|                            |             |                             |             |
|----------------------------|-------------|-----------------------------|-------------|
| Axle Ratio - Low Rear (:1) | N/A         | As Spec Curb Weight - Front | 4194.00 lbs |
| As Spec Curb Weight - Rear | 2288.00 lbs |                             |             |

Chassis

Weight Information

|                              |              |                                              |              |
|------------------------------|--------------|----------------------------------------------|--------------|
| Standard Weight - Front      | 0.00 lbs     | Standard Weight - Rear                       | 0.00 lbs     |
| Total Weight                 | 6832.00 lbs  | Gross Axle Wt Rating - Front                 | 6630 lbs     |
| Gross Axle Wt Rating - Rear  | 11020 lbs    | Curb Weight - Front                          | 4194 lbs     |
| Curb Weight - Rear           | 2288 lbs     | Option Weight - Front                        | 0.00 lbs     |
| Option Weight - Rear         | 0.00 lbs     | Reserve Axle Capacity - Front                | 2436.00 lbs  |
| Reserve Axle Capacity - Rear | 8732.00 lbs  | As Spec'd Curb Weight                        | 6482.00 lbs  |
| As Spec'd Payload            | 9518.00 lbs  | Gross Combined Wt Rating                     | 22000 lbs    |
| Cargo Weight                 | 0.00 lbs     | Gross Vehicle Weight                         | 6832.00 lbs  |
| Axle Weight                  | N/A          | Gross Axle Weight Rating                     | 17650.00 lbs |
| Curb Weight                  | 6482.00 lbs  | Reserve Axle Capacity                        | 11168.00 lbs |
| Total Option Weight          | 0.00 lbs     | Payload Weight Front                         | 0.00 lbs     |
| Payload Weight Rear          | 0.00 lbs     | Maximum Axle Rating Front                    | 3450.00 lbs  |
| Maximum Axle Rating Rear     | 3245.00 lbs  | Maximum Axle Rating Total                    | 6695.00 lbs  |
| Gross Vehicle Weight Rating  | 16000.00 lbs | Front PayLoad                                | N/A          |
| Rear Payload                 | N/A          | Total Payload Weight (Cargo + Driver + Body) | 350.00 lbs   |

Frame

|                 |                       |                         |                      |
|-----------------|-----------------------|-------------------------|----------------------|
| Frame Type      | Ladder-Type C-Section | Sect Modulus Rails Only | 6.65 in <sup>3</sup> |
| Frame RBM       | 364420                | Frame Strength          | 54800 lbs            |
| Frame Thickness | 8.50 x 2.76 x 0.24 in |                         |                      |

Suspension

|                         |                                    |                        |                                  |
|-------------------------|------------------------------------|------------------------|----------------------------------|
| Suspension Type - Front | Independent w/Tapered Leaf Springs | Suspension Type - Rear | Independent w/Multi-Leaf Springs |
|-------------------------|------------------------------------|------------------------|----------------------------------|

This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided.  
Data Version: 28181. Data Updated: Apr 7, 2026 1:47:00 AM UTC.



Vehicle: [Fleet] 2026 Chevrolet 4500 XD LCF Diesel (CT42003) 2WD Reg Cab 132.5" ( Complete )

Chassis

Suspension

|                                 |          |                                |               |
|---------------------------------|----------|--------------------------------|---------------|
| Spring Capacity - Front         | 8440 lbs | Spring Capacity - Rear         | 14308 lbs     |
| Axle Type - Front               | I-Beam   | Axle Type - Rear               | Full-Floating |
| Axle Capacity - Front           | 6830 lbs | Axle Capacity - Rear           | 11020 lbs     |
| Axle Ratio (:1) - Front         | N/A      | Axle Ratio (:1) - Rear         | 4.777         |
| Shock Absorber Diameter - Front | 42.0 mm  | Shock Absorber Diameter - Rear | 42.0 mm       |
| Stabilizer Bar Diameter - Front | 1.65 in  | Stabilizer Bar Diameter - Rear | N/A           |

Tires

|                                  |             |                                   |             |
|----------------------------------|-------------|-----------------------------------|-------------|
| Front Tire Order Code            | 2TB         | Rear Tire Order Code              | 3TB         |
| Spare Tire Order Code            | N/A         | Front Tire Size                   | 225/70R19.5 |
| Rear Tire Size                   | 225/70R19.5 | Spare Tire Size                   | N/A         |
| Front Tire Capacity              | 3450 lbs    | Rear Tire Capacity                | 3245 lbs    |
| Spare Tire Capacity              | N/A         | Revolutions/Mile @ 45 mph - Front | 643         |
| Revolutions/Mile @ 45 mph - Rear | 643         | Revolutions/Mile @ 45 mph - Spare | N/A         |
| Tire Rating Total                | 6695.00     |                                   |             |

Wheels

|                     |                  |                      |                  |
|---------------------|------------------|----------------------|------------------|
| Front Wheel Size    | 19.5 x 6 in      | Rear Wheel Size      | 19.5 x 6 in      |
| Spare Wheel Size    | N/A              | Front Wheel Material | Steel            |
| Rear Wheel Material | Steel            | Spare Wheel Material | N/A              |
| Front Bolt Pattern  | 6 Hole JIS 8.75" | Rear Bolt Pattern    | 6 Hole JIS 8.75" |
| Spare Bolt Pattern  | N/A              |                      |                  |

Steering

|                                 |           |                                 |           |
|---------------------------------|-----------|---------------------------------|-----------|
| Steering Type                   | Pwr       | Steering Ratio (:1), On Center  | 18.8-20.9 |
| Steering Ratio (:1), At Lock    | 18.8-20.9 | Turning Diameter - Curb to Curb | 40.0 ft   |
| Turning Diameter - Wall to Wall | 44.9 ft   |                                 |           |

Brakes

|                                |     |                        |         |
|--------------------------------|-----|------------------------|---------|
| Brake Type                     | Pwr | Brake ABS System       | 4-Wheel |
| Brake ABS System (Second Line) | N/A | Disc - Front (Yes or ) | Yes     |

This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided.  
Data Version: 28181. Data Updated: Apr 7, 2026 1:47:00 AM UTC.



Vehicle: [Fleet] 2026 Chevrolet 4500 XD LCF Diesel (CT42003) 2WD Reg Cab 132.5" ( Complete )

Chassis

Brakes

|                                   |                |                                    |                 |
|-----------------------------------|----------------|------------------------------------|-----------------|
| Disc - Rear (Yes or )             | N/A            | Front Brake Rotor Diam x Thickness | 14.3 x -TBD- in |
| Rear Brake Rotor Diam x Thickness | N/A            | Drum - Front (Yes or )             | N/A             |
| Front Drum Diam x Width           | N/A            | Drum - Rear (Yes or )              | Yes             |
| Rear Drum Diam x Width            | 12.6 x 4.72 in |                                    |                 |

Fuel Tank

|                            |            |                                |     |
|----------------------------|------------|--------------------------------|-----|
| Fuel Tank Capacity, Approx | 30.0 gal   | Aux Fuel Tank Capacity, Approx | N/A |
| Fuel Tank Location         | Frame Rail | Aux Fuel Tank Location         | N/A |

Trailer

|                |         |
|----------------|---------|
| Trailer Weight | 0.0 lbs |
|----------------|---------|

Dimensions

Interior Dimensions

|                    |         |                     |         |
|--------------------|---------|---------------------|---------|
| Passenger Capacity | 3       | Front Head Room     | 38.4 in |
| Front Leg Room     | 29.5 in | Front Shoulder Room | 70.7 in |
| Front Hip Room     | 67.7 in |                     |         |

Exterior Dimensions

|                             |          |                                 |           |
|-----------------------------|----------|---------------------------------|-----------|
| Wheelbase                   | 132.5 in | Length, Overall w/o rear bumper | 219.20 in |
| Length, Overall             | N/A      | Width, Max w/o mirrors          | 81.3 in   |
| Height, Overall             | 92.4 in  | Overhang, Front                 | 48.4 in   |
| Overhang, Rear w/o bumper   | 43.1 in  | Front Bumper to Back of Cab     | 70.9 in   |
| Cab to Axle                 | 110.0 in | Cab to End of Frame             | 153.1 in  |
| Ground to Top of Load Floor | N/A      | Ground to Top of Frame          | 33.0 in   |
| Frame Width, Rear           | 33.5 in  | Ground Clearance, Front         | 7.5 in    |
| Ground Clearance, Rear      | 7.5 in   | Body Length                     | 0.0 ft    |
| Cab to Body                 | 0.0 in   | Frontal Area                    | 0.00 ft²  |

This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided.  
Data Version: 28181. Data Updated: Apr 7, 2026 1:47:00 AM UTC.



Vehicle: [Fleet] 2026 Chevrolet 4500 XD LCF Diesel (CT42003) 2WD Reg Cab 132.5" ( Complete )

Selected Model and Options

MODEL

| CODE    | MODEL                                                |
|---------|------------------------------------------------------|
| CT42003 | 2026 Chevrolet 4500 XD LCF Diesel 2WD Reg Cab 132.5" |

COLORS

| CODE | DESCRIPTION                   |
|------|-------------------------------|
| 16U  | Arc White (Extra cost color.) |

ENGINE

| CODE | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| I1B  | Engine, Diesel 5.2L 4 cylinder 215 hp [160.3 kW] @2500 rpm, 452 lb-ft of torque [612.8 Nm] @ 1850-2750 rpm (Governed). 16 valve, four cycle, chain-driven dual overhead camshaft valve train, a cast iron cylinder block, and a cast aluminum cylinder head. Turbocharged, inter-cooled, water cooled EGR, direct injection, electronically controlled common rail fuel system and engine cruise control. Oil level check switch and light. Engine warning system with audible warning for low oil pressure, high coolant temperature, and a protection system that will reduce fueling if excessive coolant temperature is detected (STD) |

TRANSMISSION

| CODE | DESCRIPTION                                                                                                                                                                                                            |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IR7  | Transmission, 6-speed automatic Aisin A465 transmission with fifth and sixth gear overdrive with lock up in 2nd, 3rd, 4th, 5th and 6th, PTO capability automatic torque converter lockup in stationary PTO mode. (STD) |

AXLE

| CODE | DESCRIPTION           |
|------|-----------------------|
| 029  | Rear axle, 4.77 ratio |

PREFERRED EQUIPMENT GROUP

| CODE | DESCRIPTION                                           |
|------|-------------------------------------------------------|
| 1WT  | Preferred Equipment Group includes standard equipment |

WHEELS

| CODE | DESCRIPTION                                                            |
|------|------------------------------------------------------------------------|
| PWK  | Wheels, 19.5" x 6, steel (STD) (Standard on 4500 XD and 5500 XD only.) |

This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided.  
Data Version: 28181. Data Updated: Apr 7, 2026 1:47:00 AM UTC.



Vehicle: [Fleet] 2026 Chevrolet 4500 XD LCF Diesel (CT42003) 2WD Reg Cab 132.5" (  Complete )

FRONT TIRES

| CODE | DESCRIPTION                                   |
|------|-----------------------------------------------|
| 2TB  | Tires, front, 225/70R19.5 F, all-season (STD) |

REAR TIRES

| CODE | DESCRIPTION                                                                          |
|------|--------------------------------------------------------------------------------------|
| 3TB  | Tires, rear, 225/70R19.5 F, all-season (Standard on 4500 XD and 5500 XD only.) (STD) |

PAINT

| CODE | DESCRIPTION                   |
|------|-------------------------------|
| 16U  | Arc White (Extra cost color.) |

SEAT TYPE

| CODE | DESCRIPTION                                                                                                                                                     |
|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| A1F  | Seat, front high back bucket driver and passenger tricoat cloth covered reclining high back driver seat with single two occupant fold down passenger seat (STD) |

SEAT TRIM

| CODE | DESCRIPTION                      |
|------|----------------------------------|
| HWG  | Medium Ash Gray, Cloth Seat Trim |

RADIO

| CODE | DESCRIPTION                                                                  |
|------|------------------------------------------------------------------------------|
| UIZ  | Audio System, AM/FM stereo with auxiliary jack, USB port and Bluetooth (STD) |

ADDITIONAL EQUIPMENT - OTHER

| CODE | DESCRIPTION                                                                                                         |
|------|---------------------------------------------------------------------------------------------------------------------|
| R6V  | California Restriction Acknowledgment. TRUCKS CANNOT BE SOLD OR REGISTERED IN CALIFORNIA. (Required on all orders.) |

Options Total

This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided.  
Data Version: 28181. Data Updated: Apr 7, 2026 1:47:00 AM UTC.



Vehicle: [Fleet] 2026 Chevrolet 4500 XD LCF Diesel (CT42003) 2WD Reg Cab 132.5" (  Complete )

## Standard Equipment

| Mechanical |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|            | Emissions, Federal certification. Does NOT meet California emissions requirements - TRUCKS CANNOT BE SOLD OR REGISTERED IN CALIFORNIA.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|            | Engine, Diesel 5.2L 4 cylinder 215 hp [160.3 kW] @2500 rpm, 452 lb-ft of torque [612.8 Nm] @ 1850-2750 rpm (Governed). 16 valve, four cycle, chain-driven dual overhead camshaft valve train, a cast iron cylinder block, and a cast aluminum cylinder head. Turbocharged, inter-cooled, water cooled EGR, direct injection, electronically controlled common rail fuel system and engine cruise control. Oil level check switch and light. Engine warning system with audible warning for low oil pressure, high coolant temperature, and a protection system that will reduce fueling if excessive coolant temperature is detected (STD) |
|            | Transmission, 6-speed automatic Aisin A465 transmission with fifth and sixth gear overdrive with lock up in 2nd, 3rd, 4th, 5th and 6th, PTO capability automatic torque converter lockup in stationary PTO mode. (STD)                                                                                                                                                                                                                                                                                                                                                                                                                     |
|            | Rear axle, 4.77 ratio                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|            | Air cleaner, heavy-duty, 11" diameter dry paper single element. Air cleaner canister standard with air restriction gauge. Back of cab location.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|            | Drivetrain, rear-wheel drive                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|            | Battery, dual 750 cold-cranking amps, 12 volt, maintenance free                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|            | Alternator, 140 amps                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|            | Frame, ladder-type channel frame. Full C section straight frame 33.5" (85.1 cm) wide.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|            | Incomplete vehicle certification                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|            | Wheelbase, 132.5" (336.6 cm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|            | GVWR, 16,000 lbs. (7257 kg)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|            | Front suspension, 8,440 lbs. (3828 kg) tapered leaf springs. Includes shock absorbers and stabilizer bar. (Standard on 4500 XD and 5500 XD only.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|            | Rear Suspension, 14,308 lbs. (6490 kg), tapered leaf spring with shock absorbers (Standard on 4500 XD only.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|            | Front axle, 6,830 lbs. (3098 kg), reverse Elliot "I"-beam includes integral hydraulic power steering with an 18.8-20.9:1 gear ratio (Standard on 4500 HD and 4500 XD only.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|            | Rear axle, 11,020 lbs. (4998 kg), full-floating with oil lubricated rear wheel-bearings                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|            | Vehicle Application Truck                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|            | Brakes, 4-wheel antilock, front and rear disc with traction control and stability control                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|            | Exhaust brake                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|            | Exhaust, single horizontal outlet                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|            | Fuel tank, 30 Gallon, (113L), stainless steel includes 2 auxiliary fuel ports                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Exterior   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|            | Wheels, 19.5" x 6, steel (STD) (Standard on 4500 XD and 5500 XD only.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided.  
Data Version: 28181. Data Updated: Apr 7, 2026 1:47:00 AM UTC.



Vehicle: [Fleet] 2026 Chevrolet 4500 XD LCF Diesel (CT42003) 2WD Reg Cab 132.5" (  Complete )

Exterior

|                                                                                       |
|---------------------------------------------------------------------------------------|
| Tires, front, 225/70R19.5 F, all-season (STD)                                         |
| Tires, rear, 225/70R19.5 F, all-season (Standard on 4500 XD and 5500 XD only.) (STD)  |
| Grille, Black                                                                         |
| Assist steps                                                                          |
| Glass, tinted                                                                         |
| LED Headlamps includes integrated LED turn signal indicators                          |
| Headlamp washer system                                                                |
| Mirror, outside left-hand and right hand dual cab-mounted with integral convex mirror |
| Windshield wiper, pulse, wet arm                                                      |

Entertainment

|                                                                              |
|------------------------------------------------------------------------------|
| Audio System, AM/FM stereo with auxiliary jack, USB port and Bluetooth (STD) |
| Audio system feature, 2 speakers                                             |

Interior

|                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Seat, front high back bucket driver and passenger tricoat cloth covered reclining high back driver seat with single two occupant fold down passenger seat (STD)                                                                                                                                                                                                                                                                  |
| Seat trim, Cloth                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Cup holders                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Floor mats                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Steering wheel, urethane                                                                                                                                                                                                                                                                                                                                                                                                         |
| Steering wheel, tilt and telescopic                                                                                                                                                                                                                                                                                                                                                                                              |
| Driver Information Center, (DIC) (monitors vital functions including diesel exhaust fluid levels (DEF), particulate matter emissions level in the diesel particulate filter (DPF), diesel particulate filter regeneration, service reminders for engine oil, transmission oil, differential oil, power steering fluid, engine oil filter, and fuel filters. Also provides fuel economy reporting by average, instant, and trip.) |
| Air conditioning, single-zone electronic, integral in-dash mounted                                                                                                                                                                                                                                                                                                                                                               |
| Windows, power                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Door locks, power                                                                                                                                                                                                                                                                                                                                                                                                                |
| Remote Keyless Entry                                                                                                                                                                                                                                                                                                                                                                                                             |
| Cruise control, electronic, automatic                                                                                                                                                                                                                                                                                                                                                                                            |
| Windshield washer bottle access on passenger side dash when passenger-side door is open                                                                                                                                                                                                                                                                                                                                          |
| Storage, door pockets                                                                                                                                                                                                                                                                                                                                                                                                            |
| Lighting, interior dome                                                                                                                                                                                                                                                                                                                                                                                                          |

This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided.  
Data Version: 28181. Data Updated: Apr 7, 2026 1:47:00 AM UTC.



Vehicle: [Fleet] 2026 Chevrolet 4500 XD LCF Diesel (CT42003) 2WD Reg Cab 132.5" (  Complete )

Interior

Rear dome and body lamp switch

Storage, seatback pockets

Safety-Interior

Airbags, frontal, driver and right front passenger

Safety-Mechanical

Brake, parking, cable actuated, internal expanding drum type, transmission-mounted

Tire Pressure Monitoring System

Safety-Exterior

Daytime Running Lamps

WARRANTY

Warranty Note: <<< Preliminary 2026 Warranty >>>  
Basic Years: 3  
Basic Miles/km: Unlimited  
Drivetrain Years: 3  
Drivetrain Miles/km: Unlimited  
Corrosion Years: 4  
Corrosion Miles/km: Unlimited  
Rear Axle Years: 3  
Rear Axle Miles/km: Unlimited  
Frame Rail Years: 3  
Frame Rail Miles/km: Unlimited  
Frame Rail Note: 3 years/Unlimited Miles (no charge) AND up to 5 years/Unlimited miles (50% charge)  
Roadside Assistance Years: 3  
Roadside Assistance Miles/km: Unlimited  
Maintenance Note: First Visit: 12 Months/12,000 Miles

This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided.  
Data Version: 28181. Data Updated: Apr 7, 2026 1:47:00 AM UTC.