



Rush Enterprises Inc (S040)
555 Interstate 35 S.
New Braunfels, Texas 78130

Stock

Colton Kruse
Cell Phone: 210-392-2213
Office Phone: 830-302-5219
Email: krusec@rushenterprises.com

Stock Order

Vehicle Summary

Unit		Chassis	
Model:	Model 220	Fr Axle Load (lbs):	12000
Type:	Full Truck	Rr Axle Load (lbs):	17000
Description 1:	HGAC Spec	G.V.W.R. (lbs):	26000
Description 2:		G.C.W. (lbs):	26000
Application		Road Conditions:	
Intended Serv.:	Tanker, Liquid Bulk	Class A (Highway)	100
Commodity:	Processed Foods	Class B (Hwy/Mtn)	0
Body		Class C (Off-Hwy)	0
Type:	Vacuum	Class D (Off-Road)	0
Length (ft):	16	Maximum Grade:	6
Height (ft):	13.5	Wheelbase (in):	146
Max Laden Weight (lbs):	1000	Overhang (in):	72
Trailer		Fr Axle to BOC (in):	11.4
No. of Trailer Axles:	0	Cab to Axle (in):	134.6
Type:		Cab to EOF (in):	206.6
Length (ft):	0	Overall Comb. Length (in):	269.6
Height (ft):	0	Special Req.	
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
Base Model				
0002201	S	Model 220 The Model 220 is a beautifully compact package offering driver comfort, easy service, entry safety features and vigorous power. The 220 is available with a GVW of 26,000-33,000 lbs. Designed for driver productivity, the Model 220 features 360-degree visibility, superior maneuverability, rugged protection and convenient storage. With low chassis weight, it's perfect for high-volume payloads while the standard Allison automatic transmission and air disc brakes help to provide a comfortable driver experience. The 220 is ideal for pickup and delivery as well as beverage and refuse applications, and it is available in a right-hand drive configuration for street sweepers and paint striper operations.	109,565	9,794
0070530	O	LFNA, Euro 6, LHD, Hi-HP, w/ Console, U.S. Registry	0	0
0091030	S	Processed Foods	0	0
0093020	S	Tanker, Liquid Bulk General freight (linehaul) service using a liquid bulk (non-bulk offloading) tanker body or tanker trailer.	0	0
0095130	S	Vacuum	0	0
0098170	O	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	O	Not Applicable Secondary Manufacturer	0	0
0210260	O	Class 6 Chassis Weight Rating 26,000 lb GVWR	0	0
Frame & Equipment				
0510170	S	10-1/4" Steel Rails, Steel Crossmembers	0	-55
0612620	O	146" Wheelbase, 72" Overhang Suitable for 16' Body Length.	158	0
0644090	S	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	0	0
0651090	S	Omit Rear Mudflaps and Hangers	0	0
Front Axle & Equipment				
1011850	S	Dana Spicer E1202IR 12,000 Lb.	0	0
1111190	S	Taper Leaf Springs, Shocks 12,000 lb Hendrickson taper leaf springs, shocks for 12,000 lbs.	0	0

Price Level: January 1, 2026

98% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251954-Q2R4H3

Printed On: 4/8/2026 6:31:12 AM



Sales Code	Std/Opt	Description	\$ List	Weight
1233140	S	Power Steering, 12K Capacity, Single Power Supplier: Bosch	0	0
1354850	O	PHP10 Iron PreSet PLUS Hubs - Air Disc Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	0	0
1380290	S	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0	0
Rear Axle & Equipment				
1513310	O	Dana Spicer P20060S 17,000 lb	154	92
1616300	O	PHP10 Iron PreSet PLUS Hubs	0	0
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680950	S	Stability System Not Selected Or Not Available	0	0
1683255	S	WABCO Electronic Braking System (EBS) With Antilock And Traction Control	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0	0
1704880	O	Ratio 4.88 Rear Axle	0	0
1816140	S	Reyco 79KB Taper Leaf 21,000 lb	0	0
Engine & Equipment				
2073506	O	PACCAR PX-7 200@2400 GOV@2600 600@1600 Efficiency (2024 Emissions)	137	0

Price Level: January 1, 2026

98% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251954-Q2R4H3

Printed On: 4/8/2026 6:31:12 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		N21350 C121 64....Maximum Accelerator Pedal Ve		
		N21370 C128 64....Maximum Cruise Speed (P059)		
		N21460 C132 1400..Max PTO Speed (P046)		
		N21520 C133 5.....Timer Setting (P030)		
		N21610 C188 39....Low Ambient Temperature Thre		
		N21620 C189 60....Intermediate Ambient Tempera		
		N21630 C190 80....High Ambient Temperature Thr		
		N21550 C206 35....Engine Load Threshold (P516)		
		N21340 C209 120...Hard Maximum Speed Limit (P1		
		N21510 C225 YES...Enable Idle Shutdown Park Br		
		N21450 C231 NO....Gear Down Protection (P026)		
		N21570 C233 NO....Idle Shutdown Manual Overrul		
		N21440 C234 NO....Engine Protection Shutdown (		
		N21480 C238 NO....Auto Engine Brake in Cruise		
		N21470 C239 NO....Cruise Control Auto Resume (		
		N21430 C333 0.....Reserve Speed Limit Offset (		
		N21410 C334 0.....Maximum Cycle Distance (N202		
		N21590 C382 YES...Enable Hot Ambient Automatic		
		N21500 C395 0.....Expiration Distance (N209)		
		N21530 C396 YES...Enable Impending Shutdown Wa		
		N21540 C397 60....Timer For Impending Shutdown		
		N21320 C399 100...Standard Maximum Speed Limit		
		N21400 C400 252...Reserve Speed Function Reset		
		N21420 C401 10....Maximum Active Distance (N20		
		N21330 C402 0.....Expiration Distance (N207)		
2091305	S	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Override	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0
2092016	O	Typical Operating Speed 62 MPH	0	0
2092031	O	Powertrain Optimized for Fuel Economy Best analysis for vehicles which operate at or near cruise speed 90 plus percent of time.	0	0
2140200	O	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140660	O	CARB Emission Compliant Engine	0	0
2140700	O	EPA Engine Idling Compliance	0	0
2513050	S	160 Amp Alternator, Brushed	0	0

Price Level: January 1, 2026

98% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251954-Q2R4H3

Printed On: 4/8/2026 6:31:12 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		160 amp alternator is a brush style alternator is designed to address vehicle applications that require higher electrical output, but also want lower weight, improved temperature capability and fuel savings.		
2521330	S	Cold Start Engine Grid Heater Effective to -4 F / -20 C	0	0
2522020	S	Delco 12V Starter PX-7 Engine. Delco Starter 12 volt used on utility/work trucks to power inverters, plug-in power tools, lights and other electrical equipment. Ideal for highway trucks with multiple battery auxiliary power units.	0	0
2538030	O	2 PACCAR Premium 12V Starting Batteries 2000 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2636030	S	Viscous Type Fan Clutch	0	0
2723210	S	18.7 CFM Air Compressor PX-7, PX-9, L9N, and B6.7N Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2921160	S	Spin-On Fuel/Water Separator	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 520 1242 sq in, 579 1325 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 567 1440 sq in, 589 1604 sq in.	0	0
3270020	S	(1) Air Cleaner Fender Mounted RH BOC	0	0
3280030	S	High Air Intake	0	0
3365290	O	Exhaust Single RH Horizontal DPF/SCR RH Under Frame.	0	0
3381770	S	Curved Tip Standpipe(s)	0	1
3381890	S	18" Ht, 4" Dia Standpipe(s) Aluminum, Steel Fin Only available with clear rail frame package	36	1
Transmission & Equipment				
4052900	O	Allison 2500 HS Transmission, Gen 6 Highway Series	0	0
4210930	S	SPL100 Driveline, 1 Midship Bearing	0	0

Price Level: January 1, 2026

98% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251954-Q2R4H3

Printed On: 4/8/2026 6:31:12 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
4252940	O	Allison Neutral At Stop Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0	0
4253160	O	Allison Fuelsense Dynactive With Dynamic Shift Sensing	0	0
4256020	S	Console Mounted Push Button Shifter	0	0
4256760	S	Allison 5-Speed Configuration, Wide Ratio Gears Allison 2500 transmissions only.	0	0
Air & Trailer Equipment				
4510830	S	WABCO SS1200 Plus Air Dryer, Heater Coalescing filter	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
Tires & Wheels				
5004480	O	FF: CN 14ply 11R22.5 HSR3	0	0
5104230	O	RR: CN 14ply 11R22.5 HDR2+	0	0
5190004	S	Code-rear Tire Qty 04	0	0
5212025	O	FF: Accu-Lite Steel Armor 51487PK 22.5X8.25 PHP 10-5 Hand Holes	0	0
5312025	O	RR: Accu-Lite Steel Armor 51487PK 22.5X8.25 PHP 10-5 Hand Holes	0	0
5390004	S	Code-rear Rim Qty 04	0	0
Fuel Tanks				
5516050	O	22" Aluminum 56 Gal Fuel Tank LH BOC	0	0
5604056	O	Location LH Behind Cab 56 Gallon	0	0
5652990	O	DEF To Fuel Ratio 2:1 Or Greater	0	0
5655059	S	DEF Tank Rectangular, 8 Gal	0	0

Price Level: January 1, 2026

98% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251954-Q2R4H3

Printed On: 4/8/2026 6:31:12 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
Battery Box & Bumper				
6020010	O	Steel Battery Box RH BOC Mounted on right-hand frame rail	0	0
6030630	O	Aluminum Battery Box Cover	0	0
6121210	S	Steel Bumper Painted Gray	0	0
Cab & Equipment				
6520020	S	Steel 63.5in BBC ProBilt Cab, LH Drive	0	0
6914130	S	Sears C2 Driver Seat	0	0
6924130	O	Sears C2 Passenger Seat	125	0
6939400	S	Air Ride Driver	0	0
6939420	S	High Back Driver	0	0
6939460	S	Fabric Driver	0	0
6939500	O	Air Ride Passenger	13	0
6939520	O	High Back Passenger	0	0
6939560	S	Fabric Passenger	0	0
7000015	S	Adjustable Steering Column - Tilt Only	0	0
7001540	S	Rear Wall Storage	0	0
7001620	S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7039180	S	Interior Gray Includes View Window in RH Door and 18 inch 4-spoke Foam Soft-Touch Steering Wheel.	0	0
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0	0
7230060	S	1-Piece Curved Windshield	0	0
7230170	S	Electric Powered Window Lift, LH/RH Side	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7561170	S	LH/RH Driving Mirrors Heated/Motorized Heated and motorized mirrors for left and right sides.	0	0

Price Level: January 1, 2026

98% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251954-Q2R4H3

Printed On: 4/8/2026 6:31:12 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
7722120	O	ConcertClass, AM/FM, Weatherband, 3.5 Aux	0	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7853030	O	Center Console with Storage & 2 Cup Holders	190	0
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0	0
8041200	S	Dual Scale Speedometer MPH Over KPH	0	0
8111150	S	Headlights Dual Round Halogen, Integral Turn Signals	0	0
8121010	S	(5) Marker Lights	0	0
8133270	S	Fog / Driving Lights	0	0
8133960	S	Daytime Running Lights The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0	0
8143270	S	Stop/Tail/Turn/Backup Lights RH/LH	0	0
Paint				
8530340	S	Axalta Single Stage Non-Metallic Cab/Hood (Solid Color Paint) N85020 A - M8870EA ICE WHITE DAF N85200 FRAME L0001EA BLACK	0	0
8531330	S	Medium Duty Paint Color M8870 Ice White Lead Time for Ice White Cab is 12 weeks.	0	0
Shipping Destination				
Options Not Subject To Discount				
9400091	S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0	0
9400093	S	PACCAR PX-7 Standard Coverage 3 years/Unlimited Miles/Unlimited hrs	0	0
9408702	O	Base Warr: Emissions (CARB Operation) 5YR/150K MI - PX-7 Engine	1,454	0
Miscellaneous				
9409093	O	State Of Registry: Texas	0	0
9409641	O	Model Year 2026 Engine	0	0
9409749	O	2024 Series Emissions Engine	0	0

Promotions

Price Level: January 1, 2026

98% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251954-Q2R4H3

Printed On: 4/8/2026 6:31:12 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
------------	----------	-------------	---------	--------

Special Requirements

Special Requirement 1 0098170
Special Requirement 2
Special Requirement 3
Special Requirement 4

Fuel Efficiency Score:

Order Comments

Total List Price (W/O Freight & Warranty & Surcharges)	\$110,378
Marketing and Service Support Fee	\$1,125
Prepaid Freight	\$5,000
Total Surcharge/Options Not Subject To Discount	\$1,454
Total Weight (lbs)	9,833

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------