



Rush Enterprises Inc (S040)
555 Interstate 35 S.
New Braunfels, Texas 78130

Stock

Colton Kruse
Cell Phone: 210-392-2213
Office Phone: 830-302-5219
Email: krusec@rushenterprises.com

Stock Order

Vehicle Summary

Unit		Chassis	
Model:	Model 520	Fr Axle Load (lbs):	20000
Type:	Full Truck	Rr Axle Load (lbs):	45400
Description 1:	HGAC Spec	G.V.W.R. (lbs):	62000
Description 2:		G.C.W. (lbs):	62000
Application		Road Conditions:	
Intended Serv.:	Refuse/On-Highway	Class A (Highway)	100
Commodity:	Refuse, Scrap, Recycling	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	
Type:	Residential Front Loader		6
Length (ft):	24	Wheelbase (in):	195
Height (ft):	8	Overhang (in):	54
Max Laden Weight (lbs):	2000	Fr Axle to BOC (in):	0.1
Trailer		Cab to Axle (in):	194.9
No. of Trailer Axles:	0	Cab to EOF (in):	248.9
Type:		Overall Comb. Length (in):	306.3
Length (ft):	0	Special Req.	
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/Opt	Description	\$ List	Weight
Base Model				
0005201	S	Model 520 Peterbilt's Model 520 is built to withstand the harsh demands of the refuse industry. The rugged, aluminum cab delivers best-in-class durability for increased uptime and lap seam construction on a zinc-coated steel sub-frame for corrosion resistance. Bulkhead-style doors provide years of watertight performance. This low-cab forward vehicle adds a new dimension of productivity and versatility. An industry-leading, 65-degree cab tilt enhances maintenance and serviceability. Body installation is cost effective and efficient and the center console provides convenient access to body control integration points.	232,861	16,475
0091180	S	Refuse, Scrap, Recycling	0	0
0093035	S	Refuse/On-Highway Truck or tractor which hauls refuse, recycled material, etc. Includes roll-on/roll-off container movement, as well as hauling refuse from transfer stations to, but not into, landfills.	0	0
0095350	O	Residential Front Loader	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	O	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0514150	S	10-3/4" Steel Rails To 305" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	0	87
0601500	S	Full Steel Inner Liner	1,054	616
0644090	S	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	0	0
0651090	S	Omit Rear Mudflaps and Hangers	0	0
0713130	S	(2) Solid Mount Cable Hooks	0	40
Front Axle & Equipment				
1011890	S	PACCAR FX-20 Steer Axle 20,000 lbs. 4" Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Front axle is designed for demanding applications such as construction, heavy haul, refuse, and other vocational uses. Robust forged steel beam construction for long-lasting performance. It utilizes innovative tapered kingpin roller bearings for	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251938-D2Q3Y9

Printed On: 4/7/2026 3:20:44 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
		more efficient operation and improved steering efficiency.		
		The PACCAR Steer Axle comes standard with the PACCAR warranty of 5 years, 750,000 miles.		
1114040	O	Taper Leaf Springs, Shocks 23,000 lb Standard with Heavy Resistance Shocks.	407	210
1243010	S	Power Steering Sheppard M100 Dual Gear For use with 16,000 to 20,000 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	0	0
1354850	S	PHP10 Iron PreSet PLUS Hubs - Air Disc Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	0	0
1354870	S	Severe Service Disc Brake Rotor For refuse applications, providing the braking torque necessary to slow or stop the vehicle.	0	0
1380290	S	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0	0
Rear Axle & Equipment				
1523440	S	Dana Spicer D46-172 46,000 LBS Dana Spicer D46-172 46,000 lbs tandem drive axles offer efficiency improvement, axle weight reduction and reduced lube quantity.	0	0
1616305	S	PHP10 Iron Preset + Hubs - Air Disc	0	0
1616310	O	Severe Service Disc Brake Rotor Severe Service Disc Brake Rotor for refuse applications.	0	0
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680525	O	Pneumatic Park Brake	0	0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251938-D2Q3Y9

Printed On: 4/7/2026 3:20:44 PM



Sales Code	Std/Opt	Description	\$ List	Weight
1687040	S	Air Disc Rear Brakes, Tandem Drive Axle Includes Automatic Slack Adjusters.	0	0
1705380	O	Ratio 5.38 Rear Axle	0	0
1821860	O	Peterbilt Air Trac 46,000 lbs, 52in Axle Spacing Light Weight	0	0
1920385	O	Air Springs, Internal Bumpers Air Trac / Air Leaf suspensions	55	0
1922260	O	Dash Mtd Dump Switch with Indicator Light Dash mounted dump switch with indicator light for suspension.	93	2

Engine & Equipment

2074808	O	PACCAR PX-9 360@2000 GOV@2200 1150@1200 Productivity (2024 Emissions)	0	0
		N21350 C121 64....Maximum Accelerator Pedal Ve N21370 C128 64....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 5.....Timer Setting (P030) N21610 C188 39....Low Ambient Temperature Thre N21620 C189 60....Intermediate Ambient Tempera N21630 C190 80....High Ambient Temperature Thr N21550 C206 35....Engine Load Threshold (P516) N21340 C209 120...Hard Maximum Speed Limit (P1 N21510 C225 YES...Enable Idle Shutdown Park Br N21450 C231 NO....Gear Down Protection (P026) N21570 C233 NO....Idle Shutdown Manual Overrul N21440 C234 NO....Engine Protection Shutdown (N21480 C238 NO....Auto Engine Brake in Cruise N21470 C239 NO....Cruise Control Auto Resume (N21430 C333 0.....Reserve Speed Limit Offset (N21410 C334 0.....Maximum Cycle Distance (N202 N21590 C382 YES...Enable Hot Ambient Automatic N21500 C395 0.....Expiration Distance (N209) N21530 C396 YES...Enable Impending Shutdown Wa N21540 C397 60....Timer For Impending Shutdown N21320 C399 100...Standard Maximum Speed Limit N21400 C400 252...Reserve Speed Function Reset N21420 C401 10....Maximum Active Distance (N20 N21330 C402 0.....Expiration Distance (N207)		
2091120	O	EMUX Electronics Architecture	0	0
2091305	S	Engine Idle Shutdown Timer Enabled	0	0
2091315	S	Enable EIST Ambient Temp Override	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251938-D2Q3Y9

Printed On: 4/7/2026 3:20:44 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
2092016	O	Typical Operating Speed 62 MPH	0	0
2092033	O	Powertrain Optimized for Balance Best analysis for vehicles where service includes frequent start and stop cycles.	0	0
2140200	O	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140450	O	Remote PTO/Throttle, 12-Pin Eng Bay Remote Control Provision	106	0
2140660	O	CARB Emission Compliant Engine	0	0
2140700	O	EPA Engine Idling Compliance	0	0
2147460	O	Bed Plate for PX-9, L9N Engines Designed to increase engine longevity by incorporating a stiffener bracket on the bottom side of the engine, inside the oil pan, for additional reinforcement. Required for all PX-9/L9N refuse applications and recommended for other high load 9-liter applications.	0	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	S	Immersion Type Block Heater 110-120V Standard location is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	92	2
2522110	O	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0	0
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539740	S	Kissling Battery Disconnect Switch 300AMP Dual Tab Mounted on Battery Box	164	3
2621000	S	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	0	0
2723210	S	18.7 CFM Air Compressor PX-7, PX-9, L9N, and B6.7N Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2921110	O	PACCAR Fuel/Water Separator Standard Service PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251938-D2Q3Y9

Printed On: 4/7/2026 3:20:44 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 520 1242 sq in, 579 1325 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 567 1440 sq in, 589 1604 sq in.	0	0
3120450	S	Stainless Steel Grille	0	0
3261980	S	Heavy Duty Air Cleaner Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3367200	O	Exhaust Vertical LH DPF/SCR LH Back of Cab Vertical, Single Module	0	0
3387610	O	18" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	9	-2
Transmission & Equipment				
4052920	O	Allison 3000 RDS-P Transmission, Gen 6 Rugged Duty Series	0	0
4211000	O	SPL170 HD-XL Driveline, 1 Midship Bearing	0	0
4216330	S	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles.	0	0
4252890	O	Allison FuelSense Not Desired Dynamic Shift Sensing	-131	0
4252940	O	Allison Neutral At Stop Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0	0
4256020	S	Console Mounted Push Button Shifter	0	0
4256350	S	Auto Neutral AK, Allison HD/RDS Single steer left-hand or right-hand, add code 4540940 if plumbed to flip valve to actuate service brakes is desired	298	0
4256450	S	Allison MD/HD Shift Select AL Dual station controls	3	0
4256640	O	Allison 6-Speed Configuration, Close Ratio Gears	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251938-D2Q3Y9

Printed On: 4/7/2026 3:20:44 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
		3000 Series Transmissions.		
4256870	O	Allison Output Function S Neutral Indicator Allison output function S Neutral Indicator for PTO. Required on Refuse Packer Applications. With this configuration NEUTRAL only, PTO engagement is permitted only when the transmission is in Neutral. Once the transmission is in Neutral, the PTO is automatically engaged and fast idle is initiated when the PTO switch is on. In addition with this configuration Pack-on-the-fly, the PTO is automatically engaged and fast idle is initiated when the PTO switch is On concurrently with shifting of the transmission to Neutral.	0	0
Air & Trailer Equipment				
4510210	S	Bendix AD-HF EP Air Dryer, Heater Coalescing filter, extended purge. Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0	0
4520420	S	Pull Cords All Air Tanks	4	1
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4612000	S	Route AE Lines To Allow Welding Of Sub Frame To top of frame 8" forward of back-of-cab to end-of-frame	670	0
Tires & Wheels				
5004040	S	FF: CN 20ply 315/80R22.5 HAU3 WT Efficiency Rating: Fair Waste transportation and other high scrub, urban applications.	0	0
5104770	O	RR: CN 14Ply 295/75R22.5 HDL3 ECO+	0	0
5190008	S	Code-rear Tire Qty 08	0	0
5210550	S	FF: Accur Stl Armor 29039PK 22.5X9.00 PHP10-5 Hand Holes	0	0
5310600	S	RR: Accur Stl Armor 50291PK 22.5X8.25 Heavy Duty, Two Hand Holes	0	0
5390008	S	Code-rear Rim Qty 08	0	0
Fuel Tanks				
5532040	O	23" Aluminum 50 Gallon Fuel Tank RH BOC	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251938-D2Q3Y9

Printed On: 4/7/2026 3:20:44 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
		Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.		
5603050	O	Location RH BOC 50 Gallon	0	0
5650490	O	Fuel Cooler Required with single fuel tank	0	0
5652890	O	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	O	DEF To Fuel Ratio 2:1 Or Greater	0	0
5655069	O	DEF Tank 520, 7.3 Gal	0	0
Battery Box & Bumper				
6010050	O	Narrow Steel Battery Box Mounted LH BOC	355	13
6122810	S	Steel Bumper Swept Back Painted Requires bumper extension, includes two front tow eyes with pins	-21	2
6132400	S	Notched Top Flange Of Bumper Does not include fepto provisions	50	0
6132420	S	4-7/8" Bumper Extension, Without FEPTO	483	31
Cab & Equipment				
6501080	O	53" LCF ProBilt Cab LH Drive Includes steel frames with alum and fiberglass panels, all alum doors, dual door stops, door locks, tinted safety glass thru-out, cab and door mounted entry grab handles, 65 degree hydraulic tilt, stainless steel grille, dual rear cab fenders, service module BOC (cab tilt pump, oil fill and dipstick, coolant fill and check, fluid fill and dipstick for auto trans), door mounted armrests, power windows, doghousefull insulation, rubber floor mats, ergonomic center control console, removable instrument panel, Driver Information Display, LED backlit gauges, adjustable side flip-down interior sunvisor, 16" steering wheel with integrated horn button, tilt/telescopic adjustable column, over-door storage, driver and passenger side cup holders, USB charging port and 12VDC charging outlet, header includes HVAC controls and 12V power connection behind header cover, rear cab corner windows, 18" bolt-on step each side, self-canceling turn signals and front directional and side mounted turn signals.	0	0
6800500	S	4.5" Rubber Flares On Cab And wheel well fenders	0	0
6911720	S	Peterbilt Driver Seat	0	0
6921720	S	Peterbilt Passenger Seat	0	0
6939410	S	Non-Air Ride Driver	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251938-D2Q3Y9

Printed On: 4/7/2026 3:20:44 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
6939440	S	Low Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939510	S	Non-Air Ride Passenger	0	0
6939520	S	High Back Passenger	45	0
6939560	S	Fabric Passenger	53	0
7000000	S	Gray Interior Color Includes ABS Gray Headliner & Rear Cab Panel, Gray Vinyl Engine Tunnel Cover. For LH, RH, and Dual Steer Dual Seated Power Windows are standard on both doors. For Dual Steer RH stand-up the LH Window is Power and the RH Window is a Manual Sliding window.	0	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	0
7001620	S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7110680	S	Exterior Cab Entry Grabhandle Textured; NFPA compliant. Available on Day Cab specifications only.	0	0
7220130	S	Rear Window Back of Cab Standard Tint 18.5in X 54in	0	0
7230350	S	2-Piece Flat Windshield	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7561260	S	Black LH/RH Tri-plane Mirrors, Heated, Motorized, Mounted to Doors. Features: Heated on All Three Surfaces, Upper/Lower Mirrors are Convex and Middle is a Flat Pane Motorized Mirror.	0	0
7610020	S	(1) Air Horn 15" Painted Mounted under cab.	0	0
7722120	O	ConcertClass, AM/FM, Weatherband, 3.5 Aux	509	10
7725740	S	Midlevel Speaker Package For Cab (4) Speakers	139	6
7788335	O	Global Telematics Hardware	0	0
7851870	S	Rain Gutters Over Driver and Passenger Doors	84	8
7852150	S	Peterbilt Pantograph Windshield Wipers With intermittent feature.	0	0
7900970	S	Backup Alarm Wiring To EOF	0	0
8021315	O	Air Restriction Indicator Mounted on exhaust stanchion	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251938-D2Q3Y9

Printed On: 4/7/2026 3:20:44 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
8031120	S	Warning Light Battery Disconnect, Switch Engaged Marker light external mounted	14	0
8070860	O	Main Instrumentation Panel Digital Cluster 7" Display includes: Physical (Analog) - Speedometer, Tachometer, Oil Pressure, Coolant Temp and Display Gauges - Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure for air brake trucks.	0	0
8110090	S	Headlights Single Rectangular Halogen	0	0
8120550	S	(5) Light Guards On Marker Lights	20	2
8120570	S	(5) LED Clearance With (2) LED Marker Lights Includes (5) lights mounted on roof of cab and (1) cab side marker light mounted in front of each cab door	0	0
8133900	S	None Furnished Stop/Tail/Backup Lights Available with full truck only, not available with tractor	0	0
8133960	S	Daytime Running Lights The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0	0
8134160	O	Self-Canceling Turn Signal	0	2
Paint				
8500710	S	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85700 BUMPER L0001EA BLACK N85500 CAB ROOF L0006EY WHITE N85200 FRAME L0001EA BLACK	0	0
Shipping Destination				
Options Not Subject To Discount				
9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0
9400094	O	PACCAR PX-9 Standard Coverage 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0	0
9407147	O	Fuel Price Index Factor \$342 NET	342	0
9408634	O	SmartLINQ RD - 5YR Sub PACCAR PX Engines	799	0
9408701	O	Base Warr: Emissions (CARB Operation) 5YR/150K MI - PX-9 Engine	2,186	0
Miscellaneous				
9409093	O	State Of Registry: Texas	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251938-D2Q3Y9

Printed On: 4/7/2026 3:20:44 PM



Sales Code	Std/Opt	Description	\$ List	Weight
9409641	O	Model Year 2026 Engine	0	0
9409749	O	2024 Series Emissions Engine	0	0
9499988	O	DO NOT DRIVE (Dealer/Customer Request)	750	0

Promotions

Special Requirements

Special Requirement 1 0098170

Special Requirement 2

Special Requirement 3

Special Requirement 4

Fuel Efficiency Score:

Order Comments

Total List Price (W/O Freight & Warranty & Surcharges)	\$237,966
Marketing and Service Support Fee	\$1,725
Prepaid Freight	\$4,500
Total Surcharge/Options Not Subject To Discount	\$3,327
Total Weight (lbs)	17,508

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251938-D2Q3Y9

Printed On: 4/7/2026 3:20:44 PM



the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------