



Rush Enterprises Inc (S040)
555 Interstate 35 S.
New Braunfels, Texas 78130

Stock

Colton Kruse
Cell Phone: 210-392-2213
Office Phone: 830-302-5219
Email: krusec@rushenterprises.com

Stock Order

Vehicle Summary

Unit		Chassis	
Model:	Model 548	Fr Axle Load (lbs):	12350
Type:	Full Truck	Rr Axle Load (lbs):	22700
Description 1:	HGAC Spec	G.V.W.R. (lbs):	35050
Description 2:		G.C.W. (lbs):	49000
Application		Road Conditions:	
Intended Serv.:	City Delivery	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
Body		Class C (Off-Hwy)	0
Type:	Van	Class D (Off-Road)	0
Length (ft):	24	Maximum Grade:	6
Height (ft):	13.5	Wheelbase (in):	152
Max Laden Weight (lbs):	1000	Overhang (in):	45
Trailer		Fr Axle to BOC (in):	67.5
No. of Trailer Axles:	0	Cab to Axle (in):	84.5
Type:		Cab to EOF (in):	129.5
Length (ft):	0	Overall Comb. Length (in):	237
Height (ft):	0	Special Req.	
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
Base Model				
0005481	S	Model 548 The Model 548 meets and exceeds the demands of Class 8 specialty application markets that require a rugged workhorse for durability and a wide range of optional content. The Model 548 is available in configurations with a GVW from 33,001 to 66,000 lbs. to suit most vocational applications. The 548 also offers all-wheel-drive. From construction and crane service to utility and delivery services in Class 8 markets, the 548 is in a class of its own.	127,020	10,860
0091200	S	Other Commodity	0	0
0093340	S	City Delivery Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery.	0	0
0095040	S	Van	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0515030	S	10-5/8" Steel Rails to 285" 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	0	-35
0611300	S	Heavy Duty 5-Piece Crossmember BOC IPO Standard Class 5, 6, 7	0	0
0611790	S	Aluminum Frame Rail Crossmembers Excludes suspension	0	0
0612005	O	152" Wheelbase	0	0
0613095	O	3-Piece Suspension Crossmembers	82	0
0644090	S	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	0	0
0651010	S	Peterbilt Rear Mudflaps and Straight Hangers Mudflaps aid in protecting the frame and undercarriage from road salt, grime and debris that can cause rust and corrosion. Mud flaps also shield other vehicles from gravel, rocks and road spray.	0	0
Front Axle & Equipment				

Price Level: January 1, 2026

100% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251951-H0V5J9

Printed On: 4/7/2026 7:18:14 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
1014190	S	Hendrickson SteerTek NXT 12,500 lb 3.32" Drop	0	0
1111200	S	Taper Leaf Springs, Shocks 13,200 lb Hendrickson taper leaf springs for 13,200 lbs. offer high value to weight ratio.	0	0
1243040	S	Power Steering Sheppard HD94 Sheppard HD94 power steering gear is a light weight version of heavy duty line-haul power steering gear. For use with 10,000 to 13,200 lb. axle ratings.	0	0
1250180	S	Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1354840	S	PHP10 Iron PreSet PLUS Hubs PHP10 iron PreSet PLUS hubs have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug on drive and trailer hubs for inspection of metal particles in lubricant, with a long life oil seal and bearings are pre-adjusted. Use with Front Axle.	0	0
1380260	S	Bendix Air Cam Front Drum Brakes 16.5x5 For use with 10,000 lbs to 14,600 lbs steer axles. Includes automatic slack adjusters & outboard mounted brake drums.	0	0
1380550	O	Hendrickson Wide Track IPO Standard Hendrickson Wide Track in place of standard front axle 71" KPI IPO 69" front axle for improved turning radius.	0	0
1391410	S	Gusseted Cam Brackets, Steer Axle	0	0
Rear Axle & Equipment				
1511110	S	Meritor RS23-160 23,000 lb	0	0
1616300	S	PHP10 Iron PreSet PLUS Hubs	0	0
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680525	O	Pneumatic Park Brake	0	0
1680950	S	Stability System Not Selected Or Not Available	0	0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0	0
1683245	S	Tire Pressure Monitoring System	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the	0	0

Price Level: January 1, 2026

100% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251951-H0V5J9

Printed On: 4/7/2026 7:18:14 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
		lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.		
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0	0
1704560	O	Ratio 4.56 Rear Axle	0	0
1816020	S	Reyco 79KB Multi Leaf 23,000 Lb	0	0
Engine & Equipment				
2074802	S	PACCAR PX-9 260@2200 GOV@2200 860@1200 Productivity (2024 Emissions)	0	0
		N21350 C121 64....Maximum Accelerator Pedal Ve N21370 C128 64....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 5.....Timer Setting (P030) N21610 C188 39....Low Ambient Temperature Thre N21620 C189 60....Intermediate Ambient Tempera N21630 C190 80....High Ambient Temperature Thr N21550 C206 35....Engine Load Threshold (P516) N21340 C209 120...Hard Maximum Speed Limit (P1 N21510 C225 YES...Enable Idle Shutdown Park Br N21450 C231 NO....Gear Down Protection (P026) N21570 C233 NO....Idle Shutdown Manual Overrul N21440 C234 NO....Engine Protection Shutdown (N21480 C238 NO....Auto Engine Brake in Cruise N21470 C239 NO....Cruise Control Auto Resume (N21430 C333 0.....Reserve Speed Limit Offset (N21410 C334 0.....Maximum Cycle Distance (N202 N21590 C382 YES...Enable Hot Ambient Automatic N21500 C395 0.....Expiration Distance (N209) N21530 C396 YES...Enable Impending Shutdown Wa N21540 C397 60....Timer For Impending Shutdown N21320 C399 100...Standard Maximum Speed Limit N21400 C400 252...Reserve Speed Function Reset N21420 C401 10....Maximum Active Distance (N20 N21330 C402 0.....Expiration Distance (N207)		
2091120	S	EMUX Electronics Architecture	0	0
2091305	O	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Override	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0

Price Level: January 1, 2026

100% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251951-H0V5J9

Printed On: 4/7/2026 7:18:14 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
2092017	S	Typical Operating Speed 68 MPH	0	0
2092031	S	Powertrain Optimized for Fuel Economy Best analysis for vehicles which operate at or near cruise speed 90 plus percent of time.	0	0
2140460	S	Remote PTO/Throttle, 12-Pin, 250K BOC/BOS J1939, Remote Control Provision	0	0
2140590	S	14-Pin Body Lighting Connector, BOC	0	0
2140670	O	EPA Emission Compliant Engine	0	0
2140700	S	EPA Engine Idling Compliance	0	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2522110	S	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0	0
2538030	S	2 PACCAR Premium 12V Starting Batteries 2000 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539720	O	Low Voltage Disconnect System	0	0
2621090	S	HORTON ON/OFF Fan Clutch	0	0
2723210	S	18.7 CFM Air Compressor PX-7, PX-9, L9N, and B6.7N Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2812210	S	VGT Exhaust Brake (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger.	0	0
2921110	S	PACCAR Fuel/Water Separator Standard Service PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 520 1242 sq in, 579	0	0

Price Level: January 1, 2026

100% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251951-H0V5J9

Printed On: 4/7/2026 7:18:14 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
		1325 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 567 1440 sq in, 589 1604 sq in.		
3211140	S	(1) Air Cleaner Engine Mounted	0	0
3367170	S	Exhaust Single RH Horizontal DPF/SCR RH Under Cab, Single Module	0	0
Transmission & Equipment				
4058070	S	PACCAR TX-8 8AP860 Automatic 8-Speed, No Cooler, W/PTO	0	0
4211100	O	SPL140 HD Driveline, 1 Midship Bearing	128	-55
4252610	S	Column Mounted Shifter RH Side	0	0
4256405	O	TP1150N Torque Converter Paccar 8 Speed Transmission	0	0
Air & Trailer Equipment				
4510190	S	Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0	0
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
Tires & Wheels				
5004210	S	FF: CN 14ply 295/75R22.5 Conti HSL3	0	0
5104210	S	RR: CN 14ply 295/75R22.5 Conti HSL3	0	0
5190004	O	Code-rear Tire Qty 04	0	0
5211020	S	FF: Accur Stl Armor 51455PK 22.5X8.25 PHP10-5 hand holes.	0	0
5311020	S	RR: Accur Stl Armor 51455PK 22.5X8.25 PHP10-5 hand holes.	0	0
5390004	O	Code-rear Rim Qty 04	0	0
Fuel Tanks				

Price Level: January 1, 2026

100% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251951-H0V5J9

Printed On: 4/7/2026 7:18:14 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
5582040	S	D-Shaped Aluminum 50 Gallon Fuel Tank RH BOC	0	0
5603050	S	Location RH BOC 50 Gallon	0	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	O	DEF To Fuel Ratio 2:1 Or Greater	0	0
5655019	S	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	0	0
Battery Box & Bumper				
6020030	S	MD Battery Box, Non-Slip Step LH Under Cab	0	0
6030660	S	Plastic Battery Box Cover	0	0
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6121790	S	Aero Bumper Molded One Piece Gray ***Warning*** Due to a new legal regulations, all New Medium Duty trucks require headlights to be located in the bumper when the chassis height is GREATER than the following chassis height: Measurement to bottom of frame at front of frame: for the 107 Aero Hood 32.6, for the 109 Aero Hood 31.4, for the 109 Vocational Hood 26.7. Work with applications if your chassis height is unacceptable.	0	0
Cab & Equipment				
6510180	S	Peterbilt Aerodynamic 107in BBC SMC Hood With molded charcoal crown and aluminum cab.	0	0
6914180	S	Sears Driver Seat	0	0
6924180	S	Sears Passenger Seat	0	0
6939110	S	Toolbox Under Passenger Seat Non-Suspension Seat	0	0
6939400	S	Air Ride Driver	0	0
6939430	S	Mid Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939510	S	Non-Air Ride Passenger	0	0
6939530	S	Mid Back Passenger	0	0

Price Level: January 1, 2026

100% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251951-H0V5J9

Printed On: 4/7/2026 7:18:14 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
6939570	S	Vinyl Passenger	0	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	0
7001620	S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7036140	S	Probilt Interior Charcoal Gray - Flat Roof	0	0
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0	0
7210550	S	1-Piece Glass Rear Cab Window Fixed	0	0
7230060	S	1-Piece Curved Windshield	0	0
7230360	S	Power Door Locks and Power Window Lifts Standard	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7510070	S	Aero Rear View Mirror Housing, Molded Black	0	0
7514050	S	Look Down Mirror Over Passenger Door with Black Housing	0	0
7514090	S	Peterbilt Aero Rear View Mirror, Non-Motorized Includes top mirror with non-motorized, adjustable dual axis non-heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	0	0
7610500	S	Air Horn Mounted Under Cab	0	0
7725720	S	No Head Unit or Audio Speakers Selected	0	0
7788335	S	Global Telematics Hardware	0	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7852060	S	Solid Rear Day Cab Mounts	0	0
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0	0
8041200	O	Dual Scale Speedometer MPH Over KPH	0	0
8070860	S	Main Instrumentation Panel Digital Cluster 7" Display includes: Physical (Analog) - Speedometer, Tachometer, Oil Pressure, Coolant Temp and Display Gauges - Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure for air brake trucks.	0	0

Price Level: January 1, 2026

100% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251951-H0V5J9

Printed On: 4/7/2026 7:18:14 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
8111110	S	Headlights Composite Fender Mounted Integral DRL/Park, Turn, and Side Marker	0	0
8120980	S	(5) Marker Lights, Aero LED Standard Black Housing. Chrome Housing available with Sun Visor.	0	0
8134160	S	Self-Canceling Turn Signal	0	0
8140080	S	LED Stop/Turn/Tail/Backup Bracket mounted left-hand / right-hand end of frame	0	0
8140850	S	Moveable EOF Crossmember For Mounting Tail Lights Square end of frame with or without end of frame crossmember	0	0

Paint

8500710	S	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	0

Shipping Destination

Options Not Subject To Discount

9400091	S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0	0
9400094	S	PACCAR PX-9 Standard Coverage 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0	0
9408634	O	SmartLINQ RD - 5YR Sub PACCAR PX Engines	799	0
9408703	O	Base Warr: Emissions 5YR/100K MI	0	0

Miscellaneous

9409045	S	Aero Hood (MODEL 548)	0	0
9409093	O	State Of Registry: Texas	0	0
9409641	O	Model Year 2026 Engine	0	0
9409749	O	2024 Series Emissions Engine	0	0

Promotions

Price Level: January 1, 2026

100% Complete

Date: April 08, 2026

Deal: HGAC Spec

Quote Number: QUO-1251951-H0V5J9

Printed On: 4/7/2026 7:18:14 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
------------	----------	-------------	---------	--------

Special Requirements

Special Requirement 1 0098170
Special Requirement 2
Special Requirement 3
Special Requirement 4

Fuel Efficiency Score:

Order Comments

Total List Price (W/O Freight & Warranty & Surcharges)	\$127,030
Marketing and Service Support Fee	\$1,725
Prepaid Freight	\$3,725
Total Surcharge/Options Not Subject To Discount	\$799
Total Weight (lbs)	10,770

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information





Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------