



Rush Enterprises Inc (S040)
555 Interstate 35 S.
New Braunfels, Texas 78130

Stock

Colton Kruse
Cell Phone: 210-392-2213
Office Phone: 830-302-5219
Email: krusec@rushenterprises.com

Stock Order

Vehicle Summary

Unit		Chassis	
Model:	Model 579	Fr Axle Load (lbs):	12500
Type:	Tractor	Rr Axle Load (lbs):	40000
Description 1:	HGAC Spec	G.V.W.R. (lbs):	52500
Description 2:		G.C.W. (lbs):	80000
Application		Road Conditions:	
Intended Serv.:	General Freight	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
Body		Class C (Off-Hwy)	0
Type:		Class D (Off-Road)	0
Length (ft):	0	Maximum Grade:	6
Height (ft):	0	Wheelbase (in):	240
Max Laden Weight (lbs):	0	Overhang (in):	55.7
Trailer		Fr Axle to BOC (in):	68.2
No. of Trailer Axles:	2	Cab to Axle (in):	171.8
Type:	Van	Cab to EOF (in):	227.5
Length (ft):	53	Overall Comb. Length (in):	889.38
Height (ft):	13.5	Special Req.	
Kingpin Inset (in):	36		
Corner Radius (in):	1		
Restrictions			
Length (ft):	65		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
Base Model				
0005791	S	Model 579 The Model 579 combines aerodynamic innovation and powertrain optimization to deliver confidence and efficiency for the most cost-conscious companies. A solid and durable aluminum cab consists of the highest quality fit and finish. An in-mold process embeds color directly onto the dash for a long-lasting finish that virtually eliminates fading, scratching and peeling. Electrical wiring carriages support wiring and reduce wear and tear, adding to the overall durability of the components. Peterbilt's flexible Aero Packages provide the right combination of fairings, skirts and closeouts to exceed application-specific aerodynamic requirements. Available in a day cab, or with detachable sleeper, that adds versatility and longevity of a second life for highest resale value.	225,746	14,680
0091200	S	Other Commodity	0	0
0093170	S	General Freight Truck or tractor used in over-the-road hauling of general freight. Pickup to delivery distance is typically over 100 miles and annual mileage is typically over 60,000 miles per year. Operation is typically on-highway.	0	0
0096010	S	Van	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200614	S	SmartWay Designated - Not Selected or Unavailable For this vehicle configuration.	0	0
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0515010	O	10-5/8" Steel Rails 326-384" 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	313	155
0611790	S	Aluminum Frame Rail Crossmembers Excludes suspension	0	0
0644000	S	EOF Tractor Tapered with Crossmember Includes Kingpin Cutout	0	0
0651010	S	Peterbilt Rear Mudflaps and Straight Hangers Mudflaps aid in protecting the frame and undercarriage from road salt, grime and debris that can cause rust and corrosion. Mud flaps also shield other vehicles from gravel, rocks and road spray.	0	0
0673010	S	Polyarmor Black Quarter Fenders with Peterbilt	140	25

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251924-N5C1C9

Printed On: 4/7/2026 2:41:53 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
		Heavy duty black 24" x 24" Polyarmor Quarter Fender made with polymer material that is chip, dent and scuff resistant. Cost effective protection with style. Peterbilt logo on the flap.		
0835840	O	Holland FW17 Fifth Wheel Top Plate Using precision casting technology the FW17 series fifth wheel utilizes patented thin-walled steel casting and heat treating processes. This technology provides exceptional performance and outstanding durability while delivering a fifth wheel that is lighter.	202	-50
0870000		Rear Or Fixd Setting Centerline Bogie	0	0
0890002	O	Inboard Fifth Wheel Mounting Air Slide Only	250	0
0890090	S	LH Fifth Wheel Release	0	0
0890550	S	7.6in - 8in Fifth Wheel Height	0	16
0890641	O	Holland Lightweight Air Slide Not available with suspensions > 40k.	0	-20
0891210	S	12" Air Slide For Fifth Wheel	0	0
0898030	S	Fifth Wheel Slide Controls Provided with Speed Interlock to prevent accidental activation above 7 MPH. Configurable from 5 to 10 MPH. Required with sliding Fifth Wheels.	0	0
0960000	S	Frame Mounted Deckplate And Access Pkg, LH Side	616	41
Front Axle & Equipment				
1012140	S	Meritor MFS+12E 12,500 lb, 3.5 in. Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 13,000 pounds. Axles include special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service.	0	0
1111200	S	Taper Leaf Springs, Shocks 13,200 lb Hendrickson taper leaf springs for 13,200 lbs. offer high value to weight ratio.	160	9
1233100	S	Power Steering TRW THP60 TRW THP60 Power Steering is for use with 10,000 to 13,200 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	0	0
1250180	S	Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1353550	S	PHP10 Aluminum PreSet PLUS Hubs Air Disc PHP10 aluminum PreSet PLUS hubs air disc have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug, with a seal and bearings. Use with Front Axle.	0	0
1380380	S	Tenneco Shocks For Steer Axle Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251924-N5C1C9

Printed On: 4/7/2026 2:41:53 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
1380470	S	Meritor Wide Track IPO Standard, Front Axle Meritor wide track front axle offers greater turning radius and ease of service. MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles.	0	15
1392190	S	Meritor EX+LS Air Disc Brakes Steer Axle	1	0
Rear Axle & Equipment				
1527050	S	PACCAR DX-40 40K Tandem Axle	0	0
1616290	O	PHP10 Aluminum PreSet PLUS Hubs	-1,266	0
1680390	S	Bendix ESP Electronic Stability Program With ATC Tractor service only. The Bendix ESP system is designed to continuously monitor a variety of vehicle parameters and sensors to determine if the vehicle is reaching a critical stability threshold. If such a situation develops, the system will quickly and automatically intervene to assist the driver by selectively applying tractor and trailer brakes, and de-throttling the engine.	0	0
1680525	O	Pneumatic Park Brake	0	0
1680750	O	Meritor Q+ Air Cam Rear Drum Brakes 16.5x7	65	0
1681025	S	Adjustable Following Distance Adaptive CC	0	0
1681035	S	Standard Following Distance Adaptive CC	0	0
1681085	S	Bendix Fusion Stop And Auto-Go Advanced	0	0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0	0
1683245	S	Tire Pressure Monitoring System	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1702790	S	Ratio 2.79 Rear Axle	0	0
1821970	S	Peterbilt Low Air Leaf 40,000 lb, 52in Axle Spacing, Light Weight	607	-59
Engine & Equipment				
2075810	S	PACCAR MX-13 455@1600 GV@2200 1650@900 (2024 Emissions)	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251924-N5C1C9

Printed On: 4/7/2026 2:41:53 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
		N20700 AA003 64....CC MAX TARGET SPEED		
		N20800 AA004 10....CC MIN ENABLE SPEED		
		N22000 AA005 OFF...DYNAMIC CC ENABLE		
		N20830 AA006 MT....MULTI TORQUE IN CC		
		N21930 AA009 0.....DRIVER REWARD VEH SPD BONUS		
		N21940 AA010 -5....DRIVER REWARD VEH SPD PNLTY		
		N21920 AA013 BOTH..OFFSET MODE		
		N21950 AA015 3.....MIN SPEED FOR DR SHIFT AID		
		N21960 AA016 1.....DSA LOWEST ACTV GEAR		
		N21970 AA017 10....DSA HIGHEST ACTV GEAR		
		N21640 AA019 YES...EIST PARK BRAKE RESET ENABLE		
		N21910 AA022 30....EIST LO CLNT TEMP OVRDE		
		N20870 AA023 80....EIST HI AMBAIR TEMP OVRDE		
		N20860 AA024 39....EIST LO AMBAIR TEMP OVRDE		
		N20900 AA025 5.....EIST PTO MAX IDLE TIME		
		N20840 AA026 5.....EIST PARKED MAX IDLE TIME		
		N20850 AA027 5.....EIST STANDSTILL IDLE TIME		
		N20910 AA029 YES...EIST RESET FROM ENG LOAD		
		N21170 AA030 NO....EIST OVERRIDE FROM ENG LOAD		
		N21190 AA031 0.....EIST EXPIRATION DISTANCE		
		N21230 AA032 YES...EIST ACCEL PEDAL RESET		
		N21240 AA033 YES...EIST SERVICE BRK RESET		
		N21250 AA034 YES...EIST CLUTCH PEDAL RESET		
		N21260 AA035 YES...EIST PTO OVERRIDE		
		N20770 AA037 4.....DSL SPD OFFSET		
		N20760 AA038 2.....AUTO RTRDR VEH SPD OFFSET		
		N20750 AA039 0.1...TIME DELAY FOR RTRDR ACT		
		N20940 AA042 1900..FIC MAX ENG SPEED		
		N22080 AA043 CNCL..CAB/REM: CUSTOM PRESET 1 FUN		
		N22090 AA044 750...CAB/REM: CUSTOM PRESET 1		
		N22100 AA045 CNCL..CAB/REM: CUSTOM PRESET 2 FUN		
		N22110 AA046 850...CAB/REM: CUSTOM PRESET 2		
		N22120 AA047 CNCL..CAB/REM: CUSTOM PRESET 3 FUN		
		N22130 AA048 950...CAB/REM: CUSTOM PRESET 3		
		N22010 AA049 CNCL..CAB: CUSTOM PRESET 1 FUNC		
		N22020 AA050 0.....CAB: CUSTOM PRESET 1		
		N22030 AA051 CNCL..CAB: CUSTOM PRESET 2 FUNC		
		N22040 AA052 0.....CAB: CUSTOM PRESET 2		
		N22050 AA053 CNCL..CAB: CUSTOM PRESET 3 FUNC		
		N22060 AA054 0.....CAB: CUSTOM PRESET 3		
		N20990 AA055 ON A..CAB: CLUTCH INTLK		
		N21010 AA058 ON A..CAB: PARK BRK INTLK		
		N21030 AA057 ON A..CAB: NEUTRAL INTLK		
		N21150 AA059 ON A..SER BRK INTLK: NO PTO		
		N21130 AA060 OFF...CAB: PRESET +/- SWITCH TYPE		
		N21180 AA061 2000..CAB: MAX ENG SPD- ACCEL CTRL		
		N21120 AA062 2000..CAB: MAX ENG SPD- SW CTRL		
		N21020 AA063 6.....CAB:MAX VEH SPEED		
		N21200 AA064 650...CAB: MIN ENG SPD		
		N21220 AA065 800...CAB: DEDICATED PRESET (-)		
		N21270 AA066 900...CAB: DEDICATED PRESET (+)		

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251924-N5C1C9

Printed On: 4/7/2026 2:41:53 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
		N21900 AA067 TRQ...CAB: ACCEL PEDAL TYPE IN PTO		
		N21140 AA068 YES...CAB: ACCEL ACTV IN CAB PTO		
		N21990 AA069 YES...PTO REM PEDAL ENABLE		
		N21600 AA070 ON AD.REM: CLUTCH INTLK		
		N22140 AA071 OFF...REM: CUSTOM INTLK		
		N21700 AA072 ON AD.REM: NEUTRAL INTLK		
		N21710 AA073 ON AD.REM: SER BRK INTLK: NO PTO		
		N21980 AA074 2000..REM:MAX ENG SPD-ACCEL CTRL		
		N21110 AA075 2000..REM: MAX ENG SPD-SW/ TSC1 CT		
		N21320 AA076 650...REM: MIN ENG SPD		
		N21290 AA077 800...REM: DEDICATED PRESET (-)		
		N21490 AA078 900...REM: DEDICATED PRESET (+)		
		N21580 AA079 DEDIC.REM: PRESET +/- SWITCH TYPE		
		N20690 AA086 64....MAX ACCEL PEDAL VEH SPD		
		N21300 AA087 0.....VSL EXPIRATION DISTANCE		
		N21310 AA088 100...LRSL SPD LMT		
		N20740 AE001 NO....ENBL MX RETARDER IN NEUTRAL		
		N20710 AE002 650...IDLE TARGET		
		N20930 AE003 ON....FIC ENABLE/DISABLE		
		N22070 AA056 OFF...CAB: CUSTOM INTLK		
		N22170 AQ001 4.....PCC Max Negative Offset (AQ0		
		N22180 AQ002 4.....PCC Max Positive Offset (AQ0		
2091120	S	EMUX Electronics Architecture	0	0
2091305	S	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Overrule	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091638		Effective VSL Setting 65.0 MPH or Greater (USA)	0	0
2092017	S	Typical Operating Speed 68 MPH	0	0
2092027	O	MX Retarder State Cruise Control On (Manual Mode Engine Parameter)	0	0
2092031	S	Powertrain Optimized for Fuel Economy Best analysis for vehicles which operate at or near cruise speed 90 plus percent of time.	0	0
2092082	S	Engine Monitoring Protection - Derate (PACCAR MX) A warning is provided in the A-Panel display when DPF regeneration is required. Continued operation without regeneration will initiate automate derating of the engine's power and can result in damage to the engine.	0	0
2092092	S	Enable Driver Performance Assistant	0	0
2092093	S	DPA - Enable Driver Coaching	0	0
2092094	S	DPA - Enable Anticipation Score	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251924-N5C1C9

Printed On: 4/7/2026 2:41:53 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
2092095	S	DPA - Enable Brake Saving Score	0	0
2092097	S	DPA - Enable Tire Pressure Reminder	0	0
2092098	S	DPA - Enable Automated Trans Reminders	0	0
2092108	S	Predictive Cruise Control Package	0	0
2140200	O	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140410	S	Engine Brake Controls Located on RH Column	0	0
2140660	O	CARB Emission Compliant Engine	0	0
2141990	S	Omit Chevron Engine Oil Sticker (DELO)	-5	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	S	Immersion Type Block Heater 110-120V Standard location is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522080	S	PACCAR Premium Starter - P Engines Only PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 36 months / 350,000 mi / 560,000 km.	0	0
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539720	S	Low Voltage Disconnect System	0	0
2641010	S	Crank Mounted Variable Speed Fan Clutch MX-13 Eng Crank Mounted Variable Speed Fan Clutch MX-13 Eng. The crank-mounted fully variable speed fan drives communicate directly with the MX-13 ECM, managing the fan speed to match the exact amount of cooling required. The optimized setup creates smoother engagements, reduces noise, frees up available horsepower, and removes the requirement of a belt line to drive the fan. These fan drives are also maintenance-free.	0	0
2738410	S	WABCO 25.9 CFM Air Compressor MX, WABCO 25.9 CFM air compressor, MX only, provides greater air output aiding in cleaner operation, higher efficiency, and durability.	0	0
2811160	S	Compression Brake, Paccar Engines The Mx brake features a Jacobs Brake with an integrated compression-release brake and engine overhead. the specially designed exhaust came lobe provides both exhaust cam motion and deicated	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251924-N5C1C9

Printed On: 4/7/2026 2:41:53 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
		Compression release timing. This results in precise timing of the valve opening, unleashing higher retarding performance with minimum loading on the engine.		
2921180	S	PACCAR Fuel/Water Separator On Engine Extended life fuel filter, optimized for MX engines and Includes fuel heat, 12V electric heat and WIF sensor.	0	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 520 1242 sq in, 579 1325 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 567 1440 sq in, 589 1604 sq in.	0	0
3211140	S	(1) Air Cleaner Engine Mounted	0	0
3367170	S	Exhaust Single RH Horizontal DPF/SCR RH Under Cab, Single Module	0	0
Transmission & Equipment				
4030040	S	PACCAR TX-12 PO-16F112C12 Automated Linehaul, On Highway Intended Service with 1,650 lbs.-ft. torque. Includes 12-speed Linehaul Overdrive, transmission fluid pressure sensor notifies driver of low oil to prevent low oil failure and is backed by a low oil failure protection. Internal electrical system routing which minimizes exposure and corrosion of wires and connectors, vehicle oil-coalescing air filter to protect transmission from contamination. No oil cooler required. Forward ratios: 1st-14.4, 2nd-11.0, 3rd-8.44, 4th -6.46, 5th-4.95, 6th- 3.79, 7th- 2.91, 8th-2.23, 9th-1.71, 10th-1.30, 11th-1.0, 12th-.766. Reverse ratios: R1-16.92, R2-12.95. Overall ratio 18.85. PTO capability: 8-bolt bottom mount only. Reference Engineering Data Book for available PTOs.	0	0
4210870	S	RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanently lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field.	0	0
4211360	S	RPL25 SD Driveline, 1 Midship Bearing All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field.	905	120
4252610	S	Column Mounted Shifter RH Side	0	0
4253070	S	Economy Shift Calibration	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251924-N5C1C9

Printed On: 4/7/2026 2:41:53 PM



Sales Code	Std/Opt	Description	\$ List	Weight
4257050	S	Neutral Coast Mode Automated transmission.	0	0
Air & Trailer Equipment				
4510190	S	Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0	0
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4610920	S	Self-Returning Brake Hand Valve Dash mounted controls	0	0
4614810	S	AE Connections BOC/BOS, Hose Tenna	0	0
Tires & Wheels				
5004300	S	FF: CN 16ply 295/75R22.5 Conti Eco Plus HS3+ETRTO	0	0
5108070	O	RR: AP 14ply 295/75R22.5 EnduCombi RA	-48	56
5190008	S	Code-rear Tire Qty 08	0	0
5211510	S	FF: Accuride 43644SP 22.5X8.25 Aluminum Wheel Standard polish.	434	-58
5311995	O	RR: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP 10-2 Hand Holes	0	0
5390008	S	Code-rear Rim Qty 08	0	0
Fuel Tanks				
5556040	O	26" Aluminum 50 Gal Fuel Tank LH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	0	-2
5604050	O	Location LH BOC 50 Gallon	0	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0



Sales Code	Std/ Opt	Description	\$ List	Weight
5652990	O	DEF To Fuel Ratio 2:1 Or Greater	0	0
5655019	O	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	0	0
5760010	O	RH Tank None Furnished	-714	-86
Battery Box & Bumper				
6010030	O	Aluminum Battery Box LH Under Cab, Non-Slip Step Includes diamond pattern block shaped cover in traditional/vocational models and a smooth finish tapered cover on aerodynamic models	0	0
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6112540	S	Aero Bumper Molded 3-Piece Molded Black	0	0
6132040	S	Omit Front Tow Pin(s)	-56	-2
6132810	S	Omit Bumper Air Dam Epiq package	-102	0
Cab & Equipment				
6515790	S	Aero 118" BBC Alum Cab & Metton Hood w/ SBFA Hood has stainless steel grille with chrome plated grille surround and Peterbilt bird. Includes anti-blow down hood device.	0	0
6700000	O	No Sleeper Selected	0	0
6911100	S	Peterbilt ST Driver Peterbilt ST air seat, high height backrest, adjustable seat track length, 1 chamber lumbar support, suspension with fixed damping, fore-aft isolator with lockout, Vinyl bellows over suspension. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal carog/luggage. Standard vinyl finish - color coordinate with interior color.	0	0
6921740	S	Peterbilt ST Non-Adjustable Passenger Seat Standard vinyl, no suspension cover, no seat back recline.	0	0
6939110	S	Toolbox Under Passenger Seat Non-Suspension Seat	227	11
6939400	S	Air Ride Driver	0	0
6939420	S	High Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939510	S	Non-Air Ride Passenger	0	0
6939520	S	High Back Passenger	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251924-N5C1C9

Printed On: 4/7/2026 2:41:53 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
6939570	S	Vinyl Passenger	0	0
7000025	S	Steering Wheel With Multi-Function Includes Peterbilt logo on horn button , audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	0	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	0
7037150	S	Premier Interior - Sterling Gray Features single tone dash with tough, scratch resistant materials including soft touch points on top of dash highlighted by horizontal chrome accent, bright bezel gauges and accented door pad. Top of dash, door panel uppers, and kick panel are charcoal to conceal dirt and mitigate wear. Includes unique technical grained A,B, C & D instrument panels with contoured doorpads, padded fabric headliner and vinyl wall panels. Superior ergonomics are achieved while maximizing productivity featuring: multiple power ports, (2) coat hooks, header-mounted domelight, power lift driver and passenger windows, LH and RH door mounted map pockets with built-in courtesy lights, driver and passenger dome/reading lights and footwell lighting. Comfort features include automatic temperature HVAC controls, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, carpeted floor covering, (3) inside sunvisors, integrated "dead pedal, cup holder and map bin in dash.	1,015	0
7040150	S	Rubber Floor IPO Carpet (Black Only) Rubber Floor Covering in Cab. Standard in Prestige interior, optional in Platinum/Premier interiors.	-41	-6
7210540	O	Day Cab Rear Window Day cab rear window flush to back of cab.	0	0
7210550	O	1-Piece Glass Rear Cab Window Fixed	0	0
7230060	S	1-Piece Curved Windshield	0	0
7230360	S	Power Door Locks and Power Window Lifts Standard	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7510070	S	Aero Rear View Mirror Housing, Molded Black	0	0
7514000	S	Peterbilt Aero Rear View Mirror, Non-Motorized Includes top mirror with non-motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	0	0
7514050	S	Look Down Mirror Over Passenger Door with Black Housing	0	0
7610500	S	Air Horn Mounted Under Cab	0	0
7722120	S	ConcertClass, AM/FM, Weatherband, 3.5 Aux	463	10

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251924-N5C1C9

Printed On: 4/7/2026 2:41:53 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
7725710	S	Standard Speaker Package For Cab (2) Speakers	61	4
7728030	S	Radio Mute When In Reverse For automatic or automated transmission	0	0
7748145	S	CB Terminals/Wiring Mounted Under Header With mounting bracket	97	2
7748740	S	(2) Antennas For Factory Installed Or F/O CB Mounted RH/LH side of roof, with antenna cables	194	2
7788335	S	Global Telematics Hardware	0	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7852020	O	Cab Air Suspension	280	15
7870560	O	18 Inch Cab Side Extenders, Includes 6.5 Inch Rubber flares for daycab only.	1,201	46
8011830	S	Engine Oil Temperature Located in Digital Cluster Display.	0	0
8021800	S	Air Filter Restriction Pressure Gauge Located in Digital Cluster Display	0	0
8021810	S	Brake Application Air Pressure (Tractor) Located in Digital Cluster Display.	0	0
8070810	S	Engine Manifold Pressure (Turbo Boost) Located in Digital Cluster Display	0	0
8070820	S	Engine Percent Torque Located in Digital Cluster Display	0	0
8070830	S	Main Instrumentation Panel Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, and Voltmeter.	0	0
8111110	S	Headlights Composite Fender Mounted Integral DRL/Park, Turn, and Side Marker	0	0
8120990	S	(5) Marker Lights, Aero LED On roof, visor, or fairing	0	0
8133960	S	Daytime Running Lights The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0	0
8140000	S	Incandescent Oval Stop/Turn/Tail/Backup In tractor taper end of frame crossmember	0	0
Paint				
8500710	S	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251924-N5C1C9

Printed On: 4/7/2026 2:41:53 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
		N85020 A - L0006EY WHITE		
		N85700 BUMPER MOLDED-BLACK		
		N85500 CAB ROOF L0006EY WHITE		
		N85300 FENDER L0006EY WHITE		
		N85200 FRAME L0001EA BLACK		
		N85400 HOOD TOP L0006EY WHITE		

Shipping Destination

Options Not Subject To Discount

9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0
9400092	S	PACCAR MX Standard Coverage 2 yrs/250,000 mi (400,000 km)/6,250 hrs	0	0
9407147	O	Fuel Price Index Factor \$342 NET	342	0
9408656	O	SmartLINQ RD/OTA 5YR Sub PACCAR MX Engines	799	0
9408703	O	Base Warr: Emissions 5YR/100K MI	0	0
9408937	S	PDI After Body Upfit	0	0

Miscellaneous

9409030	O	Day Cab / Premier Interior (DR)	0	0
9409093	O	State Of Registry: Texas	0	0
9409641	O	Model Year 2026 Engine	0	0
9409749	O	2024 Series Emissions Engine	0	0

Promotions

Special Requirements

Special Requirement 1 0098170
Special Requirement 2
Special Requirement 3
Special Requirement 4

Fuel Efficiency Score:

Order Comments



Total List Price (W/O Freight & Warranty & Surcharges)	\$230,545
Marketing and Service Support Fee	\$1,725
Prepaid Freight	\$3,725
Total Surcharge/Options Not Subject To Discount	\$1,141
Total Weight (lbs)	14,924

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------