



Rush Enterprises Inc (S040)
555 Interstate 35 S.
New Braunfels, Texas 78130

Stock

Colton Kruse
Cell Phone: 210-392-2213
Office Phone: 830-302-5219
Email: krusec@rushenterprises.com

Stock Order

Vehicle Summary

Unit		Chassis	
Model:	Model 589 Traditional	Fr Axle Load (lbs):	12000
Type:	Tractor	Rr Axle Load (lbs):	38000
Description 1:	HGAC Spec	G.V.W.R. (lbs):	50000
Description 2:		G.C.W. (lbs):	80000
Application		Road Conditions:	
Intended Serv.:	General Freight	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
Body		Class C (Off-Hwy)	0
Type:		Class D (Off-Road)	0
Length (ft):	0	Maximum Grade:	6
Height (ft):	0	Wheelbase (in):	244
Max Laden Weight (lbs):	0	Overhang (in):	54.7
Trailer		Fr Axle to BOC (in):	90.1
No. of Trailer Axles:	2	Cab to Axle (in):	153.9
Type:	Van	Cab to EOF (in):	208.6
Length (ft):	53	Overall Comb. Length (in):	875
Height (ft):	13.5	Special Req.	
Kingpin Inset (in):	36		
Corner Radius (in):	2		
Restrictions			
Length (ft):	65		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
Base Model				
0005891	S	Model 589 Traditional Peterbilt is proud to introduce the Legendary Model 589. The Model 589 takes cues from heritage designs and incorporates essential customer feedback to create this legendary and luxurious truck. The Peterbilt Model 589 has a bold, distinctive style and iconic exterior features such as the aluminum hood, wrap-around grille crown with triple bars and 15" stainless steel external air cleaners. A driver centric and luxurious cabin features purposeful storage throughout, automatic climate control and plenty of available brightwork. The interior of the Model 589 provides best-in-class quality and driver comfort.	229,253	14,820
0091200	S	Other Commodity	0	0
0093170	S	General Freight Truck or tractor used in over-the-road hauling of general freight. Pickup to delivery distance is typically over 100 miles and annual mileage is typically over 60,000 miles per year. Operation is typically on-highway.	0	0
0096010	S	Van	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0514000	S	10-3/4" Steel Rails To 354" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	526	332
0644000	S	EOF Tractor Tapered with Crossmember Includes Kingpin Cutout	0	0
0651010	S	Peterbilt Rear Mudflaps and Straight Hangers Mudflaps aid in protecting the frame and undercarriage from road salt, grime and debris that can cause rust and corrosion. Mud flaps also shield other vehicles from gravel, rocks and road spray.	0	0
0854010	S	Fifth Wheel Not Furnished	0	0
0940330	S	No Access Package or Deckplate Desired Use with tractors without access package or deckplate	0	0
Front Axle & Equipment				
1012140	S	Meritor MFS+12E 12,500 lb, 3.5 in. Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 13,000 pounds. Axles include special low-friction bushings,	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251917-W0W0X1

Printed On: 4/7/2026 2:21:23 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
		double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service.		
1111190	S	Taper Leaf Springs, Shocks 12,000 lb Hendrickson taper leaf springs, shocks for 12,000 lbs.	0	0
1243040	S	Power Steering Sheppard HD94 Sheppard HD94 power steering gear is a light weight version of heavy duty line-haul power steering gear. For use with 10,000 to 13,200 lb. axle ratings.	0	0
1250180	S	Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1353550	S	PHP10 Aluminum PreSet PLUS Hubs Air Disc PHP10 aluminum PreSet PLUS hubs air disc have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug, with a seal and bearings. Use with Front Axle.	0	0
1380295	S	Bendix ADB22X-LT Front Disc Brakes	0	0
1380380	O	Tenneco Shocks For Steer Axle Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.	0	0

Rear Axle & Equipment

1523300	S	Dana Spicer DSP41 40,000 lb Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	1,046	142
1616290	S	PHP10 Aluminum PreSet PLUS Hubs	0	0
1680390	S	Bendix ESP Electronic Stability Program With ATC Tractor service only. The Bendix ESP system is designed to continuously monitor a variety of vehicle parameters and sensors to determine if the vehicle is reaching a critical stability threshold. If such a situation develops, the system will quickly and automatically intervene to assist the driver by selectively applying tractor and trailer brakes, and de-throttling the engine.	0	0
1682710	S	Anti-Lock Braking System (ABS) 6S6M ABS-6. Includes air braking system.	0	0
1683245	O	Tire Pressure Monitoring System	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251917-W0W0X1

Printed On: 4/7/2026 2:21:23 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
		lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.		
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0	0
1703250	O	Ratio 3.25 Rear Axle	0	0
1821700	S	Peterbilt Air Leaf 38,000 lb, 52in Axle Spacing Light Weight with Tracking Rods.	0	0
1922260	O	Dash Mtd Dump Switch with Indicator Light Dash mounted dump switch with indicator light for suspension.	61	2

Engine & Equipment

2075810	S	PACCAR MX-13 455@1600 GV@2200 1650@900 (2024 Emissions)	0	0
		N20700 AA003 64....CC MAX TARGET SPEED N20800 AA004 10....CC MIN ENABLE SPEED N22000 AA005 OFF...DYNAMIC CC ENABLE N20830 AA006 MT....MULTI TORQUE IN CC N21930 AA009 0.....DRIVER REWARD VEH SPD BONUS N21940 AA010 -5....DRIVER REWARD VEH SPD PNLT N21920 AA013 BOTH..OFFSET MODE N21950 AA015 3.....MIN SPEED FOR DR SHIFT AID N21960 AA016 1.....DSA LOWEST ACTV GEAR N21970 AA017 10....DSA HIGHEST ACTV GEAR N21640 AA019 YES...EIST PARK BRAKE RESET ENABLE N21910 AA022 30....EIST LO CLNT TEMP OVRDE N20870 AA023 80....EIST HI AMBAIR TEMP OVRDE N20860 AA024 39....EIST LO AMBAIR TEMP OVRDE N20900 AA025 5.....EIST PTO MAX IDLE TIME N20840 AA026 5.....EIST PARKED MAX IDLE TIME N20850 AA027 5.....EIST STANDSTILL IDLE TIME N20910 AA029 YES...EIST RESET FROM ENG LOAD N21170 AA030 NO....EIST OVERRIDE FROM ENG LOAD N21190 AA031 0.....EIST EXPIRATION DISTANCE N21230 AA032 YES...EIST ACCEL PEDAL RESET N21240 AA033 YES...EIST SERVICE BRK RESET N21250 AA034 YES...EIST CLUTCH PEDAL RESET N21260 AA035 YES...EIST PTO OVERRIDE N20770 AA037 4.....DSL SPD OFFSET N20760 AA038 2.....AUTO RTRDR VEH SPD OFFSET N20750 AA039 0.1...TIME DELAY FOR RTRDR ACT N20940 AA042 1900..FIC MAX ENG SPEED N22080 AA043 CNCL..CAB/REM: CUSTOM PRESET 1 FUN N22090 AA044 750...CAB/REM: CUSTOM PRESET 1 N22100 AA045 CNCL..CAB/REM: CUSTOM PRESET 2 FUN N22110 AA046 850...CAB/REM: CUSTOM PRESET 2 N22120 AA047 CNCL..CAB/REM: CUSTOM PRESET 3 FUN		

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251917-W0W0X1

Printed On: 4/7/2026 2:21:23 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
		N22130 AA048 950...CAB/REM: CUSTOM PRESET 3		
		N22010 AA049 CNCL...CAB: CUSTOM PRESET 1 FUNC		
		N22020 AA050 0.....CAB: CUSTOM PRESET 1		
		N22030 AA051 CNCL...CAB: CUSTOM PRESET 2 FUNC		
		N22040 AA052 0.....CAB: CUSTOM PRESET 2		
		N22050 AA053 CNCL...CAB: CUSTOM PRESET 3 FUNC		
		N22060 AA054 0.....CAB: CUSTOM PRESET 3		
		N20990 AA055 ON A..CAB: CLUTCH INTLK		
		N21010 AA058 ON A..CAB: PARK BRK INTLK		
		N21030 AA057 ON A..CAB: NEUTRAL INTLK		
		N21150 AA059 ON A..SER BRK INTLK: NO PTO		
		N21130 AA060 OFF...CAB: PRESET +/- SWITCH TYPE		
		N21180 AA061 2000..CAB: MAX ENG SPD- ACCEL CTRL		
		N21120 AA062 2000..CAB: MAX ENG SPD- SW CTRL		
		N21020 AA063 6.....CAB:MAX VEH SPEED		
		N21200 AA064 650...CAB: MIN ENG SPD		
		N21220 AA065 800...CAB: DEDICATED PRESET (-)		
		N21270 AA066 900...CAB: DEDICATED PRESET (+)		
		N21900 AA067 TRQ...CAB: ACCEL PEDAL TYPE IN PTO		
		N21140 AA068 YES...CAB: ACCEL ACTV IN CAB PTO		
		N21990 AA069 YES...PTO REM PEDAL ENABLE		
		N21600 AA070 ON AD.REM: CLUTCH INTLK		
		N22140 AA071 OFF...REM: CUSTOM INTLK		
		N21700 AA072 ON AD.REM: NEUTRAL INTLK		
		N21710 AA073 ON AD.REM: SER BRK INTLK: NO PTO		
		N21980 AA074 2000..REM:MAX ENG SPD-ACCEL CTRL		
		N21110 AA075 2000..REM: MAX ENG SPD-SW/ TSC1 CT		
		N21320 AA076 650...REM: MIN ENG SPD		
		N21290 AA077 800...REM: DEDICATED PRESET (-)		
		N21490 AA078 900...REM: DEDICATED PRESET (+)		
		N21580 AA079 DEDIC.REM: PRESET +/- SWITCH TYPE		
		N20690 AA086 64....MAX ACCEL PEDAL VEH SPD		
		N21300 AA087 0.....VSL EXPIRATION DISTANCE		
		N21310 AA088 100...LRSL SPD LMT		
		N20740 AE001 NO....ENBL MX RETARDER IN NEUTRAL		
		N20710 AE002 650...IDLE TARGET		
		N20930 AE003 ON....FIC ENABLE/DISABLE		
		N22070 AA056 OFF...CAB: CUSTOM INTLK		
		N22170 AQ001 4.....PCC Max Negative Offset (AQ0		
		N22180 AQ002 4.....PCC Max Positive Offset (AQ0		
2091120	O	EMUX Electronics Architecture	0	0
2091305	S	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Override	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251917-W0W0X1

Printed On: 4/7/2026 2:21:23 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
2092014	S	Typical Operating Speed 65 MPH	0	0
2092027	S	MX Retarder State Cruise Control On (Manual Mode Engine Parameter)	0	0
2092033	S	Powertrain Optimized for Balance Best analysis for vehicles where service includes frequent start and stop cycles.	0	0
2092082	S	Engine Monitoring Protection - Derate (PACCAR MX) A warning is provided in the A-Panel display when DPF regeneration is required. Continued operation without regeneration will initiate automate derating of the engine's power and can result in damage to the engine.	0	0
2092108	S	Predictive Cruise Control Package	659	0
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140410	S	Engine Brake Controls Located on RH Column	0	0
2140660	O	CARB Emission Compliant Engine	0	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	S	Immersion Type Block Heater 110-120V Standard location is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522080	S	PACCAR Premium Starter - P Engines Only PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 36 months / 350,000 mi / 560,000 km.	0	0
2536140	S	4 Interstate 31ECL 12V Batt 2800 CCA Fully sealed, high vibration protection, gas guard technology, rugged durability with extreme cycling to maximize battery life.	583	0
2621090	S	HORTON ON/OFF Fan Clutch	0	0
2738440	O	WABCO 37.4 CFM Air Compressor MX	1,134	46
2811160	S	Compression Brake, Paccar Engines The Mx brake features a Jacobs Brake with an integrated compression-release brake and engine overhead. the specially designed exhaust came lobe provides both exhaust cam motion and deicated Compression release timing. This results in precise timing of the valve opening, unleashing higher retarding performance with minimum loading on the engine.	0	0
2921180	S	PACCAR Fuel/Water Separator On Engine Extended life fuel filter, optimized for MX engines and Includes fuel heat, 12V electric heat and WIF sensor.	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251917-W0W0X1

Printed On: 4/7/2026 2:21:23 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 520 1242 sq in, 579 1325 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 567 1440 sq in, 589 1604 sq in.	0	0
3212030	O	(2) 15" Premium SS Air Cleaners Cowl Mounted Slotted Stainless Steel Caps	0	0
3367160	O	Exhaust Single RH Side of Cab DPF/SCR RH Under Cab, Single Module	0	0
3387370	O	60" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	296	13

Transmission & Equipment

4030040	S	PACCAR TX-12 PO-16F112C12 Automated Linehaul, On Highway Intended Service with 1,650 lbs.-ft. torque. Includes 12-speed Linehaul Overdrive, transmission fluid pressure sensor notifies driver of low oil to prevent low oil failure and is backed by a low oil failure protection. Internal electrical system routing which minimizes exposure and corrosion of wires and connectors, vehicle oil-coalescing air filter to protect transmission from contamination. No oil cooler required. Forward ratios: 1st-14.4, 2nd-11.0, 3rd-8.44, 4th -6.46, 5th-4.95, 6th- 3.79, 7th- 2.91, 8th-2.23, 9th-1.71, 10th-1.30, 11th-1.0, 12th-.766. Reverse ratios: R1-16.92, R2-12.95. Overall ratio 18.85. PTO capability: 8-bolt bottom mount only. Reference Engineering Data Book for available PTOs.	0	0
4210190	O	1810 HD Driveline, 1 Midship Bearing 4.5in x .180 wall tubing	703	90
4216590	O	1710 Driveline Interaxle For tandem rear axles	372	0
4252610	S	Column Mounted Shifter RH Side	0	0
4253080	O	Performance Shift Calibration Endurant / Paccar transmissions only	0	0
4257050	O	Neutral Coast Mode Automated transmission.	0	0

Air & Trailer Equipment

4510190	S	Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0	0
---------	---	--	---	---

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251917-W0W0X1

Printed On: 4/7/2026 2:21:23 PM



Sales Code	Std/Opt	Description	\$ List	Weight
4520420	O	Pull Cords All Air Tanks	0	0
4540420	S	Nylon Chassis Hose	0	0
4543500	O	Aluminum Air Tanks Natural under box, painted Back of Cab	0	0
4611040	O	Omit Trailer Hand Valve	-194	-4
4614810	S	AE Connections BOC/BOS, Hose Tenna	0	0
Tires & Wheels				
5066100	S	FF: BR 14ply 295/75R22.5 R213 Ecopia	26	-6
5104770	S	RR: CN 14Ply 295/75R22.5 HDL3 ECO+	0	0
5190008	S	Code-rear Tire Qty 08	0	0
5211995	S	FF: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP 10-2 Hand Holes	0	0
5311995	S	RR: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP 10-2 Hand Holes	0	0
5390008	S	Code-rear Rim Qty 08	0	0
Fuel Tanks				
5554040	O	26" Aluminum 50 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	528	13
5602050	O	Location LH U/C 50 Gallon	0	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	S	DEF To Fuel Ratio 2:1 Or Greater	0	0
5655019	S	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	0	0
5760010	O	RH Tank None Furnished	-714	-86
Battery Box & Bumper				
6010780	O	Aluminum Space Saver Battery Box RH BOC Battery access from side	168	-60
6040550	O	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251917-W0W0X1

Printed On: 4/7/2026 2:21:23 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
6121090	S	Steel Bumper Deep Tapered Chromed Two tow points	0	0
Cab & Equipment				
6510210	S	Aluminum Cab, 121" BBC Alum Hood SFFA With polished crown and spring tilt assist.	0	0
6700000	S	No Sleeper Selected	0	0
6911100	S	Peterbilt ST Driver Peterbilt ST air seat, high height backrest, adjustable seat track length, 1 chamber lumbar support, suspension with fixed damping, fore-aft isolator with lockout, Vinyl bellows over suspension. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal carog/luggage. Standard vinyl finish - color coordinate with interior color.	0	0
6921740	S	Peterbilt ST Non-Adjustable Passenger Seat Standard vinyl, no suspension cover, no seat back recline.	0	0
6939110	O	Toolbox Under Passenger Seat Non-Suspension Seat	227	11
6939400	S	Air Ride Driver	0	0
6939420	S	High Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939510	S	Non-Air Ride Passenger	0	0
6939520	S	High Back Passenger	0	0
6939570	S	Vinyl Passenger	0	0
7000025	O	Steering Wheel With Multi-Function Includes Peterbilt logo on horn button , audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	0	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	0
7033550	O	Premier Interior - Alpine Gray	0	0
7210510	O	3-Piece Glass Rear Cab Window, All Pieces Fixed	237	12
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0	0
7230060	O	1-Piece Curved Windshield	0	0
7230360	O	Power Door Locks and Power Window Lifts Standard	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251917-W0W0X1

Printed On: 4/7/2026 2:21:23 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7514050	S	Look Down Mirror Over Passenger Door with Black Housing	0	0
7516000	O	Stainless Steel Mirrors 7"X18" Heated & Motorized West Coast Style	0	0
7560860	O	(2) Convex 8 Inch Heated SSTL Mirrors Mounted under mirror brackets	0	0
7610250	O	Air Horn None Furnished	-50	-8
7722120	O	ConcertClass, AM/FM, Weatherband, 3.5 Aux	463	10
7725710	O	Standard Speaker Package For Cab (2) Speakers	61	4
7788335	O	Global Telematics Hardware	0	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7852020	O	Cab Air Suspension	176	15
8011830	S	Engine Oil Temperature Located in Digital Cluster Display.	0	0
8021810	S	Brake Application Air Pressure (Tractor) Located in Digital Cluster Display.	0	0
8070810	S	Engine Manifold Pressure (Turbo Boost) Located in Digital Cluster Display	0	0
8070820	S	Engine Percent Torque Located in Digital Cluster Display	0	0
8070830	S	Main Instrumentation Panel Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, and Voltmeter.	0	0
8111140	O	Headlights Projector Module Pod Integral Turn Signals	0	0
8120990	S	(5) Marker Lights, Aero LED On roof, visor, or fairing	0	0
8140000	S	Incandescent Oval Stop/Turn/Tail/Backup In tractor taper end of frame crossmember	0	0
Paint				
8500710	O	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE	0	0

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251917-W0W0X1

Printed On: 4/7/2026 2:21:23 PM



Sales Code	Std/Opt	Description	\$ List	Weight
	N85300	FENDER L0006EY WHITE		
	N85200	FRAME L0001EA BLACK		
	N85400	HOOD TOP L0006EY WHITE		

Shipping Destination

Options Not Subject To Discount

9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0
9400092	S	PACCAR MX Standard Coverage 2 yrs/250,000 mi (400,000 km)/6,250 hrs	0	0
9407147	O	Fuel Price Index Factor \$342 NET	342	0
9408656	O	SmartLINQ RD/OTA 5YR Sub PACCAR MX Engines	799	0
9408703	O	Base Warr: Emissions 5YR/100K MI	0	0

Miscellaneous

9409030	O	Day Cab / Premier Interior (DR)	0	0
9409053	S	State Of Registry: Arizona	0	0
9409641	O	Model Year 2026 Engine	0	0
9409749	O	2024 Series Emissions Engine	0	0
9409960	S	Presentation Created Using Featured Spec For Model	0	0

Promotions

Special Requirements

Special Requirement 1 0098170

Special Requirement 2

Special Requirement 3

Special Requirement 4

Fuel Efficiency Score:

Order Comments

Price Level: January 1, 2026

100% Complete

Date: April 07, 2026

Deal: HGAC Spec

Quote Number: QUO-1251917-W0W0X1

Printed On: 4/7/2026 2:21:23 PM



Total List Price (W/O Freight & Warranty & Surcharges)	\$235,361
Marketing and Service Support Fee	\$1,725
Prepaid Freight	\$3,725
Total Surcharge/Options Not Subject To Discount	\$1,141
Total Weight (lbs)	15,346

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------