

		30902 C-38 PO Box 932 LeMars, IA 51031 (712) 546-4409 (800) 779-8099		Phone: Phone: Fax: Website:	(800) 779-8099 (712) 546-4409 (712) 546-6008 www.sidedump.com																																																																		
Quote #	HGAC004Q	Est. Completion Date:	TBD	QUOTE IS GOOD FOR 30 DAYS																																																																			
Date:	7/15/2025			Salesman:																																																																			
Customer:	HGAC BUY SOLICITATION: PW10-25			Customer:																																																																			
Address:	PO BOX 22777	HOUSTON TX	77277-2777	Terms:	COD																																																																		
Contact:				FOB:	LEMARS, IA																																																																		
Phone:	Email:			Email:																																																																			
<table border="0"> <tr> <td>Model</td> <td>CP20 - Tractor pulled</td> </tr> <tr> <td></td> <td>8'-6" wide</td> </tr> <tr> <td>Tub Length</td> <td>24'</td> </tr> <tr> <td>Frame length</td> <td>32'</td> </tr> <tr> <td>Tub Style</td> <td>SX - Round bottom tub</td> </tr> <tr> <td></td> <td>Water level volume = 16.1 cubic yards</td> </tr> <tr> <td></td> <td>Heaped volume - 21.4 cubic yards</td> </tr> <tr> <td>Tub Sides</td> <td>1/4" AR450</td> </tr> <tr> <td>Tub Floor</td> <td>1/4" AR450</td> </tr> <tr> <td>Tub Dividers</td> <td>None</td> </tr> <tr> <td>Dolly Legs</td> <td>Mark V-CP</td> </tr> <tr> <td>Hydraulics</td> <td>5" Cylinders</td> </tr> <tr> <td>VOT</td> <td>None</td> </tr> <tr> <td>ABS-Axles</td> <td>None</td> </tr> <tr> <td>Non-ABS Axles</td> <td>25K 2</td> </tr> <tr> <td>Suspension</td> <td>H-900 Single Point Spring Suspension</td> </tr> <tr> <td>Lift Axle</td> <td>None</td> </tr> <tr> <td>Axle Track</td> <td>77-1/2"</td> </tr> <tr> <td>Axle Spacing</td> <td>57"</td> </tr> <tr> <td>Hubs</td> <td>Duralite-STD</td> </tr> <tr> <td>Brakes</td> <td>None (See optional item list)</td> </tr> <tr> <td>Drums</td> <td>Cast Steel</td> </tr> <tr> <td>Wheel Style</td> <td>Hub Piloted U/M</td> </tr> <tr> <td>Wheel Type</td> <td>(4) Steel Disc Wheels, Hub-Piloted</td> </tr> <tr> <td>Tires</td> <td>(4) Alliance 328 600/55R22.5 floatation tires</td> </tr> <tr> <td>Fenders</td> <td>None</td> </tr> <tr> <td>Tub Paint #</td> <td>Black, gray or white</td> </tr> <tr> <td>Frame Paint #</td> <td>Black or gray</td> </tr> <tr> <td>Tarp Brand</td> <td>None</td> </tr> <tr> <td>Tarp Type</td> <td>None</td> </tr> <tr> <td>Lock Out Switch</td> <td>None</td> </tr> <tr> <td colspan="2">One set of Taylor Foundry weights, curbside</td> </tr> <tr> <td colspan="2">Category 3/4 bullpull hitch</td> </tr> </table>						Model	CP20 - Tractor pulled		8'-6" wide	Tub Length	24'	Frame length	32'	Tub Style	SX - Round bottom tub		Water level volume = 16.1 cubic yards		Heaped volume - 21.4 cubic yards	Tub Sides	1/4" AR450	Tub Floor	1/4" AR450	Tub Dividers	None	Dolly Legs	Mark V-CP	Hydraulics	5" Cylinders	VOT	None	ABS-Axles	None	Non-ABS Axles	25K 2	Suspension	H-900 Single Point Spring Suspension	Lift Axle	None	Axle Track	77-1/2"	Axle Spacing	57"	Hubs	Duralite-STD	Brakes	None (See optional item list)	Drums	Cast Steel	Wheel Style	Hub Piloted U/M	Wheel Type	(4) Steel Disc Wheels, Hub-Piloted	Tires	(4) Alliance 328 600/55R22.5 floatation tires	Fenders	None	Tub Paint #	Black, gray or white	Frame Paint #	Black or gray	Tarp Brand	None	Tarp Type	None	Lock Out Switch	None	One set of Taylor Foundry weights, curbside		Category 3/4 bullpull hitch	
Model	CP20 - Tractor pulled																																																																						
	8'-6" wide																																																																						
Tub Length	24'																																																																						
Frame length	32'																																																																						
Tub Style	SX - Round bottom tub																																																																						
	Water level volume = 16.1 cubic yards																																																																						
	Heaped volume - 21.4 cubic yards																																																																						
Tub Sides	1/4" AR450																																																																						
Tub Floor	1/4" AR450																																																																						
Tub Dividers	None																																																																						
Dolly Legs	Mark V-CP																																																																						
Hydraulics	5" Cylinders																																																																						
VOT	None																																																																						
ABS-Axles	None																																																																						
Non-ABS Axles	25K 2																																																																						
Suspension	H-900 Single Point Spring Suspension																																																																						
Lift Axle	None																																																																						
Axle Track	77-1/2"																																																																						
Axle Spacing	57"																																																																						
Hubs	Duralite-STD																																																																						
Brakes	None (See optional item list)																																																																						
Drums	Cast Steel																																																																						
Wheel Style	Hub Piloted U/M																																																																						
Wheel Type	(4) Steel Disc Wheels, Hub-Piloted																																																																						
Tires	(4) Alliance 328 600/55R22.5 floatation tires																																																																						
Fenders	None																																																																						
Tub Paint #	Black, gray or white																																																																						
Frame Paint #	Black or gray																																																																						
Tarp Brand	None																																																																						
Tarp Type	None																																																																						
Lock Out Switch	None																																																																						
One set of Taylor Foundry weights, curbside																																																																							
Category 3/4 bullpull hitch																																																																							
Customer acknowledges receipt of the SMITHCO MANUFACTURING WARRANTY provided herewith. The terms and conditions of such express warranty, as well as of the Owner's Manual to be provided with the trailer, are incorporated into and made a part of the Customer's Purchase and this agreement.																																																																							
SIGNATURE: _____			DATE: _____																																																																				
SMITHCO SHALL NOT, UNDER ANY CIRCUMSTANCES, BE HELD LIABLE FOR THE CONSEQUENTIAL, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, PUNITIVE, OR ENHANCED DAMAGES, INCLUDING WITHOUT LIMITATIONS ANY LOST PROFITS, FOR ANY BREACH OF THIS AGREEMENT, REGARDLESS OF THE LEGAL OR EQUIPTABLE THEORY (E.G., CONTRACT, TORT, OR OTHERWISE) UPON WHICH THE CLAIM IS BASED. IN NO EVENT SHALL SMITHCO'S AGGREGATE LIABILITY ARISING OUT OF OR RELATED TO THIS AGREEMENT, WHETHER BASED ON BREACH OF CONTRACT, TORT, (INCLUDING NEGLIGENCE), OR OTHERWISE, EXCEED THE TOTAL AMOUNT PAID TO SMITHCO UNDER THIS AGREEMENT.																																																																							

30902 C38
PO BOX 932
LEMARS, IA 51031

712 -546 -4409
800-779-8099
FAX 712-546-6008
sidedump.com



This is to certify that SMITHCO MANUFACTURING, INC. warrants each new side dump hauler manufactured by us to be free from structural defects in material and workmanship, as originally manufactured and delivered by us, under normal use and service and with loads not exceeding the manufacturer's rated capacity, for a period of twelve (12) months from delivery of the product to the original customer. Our obligation under this warranty is limited to repairing or replacing, in our sole discretion, any part (or parts) that is returned to us during the term of this warranty and that, following our examination, we determine to have been defective.

This warranty does not apply to any components or accessories, such as tires or tarps, that were purchased from other manufacturers to be installed on this product and which may be covered under their own manufacturer's warranty. This warranty also shall not apply to any Product that has been repaired or altered outside of SMITHCO's factory in such a manner as to (in SMITHCO's sole judgment) affect its stability or reliability or to have materially altered the Product or the performance manufactured by SMITHCO. Finally, this warranty shall not apply to any Product that has been, in SMITHCO's sole judgment, subject to misuse, negligence, or accident.

To exercise any right under this warranty, you must return any part (or parts) that you believe to be defective to us with transportation charges prepaid by the customer within twelve (12) months from delivery of the product to the original customer. Upon receipt of such part (or parts), we will examine such part and, if we determine it to be defective, will repair or replace such part.

THIS WARRANTY SHALL BE THE SOLE AND EXCLUSIVE WARRANTY OF ANY KIND PROVIDED BY SMITHCO AND IS EXPRESSLY PROVIDED IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE EXPRESSLY DISCLAIMED. EXCEPT FOR THIS WARRANTY, THERE ARE NO OTHER WARRANTIES, EXPRESS OR IMPLIED, PROVIDED BY SMITHCO WITH RESPECT TO THIS PRODUCT.