



## RL SERIES

***CARRIES THE LOAD OF THE  
SOLID WASTE INDUSTRY***

World class manufacturing combined with cutting-edge technology perfectly crafts a superior product: The Pac-Mac® RL Series. The innovative RL Series is engineered using the most advanced computer modeling systems. The Pac-Mac RL Series proves that Pac-Mac is committed to providing the highest quality products in the solid waste industry and can be mounted on a non-CDL chassis. DO IT RIGHT with Pac-Mac!

**HGACBuy™**  
THE SMART PURCHASING SOLUTION



**E-PAC-MAC.COM**

Manufactured by Hol-Mac Corporation  
P.O. Box 349 • Bay Springs, MS 39422 • 601-764-4121



# RL SERIES

## TECHNICAL DATA AND SPECIFICATIONS

### MODEL

	RL6	RL8	RL10
Capacity	6 yd <sup>3</sup>	8 yd <sup>3</sup>	10 yd <sup>3</sup>
Hopper capacity	1 yd <sup>3</sup>	1 yd <sup>3</sup>	1 yd <sup>3</sup>
Body weight (body shell only)	2,537 lb	2,917 lb	3,391 lb
Body weight (complete unit, less options)	7,235 lb	7,680 lb	8,120 lb
Hopper inside width	66.3"	66.3"	66.3"

### BODY SPECIFICATIONS

	RL6	RL8	RL10
Sidewalls (curved shell)	10 ga high tensile steel	10 ga high tensile steel	10 ga high tensile steel
Floor (single sheet, flat)	7 ga high tensile steel	7 ga high tensile steel	7 ga high tensile steel
Roof (curved shell)	10 ga high tensile steel	10 ga high tensile steel	10 ga high tensile steel
Ejection panel face	10 ga high tensile steel	10 ga high tensile steel	10 ga high tensile steel
Hopper	3/16" 100 ksi T-1	3/16" 100 ksi T-1	3/16" 100 ksi T-1
Packer panel face	(1/4" T-1 option)	(1/4" T-1 option)	(1/4" T-1 option)
Slide panel face	3/16" T-1 steel	3/16" T-1 steel	3/16" T-1 steel
	3/16" high tensile steel	3/16" high tensile steel	3/16" high tensile steel
Hopper sides	3/16" T-1 steel (lower tailgate); 10 ga high tensile steel (upper tailgate)	3/16" T-1 steel (lower tailgate); 10 ga high tensile steel (upper tailgate)	3/16" T-1 steel (lower tailgate); 10 ga high tensile steel (upper tailgate)

### HYDRAULIC SYSTEM

	RL6	RL8	RL10
Cylinders			
Ejector	Single-stage 4.5" bore	2-stage 4.5" bore	2-stage 4.5" bore
Tailgate	(2) 3.5" bore; 2" rod; 20" stroke	(2) 3.5" bore; 2" rod; 20" stroke	(2) 3.5" bore; 2" rod; 20" stroke
Slide	(2) 3.5" bore; 2" rod; 19" stroke	(2) 3.5" bore; 2" rod; 19" stroke	(2) 3.5" bore; 2" rod; 19" stroke
Packer	(2) 3.5" bore; 2" rod; 19" stroke	(2) 3.5" bore; 2" rod; 19" stroke	(2) 3.5" bore; 2" rod; 19" stroke
Valves			
Shutoff	Ball	Ball	Ball
Packing controls	Sectional spool	Sectional spool	Sectional spool
Ejector/tailgate raise	Sectional spool	Sectional spool	Sectional spool
Operating pressure in PSI	2,400	2,400	2,400
Maximum operating pressure	2,700	2,700	2,700
Gallons per minute (GPM)	21 GPM	21 GPM	21 GPM
Reservoir	30 gal.	30 gal.	30 gal.
Packing cycle time			
Complete	15-17 sec	15-17 sec	15-17 sec
Reload	3 sec	3 sec	3 sec
Compaction rate in lb/yd	700-800	700-800	700-800

### STANDARD FEATURES

- One piece flat floor
- Curved shell body
- Fast cycle time
- Meets or exceeds ANSI standards
- Wide open accessibility for cleaning and maintenance
- Automatic latches and integrated tailgate props
- The industry's highest standard for hydraulic cleanliness
- LED lighting, weatherproof connections and braided loom
- Dual Amber oval rear strobes
- Heat-treated pins and replaceable bushings throughout
- Large access door with safety interlock
- Emergency stop on curb side
- Driver alert buttons on both sides
- Sectional valves
- Slide and Packer cylinders are interchangeable

### OPTIONAL EQUIPMENT

- Single cart tipper
- Reeving system: Winch type
- Kick bar and container latches (38" minimum chassis height only)
- Front-mounted pump
- Amber or clear beacon rear strobes (single or dual)
- Amber oval flush mount strobes (front and/or rear)
- Smart light strobe system (may be combined with amber ovals)
- Rear vision camera
- Work lights over hopper and tailgate sides
- Frame mounted water cooler
- Frame mounted tool box
- Emergency stop on street side
- Pressure gauge
- Tool Holder
- Hyper Hopper (34" max chassis height only)

All design, specifications, and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is for information purposes only and shall not be construed to warrant suitability of the unit for any particular purpose, as performance may vary with the conditions encountered. The only warranty is our standard written warranty for this product at the time of shipment.



**POWERED BY**  
**HOL-MAC**  
CORPORATION