



pac-mac



KB-2 SERIES

THE NON-CDL SOLUTION LOADER

The KB-2 is the non-CDL solution in the Pac-Mac Grapple Truck Series. The KB-2 is known for its quality, user-friendly design, economic efficiency, and capability to handle various public works and solid waste industry obstacles.

DO IT RIGHT with Pac-Mac!



Visit us online at www.e-pac-mac.com

Manufactured by Hol-Mac Corporation • P.O. Box 349 • Bay Springs, MS 39422 • 601-764-4121



KB-2 SERIES

TECHNICAL DATA & SPECIFICATIONS

GENERAL SPECIFICATIONS

Height of boom to ground in lowest travel positions (based on 37in chassis height):	11 ft.
Boom length:	17 ft.
Boom rotation:	270° non-continuous
Lifting capacity at 17ft. (with grapple):	2400 lbs.
Fixed H-Style Outriggers:	8 ft.
Hydraulics :	Tandem fix, hydraulic pump display
Operator Controls:	Individual levers or pilot-operated hydraulic joysticks

BODY

Length:	18 ft.
Capacity:	20 cubic yds.
Tilt:	45° +/- 1°
Floor:	3/16 in. 8 in. main sill 4 in. joist with 16 in. spacing
Sides:	4 ft. wall body 1/8 in. Hardox with built in dirt guard
Lighting:	L.E.D. Mid-body turn signals

GRAPPLE

Width:	30 in.
Fully Open:	5 ft.

LIFT CAPACITY

Radius:	
10 ft. radius:	6020 lbs.
16 ft. radius:	3025 lbs.

STANDARD FEATURES:

Body

- Double rear doors
- Smooth pads for minimal street damage
- Complete discharge due to fully opening, swinging doors(s)
- 45-degree body tilt for complete cleanout
- Fixed H-Style outrigger design
- Nylon braiding wiring harness
- L.E.D lighting

Grapple

- High-strength tempered steel replaceable edges
- Anti-scalp design
- 360-degree continuous rotation
- Easy to use when handling heavy, bulky materials

Boom

- 17 ft. boom (10 ft. main boom, 7 ft. tip boom)
- All hoses are enclosed within the pedestal
- Pilot-operated hydraulic joysticks

Hydraulics

- Twin telescopic dump cylinders
- Ductile iron gland/piston, chrome rods, replaceable bronze bushings
- Built-in holding valves for safety
- Twin cylinders provide superior biting force
- Watertight connectors

Warranty

- 1-year hydraulic warranty
- 3-year structural warranty
- 3-year warranty on gearbox and slewing ring

Safety

- Bumper meets D.O.T. rear impact standards
- Integral holding valves in the main boom, tip, and outriggers cylinders
- Boom Height Alarm
- E-Stop

OPTIONS:

- Greaseless mechanical levers
- Tarp options: spring assist with arm, spring assist armless, electric with arm
- "Outrigger down" safety feature
- Outriggers mounted strokes
- Optional work light
- Body up alarm
- Optional Paint colors



POWERED BY:

HOL-MAC
CORPORATION

Manufactured by Hol-Mac Corporation
P.O. Box 349 • Bay Springs, MS 39422 • 601-764-4121
Visit us online at www.hol-mac.com



All designs, specifications, and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is for informational purposes only and shall not be construed to warrant suitability of the unit for any particular purpose, as performance may vary with the conditions encountered. The only warranty is our standard written warranty for this product at the time of shipment.