Specification Section – Code AG005 / Cargo Van System with Chassis

1 **Ford Transit 350 HD extended body high roof van with 3.5L gas engine, 10360 GVWR. See detailed specs for full vehicle specs, to which Aries will include:**
   1 Roadside DOT-rated safety kit including fire extinguisher, triangles, and flares
   2 Adjustable LED flood lights, rear
   1 Back up alarm

Chassis
Ford Transit 350 High Roof Extended Length, 148" Wheelbase
3.5L PFDi V6 gas engine, 275hp@ 6500rpm, 262lb·ft @ 3750rpm
250A alternator
Dual 12VDC 70A·h 610CCA batteries
GVWR 10360
FAWR 4130
RAWR 7275
Tires (6) 205/75R16C A/S
Front axle with MacPherson suspension with stabilizer bar
Rear axle with parabolic leaf springs and heavy-duty gas shock absorbers
Limited slip rear differential, 4.10 ratio
25-gallon fuel tank
4-wheel disc antilock brakes
10-speed automatic transmission with overdrive and SelectShift

Interior / Exterior
Vinyl reclining bucket seats
Cab air conditioner
Heater - manually operated with defroster and window defoggers
AM/FM stereo including rear view camera display
Analog instrument panel including speedometer, odometer/trip, fuel gauge, voltmeter, engine temp, and oil pressure
Convex combination outside rearview mirrors
Intermittent windshield wipers with pulse washers
Paint: oxford white
Dimensions = 172.2" long load space, 81.5" interior height, width 45.4" at wheel wells, 70.2" maximum interior

1 **7,000W, gas powered, commercial grade generator, 120V, 60 Hz, with electric local and remote start/stop control to include:**
   1 Generator enclosure lined with maintenance access panels and ventilation grating
   1 Airflow separating mounting bridge
   1 Exhaust system with internal muffler
   1 Auxiliary battery, 12V DC and case
   1 DC converter, 45A
   1 Electric distribution panel and circuit breaker box, 12-space
   1 Electric supply transfer system, house power or generator system, automatic, 50A
   1 35' cord and house power receptacle with cover
   1 System engineering panel to include:
      1 Generator Voltage and frequency meter, digital
      1 Generator start/stop switch

1 Generator hour meter

1 Van control room interior including:
1 Lonplate non-skid floor covering
1 Pewter Formica laminated surface wall covering
1 White Kemlite embossed ceiling cover
1 Bulkhead wall with sliding Plexiglas sliding window
1 Low profile roof mounted air conditioner, 11000 BTU with heat strip
1 Modular control center, 19" rack mounted above the bulkhead window
1 3U storage drawer for controllers
1 Ergonomically contoured and finished control desk
1 Standard electrical upfitting package
1 LED lighting system
1 LED dome light with timer and switch
1 Operator chair, swivel with casters
1 Fire extinguisher, 10lb, 4A60 B:C rating, OSHA/DOT-approved

1 Van equipment room interior including:
1 Lonplate non-skid floor covering
1 Light gray Kemlite laminated surface wall covering
1 White Kemlite embossed ceiling cover
1 Standard electrical upfitting package
1 LED lighting system
1 LED dome light with timer and switch by rear body door
1 Set equipment storage hooks and tie down rings, shipped loose
1 Work bench with Lonplate worktop and vise
1 Downhole pole storage tube

1 19" LCD flat panel monitor, TV/PC viewing, mounted to control room desktop

1 Aries VL5000 video data display including:
1 Data Display control module, panel mounted
1 Alpha/Numeric Full QWERTY Keyboard for video titling and report data input for VL5000 Display
1 Set of interconnect cables

1 Digital Video Recorder system, including:
1 Modular control center, 19" rack mount location
1 Unit to compress video in MPEG4 format
1 Mini USB keyboard for recording function control
1 16GB USB flash drive
1 Set of interconnect cabling

1 Audio recording microphone, swivel neck

1 Aries Master Controller system, multi-conductor, including:
1 System power supply and control unit, 19" rack mount
1 Pegasus system control software, loaded on USB flash drive
2 Wireless Xbox One X style handheld controller
1 Wire for direct hook up / charging of Xbox One X style controller

1 Wall mounted USB port for controller

1 Aries PE3530 Pathfinder series zoom, pan & tilt camera w/ high-intensity LED lighting and integrated self-cleaning lens wiper system, including:

- Pathfinder zoom pan and tilt camera w/ multi-axis infinite rotation
- Integrated on-demand self-cleaning lens wiper system
- 120X zoom (10X optical & 12X digital)
- High-resolution 480(V) x 720(H) output
- Auto-focus with manual override
- Auto-iris with manual override
- Maintenance-free forward-facing white LED lighting located in the camera forks
- Maintenance-free directional white LED lighting that follows the camera's field of view
- White balance optimization with (4) selectable settings
- High-sensitivity camera sensor for low-light applications
- "Starlite" low-light level amplification feature with (4) user selectable amplification steps
- Automatic home feature with forks at side of camera head
- "One Touch Scanning" feature with (2) user selectable continuous joint scan presets
- "Quick Look" preset view positions (6) (Up, Down, Right, Left, Lat R, Lat L)
- Robust, environmentally sealed camera for use in live pipe, including:
  - Scratch-resistant sapphire lens window
  - Camera recessed behind forks for frontal impact protection
  - Camera housing with hardened metal finishes and non-corrosive metals
  - Recessed fasteners & no camera protrusions
- Proportionately slowed camera movements when zooming
- Fast-check internal pressure monitoring system
- On-screen camera diagnostics functions including:
  - Camera internal pressure, temperature, operating hours, internal power regulated voltage value, camera model, serial number, firmware revision, control error recognition, LED current value.

1 Camera storage and transport case
1 Camera nitrogen recharge kit

1 Aries TR3300 Pathfinder steerable self-propelled transporter for relined 6" to 15" lines, including:

1 Tractor assembly with continuous duty drive motors
6 Rubber wheels, 3" diameter
4 Rubber wheels, 4" diameter
4 Extended hub rubber wheels, 4" diameter
4 Extended hub rubber wheels, 5" diameter
1 Manual camera lifting mechanism
1 Rear viewing camera with LED lighting
1 512 Hz detachable locating beacon
1 Auxiliary detachable light head
1 Storage and transport case
1 Set maintenance parts

1 Pathfinder cable and reel assembly, with features including:

- 1000' of lightweight low friction multi-conductor cable
- Heavy-duty frame, drum and motor assembly with clutch and cable level wind assembly

Footage meter with local LCD footage display and encoder for footage signal to remote video data display system
Emergency hand crank arm
Spare cable termination kit
Sealed continuous contact collector assembly, 12 slip rings minimum
Telescoping swivel cable guide roller assembly
1 Pathfinder system test cable
1 Reel controller with desktop mounting devices
1 Interconnect cable to TV system electronics
1 Drip pan with drain

1 Mounting bridge with tractor storage underneath

1 Cable manhole guide system including:
1 Manhole top roller assembly
1 Insertion and extractor pole assembly and tractor adapter
3 Quick lock extension poles
1 Manhole bottom roller assembly and adapter hook
5 Quick lock extension poles

2 Operation / maintenance and spare parts manuals
1 Maintenance tool kit
1 Delivery of system
2 Days of training
1 One year warranty, TV system