



**DSX Access Systems, Inc.**

## **DSX-Dialup Modem SPI-1442-FI**



- RS-232 and RS-485 Outputs for Controller Communications
- Powered by Controllers
- DB9 for connections to PC
- Terminal Blocks for Controller Connections
- Over Voltage Protection
- Can be connected to DSX-LAN (M) for modem backup
- Protocol Independent
- Status LEDs

## **DSX-Dialup Modem SPI-1442-FI**

### **Size**

SPI-1442-FI = 5.5" W x 3.5" H x 1.0" D

### **Weight**

12.0 oz.

### **Temperature/Humidity**

Operating 0 to 70 C

### **Power Requirements**

DC Input Voltage 12VDC @ 300ma

### **Warranty**

Limited 2 Years

This new DSX Modem is small and DC powered. It is easily connected to a DSX-LAN(M) module for redundancy. The unit has both an RS-232 and RS-485 communications port for connecting it to any DSX controller without the use of a MCI module or adapter. There is a DB9 connector for easy connection to a serial port. This modem comes with everything needed for any DSX dialup application.

Onboard dipswitches set PC or Controller location for modem and control speaker.

### **Inputs**

1 – RS-232 via Terminal Block or DB25 female

### **Outputs**

1 – RS-485 Output / 4 Wire Terminal Block