

**DynaLock Corporation**

705 Emmett Street

Bristol, CT 06010

**Phone:** 860.582.4761 • **Fax:** 860.585.0338**Email:** [info@dynalock.com](mailto:info@dynalock.com) • **Website:** [www.dynalock.com](http://www.dynalock.com)**1900 Series All-in-One Electric Strikes**Coming 2<sup>nd</sup> Quarter 2015...

Versatile DynaLock 1900 Series All-in-One fire-rated (UL 10C, 3 hour) and non-fire-rated Electric Strikes accommodate mortise and cylindrical locksets, as well as mortise exit devices, with offset, or centerline latch entry and up to a 3/4" latch projection. The adjustable deadbolt keeper and deadlatch ramp vertically align to accommodate a wide variety of mortise locks with offset latches. A unique, sliding shim design adjusts vertically on the keeper, to provide up-to 1/8" horizontal adjustment and a "plug-in" latch monitor switch option kit may be added in the field. Field-selectable input voltage 12/24 VDC or 12/24 VAC (1921). Both models fit a HES 1006 (1003) frame cutout (hollow-metal), with no additional modifications.

ANSI (American National Standards Institute) Certified

Results 1 - 2 of 2

<u>Item #</u>	<u>Item Name</u>	<u>Finish</u>	<u>Voltage</u>	<u>Current Draw</u>	<u>Width</u>
<u>1921</u>	Fail-Secure, 12/24 VAC/VDC (Voltage Alternating Current/Voltage Direct Current), Fire-Rated All-in-One Strike	US32D	12/24 VAC/VDC	190 mA @ 24 VDC, Continuous 280 - 565 mA @ 12/24 VAC, Intermittent 375 mA @ 12 VDC, Continuous	1-1/4 in
<u>1923</u>	Fail-Safe, 12/24 VDC (Voltage Direct Current) Non Fire-Rated All-in-One Strike	US32D	12/24 VDC	190 mA @ 24 VDC, Continuous 375 mA @ 12 VDC, Continuous	1-1/4 in

Results 1 - 2 of 2