

**PM310 COLD PLANER  
MINERBIO, ITALY**Ship Weight  
lbsLIST PRICE  
AT DEALER

Standard Equipment:

**POWERTRAIN**

CAT C9.3, inline 6-cylinder,  
turbocharged, ATAAC, diesel engine  
Power and torque curve optimized for  
fuel efficiency  
Engine diagnostic connector (for Cat ET)  
Air cleaner, dry type dual element with  
integral precleaner  
Belt, automatic tensioner  
Fuel filter/water separator  
Hydrostatic transmission  
Computerized load control  
Traction control/differential lock  
Alignment controlled steering system  
with two steering modes:  
rear and assist ON/OFF  
Alignment is optimized for selected mode

**ELECTRICAL**

Backup alarm  
Alternator, 115-amp  
Batteries, two maintenance free,  
1400 CCA each  
Horn, forward warning  
Ground located horn, operator warning  
Electrical system, 24 Volt  
Work lights (8 pole mount)  
Machine diagnostic connector  
(for CAT ET)  
Self diagnostic system  
Product link equipped

**OPERATOR ENVIRONMENT**

Single right side operation station  
with adjustable seat  
Platform handrails/guardrails  
Lockable vandalism guards for all  
control panels  
Joystick propel and steering  
Control console with LED backlit panels  
Machine monitoring system  
Electronic machine management system  
Automatic throttle control  
Digital graphic display for  
diagnostics and operating instructions  
Silver-class touch screen display  
Camera ready display  
LED wake-up mode with floor light  
Integrated grade control ready  
Electronic drivetrain protection system  
Rear RH leg steering for track option  
Rear RH leg retraction  
Load control  
Ramp-in, ramp-out function  
Digital moldboard control

3 rotor speeds selectable on control  
panels  
Quick detach fuses and relays with  
blown fuse and relay detection/fault  
indication on display  
Two level warning system with action  
light and horn (warning, critical  
warning)  
Water spray system  
Electronic water level gauge  
12v ports at operator station  
Rotor service keypad control

**APPLICATION SPECIFIC COMPONENTS**

**ROTOR AND CHAMBER SYSTEM**  
Caterpillar patented tool holder with  
easy extraction feature  
External floating side plates  
Dry clutch, belt transmission and  
automatic tensioner  
Dedicated water spray for tool cooling  
and dust control  
Curb clearance right side plate  
Moldboard with floating, locked or  
service height levels and adjustable  
down pressure  
Hydraulic raiseable and floating anti-  
slab  
**CONVEYORS**  
Front loading  
600 mm (26.3") belt width collecting  
conveyor  
600 mm (26.3") belt width discharge  
conveyor  
Dual stage, infinitely variable speed  
60-degree swing either side of center  
for discharging conveyor  
Quick-detach discharge conveyor

**FLUIDS**

Extended life coolant with protection  
to -34C (-29F)

**OTHER STANDARD EQUIPMENT**

Doors, service access, hinged, locking  
Fuel tank 600 L (158 gal)  
Pressure test ports with quick connect  
Water tank 1260 L (333 gal)  
Sound suppression insulation kit  
Mirrors  
Gas-spring engine hood lift  
Emergency functions:  
Hand pump brake release  
Air filter restriction electric  
indicator

---

PM310 COLD PLANER  
MINERBIO, ITALY

Ship Weight  
lbs

LIST PRICE  
AT DEALER

---

**OTHER STANDARD EQUIPMENT (CONT.)**

On board winterization system  
Bit removal tools  
S.O.S. sampling ports  
Sight gauges (hydraulic oil, filter  
restriction)

---

PM310 COLD PLANER  
MINERBIO, ITALY

Ship Weight  
lbs

LIST PRICE  
AT DEALER

---

**Lane 2 is reserved for the Base Order Management Program.  
Please use Lane 2 when placing orders that are part of the Base  
Orders Management Program.**

<b>575-4708</b>	<b>PM310 02B COLD PLANER . . . . . 0</b>	<b>\$346,030</b>
	LANE 2 - AVAILABLE FROM MINERBIO FACTORY	
	LANE 3 - AVAILABLE FROM MINERBIO FACTORY	

AVAILABLE FOR: AM-N, Puerto Rico, Europe, Israel and South Korea

<b>0G-0616</b>	<b>PM310 MISC MATL . . . . . 0</b>	<b>NC</b>
	AVAILABLE FROM MINERBIO FACTORY	

Only reference numbers that have the text  
"ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

**LANE SELECTION**

0P-9002	LANE 2 ORDER . . . . .	0	NC
	Only for dealers enrolled in the Base Order Management (BOM) program.		
0P-9003	LANE 3 ORDER . . . . .	0	NC

**SPECIAL ARRANGEMENTS****CHASSIS**

L	575-4714	MACHINE, PM3 COMMON . . . . .	0	NC
		ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER		

**POWERTRAIN****ENGINE**

L	548-2958	ENGINE, CAT C9.3 . . . . .	0	NC
		Meets U.S. EPA Tier 4 Final, EU Stage V and Korea Tier 4 Final emission standards. Meets UN R120.		
		ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER		

**TRACTION TYPE**

L	577-6236	WHEEL, CONVERSION . . . . .	0	NC
		Includes solid rubber tires on steel wheels.		
		ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER		
L	381-6527	WHEEL, CONVERSION . . . . .	0	NC
		Includes solid rubber tires on steel wheels.		
		ONLY FOR USE WITH: 471-6427 PM310 COLD PLANER		
L	577-6234	TRACK, CONVERSION . . . . .	0	\$62,990
		Includes independent track drives with auto tensioning system.		
		ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER		

**HYDRAULICS****DUST EXTRACTION**

L	381-6682	COVER, NO VENTILATION . . . . .	0	NC
L	577-6257	VENTILATION SYSTEM . . . . .	0	\$5,930
		Dust and particles from operations are collected in multiple areas by hydraulically driven fan and discharged into secondary conveyor.		
		NOTE: option may be needed for local regulations.		
		ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
ELECTRICAL				
LIGHTING				
L	381-6575	LIGHTS, HALOGEN . . . . .	0 0	\$770 \$770 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 8 halogen lights: 1 light facing each of the 4 tracks/wheels, 1 light facing the rear of the cutter box, 1 light facing the front of the cutter box and 2 lights mounted on the top front end of the discharge conveyor.		
L	381-6572	LIGHTS, LED . . . . .	0 0	\$4,610 \$4,610 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 8 LED lights: 1 light facing each of the 4 tracks/wheels, 1 light facing the rear of the cutter box, 1 light facing the front of the cutter box and 2 lights mounted on the top front end of the discharge conveyor.		
TECHNOLOGY PRODUCTS				
PRODUCT LINK COMMUNICATION (Must select one)				
Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the cost of owning and operating your fleet. Availability varies by country. Please reference <a href="https://Dealer.cat.com/PL/Certification">https://Dealer.cat.com/PL/Certification</a> for certified countries. Please contact your Caterpillar marketing representative with questions.				
L	381-6524	PRODUCT LINK, SATELLITE PL631 . . . . .	0	\$439
		Product Link Pro series PL631 uses a satellite network to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. For use in areas with poor or no cellular coverage.		
L	488-5577	PRODUCT LINK, SATELLITE PLE631 . . . . .	0	\$813
		Product Link Elite series PLE631 (consisting of PL631 radio and PLE601 network manager) uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		
L	381-7317	PRODUCT LINK, CELLULAR PL641 . . . . .	0	NC
		Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		
L	381-6525	PRODUCT LINK, CELLULAR PLE641 . . . . .	0	\$372
		Product Link Elite series PLE641 (consisting of PL641 radio and PLE601 network manager) uses cellular networks to transmit location, utilization, health and productivity information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		
L	319-4492	NO PRODUCT LINK . . . . .	0	NC
		Product link removal - Special case, to be used only for orders to countries where Product Link is not authorized.		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

**OTHER ATTACHMENTS****MILL ROTORS**

L	522-0117	<b>ROTOR, K STD - 15 MM</b> . . . . . 0 Latest Design tool holder system with 1000 mm (39.4") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 15 mm. Includes: 91 Bits		\$25,850
C	567-0885	<b>ROTOR, K FINE - 8 MM</b> . . . . . 0 CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest design tool holder system with 1000 mm (39.4") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 8 mm. Includes: 150 Bits		\$37,470
C	567-0888	<b>ROTOR, K COARSE - 18 MM</b> . . . . . 0 CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest design tool holder system with 1000 mm (39.4") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 18 mm. Includes: 80 Bits		\$24,550
L	0F-5136	<b>OMISSION, ROTOR</b> . . . . . 0 ONLY FOR USE WITH: LANE 3		NC

**DISCHARGE CONVEYOR**

L	572-9763	<b>DISCHARGE CONVEYOR, MECHANICAL</b> . . . . . 0 Mechanical downward folding discharge conveyor. ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER		\$40,320
L	381-6529	<b>DISCHARGE CONVEYOR, MECHANICAL</b> . . . . . 0 Mechanical downward folding discharge conveyor. ONLY FOR USE WITH: 471-6427 PM310 COLD PLANER		\$40,320
L	572-9764	<b>DISCHARGE CONVEYOR, HYD. FOLD</b> . . . . . 0 Hydraulically downward folding discharge conveyor. ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER		\$48,350

**WATER TANK GROUND LEVEL FILLING PORT**

P	381-7333	<b>PORT, FILLING, WATER TANK</b> . . . . . 0 Water tank ground level Filling Port. US Standard only.		NC
---	----------	--	--	----

**STEERING GUIDES**

L	548-3070	<b>GUIDE, STANDARD STEERING</b> . . . . . 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides one standard steering guide with lateral adjustment of pendulum markers.		NC \$279 NI
L	548-6908	<b>GUIDE, TELESCOPING STEERING</b> . . . . . 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides one telescoping steering guide with multi point adjustment for advanced steering marker placement. ONLY FOR USE WITH: 577-6234 TRACK, CONVERSION or 381-6528 TRACK, CONVERSION		NC \$343 NI

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

**OTHER ATTACHMENTS (CONT.)****ROTOR DRIVE BELT GUARD**

L	578-5682	<b>GUARD, NO ROTOR TURNING DEVICE</b> . . . . . 0 Provides a rotor drive belt guard for machines not equipped with a rotor turning device. ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER		NC
L	577-6336	<b>GUARD, ROTOR TURNING DEVICE</b> . . . . . 0 Provides a rotor drive belt guard for machines equipped with a rotor turning device ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER 561-4359 ROTOR TURNING DEVICE		NC

**GRADE AND SLOPE CONTROLS**

P	481-8872	<b>CONTROL, GRADE</b> . . . . . 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Measures grade from the position of side plates, using position sensing cylinders. Provides information to machine displays for operation of grade control. ONLY FOR USE WITH: 471-6427 PM310 COLD PLANER	0	\$8,750 \$8,750 NI
L	577-2980	<b>CONTROL, GRADE</b> . . . . . 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Measures grade from the position of side plates, using position sensing cylinders. Provides information to machine displays for operation of grade control. ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER	0	\$8,750 \$8,750 NI
P	381-7320	<b>CONTROL, SLOPE</b> . . . . . 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Measures cross slope using a slope sensor mounted to the chassis. Provides information to machine for operation of grade control. ONLY FOR USE WITH: 481-8872 CONTROL, GRADE and 577-2980 CONTROL, GRADE	0	\$2,060 \$2,060 NI

**COMMISSIONING SUPPORT**

NOTE: It is recommended that startup and commissioning of machine be included as part of the machine sale. The net charge covers a three days commissioning event. Trained personnel cover proper machine setup, basic maintenance, operation and application on a customer's jobsite. To request and schedule a machine commissioning event, dealers will need to contact the Caterpillar Paving Technical Training group by filling out the online request form

URL:<https://dealer.cat.com/PavingOnDemand>

L	OP-2586	<b>COMMISSIONING, NEEDED</b> . . . . . 0 Commissioning Needed, trained personnel are required to properly commission the machine. AVAILABLE FOR: AM-N and AM-S		\$6,420 NET
	OP-2587	<b>COMMISSIONING, NOT NEEDED</b> . . . . . 0 Commissioning, Not Needed, dealer personnel are available to to properly commission the machine.		NC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

**FLUIDS*****OIL***

L	381-6481	HYDR. OIL, HYDO ADVANCED 10W . . . . . 0		NC
		Cat standard hydraulic oil.		
L	381-6489	HYDRAULIC OIL, BIODEGRADABLE . . . . . 0		\$2,250
		Hydraulic environmental ester synthetic oil is recommended when environmental compliance is required or desired.		
		ONLY FOR USE WITH: LANE 3		
L	381-6523	HYDRAULIC OIL, HIGH AMBIENT . . . . . 0		\$705
		Hydraulic synthetic oil is recommended when high ambient operation is typical for machine.		
		ONLY FOR USE WITH: LANE 3		

**INSTRUCTIONS*****DECAL PACKAGES***

L	577-2995	INSTRUCTIONS, ANSI . . . . . 0		NC
---	----------	--------------------------------	--	----

***SERVICE INSTRUCTIONS***

	421-8926	SERIALIZED TECHNICAL MEDIA KIT . . . . . 0		NC
		The technical media kit, will include the Operation & Maintenance Manual (OMM) and other media specified on the Factory Notification List required to ship products from the manufacturing facility. Kit may contain multiple Operation & Maintenance Manuals (OMM) based on the final country of destination. Contents will vary.		
		Any additional media or translations not included in the kit, should be ordered through <a href="http://publications.cat.com">publications.cat.com</a>		



USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
<b>ELECTRICAL</b>				
P	481-8732	<b>LIGHT, HAZARD, CANOPY</b> ..... 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two LED amber strobe lights, bracket mounted on a rotatable, detent pivot base. One strobe is mounted on the canopy at the rear of the machine and the other is mounted at the front of the machine at the top of the conveyor. ONLY FOR USE WITH: 563-0519 CANOPY, FOLDING, HYDRAULIC or 381-7316 CANOPY, FOLDING, HYDRAULIC or 566-6910 CANOPY, FOLDING, HYDRAULIC		<b>\$344 NI</b>
P	421-8156	<b>LIGHT, HAZARD</b> ..... 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two LED amber strobe lights: one is mounted to an adjustable height pole mount on the rear of the machine, the other is mounted at the front of the machine, at the top of the conveyor on a rotatable bracket on a detent pivot base. CANNOT BE USED WITH: 563-0519 CANOPY, FOLDING, HYDRAULIC or 381-7316 CANOPY, FOLDING, HYDRAULIC or 566-6910 CANOPY, FOLDING, HYDRAULIC	0 0	<b>\$910</b> <b>\$910 NI</b>
P	381-7323	<b>LIGHTS, ROADING AND WORKING</b> ..... 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two front mounted working lights with turn signals, two rear indicator/parking lights that signal, license plate holder with light and mounting hardware.	0 0	<b>\$3,405</b> <b>\$3,405 NI</b>
P	394-9642	<b>LAMP, HALOGEN (MAGNETIC)</b> ..... 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides a single halogen lamp with magnetic mounting.		<b>\$316 NI</b>
P	381-7330	<b>LIGHT, TRUCK SIGNAL</b> ..... 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Red/Green light to communicate with truck driver.	0 0	<b>\$555</b> <b>\$555 NI</b>
P	569-2838	<b>PUMP ACCESSORY DRIVE</b> ..... 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Electro-hydraulic pump to allow for operation of steering, elevation and canopy movement with engine power off. ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER	0 0	<b>\$610</b> <b>\$610 NI</b>
P	381-7331	<b>PUMP ACCESSORY DRIVE</b> ..... 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Electro-hydraulic pump to allow for operation of steering, elevation and canopy movement with engine power off. ONLY FOR USE WITH: 471-6427 PM310 COLD PLANER	0 0	<b>\$610</b> <b>\$610 NI</b>

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

**OPERATOR ENVIRONMENT****OPERATOR STATION**

P	566-6910	CANOPY, FOLDING, HYDRAULIC . . . . .	0	\$4,895
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER	0	\$4,895 NI
		Hydraulically folding canopy with extendible side wings.		
		REQUIRES: 569-2838 PUMP, EMERGENCY		
		ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER		
P	381-7316	CANOPY, FOLDING, HYDRAULIC . . . . .	0	\$4,895
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER	0	\$4,895 NI
		Hydraulically folding canopy with extendible side wings.		
		REQUIRES: 381-7331 PUMP, EMERGENCY		
		ONLY FOR USE WITH: 471-6427 PM310 COLD PLANER		
P	577-2997	UMBRELLA. . . . .	0	\$700 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes (1) umbrella to provide operator protection from sun		
		and rain. Umbrella measures 1372 mm x 1372 mm (54" x 54") and		
		is collapsible. Includes support shafts and mounting hardware		
		to be installed on machine at customer discretion.		
		ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER		
P	381-7324	UMBRELLA. . . . .	0	\$700 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes (1) umbrella to provide operator protection from sun		
		and rain. Umbrella measures 1372 mm x 1372 mm (54" x 54") and		
		is collapsible. Includes support shafts and mounting hardware		
		to be installed on machine at customer discretion.		
		ONLY FOR USE WITH: 471-6427 PM310 COLD PLANER		

**OTHER ATTACHMENTS****GRADE AND SLOPE CONTROLS**

L	509-2523	SENSOR, SONIC, AVERAGING . . . . .	0	\$10,230
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER	0	\$10,230 NI
		Sonic averaging ski for mounting on the LH or RH side or inboard.		
		Consists of two sonic sensors (in addition to the machine grade		
		control base system) with adjustable mounting arms.		
		ONLY FOR USE WITH: 577-2980 CONTROL, GRADE or		
		481-8872 CONTROL GRADE		
P	381-7318	DISPLAY, OPTIONAL, PLFM . . . . .	0	\$2,850 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Additional (1) display with mounting bracket for ground/operator		
		station(s).		
		Order qty 1 maximum		
		ONLY FOR USE WITH: 481-8872 CONTROL, GRADE		
P	387-9468	DISPLAY, OPTIONAL . . . . .	0	\$2,850 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Additional display (1) with mounting bracket for use at ground		
		level.		
		Order qty 1 maximum		
		ONLY FOR USE WITH: 577-2980 CONTROL, GRADE or		
		481-8872 CONTROL, GRADE		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

**OTHER ATTACHMENTS (CONT.)****VISIBILITY ENHANCEMENTS**

P	421-8146	REAR CAMERA. . . . .	0 0	\$665 \$665 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER This camera system is used to enhance the operator's rear visibility while operating. The LCD color display is designed to have a sharp, clear picture with camera mounted on the top rear end of the machine. NOTE: Mandatory for all EC countries and affiliates		
P	381-7314	CONVEYOR CAMERA. . . . .	0 0	\$925 \$925 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER This camera system is used to enhance the operator's forward visibility while operating. The LCD color display is designed to have a sharp, clear picture with camera mounted on the top front end of the discharge conveyor.		
P	488-5580	CAMERA, AUX. . . . .	0	\$750 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes camera with cable and magnetic mount. Can be placed anywhere within cable length.		
P	542-7915	CAMERA, LH DRUM EDGE . . . . .	0 0	\$635 \$635 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Positioned to assist in lining up for cutting on left hand side of rotor. Includes camera, auxiliary lamp, cable, bracket and mounting hardware.		
P	551-5925	CAMERA, CUT TRACKING . . . . .	0 0	\$825 \$825 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Mounted to view and track rotor alignment and positioning. This camera system offers the operator advanced visibility of the rotor placement with the ability to adjust alignment guides on the standard council mounted display. ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER		

**ROTOR SERVICING TOOLS**

P	376-4134	PNEUMATIC BIT REMOVAL TOOL . . . . .	0	\$630 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes pneumatic hammer, punch tools, coil hose and fittings.		
P	561-4359	ROTOR TURNING DEVICE. . . . .	0	\$3,555
		Includes control device and electrical motor for powered rotational assist when servicing the rotor. ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER		
P	381-7326	PNEUMATIC COMPRESSOR SYSTEM. . . . .	0 0	\$2,785 \$2,785 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Engine mounted air compressor with hose, tank and pressure regulator.		
P	577-4176	EXTRACTOR, TOOL HOLDER . . . . .	0	\$278 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Hand tool for extracting K System cutter bit tool holders which have broken at the shank inside the weld on block. Tool is engaged to broken shank via a threaded pulling bolt.		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

**OTHER ATTACHMENTS (CONT.)****ADDITIONAL WATER SPRAYING SYSTEM**

P	421-9634	DUST REDUCTION, ADDITIONAL . . . . .	0	\$665
			0	\$665 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Additional water spraying system for dust reduction. Includes additional spray bars located on the front and rear of the pickup conveyor. NOTE: option may be needed for local regulations.				

**HIGH PRESSURE WASHDOWN**

L	577-6255	PUMP, WASHING, HIGH PRESSURE . . . . .	0	\$4,930
			0	\$4,930 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER High pressure washdown water pump, including (1) wand with 15 m (50 ft) of hose on reel. ONLY FOR USE WITH: 575-4708 PM310 02B COLD PLANER				
L	381-7321	PUMP, WASHING, HIGH PRESSURE . . . . .	0	\$4,930
			0	\$4,930 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER High pressure washdown water pump, including (1) wand with 15 m (50 ft) of hose on reel. ONLY FOR USE WITH: 471-6427 PM310 COLD PLANER				

**LOW PRESSURE WASHDOWN**

L	544-2811	WASHDOWN, LOW PRESSURE . . . . .	0	\$1,465
			0	\$1,465 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides 13 m (43 ft) of low pressure washdown hose, spray nozzle and coiled hose storage bracket. Coiled hose storage bracket mounts to the discharge conveyor.				

**MISC ATTACHMENTS**

P	482-4046	BALLAST KIT . . . . .	0	\$3,680
			0	\$3,680 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER 510 kg of additional weight for greater milling control, especially when in deep cuts or when cutting challenging material. Recommended for machines used in a full range applications or those seeking premium cutting control.				
P	561-4363	HOSE, SUCTION . . . . .	0	\$307 NI
ALSO AVAILABLE ON MISCELLANEOUS ORDER Suction hose with strainer for filling the water tank for alternative water sources. European standard only. ONLY FOR USE WITH: 381-7332 PORT, FILLING, WATER TANK				

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

**FIELD INSTALLED ATTACHMENTS**

The following field attachments can be ordered  
through Machine Order as a miscellaneous order.

C	522-0118	<b>ROTOR, K STD - 15 MM, FLD</b> ..... 0 CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest Design tool holder system with 1000 mm (39.4") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 15 mm. Includes: 91 Bits		<b>\$25,850 NI</b>
C	567-0886	<b>ROTOR, K FINE - 8 MM, FLD</b> ..... 0 CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest design tool holder system with 1000 mm (39.4") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 8 mm. Includes: 150 Bits		<b>\$37,470 NI</b>
C	567-0889	<b>ROTOR, K COARSE - 18 MM, FLD</b> ..... 0 CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest design tool holder system with 1000 mm (39.4") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 18 mm. Includes: 80 Bits		<b>\$24,550 NI</b>

**DOCUMENTATION*****CERTIFICATES***

OF-5109	<b>CERTIFICATE OF ORIGIN</b> ..... 0	<b>\$89 NET</b>
---------	--------------------------------------	-----------------

**PACKING**

OG-0044	<b>ROLL ON-ROLL OFF</b> ..... 0	<b>NC</b>
OG-0068	<b>PACK, MISCELLANEOUS MATERIAL</b> ..... 0	<b>NC</b>