

CW34 PNEUMATIC TIRE COMPACTOR (XUZHOU)
XUZHOU, CHINA

Ship Weight
lbs

LIST PRICE
AT DEALER

Standard Equipment:

POWERTRAIN

CAT C4.4 inline 4 cylinder,
turbo-charged diesel engine
Dual element cyclonic air cleaner
Fuel filter / water separator
Ultra clean fuel filter with integrated
prime pump
Fuel reducing, automotive style,
variable speed engine control
Automatic idle shutdown
Dual braking system (service & parking)
Continuously variable hydrostatic
transmission with seamless shifting
3 Speed ranges
Auto speed control (ASC) for lower noise
and fuel consumption

Dedicated system for each tire
Intermittent adjustable spray on/off
time
Water Capacity
Self adjusting, retractable, nylon tire
scraping system
Manual brake release
Lockable fuel fill
Transport tie-down and lift points
High ambient capable (49 deg C)

ELECTRICAL

24-volt electric starting
100 - amp alternator
Two CAT maintenance free batteries
Roading lights - turn signals and low
beam forward facing lights
Rear backup light and stop indication
lamps
Halogen working lights - bumper mounted
(2 front-facing and 2 rear-facing)
Backup alarm and forward warning horn
Product link ready

OPERATOR ENVIRONMENT

Side to side sliding and plus/minus 90
degree rotating operator station
Machine and operating functions are
integrated into 4" LCD display
Fore/aft adjustable suspension seat
Oversized RH arm rest
3" wide belt
Vandalism protection
Power assisted steering
Tilt able steering column
Rubber floor mat

FLUIDS

Premixed 50% concentration of extended
life coolant with freeze protection
to -37C (-35F)

OTHER STANDARD EQUIPMENT

Locking fiberglass engine enclosure
All wheel oscillation - front and rear
Front wheel vertical equalizing
suspension
Single pump, triple filtration
pressurized water system

CW34 PNEUMATIC TIRE COMPACTOR (XUZHOU)
XUZHOU, CHINA

Ship Weight
lbs

LIST PRICE
AT DEALER

Lane 2 is reserved for the Base Order Management Program.
Please use Lane 2 when placing orders that are part of the
Base Order Management Program.

505-5712 CW34 PNEU COMP DCA1 0 \$198,400
LANE 1 - AVAILABLE FROM GALVESTON PDC

INCLUDES:

445-5711 CW34 PNEUMATIC COMPACTOR
443-8810 ENGINE, TIER 4F/STAGE 4
445-5707 FRAME, STANDARD MACHINE
355-1670 BELT, ENG
368-9296 BASE, OPERATOR STATION
364-6748 SEAT, STD VINYL
457-1622 CONTROL, PREMIUM
454-5454 PRODUCT LINK, CELLULAR PL641
460-0782 INSTALLATION, ROPS
359-7789 TIRES, STD
364-8437 OIL, HYD, FACTORY FILLED
364-6752 INSTRUCTIONS, NORTH AMERICAN
364-6757 LIGHTS, HALOGEN
364-6763 MIRRORS, EXTERNAL
359-7792 ROPS
364-6759 CANOPY, SUN, ROPS
388-7112 COCOA, MAT W/SCRAPER
359-7790 SPRAY, EMULSION
456-0084 CONTROL OPTION

NOTE: Please refer to Lane 1 section to complete your order.

505-5713 CW34 PNEUMATIC COMPACTOR DCA7 0 \$224,280
LANE 1 - AVAILABLE FROM GALVESTON PDC

INCLUDES:

445-5711 CW34 PNEUMATIC COMPACTOR
443-8810 ENGINE, TIER 4/STAGE 4
445-5707 FRAME, STANDARD MACHINE
355-1670 BELT, ENG
368-9296 BASE, OPERATOR STATION
364-6750 SEAT, HEATED VINYL
457-1622 CONTROL, PREMIUM
454-5454 PRODUCT LINK, CELLULAR PL641
460-0782 INSTALLATION, ROPS
359-7788 TIRES, MICHELIN
364-8437 OIL, HYD, FACTORY FILLED
364-6752 INSTRUCTIONS, NORTH AMERICAN
364-6755 LIGHTS, HIGH INTENSITY
359-7792 ROPS
364-6759 CANOPY, SUN, ROPS
388-7112 COCOA MAT W/SCRAPER
359-7796 INFLATION GROUP
471-3180 THERMAL, TIRE APRON

NOTE: Please refer to Lane 1 section to complete your order.

CW34 PNEUMATIC TIRE COMPACTOR (XUZHOU)
XUZHOU, CHINA

Ship Weight
lbs

LIST PRICE
AT DEALER

445-5711	CW34 PNEUMATIC COMPACTOR	17,857	\$183,840
	LANE 2 - AVAILABLE FROM XUZHOU FACTORY		
	LANE 3 - AVAILABLE FROM XUZHOU FACTORY		

0P-2788	CW34 MISC MATERIAL	0	NC
	AVAILABLE FROM XUZHOU FACTORY		
	Only reference numbers that have the text		
	"ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.		

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	--------	--------------------	-------------------------

LANE 1 AM-NORTH MANDATORY ATTACHMENTS

(MUST CHOOSE ONE FROM EACH CATEGORY)

LANE SELECTION

YOU MUST SELECT THIS REFERENCE WHEN ORDERING FROM THE PDC

0P-9001	LANE 1 ORDER	0	NC
---------	--------------------	---	----

PACKING

0P-0210	PACK, DOMESTIC TRUCK	0	NC
---------	----------------------------	---	----

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	--------	--------------------	-------------------------

LANE 1 AM-NORTH OPTIONAL ATTACHMENTS

May select additional options (not required).

BALLAST

L	488-6352	BALLAST, 33000 LB	0	\$20,750 NI
L	471-9323	BALLAST, 44,000 LB	26,817	\$44,220 NI
L	471-9326	BALLAST, 59,400 LB	33,935	\$55,990 NI

CERTIFICATES

P	0P-4990	CERTIFICATE OF ORIGIN	0	\$171
P	524-1948	COMPLIANCE FILM,ELECT-MAGNETIC	0	NC
		Film indicates EMC compliance. Required for Canada		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
OP-9003	LANE 3 ORDER	0	NC

POWERTRAIN**ENGINE**

L	587-1479	ENGINE, CAT C4.4	0	NC
		Meets U.S. EPA Tier 4 Final emission standards.		
		ONLY FOR USE WITH: 445-5711 CW34 PNEUMATIC COMPACTOR		

CHASSIS

L	445-5707	FRAME, STANDARD MACHINE	0	NC
---	----------	-----------------------------------	---	----

SERPENTINE BELT OR AIR CONDITIONING

L	355-1670	BELT, ENG	2	NC
		Serpentine belt for standard machine without air conditioning.		
L	364-6761	AIR CONDITIONER	55	\$2,335
		REQUIRES: 359-7793 CAB, ROPS w/HEATER & DEFROSTER and		
		443-8809 LINES, HEATER, HRC or		
		439-8561 LINES, HEATER, LRC		

OPERATOR ENVIRONMENT**OPERATOR STATION**

L	368-9296	BASE, OPERATOR STATION	0	NC
		Includes grab handrails and other operator station.		
		REQUIRES: 359-7792 ROPS or		
		364-6760 CANOPY, SUN		
L	359-7793	CAB, ROPS W/HEATER & DEFROSTER	2,315	\$28,300
		ROPS Cab enclosure w/heater.		
		REQUIRES: 443-8809 LINES, HEATER, HRC or		
		439-8561 LINES, HEATER, LRC		

SEAT SELECTION

L	364-6748	SEAT, STD VINYL	0	NC
		Vinyl suspension seat with fold-up arm rests, retractable seat belt, weight adj., and tilt back.		
L	364-6750	SEAT, HEATED VINYL	0	\$340
		Heated vinyl air suspension seat with high back, fold-up arm rests, retractable seat belt, adjustable fore and aft control, adjustable lumbar support, and tilt back.		
L	364-6749	SEAT, STD CLOTH	0	\$225
		Cloth suspension seat with fold-up arm rests, retractable seat belt, weight adj., and tilt back.		
		ONLY FOR USE WITH: 359-7793 CAB, ROPS w/HEATER & DEFROSTER		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

OPERATOR ENVIRONMENT (CONT.)**SEAT SELECTION (Cont.)**

L	364-6751	SEAT, HEATED CLOTH 0		\$397
		Heated cloth air suspension seat with high back, fold-up arm rests, retractable seat belt, adjustable fore and aft control, adjustable lumbar support, and tilt back.		
		ONLY FOR USE WITH: 359-7793 CAB, ROPS w/HEATER & DEFROSTER		

CONTROLS

L	367-3671	CONTROL, STD 0		NC
		Includes basic controls and vehicle wiring for base machine functions.		
L	457-1622	CONTROL, PREMIUM 0		\$1,440
			0	\$1,440 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes premier controls with upgraded vehicle wiring needed for most options.		

OPERATOR LANGUAGES

L	477-9990	LANGUAGES, OPTION 1 0		NC
		Includes standard languages (English, Spanish, French, German, Italian, Polish, Portuguese, Turkish, and Korean) for machine operation and control.		
L	461-0789	LANGUAGES, OPTION 2 0		NC
		Includes standard languages (English, Spanish, Portuguese, Turkish, Arabic, Russian, Korean, and Thai) for machine operation and control.		

TECHNOLOGY PRODUCTS**PRODUCT LINK COMMUNICATIONS**

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

L	454-5453	PRODUCT LINK, SATELLITE PL631 9		\$439
		Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		
L	454-5454	PRODUCT LINK, CELLULAR PL641 9		NC
		Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

TECHNOLOGY PRODUCTS (CONT.)***PRODUCT LINK INSTALLATION***

L	460-0781	INSTALLATION, CAB 18 Factory installation of PL on machines with open platform. ONLY FOR USE WITH: 359-7793 CAB, ROPS w/HEATER & DEFROSTER and 454-5453 PRODUCT LINK, SATELLITE PL631 or 454-5454 PRODUCT LINK, CELLULAR PL641		NC
L	460-0782	INSTALLATION, ROPS 18 Factory installation of PL on machine with open platform. REQUIRES: 359-7792 ROPS and ONLY FOR USE WITH: 368-9296 BASE, OPERATOR STATION and 454-5453 PRODUCT LINK, SATELLITE PL631 or 454-5454 PRODUCT LINK, CELLULAR PL641		NC

TIRES, RIMS, AND WHEELS

L	359-7789	TIRES, STD 0 Eight, 13/80-20, 18 ply, C-1 smooth tread, BIAS, Galaxy brand tires. Inflation pressures range 35-110 PSI.		\$-182
L	359-7788	TIRES, MICHELIN 0 Eight, 13/80-R20, 20 ply tires, C-1 smooth tread, Radial, Michelin brand tires. Inflation pressures range from 35-110 PSI.		\$9,560

FLUIDS***HYDRAULIC OIL***

L	364-8437	OIL, HYD, FACTORY FILLED 0		NC
L	364-8438	OIL, HYD, BIO, FACTORY FILLED 0 Bio degradable oil recommended for hydraulic system when environmental compliance is required or desired. Factor filled.		\$665

INSTRUCTIONS***DECAL PACKAGES***

P	364-6752	INSTRUCTIONS, NORTH AMERICAN 0 ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada).		NC
---	----------	--	--	----

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

FEATURE PACKAGES**BALLAST**

Machine ballast options that create various machine masses and wheel loads when the factory option is selected and dealer/customer is field installed.

L	471-9313	BALLAST, 30,800 LB	13,192 13,192	\$21,760 \$21,760 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed steel ballast added to base machine to achieve approximately 30,800 lbs or 14 metric tonne (mT) machine mass and approximately 3850 lbs or 1.75 mT per wheel. INCLUDES: Internal steel blocks, NO modular blocks. ONLY FOR USE WITH: 368-9296 BASE, OPERATOR STATION		
L	471-9314	BALLAST, 30,800 LB	11,307 11,307	\$18,670 \$18,670 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed steel ballast added to base machine to achieve approximately 30,800 lbs or 14 metric tonne (mT) machines mass and approximately 3850 lbs or 1.75 mT per wheel. INCLUDES: Internal steel blocks, NO modular blocks. ONLY FOR USE WITH: 359-7793 CAB, ROPS W/HEATER & DEFROSTER		
L	488-6352	BALLAST, 33000 LB	14,220 0	\$20,750 \$20,750 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed MODULAR steel ballast added to base machine to achieve approximately 33,000 lbs or 15 metric tonne (mT) machine mass and approximately 4100 lbs or 1.9 mT per wheel. INCLUDES: 8 modular blocks ONLY.		
L	471-3102	BALLAST, 35,000 LB	17,385 17,385	\$28,670 \$28,670 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed steel ballast added to base machine to achieve approximately 35,000 lbs or 16 metric tonne (mT) machine mass and approximately 4375 lbs or 2.0 mT per wheel. INCLUDES: Internal steel blocks, NO modular blocks. ONLY FOR USE WITH: 368-9296 BASE, OPERATOR STATION		
L	471-9318	BALLAST, 35,000 LB	14,656 14,656	\$24,190 \$24,190 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed steel ballast added to base machine to achieve approximately 35,000 lbs or 16 metric tonne (mT) machine mass and approximately 4375 lbs or 2.0 mT per wheel. INCLUDES: Internal steel blocks and 4 modular blocks in the front locations. ONLY FOR USE WITH: 359-7793 CAB, ROPS W/HEATER & DEFROSTER		
L	471-9320	BALLAST, 39,600 LB	19,892 19,892	\$32,810 \$32,810 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed steel ballast added to base machine to achieve approximately 39,600 lbs or 18 metric tonne (mT) machine mass and approximately 4950 lbs or 2.25 mT per wheel. INCLUDES: Internal steel blocks and 8 modular blocks. ONLY FOR USE WITH: 368-9296 BASE, OPERATOR STATION		

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

FEATURE PACKAGES (CONT.)***BALLAST (Cont.)***

L	471-9321	BALLAST, 39,600 LB	19,429 19,429	\$32,060 \$32,060 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed steel ballast added to base machine to achieve approximately 39,600 lbs or 18 metric tonne (mT) machine mass and approximately 4950 lbs or 2.25 mT per wheel. INCLUDES: Internal steel blocks and 4 modular blocks in the front locations. ONLY FOR USE WITH: 359-7793 CAB, ROPS W/HEATER & DEFROSTER		
L	471-9323	BALLAST, 44,000 LB	26,817 26,817	\$44,220 \$44,220 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed steel ballast added to base machine to achieve approximately 44,000 lbs or 20 metric tonne (mT) machine mass and approximately 5500 lbs or 2.5 mT per wheel. INCLUDES: Internal steel blocks and 4 modular blocks in the rear locations. ONLY FOR USE WITH: 368-9296 BASE, OPERATOR STATION		
L	471-9322	BALLAST, 44,000 LB	24,087 24,087	\$39,740 \$39,740 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed steel ballast added to base machine to achieve approximately 44,000 lbs or 20 metric tonne (mT) machine mass and approximately 5500 lbs or 2.5 mT per wheel. INCLUDES: Internal steel blocks and 8 modular blocks. ONLY FOR USE WITH: 359-7793 CAB, ROPS W/HEATER & DEFROSTER		
L	471-9324	BALLAST, 52,800 LB	27,855 27,855	\$45,960 \$45,960 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed steel ballast added to base machine to achieve approximately 52,800 lbs or 24 metric tonne (mT) machine mass and approximately 6600 lbs or 3.0 mT per wheel. After filling the ballast compartment with water, the total machine mass will be approximately 52,800 lbs or 24 mT. INCLUDES: Internal steel blocks and 8 modular blocks. ONLY FOR USE WITH: 368-9296 BASE, OPERATOR STATION		
L	471-9325	BALLAST, 52,800 LB	25,970 25,970	\$42,850 \$42,850 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed steel ballast added to base machine to achieve approximately 52,800 lbs or 24 metric tonne (mT) machine mass and approximately 6600 lbs or 3.0 mT per wheel. After filling the ballast compartment with water, the total machine mass will be approximately 52,800 lbs or 24 mT. INCLUDES: Internal steel blocks and 8 modular blocks. ONLY FOR USE WITH: 359-7793 CAB, ROPS W/HEATER & DEFROSTER		

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

FEATURE PACKAGES (CONT.)***BALLAST (Cont.)***

L	471-9326	BALLAST, 59,400 LB	33,935	\$55,990
			33,935	\$55,990 NI

ALSO AVAILABLE ON A MISCELLANEOUS ORDER

Factory installed steel ballast added to base machine to achieve approximately 59,400 lbs or 27 metric tonne (mT) machine mass and approximately 7425 lbs or 3.4 mT per wheel. After filling the ballast compartment with water, the total machine mass will be approximately 59,400 lbs or 27 mT.

INCLUDES: Internal steel blocks and 8 modular blocks.

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

ELECTRICAL

P	364-6757	LIGHTS, HALOGEN	7 0	\$1,145 \$1,145 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 2 front and 2 rear facing Halogen flood lamps mounted to the ROPS canopy. REQUIRES: 359-7792 ROPS or 364-6760 CANOPY, SUN or 364-6759 CANOPY, SUN, ROPS CANNOT BE USED WITH: 364-6755 LIGHTS, HIGH INTENSITY		
P	367-3674	LIGHTS, HALOGEN, CAB	11 0	\$1,145 \$1,145 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 2 front and 2 rear facing Halogen flood lamps mounted to the CAB. ONLY FOR USE WITH: 359-7793 CAB, ROPS w/HEATER & DEFROSTER CANNOT BE USED WITH: 367-3673 LIGHTS, HIGH INTENSITY, CAB		
P	364-6755	LIGHTS, HIGH INTENSITY	11 0	\$2,725 \$2,725 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 2 front and 2 rear facing HID flood lamps mounted to the ROPS canopy. REQUIRES: 359-7792 ROPS or 364-6760 CANOPY, SUN or 364-6759 CANOPY, SUN, ROPS CANNOT BE USED WITH: 364-6757 LIGHTS, HALOGEN		
P	367-3673	LIGHTS, HIGH INTENSITY, CAB	15 0	\$2,725 \$2,725 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 2 front and 2 rear facing HID flood lamps mounted to the CAB. ONLY FOR USE WITH: 359-7793 CAB, ROPS w/HEATER & DEFROSTER CANNOT BE USED WITH: 367-3674 LIGHTS, HALOGEN, CAB		

OPERATOR ENVIRONMENT

P	364-6763	MIRRORS, EXTERNAL.	33 0	\$449 \$449 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 4 external rear-view adjustable mirrors.		
P	351-3438	SUN SCREEN.	4	\$414
		Sun screen/visor inside cab. ONLY FOR USE WITH: 359-7793 CAB, ROPS w/HEATER & DEFROSTER		
P	359-7792	ROPS.	959 0	\$5,710 \$5,710 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes ROPS protective structure. Required for ADSD-N. CANNOT BE USED WITH: 359-7793 CAB, ROPS w/HEATER & DEFROSTER or 364-6760 CANOPY, SUN		
P	364-6759	CANOPY, SUN, ROPS	154 0	\$1,460 \$1,460 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Sun canopy added to ROPS machines. ONLY FOR USE WITH: 359-7792 ROPS		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

OPERATOR ENVIRONMENT (CONT.)

L	443-8809	LINES, HEATER, HRC 4		\$376
		Includes heater lines from the engine to cab required for heating.		
		ONLY FOR USE WITH: 359-7793 CAB, ROPS w/HEATER & DEFROSTER and 445-5711 CW34 PNEUMATIC COMPACTOR HRC		

TECHNOLOGY PRODUCTS**CAT COMPACTION CONTROL**

This is a factory designed and integrated pass count and temperature mapping system which requires additional components for the system to be functional.

For higher level accuracy consult your Dealer Technology Representative to order the necessary base station, data radio and option keys for RTK signal.

L	364-6767	SENSOR, MAT TEMP 11		\$3,670
			11	\$3,670 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes front and rear bumper mounted infrared, air purged temperature sensors.		
L	440-5393	MAPPING, GNSS 57		\$14,140
		Factory install of all components needed for mapping of temperature and machine pass count. Includes front and rear bumper mounted infrared, air purged temperature sensors, harnesses, system electronic controls including CB460 (17.8 cm/7.0 in) display and MS952 GPS receiver.		
		Includes: Sensor, Mat Temperature		

OTHER ATTACHMENTS

L	276-6019	BELT, SEAT, 3" SUSPENSION 0		\$144
P	388-7112	COCOA MAT W/SCRAPER 44		\$1,880
			0	\$1,880 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Additional tire scraper complete with cocoa mat for water retention.		
L	359-7796	INFLATION GROUP 772		\$12,420
		On machine air compressor and system controls for automatic tire inflation, also known as air on the run system for tire inflation. Contains on machine air compressor, electronic controls and air lines to all tires. With operator input, this system will increase, decrease and equalize the internal tire air pressure so uniform compaction can take place. Optimal tire pressure is dependent on machine weight.		
		ONLY FOR USE WITH: 457-1622 CONTROL, PREMIUM		
L	507-0411	INFLATION GROUP, MANUAL 0		\$4,960
			0	\$4,960 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Manual tire air inflation system. Contains central fill port, system pressure gauge and air lines to all tires. This system will equalize the air pressure within all tires so uniform compaction can take place. Optimal tire pressure is dependent on machine weight. Tire inflation takes place when an external air supply hose is connected to the tire fill port.		
		CANNOT BE USED WITH: 359-7796 INFLATION GROUP		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
OTHER ATTACHMENTS (CONT.)				
P	478-4819	PROTECTION PKG, INFLATION	11 11	\$650 \$650 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Protection for inflation air lines on the wheels ONLY FOR USE WITH: 359-7796 INFLATION GROUP or 507-0411 INFLATION GROUP, MANUAL		
P	471-3180	THERMAL, TIRE APRON	403 403	\$4,900 \$4,900 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Tire aprons provide wind protection to tires to retain heat.		
L	359-7790	SPRAY, EMULSION	55 0	\$2,110 \$2,110 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides emulsion tank, electric pump, and spray nozzles for each tire AND the standard water spray system. REQUIRES: 456-0084 CONTROL, OPTION ONLY FOR USE WITH: 457-1622 CONTROL, PREMIUM		
L	364-6772	EDGE CUTTER.	518 0	\$13,540 \$13,540 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Devise for cutting and compacting material. REQUIRES: 456-0084 CONTROL, OPTION ONLY FOR USE WITH: 457-1622 CONTROL, PREMIUM		
P	361-7380	SPARE, TIRE & WHEEL.	300	\$5,470 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes: 13/80-R20, 20ply tire & rim, Michelin brand. FOR USE WITH MICHELIN TIRES		
P	361-7381	SPARE, TIRE & WHEEL.	300	\$2,535 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes: 13/80-R20, 20ply tire & rim FOR USE WITH STD TIRES		
L	456-0084	CONTROL, OPTION	4 0	\$545 \$545 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes electronic control for full functions of option. FOR USE WITH: EDGE CUTTER and/or SPRAY, EMULSION Maximum of 1 per machine. ONLY FOR USE WITH: 364-6772 EDGE CUTTER 359-7990 SPRAY, EMULSION		

DOCUMENTATION**CERTIFICATES**

P	0P-4990	CERTIFICATE OF ORIGIN.	0	\$171
P	354-8706	YEAR OF MANUFACTURE PLATE	0	NC
		Plate attached to PIN plate showing year of Final Plant Shipping date. Required for all machines shipping to Brazil. CANNOT BE USED WITH: 364-6764 CE CERTIFICATION		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

PACKING**EXPORT PACKING**

OP-4507	ROLL ON-ROLL OFF	0		\$605 NET
OP-3943	PACKING, CONTAINER 1 machine per 40' High Cube container. Loaded at plant. Machine systems such as engine exhaust and options ROPS; Canopy; Sun, ROPS; Canopy, Sun; Thermal, Tire Apron and Edge Cutter will not be factory installed and will require installation at the dealer's location. Maximum weight is 26.5 mT for all regions. FOR USE WITH: BASE, OPERATOR STATION; CANOPY, SUN, ROPS or CANOPY, SUN CANNOT BE USED WITH: 359-7793 CAB, ROPS W/HEATER & DEFROSTER or BALLAST, 20M TON; BALLAST, 24M TON BALLAST, 27M TON	0		\$655 NET
OP-3762	PACKING, CONTAINER 2 machines per 40' High Cube container. Loaded at plant. Use of any ballast options with this selection would exceed on highway weight limitations. FOR USE WITH: BASE, OPERATOR STATION; ROPS; CANOPY, SUN, ROPS or CANOPY, SUN CANNOT BE USED WITH: 359-7793 CAB, ROPS W/HEATER & DEFROSTER or 364-6772 EDGE CUTTER or 471-3180 THERMAL, TIRE APRON or BALLAST	0		\$655 NET
OP-6706	BUNDLE EXPORT PACKING This OP should be ordered for all miscellaneous orders.	0		NC
OP-0210	PACK, DOMESTIC TRUCK	0		NC