

**CP68B VIBRATORY COMPACTOR
MINNEAPOLIS, MN, USA (SAP)**Ship Weight
lbsLIST PRICE
AT DEALER

Standard Equipment:

POWERTRAIN

CAT C4.4 inline four cylinder, turbo-charged diesel engine (117 kW / 156 HP) with glow-plyd heater
 Dual element air cleaner
 Fuel filter/water separator/electronic priming pump and water indicator
 Three-speed throttle switch including ECOMODE
 Dual propel pumps - 1 for drum and 1 for tires
 Dual braking systems (service & parking, drum only)
 Two-speed hydrostatic transmission
 Limited slip differential

ELECTRICAL

24-volt starting and charging system alternator
 (2) Maintenance free batteries - 750 CCA
 Halogen working lights - canopy mounted (2 front-facing and 2 rear-facing)
 Backup alarm and forward warning horn
 Product link ready
 Beacon ready

OPERATOR ENVIRONMENT

Cab, ROPS/FOPS
 Four heavy-duty isolation mounts
 Platform handrails/guardrails
 Power steering
 Adjustable tilt-steering column
 Adjustable, rotating suspension seat
 Retractable seat belt
 Adjustable, padded arm rest for propel lever operation
 On-board display with audible warning alarm and interface for:
 -hydraulic oil temperature gauge,
 -engine oil pressure gauge,
 -engine coolant temperature gauge
 -alternator charge,
 -fuel level gauge,
 -service hour meter,
 -engine RPM
 -ground speed, vibe speed
 -fuel rate gauge
 -engine load gauge
 -basic compaction measurement
 Lockable, vandalism guard for on-board display
 12-volt power point

COOLING

Premixed 50% concentration of extended life coolant with freeze protection to -37C (-35F)

DRUMS

Padfoot drum
 2134 mm (84") wide x 1534 mm (60.4") diameter
 Dual amplitude with single frequency
 Dual, pod-style eccentric weight housings
 Adjustable front and rear steel scraper

OTHER STANDARD EQUIPMENT

Locking composite engine enclosure
 Sealed-for-life hitch bearings
 Sight gauges:
 -coolant level
 -hydraulic oil level
 Hydraulic tank locking cap
 Articulated frame with safety lock
 Transport tie-down and lift points
 Fuel tank with lockable cap
 Quick connect hydraulic pressure test ports
 SOS ports:
 -engine
 -hydraulic
 -coolant
 Universal bumper

CP68B VIBRATORY COMPACTOR
MINNEAPOLIS, MN, USA (SAP)

Ship Weight
lbs

LIST PRICE
AT DEALER

**Lane 2 is reserved for the Base Order Management Program.
Please use Lane 2 when placing orders that are part of the
Base Order Management Program.**

433-1617	CP68B VIBRATORY COMPACTOR 26,985	\$231,160
	LANE 2 - AVAILABLE FROM MINNEAPOLIS FACTORY	
	LANE 3 - AVAILABLE FROM MINNEAPOLIS FACTORY	
OP-2578	CP68B MISC MATL 0	NC
	AVAILABLE FROM MINNEAPOLIS FACTORY	
	Only reference numbers that have the text	
	"ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.	

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

LANE SELECTION

0P-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
0P-9003	LANE 3 ORDER	0	NC

POWERTRAIN**ENGINE**

L	420-9160	ENGINE, TIER 4F/STAGE 4	0	NC
		U.S. EPA Tier 4 Final/EU Stage IV equivalent engine.		

ENCLOSURES

L	479-9014	SCREEN, STANDARD	7	NC
		Fixed (not openable) screen at rear, right side of the engine compartment.		
L	479-9015	FUEL SYSTEM, DOOR	23	\$360
		Hinged and CAT key lockable door to access fuel fill without opening enclosure.		

OPERATOR ENVIRONMENT**OPERATOR STATIONS**

L	435-8038	CAB, ROPS/FOPS WITH HEATER	1,620	\$16,830
		FOR USE WITH LANE 3 ONLY		
		Two front-facing and two rear-facing working lights, external rear-view mirrors, heater & defroster, and wet-arm wipers/washers (front and rear). Cab is Radio Ready, including hardware, wiring, voltage converter and 12-volt power point. Wiring only - Radio and Speakers not included.		
L	435-8036	CAB, ROPS/FOPS WITH A/C	1,700	\$22,470
		Two front-facing and two rear-facing working lights, external rear-view mirrors, air conditioner, heater & defroster, and wet-arm wipers/washers (front and rear). Cab is Radio Ready, including hardware, wiring, voltage converter and 12-volt power point. Wiring only - Radio and Speakers not included.		

SEATS

L	356-1227	SEAT, CLOTH	150	\$309
		Standard rotating cloth covered suspension seat.		
L	356-1229	SEAT, CLOTH, DELUXE	158	\$535
		Deluxe cloth seat with head rest, air suspension and additional adjustments.		

SEAT BELTS

L	382-9003	SEAT BELT, 2"	2	NC
L	387-1801	SEAT BELT, 3"	2	\$144

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

OPERATOR ENVIRONMENT (CONT.)**OPERATOR LANGUAGES**

L	477-9990	LANGUAGES, OPTION 1 0		NC
		Includes standard languages (English, Spanish, French, German Italian, Polish, Portuguese, Turkish, and Korean) for machine operation and control.		

TECHNOLOGY PRODUCTS**PRODUCT LINK**

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the cost of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

L	454-5453	PRODUCT LINK, SATELLITE PL631 9		\$439
		Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		
L	454-5454	PRODUCT LINK, CELLULAR PL641 9		NC
		Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		

PRODUCT LINK INSTALLATION

L	454-0249	INSTALLATION, CAB 8		NC
		Factory installation of PL on machines with cab.		

CAT COMPACTION CONTROL

Compaction Monitoring sensors to detect changes in soil stiffness which is an excellent indicator of load bearing strength and provides the operator with real time compaction information on the machine display.

L	444-5932	NO COMPACTION SENSOR 0		NC
		No Sensors.		
L	441-6675	SENSOR, DRIVE POWER 5		\$3,860
		Proprietary Caterpillar technology that directly measures soil stiffness via material deflection (rolling resistance).		

TIRES, RIMS, AND WHEELS

L	216-0591	TIRE, TRACTION 935		\$8,300
		23.1 x 26 12 ply traction (lug tread) tires and rims with liquid ballast.		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

DRUMS**VIBRATORY SYSTEMS**

L	355-3547	FREQUENCY, FIXED 0		NC
		Single 31.9 Hz (1914 vpm) frequency with high and low amplitude.		
L	367-4216	FREQUENCY, VARIABLE 0		\$2,430
		Frequency dial that electronically controls the displacement of the vibratory pump. Frequency range from 23.3-31.9 Hz (1400-1914 vpm).		

PAD SHAPE

L	463-2313	PAD, ROUND 0		NC
		Involute-style pad that works well on 10-18" lifts. Each pad is 5" tall with a surface area of 13.9 square inches.		
L	463-2315	PAD, SQUARE 70		NC
		Square-style pad that works well on lifts less than 10". Each pad is 3.9" tall with a surface area of 21.7 square inches.		

LEVELING BLADE

L	357-6261	NO BLADE 0		NC
L	438-2274	BLADE, LEVELING 1,438		\$14,720
		Factory installed leveling blade and controls.		

FLUIDS**HYDRUALIC OIL**

L	362-4940	OIL, HYDR, FACTORY FILLED 0		NC
		Cat standard hydraulic oil.		
L	362-4941	OIL, HYD, BIO, FACTORY FILLED 0		\$3,270
		FOR USE WITH LANE 3 ONLY		
		This Hydraulic Environmental Ester Synthetic oil is recommended for hydraulic system when environmental compliance is required or desired. Factory filled.		

INSTRUCTIONS

L	437-9886	INSTRUCTIONS, NA CAB 0		NC
		ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada).		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

ELECTRICAL

P	355-3059	LIGHTING, WARNING	5 0	\$427 \$427 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
P	355-3056	LIGHTS, UPGRADED	3 0	\$227 \$227 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		4 additional lights for increased nighttime visibility.		
P	373-4813	MODULE, RECORDING, STD FREQ	26 0	\$6,400 \$6,400 NI
		FOR USE WITH LANE 3 ONLY		
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Factory or field installed components for		
		fixed frequency recording module.		
		ONLY FOR USE WITH: 355-3547 FREQUENCY, FIXED		
P	355-3064	MODULE, RECORDING, VARIABLE	0 31	\$6,400 \$6,400 NI
		FOR USE WITH LANE 3 ONLY		
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Factory or field installed components for		
		variable frequency recording module.		
		ONLY FOR USE WITH: 367-4216 FREQUENCY, VARIABLE		

OPERATOR ENVIRONMENT

P	107-4643	MIRRORS, REARVIEW, INTERNAL	10 0	\$211 \$211 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes two rear-view mirrors mount inside of the cab.		
P	204-4390	SUN SCREEN	2 2	\$332 \$332 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Provides pull-down sunscreen for rear window, reduces heat and glare.		
P	107-4641	SUN VISOR, FRONT	2 0	\$78 \$78 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Tip-down tinted sun visor for front window, reduces heat and glare.		

TECHNOLOGY PRODUCTS**CAT COMPACTION CONTROL**

This is a factory designed and integrated SBAS accuracy level pass count and MDP mapping system which requires no off-board infrastructure. For a higher accuracy solution consult your Dealer Technology Representative to order necessary base station, data radio and higher accuracy option key for an RTK solution.

L	375-1607	MAPPING, GNSS	45	\$10,280
		CB460 Display (17.8 cm/7.0 in), MS952 antenna/receiver.		
		ONLY FOR USE WITH: 441-6675 SENSOR, DRIVE POWER		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

TECHNOLOGY PRODUCTS (CONT.)***MACHINE TO MACHINE COMMUNICATION***

Machine to machine communication is integrated hardware consisting of an electronic control module, radio and antennas with connecting wiring that enables machines to communicate key compaction data via local wireless and/or cellular data networks.

Contact your local SITECH dealer and wireless data carrier for additional support and cellular data packages.

L	569-8583	MACHINE CONNECTIVITY, SNM941 0		\$3,560
		SIM card enabled CDMA or GSM network with built in WIFI.		
		ONLY FOR USE WITH: 375-1607 MAPPING, GNSS		

OTHER ATTACHMENTS***GUARDS***

P	355-2660	GUARD, TRANSMISSION 44		\$1,115
			0	\$1,020 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Provides protection for the rear axle, hydraulic drive motor and hose fittings.		

FACTORY SOURCED KITS

P	437-9831	BLADE, LEVELING, FLD 1,170		\$14,720 NI
		FOR USE WITH LANE 3 ONLY		
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Kit for dealer installed components for leveling blade.		
P	483-5926	PRINTER PORT WIRING KIT, CAB 0		\$400 NI
		FOR USE WITH LANE 3 ONLY		
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes wiring kit only for printer (dealer installed) using on a machine with a mapping system.		
		To be used with Cab, ROPS/FOPS machine.		

DOCUMENTATION***CERTIFICATES***

P	0P-1870	CERTIFICATE OF ORIGIN 0		NC
---	---------	-----------------------------------	--	----

PACKING

	0P-0210	PACK, DOMESTIC TRUCK 0		NC
	0P-3651	PACKING, MISC MATERIAL 0		NC
		No charge for packing. Applicable freight charges may apply.		