

CCS9 VIBRATORY COMPACTOR
MINNEAPOLIS, MN, USA (SAP)

 Ship Weight
 lbs

 LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

CAT C4.4 inline four cylinder, turbo-charged diesel engine with glow-plug heater
 Dual element air cleaner
 Fuel filter/water separator/manual priming pump and water indicator
 Three-speed throttle switch including ECOMODE
 Dual propel pumps - 1 for drum and 1 for tires
 Dual braking systems (service & parking, for both drum and axle)
 Two-speed hydrostatic transmission
 Limited slip differential

ELECTRICAL

12-volt starting and charging system alternator
 Maintenance free battery - 750 CCA
 Halogen working lights - canopy mounted (2 front-facing and 2 rear-facing)
 Backup alarm and forward warning horn
 Product link ready
 Beacon ready

OPERATOR ENVIRONMENT

ROPS/FOPS platform
 Four heavy-duty isolation mounts
 Platform handrails/guardrails
 Power steering
 Adjustable tilt-steering column
 Adjustable suspension seat
 Retractable seat belt
 Adjustable, padded arm rest for propel lever operation
 On-board display with audible warning alarm and interface for:
 - hydraulic oil temperature gauge
 - engine oil pressure gauge
 - engine coolant temperature gauge
 - alternator charge
 - fuel level gauge
 - service hour meter
 Lockable, vandalism guard for on-board display
 12-volt Universal and USB power point

COOLING

Premixed 50% concentration of extended life coolant with freeze protection to -37C (-35F)

DRUMS

Smooth drum

2134 mm (84") wide x 1534 mm (60.4") diameter
 5 amplitude system with single frequency
 Pod-style eccentric weight housing
 Front and rear self adjusting drum scraper
 Self adjusting tire scraper for rear wheels

OTHER STANDARD EQUIPMENT

Locking composite engine enclosure
 Sealed-for-life hitch bearings
 Sight gauges:
 -coolant level
 -hydraulic oil level
 Hydraulic tank locking cap
 Articulated frame with safety lock
 Transport tie-down and lift points
 Fuel tank with lockable cap
 Quick connect hydraulic pressure test ports
 SOS ports:
 -engine
 -hydraulic
 -coolant

CCS9 VIBRATORY COMPACTOR
MINNEAPOLIS, MN, USA (SAP)

Ship Weight
lbs

LIST PRICE
AT DEALER

**Lane 2 is reserved for the Base Order Management Program.
Please use Lane 2 when placing orders that are part of the
Base Order Management program.**

496-0189	CCS9 VIBRATORY COMPACTOR 0	\$207,880
	LANE 2 - AVAILABLE FROM MINNEAPOLIS FACTORY	
	LANE 3 - AVAILABLE FROM MINNEAPOLIS FACTORY	

OP-4143	CCS9 MISC MATL 0	NC
	AVAILABLE FROM MINNEAPOLIS FACTORY	
	Only reference numbers that have the text	
	"ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.	

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
OP-9003	LANE 3 ORDER	0	NC

POWERTRAIN**ENGINE**

L	420-9150	ENGINE, TIER 4F/STAGE 4	0	NC
		U.S. EPA Tier 4 Final/EU Stage IV equivalent engine.		

ENCLOSURES

L	479-9014	SCREEN, STANDARD	7	NC
		Fixed (not openable) screen at rear, right side of the engine compartment.		
L	479-9015	FUEL SYSTEM, DOOR	23	\$360
		Hinged and CAT key lockable door to access fuel fill without opening enclosure.		

OPERATOR ENVIRONMENT**OPERATOR STATIONS**

L	435-8035	PLATFORM, ROPS/FOPS	1,262	NC
		Open platform with handrails, ROPS/FOPS canopy and working lights.		
L	435-8036	CAB, ROPS/FOPS WITH A/C	1,700	\$22,470
		Two front-facing and two rear-facing working lights, external rear-view mirrors, air conditioner, heater & defroster, and wet-arm wipers/washers (front and rear). Cab is Radio Ready, including hardware, wiring, voltage converter and 12-volt power point. Radio NOT supplied.		

SEATS

L	356-1226	SEAT, VINYL	150	NC
		Standard rotating vinyl covered suspension seat.		
L	356-1227	SEAT, CLOTH	150	\$309
		Standard rotating cloth covered suspension seat.		
		ONLY FOR USE WITH: 435-8036 CAB, ROPS/FOPS WITH A/C		
L	356-1229	SEAT, CLOTH, DELUXE	158	\$535
		Deluxe rotating cloth seat with head rest, air suspension and additional adjustments.		
		ONLY FOR USE WITH: 435-8036 CAB, ROPS/FOPS WITH A/C		

SEATS BELTS

L	382-9003	SEAT BELT, 2"	2	NC
L	387-1801	SEAT BELT, 3"	2	\$144

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

OPERATOR ENVIRONMENT (CONT.)**OPERATOR LANGUAGES**

L	477-9990	LANGUAGES, OPTION 1 0		NC
		Includes standard languages (English, Spanish, French, German, Italian, Polish, Portuguese, Turkish, and Korean) for machine operation and control.		

TECHNOLOGY PRODUCTS**PRODUCT LINK COMMUNICATIONS**

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

L	454-5453	PRODUCT LINK, SATELLITE PL631 9		\$439
		Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		
L	454-5454	PRODUCT LINK, CELLULAR PL641 9		NC
		Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmissions and larger volumes of data.		

PRODUCT LINK INSTALLATION

L	454-0250	INSTALLATION, ROPS/FOPS 8		NC
		Factory installation of PL on machine with ROPS/FOPS canopy. ONLY FOR USE WITH: 435-8035 PLATFORM, ROPS/FOPS 454-5453 PRODUCT LINK, SATELLITE PL631 or 454-5454 PRODUCT LINK, CELLULAR PL641		
L	454-0249	INSTALLATION, CAB 8		NC
		Factory installation of PL on machines with cab. ONLY FOR USE WITH: 435-8036 CAB, ROPS/FOPS WITH A/C 454-5453 PRODUCT LINK, SATELLITE PL631 or 454-5454 PRODUCT LINK, CELLULAR PL641		

TIRES, RIMS, AND WHEELS

L	506-4476	TIRES, 16.9-30, SMOOTH 6 PL 0		\$1,895
		6-ply smooth asphalt compaction tires and rims.		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

FLUIDS**HYDRAULIC OIL**

L	362-4940	OIL, HYDR, FACTORY FILLED 0		NC
		Cat standard hydraulic oil.		
L	362-4941	OIL, HYD, BIO, FACTORY FILLED 0		\$3,270
		FOR USE WITH LANE 3 ONLY		
		This Hydraulic Environmental Ester Synthetic oil is recommended for hydraulic system when environmental compliance is required or desired. Factory filled.		

INSTRUCTIONS

P	437-9888	INSTRUCTIONS, NA PLATFORM 0		NC
		ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada). ONLY FOR USE WITH: 435-8035 PLATFORM, ROPS/FOPS		
P	437-9886	INSTRUCTIONS, NA CAB 0		NC
		ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada). ONLY FOR USE WITH: 435-8036 CAB, ROPS/FOPS WITH A/C		

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
ELECTRICAL				
P	355-3059	LIGHTING, WARNING 0		\$427 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
P	355-3056	LIGHTS, UPGRADED 3		\$227
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER	0	\$227 NI
		4 additional lights for increased nighttime visibility		
P	107-4643	MIRRORS, REARVIEW, INTERNAL 10		\$211
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER	0	\$211 NI
		Includes two rear-view mirrors mounted inside the cab.		
		ONLY FOR USE WITH: 435-8036 CAB, ROPS/FOPS WITH A/C		
P	354-5413	MIRRORS, REARVIEW, EXTERNAL 10		\$311
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER	0	\$311 NI
		Includes two externally mounted rear-view mirrors.		
		ONLY FOR USE WITH: 435-8035 PLATFORM, ROPS/FOPS		
P	204-4390	SUN SCREEN 2		\$332
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER	2	\$332 NI
		Pull-down sunscreen for rear window, reduces heat and glare.		
		ONLY FOR USE WITH: 435-8036 CAB, ROPS/FOPS WITH A/C		
P	107-4641	SUN VISOR, FRONT 2		\$78
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER	0	\$78 NI
		Tip-down tinted sun visor for front window, reduces heat and glare.		
		ONLY FOR USE WITH: 435-8036 CAB, ROPS/FOPS WITH A/C		

TECHNOLOGY PRODUCTS**CAT COMPACTION CONTROL**

Compaction Monitoring sensors to detect changes in soil stiffness which is an excellent indicator of load bearing strength and provides the operator with real time compaction information on the machine.

P	502-6856	SENSORS, MAT TEMPERATURE 0		\$3,765
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER	0	\$3,765 NI
		Includes a single front bumper mounted infrared, air purged temperature sensor.		

OTHER ATTACHMENTS

P	492-0186	MATS, COCOA 0		\$1,405
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER	0	\$1,405 NI
		Cocoa mat for the drum.		
		CANNOT BE USED WITH: 492-0080 MATS, WATER DISTRIBUTION		
P	492-0080	MATS, WATER DISTRIBUTION 0		\$1,795
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER	0	\$1,795 NI
		Water distribution mat for the drum.		
		CANNOT BE USED WITH: 492-0186 MATS, COCOA		

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

OTHER ATTACHMENTS (CONT.)

P	492-0184	MATS, COCOA, TIRES	0	\$995
			0	\$995 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Cocoa mats for the rear tires.		

DOCUMENTATION***CERTIFICATES***

P	0P-1870	CERTIFICATE OF ORIGIN.	0	NC
---	---------	-----------------------------	---	----

PACKING

	0P-0210	PACK, DOMESTIC TRUCK	0	NC
		United States and Canadian Dealers only.		
	0P-3651	PACKING, MISC MATERIAL	0	NC
		No charge for packing. Applicable freight charges may apply.		