

**CB13 VIBRATORY ASPHALT COMPACTOR
MINNEAPOLIS, MN, USA (SAP)**Ship Weight
lbsLIST PRICE
AT DEALER

Standard Equipment:

POWERTRAIN

CAT C4.4, inline four-cylinder, turbo-charged diesel engine (106 kW / 142 HP)
Cyclonic air cleaner
Water separator
Ultra clean fuel filter with integrated electric priming pump
ECO mode throttle system
Dual braking systems (service & parking)
Two-speed hydrostatic transmission

ELECTRICAL

12-volt electric starting
120 ampere alternator
Maintenance free battery - 1000 CCA
Halogen working lights - bumper mounted (2 front-facing and 2 rear-facing)
Backup alarm and forward warning horn
Cat engine and vehicle ECM's - ET compatible
Product link ready

OPERATOR ENVIRONMENT

Isolated ROPS/FOPS structure
Platform handrails / guardrails
Four heavy-duty isolation mounts
Power steering
Adjustable, suspension, seat
50 mm (2") wide retractable seat belt
Adjustable, steering console and control/display console
Indicator light package with audible warning alarm for:
-hydraulic oil pressure
-hydraulic oil temperature
-engine oil pressure
-engine coolant temperature
-glow plugs
-service fault indicator
Fuel level gauge
Water level gauge
Service hour meter
Lockable, vandalism guard for instrument panel
Adjustable tilt-steering column / instrument panel
Sliding, rotating seat
Automatic speed control
Auto-vibe with adjustable on/off control
Vibe tachometer
Speedometer

DRUMS

Smooth solid drum
2000 mm (79") wide x 1300 mm (51") diameter
Two amplitudes with two vibe frequencies
Front and rear self adjusting scraper blades
Pod-style eccentric weight housing

FLUIDS

Premixed 50% concentration of extended life coolant with freeze protection to -37C (-35F)

OTHER STANDARD EQUIPMENT

Locking engine enclosure
Sealed for life hitch bearings
Sight gauges:
-hydraulic tank level
-air restriction indicator
Cap lock for hydraulic tank
Articulated frame with safety lock
Transport tie-down and lift points
208 L (55 gal) fuel tank capacity
835 L (220 gal) water tank capacity
Quick connect hydraulic pressure test ports
SOS ports:
-engine oil
Dual water spray bars
Dual water pumps

CB13 VIBRATORY ASPHALT COMPACTOR
MINNEAPOLIS, MN, USA (SAP)

Ship Weight
lbs

LIST PRICE
AT DEALER

**Lane 2 is reserved for the Base Order Management Program.
Please use Lane 2 when placing orders that are part of the
Base Order Management Program.**

559-5255	CB13 01A VIB COMP DCA1 0	\$206,400
	LANE 1 - AVAILABLE FROM MINNEAPOLIS PDC	

INCLUDES:

522-4606 CB13 01A VIBRATORY COMPACTOR
434-0760 ENGINE, TIER 4F, STAGE 4
355-1670 BELT, ENG
417-5262 HITCH, STANDARD
539-2602 DRUM, SOLID
424-1371 SYSTEM, VERSA-VIBE
501-6572 LIGHTS, WORKING
532-8806 PLATFORM, ROPS/FOPS
356-0924 ROTATION, FULL
454-3055 CONTROL, PREMIUM
489-6273 STEERING WHEEL, FIXED
527-8200 LANGUAGES, OPTION 1
355-3084 SEAT, HEATED VINYL
460-8862 PRODUCT LINK, CELLULAR PL641
445-8758 NOZZLES, PREMIUM
433-0408 OIL, HYD, FACTORY FILLED
434-5133 LIGHT, ROTATING BEACON
530-3115 LIGHTS, LED, ROPS
419-5625 SENSOR, MAT TEMPERATURE
433-7143 FREEZE PROTECTION, ROPS/FOPS

NOTE: Please refer to the Lane 1 section to complete your order.

522-4606	CB13 01A VIBRATORY COMPACTOR. 0	\$189,460
	LANE 2 - AVAILABLE FROM MINNEAPOLIS FACTORY	
	LANE 3 - AVAILABLE FROM MINNEAPOLIS FACTORY	

0P-4693	CB13 MISC MATERIAL. 0	NC
	AVAILABLE FROM MINNEAPOLIS FACTORY	
	Only reference numbers that have the text	
	"ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.	

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	--------	--------------------	-------------------------

LANE 1 AM-NORTH MANDATORY ATTACHMENTS***LANE SELECTION***

YOU MUST SELECT THIS REFERENCE WHEN ORDERING FROM PDC

0P-9001	LANE 1 ORDER	0	NC
---------	------------------------	---	----

INSTRUCTIONS - PICTOGRAPH FILMS

L	522-4617	INSTRUCTIONS, NORTH AMERICAN	0	NC
---	----------	--	---	----

L	522-4618	INSTRUCTIONS, INTERNATIONAL	0	NC
---	----------	---------------------------------------	---	----

PACKING

0P-0210	PACK, DOMESTIC TRUCK	0	NC
---------	--------------------------------	---	----

LANE 1 AM-NORTH OPTIONAL ATTACHMENTS***CERTIFICATES***

0P-1870	CERTIFICATE OF ORIGIN	0	NC
---------	---------------------------------	---	----

P	524-1948	COMPLIANCE FILM,ELECT-MAGNETIC	0	NC
		Film indicates EMC compliance.		
		Required for Canada		
		AVAILABLE FOR: CANADA		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

LANE SELECTION

0P-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
0P-9003	LANE 3 ORDER	0	NC

POWERTRAIN**ENGINE**

L	434-0760	ENGINE, TIER 4F, STAGE 4	1,407	NC
---	----------	------------------------------------	-------	----

BELT

L	355-1670	BELT, ENG	2	NC
		Serpentine belt for standard machine.		
L	355-1671	BELT, ENG, A/C	2	NC
		Serpentine belt for machines equipped with air conditioning.		
		REQUIRES: 435-4830 AIR CONDITIONER		

HITCH

L	417-5262	HITCH, STANDARD	937	NC
		Standard hitch without offset		
L	417-5263	HITCH, OFFSET	1,047	\$3,685
		Switch control on propel lever gives +/- 152 mm (6") of drum offset.		
		REQUIRES: 454-3055 CONTROL, PREMIUM		

DRUM TYPE

L	539-2602	DRUM, SOLID	0	NC
		2000 mm (79") solid drum.		
L	524-7906	DRUM, SOLID W/OSCILLATION STD	0	NC
		2000 mm (79") solid drums, front drum with conventional vibration and rear drum with oscillatory vibration. Both drum shells are comprised of standard material.		
L	524-7889	DRUM, SOLID W/OSCILLATION HD	0	\$10,550
		2000 mm (79") solid drums, front drum with conventional vibration consists of standard material whereas the rear drum, with oscillatory vibration, is comprised of a hardened material for better wear potential.		

HYDRAULICS**VIBRATORY HYDRAULICS**

L	424-0156	SYSTEM, 5 AMPLITUDE	1,109	NC
		Frequency of 42 Hz (2520 vpm).		
		Drum mounted handwheel with 5 manual settings for vibratory amplitude control.		
		Includes auto reversing weights.		
		ONLY FOR USE WITH: 539-2602 DRUM, SOLID		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

HYDRAULICS (CONT.)***VIBRATORY HYDRAULICS (Cont.)***

L	424-1371	SYSTEM, VERSA-VIBE 1,074 Frequency of 42 Hz (2520 vpm) and 63.3 Hz (3800 vpm). Console switch control for amplitude / frequency setting. Handwheel at drum to control amplitude. ONLY FOR USE WITH: 539-2602 DRUM, SOLID		\$6,400
L	524-7895	SYSTEM, 5 AMPLITUDE W/OSC 0 Frequency of 42 Hz (2520 vpm) conventional vibration on the front drum with oscillatory vibration at 40 Hz (2400 vpm) on the rear drum. Handwheel with 5 manual settings for amplitude control on front drum only. Includes auto reversing weights. 5 amplitude front drum with oscillatory rear drum. ONLY FOR USE WITH: 524-7889 DRUM, SOLID W/OSCILLATION HD 524-7906 DRUM, SOLID W/OSCILLATION STD		\$4,005
L	524-7896	SYSTEM, VERSA-VIBE W/OSC 0 Frequency of 42 Hz (2520 vpm) and 63.3 Hz (3800 vpm) conventional vibration on the front drum with oscillatory vibration at 40 Hz (2400 vpm) on the rear drum. Console switch control for amplitude / frequency setting and handwheel with manual high and low settings for amplitude control on front drum only. Versa-Vibe front drum with oscillatory rear drum. ONLY FOR USE WITH: 524-7889 DRUM, SOLID W/OSCILLATION HD 524-7906 DRUM, SOLID W/OSCILLATION STD		\$10,550

ELECTRICAL***LIGHTING***

L	501-6572	LIGHTS, WORKING 0 Includes 2 front and 2 rear facing clear lights located in the bumpers.		NC
L	501-6573	LIGHTS, ROADING AND WORKING 0 Includes 2 front high beams headlights, 2 rear facing flood lights, front and rear turn signals, and front and rear indicator/parking lights. All lights are attached to the bumpers.		\$850

OPERATOR ENVIRONMENT***OPERATOR STATION***

L	532-8806	PLATFORM, ROPS/FOPS 0 Includes grab handrails and foundation for the sliding and rotating operator station. Lockable personal storage container and compartments for personal item retention and 12 volt power point.		NC
L	532-8807	CAB, ROPS/FOPS 0 Cab operator's environment with heater & defroster, and wet-arm wiper/washers (front and rear). Cab is radio ready, including hardware, wiring and 12-volt power point.		\$12,820

OPERATOR STATION MOVEMENT

L	343-6115	ROTATION, HALF 40 Includes operator station controls, LCD display and station slide and 180 deg rotate levers.		NC
---	----------	---	--	----

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

OPERATOR ENVIRONMENT (CONT.)**OPERATOR STATION MOVEMENT (Cont.)**

L	356-0924	ROTATION, FULL 75 Includes operator station controls, LCD display and station slide and 359 deg rotate levers.		\$2,070
---	----------	--	--	---------

PROPEL LEVER

L	454-3054	CONTROL, STD 2 Includes vehicle wiring and basic 2 button propel lever for propel control, vibratory on/off selection, and water spray functions.		NC
L	454-3055	CONTROL, PREMIUM 2 Includes premier wiring and premium 6 button propel lever needed for most options. In addition to the standard control function, the additional 4 buttons will control the offset hitch and edge cutter functionality (only if machine is equipped with these options).		\$605

STEERING WHEEL

L	489-6273	STEERING WHEEL, FIXED 0 LH located steering wheel with a fixed location.		NC
L	489-6274	STEERING WHEEL, PIVOTING 0 LH located steering wheel with the ability to rotate 45 degrees inward toward the operator. The inward rotation allows enough movement that operators can comfortably steer with precision while performing delicate steering maneuvers. CANNOT BE USED WITH: 434-5079 MAPPING, GNSS 434-7889 MAPPING, GNSS, CAB		\$685

OPERATOR LANGUAGES

L	527-8200	LANGUAGES, OPTION 1 0 Includes standard languages (English, Spanish, French, German, Italian, Polish, Portuguese, Turkish, and Korean) for machine operation and control.		NC
---	----------	---	--	----

SEAT SELECTION

L	343-6129	SEAT, STD VINYL 157 Vinyl suspension seat with fold-up arm rests, retractable seat belt, weight adj., and tilt back.		NC
L	355-3084	SEAT, HEATED VINYL 163 Heated vinyl suspension seat with fold-up arms rests, retractable seat belt, weight adj., and tilt back.		\$319
L	344-0124	SEAT, STD CLOTH 157 Cloth suspension seat with fold-up arm rests, retractable seat belt, weight adj., and tilt back. Not recommended for use with PLATFORM, ROPS/FOPS due to potential issues from moisture in open platform environment. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS		\$212
L	355-3085	SEAT, HEATED CLOTH 163 Heated cloth suspension seat with fold-up arm rests, retractable seat belt, weight adj., and tilt back. Not recommended for use with PLATFORM, ROPS/FOPS due to potential issues from moisture in open platform environment. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS		\$371

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

TECHNOLOGY PRODUCTS**PRODUCT LINK**

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

L	460-8861	PRODUCT LINK, SATELLITE PL631 9 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or cellular coverage. ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS		\$439
L	461-1464	PRODUCT LINK, SATELLITE PL631 9 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS		\$439
L	460-8862	PRODUCT LINK, CELLULAR PL641 9 Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data. ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS		NC
L	461-1465	PRODUCT LINK, CELLULAR PL641 9 Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS		NC

OTHER ATTACHMENTS**WATER SPRAY**

P	445-8757	NOZZLES, STANDARD 1 Includes 18 high performance plastic nozzles in 2 spray bars per drum. 9 nozzles per spray bar.		NC
P	445-8758	NOZZLES, PREMIUM 2 Includes 18 high performance brass nozzles, in 2 spray bars per drum, 9 nozzles per spray bar.		\$309

FLUIDS**HYDRAULIC OIL**

L	433-0408	OIL, HYD, FACTORY FILLED 0		NC
L	433-0411	OIL, HI-AMBIENT FACTORY FILLED 0 Hydraulic oil recommended for machines operating in high temperature regions.		\$399

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

FLUIDS (CONT.)***HYDRAULIC OIL (Cont.)***

L	433-0410	OIL, HYD, BIO, FACTORY FILLED 0 FOR USE WITH LANE 3 ONLY Bio degradable oil recommended for hydraulic system when environmental compliance is required or desired.		\$685
---	----------	---	--	-------

INSTRUCTIONS***DECAL PACKAGES***

L	522-4617	INSTRUCTIONS, NORTH AMERICAN 0 ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada).		NC
---	----------	---	--	----

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
ELECTRICAL				
P	434-5133	LIGHT, ROTATING BEACON 13 Includes 2 LED amber strobe lights mounted on top of the machine.		\$690
P	434-4017	LIGHTS, HALOGEN 35 0		\$1,170 \$1,170 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 10 standard output halogen flood lamps: 2 front facing and 2 rear facing lamps mounted to the ROPS canopy; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports. ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS CANNOT BE USED WITH: 530-3115 LIGHTS, LED, ROPS 432-8358 LIGHTS, HIGH INTENSITY, ROPS		
P	351-3439	LIGHTS, HALOGEN, CAB 31 0		\$1,170 \$1,170 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 10 standard output halogen flood lamps: 2 front facing and 2 rear facing lamps mounted to the cab roof; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS CANNOT BE USED WITH: 515-1430 LIGHTS, LED, CAB 351-3441 LIGHTS, HIGH INTENSITY, CAB		
P	530-3115	LIGHTS, LED, ROPS 0 0		\$2,135 \$2,135 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 10 LED flood lamps: 2 front facing and 2 rear facing lamps mounted to the ROPS canopy; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports. ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS CANNOT BE USED WITH: 434-4017 LIGHTS, HALOGEN, ROPS 432-8358 LIGHTS, HIGH INTENSITY, ROPS		
P	515-1430	LIGHTS, LED, CAB 0 0		\$2,135 \$2,135 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 10 LED flood lamps: 2 front facing and 2 rear facing lamps mounted to the cab roof; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS CANNOT BE USED WITH: 351-3439 LIGHTS, HALOGEN, CAB 351-3441 LIGHTS, HIGH INTENSITY, CAB		
P	432-8358	LIGHTS, HIGH INTENSITY 35 0		\$2,725 \$2,725 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 4 high intensity halogen flood lamps mounted to the ROPS canopy, 2 front facing and 2 rear facing. Selection also includes 6 standard output halogen flood lamp: 1 facing the front drum surface and 1 facing the rear drum surface, and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports. ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS CANNOT BE USED WITH: 434-4017 LIGHTS, HALOGEN, ROPS 530-3115 LIGHTS, LED, ROPS		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

ELECTRICAL (CONT.)

P	351-3441	LIGHTS, HIGH INTENSITY, CAB	35 0	\$2,725 \$2,725 NI
<p>ALSO AVAILABLE ON A MISCELLANEOUS ORDER</p> <p>Includes 4 high intensity halogen flood lamps mounted to the cab roof, 2 front facing and 2 rear facing. Selection also includes 6 standard output halogen flood lamp: 1 facing the front drum surface and 1 facing the rear drum surface, and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports.</p> <p>ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS</p> <p>CANNOT BE USED WITH: 351-3439 LIGHTS, HALOGEN, CAB</p> <p>515-1430 LIGHTS, LED, CAB</p>				

TECHNOLOGY PRODUCTS**CAT COMPACTION CONTROL**

This is a factory designed and integrated SBAS accuracy level pass count and temperature mapping system which requires no off-board infrastructure.

For higher level accuracy consult your Dealer Technology Representative to order the necessary base station, data radio and options keys for RTK corrected position signal. Additionally, the machine connectivity modem identified below, requires cellular data plan sold separately. To view IC Mapping data in the office, a VisionLink subscription with the 3D Project Monitoring module (an add-on to VisionLink) is required.

P	419-5625	SENSORS, MAT TEMPERATURE	9 0	\$3,765 \$3,765 NI
<p>ALSO AVAILABLE ON A MISCELLANEOUS ORDER</p> <p>Includes front and rear bumper mounted infrared air purged temperature sensors, displayed on the standard LCD display.</p>				
P	532-8810	SENSOR, ACCELEROMETER.	0 0	\$5,450 \$5,450 NI
<p>ALSO AVAILABLE ON A MISCELLANEOUS ORDER</p> <p>Hardware mounted within the front drum to mount the Caterpillar supplied accelerometer for CMV measurement. Output is a unit-less CMV stiffness indication displayed at the operator station.</p>				
L	434-5079	MAPPING, GNSS	26	\$14,140
<p>Factory install of all components needed for mapping of temperature and machine pass count. Includes front and rear bumper mounted infrared, air purged temperature sensors, harnesses, system electronic controls including CB460 Display (17.8 cm/7.0 in) and MS952 antenna/receiver.</p> <p>Includes: Sensor, Mat Temperature</p> <p>ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS</p>				
L	434-7889	MAPPING, GNSS, CAB	26	\$14,140
<p>Factory install of all components needed for mapping of temperature and machine pass count. Includes front and rear bumper mounted infrared, air purged temperature sensors, harnesses, system electronic controls including CB460 Display (17.8 cm/7.0 in) and MS952 antenna/receiver.</p> <p>Includes: Sensor, Mat Temperature</p> <p>ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS</p>				

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

TECHNOLOGY PRODUCTS (CONT.)**MACHINE TO MACHINE COMMUNICATION**

Machine to Machine Communication is integrated hardware consisting of an electronic control module, radio and antennas with connecting wiring that enables machines to communicate key compaction data via local wireless and/or cellular data networks.

Contact your local SITECH dealer and wireless data carrier for additional support and cellular data packages.

L	567-4609	MACHINE CONNECTIVITY, SNM941	0	\$3,580
		SIM card enabled CDMA or GSM network with built in WIFI.		
		ONLY FOR USE WITH: 434-5079 MAPPING, GNSS		
		434-7889 MAPPING, GNSS, CAB		

OTHER ATTACHMENTS**OPERATOR ENVIRONMENT**

P	513-6265	SEAT BELT, 3"	0	\$144
L	435-4830	AIR CONDITIONER.	46	\$6,250
		ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS		
		355-1671 BELT, ENG, A/C		
P	351-3438	SUN SCREEN.	4	\$414
		Sun screen/visor inside cab.		
		ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS		
P	462-0499	MIRRORS, EXTERNAL, FRONT	20	\$585
			20	\$585 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes 2 external, adjustable mirrors on the front of the cab.		
		ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS		
P	462-0500	MIRRORS, EXTERNAL, REAR.	20	\$585
			20	\$585 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes 2 external, adjustable mirrors on the rear of the cab.		
		ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS		
P	362-2758	MIRRORS, EXTERNAL.	0	\$1,155
			0	\$1,155 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes 4 external adjustable mirrors, 2 mounted to the front frame, and 2 mounted to the rear frame.		

EDGE MANAGEMENT

P	530-3109	EDGE CUTTER/COMPACTOR.	0	\$8,800
			0	\$8,800 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes a straight cutting wheel, capable of cutting up to a 85 mm (3.3 in) lift, and a bevel compaction wheel, capable of edge compacting lifts greater than 96 mm (3.7 in) at a 41 degree bevel.		
		For bevel compacting thinner lifts, between 45-96 mm (1.7-3.7 in), please purchase bevel compaction wheel, 461-2682, from the Caterpillar Parts Network.		
		ONLY FOR USE WITH: 454-3055 CONTROL, PREMIUM		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

OTHER ATTACHMENTS (CONT.)**WATER SYSTEM - UPGRADES**

P	421-8128	MATS, COCOA	24 0	\$1,405 \$1,380 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER CANNOT BE USED WITH: 421-8129 MATS, WATER DISTRIBUTION		
P	421-8129	MATS, WATER DISTRIBUTION	29 0	\$1,795 \$1,760 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER CANNOT BE USED WITH: 421-8128 MATS, COCOA		
P	433-7143	FREEZE PROTECTION, ROPS/FOPS	4	\$650
		Includes a reservoir that holds windshield washer or RV antifreeze that protects the water lines, pumps, filters, and nozzles from freezing.		
		ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS		
P	433-7142	FREEZE PROTECTION, CAB	4	\$650
		Includes a reservoir that holds windshield washer or RV antifreeze that protects the water lines, pumps, filters, and nozzles from freezing.		
		ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS		

MISC ATTACHMENTS

P	257-9360	COVERS, DRUM	105	\$720
		Helps keep debris out of drums.		

FACTORY SOURCED KITS

P	487-5694	PIVOTING STEER WHEEL	5	\$685 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Field installed kit to adapt the standard fixed steering wheel location to one with the ability to rotate 45 degrees inward toward the operator. The inward rotation allows enough movement that operators can comfortably steer with precision while performing delicate steering maneuvers.		
P	544-5128	DRUM KIT, REAR OSC, FLD	0	\$23,010 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER 2000 mm (79") rear oscillatory drum kit consisting of a standard shell material for field installation into CB13 and CB64B.		
P	535-9661	DRUM KIT, REAR OSC, HD, FLD	0	\$30,090 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER 2000 mm (79") rear oscillatory drum kit consisting of a hardened shell material for field installation into CB13 or CB64B.		
P	470-1855	ACCELEROMETER READY.	0	\$3,295 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Hardware mounted within the front drum to mount the aftermarket SITECH supplied CM310 accelerometer for CMV measurement. Output is unit-less CMV stiffness indication displayed on SITECH supplied mapping system.		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

DOCUMENTATION***CERTIFICATES***

P	354-8706	YEAR OF MANUFACTURE PLATE 0 Plate attached to PIN plate showing year of Final Plant Shipping date. Available for all regions, but required in Brazil. CANNOT BE USED WITH: 535-9662 CE CERTIFICATION		NC
P	0P-1870	CERTIFICATE OF ORIGIN. 0		NC

PACKING

	0P-0210	PACK, DOMESTIC TRUCK 0		NC
	0P-3651	PACKING, MISC MATERIAL 0 No charge for packing. Applicable freight charges may apply.		NC