

PM312 COLD PLANER
MINERBIO, ITALY

 Ship Weight
 lbs

 LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

CAT C9.3, inline 6-cylinder,
 turbocharged, ATAAC, diesel engine
 Power and torque curve optimized for
 fuel efficiency
 Engine diagnostic connector (for Cat ET)
 Air cleaner, dry type dual element with
 integral precleaner
 Belt, automatic tensioner
 Fuel filter/water separator
 Hydrostatic transmission
 Computerized load control
 Traction control/differential lock
 Alignment controlled steering system
 with two steering modes:
 rear and assist ON/OFF
 Alignment is optimized for selected mode

ELECTRICAL

Backup alarm
 Alternator, 115-amp
 Batteries, two maintenance free,
 1400 CCA each
 Horn, forward warning
 Ground located horn, operator warning
 Electrical system, 24 Volt
 Work lights (8 pole mount)
 Machine diagnostic connector
 (for CAT ET)
 Self diagnostic system
 Product link equipped

OPERATOR ENVIRONMENT

Single right side operation station
 with adjustable seat
 Platform handrails/guardrails
 Lockable vandalism guards for all
 control panels
 Joystick propel and steering
 Control console with LED backlit panels
 Machine monitoring system
 Electronic machine management system
 Automatic throttle control
 Digital graphic display for
 diagnostics and operating instructions
 Silver-class touch screen display
 Camera ready display
 LED wake-up mode with floor light
 Integrated grade control ready
 Electronic drivetrain protection system
 Rear RH leg steering for track option
 Rear RH leg retraction
 Load control
 Ramp-in, ramp-out function
 Digital moldboard control

3 rotor speeds selectable on control
 panels
 Quick detach fuses and relays with
 blown fuse detection and fault
 indication on display
 Two level warning system with action
 light and horn (warning, critical
 warning)
 Water spray system
 Electronic water level gauge
 12v ports at operator station
 Rotor service keypad control

APPLICATION SPECIFIC COMPONENTS

ROTOR AND CHAMBER SYSTEM
 Caterpillar patented tool holder with
 easy extraction feature
 External floating side plates
 Dry clutch, belt transmission and
 automatic tensioner
 Dedicated water spray for tool cooling
 and dust control
 Curb clearance right side plate
 Moldboard with floating, locked or
 service height levels and adjustable
 down pressure
 Hydraulic raiseable and floating anti-
 slab
CONVEYORS
 Front loading
 600 mm (26.3") belt width collecting
 conveyor
 600 mm (26.3") belt width discharge
 conveyor
 Dual stage, infinitely variable speed
 60-degree swing either side of center
 for discharging conveyor
 Quick-detach discharge conveyor

FLUIDS

Extended life coolant with protection
 to -34C (-29F)

OTHER STANDARD EQUIPMENT

Doors, service access, hinged, locking
 Fuel tank 600 L (158 gal)
 Pressure test ports with quick connect
 Water tank 1260 L (333 gal)
 Sound suppression insulation kit
 Mirrors
 Gas-spring engine hood lift
 Emergency functions:
 Hand pump brake release
 Air filter restriction electric
 indicator

PM312 COLD PLANER
MINERBIO, ITALY

Ship Weight
lbs

LIST PRICE
AT DEALER

OTHER STANDARD EQUIPMENT (CONT.)

On board winterization system
Bit removal tools
S.O.S. sampling ports
Sight gauges (hydraulic oil, filter
restriction)

PM312 COLD PLANER
MINERBIO, ITALY

Ship Weight
lbs

LIST PRICE
AT DEALER

**Lane 2 is reserved for the Base Order Management Program.
Please use Lane 2 when placing orders that are part of the Base
Orders Management Program.**

565-5936 PM312 02A COLD PLANER DCA1 0 \$526,530
LANE 1 - AVAILABLE FROM BALTIMORE PDC

INCLUDES:

551-5920 PM312 02A COLD PLANER
561-4350 MACHINE, PM3 COMMON
548-2958 ENGINE, CAT C9.3
571-0408 TRACK, CONVERSION
563-0518 VENTILATION SYSTEM
381-6575 LIGHTS, HALOGEN
381-6525 PRODUCT LINK, CELLULAR PLE641
522-0126 ROTOR, K SYSTEM - STD
571-0407 DISCHARGE CONVEYOR, HYD. FOLD
381-7333 PORT, FILLING, WATER TANK
548-3070 GUIDE, STANDARD STEERING
381-6481 HYDR. OIL, HYDO ADVANCED 10W
381-6709 FILM, NORTH AMERICA
481-8732 LIGHT, HAZARD, CANOPY
381-7323 LIGHTS, ROADING AND WORKING
381-7330 LIGHT, TRUCK SIGNAL
569-2838 PUMP, EMERGENCY
563-0519 CANOPY, FOLDING, HYDRAULIC
481-8872 CONTROL, GRADE
381-7320 CONTROL, SLOPE
381-7318 DISPLAY, OPTIONAL
421-8146 REAR CAMERA
381-7314 CONVEYOR CAMERA
542-7915 CAMERA, LH DRUM EDGE
376-4134 PNEUMATIC BIT REMOVAL TOOL
381-7326 PNEUMATIC COMPRESSOR SYSTEM
421-9634 DUST REDUCTION, ADDITIONAL
381-7321 PUMP, WASHING, HIGH PRESSURE
482-4046 BALLAST KIT

NOTE: Please refer to Lane 1 section to complete you order.

551-5920 PM312 02A COLD PLANER 0 \$341,110
LANE 2 - AVAILABLE FROM MINERBIO FACTORY
LANE 3 - AVAILABLE FROM MINERBIO FACTORY

AVAILABLE FOR: AM-N, Puerto Rico, Europe, Israel and South Korea

PM312 COLD PLANER MINERBIO, ITALY	Ship Weight lbs	LIST PRICE AT DEALER
--------------------------------------	--------------------	-------------------------

0G-0617	PM312 MISC MATL 0 AVAILABLE FROM MINERBIO FACTORY	NC
---------	--	----

Only reference numbers that have the text
"ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.

USE	REF NO.	MANDATORY ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-----------------------	--------------------	-------------------------

LANE 1 AM-NORTH MANDATORY ATTACHMENTS***LANE SELECTION***

OP-9001	LANE 1 ORDER	0	NC
---------	------------------------	---	----

COMMISSIONING

OP-2586	COMMISSIONING, NEEDED	0	\$6,420 NET
		0	\$6,420 NI
			NET

Commissioning Needed, trained personnel are required to properly
commission the machine.

OP-2587	COMMISSIONING, NOT NEEDED	0	NC
	Commissioning, Not Needed, necessary dealer resource are available to properly commission the machine.		

PACKING

OG-0044	ROLL ON-ROLL OFF	0	NC
---------	----------------------------	---	----

OP-0210	PACK, DOMESTIC TRUCK	0	NC
---------	--------------------------------	---	----

LANE 1 AM-NORTH OPTIONAL ATTACHMENTS***DOCUMENTATION***

L	524-1948	COMPLIANCE FILM,ELECT-MAGNETIC	0	NC
		REQUIRED BY: Canada		
	OF-5109	CERTIFICATE OF ORIGIN	0	\$89 NET

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Order Management (BOM) program.		
OP-9003	LANE 3 ORDER	0	NC

SPECIAL ARRANGEMENTS**CHASSIS**

L	561-4350	MACHINE, PM3 COMMON	0	NC
		ONLY FOR USE WITH: 551-5920 PM312 02A COLD PLANER		

POWERTRAIN**ENGINE**

L	548-2958	ENGINE, CAT C9.3	0	NC
		Meets U.S. EPA Tier 4 Final, EU Stage V and Korea Tier 4 Final emission standards. Meets UN R120.		
		ONLY FOR USE WITH: 551-5920 PM312 02A COLD PLANER		

TRACTION TYPE

L	381-6527	WHEEL, CONVERSION	0	NC
		Includes solid rubber tires on steel wheels.		
L	571-0408	TRACK, CONVERSION	0	\$62,990
		Includes independent track drives with auto tensioning system.		
		ONLY FOR USE WITH: 551-5920 PM312 02A COLD PLANER		

HYDRAULICS**DUST EXTRACTION**

L	381-6682	COVER, NO VENTILATION	0	NC
L	563-0518	VENTILATION SYSTEM	0	\$5,940
		Dust and particles from operations are collected in multiple areas by hydraulically driven fan and discharged into secondary conveyor.		
		NOTE: option may be needed for local regulations.		
		ONLY FOR USE WITH: 551-5920 PM312 02A COLD PLANER		

ELECTRICAL**LIGHTING**

L	381-6575	LIGHTS, HALOGEN	0	\$770
			0	\$770 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes 8 halogen lights: 1 light facing each of the 4 tracks/wheels, 1 light facing the rear of the cutter box, 1 light facing the front of the cutter box and 2 lights mounted on the top front end of the discharge conveyor.		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

ELECTRICAL (CONT.)***LIGHTING (Cont.)***

L	381-6572	LIGHTS, LED	0	\$4,610
			0	\$4,610 NI
<p>ALSO AVAILABLE ON A MISCELLANEOUS ORDER</p> <p>Includes 8 LED lights: 1 light facing each of the 4 tracks/wheels, 1 light facing the rear of the cutter box, 1 light facing the front of the cutter box and 2 lights mounted on the top front end of the discharge conveyor.</p>				

TECHNOLOGY PRODUCTS***PRODUCT LINK COMMUNICATION (Must select one)***

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the cost of owning and operating your fleet. Availability varies by country. Please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

L	381-6524	PRODUCT LINK, SATELLITE PL631	0	\$439
		Product Link Pro series PL631 uses a satellite network to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. For use in areas with poor or no cellular coverage.		
L	488-5577	PRODUCT LINK, SATELLITE PLE631	0	\$813
		Product Link Elite series PLE631 (consisting of PL631 radio and PLE601 network manager) uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		
L	381-7317	PRODUCT LINK, CELLULAR PL641	0	NC
		Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		
L	381-6525	PRODUCT LINK, CELLULAR PLE641	0	\$372
		Product Link Elite series PLE641 (consisting of PL641 radio and PLE601 network manager) uses cellular networks to transmit location, utilization, health and productivity information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		
L	319-4492	NO PRODUCT LINK	0	NC
		Product link removal - Special case, to be used only for orders to countries where Product Link is not authorized.		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

OTHER ATTACHMENTS**MILL ROTORS**

L	522-0126	ROTOR, K STD - 15 MM 0 Latest Design tool holder system with 1225 mm (48.2") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 15 mm. Includes: 106 Bits		\$28,610
C	567-0891	ROTOR, K FINE - 8 MM 0 CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest Design tool holder system with 1225 mm (48.2") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 8 mm. Includes: 172 Bits		\$41,470
C	567-0940	ROTOR, K COARSE - 18 MM 0 CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest Design tool holder system with 1225 mm (48.2") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 18 mm. Includes: 92 Bits		\$27,170
L	0F-5136	OMISSION, ROTOR 0 ONLY FOR USE WITH: LANE 3		NC

DISCHARGE CONVEYOR

L	381-6529	DISCHARGE CONVEYOR, MECHANICAL 0 Mechanical downward folding discharge conveyor.		\$40,320
L	571-0407	DISCHARGE CONVEYOR, HYD. FOLD 0 Hydraulically downward folding discharge conveyor. ONLY FOR USE WITH: 551-5920 PM312 02A COLD PLANER		\$48,350

WATER TANK GROUND LEVEL FILLING PORT

P	381-7333	PORT, FILLING, WATER TANK 0 Water tank ground level Filling Port, US Standard only		NC
---	----------	--	--	-----------

STEERING GUIDES

L	548-3070	GUIDE, STANDARD STEERING 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides one standard steering guide with lateral adjustment of pendulum markers.	0	NC \$279 NI
L	548-6908	GUIDE, TELESCOPING STEERING 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides one telescoping steering guide with multi point adjustment for advanced steering marker placement. ONLY FOR USE WITH: 571-0408 TRACK, CONVERSION or 381-6528 TRACK, CONVERSION	0	NC \$343 NI

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

OTHER ATTACHMENTS (CONT.)**COMMISSIONING SUPPORT**

NOTE: It is recommended that startup and commissioning of machine be included as part of the machine sale. The net charge covers a three days commissioning event. Trained personnel cover proper machine setup, basic maintenance, operation and application on a customer's jobsite. To request and schedule a machine commissioning event, dealers will need to contact the Caterpillar Paving Technical Training group by filling out the online request form

URL: <https://dealer.cat.com/PavingOnDemand>

L	OP-2586	COMMISSIONING, NEEDED 0	\$6,420 NET
		Commissioning Needed, trained personnel are required to properly commission the machine.	
		AVAILABLE FOR: AM-N and AM-S	
	OP-2587	COMMISSIONING, NOT NEEDED 0	NC
		Commissioning, Not Needed, dealer personnel are available to properly commission the machine.	

FLUIDS**OIL**

L	381-6481	HYDR. OIL, HYDO ADVANCED 10W 0	NC
		Cat standard hydraulic oil.	
L	381-6489	HYDRAULIC OIL, BIODEGRADABLE 0	\$2,250
		Hydraulic environmental ester synthetic oil is recommended when environmental compliance is required or desired.	
		ONLY FOR USE WITH: LANE 3	
L	381-6523	HYDRAULIC OIL, HIGH AMBIENT 0	\$705
		Hydraulic synthetic oil is recommended when high ambient operation is typical for machine.	
		ONLY FOR USE WITH: LANE 3	

INSTRUCTIONS**DECAL PACKAGES**

L	381-6709	FILM, NORTH AMERICA 0	NC
---	----------	---------------------------------	----

SERVICE INSTRUCTIONS

421-8926	SERIALIZED TECHNICAL MEDIA KIT 0	NC
	The technical media kit, will include the Operation & Maintenance Manual (OMM) and other media specified on the Factory Notification List required to ship products from the manufacturing facility. Kit may contain multiple Operation & Maintenance Manuals (OMM) based on the final country of destination. Contents will vary.	

Any additional media or translations not included in the kit, should be ordered through publications.cat.com

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
ELECTRICAL				
P	481-8732	LIGHT, HAZARD, CANOPY 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two LED amber strobe lights, bracket mounted on a rotatable, detent pivot base. One strobe is mounted on the canopy at the rear of the machine and the other is mounted at the front of the machine at the top of the conveyor. ONLY FOR USE WITH: 563-0519 CANOPY, FOLDING, HYDRAULIC or 381-7316 CANOPY, FOLDING, HYDRAULIC		\$344 NI
P	421-8156	LIGHT, HAZARD 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two LED amber strobe lights: one is mounted to an adjustable height pole mount on the rear of the machine, the other is mounted at the front of the machine, at the top of the conveyor on a rotatable bracket on a detent pivot base. CANNOT BE USED WITH: 563-0519 CANOPY, FOLDING, HYDRAULIC or 381-7316 CANOPY, FOLDING, HYDRAULIC	0	\$910 \$910 NI
P	381-7323	LIGHTS, ROADING AND WORKING 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two front mounted working lights with turn signals, two rear indicator/parking lights that signal, license plate holder with light and mounting hardware.	0	\$3,405 \$3,405 NI
P	394-9642	LAMP, HALOGEN (MAGNETIC) 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides a single halogen lamp with magnetic mounting.	0	\$316 NI
P	381-7330	LIGHT, TRUCK SIGNAL 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Red/Green light to communicate with truck driver.	0	\$555 \$555 NI
P	569-2838	PUMP ACCESSORY DRIVE 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Electro-hydraulic pump to allow for operation of steering, elevation and canopy movement with engine power off. ONLY FOR USE WITH: 551-5920 PM312 02A COLD PLANER	0	\$610 \$610 NI

OPERATOR ENVIRONMENT**OPERATOR STATION**

P	563-0519	CANOPY, FOLDING, HYDRAULIC 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Hydraulically folding canopy with extendible side wings. REQUIRES: 569-2838 PUMP, EMERGENCY ONLY FOR USE WITH: 551-5920 PM312 02A COLD PLANER	0	\$4,895 \$4,895 NI
P	381-7324	UMBRELLA 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes (1) umbrella to provide operator protection from sun and rain. Umbrella measures 1372 mm x 1372 mm (54" x 54") and is collapsible. Includes support shafts and mounting hardware to be installed on machine at customer discretion.	0	\$700 NI

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

OTHER ATTACHMENTS**GRADE AND SLOPE CONTROLS**

P	481-8872	CONTROL, GRADE	0 0	\$8,750 \$8,750 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Measures grade from the position of side plates, using position sensing cylinders. Provides information to machine displays for operation of grade control.		
P	381-7320	CONTROL, SLOPE	0 0	\$2,060 \$2,060 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Measures cross slope using a slope sensor mounted to the chassis. Provides information to machine for operation of grade control. ONLY FOR USE WITH: 481-8872 CONTROL, GRADE		
L	509-2523	SENSOR, SONIC, AVERAGING	0 0	\$10,230 \$10,230 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Sonic averaging ski for mounting on the LH or RH side or inboard. Consists of two sonic sensors (in addition to the machine grade control base system) with adjustable mounting arms. ONLY FOR USE WITH: 481-8872 CONTROL, GRADE		
P	381-7318	DISPLAY, OPTIONAL, PLFM	0	\$2,850 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Additional (1) display with mounting bracket for ground/operator station(s). Order qty 1 maximum ONLY FOR USE WITH: 481-8872 CONTROL, GRADE		

VISIBILITY ENHANCEMENTS

P	421-8146	REAR CAMERA.	0 0	\$665 \$665 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER This camera system is used to enhance the operator's rear visibility while operating. The LCD color display is designed to have a sharp, clear picture with camera mounted on the top rear end of the machine. REQUIRED BY: European dealers and affiliates		
P	381-7314	CONVEYOR CAMERA.	0 0	\$925 \$925 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER This camera system is used to enhance the operator's forward visibility while operating. The LCD color display is designed to have a sharp, clear picture with camera mounted on the top front end of the discharge conveyor.		
P	488-5580	CAMERA, AUX.	0	\$750 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes camera with cable and magnetic mount. Can be placed anywhere within cable length.		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

OTHER ATTACHMENTS (CONT.)**VISIBILITY ENHANCEMENTS (Cont.)**

P	542-7915	CAMERA, LH DRUM EDGE	0	\$635
			0	\$635 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Positioned to assist in lining up for cutting on left hand side of rotor. Includes camera, auxiliary lamp, cable, bracket and mounting hardware.		

ROTOR SERVICING TOOLS

P	376-4134	PNEUMATIC BIT REMOVAL TOOL	0	\$630 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes pneumatic hammer, punch tools, coil hose and fittings.		
P	381-7326	PNEUMATIC COMPRESSOR SYSTEM	0	\$2,785
			0	\$2,785 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Engine mounted air compressor with hose, tank and pressure regulator.		
P	577-4176	EXTRACTOR, TOOL HOLDER	0	\$278 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Hand tool for extracting K System cutter bit tool holders which have broken at the shank inside the weld on block. Tool is engaged to broken shank via a threaded pulling bolt.		

ADDITIONAL WATER SPRAYING SYSTEM

P	421-9634	DUST REDUCTION, ADDITIONAL	0	\$665
			0	\$665 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Additional water spraying system for dust reduction. Includes additional spray bars located on the front and rear of the pickup conveyor. NOTE: option may be needed for local regulations.		

HIGH PRESSURE WASHDOWN

L	381-7321	PUMP, WASHING, HIGH PRESSURE	0	\$4,930
			0	\$4,930 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER High pressure washdown water pump, including (1) wand with 15 m (50 ft) of hose on reel.		

LOW PRESSURE WASHDOWN

L	544-2811	WASHDOWN, LOW PRESSURE	0	\$1,465
			0	\$1,465 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides 13 m (43 ft) of low pressure washdown hose, spray nozzle and coiled hose storage bracket. Coiled hose storage bracket mounts to the discharge conveyor.		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

OTHER ATTACHMENTS (CONT.)**MISC ATTACHMENTS**

P	482-4046	BALLAST KIT	0	\$3,680
			0	\$3,680 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		510 kg of additional weight for greater milling control, especially		
		when in deep cuts or when cutting challenging material.		
		Recommended for machines used in a full range applications or those		
		seeking premium cutting control.		
P	561-4363	HOSE, SUCTION	0	\$307 NI
		ALSO AVAILABLE ON MISCELLANEOUS ORDER		
		Suction hose with strainer for filling the water tank for alternative		
		water sources. European standard only.		
		ONLY FOR USE WITH: 381-7332 PORT, FILLING, WATER TANK		

FIELD INSTALLED ATTACHMENTS

The following field attachments can be ordered
through Machine Order as a miscellaneous order.

C	522-0127	ROTOR, K STD - 15 MM, FLD	0	\$28,610 NI
		CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY		
		Latest Design tool holder system with 1225 mm (48.2") cut width.		
		Allows for quick change of tool holder without the need for welding,		
		replaceable bolt on kicker paddles, tooth spacing 15 mm.		
		Includes: 106 Bits		
C	567-0892	ROTOR, K FINE - 8 MM, FLD	0	\$41,470 NI
		CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY		
		Latest Design tool holder system with 1225 mm (48.2") cut width.		
		Allows for quick change of tool holder without the need for welding,		
		replaceable bolt on kicker paddles, tooth spacing 8 mm.		
		Includes: 172 Bits		
C	567-0895	ROTOR, K COARSE - 18 MM, FLD	0	\$27,170 NI
		CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY		
		Latest Design tool holder system with 1225 mm (48.2") cut width.		
		Allows for quick change of tool holder without the need for welding,		
		replaceable bolt on kicker paddles, tooth spacing 18 mm.		
		Includes: 92 Bits		

DOCUMENTATION**CERTIFICATES**

0F-5109	CERTIFICATE OF ORIGIN	0	\$89 NET
---------	---------------------------------	---	----------

PACKING

0G-0044	ROLL ON-ROLL OFF	0	NC
0G-0068	PACK, MISCELLANEOUS MATERIAL	0	NC