

CP56B VIBRATORY COMPACTOR
MINNEAPOLIS, MN, USA (SAP)

Ship Weight
lbs

LIST PRICE
AT DEALER

Standard Equipment:

POWERTRAIN

CAT C4.4 inline four cylinder, turbo-charged diesel engine (117 kW / 156 HP) with glow-plug heater
Dual element air cleaner
Fuel filter/water separator/electronic priming pump and water indicator
Three-speed throttle switch including ECOMODE
Dual propel pumps - 1 for drum and 1 for tires
Dual braking systems (service & parking, drum only)
Two-speed hydrostatic transmission
Limited slip differential

ELECTRICAL

24-volt starting and charging system alternator
(2) Maintenance free batteries - 750 CCA
Halogen working lights - canopy mounted (2 front-facing and 2 rear-facing)
Backup alarm and forward warning horn
Product link ready
Beacon ready

OPERATOR ENVIRONMENT

ROPS/FOPS platform
Four heavy-duty isolation mounts
Platform handrails/guardrails
Power steering
Adjustable tilt-steering column
Adjustable, rotating suspension seat
Retractable seat belt
Adjustable, padded arm rest for propel lever operation
On-board display with audible warning alarm and interface for:
-hydraulic oil temperature gauge,
-engine oil pressure gauge,
-engine coolant temperature gauge
-alternator charge,
-fuel level gauge,
-service hour meter,
-engine RPM
-ground speed, vibe speed
-fuel rate gauge
-engine load gauge
-basic compaction measurement
Lockable, vandalism guard for on-board display
12-volt power point

COOLING

Premixed 50% concentration of extended life coolant with freeze protection to -37C (-35F)

DRUMS

Padfoot drum
2134 mm (84") wide x 1534 mm (60.4") diameter
Dual amplitude with single frequency
Dual, pod-style eccentric weight housings
Adjustable front and rear steel scraper

OTHER STANDARD EQUIPMENT

Locking composite engine enclosure
Sealed-for-life hitch bearings
Sight gauges:
-coolant level
-hydraulic oil level
Hydraulic tank locking cap
Articulated frame with safety lock
Transport tie-down and lift points
Fuel tank with lockable cap
Quick connect hydraulic pressure test ports
SOS ports:
-engine
-hydraulic
-coolant
Universal bumper

CP56B VIBRATORY COMPACTOR
MINNEAPOLIS, MN, USA (SAP)

Ship Weight
lbs

LIST PRICE
AT DEALER

**Lane 2 is reserved for the Base Order Management Program.
Please use Lane 2 when placing order that are part of the
Base Order Management Program.**

497-5485	CP56B VIBRATORY COMPACTOR DCA1 0 LANE 1 - AVAILABLE FROM MINNEAPOLIS PDC	\$266,980
-----------------	--	------------------

INCLUDES:

433-1615 CP56B VIBRATORY COMPACTOR
420-9160 ENGINE, TIER 4F/STAGE 4
479-9014 SCREEN, STANDARD
435-8036 CAB, ROPS/FOPS WITH A/C
356-1227 SEAT, CLOTH
387-1801 BELT SEAT, 3"
477-9990 LANGUAGES, OPTION 1
454-5454 PRODUCT LINK, CELLULAR PL641
454-0249 INSTALLATION, CAB
441-6675 SENSOR, DRIVE POWER
203-4718 TIRE, TRACTION
355-3547 FREQUENCY, FIXED
463-2310 PAD, ROUND
438-2273 BLADE, LEVELING
362-4940 OIL, HYD, FACTORY FILLED
355-3056 LIGHTS, UPGRADED
107-4643 MIRRORS, REARVIEW, INTERNAL
204-4390 SUN SCREEN
107-4641 SUN VISOR, FRONT
355-2660 GUARD, TRANSMISSION

NOTE: Please refer to the Lane 1 section to complete your order.

CP56B VIBRATORY COMPACTOR
MINNEAPOLIS, MN, USA (SAP)

Ship Weight
lbs

LIST PRICE
AT DEALER

497-5484	CP56B VIBRATORY COMPACTOR DCA3 0 LANE 1 - AVAILABLE FROM MINNEAPOLIS PDC	\$243,890
-----------------	--	------------------

INCLUDES:

433-1615 CP56B VIBRATORY COMPACTOR
420-9160 ENGINE, TIER 4F/STAGE 4
479-9014 SCREEN, STANDARD
435-8035 PLATFORM, ROPS/FOPS
356-1226 SEAT, VINYL
387-1801 SEAT BELT, 3"
477-9990 LANGUAGES, OPTION 1
454-5454 PRODUCT LINK, CELLULAR PL641
454-0250 INSTALLATION, ROPS/FOPS
441-6675 SENSOR, DRIVE POWER
203-4718 TIRE, TRACTION
355-3547 FREQUENCY, FIXED
463-2310 PAD, ROUND
438-2273 BLADE, LEVELING
362-4940 OIL, HYD, FACTORY FILLED
355-3056 LIGHTS, UPGRADED
354-5413 MIRRORS, REARVIEW, EXTERNAL
355-2660 GUARD, TRANSMISSION

NOTE: Please refer to the Lane 1 section to complete your order.

433-1615	CP56B VIBRATORY COMPACTOR 19,515 LANE 2 - AVAILABLE FROM MINNEAPOLIS FACTORY LANE 3 - AVAILABLE FROM MINNEAPOLIS FACTORY	\$221,320
-----------------	---	------------------

OP-2575	CP56B MISC MATL 0 AVAILABLE FROM MINNEAPOLIS FACTORY Only reference numbers that have the text "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.	NC
----------------	---	-----------

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	--------	--------------------	-------------------------

LANE 1 AM-NORTH MANDATORY ATTACHMENTS***LANE SELECTION***

0P-9001	LANE 1 ORDER	0	NC
---------	------------------------	---	----

INSTRUCTIONS - PICTOGRAPH FILMS

L	437-9888	INSTRUCTIONS, NA PLATFORM	0	NC
---	----------	-------------------------------------	---	----

L	437-9887	INSTRUCTIONS, INT'L PLATFORM	0	NC
---	----------	--	---	----

L	437-9886	INSTRUCTIONS, NA CAB	0	NC
---	----------	--------------------------------	---	----

L	437-9885	INSTRUCTIONS, INT'L CAB	0	NC
---	----------	-----------------------------------	---	----

PACKING

0P-0210	PACK, DOMESTIC TRUCK	0	NC
---------	--------------------------------	---	----

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	--------	--------------------	-------------------------

LANE 1 AM-NORTH OPTIONAL ATTACHMENTS***CERTIFICATES***

	0P-1870	CERTIFICATE OF ORIGIN.	0	NC
P	524-1948	COMPLIANCE FILM,ELECT-MAGNETIC Film indicates EMC compliance. Required for Canada	0	NC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Mangement (BOM) program.		
OP-9003	LANE 3 ORDER	0	NC

POWERTRAIN**ENGINE**

L	420-9160	ENGINE, TIER 4F/STAGE 4	0	NC
		U.S. EPA Tier 4 Final/EU Stage IV equivalent engine.		

ENCLOSURES

L	479-9014	SCREEN, STANDARD	7	NC
		Fixed (not openable) screen at rear, right side of the engine compartment.		
L	479-9015	FUEL SYSTEM, DOOR	23	\$360
		Hinged and CAT key lockable door to access fuel fill without opening enclosure.		

OPERATOR ENVIRONMENT**OPERATOR STATIONS**

L	435-8035	PLATFORM, ROPS/FOPS	1,262	NC
		Open platform with handrails, ROPS/FOPS canopy and working lights.		
L	435-8038	CAB, ROPS/FOPS WITH HEATER	1,620	\$16,830
		FOR USE WITH LANE 3 ONLY		
		Two front-facing and two rear-facing working lights, external rear-view mirrors, heater & defroster, and wet-arm wipers/washers (front and rear). Cab is Radio Ready, including hardware, wiring, voltage converter and 12-volt power point. Wiring only - Radio and Speakers not included.		
L	435-8036	CAB, ROPS/FOPS WITH A/C	1,700	\$22,470
		Two front-facing and two rear-facing working lights, external rear-view mirrors, air conditioner, heater & defroster, and wet-arm wipers/washers (front and rear). Cab is Radio Ready, including hardware, wiring, voltage converter and 12-volt power point. Wiring only - Radio and Speakers not included.		

SEATS

L	356-1226	SEAT, VINYL	150	NC
		Standard rotating vinyl covered suspension seat.		
L	356-1227	SEAT, CLOTH	150	\$309
		Standard rotating cloth covered suspension seat.		
		ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		
L	356-1229	SEAT, CLOTH, DELUXE	158	\$535
		Deluxe cloth seat with head rest, air suspension and additional adjustments.		
		ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

OPERATOR ENVIRONMENT (CONT.)**SEAT BELTS**

L	382-9003	SEAT BELT, 2"	2	NC
L	387-1801	SEAT BELT, 3"	2	\$144

OPERATOR LANGUAGES

L	477-9990	LANGUAGES, OPTION 1	0	NC
		Includes standard languages (English, Spanish, French, German, Italian, Polish, Portuguese, Turkish, and Korean) for machine operation and control.		

TECHNOLOGY PRODUCTS**PRODUCT LINK**

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the cost of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact you Caterpillar marketing representative with questions.

L	454-5453	PRODUCT LINK, SATELLITE PL631	9	\$439
		Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		
L	454-5454	PRODUCT LINK, CELLULAR PL641	9	NC
		Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		

PRODUCT LINK INSTALLATION

L	454-0250	INSTALLATION, ROPS/FOPS	8	NC
		Factory installation of PL on machine with ROPS/FOPS canopy. ONLY FOR USE WITH: 435-8035 PLATFORM, ROPS/FOPS		
L	454-0249	INSTALLATION, CAB	8	NC
		Factory installation of PL on machines with cab. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

TECHNOLOGY PRODUCTS (CONT.)**CAT COMPACTION CONTROL**

Compaction Monitoring sensors to detect changes in soil stiffness which is an excellent indicator of load bearing strength and provides the operator with real time compaction information on the machine display.

L	444-5932	NO COMPACTION SENSOR	0	NC
		No Sensors.		
L	441-6675	SENSOR, DRIVE POWER	5	\$3,860
		Proprietary Caterpillar technology that directly measures soil stiffness via material deflection (rolling resistance).		

TIRES, RIMS, AND WHEELS

L	203-4718	TIRE, TRACTION	935	\$3,420
		23.1 x 26 8 ply traction (lug tread) tires and rims with liquid ballast.		

DRUMS**VIBRATORY SYSTEMS**

L	355-3547	FREQUENCY, FIXED	0	NC
		Single 31.9 Hz (1914 vpm) frequency with high and low amplitude.		
L	355-3546	FREQUENCY, VARIABLE	0	\$2,430
		Frequency dial that electronically controls the displacement of the vibratory pump. Frequency range from 23.3-31.9 Hz (1400-1914 vpm).		

PAD SHAPE

L	463-2310	PAD, ROUND	0	NC
		Involute-style pad that works well on 10-18" lifts. Each pad is 5" tall with a surface area of 13.9 square inches.		
L	463-2311	PAD, SQUARE	70	NC
		Square-style pad that works well on lifts less than 10". Each pad is 3.9" tall with a surface area of 21.7 square inches.		

LEVELING BLADE

L	357-6261	NO BLADE	0	NC
L	438-2273	BLADE, LEVELING	1,438	\$13,490
		Factory installed leveling blade and controls.		

FLUIDS**HYDRAULIC OIL**

L	362-4940	OIL, HYDR, FACTORY FILLED	0	NC
		Cat standard hydraulic oil.		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

FLUIDS (CONT.)***HYDRAULIC OIL (Cont.)***

L	362-4941	OIL, HYD, BIO, FACTORY FILLED 0 FOR USE WITH LANE 3 ONLY This Hydraulic Environmental Ester Synthetic oil is recommended for hydraulic system when environmental compliance is required or desired. Factory filled.		\$3,270
---	----------	---	--	---------

INSTRUCTIONS

L	437-9888	INSTRUCTIONS, NA PLATFORM 0 ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada). ONLY FOR USE WITH: 435-8035 PLATFORM, ROPS/FOPS		NC
L	437-9886	INSTRUCTIONS, NA CAB 0 ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada). ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		NC

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
ELECTRICAL				
P	355-3059	LIGHTING, WARNING	5 0	\$427 \$427 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
P	355-3056	LIGHTS, UPGRADED	3 0	\$227 \$227 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		4 additional lights for increased nighttime visibility.		
P	355-3062	MODULE, RECORDING, STD FREQ	0 26	\$6,400 \$6,400 NI
		FOR USE WITH LANE 3 ONLY		
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Factory or field installed components for		
		fixed frequency recording module.		
		ONLY FOR USE WITH: 355-3547 FREQUENCY, FIXED and		
		435-8038 CAB, ROPS/FOPS WITH HEATER or		
		435-8036 CAB, ROPS/FOPS WITH A/C		
P	355-3064	MODULE, RECORDING, VARIABLE	0 31	\$6,400 \$6,400 NI
		FOR USE WITH LANE 3 ONLY		
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Factory or field installed components for		
		variable frequency recording module.		
		ONLY FOR USE WITH: 355-3546 FREQUENCY, VARIABLE and		
		435-8038 CAB, ROPS/FOPS WITH HEATER or		
		435-8036 CAB, ROPS/FOPS WITH A/C		
OPERATOR ENVIRONMENT				
P	354-5413	MIRRORS, REARVIEW, EXTERNAL	10 0	\$311 \$311 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes two externally mounted rear-view mirrors.		
		ONLY FOR USE WITH: 435-8035 PLATFORM, ROPS/FOPS		
P	107-4643	MIRRORS, REARVIEW, INTERNAL	10 0	\$211 \$211 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes two rear-view mirrors mounted inside the cab.		
		ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or		
		435-8036 CAB, ROPS/FOPS WITH A/C		
P	204-4390	SUN SCREEN	2 2	\$332 \$332 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Provides two rear-view mirrors mounted inside the cab.		
		ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or		
		435-8036 CAB, ROPS/FOPS WITH A/C		
P	107-4641	SUN VISOR, FRONT	2 0	\$78 \$78 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Tip-down tinted sun visor for front window, reduces heat and glare.		
		ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or		
		435-8036 CAB, ROPS/FOPS WITH A/C		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

TECHNOLOGY PRODUCTS**CAT COMPACTION CONTROL**

This is a factory designed and integrated SBAS accuracy level pass count and mapping system which requires no off-board infrastructure. For a higher accuracy solution, consult your Dealer Technology Representative to order necessary base station, data radio and higher accuracy option key for an RTK solution.

L	375-1612	MAPPING, GNSS 45		\$10,280
		CB460 Display (17.8 cm/7.0 in), MS952 antenna/receiver.		
		ONLY FOR USE WITH: 435-8035 PLATFORM, ROPS/FOPS and 441-6675 SENSOR, DRIVE POWER		
L	375-1607	MAPPING, GNSS 45		\$10,280
		CB460 Display (17.8 cm/7.0 in), MS952 antenna/receiver.		
		ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C and 441-6675 SENSOR, DRIVE POWER		

MACHINE TO MACHINE COMMUNICATION

Machine to machine communication is integrated hardware consisting of an electronic control module, radio and antennas with connecting wiring that enables machines to communicate key compaction data via local wireless and/or cellular data networks.

Contact your local SITECH dealer and wireless data carrier for additional support and cellular data packages.

L	569-8583	MACHINE CONNECTIVITY, SNM941 0		\$3,560
		SIM card enabled CDMA or GSM network with built in WIFI.		
		ONLY FOR USE WITH: 375-1612 MAPPING, GNSS 375-1607 MAPPING, GNSS		

OTHER ATTACHMENTS**GUARDS**

P	355-2660	GUARD, TRANSMISSION 44		\$1,115
			0	\$1,020 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Provides protection for the rear axle, hydraulic drive motor and hose fittings.		

FIELD INSTALLED ATTACHMENTS

P	437-9830	BLADE, LEVELING, FLD 1,170		\$13,490 NI
		FOR USE WITH LANE 3 ONLY		
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Kit for dealer installed components for leveling blade.		
P	483-5926	PRINTER PORT WIRING KIT, CAB 0		\$400 NI
		FOR USE WITH LANE 3 ONLY		
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes wiring kit only for printer (dealer installed) using on a machine with a mapping system.		
		To be used with Cab, ROPS/FOPS machine.		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

FIELD INSTALLED ATTACHMENTS (CONT.)

P	483-6357	PRINTER PORT WIRING KIT, PLFM 0		\$400 NI
		FOR USE WITH LANE 3 ONLY		
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes wiring kit only for printer (dealer installed) used on		
		a machine with a mapping system.		
		To be used with Platform, ROPS/FOPS machine.		

DOCUMENTATION***CERTIFICATES***

P	0P-1870	CERTIFICATE OF ORIGIN 0		NC
---	---------	-----------------------------------	--	----

PACKING

	0P-0210	PACK, DOMESTIC TRUCK 0		NC
	0P-3651	PACKING, MISC MATERIAL 0		NC
		No charge for packing. Applicable freight charges may apply.		