

**PM313 COLD PLANER  
MINERBIO, ITALY**Ship Weight  
lbsLIST PRICE  
AT DEALER

Standard Equipment:

**POWERTRAIN**

CAT C9.3, inline 6-cylinder,  
turbocharged, ATAAC, diesel engine  
Power and torque curve optimized for  
fuel efficiency  
Engine diagnostic connector (for Cat ET)  
Air cleaner, dry type dual element with  
integral precleaner  
Belt, automatic tensioner  
Fuel filter/water separator  
Hydrostatic transmission  
Computerized load control  
Traction control/differential lock  
Alignment controlled steering system  
with two steering modes:  
rear and assist ON/OFF  
Alignment is optimized for selected mode

**ELECTRICAL**

Backup alarm  
Alternator, 115-amp  
Batteries, two maintenance free,  
1400 CCA each  
Horn, forward warning  
Ground located horn, operator warning  
Electrical system, 24 Volt  
Work lights (8 pole mount)  
Machine diagnostic connector  
(for CAT ET)  
Self diagnostic system  
Product link equipped

**OPERATOR ENVIRONMENT**

Single right side operation station  
with adjustable seat  
Platform handrails/guardrails  
Lockable vandalism guards for all  
control panels  
Joystick propel and steering  
Control console with LED backlit panels  
Machine monitoring system  
Electronic machine management system  
Automatic throttle control  
Digital graphic display for  
diagnostics and operating instructions  
Silver-class touch screen display  
Camera ready display  
LED wake-up mode with floor light  
Integrated grade control ready  
Electronic drivetrain protection system  
Rear RH leg steering for track option  
Rear RH leg retraction  
Load control  
Ramp-in, ramp-out function  
Digital moldboard control

3 rotor speeds selectable on control  
panels  
Quick detach fuses and relays with  
blown fuse detection and fault  
indication on display  
Two level warning system with action  
light and horn (warning, critical  
warning)  
Water spray system  
Electronic water level gauge  
12v ports at operator station  
Rotor service keypad control

**APPLICATION SPECIFIC COMPONENTS**

**ROTOR AND CHAMBER SYSTEM**  
Caterpillar patented tool holder with  
easy extraction feature  
External floating side plates  
Dry clutch, belt transmission and  
automatic tensioner  
Dedicated water spray for tool cooling  
and dust control  
Curb clearance right side plate  
Moldboard with floating, locked or  
service height levels and adjustable  
down pressure  
Hydraulic raiseable and floating anti-  
slab  
**CONVEYORS**  
Front loading  
600 mm (26.3") belt width collecting  
conveyor  
600 mm (26.3") belt width discharge  
conveyor  
Dual stage, infinitely variable speed  
60-degree swing either side of center  
for discharging conveyor  
Quick-detach discharge conveyor

**FLUIDS**

Extended life coolant with protection  
to -34C (-29F)

**OTHER STANDARD EQUIPMENT**

Doors, service access, hinged, locking  
Fuel tank 600 L (158 gal)  
Pressure test ports with quick connect  
Water tank 1260 L (333 gal)  
Sound suppression insulation kit  
Mirrors  
Gas-spring engine hood lift  
Emergency functions:  
Hand pump brake release  
Air filter restriction electric  
indicator

---

PM313 COLD PLANER  
MINERBIO, ITALY

Ship Weight  
lbs

LIST PRICE  
AT DEALER

---

**OTHER STANDARD EQUIPMENT (CONT.)**

On board winterization system  
Bit removal tools  
S.O.S. sampling ports  
Sight gauges (hydraulic oil, filter  
restriction)

PM313 COLD PLANER  
MINERBIO, ITALY

Ship Weight  
lbs

LIST PRICE  
AT DEALER

**Lane 2 is reserved for the Base Order Management Program.  
Please use Lane 2 when placing orders that are part of the Base  
Orders Management Program.**

**565-5937      PM313 02A COLD PLANER DCA1 . . . . . 0      \$529,990**  
LANE 1 - AVAILABLE FROM BALTIMORE PDC

**INCLUDES:**

551-5921 PM313 02A COLD PLANER  
561-4350 MACHINE, PM3 COMMON  
548-2958 ENGINE, CAT C9.3  
571-0408 TRACK, CONVERSION  
563-0518 VENTILATION SYSTEM  
381-6575 LIGHTS, HALOGEN  
381-6525 PRODUCT LINK, CELLULAR PLE641  
522-0132 ROTOR, K SYSTEM - STD  
571-0407 DISCHARGE CONVEYOR, HYD. FOLD  
381-7333 PORT, FILLING, WATER TANK  
548-3070 GUIDE, STANDARD STEERING  
381-6481 HYDR. OIL, HYDO ADVANCED 10W  
381-6709 FILM, NORTH AMERICA  
481-8732 LIGHT, HAZARD, CANOPY  
381-7323 LIGHTS, ROADING AND WORKING  
381-7330 LIGHT, TRUCK SIGNAL  
569-2838 PUMP, EMERGENCY  
563-0519 CANOPY, FOLDING, HYDRAULIC  
481-8872 CONTROL, GRADE  
381-7320 CONTROL, SLOPE  
381-7318 DISPLAY, OPTIONAL  
421-8146 REAR CAMERA  
381-7314 CONVEYOR CAMERA  
542-7915 CAMERA, LH DRUM EDGE  
376-4134 PNEUMATIC BIT REMOVAL TOOL  
381-7326 PNEUMATIC COMPRESSOR SYSTEM  
421-9634 DUST REDUCTION, ADDITIONAL  
381-7321 PUMP, WASHING, HIGH PRESSURE  
482-4046 BALLAST KIT

NOTE: Please refer to Lane 1 section to complete you order.

**551-5921      PM313 02A COLD PLANER . . . . . 0      \$343,590**  
LANE 2 - AVAILABLE FROM MINERBIO FACTORY  
LANE 3 - AVAILABLE FROM MINERBIO FACTORY

AVAILABLE FOR: AM-N, Puerto Rico

PM313 COLD PLANER MINERBIO, ITALY	Ship Weight lbs	LIST PRICE AT DEALER
--------------------------------------	--------------------	-------------------------

0G-0618	PM313 MISC MATL.....0 AVAILABLE FROM MINERBIO FACTORY	NC
---------	--	----

Only reference numbers that have the text  
"ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.

USE	REF NO.	MANDATORY ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-----------------------	--------------------	-------------------------

**LANE 1 AM-NORTH MANDATORY ATTACHMENTS*****LANE SELECTION***

OP-9001	LANE 1 ORDER . . . . .	0	NC
---------	------------------------	---	----

***COMMISSIONING***

L	OP-2586	COMMISSIONING, NEEDED . . . . .	0	\$6,420 NET
			0	\$6,420 NI
				NET

Commissioning Needed, trained personnel are required to properly  
commission the machine.

L	OP-2587	COMMISSIONING, NOT NEEDED . . . . .	0	NC
		Commissioning, Not Needed, necessary dealer resource are available to properly commission the machine.		

***PACKING***

OG-0044	ROLL ON-ROLL OFF . . . . .	0	NC
---------	----------------------------	---	----

OP-0210	PACK, DOMESTIC TRUCK . . . . .	0	NC
---------	--------------------------------	---	----

**LANE 1 AM-NORTH OPTIONAL ATTACHMENTS*****DOCUMENTATION***

L	524-1948	COMPLIANCE FILM,ELECT-MAGNETIC . . . . .	0	NC
		REQUIRED BY: Canada		
	OF-5109	CERTIFICATE OF ORIGIN . . . . .	0	\$89 NET

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

**LANE SELECTION**

0P-9002	LANE 2 ORDER . . . . .	0	NC
	Only for dealers enrolled in the Base Order Management (BOM) program.		
0P-9003	LANE 3 ORDER . . . . .	0	NC

**SPECIAL ARRANGEMENTS****CHASSIS**

L	561-4350	MACHINE, PM3 COMMON . . . . .	0	NC
		ONLY FOR USE WITH: 551-5921 PM313 02A COLD PLANER		

**POWERTRAIN****ENGINE**

L	548-2958	ENGINE, CAT C9.3 . . . . .	0	NC
		Meets U.S. EPA Tier 4 Final, EU Stage V and Korea Tier 4 Final emission standards. Meets UN R120.		
		ONLY FOR USE WITH: 551-5921 PM313 02A COLD PLANER or 575-4710 PM313 02B COLD PLANER		

**TRACTION TYPE**

L	381-6527	WHEEL, CONVERSION . . . . .	0	NC
		Includes solid rubber tires on steel wheels.		
		ONLY FOR USE WITH: 551-5921 PM313 02A COLD PLANER or 477-1340 PM313 COLD PLANER		
L	571-0408	TRACK, CONVERSION . . . . .	0	\$62,990
		Includes independent track drives with auto tensioning system.		
		ONLY FOR USE WITH: 551-5921 PM313 02A COLD PLANER		

**HYDRAULICS****DUST EXTRACTION**

L	381-6682	COVER, NO VENTILATION . . . . .	0	NC
L	563-0518	VENTILATION SYSTEM . . . . .	0	\$5,940
		Dust and particles from operations are collected in multiple areas by hydraulically driven fan and discharged into secondary conveyor.		
		NOTE: option may be need for local regulations.		
		ONLY FOR USE WITH: 551-5921 PM313 02A COLD PLANER		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
<b>ELECTRICAL</b>				
<b>LIGHTING</b>				
L	381-6575	LIGHTS, HALOGEN . . . . .	0	\$770
			0	\$770 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 8 halogen lights: 1 light facing each of the 4 tracks/wheels, 1 light facing the rear of the cutter box, 1 light facing the front of the cutter box and 2 lights mounted on the top front end of the discharge conveyor.				
L	381-6572	LIGHTS, LED . . . . .	0	\$4,610
			0	\$4,610 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 8 LED lights: 1 light facing each of the 4 tracks/wheels, 1 light facing the rear of the cutter box, 1 light facing the front of the cutter box and 2 lights mounted on the top front end of the discharge conveyor.				
<b>TECHNOLOGY PRODUCTS</b>				
<b>PRODUCT LINK COMMUNICATION (Must select one)</b>				
Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the cost of owning and operating your fleet. Availability varies by country. Please reference <a href="https://Dealer.cat.com/PL/Certification">https://Dealer.cat.com/PL/Certification</a> for certified countries. Please contact your Caterpillar marketing representative with questions.				
L	381-6524	PRODUCT LINK, SATELLITE PL631 . . . . .	0	\$439
Product Link Pro series PL631 uses a satellite network to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. For use in areas with poor or no cellular coverage.				
L	488-5577	PRODUCT LINK, SATELLITE PLE631 . . . . .	0	\$813
Product Link Elite series PLE631 (consisting of PL631 radio and PLE601 network manager) uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.				
L	381-7317	PRODUCT LINK, CELLULAR PL641 . . . . .	0	NC
Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.				
L	381-6525	PRODUCT LINK, CELLULAR PLE641 . . . . .	0	\$372
Product Link Elite series PLE641 (consisting of PL641 radio and PLE601 network manager) uses cellular networks to transmit location, utilization, health and productivity information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.				
L	319-4492	NO PRODUCT LINK . . . . .	0	NC
Product link removal - Special case, to be used only for orders to countries where Product Link is not authorized.				

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

**OTHER ATTACHMENTS****MILL ROTORS**

L	522-0132	<b>ROTOR, K STD - 15 MM</b> . . . . . 0 Latest Design tool holder system with 1300 mm (51.2") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 15 mm. Includes: 111 Bits		\$29,590
C	567-0897	<b>ROTOR, K FINE - 8 MM</b> . . . . . 0 CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest design tool holder system with 1300 mm (51.2") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 8 mm. Includes: 181 Bits		\$42,900
C	567-0900	ONLY FOR USE WITH: LANE 3 <b>ROTOR, K COARSE - 18 MM</b> . . . . . 0 CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest design tool holder system with 1300 mm (51.2") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 18 mm. Includes: 98 Bits		\$28,120
L	0F-5136	ONLY FOR USE WITH: LANE 3 <b>OMISSION, ROTOR</b> . . . . . 0 ONLY FOR USE WITH: LANE 3		NC

**DISCHARGE CONVEYOR**

L	381-6529	<b>DISCHARGE CONVEYOR, MECHANICAL</b> . . . . . 0 Mechanical downward folding discharge conveyor. ONLY FOR USE WITH: 551-5921 PM313 02A COLD PLANER or 477-1340 PM313 COLD PLANER		\$40,320
L	571-0407	<b>DISCHARGE CONVEYOR, HYD. FOLD</b> . . . . . 0 Hydraulically downward folding discharge conveyor. ONLY FOR USE WITH: 551-5921 PM313 02A COLD PLANER		\$48,350

**WATER TANK GROUND LEVEL FILLING PORT**

P	381-7333	<b>PORT, FILLING, WATER TANK</b> . . . . . 0 Water tank ground level Filling Port, US Standard only		NC
---	----------	--	--	----

**STEERING GUIDES**

L	548-3070	<b>GUIDE, STANDARD STEERING</b> . . . . . 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides one standard steering guide with lateral adjustment of pendulum markers.	0	NC \$279 NI
L	548-6908	<b>GUIDE, TELESCOPING STEERING</b> . . . . . 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides one telescoping steering guide with multi point adjustment for advanced steering marker placement. ONLY FOR USE WITH: 571-0408 TRACK, CONVERSION or 381-6528 TRACK, CONVERSION or 577-6234 TRACK, CONVERSION	0	NC \$343 NI



USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

**OTHER ATTACHMENTS (CONT.)****ROTOR DRIVE BELT GUARD**

L	578-5682	<b>GUARD, NO ROTOR TURNING DEVICE</b> . . . . . 0 Provides a rotor drive belt guard for machines not equipped with a rotor turning device. ONLY FOR USE WITH: 575-4710 PM313 02B COLD PLANER		NC
L	577-6336	<b>GUARD, ROTOR TURNING DEVICE</b> . . . . . 0 Provides a rotor drive belt guard for machines equipped with a rotor turning device ONLY FOR USE WITH: 575-4710 PM313 02B COLD PLANER and 561-4359 ROTOR TURNING DEVICE		NC

**GRADE AND SLOPE CONTROLS**

L	481-8872	<b>CONTROL, GRADE</b> . . . . . 0 Measures grade from the position of side plates, using position sensing cylinders. Provides information to machine displays for operation of grade control. ONLY FOR USE WITH: 551-5921 PM313 02A COLD PLANER or 477-1340 PM313 COLD PLANER		\$8,750
L	577-2980	<b>CONTROL, GRADE</b> . . . . . 0 Measures grade from the position of side plates, using position sensing cylinders. Provides information to machine displays for operation of grade control. ONLY FOR USE WITH: 575-4710 PM313 02B COLD PLANER		\$8,750
L	381-7320	<b>CONTROL, SLOPE</b> . . . . . 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Measures cross slope using a slope sensor mounted to the chassis. Provides information to machine for operation of grade control. ONLY FOR USE WITH: 481-8872 CONTROL, GRADE and 577-2980 CONTROL, GRADE		\$2,060

**COMMISSIONING SUPPORT**

NOTE: It is recommended that startup and commissioning of machine be included as part of the machine sale. The net charge covers a three days commissioning event. Trained personnel cover proper machine setup, basic maintenance, operation and application on a customer's jobsite. To request and schedule a machine commissioning event, dealers will need to contact the Caterpillar Paving Technical Training group by filling out the online request form

URL: <https://dealer.cat.com/PavingOnDemand>

L	0P-2586	<b>COMMISSIONING, NEEDED</b> . . . . . 0 Commissioning Needed, trained personnel are required to properly commission the machine. AVAILABLE FOR: AM-N and AM-S		\$6,420 NET
	0P-2587	<b>COMMISSIONING, NOT NEEDED</b> . . . . . 0 Commissioning, Not Needed, dealer personnel are available to to properly commission the machine.		NC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

**FLUIDS*****OIL***

L	381-6481	HYDR. OIL, HYDO ADVANCED 10W . . . . . 0		NC
		Cat standard hydraulic oil.		
L	381-6489	HYDRAULIC OIL, BIODEGRADABLE . . . . . 0		\$2,250
		Hydraulic environmental ester synthetic oil is recommended when environmental compliance is required or desired.		
		ONLY FOR USE WITH: LANE 3		
L	381-6523	HYDRAULIC OIL, HIGH AMBIENT . . . . . 0		\$705
		Hydraulic synthetic oil is recommended when high ambient operation is typical for machine.		
		ONLY FOR USE WITH: LANE 3		

**INSTRUCTIONS*****DECAL PACKAGES***

L	381-6709	FILM, NORTH AMERICA . . . . . 0		NC
		ONLY FOR USE WITH: 551-5921 PM313 02A COLD PLANER		
L	577-2995	INSTRUCTIONS, ANSI . . . . . 0		NC
		ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada).		
		ONLY FOR USE WITH: 575-4710 PM313 02B COLD PLANER		

***SERVICE INSTRUCTIONS***

	421-8926	SERIALIZED TECHNICAL MEDIA KIT . . . . . 0		NC
		The technical media kit, will include the Operation & Maintenance Manual (OMM) and other media specified on the Factory Notification List required to ship products from the manufacturing facility. Kit may contain multiple Operation & Maintenance Manuals (OMM) based on the final country of destination. Contents will vary.		
		Any additional media or translations not included in the kit, should be ordered through <a href="http://publications.cat.com">publications.cat.com</a>		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

**ELECTRICAL**

P	481-8732	<b>LIGHT, HAZARD, CANOPY</b> ..... 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two LED amber strobe lights, bracket mounted on a rotatable, detent pivot base. One strobe is mounted on the canopy at the rear of the machine and the other is mounted at the front of the machine at the top of the conveyor. ONLY FOR USE WITH: 563-0519 CANOPY, FOLDING, HYDRAULIC or 566-6910 CANOPY, FOLDING, HYDRAULIC or 381-7316 CANOPY, FOLDING, HYDRAULIC		<b>\$344 NI</b>
P	421-8156	<b>LIGHT, HAZARD</b> ..... 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two LED amber strobe lights: one is mounted to an adjustable height pole mount on the rear of the machine, the other is mounted at the front of the machine, at the top of the conveyor on a rotatable bracket on a detent pivot base. CANNOT BE USED WITH: 563-0519 CANOPY, FOLDING, HYDRAULIC or 566-6910 CANOPY, FOLDING, HYDRAULIC or 381-7316 CANOPY, FOLDING, HYDRAULIC	0	<b>\$910</b> <b>\$910 NI</b>
P	381-7323	<b>LIGHTS, ROADING AND WORKING</b> ..... 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two front mounted working lights with turn signals, two rear indicator/parking lights that signal, license plate holder with light and mounting hardware.	0	<b>\$3,405</b> <b>\$3,405 NI</b>
P	394-9642	<b>LAMP, HALOGEN (MAGNETIC)</b> ..... 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides a single halogen lamp with magnetic mounting.		<b>\$316 NI</b>
P	381-7330	<b>LIGHT, TRUCK SIGNAL</b> ..... 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Red/Green light to communicate with truck driver.	0	<b>\$555</b> <b>\$555 NI</b>
P	569-2838	<b>PUMP ACCESSORY DRIVE</b> ..... 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Electro-hydraulic pump to allow for operation of steering, elevation and canopy movement with engine power off. ONLY FOR USE WITH: 551-5921 PM313 02A COLD PLANER or 575-4710 PM313 02B COLD PLANER	0	<b>\$610</b> <b>\$610 NI</b>

**OPERATOR ENVIRONMENT****OPERATOR STATION**

P	563-0519	<b>CANOPY, FOLDING, HYDRAULIC</b> ..... 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Hydraulically folding canopy with extendible side wings. REQUIRES: 569-2838 PUMP ACCESSORY DRIVE ONLY FOR USE WITH: 551-5921 PM313 02A COLD PLANER	0	<b>\$4,895</b> <b>\$4,895 NI</b>
---	----------	--	---	-------------------------------------

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

**OPERATOR ENVIRONMENT (CONT.)****OPERATOR STATION (Cont.)**

P	566-6910	CANOPY, FOLDING, HYDRAULIC . . . . .	0 0	\$4,895 \$4,895 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Hydraulically folding canopy with extendible side wings. REQUIRES: 569-2838 PUMP ACCESSORY DRIVE ONLY FOR USE WITH: 575-4710 PM313 02B COLD PLANER		
P	381-7324	UMBRELLA. . . . .	0	\$700 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes (1) umbrella to provide operator protection from sun and rain. Umbrella measures 1372 mm x 1372 mm (54" x 54") and is collapsible. Includes support shafts and mounting hardware to be installed on machine at customer discretion. ONLY FOR USE WITH: 551-5921 PM313 02A COLD PLANER or 477-1340 PM313 COLD PLANER		
P	577-2997	UMBRELLA. . . . .	0	\$700 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes (1) umbrella to provide operator protection from sun and rain. Umbrella measures 1372 mm x 1372 mm (54" x 54") and is collapsible. Includes support shafts and mounting hardware to be installed on machine at customer discretion. ONLY FOR USE WITH: 575-4710 PM313 02B COLD PLANER		

**OTHER ATTACHMENTS****GRADE AND SLOPE CONTROLS**

L	509-2523	SENSOR, SONIC, AVERAGING . . . . .	0 0	\$10,230 \$10,230 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Sonic averaging ski for mounting on the LH or RH side or inboard. Consists of two sonic sensors (in addition to the machine grade control base system) with adjustable mounting arms. ONLY FOR USE WITH: 481-8872 CONTROL, GRADE or 577-2980 CONTROL, GRADE		
P	381-7318	DISPLAY, OPTIONAL, PLFM . . . . .	0	\$2,850 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Additional (1) display with mounting bracket for ground/operator station(s). Order qty 1 maximum		
P	387-9468	DISPLAY, OPTIONAL . . . . .	0	\$2,850 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Additional display (1) with mounting bracket for use at ground level. Order qty 1 maximum		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

**OTHER ATTACHMENTS (CONT.)****VISIBILITY ENHANCEMENTS**

P	421-8146	REAR CAMERA. . . . .	0 0	\$665 \$665 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER This camera system is used to enhance the operator's rear visibility while operating. The LCD color display is designed to have a sharp, clear picture with camera mounted on the top rear end of the machine. REQUIRED BY: European dealer sand affiliates		
P	381-7314	CONVEYOR CAMERA. . . . .	0 0	\$925 \$925 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER This camera system is used to enhance the opearator's forward visibility while operating. The LCD color display is designed to have a sharp, clear picture with camera mounted on the top front end of the discharge conveyor.		
P	488-5580	CAMERA, AUX. . . . .	0	\$750 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes camera with cable and magnetic mount. Can be placed anywhere within cable length.		
P	542-7915	CAMERA, LH DRUM EDGE . . . . .	0 0	\$635 \$635 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Positioned to assist in lining up for cutting on left hand side of rotor. Includes camera, auxiliary lamp, cable, bracket and mounting hardware.		
P	551-5925	CAMERA, CUT TRACKING . . . . .	0 0	\$825 \$825 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Mounted to view and track rotor alignment and positioning. This camera system offers the operator advanced visibility of the rotor placement with the ability to adjust alignment guides on the standard council mounted display. ONLY FOR USE WITH: 575-4710 PM313 02B COLD PLANER		

**ROTOR SERVICING TOOLS**

P	376-4134	PNEUMATIC BIT REMOVAL TOOL . . . . .	0	\$630 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes pneumatic hammer, punch tools, coil hose and fittings.		
P	561-4359	ROTOR TURNING DEVICE. . . . .	0	\$3,555
		Includes control device and electrical motor for powered rotational assist when servicing the rotor. ONLY FOR USE WITH: 575-4710 PM313 02B COLD PLANER		
P	381-7326	PNEUMATIC COMPRESSOR SYSTEM . . . . .	0 0	\$2,785 \$2,785 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Engine mounted air compressor with hose, tank and pressure regulator.		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

**OTHER ATTACHMENTS (CONT.)****ROTOR SERVICING TOOLS (Cont.)**

P	577-4176	EXTRACTOR, TOOL HOLDER . . . . . 0		\$278 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Hand tool for extracting K System cutter bit tool holders which		
		have broken at the shank inside the weld on block. Tool is engaged		
		to broken shank via a threaded pulling bolt.		

**ADDITIONAL WATER SPRAYING SYSTEM**

P	421-9634	DUST REDUCTION, ADDITIONAL . . . . . 0		\$665
			0	\$665 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Additional water spraying system for dust reduction.		
		Includes additional spray bars located on the front and		
		rear of the pickup conveyor.		
		NOTE: option may be need for local regulations.		

**HIGH PRESSURE WASHDOWN**

L	381-7321	PUMP, WASHING, HIGH PRESSURE . . . . . 0		\$4,930
			0	\$4,930 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		High pressure washdown water pump, including (1) wand with		
		15 m (50 ft) of hose on reel.		
		ONLY FOR USE WITH: 551-5921 PM313 02A COLD PLANER or		
		477-1340 PM313 COLD PLANER		
L	577-6255	PUMP, WASHING, HIGH PRESSURE . . . . . 0		\$4,930
			0	\$4,930 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		High pressure washdown water pump, including (1) wand with		
		15 m (50 ft) of hose on reel.		
		ONLY FOR USE WITH: 575-4710 PM313 02B COLD PLANER		

**LOW PRESSURE WASHDOWN**

L	544-2811	WASHDOWN, LOW PRESSURE . . . . . 0		\$1,465
			0	\$1,465 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Provides 13 m (43 ft) of low pressure washdown hose,		
		spray nozzle and coiled hose storage bracket.		
		Coiled hose storage bracket mounts to the discharge conveyor.		

**MISC ATTACHMENTS**

P	482-4046	BALLAST KIT . . . . . 0		\$3,680
			0	\$3,680 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		510 kg of additional weight for greater milling control, especially		
		when in deep cuts or when cutting challenging material.		
		Recommended for machines used in a full range applications or those		
		seeking premium cutting control.		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

**OTHER ATTACHMENTS (CONT.)****MISC ATTACHMENTS (Cont.)**

P	561-4363	HOSE, SUCTION . . . . . 0		\$307 NI
		ALSO AVAILABLE ON MISCELLANEOUS ORDER		
		Suction hose with strainer for filling the water tank for alternative water sources. European standard only.		
		ONLY FOR USE WITH: 381-7332 PORT, FILLING, WATER TANK		

**FIELD INSTALLED ATTACHMENTS**

The following field attachments can be ordered through Machine Order as a miscellaneous order.

C	522-0133	ROTOR, K STD - 15 MM, FLD . . . . . 0		\$29,590 NI
		CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY		
		Latest Design tool holder system with 1300 mm (51.2") cut width.		
		Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 15 mm.		
		Includes: 111 Bits		
C	567-0898	ROTOR, K FINE - 8 MM, FLD . . . . . 0		\$42,900 NI
		CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY		
		Latest design tool holder system with 1300 mm (51.2") cut width.		
		Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 8 mm.		
		Includes: 181 Bits		
C	567-0901	ROTOR, K COARSE - 18 MM, FLD . . . . . 0		\$28,120 NI
		CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY		
		Latest design tool holder system with 1300 mm (51.2") cut width.		
		Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 18 mm.		
		Includes: 98 Bits		

**DOCUMENTATION****CERTIFICATES**

OF-5109	CERTIFICATE OF ORIGIN . . . . . 0		\$89 NET
---------	-----------------------------------	--	----------

**PACKING**

OG-0044	ROLL ON-ROLL OFF . . . . . 0		NC
OG-0068	PACK, MISCELLANEOUS MATERIAL . . . . . 0		NC