

**CB7 VIBRATORY ASPHALT COMPACTOR  
XUZHOU, CHINA**Ship Weight  
lbsLIST PRICE  
AT DEALER

Standard Equipment:

**POWERTRAIN**

CAT, inline four-cylinder, turbo-charged  
aftercooled, diesel engine  
Cyclonic air cleaner  
Water separator  
Ultra clean fuel filter with integrated  
electric priming pump  
ECO mode throttle system  
Dual braking systems (service & parking)  
Two-speed hydrostatic transmission

**ELECTRICAL**

12-volt electric starting  
120 ampere alternator  
Maintenance free battery - 1000 CCA  
Backup alarm and forward warning horn  
Cat engine and vehicle ECM's - ET  
compatible  
Product link ready

**OPERATOR ENVIRONMENT**

Isolated ROPS/FOPS structure  
Platform handrails / guardrails  
Four heavy-duty isolation mounts  
Power steering  
Adjustable, suspension, seat  
Adjustable, steering console and  
control/display console  
Indicator light package with audible  
warning alarm for:  
-hydraulic oil pressure  
-hydraulic oil temperature  
-engine oil pressure  
-engine coolant temperature  
-glow plugs  
-service fault indicator  
Fuel level gauge  
Water level gauge  
Service hour meter  
Lockable, vandalism guard for instrument  
panel  
Sliding, rotating seat  
Automatic speed control  
Auto-vibe with adjustable on/off control  
Vibe tachometer  
Speedometer

**DRUMS**

Smooth drum  
1500 mm (59") wide x 1100 mm (43")  
diameter  
Front and rear self adjusting scraper  
blades  
Pod-style eccentric weight housing

**FLUIDS**

Premixed 50% concentration of extended  
life coolant with freeze protection  
to -37C (-35F)

**OTHER STANDARD EQUIPMENT**

Locking engine enclosure  
Sealed for life hitch bearings  
Sight gauges:  
-hydraulic tank level  
-air restriction indicator  
Cap lock for hydraulic tank  
Articulated frame with safety lock  
Transport tie-down and lift points  
Quick connect hydraulic pressure test  
ports  
SOS ports:  
-engine oil  
Dual spray bar pumps  
Single water spray bar per drum

---

CB7 VIBRATORY ASPHALT COMPACTOR  
XUZHOU, CHINA

Ship Weight  
lbs

LIST PRICE  
AT DEALER

---

**Lane 2 is reserved for the Base Order Management Program.  
Please use Lane 2 when placing orders that are part of the  
Base Order Management program.**

|                 |  |                  |
|-----------------|--|------------------|
| <b>541-9919</b> | <b>CB7 02A VIBRATORY COMPACTOR</b> ..... 0                             | <b>\$136,050</b> |
|                 | LANE 3 - AVAILABLE FROM SAVANNAH EPC                                   |                  |
|                 | AVAILABLE FOR: ADSD-N  |                  |
| <b>OP-4184</b>  | <b>CB7 MISC MATL</b> ..... 0   | <b>NC</b>        |
|                 | AVAILABLE FROM XUZHOU FACTORY  |                  |
|                 | Only reference numbers that have the text                              |                  |
|                 | "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order. |                  |

| USE | REF<br>NO. | LANE 2 / 3 MANDATORY | Ship Weight<br>lbs | LIST PRICE<br>AT DEALER |
|-----|------------|----------------------|--------------------|-------------------------|
|-----|------------|----------------------|--------------------|-------------------------|

**LANE SELECTION**

OP-9003 LANE 3 ORDER . . . . . 0 NC

**POWERTRAIN****ENGINE**

L 550-7871 ENGINE, CAT C3.6 . . . . . 0 NC  
 FOR USE WITH LANE 3 ONLY  
 Meets U.S. EPA Tier 4 Final and EU Stage V emission standards.  
 ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR

**BELT**

L 541-9992 BELT, ENG . . . . . 0 NC  
 FOR USE WITH LANE 3 ONLY  
 Serpentine belt for standard machine.  
 ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR

**HITCH**

L 556-3447 HITCH, STANDARD . . . . . 0 NC  
 FOR USE WITH LANE 3 ONLY  
 Standard hitch without offset.  
 ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR

L 556-3448 HITCH, OFFSET . . . . . 0 \$3,430  
 FOR USE WITH LANE 3 ONLY  
 Switch control on propel lever gives + / - 170 mm (6.6") of drum  
 offset.  
 ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR

**HYDRAULICS****CONVENTIONAL VIBRATION**

May select 1 Dual System OR 1 Front and 1 Rear System

L 556-4403 DUAL SYSTEM, 2A/2F . . . . . 0 NC  
 FOR USE WITH LANE 3 ONLY  
 Frequency of 53.3 Hz (3200 vpm) and 63.3 Hz (3800 vpm) for countries  
 outside the governance of CE certification; 50 Hz (3000 vpm) and  
 57 Hz (3420 vpm) for countries requiring CE certification.  
 Console switch control for amplitude/frequency setting.  
 ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR

L 556-4400 FRONT SYSTEM, 2A/2F . . . . . 0 NC  
 FOR USE WITH LANE 3 ONLY  
 Frequency of 53.3 Hz (3200 vpm) and 63.3 Hz (3800 vpm) for countries  
 outside the governance of CE certification; 50 Hz (3000 vpm) and  
 57 Hz (3420 vpm) for countries requiring CE certification.  
 Console switch control for amplitude/frequency setting.  
 ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR

L 556-4410 REAR SYSTEM, OSCILLATION STD . . . . . 0 \$4,300  
 FOR USE WITH LANE 3 ONLY  
 Oscillatory vibration at a frequency of 33 Hz (1980 vpm) and 40 Hz  
 (2400 vpm) on the rear drum.  
 ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR

| USE | REF<br>NO. | LANE 2 / 3 MANDATORY | Ship Weight<br>lbs | LIST PRICE<br>AT DEALER |
|-----|------------|----------------------|--------------------|-------------------------|
|-----|------------|----------------------|--------------------|-------------------------|

**HYDRAULICS (CONT.)****CORE MACHINE HYDRAULICS**

|   |          |   |  |    |
|---|----------|---|--|----|
| L | 546-4792 | HYDRAULICS, SOLID DRUM, STD . . . . . 0                     |  | NC |
|   |          | FOR USE WITH LANE 3 ONLY                                    |  |    |
|   |          | Hydraulic system for machines with solid drums and no       |  |    |
|   |          | chipsreader controls.                                       |  |    |
|   |          | ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR and |  |    |
|   |          | 556-4403 DUAL SYSTEM, 2A/2F or                              |  |    |
|   |          | 556-4400 FRONT SYSTEM, 2A/2F                                |  |    |

**AUXILIARY HYDRAULICS**

|   |          |   |  |         |
|---|----------|---|--|---------|
| L | 556-5970 | STD MACHINE . . . . . 0                                 |  | \$2,650 |
|   |          | FOR USE WITH LANE 3 ONLY                                |  |         |
|   |          | No chipsreader controls.                                |  |         |
|   |          | ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |  |         |

**ELECTRICAL****LIGHTING**

|   |          |  |  |       |
|---|----------|--|--|-------|
| L | 556-6075 | LIGHTS, WORKING . . . . . 0                                      |  | NC    |
|   |          | FOR USE WITH LANE 3 ONLY   |  |       |
|   |          | Includes 2 front and 2 rear facing bezel mounted, clear, LED     |  |       |
|   |          | flood lights located in the bumpers.                             |  |       |
|   |          | ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR          |  |       |
| L | 583-4156 | LIGHTS, WORKING W/SIGNALS . . . . . 0                            |  | \$950 |
|   |          | FOR USE WITH LANE 3 ONLY   |  |       |
|   |          | Includes 4 rear facing LED flood lights, front and rear LED turn |  |       |
|   |          | signals, and front and rear LED indicator/parking lights. All    |  |       |
|   |          | lights are mounted to bezels located in the bumpers.             |  |       |
|   |          | ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR          |  |       |

**AUXILIARY LIGHTING**

|   |          |   |   |            |
|---|----------|---|---|------------|
| P | 556-6097 | LIGHTS, LED, BASIC . . . . . 0  |   | \$1,350    |
|   |          |   | 0 | \$1,350 NI |
|   |          | FOR USE WITH LANE 3 ONLY  |   |            |
|   |          | ALSO AVAILABLE ON A MISCELLANEOUS ORDER                               |   |            |
|   |          | Includes 10 LED flood lamps: 2 front facing and 2 rear facing lamps   |   |            |
|   |          | mounted to the roof with 850 lumens of output each; 2 LED light bars, |   |            |
|   |          | 1 facing the front drum surface and 1 facing the rear drum surface    |   |            |
|   |          | with 1,800 lumens of output each; and 4 lights facing the lower drum  |   |            |
|   |          | edge, mounted to each of the machine's folded drum supports with 850  |   |            |
|   |          | lumens of output each.  |   |            |
|   |          | ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR               |   |            |

| USE | REF<br>NO. | LANE 2 / 3 MANDATORY | Ship Weight<br>lbs | LIST PRICE<br>AT DEALER |
|-----|------------|----------------------|--------------------|-------------------------|
|-----|------------|----------------------|--------------------|-------------------------|

**ELECTRICAL (CONT.)****AUXILIARY LIGHTING (Cont.)**

|   |          |  |        |                       |
|---|----------|--|--------|-----------------------|
| P | 556-6100 | LIGHTS, LED, PREMIUM . . . . .   | 0<br>0 | \$2,725<br>\$2,725 NI |
|   |          | FOR USE WITH LANE 3 ONLY<br>ALSO AVAILABLE ON A MISCELLANEOUS ORDER<br>Includes 10 LED flood lamps, 2 front facing and 2 rear facing lamps<br>mounted to the roof with 2,000 lumens of output each; 2 LED light<br>bars, 1 facing the front drum surface and 1 facing the rear drum<br>surface with 1,800 lumens of output each; and 4 lights facing the<br>lower drum edge, mounted to each of the machine's folded drum<br>supports with 850 lumens of output each.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |        |                       |
| P | 587-9551 | COVER, NO LED LIGHTS . . . . .   | 0      | NC                    |
|   |          | FOR USE WITH LANE 3 ONLY<br>Includes 4 covers for shrouding the cavities in the canopy to where<br>auxiliary lighting options would have been.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR  |        |                       |

**OPERATOR ENVIRONMENT****OPERATOR STATION**

|   |          |   |   |    |
|---|----------|---|---|----|
| L | 556-4308 | PLATFORM, ROPS/FOPS . . . . .   | 0 | NC |
|   |          | FOR USE WITH LANE 3 ONLY<br>Includes grab handrails and foundation for the sliding and<br>rotating operator station.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |   |    |

**OPERATOR STATION MOVEMENT**

|   |          |   |   |         |
|---|----------|---|---|---------|
| L | 583-4760 | ROTATION, HALF . . . . .  | 0 | NC      |
|   |          | FOR USE WITH LANE 3 ONLY<br>Includes operator station slide and 180 deg rotate mechanism.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR                          |   |         |
| L | 583-4761 | ROTATION, FULL . . . . .  | 0 | \$2,070 |
|   |          | FOR USE WITH LANE 3 ONLY<br>Includes operator station slide and 359 deg rotate mechanism,<br>and position sensors.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |   |         |

**IGNITION SWITCH**

|   |          |  |   |    |
|---|----------|--|---|----|
| L | 560-1623 | SWITCH, STD IGNITION . . . . .   | 0 | NC |
|   |          | FOR USE WITH LANE 3 ONLY<br>Key switch engine start and stop.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |   |    |

**PROPEL LEVER**

|   |          |   |   |    |
|---|----------|---|---|----|
| L | 586-7552 | CONTROL, STANDARD . . . . .   | 0 | NC |
|   |          | FOR USE WITH LANE 3 ONLY<br>Basic 4 button propel lever for propel control, vibratory on/off<br>selection, water on/off spray, and offset hitch left/right adjustment.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |   |    |

| USE | REF<br>NO. | LANE 2 / 3 MANDATORY | Ship Weight<br>lbs | LIST PRICE<br>AT DEALER |
|-----|------------|----------------------|--------------------|-------------------------|
|-----|------------|----------------------|--------------------|-------------------------|

**OPERATOR ENVIRONMENT (CONT.)****STEERING WHEEL**

|   |          |   |  |         |
|---|----------|---|--|---------|
| L | 561-2140 | <b>STEERING WHEEL, STD</b> ..... 0<br>FOR USE WITH LANE 3 ONLY<br>Steering wheel, on the left-hand side of the operator station, is mounted in a fixed, horizontal location.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR   |  | NC      |
| L | 556-4489 | <b>STEERING WHEEL, ELEVATED</b> ..... 0<br>FOR USE WITH LANE 3 ONLY<br>Steering wheel, on the left-hand side of the operator station, can rotate upwards towards (or away from) the operator to offer a more traditional placement and feel of machine steering control.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |  | \$1,200 |

**SEAT SELECTION**

|   |          |   |  |       |
|---|----------|---|--|-------|
| L | 556-4371 | <b>SEAT, STANDARD VINYL</b> ..... 0<br>FOR USE WITH LANE 3 ONLY<br>Vinyl suspension seat with fold-up arm rest, weight adj., and tilt back.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR  |  | NC    |
| L | 583-7947 | <b>SEAT, HEATED VINYL</b> ..... 0<br>FOR USE WITH LANE 3 ONLY<br>Heated vinyl seat with air suspension adjustment, manual lumbar control, manual slide adjustment, and manual tilt back.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |  | \$319 |

**SEAT BELT**

|   |          |  |  |    |
|---|----------|--|--|----|
| L | 593-9841 | <b>SEAT BELT, 3"</b> ..... 0<br>FOR USE WITH LANE 3 ONLY<br>76 mm (3") wide, high visibility orange, polyester fiber webbed belt.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |  | NC |
|---|----------|--|--|----|

**FRONT STEPS**

|   |          |   |  |    |
|---|----------|---|--|----|
| P | 581-6845 | <b>STEPS, REFILL ASSIST, FRONT</b> ..... 0<br>FOR USE WITH LANE 3 ONLY<br>Fold down steps mounted to the left-hand side of the machine. Step mounts to the front drum support and have a grab handle mounted to the frame side plate for assisting with water refilling.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |  | NC |
|---|----------|---|--|----|

| USE | REF<br>NO. | LANE 2 / 3 MANDATORY | Ship Weight<br>lbs | LIST PRICE<br>AT DEALER |
|-----|------------|----------------------|--------------------|-------------------------|
|-----|------------|----------------------|--------------------|-------------------------|

**TECHNOLOGY PRODUCTS****PRODUCT LINK**

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the cost of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

|   |          |   |  |       |
|---|----------|---|--|-------|
| L | 585-7224 | <b>PRODUCT LINK, DUAL PLE783</b> . . . . . 0<br>FOR USE WITH LANE 3 ONLY<br>Product Link Elite series dual mode PLE783 (consisting of PL083 radio and PLE702 network manager) uses a combination of cellular and satellite networks to transmit, location, utilization and health information for viewing in Product Link user applications. For use where travel between areas of both cellular and satellite coverage is required.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR                                     |  | \$439 |
| L | 585-8769 | <b>PRODUCT LINK, CELLULAR PLE743</b> . . . . . 0<br>FOR USE WITH LANE 3 ONLY<br>Product Link Elite series PLE743 (consisting of PL243 radio and PLE702 network manager) uses cellular networks to transmit location, utilization, health and productivity information for viewing in Product Link user applications. Provides support for remote services and other advanced feature. Cellular technology enables more frequent transmission and larger volumes of data.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |  | NC    |

**RADAR INSTALLATION**

|   |          |   |  |    |
|---|----------|---|--|----|
| L | 570-4247 | <b>BUMPER COVER, STD</b> . . . . . 0<br>FOR USE WITH LANE 3 ONLY<br>Bumper covers for machine without the optional radar system.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |  | NC |
|---|----------|---|--|----|

**FLUIDS****HYDRAULIC OIL**

|   |          |   |  |       |
|---|----------|---|--|-------|
| L | 556-7020 | <b>OIL, HYD, STANDARD</b> . . . . . 0<br>FOR USE WITH LANE 3 ONLY<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR  |  | NC    |
| L | 556-7021 | <b>OIL, HYD, BIODEGRADABLE</b> . . . . . 0<br>FOR USE WITH LANE 3 ONLY<br>Biodegradable oil recommended for hydraulic system when environmental compliance is required or desired.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |  | \$630 |

---

| USE | REF<br>NO. | LANE 2 / 3 MANDATORY | Ship Weight<br>lbs | LIST PRICE<br>AT DEALER |
|-----|------------|----------------------|--------------------|-------------------------|
|-----|------------|----------------------|--------------------|-------------------------|

---

**INSTRUCTIONS*****DECAL PACKAGES***

|   |          |   |    |
|---|----------|---|----|
| L | 556-3657 | INSTRUCTIONS, ANSI . . . . . 0                                  | NC |
|   |          | FOR USE WITH LANE 3 ONLY  |    |
|   |          | ANSI picto warning decals using symbols plus the word "WARNING" |    |
|   |          | as required for North America (except Quebec, Canada).          |    |
|   |          | ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR         |    |



| USE | REF<br>NO. | OPTIONAL ATTACHMENTS | Ship Weight<br>lbs | LIST PRICE<br>AT DEALER |
|-----|------------|----------------------|--------------------|-------------------------|
|-----|------------|----------------------|--------------------|-------------------------|

**TECHNOLOGY PRODUCTS*****CAT COMPACTION CONTROL***

This is a factory designed and integrated SBAS accuracy level pass count and temperature mapping system which requires no off-board infrastructure. For higher level accuracy consult your Dealer Technology Representative to order the necessary base station, data radio and options keys for RTK corrected position signal. Additionally, the machine connectivity identified below, requires cellular data plan sold separately. To view IC Mapping data in the office, a VisionLink subscription with the 3D Project Monitoring module (an add-on to VisionLink) is required.

|   |          |  |   |            |
|---|----------|--|---|------------|
| L | 552-1722 | <b>SENSORS, MAT TEMPERATURE</b> . . . . .  | 0 | \$3,150    |
|   |          |  | 0 | \$3,150 NI |
|   |          | FOR USE WITH LANE 3 ONLY<br>ALSO AVAILABLE ON A MISCELLANEOUS ORDER<br>Includes bumper mounted (front and rear) infrared, air purged, temperature sensors. Temperature information is displayed on the machine display.<br>REQUIRES: 567-6815 MOUNT, INSTRUMENTATION<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR  |   |            |
| L | 510-4015 | <b>SENSOR, ACCELEROMETER.</b> . . . . .  | 0 | \$5,450    |
|   |          |  | 0 | \$5,450 NI |
|   |          | ALSO AVAILABLE ON A MISCELLANEOUS ORDER.<br>Hardware and an accelerometer mounted within the front drum. Output is a unit-less CMV stiffness indication displayed at the operator station.<br>ONLY FOR USE WITH: 539-2601 DRUM, SOLID or<br>539-2608 DRUM, SOLID W/OSCILLATION STD<br>556-4403 DUAL SYSTEM, 2A/2F or<br>556-4400 FRONT SYSTEM, 2A/2F   |   |            |
| L | 552-1727 | <b>MAPPING, GNSS</b> . . . . .   | 0 | \$14,140   |
|   |          | FOR USE WITH LANE 3 ONLY<br>Factory install of all components needed for mapping of temperature and machine pass count. Includes front and rear bumper mounted infrared, air purged temperature sensors, harnesses, system electronic controls including CB460 Display (17.8 cm/7.0 in) and MS952 antenna/receiver. Includes: Sensor, Mat Temperature<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR and<br>556-4309 PLATFORM, ROPS/FOPS |   |            |

**OTHER ATTACHMENTS*****OPERATOR ENVIRONMENT***

|   |          |  |   |          |
|---|----------|--|---|----------|
| L | 594-9448 | <b>HEADREST, SEAT, VINYL</b> . . . . .   | 0 | \$150    |
|   |          |  | 0 | \$150 NI |
|   |          | FOR USE WITH LANE 3 ONLY<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR and<br>556-4371 SEAT, STANDARD VINYL or<br>583-7947 SEAT, HEATED VINYL |   |          |

| USE | REF<br>NO. | OPTIONAL ATTACHMENTS | Ship Weight<br>lbs | LIST PRICE<br>AT DEALER |
|-----|------------|----------------------|--------------------|-------------------------|
|-----|------------|----------------------|--------------------|-------------------------|

**OTHER ATTACHMENTS (CONT.)****OPERATOR ENVIRONMENT (Cont.)**

|   |          |                            |        |                   |
|---|----------|----------------------------|--------|-------------------|
| P   | 556-4354 | MIRRORS, EXTERNAL. . . . . | 0<br>0 | \$600<br>\$600 NI |
| FOR USE WITH LANE 3 ONLY<br>ALSO AVAILABLE ON A MISCELLANEOUS ORDER<br>Includes 2 external adjustable mirrors on the front frame. Secondary set may be purchased and is to be mounted on the rear frame. Mounting provisions are provided standard on the front and rear frames.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |          |                            |        |                   |

**WATER SYSTEM - UPGRADES**

|  |          |  |        |                       |
|--|----------|--|--------|-----------------------|
| P  | 577-1902 | MATS, COCOA . . . . .                  | 0<br>0 | \$1,315<br>\$1,315 NI |
| FOR USE WITH LANE 3 ONLY<br>ALSO AVAILABLE ON A MISCELLANEOUS ORDER<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR<br>CANNOT BE USED WITH: 577-2393 MATS, WATER DISTRIBUTION   |          |  |        |                       |
| P  | 577-2393 | MATS, WATER DISTRIBUTION . . . . .     | 0<br>0 | \$1,670<br>\$1,670 NI |
| FOR USE WITH LANE 3 ONLY<br>ALSO AVAILABLE ON A MISCELLANEOUS ORDER<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR<br>CANNOT BE USED WITH: 577-1902 MATS, COCOA  |          |  |        |                       |
| P  | 564-2040 | FREEZE PROTECTION, ROPS/FOPS . . . . . | 0      | \$600                 |
| FOR USE WITH LANE 3 ONLY<br>Includes a reservoir that holds windshield washer or RV antifreeze that protects water lines, pumps, filters, and nozzles from freezing.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR and 556-4309 PLATFORM, ROPS/FOPS |          |  |        |                       |

**MISC ATTACHMENTS**

|  |          |                                      |        |                   |
|--|----------|--------------------------------------|--------|-------------------|
| P  | 567-6815 | MOUNT, OPTIONAL SENSOR(S) . . . . .  | 0<br>0 | \$200<br>\$200 NI |
| FOR USE WITH LANE 3 ONLY<br>ALSO AVAILABLE ON A MISCELLANEOUS ORDER<br>Bracket for mounting optional radar, bumper camera, and/or asphalt mat temperature sensors.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR and 552-1722 SENSORS, MAT TEMPERATURE                      |          |                                      |        |                   |
| P  | 594-4643 | STEPS, REFILL ASSIST, REAR . . . . . | 0<br>0 | \$400<br>\$400 NI |
| FOR USE WITH LANE 3 ONLY<br>Fold down steps mounted to the left-hand side of the machine. Step mounts to the rear drum support and includes a grab handle mounted to the frame side plate for assisting with water refilling.<br>ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR |          |                                      |        |                   |

| USE | REF<br>NO. | OPTIONAL ATTACHMENTS | Ship Weight<br>lbs | LIST PRICE<br>AT DEALER |
|-----|------------|----------------------|--------------------|-------------------------|
|-----|------------|----------------------|--------------------|-------------------------|

**FACTORY SOURCED KITS**

|   |          |   |  |                    |
|---|----------|---|--|--------------------|
| P | 577-7283 | <b>DRUM KIT, REAR, OSC, FLD</b> . . . . . 0                       |  | <b>\$15,300 NI</b> |
|   |          | FOR USE WITH LANE 3 ONLY  |  |                    |
|   |          | ALSO AVAILABLE ON A MISCELLANEOUS ORDER                           |  |                    |
|   |          | 1500 mm (59") solid drums, front drum with conventional vibration |  |                    |
|   |          | and rear drum with oscillatory vibration. Both drums shells are   |  |                    |
|   |          | comprised of standard material for field installation into CB7,   |  |                    |
|   |          | CB44B, CD8, or CD44B.   |  |                    |
|   |          | ONLY FOR USE WITH: 541-9919 CB7 02A VIBRATORY COMPACTOR           |  |                    |

**DOCUMENTATION*****CERTIFICATES***

|   |          |  |  |              |
|---|----------|--|--|--------------|
| P | 354-8706 | <b>YEAR OF MANUFACTURE PLATE</b> . . . . . 0                           |  | <b>NC</b>    |
|   |          | Plate attached to PIN plate showing year of Final Plant Shipping date. |  |              |
|   |          | Required for all machines shipping to Brazil.                          |  |              |
|   |          | CANNOT BE USED WITH: 434-1984 CE CERTIFICATION                         |  |              |
| P | 0P-4990  | <b>CERTIFICATE OF ORIGIN</b> . . . . . 0                               |  | <b>\$171</b> |

**PACKING*****EXPORT PACKING***

|         |                                     |  |                  |
|---------|-------------------------------------|--|------------------|
| 0P-4507 | <b>ROLL ON-ROLL OFF</b> . . . . . 0 |  | <b>\$605 NET</b> |
|---------|-------------------------------------|--|------------------|

***MISCELLANEOUS PACKING***

|         |   |  |           |
|---------|---|--|-----------|
| 0P-6706 | <b>BUNDLE EXPORT PACKING</b> . . . . . 0                |  | <b>NC</b> |
|         | This OP should be ordered for all miscellaneous orders. |  |           |