

CP44B VIBRATORY COMPACTOR
PIRACICABA, BRAZIL

Ship Weight
lbs

LIST PRICE
AT DEALER

Standard Equipment:

POWERTRAIN

Dual element air cleaner
Fuel filter/water separator/manual
priming pump and water indicator
Three-speed throttle switch including
ECOMODE
Dual propel pumps - 1 for drum and
1 for tires
Dual braking systems (service &
parking, for both drum and axle)
Two-speed hydrostatic transmission
Limited slip differential

ELECTRICAL

12-volt starting and charging system
alternator
Maintenance free battery - 750 CCA
Halogen working lights - canopy mounted
(2 front-facing and 2 rear-facing)
Backup alarm and forward warning horn
Product link ready
Beacon ready

OPERATOR ENVIRONMENT

ROPS/FOPS platform
Four heavy-duty isolation mounts
Platform handrails/guardrails
Power steering
Adjustable tilt-steering column
Adjustable suspension seat
Retractable seat belt
Adjustable, padded arm rest for
propel lever operation
On-board display with audible
warning alarm and interface for:
-hydraulic oil temperature gauge
-engine oil pressure gauge
-engine coolant temperature gauge
-alternator charge
-fuel level gauge
-service hour meter
Lockable, vandalism guard for
on-board display
12-volt power (Universal and USB point)

COOLING

Premixed 50% concentration of extended
life coolant with freeze protection
to -37C (-35F)

DRUMS

Padfoot drum
1676 mm (66") wide x 1225 mm (48") of
diameter
Dual amplitude with single frequency

Pod-style eccentric weight
housing
Adjustable front and rear steel scrapers

OTHER STANDARD EQUIPMENT

Locking composite engine enclosure
Sealed-for-life hitch bearings
Sight gauges:
-coolant level
-hydraulic oil level
Hydraulic tank locking cap
Articulated frame with safety lock
Transport tie-down and lift points
Fuel tank with lockable cap
Quick connect hydraulic pressure test
ports
SOS ports:
-engine
-hydraulic
-coolant
CP Universal bumper
Seat belt, 76.2 mm (3")

CP44B VIBRATORY COMPACTOR
 PIRACICABA, BRAZIL

Ship Weight
 lbs

LIST PRICE
 AT DEALER

**Lane 2 is reserved for the Base Order Management Program.
 Please use Lane 2 when placing orders that are part of the Base Order
 Management program**

560-6326 CP44B VIBRATORY COMPACTOR DCA1 0 \$186,580
 LANE 1 - AVAILABLE FROM BALTIMORE PDC

INCLUDES:

386-5371 CP44B VIBRATORY COMPACTOR
 186-2335 TIRE, TRACTION
 386-5323 OIL, HYDR, FACTORY FILLED
 386-5324 FREQUENCY, FIXED
 386-5390 CONTROL, BASIC
 386-5456 GUARD, TRANSMISSION
 386-5571 ENGINE, TIER/STAGE 4 CERTIFIED
 386-5608 PAD, OVAL
 417-9445 PLATFORM, ROPS/FOPS
 426-2675 SEAT, DELUXE CONTROL
 433-2403 BLADE, LEVELING
 454-5454 PRODUCT LINK, CELLULAR PL641
 467-7329 INSTALLATION, ROPS/FOPS
 477-9990 LANGUAGES, OPTION 1
 554-1057 FILMS

NOTE: Please refer to the Lane 1 section to complete your order.

386-5371 CP44B VIBRATORY COMPACTOR 15,717 \$166,040
 LANE 3 - AVAILABLE FROM PIRACICABA FACTORY

AVAILABLE FOR: EU, Australia & New Zealand

0P-4245 CP44B MISC MATL 0 NC
 AVAILABLE FROM PIRACICABA FACTORY

Only reference numbers that have the text
 "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.

| USE | REF NO. | LANE 1 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|------------|------------------|--------------------|-------------------------|
|-----|------------|------------------|--------------------|-------------------------|

LANE 1 AM-NORTH MANDATORY ATTACHMENTS***LANE***

| | | | |
|---------|------------------------|---|----|
| 0P-9001 | LANE 1 ORDER | 0 | NC |
|---------|------------------------|---|----|

INSTRUCTIONS

| | | | | |
|---|----------|---|---|----|
| L | 386-5313 | INSTRUCTIONS, NORTH AMERICAN | 0 | NC |
| | | ANSI picto warning decals using symbols plus the word "WARNING" | | |
| | | as required for North America (except Quebec, Canada). | | |

| | | | | |
|---|----------|---|---|----|
| L | 386-5314 | INSTRUCTIONS, INTERNATIONAL | 0 | NC |
| | | ISO picto warning decals using symbols only as required for | | |
| | | all non-North American countries and Quebec, Canada. | | |

ANTIFREEZE

| | | | |
|---------|-----------------------------------|---|----|
| 0P-1940 | WINDSHIELD WASHER EMPTY | 0 | NC |
|---------|-----------------------------------|---|----|

FUEL PROTECTION

| | | | | |
|---|---------|--|---|----|
| P | 0P-4269 | ANTIFREEZE, -25C (-13F) | 0 | NC |
| | | Provides fuel (diesel) antifreeze protection down to -45C (-50F) | | |

STORAGE PROTECTION

| | | | |
|---------|------------------------------|---|----|
| 0P-4782 | STORAGE PROTECTION | 0 | NC |
|---------|------------------------------|---|----|

CYLINDER PROTECTION

| | | | |
|---------|------------------------------------|---|----|
| 0P-3940 | PROTECTION, CYLINDER ROD | 0 | NC |
|---------|------------------------------------|---|----|

SERVICE MANUAL

| | | | |
|---------|---------------------------|---|----|
| 0P-0996 | MANUAL, ENGLISH | 0 | NC |
|---------|---------------------------|---|----|

| | | | |
|---------|--------------------------------|---|----|
| 0P-3389 | INSTRUCTIONS, FRENCH | 0 | NC |
|---------|--------------------------------|---|----|

| USE | REF NO. | LANE 1 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|------------|-----------------|--------------------|-------------------------|
|-----|------------|-----------------|--------------------|-------------------------|

LANE 1 AM-NORTH OPTIONAL ATTACHMENTS

CERTIFICATES

| | | | | |
|---|----------|---|---|----|
| P | 0P-1870 | CERTIFICATE OF ORIGIN. | 0 | NC |
| P | 524-1948 | COMPLIANCE FILM,ELECT-MAGNETIC Film indicates EMC compliance. REQUIRED BY: CANADA | 0 | NC |

PACKING

| | | | | |
|--|---------|--------------------------------|---|----|
| | 0P-0210 | PACK, DOMESTIC TRUCK | 0 | NC |
|--|---------|--------------------------------|---|----|

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|------------|----------------------|--------------------|-------------------------|
|-----|------------|----------------------|--------------------|-------------------------|

LANE SELECTION

| | | | |
|---------|--|---|----|
| OP-9002 | LANE 2 ORDER | 0 | NC |
| | Only for dealers enrolled in the Base Orders Management (BOM) program. | | |
| OP-9003 | LANE 3 ORDER | 0 | NC |

POWERTRAIN

| | | | | |
|---|----------|---|---|----|
| L | 386-5571 | ENGINE, TIER/STAGE 4 CERTIFIED | 0 | NC |
| | | Meets U.S. EPA Tier 4 Final emission standards. | | |
| | | ONLY FOR USE WITH: 386-5371 CP44B VIBRATORY COMPACTOR | | |

OPERATOR ENVIRONMENT**OPERATORS STATION**

| | | | | |
|---|----------|--|-----|----------|
| L | 417-9445 | PLATFORM, ROPS/FOPS | 0 | \$5,890 |
| | | Open platform with handrails, ROPS/FOPS canopy and working lights. | | |
| | | ONLY FOR USE WITH: 386-5361 CS44B VIBRATORY COMPACTOR | | |
| L | 431-6557 | CAB, ROPS/FOPS W/HTR | 553 | \$17,830 |
| | | ROPS/FOPS Cab, heater/defroster, radio ready headliner, 12-volt power point and working lights | | |
| | | ONLY FOR USE WITH: 386-5371 CP44B VIBRATORY COMPACTOR | | |
| L | 391-0157 | CAB, ROPS/FOPS W/ HTR & AC | 613 | \$27,140 |
| | | ROPS/FOPS Cab, air conditioning, heater/defroster, radio ready headliner, 12-volt power point and working lights | | |
| | | ONLY FOR USE WITH: 386-5371 CP44B VIBRATORY COMPACTOR | | |

SEATS

| | | | | |
|---|----------|--|-----|-------|
| L | 441-5222 | SEAT, BASIC CONTROL | 248 | NC |
| | | LCD display and vinyl seat with no rotation | | |
| | | ONLY FOR USE WITH: 417-9445 PLATFORM, ROPS/FOPS or 446-4913 PLATFORM, ROPS/FOPS | | |
| L | 426-2675 | SEAT, DELUXE CONTROL | 273 | \$499 |
| | | LCD display and vinyl seat with 20 deg RH operator station rotation | | |
| | | ONLY FOR USE WITH: 417-9445 PLATFORM, ROPS/FOPS or 446-4913 PLATFORM, ROPS/FOPS | | |
| L | 426-2676 | SEAT, DELUXE CONTROL, CAB | 172 | \$535 |
| | | LCD display and cloth seat with no rotation | | |
| | | ONLY FOR USE WITH: 431-6557 CAB, ROPS/FOPS W/HTR or 391-0157 CAB, ROPS/FOPS W/ HTR & AC or 441-3374 CAB, ROPS/FOPS W/ HTR & AC | | |

OPERATOR CONTROLS

| | | | | |
|---|----------|---|---|----|
| L | 386-5390 | CONTROL, BASIC | 0 | NC |
| | | Basic controls with the following standard machine parameters; Engine faults, machine faults, display of coolant temperature, engine oil pressure, fuel tank level, DEF tank level, battery voltage, hyd oil temp, engine rpm, engine load, fuel consumption rate and ambient air temperature | | |

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|------------|----------------------|--------------------|-------------------------|
|-----|------------|----------------------|--------------------|-------------------------|

OPERATOR ENVIRONMENT (CONT.)**OPERATOR CONTROLS (Cont.)**

| | | | | |
|---|----------|---|--|--------------|
| L | 386-5389 | CONTROL, DELUXE 5 | | \$640 |
| | | Deluxe controls includes all the basic control features with the addition of machine speed and vibratory speeds (VPM gauge, if equipped with FREQUENCY, VARIABLE system). In addition, the deluxe controls allows for other technology upgrades | | |

LANGUAGE OPTIONS

| | | | | |
|---|----------|---|--|-----------|
| L | 477-9990 | LANGUAGES, OPTION 1 0 | | NC |
| | | Includes standard languages (English, Spanish, French, German, Italian, Polish, Portuguese, Turkish, and Korean) for machine operation and control. | | |

TECHNOLOGY PRODUCTS**PRODUCT LINK**

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country, please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Cat marketing representative with questions.

| | | | | |
|---|----------|--|--|--------------|
| L | 454-5453 | PRODUCT LINK, SATELLITE PL631 9 | | \$439 |
| | | Product Link Pro series PL631 uses a satellite network to transmit location, utilization and condition information for viewing in product link's remote monitoring web interface. For use in areas with poor or no cellular coverage | | |
| L | 454-5454 | PRODUCT LINK, CELLULAR PL641 9 | | NC |
| | | Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and condition information for viewing in Product Link-s remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data | | |

PRODUCT LINK INSTALLATION

| | | | | |
|---|----------|---|--|-----------|
| L | 467-7328 | INSTALLATION, CAB 8 | | NC |
| | | Factory installation of PL on machines with cab ONLY FOR USE WITH: 431-6557 CAB, ROPS/FOPS W/HTR or 391-0157 CAB, ROPS/FOPS W/ HTR & AC or 441-3374 CAB, ROPS/FOPS W/ HTR & AC | | |
| L | 467-7329 | INSTALLATION, ROPS/FOPS 8 | | NC |
| | | ONLY FOR USE WITH: 417-9445 PLATFORM, ROPS/FOPS or 446-4913 PLATFORM, ROPS/FOPS | | |

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|------------|----------------------|--------------------|-------------------------|
|-----|------------|----------------------|--------------------|-------------------------|

TIRES, RIMS, AND WHEELS

| | | | | |
|---|----------|--|--|--------------|
| L | 186-2335 | TIRES, 14.9-24 8PR R-1 0 6-ply traction (lug tread) tires and rims with liquid ballast Typically used with padfoot style drum | | \$540 |
|---|----------|--|--|--------------|

DRUMS**VIBRATORY SYSTEMS**

| | | | | |
|---|----------|--|--|-----------------|
| L | 386-5324 | FREQUENCY, FIXED 61 Single 31.9 Hz (1914 vpm) frequency with high and low amplitude | | NC |
| L | 386-5334 | FREQUENCY, VARIABLE 67 Frequency dial that electronically controls the displacement of the vibratory pump. Frequency range from 23.3-31.9 Hz (1400-1914 vpm) ONLY FOR USE WITH: 386-5389 CONTROL, DELUXE | | \$2, 615 |

PAD STYLE

| | | | | |
|---|----------|---|--|-----------|
| L | 386-5608 | PAD, OVAL 0 Involute-style pad that works well on 254-457 mm (10-18") lifts. Each pad is 127 mm (5") tall with a surface area of 13.9 square inches | | NC |
| L | 386-5609 | PAD, SQUARE 30 Square-style pad that works well on lifts less than 254 mm (10"). Each pad is 99 mm (3.9") tall with a surface area of 21.7 square inches | | NC |

BLADES**LEVELING BLADE**

| | | | | |
|---|----------|--|--|------------------|
| L | 433-2404 | NO BLADE 0 | | NC |
| L | 433-2403 | BLADE, LEVELING 1, 121 Factory installed leveling blade and controls | | \$12, 500 |

FLUIDS**HYDRAULIC OIL**

| | | | | |
|---|----------|--|--|-----------------|
| L | 386-5323 | OIL, HYDR, FACTORY FILLED 0 Cat standard hydraulic oil | | NC |
| L | 386-5333 | OIL, BIO HYDR, FACTORY FILLED 0 This Hydraulic Environmental Ester Synthetic oil is recommended for hydraulic system when environmental compliance is required or desired. Factory filled. | | \$4, 665 |

ANTIFREEZE

| | | | | |
|--|---------|---|--|-----------|
| | 0P-1940 | WINDSHIELD WASHER EMPTY 0 For use with machines with cab. ONLY FOR USE WITH: 431-6557 CAB, ROPS/FOPS W/HTR or 391-0157 CAB, ROPS/FOPS W/ HTR & AC or 441-3374 CAB, ROPS/FOPS W/ HTR & AC | | NC |
|--|---------|---|--|-----------|

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|------------|----------------------|--------------------|-------------------------|
|-----|------------|----------------------|--------------------|-------------------------|

FLUIDS (CONT.)**FUEL PROTECTION**

| | | | | |
|---|---------|--|--|----|
| P | 0P-4269 | ANTIFREEZE, -25C (-13F) 0 | | NC |
| | | Provides fuel (diesel) antifreeze protection down to -45C (-50F) | | |

CYLINDER PROTECTION

| | | | | |
|--|---------|--------------------------------------|--|----|
| | 0P-3940 | PROTECTION, CYLINDER ROD 0 | | NC |
|--|---------|--------------------------------------|--|----|

STORAGE PROTECTION

| | | | | |
|--|---------|--------------------------------|--|----|
| | 0P-4782 | STORAGE PROTECTION 0 | | NC |
|--|---------|--------------------------------|--|----|

INSTRUCTIONS**DECAL PACKAGES**

| | | | | |
|---|----------|---|--|----|
| L | 386-5313 | INSTRUCTIONS, NORTH AMERICAN 0 | | NC |
| | | ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada). | | |
| | | ONLY FOR USE WITH: 417-9445 PLATFORM, ROPS/FOPS | | |
| L | 386-5314 | INSTRUCTIONS, INTERNATIONAL 0 | | NC |
| | | ISO picto warning decals using symbols only as required for all non-North American countries and Quebec, Canada. | | |
| | | ONLY FOR USE WITH: 386-5371 CP44B VIBRATORY COMPACTOR and 417-9445 PLATFORM, ROPS/FOPS | | |
| L | 386-5315 | INSTRUCTIONS, NORTH AMERICAN 0 | | NC |
| | | ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada). | | |
| | | ONLY FOR USE WITH: 431-6557 CAB, ROPS/FOPS W/HTR or 391-0157 CAB, ROPS/FOPS W/ HTR & AC | | |
| L | 386-5316 | INSTRUCTIONS, INTERNATIONAL 0 | | NC |
| | | ISO picture warning decals using symbols only as required for all non-North American countries and Quebec, Canada. | | |
| | | ONLY FOR USE WITH: 386-5371 CP44B VIBRATORY COMPACTOR and 391-0157 CAB, ROPS/FOPS W/HTR + AC or 431-6557 CAB, ROPS/FOPS W/HTR | | |

SERVICE INSTRUCTIONS

| | | | | |
|--|---------|-----------------------------|--|----|
| | 0P-0996 | MANUAL, ENGLISH 0 | | NC |
|--|---------|-----------------------------|--|----|

FILM GP

| | | | | |
|---|----------|--------------------------------------|--|----|
| L | 554-1057 | FILM GP "MADE IN BRAZIL" 0 | | NC |
|---|----------|--------------------------------------|--|----|

| USE | REF NO. | LANE 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|------------|-----------------|--------------------|-------------------------|
|-----|------------|-----------------|--------------------|-------------------------|

ELECTRICAL**BEACON ROTATING**

| | | | | |
|---|----------|----------------------------|---|----------|
| P | 449-6298 | BEACON, ROTATING | 3 | \$427 |
| | | | 3 | \$427 NI |

ALSO AVAILABLE ON A MISCELLANEOUS ORDER

LIGHTS UPGRADED

| | | | | |
|---|----------|----------------------------|---|----------|
| P | 452-6686 | LIGHTS, UPGRADED | 5 | \$227 |
| | | | 5 | \$227 NI |

ALSO AVAILABLE ON A MISCELLANEOUS ORDER
4 additional lights for increased nighttime visibility**MODULES**

| | | | | |
|---|----------|---------------------------------------|---|------------|
| P | 386-5611 | MODULE, RECORDING, FIX FREQ | 7 | \$6,400 |
| | | | 7 | \$6,400 NI |

ALSO AVAILABLE ON A MISCELLANEOUS ORDER
Factory installed fixed frequency recording module required for
French market
ONLY FOR USE WITH: 386-5371 CP44B VIBRATORY COMPACTOR
386-5324 FREQUENCY, FIXED and
431-3557 CAB, ROPS/FOPS W/HTR or
391-0157 CAB, ROPS/FOPS W/ HTR & AC

| | | | | |
|---|----------|---------------------------------------|---|------------|
| P | 386-5670 | MODULE, RECORDING, VARIABLE | 7 | \$6,400 |
| | | | 7 | \$6,400 NI |

ALSO AVAILABLE ON A MISCELLANEOUS ORDER
Factory installed variable frequency recording module required
for French market
ONLY FOR USE WITH: 386-5371 CP44B VIBRATORY COMPACTOR
386-5334 FREQUENCY, VARIABLE and
431-3557 CAB, ROPS/FOPS W/HTR or
391-0157 CAB, ROPS/FOPS W/ HTR & AC**GUARDS**

| | | | | |
|---|----------|-------------------------------|----|------------|
| P | 386-5456 | GUARD, TRANSMISSION | 44 | \$1,115 |
| | | | 44 | \$1,115 NI |

ALSO AVAILABLE ON A MISCELLANEOUS ORDER
Protection for the rear axle, hydraulic drive motor and hose
fittings
REQUIRED BY: EU DEALERS**FACTORY SOURCED KITS**

| | | | | |
|---|----------|--------------------------------|-------|-------------|
| P | 465-1000 | BLADE, LEVELING, FLD | 1,121 | \$10,920 NI |
|---|----------|--------------------------------|-------|-------------|

ALSO AVAILABLE ON A MISCELLANEOUS ORDER
INCLUDES:
Field installed components for leveling blade

| USE | REF NO. | LANE 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|------------|-----------------|--------------------|-------------------------|
|-----|------------|-----------------|--------------------|-------------------------|

DOCUMENTATION***CERTIFICATES***

| | | | |
|---|----------|---|----|
| L | 354-8706 | YEAR OF MANUFACTURE PLATE 0 | NC |
| | | Plate attached to PIN plate showing year of Final Plant Shipping date. May use on all machines, but required for shipping to Brazil. REQUIRED BY: South America dealers | |

| | | | |
|---|---------|-----------------------------------|----|
| P | 0P-1870 | CERTIFICATE OF ORIGIN 0 | NC |
|---|---------|-----------------------------------|----|

PACKING

| | | | |
|--|---------|------------------------------|-----------|
| | 0P-4505 | ROLL ON-ROLL OFF 0 | \$900 NET |
|--|---------|------------------------------|-----------|

| | | | |
|--|---------|--|----|
| | 0P-6706 | BUNDLE EXPORT PACKING 0 | NC |
| | | This OP should be ordered for all miscellaneous orders | |