Roadtec Pricing Effective 7/1/2021

Quoted Item		Price Code	List Price	Customer Configuration
MTV-1100 – Material Transfer Vehicle				
	MTV-1100e STANDARD FEATURES:			
	Truck dump front hopper with two ground control boxes & swivelling support casters			
	Hydraulic adjustable push rollers			
	Hydraulic baffle on dump hopper			
	600 TPH truck unloading conveyor (C-1) with dual roller bushing chain and ½" Ni-hard floor liners			
	Triple Pitch Augers in C-1			
	600 TPH loading conveyor (C-3) with ½" 500 BHN floor liners			
	Paver loading conveyor (C-3) swings 55 degrees to either side			
	Insulated C-3 conveyor floor			
	Paver loading conveyor (C-3) bump bars			
	C-3 Maximum Discharge Height is 12'-0"			
	Four (4) 17.5" x 25" Tires			
	Hydrostatic Four Wheel Drive, Front Wheel Steer			
	Two (2) Comfort Drive™ Finger Tip Control Operators Stations with Single Joystick Travel Control			
	Hydraulic Cleanout Doors on All Conveyors			
	Remote Lubrication Points for C-1 Conveyor			
	24 Volt Electrical System with Master Disconnect Switches			
	Power Pack for hydraulic control without running engine			
	Amber Warning Beacon			
	One (1) Operators Umbrella			
	Mirror Package			
	Retractable Wash-down System with 50' Hose Length			
	120 Gallon Fuel Tank Capacity			
	Road Light Package - Five 24V work lights installed on machine			
	MTV-1100e Cummins QSB6.7, 6 cylinder, 250 HP (186 kW), Tier IV Final	04-1100-01-0001	$ 493,320	$ -
	MTV-1100 OPTIONS:			
	Auxiliary Power			
	4KW 60 Hz Continuous Duty Hydraulic Generator	04-1100-02-0001	$ 8,065	$ -
	Additional Lighting			
	24V LED Night Light Package Includes 5 24V Wide Flood Lights Mounted At Machine Corners and on C-3.	04-1100-02-0003	$ 4,100	$ -
	Truck Dump Signal Light LED Signal light to indicate to truck driver whether to dump, stop or lower.	04-1100-02-0004	$ 3,610	$ -
	Dump Hopper Landing Lights Lights located on both sides of hopper opening for trucks to use as a guide.	04-1100-02-0022	$ 1,360	$ -
	Mass Flow Hopper Inserts			
	Mass Flow Low Profile Hopper Insert for 8' Pavers - Not Self-Relieving	04-1100-02-0005	$ 9,320	$ -
	Mass Flow Hopper Side Wall Extensions - for 8' Pavers	04-1100-02-0006	$ 895	$ -
	RP-170/175 Self Relieving Hopper Insert	04-1100-02-0028	$ 9,320	$ -
	RP-170/175 Hopper Insert Side Wall Extensions	04-1100-02-0029	$ 1,000	$ -
	RP-190 Self-Relieving Hopper Insert	04-1100-02-0009	$ 9,320	$ -
	RP-190 Self-Relieving Hopper Sidewall Extensions	04-1100-02-0010	$ 895	$ -
	RP-195 Self-Relieving Hopper Insert	04-1100-02-0011	$ 9,320	$ -
	RP-195 Self-Relieving Hopper Sidewall Extensions	04-1100-02-0012	$ 895	$ -
	Univeral Design Self-Relieving Hopper Insert for 10' Pavers Does not provide all anti-segregation features of machine specific hopper inserts	04-1100-02-0013	$ 9,320	$ -
	Universal Design Self-Relieving Hopper Sidewall Extensions	04-1100-02-0014	$ 895	$ -
	Miscellaneous			
	Guardian Telematics System Roadtec GuardianTM Telematics System to send and receive data remotely, with the ability to change function settings (One Year Free Subscription)	04-1100-02-0026	$ 8,700	$ -
	Canopy for Main Operator's Station Fiberglass canopy with slide out shades on each side. Hydraulically raise and lower.	04-1100-02-0027	$ 7,030	$ -

	Lincoln Lube Automated Lubrication System	04-1100-02-0015	$	8,340	$ -
	Truck Hitch In Lieu of Push Rollers	04-1100-02-0016	$	16,620	$ -
	Tire Spray System Includes spray bars, piping, water tank, and controls	04-1100-02-0023	$	6,745	$ -
	Environmental Tank Spray Down System Includes 32 Gallon Tank, Pump, Retractable Hose Reel with 50' Hose Length (Replaces Standard Wash-down)	04-1100-02-0017	$	3,015	$ -
	Automated Release Agent Spray Down System Replaces standard washdown and cannot be selected with Environmental Washdown. Includes 50 gal. Tank, control and pump assembly that will supply 10-spray nozzles located on C-1, and C-3 conveyors. Release agent is distributed to each of the 10 spray nozzles for approximately 2-3 minutes with a controlled timer. 1-hand wand is also included on machine for external use. Pump and fittings supplied will work with most available release agents. Filters are located on the suction and in each spray nozzle assembly.	04-1100-02-0025	$	6,800	$ -
	Autotracking Package System to have MTV maintain distance and pace in front of paver. Can automatically bring machine to full stop and restart as needed. Includes 1 sensor, 2 light towers, 1 operator console controls, and auto-leveling hardware.	04-1100-02-0024	$	12,550	$ -
	Automatic Feed Control System Controls C2 and C3 output based on HMA level in PAVER hopper. Includes 1 sonic sensor, feeder control for operator console, mounting hardware, necessary electrical components and wiring (Requires Autotracking Package)	04-1100-02-0019	$	5,550	$ -

Warranties				
Roadtec Edge Extended Warranty (3 years or 3,000 hours total)	04-1100-05-0001	$	8,100	$ -
Manufacturer's Extended Engine Warranty (5 years or 6,000 hours total)	04-1100-05-0002	$	3,820	$ -

Roadtec Pricing Effective 7/1/2021

Quoted Item		Price Code	List Price	Customer Configuration
MTV-1105 – Tracked Material Transfer Vehicle				
	MTV-1105e STANDARD FEATURES:			
	Truck dump front hopper with two ground control boxes & swivelling support casters Hydraulic adjustable push rollers Hydraulic baffle on dump hopper 600 TPH truck unloading conveyor (C-1) with dual roller bushing chain and ½" Ni-hard floor liners Triple Pitch Augers in C-1 600 TPH loading conveyor (C-3) with ½" 500 BHN floor liners Paver loading conveyor (C-3) swings 55 degrees to either side Insulated C-3 conveyor floor Paver loading conveyor (C-3) bump bars C-3 Maximum Discharge Height is 12'-0" Friction Drive Undercarriage 14" (355 mm) Wide, Steel Reinforced Rubber Track Band Two (2) Comfort Drive™ Finger Tip Control Operators Stations with Single Joystick Travel Control Hydraulic Cleanout Doors on All Conveyors Remote Lubrication Points for C-1 Conveyor 24 Volt Electrical System with Master Disconnect Switches Power Pack for hydraulic control without running engine Amber Warning Beacon One (1) Operators Umbrella Mirror Package Retractable Wash-down System with 50' Hose Length 120 Gallon Fuel Tank Capacity Road Light Package - Five 24V work lights installed on machine			
	MTV-1105e Cummins QSB6.7, 6 cylinder, 250 HP (186 kW), Tier IV Final	04-1105-01-0001	$ 602,190	$ -
				$ -
	MTV-1105 OPTIONS:			
	Auxiliary Power			
	4KW 60 Hz Continuous Duty Hydraulic Generator	04-1105-02-0001	$ 8,065	$ -
	Additional Lighting			
	24V LED Night Light Package Includes 5 24V Wide Flood Lights Mounted At Machine Corners and on C-3.	04-1105-02-0003	$ 4,100	$ -
	Truck Dump Signal Light LED Signal light to indicate to truck driver whether to dump, stop or lower.	04-1105-02-0004	$ 3,605	$ -
	Dump Hopper Landing Lights Lights located on both sides of hopper opening for trucks to use as a guide.	04-1105-02-0022	$ 1,360	$ -
	Mass Flow Hopper Inserts			
	Mass Flow Low Profile Hopper Insert for 8' Pavers - Not Self-Relieving	04-1105-02-0005	$ 9,320	$ -
	Mass Flow Hopper Side Wall Extensions - for 8' Pavers	04-1105-02-0006	$ 895	$ -
	RP-170/175 Self Relieving Hopper Insert	04-1105-02-0028	$ 9,320	$ -
	RP-170/175 Hopper Insert Side Wall Extensions	04-1105-02-0029	$ 895	$ -
	RP-190 Self-Relieving Hopper Insert	04-1105-02-0009	$ 9,320	$ -
	RP-190 Self-Relieving Hopper Sidewall Extensions	04-1105-02-0010	$ 895	$ -
	RP-195 Self-Relieving Hopper Insert	04-1105-02-0011	$ 9,320	$ -
	RP-195 Self-Relieving Hopper Sidewall Extensions	04-1105-02-0012	$ 895	$ -
	Univeral Design Self-Relieving Hopper Insert for 10' Pavers Does not provide all anti-segregation features of machine specific hopper inserts	04-1105-02-0013	$ 9,320	$ -
	Universal Design Self-Relieving Hopper Sidewall Extensions	04-1105-02-0014	$ 895	$ -
	Miscellaneous			
	Guardian Telematics System	04-1105-02-0026	$ 8,700	$ -

	Roadtec GuardianTM Telematics System to send and receive data remotely, with the ability to change function settings (One Year Free Subscription)				
	Canopy for Main Operator's Station Fiberglass canopy with slide out shades on each side. Hydraulically raise and lower.	04-1105-02-0027	$ 7,030	$	-
	Lincoln Lube Automated Lubrication System	04-1105-02-0015	$ 8,340	$	-
	Truck Hitch In Lieu of Push Rollers	04-1105-02-0016	$ 16,620	$	-
	Environmental Tank Spray Down System Includes 32 Gallon Tank, Pump, Retractable Hose Reel with 50' Hose Length (Replaces Standard Wash-down)	04-1105-02-0017	$ 3,015	$	-
	Extra Large Tank for Environmental Spray Down System Adds larger tank for the Environmental Tank Spray Down System - should be paired with full system above.	04-1105-02-0018	$ 4,085	$	-
	Automated Release Agent Spray Down System Replaces standard washdown and cannot be selected with Environmental Washdown. Includes 50 gal. Tank, control and pump assembly that will supply 10-spray nozzles located on C-1, and C-3 conveyors. Release agent is distributed to each of the 10 spray nozzles for approximately 2-3 minutes with a controlled timer. 1-hand wand is also included on machine for external use. Pump and fittings supplied will work with most available release agents. Filters are located on the suction and in each spray nozzle assembly.	04-1105-02-0025	$ 6,800	$	-
	Powered Chain Tension C1	04-1105-02-0020	$ 7,460	$	-
	Powered Chain Tension C3	04-1105-02-0021	$ 7,460	$	-
	Autotracking Package Includes 1 ultrasonic sensor, 2 light towers, 1 operator console switch, 2 (left/right) C1 console switches, mounting hardware, and pendant.	04-1105-02-0024	$ 12,550	$	-
	Automatic Feed Control System Controls C2 and C3 output based on HMA level in PAVER hopper. Includes 1 sonic sensor, feeder control for operator console, mounting hardware, necessary electrical components and wiring (Requires Autotracking Package)	04-1105-02-0030	$ 5,550	$	-
	Warranties				
	Roadtec Edge Extended Warranty (3 years or 3,000 hours total)	04-1500-05-0001	$ 14,125	$	-
	Manufacturer's Extended Engine Warranty (5 years or 6,000 hours total)	04-1105-05-0002	$ 3,820	$	-

Roadtec Pricing Effective 7/1/2021

Quoted Item	Option Not Included		Price Code	List Price	Customer Configuration
SB-1500 SHUTTLE BUGGY – Material Transfer Vehicle					
		SB-1500 STANDARD FEATURES:			
		Truck Dump Front Hopper with Two Ground Control Boxes & Swivel Support Casters			
		Roadtec Guardian TM Telematics System to send/receive data remotely, change function settings (1Yr Free Subscription)			
		Hydraulic Adjustable Push Rollers			
		Pivoting Curved Hydraulic Baffle Design Improves Material Flow			
		600 TPH Truck Unloading Conveyor (C-1) with Dual Roller Bushing Chain and ¾" Ni-Hard Floor Liners			
		15 Ton Storage Capacity Hopper with Triple-Pitch Antisegregation Remix Auger			
		600 TPH Split (C-2) Conveyor with ¾" Ni-Hard Floor Liners			
		600 TPH Loading Conveyor (C-3) with ½" 500 BHN Floor Liners			
		Paver Loading Conveyor (C-3) Swings 45 Degrees to Either Side			
		Insulated C-3 Conveyor Floor			
		Paver Loading Conveyor (C-3), Guard Rails Standard			
		C-3 Discharge Height is 10'-9"			
		Four (4) 18:00 x 25" High Flotation Tires			
		Hydrostatic Four (4) Wheel Drive, Front Wheel Steer			
		Raising Operators Platform with Dual Seats			
		FXS Fume Extraction System with Dual Fans			
		One Piece Hydraulic Raisable Hood for Quick Engine Access			
		Hinged Access Door to Oil Cooler, Radiator and Pumps			
		Hydraulic Cleanout Doors on All Conveyors			
		Remote Lubrication Points for C-1 and C-2 Conveyors			
		24 Volt Starting System with Master Disconnect Switches			
		Amber Beacon			
		One (1) Operators Umbrella			
		Mirror Package			
		Retractable Wash-down System with 50' Hose Length			
		135 Gallon Fuel Tank Capacity			
		Road Light Package - Five 24 V work lights installed on machine			
		SB-1500e	04-1500-01-0001	$ 593,835	$ -
		Cummins QSL9 Tier IV Final			
		SB-1500 OPTIONS:			
		Auxiliary Power			
		4KW 60 Hz 120V Continuous Duty Hyd. Gen. w/ Outlets	04-1500-02-0001	$ 8,725	$ -
		4KW 50 Hz 240V Continuous Duty Hyd. Gen. w/ Outlets	04-1500-02-0002	$ 9,505	$ -
		(For European/CE Standards)		$ -	$ -
		4KW 60 Hz 240V Continuous Duty Hyd. Gen. w/ Outlets	04-1500-02-0003	$ 9,505	$ -
		(For Australian Standards)		$ -	$ -
		6.2KW 60 Hz 120V Continuous Duty Hyd. Gen. w/ Outlets	04-1500-02-0004	$ 11,360	$ -
		Electrical Outlets	04-1500-02-0005	$ 660	$ -
		Four (4) electrical outlets - one at each corner of machine			
		Additional Lighting			
		24V LED Night Light Package	04-1500-02-0006	$ 4,100	$ -
		Includes Five 24V Lights mounted at machine corners and on C-3			
		Truck Dump Signal Light	04-1500-02-0007	$ 3,605	$ -
		LED Signal light to indicate to truck driver whether to dump, stop or lower.			
		Dump Hopper Landing Lights	04-1500-02-0029	$ 1,360	$ -
		Lights located on both sides of hopper opening for trucks to use as a guide.			

Mass Flow Hopper Inserts					
Mass Flow Low Profile Hopper Insert for 8' Pavers - Not Self Relieving	04-1500-02-0008	$	9,320	$	-
Mass Flow Hopper Side Wall Extensions - for 8' Pavers	04-1500-02-0009	$	895	$	-
RP-170/175 Self Relieving Hopper Insert	04-1500-02-0037	$	9,320	$	-
RP-170/175 Hopper Insert Side Wall Extensions	04-1500-02-0038	$	895	$	-
RP-190 Self Relieving Hopper Insert	04-1500-02-0012	$	9,320	$	-
RP-190 Self Relieving Hopper Sidewall Extensions	04-1500-02-0013	$	895	$	-
RP-195 Self Relieving Hopper Insert	04-1500-02-0014	$	9,320	$	-
RP-195 Self Relieving Hopper Sidewall Extensions	04-1500-02-0015	$	895	$	-
Universal Design Self Relieving Hopper Insert	04-1500-02-0016	$	9,320	$	-
Does not provide all anti-segregation features of machine specific hopper inserts					
Universal Design Self Relieving Hopper Sidewall Extensions	04-1500-02-0017	$	895	$	-

Miscellaneous					
Lincoln Lube Automated Lubrication System	04-1500-02-0018	$	10,785	$	-
Vandal Covers	04-1500-02-0032	$	2,890	$	-
Includes vandal covers for ground boxes, operator's station and C1 manifold					
Truck Hitch In Lieu of Push Rollers	04-1500-02-0019	$	16,615	$	-
Tire Spray System	04-1500-02-0033	$	7,460	$	-
Includes spray bars, piping, water tank, wiring, and controls					
Environmental Tank Spray Down System	04-1500-02-0020	$	3,015	$	-
Includes 55 Gallon Tank, Pump, Retractable Hose Reel with 50' Hose Length (Replaces Standard Wash-down)					
Automated Release Agent Spray Down System	04-1500-02-0021	$	12,010	$	-
Replaces standard washdown and cannot be selected with Environmental Washdown. Includes 50 gal. Tank, control and pump assembly that will supply 16-spray nozzles located on C-1, C-2 and C-3 conveyors. Release agent is distributed to each of the 16 spray nozzles for approximately 2-3 minutes with a controlled timer. 4-hand wands are also included - 2 front and 2 rear on machine for external use. Pump and fittings supplied will work with most available release agents. Filters are located on the suction and in each spray nozzle assembly.					
Autotracking Package	04-1500-02-0031	$	14,400	$	-
Includes 1 ultrasonic sensor, 2 light towers, 1 operator console switch, 2 (left/right) C1 console switches, mounting hardware, pendant					
Automatic Feed Control System	04-1500-02-0034	$	5,550	$	-
Controls C2 and C3 output based on HMA level in PAVER hopper. Includes 1 sonic sensor, feeder control for operator console, mounting hardware, necessary electrical components and wiring (Requires Autotracking Package)					
C2 Level Indication System	04-1500-02-0024	$	5,625	$	-
Two sonic sensors to monitor material level in main hopper of Shuttle Buggy MTV. Lights on operators station and atop C1 indicate hopper level.					
Canopy for Main Operator's Station	04-1500-02-0036	$	7,030	$	-
Fiberglass canopy with slide out shades on each side. Hydraulically raise and lower.					
Camera System	04-1500-02-0026	$	5,680	$	-
Includes magnetic base weather sealed box with monitor and 2 remote night vision cameras with adjustable magnetic base.					

Material Heads For C-1					
Windrow Pick Up Head In-Lieu of Dump Hopper	04-1500-02-0027	$	19,785	$	-
Windrow Pick Up Head Assembly as Spare	04-1500-02-0028	$	30,155	$	-
Windrow Head Includes Oscillating C-1 Pivot, Hinged Adjustable Scraper Edge and Spring Activated End Gates					

Warranties					
Roadtec Edge Extended Warranty (3 years or 3,000 hours total)	04-1500-06-0001	$	13,925	$	-
Manufacturer's Extended Engine Warranty (5 years or 6,000 hours total)	04-1500-06-0002	$	4,400	$	-

Quoted Item		Price Code	List Price	Customer Configuration

SB-3000 SHUTTLE BUGGY – Material Transfer Vehicle

SB-3000 STANDARD FEATURES:

Truck Dump Front Hopper with Swivel Support Casters
Roadtec Guardian TM Telematics System to send/receive data remotely, change function settings (1Yr Free Subscription)
Inset Ground Operator Stations on each side of C1 for control while protected from traffic intrusions
Oscillating, Hydraulic Adjustable Push Rollers
Hydraulic Baffle Improves Material Flow
1,000 TPH Truck Unloading Conveyor (C-1) with Larger Offset Dual Roller Bushing Chain
25 Ton Storage Capacity Hopper with Triple-Pitch Antisegregation Remix Auger
26" Cast Remixing Augers in Main storage hopper
600 TPH (C-2) Conveyor with Larger Offset Dual Roller Bushing Chain
600 TPH Loading Conveyor (C-3) with Larger Offset Dual Roller Bushing Chain
Paver Loading Conveyor (C-3) Discharge Swings 14'9" to Either Side with Standard Guard Rails
Insulated C-3 Conveyor Floor
Four (4) Low Profile, High Flotation Tires
Hydrostatic Four (4) Wheel Drive, Front Wheel Steer
Dual Operators Control stations with 90° swing out for complete machine side visibility
Comfort Drive™ armrest consoles for all day comfortable operation
FXS Fume Extraction System with solid mount exhaust tube
Ground Level Engine for Quick Access to all regular maintenance
Hydraulic Cleanout Doors on All Conveyors
Remote Lubrication Points for All Conveyors
24 Volt Electrical System with Master Disconnect Switch
Amber Warning Beacon
One (1) Operators Umbrella
Mirror Package
Standard Wash-down System with three easy-access hoses
140 Gallon Fuel Tank Capacity for 12 hours of paving
Standard Lights - Large light bars front and back of machine for machine loading and unloading

	SB-3000 Cummins B6.7 310 HP Stage V / Tier 4f Diesel Engine	04-3000-01-0001	$ 628,210	$	-

SB-3000 OPTIONS:

	Additional Lighting				
	Night Work Premium Lighting Package Lights on ground operator, wheels, and ladders for extra visibility close to the machine. System stays on one minute after machine is turned off to assist egress	04-3000-02-0001	$ 4,100	$	-
	Truck Signal Light Light system to communicate to trucks, built into base of seat(s). Please use Notes to indicate Left, Right, or both (order qty 2)	04-3000-02-0002	$ 3,610	$	-
	Dump Hopper Landing Lights Projectors mounted on the edges of the dump hopper to guide trucks back to the machine	04-3000-02-0003	$ 1,355	$	-
	Turn Signal and Brake Lights	04-3000-02-0004	$ 1,349	$	-
	LED Work Lights with Magnetic Base	04-3000-02-0005	$ 325	$	-
	Operator Packages				
	Adaptive Cruise Control Set a distance between Shuttle Buggy and Paver to be automatically maintained. Adapts to changes in paver speed	04-3000-03-0001	$ 4,493	$	-
	C2 Level Indicator Two sonic sensors to monitor material level in main hopper of Shuttle Buggy MTV. Lights on operators stations (main and ground) indicate hopper level.	04-3000-03-0002	$ 5,625	$	-
	Material Flow Control (C2 / C3) Machine's C2 and C3 speeds are controlled to maintain the optimal pile height in the paver hopper insert at all times.	04-3000-03-0003	$ 2,960	$	-
	Seat Canopy Shade canopy over the main operator seat with powered raise / lower for easy adjustment. Includes overhead fan to help keep comfortable by moving air all day. Please use Notes to indicate Left, Right, or both (order qty 2)	04-3000-03-0004	$ 2,730	$	-
	Four Wheel Steer Steer all wheels on the machine for improved maneuverability. Includes capability of Front Only, Coordinated, Crab, and Rear Only.	04-3000-03-0006	$ 9,310	$	-
	Automatic Lubrication Connected to the Guardian telematics system for remote access to run history and empty tub warning.	04-3000-03-0007	$ 12,080	$	-
	C3 Horn Kit	04-3000-03-0008	$ 1,130		
	Side View Camera System	04-3000-03-0009	$ 5,415		
	Wash Down				
	Environmental Washdown	04-3000-04-0001	$ 4,120	$	-

Converts standard three coil hoses for washdown to use water-based release agent. Built with dosing system that receives 5 gallon of full strength release agent. Includes 110 gallon water tank and all hardware.					
Auto Chain Spray (Diesel)	04-3000-04-0002	$	7,900	$	-
Includes 16 nozzles to spray release agent directly on all conveyor chains and sprockets to significantly improve longevity of wear parts. Uses machine diesel fuel.					
Auto Chain Spray (Environmental)	04-3000-04-0003	$	7,900	$	-
Includes 16 nozzles to spray release agent directly on all conveyor chains and sprockets to significantly improve longevity of wear parts. Uses water tank and dosing system from Environmental Washdown option (must order that option separately).					
Tire Spray	04-3000-04-0004	$	5,700	$	-
Sprays water on each tire as machine moves forward to help prevent buildup of tack or HMA. Includes 110 gallon water tank and all hardware.					
Conveyor Packages					
Powered Chain Tension C1	04-3000-05-0001	$	3,951	$	-
Powered Chain Tension C2 / C3	04-3000-05-0002	$	7,901	$	-
Quick Change Windrow Pick-up Head in Addition to Dump Hopper	04-3000-05-0003	$	38,415	$	-
Option adds the Windrow head as built with the Quick Change system – includes all necessary equipment to run Truck Dump Head or Windrow Pick Up Shuttle Buggy. Please include Note to designate which head should be mounted on machine at shipment.					
Quick Change Windrow Pick-up Head in-lieu of Dump Hopper	04-3000-05-0004	$	23,225	$	-
Option adds the Windrow head as built with the Quick Change system – includes all necessary equipment to run Windrow Pick Up Shuttle Buggy. Does NOT include Truck Dump head.					
Pintle Hook Relief on C1 Dump Hopper	04-3000-05-0006	$	1,915	$	-
Extended Push Rollers	04-3000-05-0007	$	2,055	$	-
Heavy Duty (Clad Liners)	04-3000-05-0008	$	15,975	$	-
Chromium Carbide liners in all conveyors to increase the longevity of wear parts.					
Truck Hitch	04-3000-05-0009	$	16,290	$	-
In Lieu of Push Rollers					
Auxiliary Power					
4KW 60 Hz 120V Continuous Duty Hyd. Gen. w/ Outlets	04-3000-06-0001	$	8,725	$	-
4KW 50 Hz 240V Continuous Duty Hyd. Gen. w/ Outlets	04-3000-06-0002	$	9,505	$	-
(For European/CE Standards)					
4KW 60 Hz 240V Continuous Duty Hyd. Gen. w/ Outlets	04-3000-06-0003	$	9,505	$	-
(For Australian Standards)					
Mass Flow Hopper Inserts					
Mass Flow Low Profile Hopper Insert for 8' Pavers - Not Self Relieving	04-3000-07-0001	$	9,320	$	-
Mass Flow Hopper Side Wall Extensions - for 8' Pavers	04-3000-07-0002	$	895	$	-
RP-170/175 Self Relieving Hopper Insert	04-3000-07-0003	$	9,320	$	-
RP-170/175 Hopper Insert Side Wall Extensions	04-3000-07-0004	$	895	$	-
RP-190 Self Relieving Hopper Insert	04-3000-07-0005	$	9,320	$	-
RP-190 Self Relieving Hopper Sidewall Extensions	04-3000-07-0006	$	895	$	-
RP-195 Self Relieving Hopper Insert	04-3000-07-0007	$	9,320	$	-
RP-195 Self Relieving Hopper Sidewall Extensions	04-3000-07-0008	$	895	$	-
Universal Design Self Relieving Hopper Insert	04-3000-07-0009	$	9,320	$	-
Does not provide all anti-segregation features of machine specific hopper inserts					
Universal Design Self Relieving Hopper Sidewall Extensions	04-3000-07-0010	$	895	$	-
Miscellaneous					
Service Pendant for Engine Compartment	04-3000-08-0002	$	1,250	$	-
Allows for engine start, stop, conveyors forward and reverse, and C3 movement from the rear of the machine for service troubleshooting					
Warranties					
Roadtec Edge Extended Warranty (3years, 3,000 hours total)	04-3000-50-0001	$	15,165	$	-
Manufacturer's Extended Engine Warranty (5 years or 6,000 hours total)	04-3000-50-0002	$	3,820	$	-

Quoted Item		Price Code	List Price	Customer Configuration

RP-170 - 8' (2.5M) RUBBER TIRE ASPHALT PAVER

RP-170 STANDARD FEATURES:

1/2" (12.5 mm) Thick Continuous Side Sheet Frame Construction
4" (50 mm) Thick Front Cross Frame Member
Hydraulically Driven Fan
Oscillating Push Rollers
Direct Hydraulic Planetary Drive
11 Ton (11.2 MT) Capacity/202 ft3 (5.7 m3) Self Dumping Hopper
Electric Flow Gates
Independently Driven Variable Speed Feeder Conveyors with 3/8" (9.5 mm) Thick 400 BHN Liners
Hydraulically Raise, Lower and Tilting Auger Assembly
Hydraulically Operated Rear Frame Extensions for head of material control
16:00 x 24" (610 mm) Hydroflated High Flotation Sand Rib Drive Tires
Dual 12" (304 mm) x 22" (559 mm) Front Bogies
Two (2) Comfort Drive Operators Stations with Tilt Steering Wheel and Finger Tip Paver Control
Operators stations slide out past edge of machine for increased visibility
Steering Assist Provides Inside Turning Radius of 30" (.8 m)
24 Volt Starting System with Master Disconnect Switch
Clearview FXS Fume Extraction System
Amber Warning Beacon, Back Up Alarm and Fire Extinguisher
One (1) Operators Umbrella
Remote Central Point Tractor Lubrication
Lighted Dual Screed Control Stations for head of material and screed control with Fixed Remotes and lockable vandal covers
Retractable Wash-down System with 30' (9.1 m) Hose Length
105 Gallon (397 L) Fuel Tank Capacity
Conveyor By-Pass Permits Independent Operation of Feeders
Electrical wiring and hydraulic hoses for connection to screed

RP-170e Cummins QSB6.7 Tier 4 Final @ 174 hp	03-0170-01-0001	$ 293,720	$	-

RP-170 OPTIONS:

Undercarriage Options				
Front Wheel Assist Includes additional hydraulic motor on both rear bogie wheels.	03-0170-02-0001	$ 24,220	$	-
Screed Options				
Two-Speed Screed Heat High heat mode cuts power to auxilaries and increases generator output to cut screed heating time in half. Automatically switches to standard power mode when screed reaches pre-set temperature. (Does not pair with Eagle, EZ-R2.)	03-0170-02-0034	$ 2,625	$	-
Hydraulic Screed Assist Package Designed for use with Eagle Screed. Constant up pressure on screed essentially reducing its weight all the time while in Pave mode, whether in forward, neutral or reverse.	03-0170-02-0004	$ 3,180	$	-
Hydraulic Screed Boost Package Pressurizes the screed lift cylinders when the paver is in neutral and in pave mode to prevent depression in mat when paver stops. Lifting pressure is adjustable. Pressure is applied for adjustable time period once paver starts moving forward again. Time can be set at 0, 3 or 6 seconds.	03-0170-02-0005	$ 2,815	$	-
Auto Feed Control Paddle Sensor Incudes standardsonic feed sensors as well as paddle sensor. Machine Screed Control Box will have switch to select desired sensor.	03-0170-02-0008	$ 5,165	$	-
Electrical and Lighting Options				
24V LED Night Light Package	03-0170-02-0009	$ 4,455	$	-
Saber Light	03-0170-02-0011	$ 4,275	$	-

Two 92-watt, LED light panels provide over 10,000 lumens					
Airstar Balloon Light Assembly	03-0170-02-0012	$	4,370	$	-
Includes Two 1,000 W Halogen Bulbs, Fan, Telescoping Pole, Two Brackets & Case					
Laser Pointer Alignment Guide	03-0170-02-0013	$	3,315	$	-
High intensity laser mounted to tractor can be positioned along line of travel to aid operator in aligning paver correctly.					
Truck Dump Signal Light	03-0170-02-0032	$	3,405	$	-
LED Signal light to indicate to truck driver whether to dump, stop or lower.					

Material Feed System Options					
12” Left Hand ¾” Thick Ni-Hard Auger Extension	03-0170-02-0015	$	1,295	$	-
12” Right Hand ¾” Thick Ni-Hard Auger Extension	03-0170-02-0016	$	1,295	$	-
12” Tunnel Extension (Either Handed)	03-0170-02-0017	$	485	$	-
12” Hydraulic Tunnel Extensions	03-0170-02-0018	$	6,255	$	-
Auger Extension Remotes	03-0170-02-0051	$	1,525	$	-
6' Tunnel and Auger Extension Package	03-0170-02-0019	$	14,480	$	-
Extends Augers and Tunnels 3' to each side. Includes all necessary hardware to extend augers and tunnels 3' to each side including outboard auger bearing supports and tunnel extension braces. An additional 1' auger extension and 2- 1' tunnel extension segments can be added to each side. Does not include any screed extensions.					

Miscellaneous					
Guardian Telematics System	03-0170-02-0030	$	8,615	$	-
Roadtec GuardianTM Telematics System to send and receive data remotely, with the ability to change function settings (One Year Free Subscription)					
Truck Hitch In Lieu of Push Rollers	03-0170-02-0021	$	15,660	$	-
Lincoln Lube Automated Lubrication System	03-0170-02-0022	$	10,165	$	-
Reversing Distribution Augers	03-0170-02-0023	$	1,925	$	-
Additional Umbrella	03-0170-02-0024	$	130	$	-
Environmental Release Agent Spray Down System	03-0170-02-0026	$	2,845	$	-
Includes 13 Gallon (49 L) Tank and Pump (Replaces Standard Wash-down)					
Soft Rubber front flashing	03-0170-02-0031	$	205	$	-

Mass Flow Hopper Inserts					
RP-170/175 Self Relieving Hopper Insert	03-0170-02-0032	$	9,230	$	-
RP-170/175 Hopper Insert Side Wall Extensions	03-0170-02-0033	$	885	$	-
Mass Flow Low Profile Hopper Insert for 8' Pavers - Not Self Relieving	03-0170-02-0028	$	9,230	$	-
Mass Flow Hopper Side Wall Extensions - for 8' Pavers	03-0170-02-0048	$	885	$	-

Screed Automation - Grade And Slope Control					
TOPCON Sonic Grade And Slope Control	03-0170-03-0007	$	16,835	$	-
Features Dual Sonic Grade Sensors And Single Slope Sensor.					
MOBA-MATIC II Sonic Grade And Slope Control	03-0170-03-0008	$	20,120	$	-
Features MOBA MATIC II controller with Dual Sonic Grade Sensors And Slope Sensor.					
TOPCON Sonic Averaging Ski With Hardware	03-0170-03-0009	$	15,915	$	-
Includes 3 Additional Sonic Trackers. (Requires Topcon Sonic Grade and Slope System)					
MOBA Sonic Averaging Ski With Hardware	03-0170-03-0010	$	15,915	$	-
Includes 2 Additional Sonic Trackers. (Requires MOBA Sonic Grade and Slope System)					
MOBA Mounting Kit	03-0170-03-0011	$	2,605	$	-
Provides hardware to easily install existing MOBA Grade & Slope System. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)					
MOBA Slope Sensor	03-0170-03-0012	$	1,800	$	-
MOBA Ski Hardware	03-0170-03-0013	$	6,240	$	-
Provides physical ski, arms, sensor mounting poles, ski mounting harware, and junction box to plug in sensors. (Does not include sensor cables.)					
TOPCON Mounting Kit	03-0170-03-0014	$	3,165	$	-

Provides hardware to easily install existing TOPCON Grade & Slope. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)

TOPCON Slope Sensor	03-0170-03-0015	**$**	**2,270**	**$**	**-**

SCREEDS

S-8 FIXED WIDTH SCREED

S-8 STANDARD FEATURES:

8' (2.4m) Vibratory Standard Screed with 3' (0.9m) Hydraulic Strike-offs
26" (660 mm) Long, ½" (12.5 mm) Thick 400 BHN Screed Plate
Strike-off Articulation from 6.6% Positive to 3.3% Negative
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM
Power Crown, 3"(75 mm) Positive to 1" (25 mm) Negative
Individual Lead and Tail Crown Adjustment
18" (457 mm) Wide Full Width Hinged Heavy Duty Walkway
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Screed Plate Temperature Thermostatically Controlled with Adjustable Set Point
4 KW @ 120 Volts Available for Accessory Use or Lighting
Heater Hold-down System Allows Heater Change Without Removing the Screed Plate
Spring Loaded Two Piece End Gates
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

S-8	03-0170-04-0001	**$**	**76,265**	**$**	**-**

S-8 OPTIONS:

Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0170-04-0011	**$**	**-**	**$**	**-**
Counter-Clockwise Raise Angle of Attack Screws Clockwise lowers - "Roadtec Standard"	03-0170-04-0012	**$**	**-**	**$**	**-**
Screed Extensions					
6" Screed Extension	03-0170-04-0002	**$**	**3,845**	**$**	**-**
12" Screed Extension With Heat	03-0170-04-0003	**$**	**4,290**	**$**	**-**
24" Screed Extension With Heat and Vibration	03-0170-04-0004	**$**	**5,645**	**$**	**-**
Attachments					
Left Hand Safety Edge Beveled Endgate Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	03-0170-04-0005	**$**	**2,680**	**$**	**-**
Right Hand Safety Edge Beveled Endgate Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	03-0170-04-0006	**$**	**2,680**	**$**	**-**
Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0170-04-0017	**$**	**460**	**$**	**-**

EZ-IV-8 FRONT EXTENDABLE SCREED

EZ-IV-8 STANDARD FEATURES:

8' (2.4 m) to 15' (4.5 m) Hydraulically Extendable Carlson Easy Screed IV with Wide Blade Electric Heat
One 4' (1.2 m) Long & One 3' (0.9 m) Long Front Mounted Extensions
Extensions Move on High Composite Bushings & Chrome Slide Track
Extensions are 8" (203 mm) Wide, with Heat, Vibration and Adjustable Angle of Attack
Front Mounted Extensions Provide 9% Positive Slope
Electric Valves Control In/Out, Slope & Vertical Height
Carlson's Patented "Front Taper Design" Main Screed
Main Screed is 26" (660 mm) Long, ½" (12.5 mm) Thick 400 BHN Screed Plate

Power Crown, 2½” (63 mm) Positive to ¾” (19 mm) Negative
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Thermostatically Controlled Plate Temperature with Analog Display
5.5 KW @ 120 Volts Available for Accessory Use in 8 Outlets
Heater Hold Down System Allows Heater Change Without Removing the Screed Plate
Electrically Heated Oven for Warming Meals
Spring Loaded Two Piece End Gates
20” (508 mm) Wide Main Screed Hinged Heavy Duty Walkway
12” (304 mm) Wide Hinged Extension Walkways
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

EZ-IV-8	03-0170-06-0001	**$**	**87,975**	**$**	**-**

EZ-IV-8 OPTIONS:

Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0170-06-0019	**$**	**-**	**$**	**-**
Counter-Clockwise Raise Angle of Attack Screws Clockwise lowers - "Roadtec Standard"	03-0170-06-0020	**$**	**-**	**$**	**-**
Screed Options					
Pair of 12" Bolt-on Screed Extensions with Heat, Left and Right	03-0170-06-0002	**$**	**4,685**	**$**	**-**
Pair of 18" Bolt-on Screed Extensions with Heat, Left and Right	03-0170-06-0003	**$**	**4,795**	**$**	**-**
Pair of 24" Bolt-on Screed Extensions with Heat, Left and Right	03-0170-06-0004	**$**	**4,910**	**$**	**-**
Beveled Edger for "Tapered Notch" For 12" Tapered Notched Wedge Joint One edger fits left or right side Heated	03-0170-06-0005	**$**	**3,785**	**$**	**-**
Hydraulic Berm Builder with Electric Control Valves (Single Side) Manual Adjust not Available - 12”	03-0170-06-0006	**$**	**2,880**	**$**	**-**
Pair of Additional 6” Cut-off Shoes	03-0170-06-0007	**$**	**255**	**$**	**-**
Left Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0170-06-0008	**$**	**2,605**	**$**	**-**
Right Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0170-06-0009	**$**	**2,605**	**$**	**-**
Pair of Heated End Gates	03-0170-06-0010	**$**	**1,630**	**$**	**-**
Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0170-06-0012	**$**	**445**	**$**	**-**

EZ-R2-08 REAR EXTENDABLE SCREED

EZ-R2-08 STANDARD FEATURES:

8’ to 15’6" Hydraulically Extendable Screed with Integral Rear Mounted Extensions
Electric Heat with Thermostatically Controlled Temperature
Screed Plates are 20 Wide, ½ Thick 450 BHN Material.
Fully adjustable screed plates with adjustment cones on main and extensions.
Fully adjustable Pre Strike-Off on Main and extensions
Extensions Supported by Two 4 Guide tubes with Teflon Bushings.
Exclusive Carlson slide track system allowing for adjustment of extension parallel
Independent Angle of Attach Adjustments for Extensions.
Extensions Provide 12% Positive Slope to 5% Negative Slope.
Power Crown Provides 2" Positive to 1" Negative.
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM.
18" Wide Full Width Telescoping Heavy Duty Walkway.

Electric Valves Control Extensions, Slope, Crown & Vertical Height.
Full Length Spring Loaded Two Piece End Gates.
Rear Extensions
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
4 kW @ 120 Volts Available for Accessory Use in Outlets
Lighted Dual Screed Control Stations with Fixed Remote
Material Height Control and Lockable Vandal Covers
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

EZ-R2-08	03-0170-08-0001	**$**	**116,340**	**$**	**-**

EZ-R2-08 OPTIONS:

Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0170-08-0013	**$**	**-**	**$**	**-**
Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-0170-08-0014	**$**	**-**	**$**	**-**
Screed Options					
16” Screed Extension With Heat (each, can be left or right)	03-0170-08-0002	**$**	**6,100**	**$**	**-**
28” Screed Extension With Heat (each, can be left or right)	03-0170-08-0003	**$**	**7,215**	**$**	**-**
Pair of 1’ RH & 1’ LH Cut-off Shoes	03-0170-08-0004	**$**	**1,260**	**$**	**-**
Pair of 2’ RH & 2’ LH Cut-off Shoes	03-0170-08-0005	**$**	**1,540**	**$**	**-**
Left Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0170-08-0006	**$**	**2,605**	**$**	**-**
Right Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0170-08-0007	**$**	**2,605**	**$**	**-**
Heated Endgates	03-0170-08-0008	**$**	**1,630**	**$**	**-**
Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0170-08-0010	**$**	**445**	**$**	**-**

Warranties					
Roadtec Edge Extended Warranty (3 years or 3,000 hours total)	03-0170-12-0001	**$**	**6,955**	**$**	**-**
Manufacturer's Extended Engine Warranty (5 years or 6,000 hours total)	03-0170-12-0002	**$**	**3,850**	**$**	**-**

Quoted Item	Option Not Included		Price Code	List Price	Customer Configuration

RP-175 - 8' (2.5M) RUBBER TRACK ASPHALT PAVER

RP-175 STANDARD FEATURES:

1/2" (12.5 mm) Thick Grade 80 Continuous Side Sheet Frame Construction
2 Hydraulically Driven Fans
Oscillating Push Rollers
Direct Hydraulic Planetary Drive
Dual Brake System; Hydrodynamic, Parking
11.5 Ton (10.4 MT) Capacity/200 ft3 (5.7 m3) Self Dumping Hopper
Electric Flow Gates
Independently Driven Variable Speed Feeder Conveyors
1/2" (12.5 mm) cast head and tail plates with chromium carbide clad floor plates
16" (406 mm) Cast Ni-hard Augers
Hydraulically Raise, Lower and Tilting Auger Assembly
Friction Drive Undercarriage
03-0175-06-0013
0-0175-06-00143
Operators stations hydraulically swing out past edge of machine for increased visibility
24 Volt Electrical System with Master Disconnect Switch
95 Amp Alternator
Clearview FXS Fume Extraction System
Amber Warning Beacon, Back Up Alarm and Fire Extinguisher
One (1) Operators Umbrella
Remote Central Point Tractor Lubrication
Lighted Dual Screed Control Stations for head of material and screed control with Fixed Remotes and lockable vandal covers
Retractable Wash-down System with 30' (9.1 m) Hose Length (located on screed)
81.5 Gallon (308.5 L) Fuel Tank Capacity
Conveyor By-Pass Permits Independent Operation of Feeders
8" (203 mm) Hydraulic Tunnel Extensions
Road Light Package - Includes six 24V lights (2 hopper, 2 screed, 2 tunnel)
Electrical wiring and hydraulic hoses for connection to screed

	RP-175e Cummins QSB6.7 Tier 4 Final @ 174 hp	03-0175-01-0001	$ 358,840	$	-

RP-175 OPTIONS:

Screed Options

	Two-Speed Screed Heat High heat mode cuts power to auxilaries and increases generator output to cut screed heating time in half. Automatically switches to standard power mode when screed reaches pre-set temperature. (Does not pair with Eagle, EZ-R2.)	03-0175-02-0032	$ 2,625	$	-
	Hydraulic Screed Assist Package Designed for use with Eagle Screed. Constant up pressure on screed essentially reducing its weight all the time while in Pave mode, whether in forward, neutral or reverse.	03-0175-02-0001	$ 3,180	$	-
	Hydraulic Screed Boost Package Pressurizes the screed lift cylinders when the paver is in neutral and in pave mode to prevent depression in mat when paver stops. Lifting pressure is adjustable. Pressure is applied for adjustable time period once paver starts moving forward again. Time can be set at 0, 3 or 6 seconds.	03-0175-02-0002	$ 2,815	$	-
	Auto Feed Control Paddle Sensor Incudes standardsonic feed sensors as well as paddle sensor. Machine Screed Control Box will have switch to select desired sensor.	03-0175-02-0003	$ 5,165	$	-

Additional Lighting

	24V LED Night Light Package Includes Six 24V Lights	03-0175-02-0006	$ 4,455	$	-
	Saber Light Two 92-watt, LED light panels provide over 10,000 lumens	03-0175-02-0008	$ 4,275	$	-
	Airstar Balloon Light Assembly Includes Two 500 W Halogen Bulbs, Fan, Telescoping Pole, Two Brackets & Case	03-0175-02-0009	$ 4,370	$	-
	Laser Pointer Alignment Guide High intensity laser mounted to tractor can be positioned along line of travel to aid operator in aligning paver correctly.	03-0175-02-0010	$ 3,315	$	-

Truck Dump Signal Light LED Signal light to indicate to truck driver whether to dump, stop or lower.	03-0175-02-0028	$	3,405	$	-
One Additional Amber Beacon	03-0175-02-0011	$	395	$	-
Auger and Tunnel Extensions					
12” Left Hand ¾” Thick Ni-Hard Auger Extension	03-0175-02-0012	$	1,295	$	-
12” Right Hand ¾” Thick Ni-Hard Auger Extension	03-0175-02-0013	$	1,295	$	-
12” Tunnel Extension (Either Handed)	03-0175-02-0014	$	485	$	-
Auger Extension Remotes Remotes attached to fixed remote on left and right sides to controls augers and extensions. Includes a 6 ft cord and can be disconnected for storage.	03-0175-02-0049	$	1,525	$	-
6' Tunnel and Auger Extension Package Extends Augers and Tunnels 3' to each side. Includes all necessary hardware to extend augers and tunnels 3' to each side including outboard auger bearing supports and tunnel extension braces. An additional 1' auger extension and 2- 1' tunnel extension segments can be added to each side. Does not include any screed extensions.	03-0175-02-0015	$	14,480	$	-
16' Auger and Tunnel Extension Package Provides a total of 16' of augers and 16' of tunnels, can add additional 1' auger extension to each side for total of 18' of augers and additional 1' tunnel extension to each side for a total of 18' of tunnels	03-0175-02-0046	$	10,360	$	-
Miscellaneous					
Guardian Telematics System Roadtec GuardianTM Telematics System to send and receive data at the machine or remotely, with the ability to change function settings (One Year Free Subscription)	03-0175-02-0024	$	8,615	$	-
Electrical Outlets 4 outlets: 2 located on operator station and 2 located on back of tractor	03-0175-02-0025	$	860	$	-
Truck Hitch In Lieu of Push Rollers	03-0175-02-0016	$	15,660	$	-
Lincoln Lube Automated Lubrication System	03-0175-02-0017	$	10,165	$	-
Reversing Distribution Augers	03-0175-02-0018	$	1,925	$	-
Additional Umbrella	03-0175-02-0019	$	130	$	-
Environmental Release Agent Spray Down System Includes 20 Gallon (49 L) Tank and Pump (Replaces Standard Wash-down)	03-0175-02-0021	$	2,845	$	-
Soft Rubber front flashing	03-0175-02-0027	$	205	$	-
Mass Flow Hopper Inserts					
RP-170/175 Self Relieving Hopper Insert	03-0175-02-0033	$	9,230	$	-
RP-170/175 Hopper Insert Side Wall Extensions	03-0175-02-0034	$	885	$	-
Mass Flow Low Profile Hopper Insert for 8' Pavers - Not Self Relieving	03-0175-02-0023	$	9,230	$	-
Mass Flow Hopper Side Wall Extensions - for 8' Pavers	03-0175-02-0047	$	885	$	-
Screed Automation - Grade And Slope Control					
TOPCON Sonic Grade And Slope Control Features Dual Sonic Grade Sensors And Single Slope Sensor.	03-0175-03-0007	$	16,835	$	-
MOBA-MATIC II Sonic Grade And Slope Control Features MOBA MATIC II controller with Dual Sonic Grade Sensors And Slope Sensor.	03-0175-03-0008	$	20,120	$	-
TOPCON Sonic Averaging Ski With Hardware Includes 3 Additional Sonic Trackers. (Requires Topcon Sonic Grade and Slope System)	03-0175-03-0009	$	15,915	$	-
MOBA Sonic Averaging Ski With Hardware Includes 2 Additional Sonic Trackers. (Requires MOBA Sonic Grade and Slope System)	03-0175-03-0010	$	15,915	$	-
MOBA Mounting Kit Provides hardware to easily install existing MOBA Grade & Slope System. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)	03-0175-03-0011	$	2,605	$	-
MOBA Slope Sensor	03-0175-03-0012	$	1,800	$	-
MOBA Ski Hardware Provides physical ski, arms, sensor mounting poles, ski mounting harware, and junction box to plug in sensors. (Does not include sensor cables.)	03-0175-03-0013	$	6,240	$	-
TOPCON Mounting Kit Provides hardware to easily install existing TOPCON Grade & Slope. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)	03-0175-03-0014	$	3,165	$	-
TOPCON Slope Sensor	03-0175-03-0015	$	2,270	$	-

SCREEDS

S-8 FIXED WIDTH SCREED

S-8 STANDARD FEATURES:

8' (2.4m) Vibratory Standard Screed with 3' (0.9m) Hydraulic Strike-offs
24 Volt Electrical System (Tier 4 Final Machines Only)
26" (660 mm) Long, ½" (12.5 mm) Thick 400 BHN Screed Plate
Strike-off Articulation from 6.6% Positive to 3.3% Negative
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM
Power Crown, 3"(75 mm) Positive to 1" (25 mm) Negative
Individual Lead and Tail Crown Adjustment
18" (457 mm) Wide Full Width Hinged Heavy Duty Walkway
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Screed Plate Temperature Thermostatically Controlled with Adjustable Set Point
4 KW @ 120 Volts Available for Accessory Use or Lighting
Heater Hold-down System Allows Heater Change Without Removing the Screed Plate
Spring Loaded Two Piece End Gates
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

S-8	03-0175-04-0001	$	76,265	$	-

S-8 OPTIONS:

Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0175-04-0014	$	-	$	-
Counter-Clockwise Raise Angle of Attack Screws Clockwise lowers - "Roadtec Standard"	03-0175-04-0015	$	-	$	-
Screed Options					
6" Screed Extension	03-0175-04-0002	$	3,845	$	-
12" Screed Extension With Heat	03-0175-04-0003	$	4,290	$	-
24" Screed Extension With Heat and Vibration	03-0175-04-0004	$	5,645	$	-
Left Hand Safety Edge Beveled Endgate Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	03-0175-04-0005	$	2,680	$	-
Right Hand Safety Edge Beveled Endgate Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	03-0175-04-0006	$	2,680	$	-
Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0175-04-0012	$	460	$	-
S-8 Electric Heat Screed/Auger Extension Packages:					
10' Paving Package Includes: 2 x 12" Screed Extensions With Heat	03-0175-04-0007	$	8,123	$	-
12' Paving Package Includes: 1 x 24" Screed Extension With Heat and Vibration, 2 x 12" Screed Extensions With Heat, 2 x 12" Auger Extensions and 2 x 12" Tunnel Extensions	03-0175-04-0008	$	16,497	$	-

EZ-IV-8 FRONT EXTENDABLE SCREED

EZ-IV-8 STANDARD FEATURES:

8' (2.4 m) to 15' (4.5 m) Hydraulically Extendable Carlson Easy Screed IV with Wide Blade Electric Heat
24 Volt Electrical System (Tier 4 Final Machines Only)
One 4' (1.2 m) Long & One 3' (0.9 m) Long Front Mounted Extensions
Extensions Move on High Composite Bushings & Chrome Slide Track
Extensions are 8" (203 mm) Wide, with Heat, Vibration and Adjustable Angle of Attack
Front Mounted Extensions Provide 9% Positive Slope
Electric Valves Control In/Out, Slope & Vertical Height
Carlson's Patented "Front Taper Design" Main Screed
Main Screed is 26" (660 mm) Long, ½" (12.5 mm) Thick 400 BHN Screed Plate
Power Crown, 2½" (63 mm) Positive to ¾" (19 mm) Negative
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Thermostatically Controlled Plate Temperature with Analog Display
5.5 KW @ 120 Volts Available for Accessory Use in 8 Outlets
Heater Hold Down System Allows Heater Change Without Removing the Screed Plate

Electrically Heated Oven for Warming Meals
Spring Loaded Two Piece End Gates
20” (508 mm) Wide Main Screed Hinged Heavy Duty Walkway
12” (304 mm) Wide Hinged Extension Walkways
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

EZ-IV-8	03-0175-06-0001	**$**	**87,975**	**$**	**-**

EZ-IV-8 OPTIONS:

Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0175-06-0011	**$**	**-**	**$**	**-**
Counter-Clockwise Raise Angle of Attack Screws Clockwise lowers - "Roadtec Standard"	03-0175-06-0012	**$**	**-**	**$**	**-**
Screed Options					
Pair of 12" Bolt-on Screed Extensions with Heat, Left and Right	03-0175-06-0002	**$**	**4,685**	**$**	**-**
Pair of 18" Bolt-on Screed Extensions with Heat, Left and Right	03-0175-06-0003	**$**	**4,795**	**$**	**-**
Pair of 24" Bolt-on Screed Extensions with Heat, Left and Right	03-0175-06-0004	**$**	**4,910**	**$**	**-**
Beveled Edger for "Tapered Notch" For 12" Tapered Notched Wedge Joint One edger fits left or right side Heated	03-0175-06-0005	**$**	**3,785**	**$**	**-**
Hydraulic Berm Builder with Electric Control Valves (Single Side) Manual Adjust not Available - 12”	03-0175-06-0006	**$**	**2,880**	**$**	**-**
Pair of Additional 6” Cut-off Shoes	03-0175-06-0007	**$**	**255**	**$**	**-**
Left Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0175-06-0008	**$**	**2,605**	**$**	**-**
Right Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0175-06-0009	**$**	**2,605**	**$**	**-**
Pair of Heated End Gates	03-0175-06-0010	**$**	**1,630**	**$**	**-**
Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0175-06-0014	**$**	**434**	**$**	**-**

EZ-R2-08 REAR EXTENDABLE SCREED

EZ-R2-08 STANDARD FEATURES:

8’ to 15’6" Hydraulically Extendable Screed with Integral Rear Mounted Extensions
Electric Heat with Thermostatically Controlled Temperature
Screed Plates are 20 Wide, ½ Thick 450 BHN Material.
Fully adjustable screed plates with adjustment cones on main and extensions.
Fully adjustable Pre Strike-Off on Main and extensions
Extensions Supported by Two 4 Guide tubes with Teflon Bushings.
Exclusive Carlson slide track system allowing for adjustment of extension parallel
Independent Angle of Attach Adjustments for Extensions.
Extensions Provide 12% Positive Slope to 5% Negative Slope.
Power Crown Provides 2" Positive to 1" Negative.
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM.
18" Wide Full Width Telescoping Heavy Duty Walkway.
Electric Valves Control Extensions, Slope, Crown & Vertical Height.
Full Length Spring Loaded Two Piece End Gates.
Rear Extensions
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
4 kW @ 120 Volts Available for Accessory Use in Outlets
Lighted Dual Screed Control Stations with Fixed Remote
Material Height Control and Lockable Vandal Covers
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

EZ-R2-08	03-0175-08-0001	**$**	**116,340**	**$**	**-**

EZ-R2-08 OPTIONS:					
Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0175-08-0013	$	-	$	-
Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-0175-08-0014	$	-	$	-
Screed Options					
16” Screed Extension With Heat (each, can be left or right)	03-0175-08-0002	$	6,100	$	-
28” Screed Extension With Heat (each, can be left or right)	03-0175-08-0003	$	7,215	$	-
Pair of 1’ RH & 1’ LH Cut-off Shoes	03-0175-08-0004	$	1,260	$	-
Pair of 2’ RH & 2’ LH Cut-off Shoes	03-0175-08-0005	$	1,540	$	-
Left Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element.	03-0175-08-0006	$	2,605	$	-
Right Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element.	03-0175-08-0007	$	2,605	$	-
Heated Endgates	03-0175-08-0008	$	1,630	$	-
Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0175-08-0010	$	445	$	-

Warranties					
Roadtec Edge Extended Warranty (3 years or 3,000 hours total)	03-0175-11-0001	$	8,750	$	-
Manufacturer's Extended Engine Warranty (5 years or 6,000 hours total)	03-0170-11-0002	$	3,820	$	-

Roadtec Pricing Effective 7/1/2021

Quoted Item		Price Code	List Price	Customer Configuration
RP-190 - 10' (3M) RUBBER TIRE ASPHALT PAVER				
	RP-190 STANDARD FEATURES:			
	¾" (19 mm) Thick Continuous Side Sheet Frame Construction 2" (50 mm) Thick Front Cross Frame Member Roadtec Guardian TM Telematics System to send/receive data remotely, change function settings (1Yr Free Subscription) Oscillating Push Rollers Direct Hydraulic Planetary Drive Three Brake System; Hydrodynamic, Parking, PMP Planetary 15.5 Ton (14 mt) Capacity/ 290 Cubic Feet Self Dumping Hopper Electric Flow Gates Independently driven variable speed feeder conveyors 1/2" (12.5 mm) 550 BHN cast head and tail plates and chromium carbide clad floor plates Conveyor By-Pass – Operate Augers Independent of Feeders 16" (406 mm) Cast ¾" Thick Ni-hard Augers Hydraulically Raise, Lower and Tilting Auger Assembly 18:00 x 25" (635 mm) Hydroflated High Flotation Sand Rib Drive Tires Dual 14" (355 mm) x 22" (558 mm) Front Bogies Two (2) Comfort Drive Operators Stations with Tilt Steering Wheel and Finger Tip Paver Control Dual Comfort Drive Operators stations hydraulically swing out past edge of machine for increased visibility Display at each operators station for engine diagnostics, paver diagnostics as well as speed and flow gate position Steering Assist Provides Inside Turning Radius of 4'-6" 24 Volt Starting System with Master Disconnect Switches 95 Amp Alternator Clearview FXS Fume Extraction System Hydraulic Engine Hood Raise with Manual Back Up Amber Warning Beacon, Back Up Alarm and Fire Extinguisher 1 umbrella for operator station and brackets for installation Lighted Dual Screed Control Stations for head of material and screed control with Fixed Remotes and lockable vandal covers Retractable wash-down hose reel system with 30' (9.1 m) hose length 100 gallon (378 l) fuel tank capacity Road Light Package - Includes six 24V lights (2 hopper, 2 screed, 2 tunnel) Electrical wiring and hydraulic hoses for connection to screed			
	RP-190e Cummins QSB 6.7 230 HP Tier 4f/Stage IV Diesel Engine	03-0190-01-0003	$ 325,180	$ -
	RP-190 OPTIONS:			
	Front Wheel Assist			
	Front Wheel Assist Includes additional hydraulic motor on both rear bogie wheels.	03-0190-02-0001	$ 24,225	$ -
	Screed Options			
	Two-Speed Screed Heat High heat mode cuts power to auxilaries and increases generator output to cut screed heating time in half. Automatically switches to standard power mode when screed reaches pre-set temperature. (Does not pair with Eagle, EZ-R2.)	03-0190-02-0035	$ 2,625	$ -
	Hydraulic Screed Assist Package Designed for use with Eagle Screed. Constant up pressure on screed essentially reducing its weight all the time while in Pave mode, whether in forward, neutral or reverse.	03-0190-02-0004	$ 3,180	$ -
	Hydraulic Screed Boost Package Pressurizes the screed lift cylinders when the paver is in neutral and in pave mode to prevent depression in mat when paver stops. Lifting pressure is adjustable. Pressure is applied for adjustable time period once paver starts moving forward again. Time can be set at 0, 3 or 6 seconds.	03-0190-02-0005	$ 2,815	$ -
	Auto Feed Control Paddle Sensor Incudes standardsonic feed sensors as well as paddle sensor. Machine Screed Control Box will have switch to select desired sensor.	03-0190-02-0006	$ 5,165	$ -
	Additional Lighting			
	24V LED Night Light Package Includes Six 24V Lights	03-0190-02-0008	$ 4,455	$ -
	Saber Light Two 92-watt, LED light panels provide over 10,000 lumens	03-0190-02-0010	$ 4,275	$ -
	Airstar Balloon Light Assembly	03-0190-02-0011	$ 4,370	$ -

	Includes Two 500 W Halogen Bulbs, Fan, Telescoping Pole, Two Brackets & Case				
	Laser Pointer Alignment Guide	03-0190-02-0012	$ 3,315	$	-
	High intensity laser mounted to tractor can be positioned along line of travel to aid operator in aligning paver correctly.				
	Truck Dump Signal Light	03-0190-02-0013	$ 3,405	$	-
	LED Signal light to indicate to truck driver whether to dump, stop or lower.				
	One Additional Amber Beacon	03-0190-02-0033	$ 395	$	-
	Auger and Tunnel Extensions				
	12” Left Hand ¾” Thick Ni-Hard Auger Extension	03-0190-02-0014	$ 1,264	$	-
	12” Right Hand ¾” Thick Ni-Hard Auger Extension	03-0190-02-0015	$ 1,264	$	-
	12” Tunnel Extension (Either Handed)	03-0190-02-0016	$ 474	$	-
	Hydraulic Tunnel Extensions	03-0190-02-0017	$ 6,105	$	-
	Provides 18" hydraulically extending tunnel extensions for both left and right side of machine.				
	Auger Extension Remotes	03-0190-02-0051	$ 1,525	$	-
	Remotes attached to fixed remote on left and right sides to controls augers and extensions. Includes a 6 ft cord and can be disconnected				
	6' Tunnel and Auger Extension Package	03-0190-02-0018	$ 13,080	$	-
	Extends Augers and Tunnels 3' to each side. Includes all necessary hardware to extend augers and tunnels 3' to each side including outboard auger bearing supports and tunnel extension braces. An additional 1' auger extension and 2- 1' tunnel extension segments can be added to each side. Does not include any screed extensions.				
	20.5' auger and 20.75' tunnel extension package	03-0190-02-0019	$ 30,315	$	-
	Provides a total of 20.5' of augers and 20.75' of tunnels, can add additional 1' auger extension to each side for total of 22.5' of augers and and additional 1' tunnel extension to each side for a total of 22.75' of tunnels				
	Miscellaneous				
	Electrical Outlets	03-0190-02-0030	$ 860	$	-
	4 outlets: 2 located on operator station and 2 located on back of tractor				
	Truck Hitch In Lieu of Push Rollers	03-0190-02-0020	$ 15,660	$	-
	Lincoln Lube Automated Lubrication System	03-0190-02-0021	$ 10,165	$	-
	Reversing Distribution Augers	03-0190-02-0022	$ 1,925	$	-
	Additional Umbrella Kit	03-0190-02-0027	$ 250	$	-
	HD Conveyor Chain Package	03-0190-02-0029	$ 6,200	$	-
	Includes Offset Link Conveyor Chains in lieu of standard conveyor chains				
	Bridgestone VHS (Stiff) Tires	03-2505-02-0034	$ 3,080	$	-
	Soft Rubber front flashing	03-2505-02-0033	$ 205	$	-
	Mass Flow Hopper Inserts				
	RP-190 Self Relieving Hopper Insert	03-0190-02-0025	$ 9,230	$	-
	RP-190 Self Relieving Hopper Sidewall Extensions	03-0190-02-0026	$ 885	$	-
	Screed Automation - Grade And Slope Control				
	TOPCON Sonic Grade And Slope Control	03-0190-03-0007	$ 16,835	$	-
	Features Dual Sonic Grade Sensors And Single Slope Sensor.				
	MOBA-MATIC II Sonic Grade And Slope Control	03-0190-03-0008	$ 20,120	$	-
	Features MOBA MATIC II controller with Dual Sonic Grade Sensors And Single Slope Sensor.				
	TOPCON Sonic Averaging Ski With Hardware	03-0190-03-0009	$ 15,915	$	-
	Includes 3 Additional Sonic Trackers. (Requires Topcon Sonic Grade and Slope System)				
	MOBA Sonic Averaging Ski With Hardware	03-0190-03-0010	$ 15,915	$	-
	Includes 2 Additional Sonic Trackers. (Requires MOBA Sonic Grade and Slope System)				
	MOBA Mounting Kit	03-0190-03-0011	$ 2,605	$	-
	Provides hardware to easily install existing MOBA Grade & Slope System. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)				
	MOBA Slope Sensor	03-0190-03-0012	$ 1,800	$	-
	MOBA Ski Hardware	03-0190-03-0013	$ 6,240	$	-
	Provides physical ski, arms, sensor mounting poles, ski mounting harware, and junction box to plug in sensors. (Does not include sensor cables.)				
	TOPCON Mounting Kit	03-0190-03-0014	$ 3,165	$	-
	Provides hardware to easily install existing TOPCON Grade & Slope. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)				
	TOPCON Slope Sensor	03-0190-03-0015	$ 2,270	$	-

SCREEDS

S-10e FIXED WIDTH SCREED

S-10e STANDARD FEATURES:

10' (3 m) Vibratory Standard Screed with 4' (1.2 m) Hydraulic Strike-offs
32" (0.8 m) Long, ½" (12.5 mm) Thick 400 BHN Screed Plate
Strike-off Articulation from 6.6% Positive to 3.3% Negative
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM
Power Crown, 3" (75 mm) Positive to 1" (25 mm) Negative
Individual Lead and Tail Crown Adjustment
18" (457 mm) Wide Full Width Hinged Heavy Duty Walkway
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Screed Plate Temperature Thermostatically Controlled with Adjustable Set Point
4 kW @ 120 Volts Available for Accessory Use or Lighting
Heater Hold-down System Allows Heater Change Without Removing the Screed Plate
Lighted Dual Screed Control Stations with Fixed Remote, Material Control and Lockable Vandal Covers
Spring Loaded Two Piece End Gates
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

S-10e	03-0190-04-0001	**$**	**85,300**	**$**	**-**

S-10e OPTIONS

Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0190-06-0013	**$**	**-**	**$**	**-**
Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-0190-06-0014	**$**	**-**	**$**	**-**
Screed Options					
6" Screed Extension	03-0190-04-0002	**$**	**3,845**	**$**	**-**
12" Screed Extension With Heat	03-0190-04-0003	**$**	**4,290**	**$**	**-**
24" Screed Extension With Heat and Vibration	03-0190-04-0004	**$**	**5,645**	**$**	**-**
36" Screed Extension With Heat and Vibration	03-0190-04-0005	**$**	**7,005**	**$**	**-**
24" Crownable Screed Extension With Heat - No Vibration	03-0190-04-0006	**$**	**7,765**	**$**	**-**
Left Hand Safety Edge Beveled Endgate Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	03-0190-04-0007	**$**	**2,680**	**$**	**-**
Right Hand Safety Edge Beveled Endgate Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	03-0190-04-0008	**$**	**2,680**	**$**	**-**
Pair of Heated End Gates	03-0190-06-0007	**$**	**1,680**	**$**	**-**
Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0190-04-0010	**$**	**455**	**$**	**-**

EZ-IV-10 FRONT EXTENDABLE SCREED

EZ-IV-10 STANDARD FEATURES:

10' (3 m) to 19' (5.8 m) Hydraulically Extendable Carlson Easy Screed IV with Wide Blade Electric Heat
One 5' (1.5 m) Long & One 4' (1.2 m) Long Front Mounted Extensions
Extensions Move on High Composite Bushings & Chrome Slide Track
Extensions are 8" (203 mm) Wide, with Heat, Vibration and Adjustable Angle of Attack
Extensions Provide 9% Positive Slope
Electric Valves Control In/Out, Slope & Vertical Height
Carlson's Patented "Front Taper Design" Main Screed
Main Screed is 26" (660 mm) Long, ½" (12.5 mm) Thick 400 BHN Screed Plate
Power Crown, 2½" (63 mm) Positive to ¾" (19 mm) Negative
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Thermostatically Controlled Plate Temperature with Analog Display
5.5 KW @ 120 Volts Available for Accessory Use in 8 Outlets
Heater Hold Down System Allows Heater Change Without Removing the Screed Plate
Electrically Heated Oven for Warming Meals
Spring Loaded Two Piece End Gates
20" (508 mm) Wide Main Screed Hinged Heavy Duty Walkway
12" (304 mm) Wide Hinged Extension Walkways
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

EZ-IV-10	03-0190-06-0001	**$**	**96,865**	**$**	**-**

EZ-IV-10 OPTIONS:

Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0190-06-0013	$	-	$	-
Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-0190-06-0014	$	-	$	-
Screed Options					
Pair of 12" Bolt-on Screed Extensions with Heat, Left and Right	03-0190-06-0002	$	4,685	$	-
Pair of 18" Bolt-on Screed Extensions with Heat, Left and Right	03-0190-06-0003	$	4,795	$	-
Pair of 24" Bolt-on Screed Extensions with Heat, Left and Right	03-0190-06-0004	$	4,910	$	-
Beveled Edger for "Tapered Notch" For 12" Tapered Notched Wedge Joint One edger fits left or right side Heated	03-0190-06-0005	$	3,785	$	-
Hydraulic Berm Builder with Electric Control Valves (Single Side) Manual Adjust not Available - 12"	03-0190-06-0006	$	2,880	$	-
Pair of Heated End Gates	03-0190-06-0007	$	1,630	$	-
Left Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0190-06-0008	$	2,605	$	-
Right Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0190-06-0009	$	2,605	$	-
Pair of Additional 6" Cut-off Shoes	03-0190-06-0010	$	255	$	-
Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0190-06-0012	$	445	$	-

EZ-V-10 FRONT EXTENDABLE SCREED

EZ-V-10 STANDARD FEATURES:

10' (3 m) to 19.5' (5.9 m) Hydraulically Extendable Carlson Easy Screed IV with Wide Blade Electric Heat
One 5' (1.5 m) Long & One 4' (1.2 m) Long Front Mounted Extensions
Extensions Move on High Composite Bushings & Chrome Slide Track with Improved Strength
Extensions are 8" (203 mm) Wide, with Heat, Vibration and Adjustable Angle of Attack
Extensions Provide 9% Positive Slope
Electric Valves Control In/Out, Slope & Vertical Height
Carlson's Patented "Front Taper Design" Main Screed
Main Screed is 26" (660 mm) Long, ½" (12.5 mm) Thick Hardox 450 Hardened Steel Screed Plate
Power Crown, 2½" (63 mm) Positive to ¾" (19 mm) Negative
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Thermostatically Controlled Plate Temperature with Analog Display
5.5 KW @ 120 Volts Available for Accessory Use in 8 Outlets
Heater Hold Down System Allows Heater Change Without Removing the Screed Plate
Electrically Heated Oven for Warming Meals
Spring Loaded Two Piece, Heated End Gates with easy slide on and off attachment shoes
20" (508 mm) Wide Main Screed Hinged Heavy Duty Walkway
12" (304 mm) Wide Hinged Extension Walkways
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

EZ-V-10	03-0190-09-0001	$	120,620	$	-

EZ-V-10 OPTIONS:

Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0190-09-0013	$	-	$	-
Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-0190-09-0014	$	-	$	-
Screed Options					
Pair of 12" Bolt-on Screed Extensions with Heat, Left and Right	03-0190-09-0002	$	4,685	$	-
Pair of 18" Bolt-on Screed Extensions with Heat, Left and Right	03-0190-09-0003	$	4,795	$	-
Pair of 24" Bolt-on Screed Extensions with Heat, Left and Right	03-0190-09-0004	$	4,910	$	-
Beveled Edger for "Tapered Notch" For 12" Tapered Notched Wedge Joint One edger fits left or right side Heated	03-0190-09-0005	$	3,785	$	-

Hydraulic Berm Builder with Electric Control Valves (Single Side) Manual Adjust not Available - 12”	03-0190-09-0006	$	2,880	$	-
Pair of Heated End Gates	03-0190-09-0007	$	1,630	$	-
Left Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0190-09-0008	$	2,605	$	-
Right Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0190-09-0009	$	2,605	$	-
Pair of Additional 6” Cut-off Shoes	03-0190-09-0010	$	255	$	-
Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0190-09-0012	$	445	$	-

Eagle-10 REAR EXTENDABLE SCREED

Eagle-10 STANDARD FEATURES:

10’ to 19’-6” Hydraulically Extendable Screed with Integral Rear Mounted Extensions
4’-9” Long Rear Extensions with 20” Wide U-Shaped Plate
Extension Plates are ½” Thick, 400 BHN Material
Extensions Move on Dual 5” Guide Tubes & Teflon Bushings
Extensions Include Pre Strike-offs, Independent Sub-Frames, Electric Heat, Vibration, and Angle of Attack Adjustment
Extensions Provide 14% Positive Slope, 5% Negative Slope
Electric Valves Control In/Out, Slope & Vertical Height
Main Screed Plate is 20” Long, ½” Thick 400 BHN Material
Main Screed Includes Adjustable Pre Strike-off, Independent Sub-Frames, Electric Heat, and Angle of Attack Adjustment
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM
Reversible U-Shaped Main Screed Plate for Extended Wear Life
Power Crown, 3” Positive to 1” Negative
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Thermostatically Controlled Screed Plate Temperature
4 kW @ 120 Volts Available for Accessory Use in Outlets
Lighted Dual Screed Control Stations with Fixed Remote
Material Height Control and Lockable Vandal Covers
Full Length Spring Loaded Two Piece End Gates
12” Wide Full Width Telescoping Heavy Duty Walkway
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

Eagle-10	03-0190-07-0001	$	109,135	$	-

EAGLE-10 OPTIONS:

Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0190-06-0013	$	-	$	-
Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-0190-06-0014	$	-	$	-
Screed Options					
16” Screed Extension With Heat (each, can be left or right)	03-0190-07-0002	$	6,095	$	-
28” Screed Extension With Heat (each, can be left or right) (E8B Screed Extensions will not Fit the Eagle-10 Screed)	03-0190-07-0003	$	7,215	$	-
Pair of 1’ RH & 1’ LH Cut-off Shoes	03-0190-07-0004	$	1,260	$	-
Pair of 2’ RH & 2’ LH Cut-off Shoes	03-0190-07-0005	$	1,540	$	-
Left Hand Safety Edge Beveled Endgate Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	03-0190-07-0006	$	2,605	$	-
Right Hand Safety Edge Beveled Endgate Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	03-0190-07-0007	$	2,605	$	-
Heated Endgates	03-0190-07-0008	$	1,630	$	-
Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0190-07-0010	$	445	$	-

EZ-R2-10 REAR EXTENDABLE SCREED

EZ-R2-10 STANDARD FEATURES:

10’ to 19’-6” Hydraulically Extendable Screed with Integral Rear Mounted Extensions

Electric Heat with Thermostatically Controlled Temperature with 1500 watt elements
Screed Plates are 20 Wide, ½ Thick 450 BHN Material.
Fully adjustable screed plates with adjustment cones on main and extensions.
Fully adjustable Pre Strike-Off on Main and extensions
Extensions Supported by Two 4 Guide tubes with Teflon Bushings.
Exclusive Carlson slide track system allowing for adjustment of extension parallel
Independent Angle of Attach Adjustments for Extensions.
Extensions Provide 12% Positive Slope to 5% Negative Slope.
Power Crown Provides 2" Positive to 1" Negative.
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM.
18" Wide Full Width Telescoping Heavy Duty Walkway.
Electric Valves Control Extensions, Slope, Crown & Vertical Height.
Full Length Spring Loaded Two Piece End Gates.
4'-9" Long Rear Extensions
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
4 kW @ 120 Volts Available for Accessory Use in Outlets
Lighted Dual Screed Control Stations with Fixed Remote
Material Height Control and Lockable Vandal Covers
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

	EZ-R2-10	03-0190-08-0001	$	116,340	$	-
	EZ-R2-10 OPTIONS:					
	Angle of Attack Screws (Must Choose One)					
	Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0190-06-0013	$	-	$	-
	Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-0190-06-0014	$	-	$	-
	Screed Options					
	16" Screed Extension With Heat (each, can be left or right)	03-0190-08-0002	$	6,095	$	-
	28" Screed Extension With Heat (each, can be left or right)	03-0190-08-0003	$	7,215	$	-
	Pair of 1' RH & 1' LH Cut-off Shoes	03-0190-08-0004	$	1,260	$	-
	Pair of 2' RH & 2' LH Cut-off Shoes	03-0190-08-0005	$	1,540	$	-
	Left Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0190-08-0006	$	2,605	$	-
	Right Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0190-08-0007	$	2,605	$	-
	Heated Endgates	03-0190-08-0008	$	1,630	$	-
	Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0190-08-0010	$	445	$	-
	Warranties					
	Roadtec Edge Extended Warranty (3 years or 3,000 hours total)	03-0190-03-0020	$	7,700	$	-
	Manufacturer's Extended Engine Warranty (5 years or 6,000 hours total)	03-0190-03-0021	$	3,820	$	-

Roadtec Pricing Effective 7/1/2021

Quoted Item	Option Not Included		Price Code	List Price	Customer Configuration
RP-195 - 10' (3M) RUBBER TRACK ASPHALT PAVER					
		RP-195 STANDARD FEATURES:			
		¾" (19 mm) Thick Continuous Side Sheet Frame Construction 2" (50 mm) Thick Front Cross Frame Member Roadtec Guardian TM Telematics System to send/receive data remotely, change function settings (1Yr Free Subscription) Oscillating Push Rollers Direct Hydraulic Planetary Drive 15.5 Ton (14 mt) Capacity/ 290 Cubic Feet Self Dumping Hopper Electric Flow Gates Independently driven variable speed feeder conveyors 1/2" (12.5 mm) 550 BHN cast head and tail plates and chromium carbide clad floor plates Conveyor By-Pass – Operation of Augers Independent of Feeders 16" (355 mm) Cast ¾" Thick Ni-hard Augers Hydraulically Raise, Lower and Tilting Auger Assembly Friction Drive Undercarriage with Three sets of Oscillating Bogies 18" (457 mm) Wide Reinforced Smooth Tread Rubber Track Two (2) Comfort Drive Operators Stations, Finger Tip Paver Control with Total Control Joystick Dual Comfort Drive Operators stations hydraulically swing out past edge of machine for increased visibility Total Control Joystick combines all tractor propel controls into single joystick Display at each operators station for engine diagnostics, paver diagnostics as well as speed and flow gate position 24 Volt Starting System with Master Disconnect Switches 95 Amp Alternator Clearview FXS Fume Extraction System Hydraulic Engine Hood Raise with Manual Back Up Amber Warning Beacon, Back Up Alarm and Fire Extinguisher 1 Umbrella for operator station and brackets for installation Lighted Dual Screed Control Stations for head of material and screed control with Fixed Remotes and lockable vandal covers Retractable wash-down hose reel system with 30' (9.1 m) hose length 100 gallon (378 l) fuel tank capacity 18" hydraulic tunnel extensions Road Light Package - Includes six 24V lights (2 hopper, 2 screed, 2 tunnel) Electrical wiring and hydraulic hoses for connection to screed			
		RP-195e Cummins QSB 6.7 230 HP Tier 4f/Stage IV Diesel Engine	03-0195-01-0003	$ 385,385	$ -
		RP-195 OPTIONS:			
		Screed Options			
		Two-Speed Screed Heat High heat mode cuts power to auxilaries and increases generator output to cut screed heating time in half. Automatically switches to standard power mode when screed reaches pre-set temperature. (Does not pair with Eagle, EZ-R2.)	03-0195-02-0033	$ 2,625	$ -
		Hydraulic Screed Assist Package Designed for use with Eagle Screed. Constant up pressure on screed essentially reducing its weight all the time while in Pave mode, whether in forward, neutral or reverse.	03-0195-02-0001	$ 3,180	$ -
		Hydraulic Screed Boost Package Pressurizes the screed lift cylinders when the paver is in neutral and in pave mode to prevent depression in mat when paver stops. Lifting pressure is adjustable. Pressure is applied for adjustable time period once paver starts moving forward again. Time can be set at 0, 3 or 6 seconds.	03-0195-02-0002	$ 2,815	$ -
		Auto Feed Control Paddle Sensor Incudes standardsonic feed sensors as well as paddle sensor. Machine Screed Control Box will have switch to select desired sensor.	03-0195-02-0003	$ 5,165	$ -

Additional Lighting					
24V LED Night Light Package Includes Six 24V Lights	03-0195-02-0005	$	4,455	$	-
Saber Light Two 92-watt, LED light panels provide over 10,000 lumens	03-0195-02-0007	$	4,275	$	-
Airstar Balloon Light Assembly Includes Two 500 W Halogen Bulbs, Fan, Telescoping Pole, Two Brackets & Case	03-0195-02-0008	$	4,370	$	-
Laser Pointer Alignment Guide High intensity laser mounted to tractor can be positioned along line of travel to aid operator in aligning paver correctly.	03-0195-02-0009	$	3,315	$	-
Truck Dump Signal Light LED Signal light to indicate to truck driver whether to dump, stop or lower.	03-0195-02-0010	$	3,405	$	-
One Additional Amber Beacon	03-0195-02-0011	$	395	$	-

Auger and Tunnel Extensions					
12” Left Hand ¾” Thick Ni-Hard Auger Extension	03-0195-02-0012	$	1,295	$	-
12” Right Hand ¾” Thick Ni-Hard Auger Extension	03-0195-02-0013	$	1,295	$	-
12” Tunnel Extension (Either Handed)	03-0195-02-0014	$	485	$	-
Auger Extension Remotes	03-0195-02-0036	$	1,525	$	-
6' Tunnel and Auger Extension Package Extends Augers and Tunnels 3' to each side. Includes all necessary hardware to extend augers and tunnels 3' to each side including outboard auger bearing supports and tunnel extension braces. An additional 1' auger extension and 2- 1' tunnel extension segments can be added to each side. Does not include any screed extensions.	03-0195-02-0016	$	13,080	$	-
20.5' auger and 20.75' tunnel extension package Provides a total of 20.5' of augers and 20.75' of tunnels, can add additional 1' auger extension to each side for total of 22.5' of augers and and additional 1' tunnel extension to each side for a total of 22.75' of tunnels	03-0195-02-0017	$	31,935	$	-

Miscellaneous					
Electrical Outlets 4 outlets: 2 located on operator station and 2 located on back of tractor	03-0195-02-0029	$	860	$	-
Steel Tracks in Lieu of Rubber Tracks	03-0195-02-0018	$	5,010	$	-
Truck Hitch In Lieu of Push Rollers	03-0195-02-0019	$	15,660	$	-
Lincoln Lube Automated Lubrication System	03-0195-02-0020	$	10,165	$	-
Reversing Distribution Augers	03-0195-02-0021	$	1,925	$	-
Additional Umbrella Kit	03-0195-02-0026	$	250	$	-
HD Conveyor Chain Package	03-0195-02-0028	$	6,200	$	-
Soft Rubber front flashing	03-0195-02-0032	$	205	$	-

Mass Flow Hopper Inserts					
RP-195 Self Relieving Hopper Insert	03-0195-02-0024	$	9,230	$	-
RP-195 Self Relieving Hopper Sidewall Extensions	03-0195-02-0025	$	885	$	-

Screed Automation - Grade And Slope Control					
TOPCON Sonic Grade And Slope Control Features Dual Sonic Grade Sensors And Single Slope Sensor.	03-0195-03-0007	$	16,835	$	-
MOBA-MATIC II Sonic Grade And Slope Control Features MOBA MATIC II controller with Dual Sonic Grade Sensors And Slope Sensor.	03-0195-03-0008	$	20,120	$	-
TOPCON Sonic Averaging Ski With Hardware Includes 3 Additional Sonic Trackers. (Requires Topcon Sonic Grade and Slope System)	03-0195-03-0009	$	15,915	$	-
MOBA Sonic Averaging Ski With Hardware Includes 2 Additional Sonic Trackers. (Requires MOBA Sonic Grade and Slope System)	03-0195-03-0010	$	15,915	$	-
MOBA Mounting Kit	03-0195-03-0011	$	2,605	$	-

	Provides hardware to easily install existing MOBA Grade & Slope System. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)					
	MOBA Slope Sensor	03-0195-03-0012	$	1,800	$	-
	MOBA Ski Hardware	03-0195-03-0013	$	6,240	$	-
	Provides physical ski, arms, sensor mounting poles, ski mounting harware, and junction box to plug in sensors. (Does not include sensor cables.)					
	TOPCON Mounting Kit	03-0195-03-0014	$	3,165	$	-
	Provides hardware to easily install existing TOPCON Grade & Slope. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)					
	TOPCON Slope Sensor	03-0195-03-0015	$	2,270	$	-

SCREEDS

S-10e FIXED WIDTH SCREED

S-10e STANDARD FEATURES:

10’ (3 m) Vibratory Standard Screed with 4’ (1.2 m) Hydraulic Strike-offs
32” (0.8 m) Long, ½” (12.5 mm) Thick 400 BHN Screed Plate
Strike-off Articulation from 6.6% Positive to 3.3% Negative
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM
Power Crown, 3” (75 mm) Positive to 1” (25 mm) Negative
Individual Lead and Tail Crown Adjustment
18” (457 mm) Wide Full Width Hinged Heavy Duty Walkway
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Screed Plate Temperature Thermostatically Controlled with Adjustable Set Point
4 kW @ 120 Volts Available for Accessory Use or Lighting
Heater Hold-down System Allows Heater Change Without Removing the Screed Plate
Lighted Dual Screed Control Stations with Fixed Remote, Material Control and Lockable Vandal Covers
Spring Loaded Two Piece End Gates
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

	S-10e	03-0195-04-0001	$	85,300	$	-

S-10e OPTIONS

	Angle of Attack Screws (Must Choose One)					
	Clockwise Raise Angle of Attack Screws	03-0195-04-0018	$	-	$	-
	Counter-clockwise lowers					
	Counter-Clockwise Raise Angle of Attack Screws	03-0195-04-0019	$	-	$	-
	Clockwise Lowers - "Roadtec Standard"					
	Screed Extensions					
	6” Screed Extension	03-0195-04-0002	$	3,845	$	-
	12” Screed Extension With Heat	03-0195-04-0003	$	4,290	$	-
	24” Screed Extension With Heat and Vibration	03-0195-04-0004	$	5,645	$	-
	36” Screed Extension With Heat and Vibration	03-0195-04-0005	$	7,005	$	-
	24” Crownable Screed Extension With Heat - No Vibration	03-0195-04-0006	$	7,765	$	-
	Left Hand Safety Edge Beveled Endgate	03-0195-04-0007	$	2,680	$	-
	Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.					
	Right Hand Safety Edge Beveled Endgate	03-0195-04-0008	$	2,680	$	-
	Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.					
	Pair of Heated End Gates	03-0195-06-0007	$	1,680	$	-
	Remote Jumper Harnesses	03-0195-04-0010	$	455	$	-

Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.

12' Paving Package Includes: 2 x 12" Screed Extensions With Heat	03-0195-04-0011	$	8,575	$	-
14' Paving Package Includes: 1 x 24" Screed Extension With Heat and Vibration, 2 x 12" Screed Extensions With Heat, 2 x 12" Auger Extensions and 2 x 12" Tunnel Extensions	03-0195-04-0012	$	17,790	$	-
16' Paving Package Includes: 2 x 24" Screed Extensions With Heat and Vibration, 2 x 12" Screed Extensions With Heat, 4 x 12" Auger Extensions, 4 x 12" Tunnel Extensions	03-0195-04-0013	$	26,995	$	-

EZ-IV-10 FRONT EXTENDABLE SCREED

EZ-IV-10 STANDARD FEATURES:

10' (3 m) to 19' (5.8 m) Hydraulically Extendable Carlson Easy Screed IV with Wide Blade Electric Heat
One 5' (1.5 m) Long & One 4' (1.2 m) Long Front Mounted Extensions
Extensions Move on High Composite Bushings & Chrome Slide Track
Extensions are 8" (203 mm) Wide, with Heat, Vibration and Adjustable Angle of Attack
Extensions Provide 9% Positive Slope
Electric Valves Control In/Out, Slope & Vertical Height
Carlson's Patented "Front Taper Design" Main Screed
Main Screed is 26" (660 mm) Long, ½" (12.5 mm) Thick 400 BHN Screed Plate
Power Crown, 2½" (63 mm) Positive to ¾" (19 mm) Negative
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Thermostatically Controlled Plate Temperature with Analog Display
5.5 KW @ 120 Volts Available for Accessory Use in 8 Outlets
Heater Hold Down System Allows Heater Change Without Removing the Screed Plate
Electrically Heated Oven for Warming Meals
Spring Loaded Two Piece End Gates
20" (508 mm) Wide Main Screed Hinged Heavy Duty Walkway
12" (304 mm) Wide Hinged Extension Walkways
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

EZ-IV-10	03-0195-06-0001	$	96,865	$	-

EZ-IV-10 OPTIONS:

Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0190-06-0013	$	-	$	-
Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-0190-06-0014	$	-	$	-
Screed Options					
Pair of 12" Bolt-on Screed Extensions with Heat, Left and Right	03-0195-06-0002	$	4,685	$	-
Pair of 18" Bolt-on Screed Extensions with Heat, Left and Right	03-0195-06-0003	$	4,795	$	-
Pair of 24" Bolt-on Screed Extensions with Heat, Left and Right	03-0195-06-0004	$	4,910	$	-
Beveled Edger for "Tapered Notch" For 12" Tapered Notched Wedge Joint One edger fits left or right side Heated	03-0195-06-0005	$	3,785	$	-
Hydraulic Berm Builder with Electric Control Valves (Single Side) Manual Adjust not Available - 12"	03-0195-06-0006	$	2,880	$	-
Pair of Heated End Gates	03-0195-06-0007	$	1,630	$	-
Left Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0195-06-0008	$	2,605	$	-

Right Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0195-06-0009	$	2,605	$	-
Pair of Additional 6" Cut-off Shoes	03-0195-06-0010	$	255	$	-
Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0195-06-0012	$	445	$	-

EZ-V-10 FRONT EXTENDABLE SCREED

EZ-V-10 STANDARD FEATURES:

10' (3 m) to 19.5' (5.9 m) Hydraulically Extendable Carlson Easy Screed IV with Wide Blade Electric Heat
One 5' (1.5 m) Long & One 4' (1.2 m) Long Front Mounted Extensions
Extensions Move on High Composite Bushings & Chrome Slide Track with Improved Strength
Extensions are 8" (203 mm) Wide, with Heat, Vibration and Adjustable Angle of Attack
Extensions Provide 9% Positive Slope
Electric Valves Control In/Out, Slope & Vertical Height
Carlson's Patented "Front Taper Design" Main Screed
Main Screed is 26" (660 mm) Long, ½" (12.5 mm) Thick Hardox 450 Hardened Steel Screed Plate
Power Crown, 2½" (63 mm) Positive to ¾" (19 mm) Negative
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Thermostatically Controlled Plate Temperature with Analog Display
5.5 KW @ 120 Volts Available for Accessory Use in 8 Outlets
Heater Hold Down System Allows Heater Change Without Removing the Screed Plate
Electrically Heated Oven for Warming Meals
Spring Loaded Two Piece, Heated End Gates with easy slide on and off attachment shoes
20" (508 mm) Wide Main Screed Hinged Heavy Duty Walkway
12" (304 mm) Wide Hinged Extension Walkways
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

EZ-V-10	03-0195-09-0001	$	120,620	$	-

EZ-V-10 OPTIONS:

Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0195-09-0013	$	-	$	-
Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-0195-09-0014	$	-	$	-
Screed Options					
Pair of 12" Bolt-on Screed Extensions with Heat, Left and Right	03-0195-09-0002	$	4,685	$	-
Pair of 18" Bolt-on Screed Extensions with Heat, Left and Right	03-0195-09-0003	$	4,795	$	-
Pair of 24" Bolt-on Screed Extensions with Heat, Left and Right	03-0195-09-0004	$	4,910	$	-
Beveled Edger for "Tapered Notch" For 12" Tapered Notched Wedge Joint One edger fits left or right side Heated	03-0195-09-0005	$	3,785	$	-
Hydraulic Berm Builder with Electric Control Valves (Single Side) Manual Adjust not Available - 12"	03-0195-09-0006	$	2,880	$	-
Pair of Heated End Gates	03-0195-09-0007	$	1,630	$	-
Left Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0195-09-0008	$	2,605	$	-
Right Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0195-09-0009	$	2,605	$	-

Pair of Additional 6” Cut-off Shoes	03-0195-09-0010	$	255	$	-
Remote Jumper Harnesses	03-0195-09-0012	$	445	$	-
Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.					

Eagle-10 REAR EXTENDABLE SCREED

Eagle-10 STANDARD FEATURES:

10’ to 19’-6” Hydraulically Extendable Screed with Integral Rear Mounted Extensions
4’-9” Long Rear Extensions with 20” Wide U-Shaped Plate
Extension Plates are ½” Thick, 400 BHN Material
Extensions Move on Dual 5” Guide Tubes & Teflon Bushings
Extensions Include Pre Strike-offs, Independent Sub-Frames, Electric Heat, Vibration, and Angle of Attack Adjustment
Extensions Provide 14% Positive Slope, 5% Negative Slope
Electric Valves Control In/Out, Slope & Vertical Height
Main Screed Plate is 20” Long, ½” Thick 400 BHN Material
Main Screed Includes Adjustable Pre Strike-off, Independent Sub-Frames, Electric Heat, and Angle of Attack Adjustment
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM
Reversible U-Shaped Main Screed Plate for Extended Wear Life
Power Crown, 3” Positive to 1” Negative
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Thermostatically Controlled Screed Plate Temperature
4 kW @ 120 Volts Available for Accessory Use in Outlets
Full Length Spring Loaded Two Piece End Gates
12” Wide Full Width Telescoping Heavy Duty Walkway
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

Eagle-10	03-0195-07-0001	$	109,135	$	-

EAGLE-10 OPTIONS:

Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws	03-0195-07-0013	$	-	$	-
Counter-clockwise lowers					
Counter-Clockwise Raise Angle of Attack Screws	03-0195-07-0014	$	-	$	-
Clockwise Lowers - "Roadtec Standard"					
Screed Options					
16” Screed Extension With Heat (each, can be left or right)	03-0195-07-0002	$	6,095	$	-
28” Screed Extension With Heat (each, can be left or right)	03-0195-07-0003	$	7,215	$	-
Pair of 1’ RH & 1’ LH Cut-off Shoes	03-0195-07-0004	$	1,260	$	-
Pair of 2’ RH & 2’ LH Cut-off Shoes	03-0195-07-0005	$	1,540	$	-
Left Hand Safety Edge Beveled Endgate	03-0195-07-0006	$	2,605	$	-
Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.					
Right Hand Safety Edge Beveled Endgate	03-0195-07-0007	$	2,605	$	-
Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.					
Heated Endgates	03-0195-07-0008	$	1,630	$	-
Remote Jumper Harnesses	03-0195-07-0010	$	445	$	-
Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.					

EZ-R2-10 REAR EXTENDABLE SCREED

EZ-R2-10 STANDARD FEATURES:

10’ to 19’-6” Hydraulically Extendable Screed with Integral Rear Mounted Extensions
Electric Heat with Thermostatically Controlled Temperature with 1500 watt elements
Screed Plates are 20 Wide, ½ Thick 450 BHN Material.
Fully adjustable screed plates with adjustment cones on main and extensions.

Fully adjustable Pre Strike-Off on Main and extensions
Extensions Supported by Two 4 Guide tubes with Teflon Bushings.
Exclusive Carlson slide track system allowing for adjustment of extension parallel
Independent Angle of Attach Adjustments for Extensions.
Extensions Provide 12% Positive Slope to 5% Negative Slope.
Power Crown Provides 2" Positive to 1" Negative.
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM.
18" Wide Full Width Telescoping Heavy Duty Walkway.
Electric Valves Control Extensions, Slope, Crown & Vertical Height.
Full Length Spring Loaded Two Piece End Gates.
4'-9" Long Rear Extensions
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
4 kW @ 120 Volts Available for Accessory Use in Outlets
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

EZ-R2-10	03-0195-08-0001	**$**	**116,340**	**$**	**-**
EZ-R2-10 OPTIONS:					
Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0195-08-0013	**$**	**-**	**$**	**-**
Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-0195-08-0014	**$**	**-**	**$**	**-**
Screed Options					
16" Screed Extension With Heat (each, can be left or right)	03-0195-08-0002	**$**	**6,095**	**$**	**-**
28" Screed Extension With Heat (each, can be left or right)	03-0195-08-0003	**$**	**7,215**	**$**	**-**
Pair of 1' RH & 1' LH Cut-off Shoes	03-0195-08-0004	**$**	**1,260**	**$**	**-**
Pair of 2' RH & 2' LH Cut-off Shoes	03-0195-08-0005	**$**	**1,540**	**$**	**-**
Left Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0195-08-0006	**$**	**2,605**	**$**	**-**
Right Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	03-0195-08-0007	**$**	**2,605**	**$**	**-**
Heated Endgates	03-0195-08-0008	**$**	**1,630**	**$**	**-**
Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0195-08-0010	**$**	**445**	**$**	**-**
Warranties					
Roadtec Edge Extended Warranty (3 years or 3,000 hours total)	03-0195-03-0020	**$**	**9,400**	**$**	**-**
Manufacturer's Extended Engine Warranty (5 years or 6,000 hours total)	03-0195-03-0021	**$**	**3,820**	**$**	**-**

Roadtec Pricing Effective 7/1/2021

Quoted Item		Price Code	List Price	Customer Configuration
RP-250 - 10' (3M) RUBBER TIRE ASPHALT PAVER with Frame Raise				
	RP-250 STANDARD FEATURES:			
	¾" (19 mm) Thick Continuous Side Sheet Frame Construction 2" (50 mm) Thick Front Cross Frame Member Roadtec Guardian TM Telematics System to send/receive data remotely, change function settings (1Yr Free Subscription) Oscillating Push Rollers Direct Hydraulic Planetary Drive Three Brake System; Hydrodynamic, Parking, PMP Planetary 15.5 Ton (14 mt) Capacity/ 290 Cubic Feet Self Dumping Hopper Electric Flow Gates Independently driven variable speed feeder conveyors 1/2" (12.5 mm) 550 BHN cast head and tail plates and chromium carbide clad floor plates Conveyor By-Pass – Operate Augers Independent of Feeders 16" (406 mm) Cast ¾" Thick Ni-hard Augers Hydraulically Raise, Lower and Tilting Auger Assembly Hydroflated 24.5X32 diamond tread tires Dual 14" (355 mm) x 22" (558 mm) Front Bogies Two (2) Comfort Drive Operators Stations with Tilt Steering Wheel and Finger Tip Paver Control Dual Comfort Drive Operators stations hydraulically swing out past edge of machine for increased visibility Display at each operators station for engine diagnostics, paver diagnostics as well as speed and flow gate position Steering Assist Provides Inside Turning Radius of 4'-6" 24 Volt Starting System with Master Disconnect Switches 95 Amp Alternator Clearview FXS Fume Extraction System Hydraulic Engine Hood Raise with Manual Back Up Amber Warning Beacon, Back Up Alarm and Fire Extinguisher 1 umbrella for operator station and brackets for installation Lighted Dual Screed Control Stations for head of material and screed control with Fixed Remotes and lockable vandal covers 100 gallon (378 l) fuel tank capacity Road Light Package - Includes six 24V lights (2 hopper, 2 screed, 2 tunnel) Electrical wiring and hydraulic hoses for connection to screed			
	RP-250e Cummins QSB 6.7 250 HP Tier 4f/Stage IV Diesel Engine	03-0250-01-0003	**$ 381,385**	**$ -**
	RP-250 OPTIONS:			
	Front Wheel Assist			
	Front Wheel Assist Includes additional hydraulic motor on both rear bogie wheels.	03-0250-02-0001	**$ 25,410**	**$ -**
	Screed Options			
	Two-Speed Screed Heat High heat mode cuts power to auxilaries and increases generator output to cut screed heating time in half. Automatically switches to standard power mode when screed reaches pre-set temperature. (Does not pair with Eagle, EZ-R2.)	03-0250-02-0035	**$ 2,750**	**$ -**
	Hydraulic Screed Assist Package Designed for use with Eagle Screed. Constant up pressure on screed essentially reducing its weight all the time while in Pave mode, whether in forward, neutral or reverse.	03-0250-02-0004	**$ 3,335**	**$ -**
	Hydraulic Screed Boost Package Pressurizes the screed lift cylinders when the paver is in neutral and in pave mode to prevent depression in mat when paver stops. Lifting pressure is adjustable. Pressure is applied for adjustable time period once paver starts moving forward again. Time can be set at 0, 3 or 6 seconds.	03-0250-02-0005	**$ 2,950**	**$ -**
	Auto Feed Control Paddle Sensor Incudes standardsonic feed sensors as well as paddle sensor. Machine Screed Control Box will have switch to select desired sensor.	03-0250-02-0006	**$ 5,420**	**$ -**
	Additional Lighting			
	24V LED Night Light Package Includes Six 24V Lights	03-0250-02-0008	**$ 4,670**	**$ -**
	Saber Light Two 92-watt, LED light panels provide over 10,000 lumens	03-0250-02-0010	**$ 4,485**	**$ -**
	Airstar Balloon Light Assembly Includes Two 500 W Halogen Bulbs, Fan, Telescoping Pole, Two Brackets & Case	03-0250-02-0011	**$ 4,585**	**$ -**
	Laser Pointer Alignment Guide High intensity laser mounted to tractor can be positioned along line of travel to aid operator in aligning paver correctly.	03-0250-02-0012	**$ 3,480**	**$ -**
	Truck Dump Signal Light LED Signal light to indicate to truck driver whether to dump, stop or lower.	03-0250-02-0013	**$ 3,570**	**$ -**

One Additional Amber Beacon	03-0250-02-0033	$ 415	$	-

Auger and Tunnel Extensions				
12” Left Hand ¾” Thick Ni-Hard Auger Extension	03-0250-02-0014	$ 1,360	$	-
12” Right Hand ¾” Thick Ni-Hard Auger Extension	03-0250-02-0015	$ 1,360	$	-
12” Tunnel Extension (Either Handed)	03-0250-02-0016	$ 510	$	-
Hydraulic Tunnel Extensions Provides 18" hydraulically extending tunnel extensions for both left and right side of machine.	03-0250-02-0017	$ 6,560	$	-
Auger Extension Remotes	03-0250-02-0038	$ 1,600	$	-
6' Tunnel and Auger Extension Package Extends Augers and Tunnels 3' to each side. Includes all necessary hardware to extend augers and tunnels 3' to each side including outboard auger bearing supports and tunnel extension braces. An additional 1' auger extension and 2- 1' tunnel extension segments can be added to each side. Does not include any screed extensions.	03-0250-02-0018	$ 15,185	$	-
20.5' auger and 20.75' tunnel extension package Provides a total of 20.5' of augers and 20.75' of tunnels, can add additional 1' auger extension to each side for total of 22.5' of augers and and additional 1' tunnel extension to each side for a total of 22.75' of tunnels	03-0250-02-0019	$ 31,795	$	-

Miscellaneous				
Electrical Outlets 4 outlets: 2 located on operator station and 2 located on back of tractor	03-0250-02-0030	$ 905	$	-
Truck Hitch In Lieu of Push Rollers	03-0250-02-0020	$ 16,425	$	-
Lincoln Lube Automated Lubrication System	03-0250-02-0021	$ 10,660	$	-
Reversing Distribution Augers	03-0250-02-0022	$ 2,020	$	-
Additional Umbrella Kit	03-0250-02-0027	$ 265	$	-
Environmental Release Agent Spray Down System Includes 20 Gallon (49 L) Tank and Pump Retractable wash-down hose reel system with 30’ (9.1 m) hose length	03-0250-02-0036	$ 2,435	$	-
HD Conveyor Chain Package Includes Offset Link Conveyor Chains in lieu of standard conveyor chains	03-0250-02-0029	$ 6,505	$	-
Soft Rubber front flashing	03-0250-02-0033	$ 215	$	-

Mass Flow Hopper Inserts				
RP-190 Self Relieving Hopper Insert	03-0250-02-0025	$ 9,680	$	-
RP-190 Self Relieving Hopper Sidewall Extensions	03-0250-02-0026	$ 930	$	-

Screed Automation - Grade And Slope Control				
TOPCON Sonic Grade And Slope Control Features Dual Sonic Grade Sensors And Single Slope Sensor.	03-0250-03-0007	$ 16,835	$	-
MOBA-MATIC II Sonic Grade And Slope Control Features MOBA MATIC II controller with Dual Sonic Grade Sensors And Single Slope Sensor.	03-0250-03-0008	$ 20,120	$	-
TOPCON Sonic Averaging Ski With Hardware Includes 3 Additional Sonic Trackers. (Requires Topcon Sonic Grade and Slope System)	03-0250-03-0009	$ 15,915	$	-
MOBA Sonic Averaging Ski With Hardware Includes 2 Additional Sonic Trackers. (Requires MOBA Sonic Grade and Slope System)	03-0250-03-0010	$ 15,915	$	-
MOBA Mounting Kit Provides hardware to easily install existing MOBA Grade & Slope System. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)	03-0250-03-0011	$ 2,605	$	-
MOBA Slope Sensor	03-0250-03-0012	$ 1,800	$	-
MOBA Ski Hardware Provides physical ski, arms, sensor mounting poles, ski mounting harware, and junction box to plug in sensors. (Does not include sensor cables.)	03-0250-03-0013	$ 6,240	$	-
TOPCON Mounting Kit Provides hardware to easily install existing TOPCON Grade & Slope. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)	03-0250-03-0014	$ 3,165	$	-
TOPCON Slope Sensor	03-0250-03-0015	$ 2,270	$	-

SCREEDS

S-10e FIXED WIDTH SCREED

S-10e STANDARD FEATURES:

10’ (3 m) Vibratory Standard Screed with 4’ (1.2 m) Hydraulic Strike-offs
32” (0.8 m) Long, ½” (12.5 mm) Thick 400 BHN Screed Plate
Strike-off Articulation from 6.6% Positive to 3.3% Negative
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM
Power Crown, 3” (75 mm) Positive to 1” (25 mm) Negative
Individual Lead and Tail Crown Adjustment
18” (457 mm) Wide Full Width Hinged Heavy Duty Walkway
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Screed Plate Temperature Thermostatically Controlled with Adjustable Set Point

4 kW @ 120 Volts Available for Accessory Use or Lighting
Heater Hold-down System Allows Heater Change Without Removing the Screed Plate
Lighted Dual Screed Control Stations with Fixed Remote, Material Control and Lockable Vandal Covers
Spring Loaded Two Piece End Gates
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

S-10e	03-0250-04-0001	**$**	**85,300**	**$**	**-**

S-10e OPTIONS

Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0250-06-0013	**$**	**-**	**$**	**-**
Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-0250-06-0014	**$**	**-**	**$**	**-**
Screed Extensions					
6” Screed Extension	03-0250-04-0002	**$**	**3,845**	**$**	**-**
12” Screed Extension With Heat	03-0250-04-0003	**$**	**4,290**	**$**	**-**
24” Screed Extension With Heat and Vibration	03-0250-04-0004	**$**	**5,645**	**$**	**-**
36” Screed Extension With Heat and Vibration	03-0250-04-0005	**$**	**7,005**	**$**	**-**
24” Crownable Screed Extension With Heat - No Vibration	03-0250-04-0006	**$**	**7,765**	**$**	**-**
Left Hand Safety Edge Beveled Endgate Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	03-0250-04-0007	**$**	**2,680**	**$**	**-**
Right Hand Safety Edge Beveled Endgate Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	03-0250-04-0008	**$**	**2,680**	**$**	**-**
Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0250-04-0010	**$**	**455**	**$**	**-**

EZ-IV-10 FRONT EXTENDABLE SCREED

EZ-IV-10 STANDARD FEATURES:

10’ (3 m) to 19’ (5.8 m) Hydraulically Extendable Carlson Easy Screed IV with Wide Blade Electric Heat
One 5’ (1.5 m) Long & One 4’ (1.2 m) Long Front Mounted Extensions
Extensions Move on High Composite Bushings & Chrome Slide Track
Extensions are 8” (203 mm) Wide, with Heat, Vibration and Adjustable Angle of Attack
Extensions Provide 9% Positive Slope
Electric Valves Control In/Out, Slope & Vertical Height
Carlson’s Patented “Front Taper Design” Main Screed
Main Screed is 26” (660 mm) Long, ½” (12.5 mm) Thick 400 BHN Screed Plate
Power Crown, 2½” (63 mm) Positive to ¾” (19 mm) Negative
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Thermostatically Controlled Plate Temperature with Analog Display
5.5 KW @ 120 Volts Available for Accessory Use in 8 Outlets
Heater Hold Down System Allows Heater Change Without Removing the Screed Plate
Electrically Heated Oven for Warming Meals
Spring Loaded Two Piece End Gates
20” (508 mm) Wide Main Screed Hinged Heavy Duty Walkway
12” (304 mm) Wide Hinged Extension Walkways
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

EZ-IV-10	03-0250-06-0001	**$**	**96,865**	**$**	**-**

EZ-IV-10 OPTIONS:

Angle of Attack Screws (Must Choose One)					
Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0250-06-0013	**$**	**-**	**$**	**-**
Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-0250-06-0014	**$**	**-**	**$**	**-**
Screed Options					
Pair of 12" Bolt-on Screed Extensions with Heat, Left and Right	03-0250-06-0002	**$**	**4,685**	**$**	**-**
Pair of 18" Bolt-on Screed Extensions with Heat, Left and Right	03-0250-06-0003	**$**	**4,795**	**$**	**-**
Pair of 24" Bolt-on Screed Extensions with Heat, Left and Right	03-0250-06-0004	**$**	**4,910**	**$**	**-**
Beveled Edger for "Tapered Notch" For 12" Tapered Notched Wedge Joint One edger fits left or right side Heated	03-0250-06-0005	**$**	**3,785**	**$**	**-**
Hydraulic Berm Builder with Electric Control Valves (Single Side) Manual Adjust not Available - 12”	03-0250-06-0006	**$**	**2,880**	**$**	**-**
Pair of Heated End Gates	03-0250-06-0007	**$**	**1,630**	**$**	**-**
Left Hand Heated Safety Edge Beveled Endgate Shoe	03-0250-06-0008	**$**	**2,605**	**$**	**-**

Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element.
Ships new in box with paver. Standard shoes installed on paver from factory.

Right Hand Heated Safety Edge Beveled Endgate Shoe	03-0250-06-0009	$	2,605	$	-

Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element.
Ships new in box with paver. Standard shoes installed on paver from factory.

Pair of Additional 6" Cut-off Shoes	03-0250-06-0010	$	255	$	-
Remote Jumper Harnesses	03-0250-06-0012	$	445	$	-

Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.

EZ-V-10 FRONT EXTENDABLE SCREED

EZ-V-10 STANDARD FEATURES:

10' (3 m) to 19.5' (5.9 m) Hydraulically Extendable Carlson Easy Screed IV with Wide Blade Electric Heat
One 5' (1.5 m) Long & One 4' (1.2 m) Long Front Mounted Extensions
Extensions Move on High Composite Bushings & Chrome Slide Track with Improved Strength
Extensions are 8" (203 mm) Wide, with Heat, Vibration and Adjustable Angle of Attack
Extensions Provide 9% Positive Slope
Electric Valves Control In/Out, Slope & Vertical Height
Carlson's Patented "Front Taper Design" Main Screed
Main Screed is 26" (660 mm) Long, ½" (12.5 mm) Thick Hardox 450 Hardened Steel Screed Plate
Power Crown, 2½" (63 mm) Positive to ¾" (19 mm) Negative
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Thermostatically Controlled Plate Temperature with Analog Display
5.5 KW @ 120 Volts Available for Accessory Use in 8 Outlets
Heater Hold Down System Allows Heater Change Without Removing the Screed Plate
Electrically Heated Oven for Warming Meals
Spring Loaded Two Piece, Heated End Gates with easy slide on and off attachment shoes
20" (508 mm) Wide Main Screed Hinged Heavy Duty Walkway
12" (304 mm) Wide Hinged Extension Walkways
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

EZ-V-10	03-0250-09-0001	$	120,620	$	-

EZ-V-10 OPTIONS:

Angle of Attack Screws (Must Choose One)

Clockwise Raise Angle of Attack Screws	03-0250-09-0013	$	-	$	-

Counter-clockwise lowers

Counter-Clockwise Raise Angle of Attack Screws	03-0250-09-0014	$	-	$	-

Clockwise Lowers - "Roadtec Standard"

Screed Options

Pair of 12" Bolt-on Screed Extensions with Heat, Left and Right	03-0250-09-0002	$	4,685	$	-
Pair of 18" Bolt-on Screed Extensions with Heat, Left and Right	03-0250-09-0003	$	4,795	$	-
Pair of 24" Bolt-on Screed Extensions with Heat, Left and Right	03-0250-09-0004	$	4,910	$	-
Beveled Edger for "Tapered Notch"	03-0250-09-0005	$	3,785	$	-

For 12" Tapered Notched Wedge Joint
One edger fits left or right side
Heated

Hydraulic Berm Builder with Electric Control Valves (Single Side)	03-0250-09-0006	$	2,880	$	-

Manual Adjust not Available - 12"

Pair of Heated End Gates	03-0250-09-0007	$	1,630	$	-
Left Hand Heated Safety Edge Beveled Endgate Shoe	03-0250-09-0008	$	2,605	$	-

Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element.
Ships new in box with paver. Standard shoes installed on paver from factory.

Right Hand Heated Safety Edge Beveled Endgate Shoe	03-0250-09-0009	$	2,605	$	-

Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element.
Ships new in box with paver. Standard shoes installed on paver from factory.

Pair of Additional 6" Cut-off Shoes	03-0250-09-0010	$	255	$	-
Remote Jumper Harnesses	03-0250-09-0012	$	445	$	-

Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.

Eagle-10 REAR EXTENDABLE SCREED

Eagle-10 STANDARD FEATURES:

10' to 19'-6" Hydraulically Extendable Screed with Integral Rear Mounted Extensions
4'-9" Long Rear Extensions with 20" Wide U-Shaped Plate
Extension Plates are ½" Thick, 400 BHN Material
Extensions Move on Dual 5" Guide Tubes & Teflon Bushings
Extensions Include Pre Strike-offs, Independent Sub-Frames, Electric Heat, Vibration, and Angle of Attack Adjustment
Extensions Provide 14% Positive Slope, 5% Negative Slope
Electric Valves Control In/Out, Slope & Vertical Height
Main Screed Plate is 20" Long, ½" Thick 400 BHN Material

Main Screed Includes Adjustable Pre Strike-off, Independent Sub-Frames, Electric Heat, and Angle of Attack Adjustment
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM
Reversible U-Shaped Main Screed Plate for Extended Wear Life
Power Crown, 3" Positive to 1" Negative
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Thermostatically Controlled Screed Plate Temperature
4 kW @ 120 Volts Available for Accessory Use in Outlets
Lighted Dual Screed Control Stations with Fixed Remote
Material Height Control and Lockable Vandal Covers
Full Length Spring Loaded Two Piece End Gates
12" Wide Full Width Telescoping Heavy Duty Walkway
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

	Eagle-10	03-0250-07-0001	**$ 109,135**	**$**	**-**

EAGLE-10 OPTIONS:

	Angle of Attack Screws (Must Choose One)				
	Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0250-06-0013	**$ -**	**$**	**-**
	Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-0250-06-0014	**$ -**	**$**	**-**
	Screed Options				
	16" Screed Extension With Heat (each, can be left or right)	03-0250-07-0002	**$ 6,095**	**$**	**-**
	28" Screed Extension With Heat (each, can be left or right) (E8B Screed Extensions will not Fit the Eagle-10 Screed)	03-0250-07-0003	**$ 7,215**	**$**	**-**
	Pair of 1' RH & 1' LH Cut-off Shoes	03-0250-07-0004	**$ 1,260**	**$**	**-**
	Pair of 2' RH & 2' LH Cut-off Shoes	03-0250-07-0005	**$ 1,540**	**$**	**-**
	Left Hand Safety Edge Beveled Endgate Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	03-0250-07-0006	**$ 2,605**	**$**	**-**
	Right Hand Safety Edge Beveled Endgate Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	03-0250-07-0007	**$ 2,605**	**$**	**-**
	Heated Endgates	03-0250-07-0008	**$ 1,630**	**$**	**-**
	Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0250-07-0010	**$ 445**	**$**	**-**

EZ-R2-10 REAR EXTENDABLE SCREED

EZ-R2-10 STANDARD FEATURES:

10' to 19'-6" Hydraulically Extendable Screed with Integral Rear Mounted Extensions
Electric Heat with Thermostatically Controlled Temperature with 1500 watt elements
Screed Plates are 20 Wide, ½ Thick 450 BHN Material.
Fully adjustable screed plates with adjustment cones on main and extensions.
Fully adjustable Pre Strike-Off on Main and extensions
Extensions Supported by Two 4 Guide tubes with Teflon Bushings.
Exclusive Carlson slide track system allowing for adjustment of extension parallel
Independent Angle of Attach Adjustments for Extensions.
Extensions Provide 12% Positive Slope to 5% Negative Slope.
Power Crown Provides 2" Positive to 1" Negative.
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM.
18" Wide Full Width Telescoping Heavy Duty Walkway.
Electric Valves Control Extensions, Slope, Crown & Vertical Height.
Full Length Spring Loaded Two Piece End Gates.
4'-9" Long Rear Extensions
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
4 kW @ 120 Volts Available for Accessory Use in Outlets
Lighted Dual Screed Control Stations with Fixed Remote
Material Height Control and Lockable Vandal Covers
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

	EZ-R2-10	03-0250-08-0001	**$ 116,340**	**$**	**-**

EZ-R2-10 OPTIONS:

	Angle of Attack Screws (Must Choose One)				
	Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-0250-06-0013	**$ -**	**$**	**-**
	Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-0250-06-0014	**$ -**	**$**	**-**
	Screed Options				
	16" Screed Extension With Heat (each, can be left or right)	03-0250-08-0002	**$ 5,070**	**$**	**-**
	28" Screed Extension With Heat (each, can be left or right)	03-0250-08-0003	**$ 7,215**	**$**	**-**
	Pair of 1' RH & 1' LH Cut-off Shoes	03-0250-08-0004	**$ 1,260**	**$**	**-**

	Pair of 2' RH & 2' LH Cut-off Shoes	03-0250-08-0005	$	1,540	$	-
	Left Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element.	03-0250-08-0006	$	2,605	$	-
	Right Hand Heated Safety Edge Beveled Endgate Shoe Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.Includes heating element.	03-0250-08-0007	$	2,605	$	-
	Heated Endgates	03-0250-08-0008	$	1,630	$	-
	Remote Jumper Harnesses Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	03-0250-08-0010	$	445	$	-
	Warranties					
	Roadtec Edge Extended Warranty (3 years or 3,000 hours total)	03-0250-11-0001	$	8,870	$	-
	Manufacturer's Extended Engine Warranty (5 years 6,000 hours total)	03-0250-11-0002	$	3,820	$	-

Roadtec Pricing Effective 7/1/2021

Quoted Item		Price Code	List Price	Customer Configuration
SP-200 - 10' (3M) SPRAY PAVER				
	SP-200 STANDARD FEATURES:			
	Direct Hydraulic Planetary Drive 12 Ton Capacity Gravity Fed Hopper with Clam Shell Feed Gates 14" Cast Ni-hard Augers Frame Raise System to raise hopper, spray bar, auger assembly and screed for loading Hydraulically Raise and Lower Auger Assembly Heavy Duty D-4 Size Steel Tracks With 18" Polyurethane Grousers Dual hydraulic swing out operator's stations for improved visibility 24 Volt Electrical System with Master Disconnect Switches FXS Fume Extraction System Amber Warning Beacon, Back Up Alarm and Fire Extinguisher One (1) Operators Umbrella Lighted Dual Screed Control Stations for head of material and screed control with Fixed Remotes and lockable vandal covers Retractable Wash-down System with 50' Hose Length 145 Gallon Fuel Tank Capacity 2100 Gallon Insulated Integral Bitumen Tank Mounted In Frame of SP-200e Spray Bar System Including Emulsion Pump, Extendable Spray Bar, re-circulating System and GPM Control Box Road Light Package - Includes six 24V lights (2 front, 2 screed, 2 tunnel) Electrical wiring and hydraulic hoses for connection to screed			
	SP-200e Cummins QSB 6.7 230 HP Tier 4f Diesel Engine (Does Not Include Screed)	03-S200-01-0001	$ 918,720	$ -
	SP-200 OPTIONS:			
	Additional Lighting			
	24V LED Night Light Package Includes Six 24V Lights	03-S200-02-0001	$ 4,430	$ -
	Saber Light Two 92-watt, LED light panels provide over 10,000 lumens	03-S200-02-0003	$ 4,255	$ -
	Airstar Balloon Light Assembly Includes Two 500 W Halogen Bulbs, Fan, Telescoping Pole, Two Brackets & Case	03-S200-02-0004	$ 4,350	$ -
	One Additional Amber Beacon	03-S200-02-0005	$ 395	$ -
	Auger and Tunnel Extensions			
	12" Left Hand ¾" Thick Ni-Hard Auger Extension	03-S200-02-0006	$ 1,290	$ -
	12" Right Hand ¾" Thick Ni-Hard Auger Extension	03-S200-02-0007	$ 1,290	$ -
	12" Tunnel Extension (Either Handed)	03-S200-02-0008	$ 485	$ -
	6' Tunnel and Auger Extension Package Extends Augers and Tunnels 3' to each side. Includes all necessary hardware to extend augers and tunnels 3' to each side including outboard auger bearing supports and tunnel extension braces. An additional 1' auger extension and 2- 1' tunnel extension segments can be added to each side. Does not include any screed extensions.	03-S200-02-0009	$ 14,410	$ -
	Miscellaneous			
	Reversing Distribution Augers	03-S200-02-0010	$ 1,920	$ -
	Additional Umbrella Kit	03-S200-02-0011	$ 130	$ -
	Screed Automation - Grade And Slope Control			
	TOPCON Sonic Grade And Slope Control Features Dual Sonic Grade Sensors And Single Slope Sensor.	03-S200-03-0007	$ 16,755	$ -
	MOBA-MATIC II Sonic Grade And Slope Control	03-S200-03-0008	$ 18,455	$ -

	Features MOBA MATIC II controller with Dual Sonic Grade Sensors And Single Slope Sensor.				
	TOPCON Sonic Averaging Ski With Hardware Includes 3 Additional Sonic Trackers. (Requires Topcon Sonic Grade and Slope System)	03-S200-03-0009	**$ 15,835**	**$**	**-**
	MOBA Sonic Averaging Ski With Hardware Includes 2 Additional Sonic Trackers. (Requires MOBA Sonic Grade and Slope System)	03-S200-03-0010	**$ 15,835**	**$**	**-**
	MOBA Mounting Kit Provides hardware to easily install existing MOBA Grade & Slope System. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)	03-S200-03-0011	**$ 2,590**	**$**	**-**
	MOBA Slope Sensor	03-S200-03-0012	**$ 1,790**	**$**	**-**
	MOBA Ski Hardware Provides physical ski, arms, sensor mounting poles, ski mounting harware, and junction box to plug in sensors. (Does not include sensor cables.)	03-S200-03-0013	**$ 6,210**	**$**	**-**
	TOPCON Mounting Kit Provides hardware to easily install existing TOPCON Grade & Slope. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)	03-S200-03-0014	**$ 3,151**	**$**	**-**
	TOPCON Slope Sensor	03-S200-03-0015	**$ 2,260**	**$**	**-**

SCREEDS

Eagle-10 REAR EXTENDABLE SCREED

Eagle-10 STANDARD FEATURES:

10’ to 19’-6” Hydraulically Extendable Screed with Integral Rear Mounted Extensions
4’-9” Long Rear Extensions with 20” Wide U-Shaped Plate
Extension Plates are ½” Thick, 400 BHN Material
Extensions Move on Dual 5” Guide Tubes & Teflon Bushings
Extensions Include Pre Strike-offs, Independent Sub-Frames, Electric Heat, Vibration, and Angle of Attack Adjustment
Extensions Provide 14% Positive Slope, 5% Negative Slope
Electric Valves Control In/Out, Slope & Vertical Height
Main Screed Plate is 20” Long, ½” Thick 400 BHN Material
Main Screed Includes Adjustable Pre Strike-off, Independent Sub-Frames, Electric Heat, and Angle of Attack Adjustment
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM
Reversible U-Shaped Main Screed Plate for Extended Wear Life
Power Crown, 3” Positive to 1” Negative
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump
Thermostatically Controlled Screed Plate Temperature
4 kW @ 120 Volts Available for Accessory Use in Outlets
Full Length Spring Loaded Two Piece End Gates
12” Wide Full Width Telescoping Heavy Duty Walkway
Sonic Feeder Control System
Tow arms with mounting locations for automatic grade controls

	Eagle-10	03-S200-04-0001	**$ 102,595**	**$**	**-**

EAGLE-10 OPTIONS:

	Angle of Attack Screws (Must Choose One)				
	Clockwise Raise Angle of Attack Screws Counter-clockwise lowers	03-S200-04-0013	**$ -**	**$**	**-**
	Counter-Clockwise Raise Angle of Attack Screws Clockwise Lowers - "Roadtec Standard"	03-S200-04-0014	**$ -**	**$**	**-**
	Screed Options				
	Pair of 1’ RH & 1’ LH Cut-off Shoes	03-S200-04-0002	**$ 1,260**	**$**	**-**
	Pair of 2’ RH & 2’ LH Cut-off Shoes	03-S200-04-0003	**$ 1,540**	**$**	**-**
	Left Hand Safety Edge Beveled Endgate Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	03-S200-04-0004	**$ 1,580**	**$**	**-**

	Right Hand Safety Edge Beveled Endgate Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	03-S200-04-0005	**$**	**1,580**	**$**	**-**
	Heated Endgates	03-S200-04-0006	**$**	**1,635**	**$**	**-**
	Warranties					
	Roadtec Edge Extended Warranty (3 years or 3,000 hours total)	03-s200-12-0001	**$**	**21,865**	**$**	**-**
	Manufacturer's Extended Engine Warranty (5 years or 6,000 hours total)	03-s200-12-0001	**$**	**3,820**	**$**	**-**

Roadtec Pricing Effective 7/1/2021

Quoted Item		Price Code	List Price	Customer Configuration
FB-100 - FRONT MOUNTED BROOM				
	FB-100 STANDARD FEATURES:			
	Kubota 74 HP Tier 4 Final Engine			
	Heavy Duty 14,000 lbs capacity axles			
	Rear steering axle			
	Working Speed 13 mph (21 kph), Travel Speed 22 mph (35 kph)			
	LT215-75 R15 Tires with heavy duty steel wheels			
	Infinitely variable width broom head with side shift capabilities			
	Closed loop hydraulic circuit for propel			
	Load sense auxiliary hydraulic circuit			
	Planetary reduction at the wheels with sealed wet disc brakes			
	Pressurized cab with A/C and heat			
	Sealed AC Compressor			
	Manual lift, removable hood raises for excellent engine access			
	Steering wheel control of tractor steering			
	Levers for throttle and drive direction with push button control of broom head			
	Fully adjustable reclining seat with armrests			
	Down pressure adjustment for broom located in cab			
	Speed adjustment for broom rotation located in cab			
	Minimum broom width 72" (183 cm), Maximum broom width 96" (244 cm)			
	Sealed wet brakes with parking brake			
	Expandable headlight bar with front and rear lights			
	Windshield wiper with washer			
	Heavy duty 16 gauge wiring			
	FB-100e	11-F100-01-0001	**$ 103,050**	**$ -**
	FB-100 OPTIONS:			
	Miscellaneous			
	Spare Tire	11-F100-02-0001	**$ 630**	**$ -**
	Wafer Broom Core in lieu of standard solid broom core	11-F100-02-0004	**$ 3,015**	**$ -**
	Water Spray System	11-F100-02-0003	**$ 8,000**	**$ -**
	Includes water spray bar, hosing, 110 gal water tank and controls		**$ -**	
	Flasher/Brake Light/ Blinker Package	11-F100-02-0005	**$ 2,140**	**$ -**
	Hood Hydraulic Cylinder w/ hand jack	11-F100-02-0007	**$ 2,015**	**$ -**

Roadtec Pricing Effective 7/1/2021

Quoted Item		Price Code	List Price	Customer Configuration
RX-505 - HALF LANE COLD PLANER				
	RX-505 STANDARD FEATURES:			
	Engine Load Control Automatic Traction Control Front, Rear Auto-Center, Crab and Coordinated Steer Direct Hydraulic Planetary Track Drives Folding Operator Seats 900 Gallon Water Tank with Three Fill Stations High Pressure Wash Down System with Retractable Hose Reel Hydraulic Variable Flow Water Pump Automated Water Spray System 32” Primary Conveyor With Endless Heavy Duty Belt 32” Secondary Conveyor With Endless Belt Secondary Conveyor Has Full 120 Degree Swing Capability Hydraulically Folding Secondary Conveyor Endless Belts with ¾” Tall Molded Rubber Cleats Truck Rails on Secondary Conveyor Self-Cleaning Head And Tail Pulleys Left Side/Right Side Full Function Operators Control Stations Lighted Instrument Console with Liquid Filled Gauges Air Compressor With Reservoir And Air Tools Ground Level Storage Compartments Ground Level Controls For Moldboard, End Gates, Elevation, and Secondary Conveyor Remote Grease Fittings Arranged In Zones Light Package Consisting of Ten (10) 24 Volt Lights Two magnetic base 24 VDC halogen work lights Six 24 VDC power outlets. Shock mounted operator’s platform and console. Polyurethane Bolt-On Replaceable Track Pads Dust Extraction System (Tier 4 version only) Safety Controls Including Emergency Engine Shut-Down, Cutter Disengage and Engine Shut-Down when Cutter Door is Opened Rear back-up camera			
	RX-505e-4 4 Track - Tier 4F Cummins QSX-15 Engine rated at 600 HP	02-0505-01-0002	$ 529,986	$ -
	RX-505 OPTIONS:			
	Auxiliary Power			
	4 kW Generator Set	02-0505-02-0001	$ 5,529	$ -
	Additional Lighting			
	24V LED Night Light Package Light set consisting of four 24V Lights, mounting hardware and wiring.	02-0505-02-0002	$ 2,245	$ -
	Miscellaneous			
	Automated Lubrication System	02-0505-02-0005	$ 9,996	$ -
	Hydraulically Folding Canopy	02-0505-02-0006	$ 13,610	$ -
	Automation - Grade and Slope Controls			
	ACE Grade and Slope Automation with Auto-Cut	02-0505-03-0001	$ 26,713	$ -

Automates elevation of front and rear legs of milling machine by using grade sensors or a slope sensor for the right and left hand side of machine. System automates rear elevation of machine during entry of each cut. System includes 3 ACE Control panels that can be connected at the operator station and on the ground at the middle of the machine or in the rear to control both sides of the machine, 1 central microcontroller, 1 5-eye sonic sensor, plugs at side of machine for controls and sensors, mounting hardware, cables and junction boxes. Utilizes MOBA brand slope and sonic sensors.

Prewiring for ACE Averaging Ski		**$**	**3,851**	**$**	**-**
Includes junction boxes and cables to corners of machine for Averaging Ski, does not included sensors or mounting hardware.					
ACE - Single Averaging Ski - Requires Base System		**$**	**9,962**	**$**	**-**
Provides averaging of grade for one side of machine. Junction box and sensor connections are installed on both sides of machine so sensors and arms can easily be swapped to either side of machine. Requires base ACE Grade and Slope Automation. Includes 2 sonic sensors with 5 transducers each. One for front and rear corner of machine, 2 junction boxes, cables and mounting hardware.					
ACE - Dual Averaging Ski - Requires both Single Ski and Base Systems		**$**	**6,775**	**$**	**-**
Provides hardware to upgrade single averaging ski to dual averaging ski. Requires ACE Grade and Slope Automation and ACE Single Averaging Ski. Includes 2 sonic sensors with 5 transducers each. One for front and rear corner of machine, cables and mounting hardware.					

CUTTER HOUSINGS

79" (2.0 m) Cutter Housing - CH505-79

CH505-79 STANDARD FEATURES:

Bolt-On Cutter Assembly With Mechanical V-Belt Drive
O&K Cutter Gear Box
Belt Lifting Device for Cutter Maintenance
Drum Index
Front & Rear Water Spray Bars with Flow and Pressure Control
13” Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners

CH505-79	02-0505-04-0001	**$**	**78,820**	**$**	**-**
79" Housing (CUTTER HOUSING ONLY)					

CH505-79 OPTIONS

Drum Options

6’7” (79") (2.0 m) QX1 Single Hit Drum with 5/8” Spacing	02-0505-04-0002	**$**	**32,064**	**$**	**-**
6’7” (79") (2.0 m) Kennametal Single Hit Drum with 5/8” Spacing	02-0505-04-0003	**$**	**34,251**	**$**	**-**

86" (2.18 m) Cutter Housing - CH505-86

CH505-86 STANDARD FEATURES:

Bolt-On Cutter Assembly With Mechanical V-Belt Drive
O&K Cutter Gear Box
Belt Lifting Device for Cutter Maintenance
Drum Index
Front & Rear Water Spray Bars with Flow and Pressure Control
13” Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners

CH505-86	02-0505-05-0001	**$**	**79,770**	**$**	**-**
86" Housing (CUTTER HOUSING ONLY)					

CH505-86 OPTIONS

Drum Options

	7'2" (86") (2.18 m) QX1 Single Hit Drum with 5/8" Spacing	02-0505-05-0002	**$**	**37,685**	**$**	**-**
	7'2" (86") (2.18 m) Kennametal Single Hit Drum with 5/8" Spacing	02-0505-05-0003	**$**	**39,801**	**$**	**-**
	Warranties					
	Roadtec Edge Extended Warranty (3 years or 3,000 hours total)	02-0505-06-0001	**$**	**8,333**	**$**	**-**
	Manufacturer's Extended Engine Warranty (5 years or 6,000 hours total)	02-0505-06-0002	**$**	**8,078**	**$**	**-**

Roadtec Pricing Effective 7/1/2021

Quoted Item	Option Not Included		Price Code	List Price	Customer Configuration
RX-600 - HALF LANE COLD PLANER					
		RX-600 STANDARD FEATURES:			
		Engine Load Control Automatic Traction Control Front, Rear Auto-Center, Crab and Coordinated Steer Direct Hydraulic Planetary Track Drives Foot per minute meter 800 Gallon Water Tank with Three Fill Stations High Pressure Wash Down System with Retractable Hose Reel Hydraulic Variable Flow Water Pump Auto on/off spray water system 32” Primary Conveyor With Endless Heavy Duty Belt 32” Secondary Conveyor With Endless Belt Secondary Conveyor Has Full 120 Degree Swing Capability Endless Belts with ¾” Tall Molded Rubber Cleats Truck Rails on Secondary Conveyor Self-Cleaning Head And Tail Pulleys Left Side/Right Side Full Function Operators Control Stations Lighted Instrument Console with Liquid Filled Gauges Air Compressor With Reservoir And Air Tools Operators Console Umbrella with Mounting Hardware Ground Level Controls For Moldboard, End Gates & Elevation Remote Grease Fittings Arranged In Zones Light Package Consisting of Ten (10) 24 Volt Lights Two magnetic base 24 VDC halogen work lights Six 24 VDC power outlets. Shock mounted operator’s platform and console. Polyurethane Bolt-On Replaceable Track Pads Dust Extraction System Safety Controls Including Emergency Engine Shut-Down, Cutter Disengage and Engine Shut-Down when Cutter Door is Opened Rear back-up camera			
		RX-600e-3 3 Track - Tier 4F Cummins QSX-15 Engine rated at 675 HP	02-0600-01-0005	$ 502,195	$ -
		RX-600e-4 4 Track - Tier 4F Cummins QSX-15 Engine rated at 675 HP	02-0600-01-0006	$ 524,785	$ -
		RX-600 OPTIONS:			
		Conveyor			
		Straight Secondary Conveyor	02-0600-02-0028	$ -	$ -
		Hydraulic Folding Secondary Conveyor	02-0600-02-0004	$ 16,915	$ -
		Auxiliary Power			
		4 kW Generator Set	02-0600-02-0001	$ 5,695	$ -
		7.5 kW Generator Set	02-0600-02-0002	$ 8,070	$ -
		Additional Lighting			
		24V LED Night Light Package Light set consisting of four 24V Lights, mounting hardware and wiring.	02-0600-02-0003	$ 2,310	$ -
		Saber Light	02-0600-02-0026	$ 4,170	$ -

Two 92-watt, LED light panels provide over 10,000 lumens

Truck Signal Light	02-0600-02-0027	$	2,895	$	-
Magnetic based LED light to indicate to dump truck driver when to stop or proceed					

Miscellaneous					
Automated Lubrication System	02-0600-02-0005	$	10,295	$	-
Operator Seats	02-0600-02-0007	$	3,610	$	-
Includes an operator's seat for each control station that can be used during operation and then slid out of the way for standing operation or transport.					
Hydraulically Folding Canopy	02-0600-02-0008	$	14,710	$	-
Rear Water Pump	02-0600-02-0013	$	3,530	$	-
Secondary Conveyor Camera	02-0600-02-0029	$	1,425	$	-
Guardian Totalizer	02-0600-02-0025	$	1,995	$	-
LED Display of real time production					
Rear Object Detection System	02-0600-02-0031	$	12,190	$	-

Automation - Grade and Slope Controls					
ACE Grade and Slope Automation with Auto-Cut	02-0600-03-0002	$	27,515	$	-
Automates elevation of front and rear legs of milling machine by using grade sensors or a slope sensor for the right and left hand side of machine. System automates rear elevation of machine during entry of each cut. System includes 3 ACE Control panels that can be connected at the operator station and on the ground at the middle of the machine or in the rear to control both sides of the machine, 1 central microcontroller, 1 5-eye sonic sensor, plugs at side of machine for controls and sensors, mounting hardware, cables and junction boxes. Utilizes MOBA brand slope and sonic sensors.					
Prewiring for ACE Averaging Ski	02-0600-03-0003	$	3,970	$	-
Includes junction boxes and cables to corners of machine for Averaging Ski, does not included sensors or mounting hardware.					
ACE - Single Averaging Ski - Requires Base System	02-0600-03-0004	$	10,260	$	-
Provides averaging of grade for one side of machine. Junction box and sensor connections are installed on both sides of machine so sensors and arms can easily be swapped to either side of machine. Requires base ACE Grade and Slope Automation. Includes 2 sonic sensors with 5 transducers each. One for front and rear corner of machine, 2 junction boxes, cables and mounting hardware.					
ACE - Dual Averaging Ski - Requires both Single Ski and Base Systems	02-0600-03-0005	$	6,975	$	-
Provides hardware to upgrade single averaging ski to dual averaging ski. Requires ACE Grade and Slope Automation and ACE Single Averaging Ski. Includes 2 sonic sensors with 5 transducers each. One for front and rear corner of machine, cables and mounting hardware.					

CUTTER HOUSINGS

75" (1.9 m) Cutter Housing - CH601-75 - Only Available with 3 Track

CH601-75 STANDARD FEATURES:

Bolt-On Cutter Assembly With Mechanical V-Belt Drive
W-40 Fairfield Cutter Gear Box with “Break-a-Way” Input Shaft
Front & Rear Water Spray Bars with Flow and Pressure Control
13” Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners

CH601-75	02-0600-04-0001	$	76,975	$	-
75" Housing (CUTTER HOUSING ONLY) - Only with 3 Track:					

CH601-75 OPTIONS

Drum Options					
75" (1.9 m) QX1 with 5/8" Spacing	02-0600-04-0009	**$**	**30,770**	**$**	**-**
75" (1.9 m) Kennametal Drum with 5/8" Spacing	02-0600-04-0003	**$**	**34,400**	**$**	**-**
75" (1.9 m) "Roadrunner" QX1 Double Hit - 0.851" Spacing	02-0600-04-0010	**$**	**43,075**	**$**	**-**
75" (1.9 m) "Roadrunner" Kennametal Double Hit - 0.851" Spacing	02-0600-04-0005	**$**	**46,710**	**$**	**-**
75" (1.9 m) QX1 Profiling Drum with 3/8" Spacing	02-0600-04-0011	**$**	**55,380**	**$**	**-**
75" (1.9 m) Kennametal Profiling Drum with 3/8" Spacing	02-0600-04-0007	**$**	**59,015**	**$**	**-**
75" (1.9 m) Weld-on Micromill Drum with 0.2" Spacing Kennametal C10	02-0600-04-0008	**$**	**60,245**	**$**	**-**

79" (2.0 m) Cutter Housing - CH601-79

CH601-79 STANDARD FEATURES:

Bolt-On Cutter Assembly With Mechanical V-Belt Drive
W-40 Fairfield Cutter Gear Box with "Break-a-Way" Input Shaft
Front & Rear Water Spray Bars with Flow and Pressure Control
13" Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners

CH601-79 79" Housing (CUTTER HOUSING ONLY)	02-0600-05-0001	**$**	**78,055**	**$**	**-**

CH601-79 OPTIONS

Drum Options					
6'7" (79") (2.0 m) QX1 Single Hit Drum with 5/8" Spacing	02-0600-05-0002	**$**	**31,755**	**$**	**-**
6'7" (79") (2.0 m) Kennametal Single Hit Drum with 5/8" Spacing	02-0600-05-0003	**$**	**36,140**	**$**	**-**
6'7" (79") (2.0 m) "Roadrunner" QX1 Double Hit - 0.851" Spacing	02-0600-05-0010	**$**	**45,050**	**$**	**-**
6'7" (79") (2.0 m) "Roadrunner" Kennametal Double Hit - 0.851" Spacing	02-0600-05-0005	**$**	**49,105**	**$**	**-**
6'7" (79") (2.0 m) QX1 Profiling Single Hit Drum with 3/8" Spacing	02-0600-05-0011	**$**	**58,335**	**$**	**-**
6'7" (79") (2.0 m) Kennametal Profiling Drum with 3/8" Spacing	02-0600-05-0007	**$**	**62,060**	**$**	**-**
6'7" (79") (2.0 m) QX1 Single Hit Drum with 8mm Spacing		**$**	**62,975**	**$**	**-**
6'7" (79") (2.0 m) QX1 Single Hit Drum with 6mm Spacing		**$**	**68,455**	**$**	**-**
6'7" (79") (2.0 m) Weld-on Micromill Single Hit Drum with 0.2" Spacing Kennametal C10	02-0600-05-0008	**$**	**63,360**	**$**	**-**

86" (2.18 m) Cutter Housing - CH601-86

CH601-86 STANDARD FEATURES:

Bolt-On Cutter Assembly With Mechanical V-Belt Drive
W-40 Fairfield Cutter Gear Box with "Break-a-Way" Input Shaft
Front & Rear Water Spray Bars with Flow and Pressure Control
13" Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners

CH601-86 79" Housing (CUTTER HOUSING ONLY)	02-0600-06-0001	**$**	**78,995**	**$**	**-**

CH601-86 OPTIONS

Drum Options					
7'2" (86") (2.18 m) QX1 Single Hit Drum with 5/8" Spacing	02-0600-06-0002	**$**	**35,280**	**$**	**-**
7'2" (86") (2.18 m) Kennametal Single Hit Drum with 5/8" Spacing	02-0600-06-0003	**$**	**39,145**	**$**	**-**
7'2" (86") (2.2 m) "Roadrunner" QX1 Double Hit - 0.851" Spacing	02-0600-06-0011	**$**	**48,720**	**$**	**-**
7'2" (86") (2.2 m) "Roadrunner" Kennametal Double Hit - 0.851" Spacing	02-0600-06-0005	**$**	**53,255**	**$**	**-**
7'2" (86") (2.18 m) QX1 Profiling Single Hit Drum with 3/8" Spacing	02-0600-06-0012	**$**	**62,980**	**$**	**-**
7'2" (86") (2.18 m) Kennametal Profiling Single Hit Drum with 3/8" Spacing	02-0600-06-0007	**$**	**63,970**	**$**	**-**
7'2" (86") (2.18 m) QX1 Single Hit Drum With 8mm Spacing	02-0600-06-0013	**$**	**70,400**	**$**	**-**
7'2" (86") (2.18 m) QX1 Single Hit Drum With 6mm Spacing	02-0600-06-0010	**$**	**78,205**	**$**	**-**
7'2" (86") (2.18 m) Weld-on Micromill Single Hit Drum with 0.2" Spacing Kennametal C10	02-0600-06-0008	**$**	**68,780**	**$**	**-**

Variable Cutter System (VCS) Housing CH601-VCS12

VCS STANDARD FEATURES:

Bolt-On Cutter Assembly With Mechanical V-Belt Drive
W-40 Fairfield Cutter Gear Box with “Break-a-Way” Input Shaft
Front & Rear Water Spray Bars with Flow and Pressure Control
13” Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners
12" Depth of Cut
Special VCS Housing with segmented rear moldboard allows change of cutting widths by only changing drum shell

CH601-VCS12	02-0600-07-0001	**$**	**98,590**	**$**	**-**
Variable Cutter System Housing (DOES NOT INCLUDE ANY DRUM):					

CH601-VCS12 OPTIONS:

Drum Options					
24” (610 m) Standard Drum - 5/8” (16 mm) Spacing - QX1	02-0600-07-0018	**$**	**22,525**	**$**	**-**
24” (610 m) Standard Drum - 5/8” (16 mm) Spacing - Kennametal	02-0600-07-0003	**$**	**23,435**	**$**	**-**
36” (914 m) Standard Drum - 5/8” (16 mm) Spacing - QX1	02-0600-07-0020	**$**	**25,920**	**$**	**-**
36” (914 m) Standard Drum - 5/8” (16 mm) Spacing - Kennametal	02-0600-07-0008	**$**	**26,780**	**$**	**-**
48” (1.22 m) Standard Drum - 5/8” (16 mm) Spacing - QX1	02-0600-07-0022	**$**	**59,920**	**$**	**-**
48” (1.22 m) Standard Drum - 5/8” (16 mm) Spacing - Kennametal	02-0600-07-0013	**$**	**30,125**	**$**	**-**
Cutter Housing Options					
5' (1.5 m) Cutting Width Package	02-0600-07-0017	**$**	**34,362**	**$**	**-**
Includes 5' (1.5 m) Cutter Drum, 5' (1.5 m) wide rear moldboard and 1' (610 mm) bolt on extension to cutter housing and front moldboard. Also includes water spray bar extensions.					

Warranties					
Roadtec Edge Extended Warrranty - RX-600e 3 track (3 yr / 3000 hr Total)	02-0600-50-0001	**$**	**12,310**	**$**	**-**
Roadtec Edge Extended Warrranty - RX-600e 4 track (3 yr / 3000 hr Total)	02-0600-50-0004	**$**	**12,865**		
Manufacturer's Extended Engine Warranty (5 years or 6,000 hours total)	02-0600-02-0021	**$**	**9,515**	**$**	**-**

Roadtec Pricing Effective 7/1/2021

Quoted Item		Price Code	List Price	Customer Configuration
RX-700 - HIGH PRODUCTION HALF LANE COLD PLANER				
	RX-700 STANDARD FEATURES:			
	Engine Load Control Automatic Traction Control Front, Rear, Crab and Coordinated Steer Direct Hydraulic Planetary Track Drives Foot per minute meter High Pressure Wash Down System Hydraulic Variable Flow Water Pump Auto on/off spray water system 36” Primary Conveyor With Endless Heavy Duty Belt 36” Secondary Conveyor With Endless Belt Secondary Conveyor Has Full 120 Degree Swing Capability Endless Belts with ¾” Tall Molded Rubber Cleats Truck Rails on Secondary Conveyor Self-Cleaning Head And Tail Pulleys Left Side/Right Side Full Function Operators Control Stations Lighted Instrument Console with Liquid Filled Gauges Air Compressor With Reservoir And Air Tools Operators Console Umbrella with Mounting Hardware Ground Level Controls For Moldboard, End Gates & Elevation Remote Grease Fittings Arranged In Zones Light Package Consisting of Ten (10) 24 Volt Lights Two magnetic base 24 VDC halogen work lights Six 24 VDC power outlets. Polyurethane Bolt-On Replaceable Track Pads Shock mounted operator’s platform and console. Dust Extraction System Safety Controls Including Emergency Engine Shut-Down, Cutter Disengage, Rear back-up camera, and Engine Shut-Down when Cutter Door is Opened			
	RX-700e-3 Tier 4F Caterpillar C18 engine rated at 800 hp	02-0700-01-0005	$ 621,445	$ -
	RX-700e-4 Tier 4F Caterpillar C18 engine rated at 800 hp	02-0700-01-0006	$ 653,165	$ -
	RX-700 OPTIONS:			
	Conveyor			
	Straight Secondary Conveyor	02-0700-02-0028		$ -
	Hydraulic Folding Secondary Conveyor	02-0700-02-0004	$ 17,165	$ -
	Auxiliary Power			
	4 kW Generator Set	02-0700-02-0001	$ 5,780	$ -
	15 kW Generator Set	02-0700-02-0002	$ 8,185	$ -
	Additional Lighting			
	24V LED Night Light Package Light set consisting of four 24V Lights, mounting hardware and wiring.	02-0700-02-0003	$ 2,345	$ -
	Saber Light Two 92-watt, LED light panels provide over 10,000 lumens	02-0700-02-0026	$ 4,235	$ -
	Truck Signal Light	02-0700-02-0027	$ 2,940	$ -

Magnetic based LED light to indicate to dump truck driver when to stop or proceed

Miscellaneous					
Automated Lubrication System	02-0700-02-0005	$	10,450	$	-
Operator Seats	02-0700-02-0006	$	3,590	$	-
Includes an operator's seat for each control station that can be used during operation and then slid out of the way for standing operation or transport. Cannot be installed on units configured					
Rear Tow Hitch Assembly	02-0700-02-0007	$	2,775	$	-
Weldment to tow machine or to connect to tanker for water or emulsion. Includes pintle hitch and support structure directly welded to frame. Not needed with CIR additive system.					
Hydraulically Folding Canopy	02-0700-02-0008	$	14,925	$	-
Secondary Conveyor Camera	02-0700-02-0029	$	1,425	$	-
Rear Object Detection System	02-0700-02-0032	$	12,370	$	-
Guardian Totalizer	02-0700-02-0025	$	2,025	$	-
LED Display of real time production					

Automation - Grade and Slope Controls					
ACE Grade and Slope Automation with Auto-Cut	02-0700-03-0002	$	27,920	$	-
Automates elevation of front and rear legs of milling machine by using grade sensors or a slope sensor for the right and left hand side of machine. System automates rear elevation of machine during entry of each cut. System includes 3 ACE Control panels that can be connected at the operator station and on the ground at the middle of the machine or in the rear to control both sides of the machine, 1 central microcontroller, 1 5-eye sonic sensor, plugs at side of machine for controls and sensors, mounting hardware, cables and junction boxes. Utilizes MOBA brand slope and sonic sensors.					
Prewiring for ACE Averaging Ski	02-0700-03-0003	$	4,025	$	-
Includes junction boxes and cables to corners of machine for Averaging Ski, does not included sensors or mounting hardware.					
ACE - Single Averaging Ski - Requires Base System	02-0700-03-0004	$	10,410	$	-
Provides averaging of grade for one side of machine. Junction box and sensor connections are installed on both sides of machine so sensors and arms can easily be swapped to either side of machine. Requires base ACE Grade and Slope Automation. Includes 2 sonic sensors with 5 transducers each. One for front and rear corner of machine, 2 junction boxes, cables and mounting hardware.					
ACE - Dual Averaging Ski - Requires both Single Ski and Base Systems	02-0700-03-0005	$	7,080	$	-
Provides hardware to upgrade single averaging ski to dual averaging ski. Requires ACE Grade and Slope Automation and ACE Single Averaging Ski. Includes 2 sonic sensors with 5 transducers each. One for front and rear corner of machine, cables and mounting hardware.					

CUTTER HOUSINGS

79" (2.0 m) Cutter Housing - CH701-79

CH701-79 STANDARD FEATURES:

Bolt-On Cutter Assembly With Mechanical V-Belt Drive
W-50 Fairfield Cutter Gear Box with “Break-a-Way” Input Shaft
Front & Rear Water Spray Bars with Flow and Pressure Control
14” Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners

CH701-79	02-0700-04-0001	$	82,470	$	-
79" Housing (CUTTER HOUSING ONLY)					

CH701-79 OPTIONS

Drum Options					
6’7” (79") (2.0 m) QX1 Single Hit Drum with 5/8” Spacing	02-0700-04-0010	$	34,535	$	-
6’7” (79") (2.0 m) Kennametal Single Hit Drum with 5/8” Spacing	02-0700-04-0003	$	37,025	$	-

6’7” (79") (2.0 m) "Roadrunner" QX1 Double Hit - 0.851" Spacing	02-0700-04-0011	**$**	**47,155**	**$**	**-**
6’7” (79") (2.0 m) "Roadrunner" Kennametal Double Hit - 0.851" Spacing	02-0700-04-0005	**$**	**50,310**	**$**	**-**
6’7” (79") (2.0 m) QX1 Profiling Single Hit Drum with 3/8” Spacing	02-0700-04-0012	**$**	**59,770**	**$**	**-**
6’7” (79") (2.0 m) Kennametal Profiling Drum with 3/8” Spacing	02-0700-04-0007	**$**	**63,595**	**$**	**-**
6’7” (79") (2.0 m) QX1 Single Hit Drum with 8mm Spacing	02-0700-04-0014	**$**	**64,980**	**$**	**-**
6’7” (79") (2.0 m) QX1 Single Hit Drum with 6mm Spacing	02-0700-04-0015	**$**	**74,855**	**$**	**-**
6’7” (79") (2.0 m) Weld-on Micromill Single Hit Drum with 0.2” Spacing Kennamet	02-0700-04-0008	**$**	**64,925**	**$**	**-**
Cutter Housing Options					
Cutter Housing Bi-Directional Package Includes scraper blade on conveyor side moldboard, reversed endgates, additional flashing at corners of housing.	02-0700-04-0009	**$**	**4,965**	**$**	**-**
W-80 Gearbox in Lieu of Standard W-50 Gearbox Replaces standard Fairfield W-50 Cutter Drum Gearbox with W-80 Gearbox	02-0700-04-0013	**$**	**9,680**	**$**	**-**

86" (2.18 m) Cutter Housing - CH701-86

CH701-86 STANDARD FEATURES:

Bolt-On Cutter Assembly With Mechanical V-Belt Drive
W-50 Fairfield Cutter Gear Box with “Break-a-Way” Input Shaft
Front & Rear Water Spray Bars with Flow and Pressure Control
14” Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners

CH701-86 86" Housing (CUTTER HOUSING ONLY)	02-0700-05-0001	**$**	**83,305**	**$**	**-**

CH701-86 OPTIONS

Drum Options					
7’2” (86") (2.18 m) QX1 Single Hit Drum with 5/8” Spacing	02-0700-05-0011	**$**	**37,595**	**$**	**-**
7’2” (86") (2.18 m) Kennametal Single Hit Drum with 5/8” Spacing	02-0700-05-0003	**$**	**40,105**	**$**	**-**
7’2” (86") (2.2 m) "Roadrunner" QX1 Double Hit - 0.851" Spacing	02-0700-05-0012	**$**	**51,330**	**$**	**-**
7’2” (86") (2.2 m) "Roadrunner" Kennametal Double Hit - 0.851" Spacing	02-0700-05-0005	**$**	**54,570**	**$**	**-**
7’2” (86") (2.2 m) Sollami Double Hit - 0.5" Spacing	02-0700-05-0019	**$**	**73,920**	**$**	**-**
7’2” (86") (2.18 m) QX1 Profiling Single Hit Drum with 3/8” Spacing	02-0700-05-0013	**$**	**65,070**	**$**	**-**
7’2” (86") (2.18 m) Kennametal Profiling Single Hit Drum with 3/8” Spacing	02-0700-05-0007	**$**	**69,030**	**$**	**-**
7'2" (86") (2.18 m) QX1 Single Hit Drum With 8mm Spacing	02-0700-05-0015	**$**	**69,645**	**$**	**-**
7'2" (86") (2.18 m) QX1 Single Hit Drum With 6mm Spacing	02-0700-05-0016	**$**	**83,105**	**$**	**-**
7’2” (86") (2.18 m) Weld-on Micromill Single Hit Drum with 0.2” Spacing Kenname	02-0700-05-0008	**$**	**70,475**	**$**	**-**
Cutter Housing Options					
Cutter Housing Bi-Directional Package Includes scraper blade on conveyor side moldboard, reversed endgates, additional flashing at corners of housing.	02-0700-05-0009	**$**	**5,040**	**$**	**-**
W-80 Gearbox in Lieu of Standard W-50 Gearbox Replaces standard Fairfield W-50 Cutter Drum Gearbox with W-80 Gearbox	02-0700-05-0014	**$**	**9,680**	**$**	**-**

98" (2.5 m) Cutter Housing - CH702-98

CH702-98 STANDARD FEATURES:

Bolt-On Cutter Assembly With Mechanical V-Belt Drive
W-50 Fairfield Cutter Gear Box with “Break-a-Way” Input Shaft
Front & Rear Water Spray Bars with Flow and Pressure Control
14” Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners

CH702-98 98" Housing (CUTTER HOUSING ONLY)	02-0700-06-0001	**$**	**86,585**	**$**	**-**

CH701-98 OPTIONS					
Drum Options					
8’2” (98") (2.5 m) QX1 Single Hit Drum With 5/8” Spacing	02-0700-06-0010	$	45,310	$	-
8’2” (98") (2.5 m) Kennametal Single Hit Drum With 5/8” Spacing	02-0700-06-0003	$	49,820	$	-
8’2” (98") (2.5 m) "Roadrunner" QX1 Double Hit - 0.851" Spacing	02-0700-06-0011	$	59,730	$	-
8’2” (98") (2.5 m) "Roadrunner" Kennametal Double Hit - 0.851" Spacing	02-0700-06-0005	$	64,235	$	-
8’2” (98") (2.5 m) QX1 Profiling Single Hit Drum With 3/8” Spacing	02-0700-06-0012	$	74,145	$	-
8’2” (98") (2.5 m) Kennametal Profiling Single Hit Drum With 3/8” Spacing	02-0700-06-0007	$	77,105	$	-
8’2” (98") (2.5 m) QX1 Single Hit Drum With 8mm Spacing	02-0700-06-0014	$	79,565	$	-
8’2” (98") (2.5 m) QX1 Single Hit Drum With 6mm Spacing	02-0700-06-0015	$	89,930	$	-
8’2” (98") (2.5 m) Weld-on Micromill Single Hit Drum With 0.2” Spacing Kenname	02-0700-06-0008	$	79,185	$	-
Cutter Housing Options					
Cutter Housing Bi-Directional Package Includes scraper blade on conveyor side moldboard, reversed endgates, additional flashing at corners of housing.	02-0700-06-0009	$	5,290	$	-
W-80 Gearbox in Lieu of Standard W-50 Gearbox Replaces standard Fairfield W-50 Cutter Drum Gearbox with W-80 Gearbox	02-0700-06-0013	$	9,680	$	-

126" (3.2 m) Cutter Housing - CH702-126

CH702-126 STANDARD FEATURES:

Bolt-On Cutter Assembly With Mechanical V-Belt Drive
W-50 Fairfield Cutter Gear Box with “Break-a-Way” Input Shaft
Front & Rear Water Spray Bars with Flow and Pressure Control
14” Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners

CH702-126 126" Housing (CUTTER HOUSING ONLY)	02-0700-07-0001	$	107,165	$	-

CH702-126 OPTIONS					
Drum Options					
10’6” (126") (3.2 m) QX1 Single Hit Drum With 5/8” Spacing	02-0700-07-0005	$	53,720	$	-
10’6” (126") (3.2 m) Kennametal Single Hit Drum With 5/8” Spacing	02-0700-07-0003	$	58,260	$	-
Cutter Housing Options					
Cutter Housing Bi-Directional Package Includes scraper blade on conveyor side moldboard, reversed endgates, additional flashing at corners of housing.	02-0700-07-0004	$	5,290	$	-
W-80 Gearbox in Lieu of Standard W-50 Gearbox Replaces standard Fairfield W-50 Cutter Drum Gearbox with W-80 Gearbox	02-0700-07-0006	$	9,680	$	-

150" (3.8 m) Cutter Housing - CH702-150

CH702-150 STANDARD FEATURES:

Bolt-On Cutter Assembly With Mechanical V-Belt Drive
W-50 Fairfield Cutter Gear Box with “Break-a-Way” Input Shaft
Front & Rear Water Spray Bars with Flow and Pressure Control
14” Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners

CH702-150 150" Housing (CUTTER HOUSING ONLY)	02-0700-08-0001	$	131,775	$	-

CH702-150 OPTIONS					
Drum Options					
12’6” (150") (3.8 m) QX1 Single Hit Drum With 5/8” Spacing	02-0700-08-0002	$	77,030	$	-
12’6” (150") (3.8 m) Kennametal Single Hit Drum With 5/8” Spacing	02-0700-08-0003	$	81,595	$	-

Cutter Housing Options					
Cutter Housing Bi-Directional Package Includes scraper blade on conveyor side moldboard, reversed endgates, additional flashing at corners of housing.		**$**	**5,700**	**$**	**-**
W-80 Gearbox in Lieu of Standard W-50 Gearbox Replaces standard Fairfield W-50 Cutter Drum Gearbox with W-80 Gearbox		**$**	**9,680**	**$**	**-**

Warranties					
Roadtec Edge Extended Warrranty - RX-700e 3 track (3 yr / 3000 hr Total)	02-0700-50-0001	**$**	**14,575**	**$**	**-**
Roadtec Edge Extended Warrranty - RX-700e 4 track (3 yr / 3000 hr Total)	02-0700-50-0004	**$**	**15,320**	**$**	**-**
Manufacturer's Extended Engine Warranty (5 years or 6,000 hours total)	02-0700-10-0002	**$**	**14,885**	**$**	**-**

Roadtec Pricing Effective 7/1/2021

Quoted Item	Option Not Included		Price Code	List Price	Customer Configuration
RX-900 - HIGH PRODUCTION HALF TO FULL LANE COLD PLANER					
		RX-900 STANDARD FEATURES:			
		Engine load control Automatic traction control Front, rear, crab and coordinated steer Direct hydraulic planetary track drives Foot per minute meter 1300 gallon (4921 L) water tank with three fill stations High pressure wash down system Hydraulic variable flow water pump Auto on/off spray water system 42” (1066 mm) wide primary conveyor with endless heavy duty belt with 1” (25 mm) tall molded rubber cleats 42” (1066 mm) wide secondary conveyor with endless belt with 1” (25 mm) tall molded rubber cleats Secondary conveyor has full 120 degree swing capability Truck Rails on Secondary Conveyor Self-cleaning head and tail pulleys Left side/right side full function operators control stations Lighted instrument console with liquid filled gauges Air compressor with reservoir and air tools Operator's console umbrella with mounting hardware Ground level controls for moldboard, end gates & elevation Remote grease fittings arranged in zones Light package consisting of ten (10) 24 V lights Two magnetic base 24 V DC halogen work lights Six 24 V DC power outlets Polyurethane bolt-on replaceable track pads Shock mounted operator’s platform and console Dust Extraction System Safety controls including emergency engine shut-down, cutter disengage and engine shut-down when cutter door is opened Rear back-up camera			
		RX-900e-3 Tier 4F Caterpillar C27 engine rated at 1050 hp	02-0900-01-0005	$ 717,645	$ -
		RX-900e-4 Tier 4F Caterpillar C27 engine rated at 1050 hp	02-0900-01-0006	$ 753,120	$ -
		RX-900e/ex OPTIONS:			
		Conveyor			
		Straight Secondary Conveyor	02-0900-02-0030	$ -	$ -
		Hydraulic Folding Secondary Conveyor	02-0900-02-0004	$ 17,165	$ -
		Auxiliary Power			
		4 kW Generator Set	02-0900-02-0001	$ 5,780	$ -
		15 kW Generator Set	02-0900-02-0002	$ 8,185	$ -
		Additional Lighting			
		24V LED Night Light Package Light set consisting of four 24V Lights, mounting hardware and wiring	02-0900-02-0003	$ 2,345	$ -
		Saber Light Two 92-watt, LED light panels provide over 10,000 lumens	02-0900-02-0027	$ 4,235	$ -
		Truck Signal Light	02-0900-02-0029	$ 2,940	$ -

Magnetic based LED light to indicate to dump truck driver when to stop or proceed

Miscellaneous					
Operator Seats Includes an operator's seat for each control station that can be used during operation and then slid out of the way for standing operation or transport. Cannot be installed on units configured for CIR.	02-0900-02-0005	$	3,590	$	-
Automated Lubrication System	02-0900-02-0006	$	10,450	$	-
Hydraulically Folding Canopy	02-0900-02-0007	$	14,925	$	-
Guardian Totalizer LED Display of real time production	02-0900-02-0025	$	2,025	$	-
Rear Water Pump	02-0900-02-0028	$	3,515	$	-
Secondary Conveyor Camera	02-0900-02-0031	$	1,425	$	-
Rear Object Detection System	02-0900-02-0034	$	12,370	$	-

Automation - Grade and Slope Controls					
ACE Grade and Slope Automation with Auto-Cut Automates elevation of front and rear legs of milling machine by using grade sensors or a slope sensor for the right and left hand side of machine. System automates rear elevation of machine during entry of each cut. System includes 3 ACE Control panels that can be connected at the operator station and on the ground at the middle of the machine or in the rear to control both sides of the machine, 1 central microcontroller, 1 5-eye sonic sensor, plugs at side of machine for controls and sensors, mounting hardware, cables and junction boxes. Utilizes MOBA brand slope and sonic sensors.	02-0900-03-0002	$	27,920	$	-
Prewiring for ACE Averaging Ski Includes junction boxes and cables to corners of machine for Averaging Ski, does not included sensors or mounting hardware.	02-0900-03-0003	$	4,025	$	-
ACE - Single Averaging Ski - Requires Base System Provides averaging of grade for one side of machine. Junction box and sensor connections are installed on both sides of machine so sensors and arms can easily be swapped to either side of machine. Requires base ACE Grade and Slope Automation. Includes 2 sonic sensors with 5 transducers each. One for front and rear corner of machine, 2 junction boxes, cables and mounting hardware.	02-0900-03-0004	$	10,410	$	-
ACE - Dual Averaging Ski - Requires both Single Ski and Base Systems Provides hardware to upgrade single averaging ski to dual averaging ski. Requires ACE Grade and Slope Automation and ACE Single Averaging Ski. Includes 2 sonic sensors with 5 transducers each. One for front and rear corner of machine, cables and mounting hardware.	02-0900-03-0005	$	7,080	$	-

CUTTER HOUSINGS

86" (2.2 m) Cutter Housing - CH903-86

CH903-86 STANDARD FEATURES:

Bolt-On Cutter Assembly With Mechanical V-Belt Drive
W-80 Fairfield Cutter Gear Box with “Break-a-Way” Input Shaft
Front & Rear Water Spray Bars with Flow and Pressure Control
14” Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners

CH903-86 86" Cutter Housing (CUTTER HOUSING ONLY)	02-0900-04-0001	$	87,570	$	-

CH903-86 OPTIONS

Drum Options					
7’2” (86") (2.2 m) QX1 Single Hit Drum With 5/8” Spacing	02-0900-04-0010	$	39,765	$	-
7’2” (86") (2.2 m) Kennametal Single Hit Drum With 5/8” Spacing	02-0900-04-0003	$	43,885	$	-

7’2” (86") (2.2 m) "Roadrunner" QX1 Double Hit Drum With 0.851” Spacin	02-0900-04-0011	**$**	**52,415**	**$**	**-**
7’2” (86") (2.2 m) "Roadrunner" Kennametal Double Hit Drum With 0.851”	02-0900-04-0005	**$**	**56,535**	**$**	**-**
7’2” (86") (2.2 m) QX1 Profiling Single Hit Drum With 3/8” Spacing	02-0900-04-0012	**$**	**65,070**	**$**	**-**
7’2” (86") (2.2 m) Kennametal Profiling Single Hit Drum With 3/8” Spacing	02-0900-04-0007	**$**	**69,190**	**$**	**-**
7'2" (86") (2.2 m) QX1 Single Hit Drum With 8mm Spacing	02-0900-04-0014	**$**	**69,645**	**$**	**-**
7'2" (86") (2.2 m) QX1 Single Hit Drum With 6mm Spacing	02-0900-04-0015	**$**	**83,105**	**$**	**-**
7’2” (86") (2.2 m) Weld-on Micromill Single Hit Drum With 0.2” Spacing Kenname	02-0900-04-0008	**$**	**71,170**	**$**	**-**
Cutter Housing Options					
Cutter Housing Bi-Directional Package Includes scraper blade on conveyor side moldboard, reversed endgates, additional flashing at corners of housing.	02-0900-04-0009	**$**	**5,125**	**$**	**-**

98" (2.5 m) Cutter Housing - CH903-98

CH903-98 STANDARD FEATURES:

Bolt-On Cutter Assembly With Mechanical V-Belt Drive
W-80 Fairfield Cutter Gear Box with “Break-a-Way” Input Shaft
Front & Rear Water Spray Bars with Flow and Pressure Control
14” Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners

CH903-98 98" Cutter Housing (CUTTER HOUSING ONLY)	02-0900-05-0001	**$**	**93,085**	**$**	**-**

CH903-98 OPTIONS

Drum Options					
8’2” (98") (2.5 m) QX1 Single Hit Drum With 5/8" Spacing	02-0900-05-0012	**$**	**45,310**	**$**	**-**
8’2” (98") (2.5 m) Kennametal Single Hit Drum With 5/8” Spacing	02-0900-05-0003	**$**	**49,820**	**$**	**-**
8’2” (98") (2.5 m) "Roadrunner" QX1 Double Hit Drum With 0.851” Spacin	02-0900-05-0013	**$**	**59,730**	**$**	**-**
8’2” (98") (2.5 m) "Roadrunner" Kennametal Double Hit Drum With 0.851”	02-0900-05-0005	**$**	**64,235**	**$**	**-**
8’2” (98") (2.5 m) QX1 Profiling Single Hit Drum With 3/8” Spacing	02-0900-05-0014	**$**	**74,145**	**$**	**-**
8’2” (98") (2.5 m) Kennametal Profiling Single Hit Drum With 3/8” Spacing	02-0900-05-0007	**$**	**78,655**	**$**	**-**
8’2” (98") (2.5 m) Weld-on Micromill Single Hit Drum With 0.2” Spacing Kenname	02-0900-05-0008	**$**	**75,800**	**$**	**-**
8’2” (98") (2.5 m) QX1 Quad Wrap Single Hit Drum With 6mm Spacing	02-0900-05-0015	**$**	**87,040**	**$**	**-**
8’2” (98") (2.5 m) QX1 Single Hit Drum With 8mm Spacing	02-0900-05-0016	**$**	**75,525**	**$**	**-**
Cutter Housing Options					
Cutter Housing Bi-Directional Package Includes scraper blade on conveyor side moldboard, reversed endgates, additional flashing at corners of housing.	02-0900-05-0009	**$**	**5,290**	**$**	**-**

Segmented Cutter Housing - CH903V-Only Available with 4 Track

CH903V STANDARD FEATURES:

9'6" base drum with necessary segments to provide cut widths of 10'6", 11'6", 12'6" and 13'6"
10'6" Base Cutter Housing w/ extension segments for housing, moldboards and spray bars to provide cut widths of 10'6", 11'6", 12'6", 13'6"
Sollami Quick Change System standard
48” tip diameter
5/8” Spacing, triple wrap with cutter bits for traditional milling
Bolt-On Cutter Assembly With Mechanical V-Belt Drive
Automatic Drive Belt Tensioning
W-80 Fairfield Cutter Gear Box with “Break-a-Way” Input Shaft
Front & Rear Water Spray Bars with Flow and Pressure Control
14” Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
“Extended Wear” Cutter Housing with Clad Wear Liners
*This Option is Only Available on 4-Track Machine

CH903V Segmented cutter housing (INCLUDES DRUM AND SEGMENTS)	02-0900-06-0001	$	261,890	$	-
CH903V OPTIONS					
Drum Options					
Kennametal in lieu of Sollami	02-0900-06-0002	$	-	$	-
Cutter Housing Options					
Cutter Housing Bi-Directional Package Includes scraper blade on conveyor side moldboard, reversed endgates, additional flashing at corners of housing.	02-0900-06-0003	$	6,105	$	-

150" (3.8 m) Cutter Housing - CH903-150

CH903-150 STANDARD FEATURES:

Bolt-On Cutter Assembly With Mechanical V-Belt Drive
W-80 Fairfield Cutter Gear Box with “Break-a-Way” Input Shaft
Front & Rear Water Spray Bars with Flow and Pressure Control
14” Depth of Cut with Sloped Front & Rear Moldboards
Powered Wrap Around End Gates With Replaceable Wear Shoes
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners

CH903-150 150" Housing (CUTTER HOUSING ONLY)	02-0900-07-0001	$	137,985	$	-
CH903-150 OPTIONS					
Drum Options					
12’6” (150") (3.8 m) QX1 Single Hit Drum With 5/8” Spacing	02-0900-07-0010	$	77,030	$	-
12’6” (150") (3.8 m) Kennametal Single Hit Drum With 5/8” Spacing	02-0900-07-0003	$	81,595	$	-
12’6” (150") (3.8 m) "Roadrunner" QX1 Double Hit Drum With 0.851” Spac	02-0900-07-0011	$	101,245	$	-
12’6” (150") (3.8 m) "Roadrunner" Kennametal Double Hit Drum w/ 0.851”	02-0900-07-0005	$	107,555	$	-
12’6” (150") (3.8 m) Kennametal Single Hit Drum With 8mm Spacing	02-0900-07-0014	$	135,385	$	-
12'6" (150") (3.8m) QX1 Single Hit Drum With 8mm Spacing	02-0900-07-0015	$	129,135	$	-
12'6" (150") (3.8m) QX1 Single Hit Drum With 6mm Spacing	02-0900-07-0016	$	142,685	$	-
12’6” (150") (3.8 m) Weld-on Micromill Single Hit Drum With 0.2” Spacing Kennar	02-0900-07-0008	$	136,540	$	-
Cutter Housing Options					
Cutter Housing Bi-Directional Package Includes scraper blade on conveyor side moldboard, reversed endgates, additional flashing at corners of housing.	02-0900-07-0009	$	5,700	$	-

Warranties					
Roadtec Edge Extended Warrranty - RX-900e 3 track (3 yr / 3000 hr Total)	02-0900-50-0001	$	16,830	$	-
Roadtec Edge Extended Warrranty - RX-900e 4 track (3 yr / 3000 hr Total)	02-0900-50-0003	$	17,660	$	-
Manufacturer's Engine Extended Warranty - RX-900e/ex (5 yr / 6000 hr Total)	02-0900-50-0002	$	25,245	$	-

Roadtec Pricing Effective 7/1/2021

Quoted Item	Option Not Included		Price Code	List Price	Customer Configuration
SX-5 SOIL STABILIZER / RECLAIMER					
		SX-5 STANDARD FEATURES:			
		Cummins QSG12 Tier IV final diesel engine Engine Load control 4 Wheel Drive with Differential Lock Fully enclosed cab with positive pressure heat & air conditioning system Five selectable cutter speeds Two speed fully hydrostatic propel system Four wheel drive with traction control Hydrostatic cutter drive with two planetary gearboxes Four heavy duty wheels prevent rim slippage and tire failure High flotation, deep tread 23.5-25 L-2 operator station located on front of machine Seat and console swivel 90 degrees and slide for operation from either side of machine Backup Camera to provide additional visibility while operating the machine in reverse Four wheel steering with four modes – coordinated, crab, front only and rear only - all joystick controlled 90 gallon (341 L) Hydraulic tank 280 gallon (1060 L) fuel capacity CAN Bus controls Variable speed, demand driven cooling fan			
		SX-5e Tier 4 Final-QSG12 rated at 513 hp - Does not Include Cutter	08-0005-01-0001	$ 472,781	$ -
		SX-5 OPTIONS:			
		Additive Systems			
		Automated Water and Emulsion Additive System 500 GPM, fully automatic controls with manual override, includes pump, flow meter, spray system manifold, push bar, nurse line, and nozzles for flow rates from 30 GPM up to 500 GPM. Automatic mode modulates flow based on cut depth, number of nozzles open and machine speed.	08-0005-02-0001	$ 44,884	$ -
		Basic Water System 350 GPM with manual controls. Includes pump, flow meter, spray bar	08-0005-02-0002	$ 28,103	$ -
		Miscellaneous			
		Rear Tow Hitch Assembly to pull tanker behind machine	08-0005-02-0003	$ 3,091	$ -
		Air System	08-0005-02-0004	$ 11,811	$ -
		Additional Seat in Cab	08-0005-02-0005	$ 3,316	$ -
		2 Camera Package Includes 2 additional cameras, 7" monitor, mounts, and necessary electrical components	08-0005-02-0006	$ 3,608	$ -
		4 Camera Package Includes 4 additional cameras, 12" monitor, mounts, and necessary electrical components	08-0005-02-0007	$ 6,873	$ -
		CUTTER HOUSINGS			
		96" Cutter Housing - CHX5-96			
		CHX5-96 STANDARD FEATURES:			
		8' (96") width cutter drum Hydraulically Driven Cutter Dual Planetary Gearboxes			

	16" Depth of Cut					
	CHX5-96 96" Housing (CUTTER HOUSING ONLY)	08-0005-03-0001	**$**	**84,753**	**$**	**-**
	CHX5-96 OPTIONS					
	Drum Options					
	50" Diameter - 1.047" Spaced Kennametal Welded Drum	08-0005-03-0002	**$**	**54,619**	**$**	**-**
	50" Diameter - 0.737" Spaced QX1	08-0005-03-0003	**$**	**56,344**	**$**	**-**
	50" Diameter - 0.737" Spaced Kennametal 301 Quick Change	08-0005-03-0004	**$**	**58,521**	**$**	**-**
	Warranties					
	Roadtec Edge Extended Warranty (3 years or 3,000 hours total)	08-0008-06-0001	**$**	**8,590**	**$**	**-**
	Manufacturer's Extended Engine Warranty (5 years or 6,000 hours total)	08-0008-06-0002	**$**	**6,160**	**$**	**-**

Roadtec Pricing Effective 7/1/2021

Quoted Item	Option Not Included		Price Code	List Price	Customer Configuration
SX-6 SOIL STABILIZER / RECLAIMER					
		SX-6e 4000 Series STANDARD FEATURES:			
		24 Volt Electrical System Hyrdaulically tensioned mechanical belt drive to planetary unit to drive cutter drum RH Flush Cut Hydraulic actuated clutch for transmission of power to cutter from engine 4 Speed air shift transmission for drum rotation speed Four cutting speeds 92 rpm, 117 rpm, 146 rpm and 180 rpm Two speed fully hydrostatic propel system Four wheel drive - Four individual drive pumps 266 fpm (81 mpm) working speed and 6 mph (10 kph) travel speed Four heavy duty 3 piece wheels prevent rim slippage and tire failure High flotation, deep tread 28LR26 tires Low profile operator station located on front of machine Seat and console swivel 90 degrees for operation from either side of machine in either direction Backup Camera to provide additional visibility while operating the machine in reverse Four wheel steering with four modes – coordinated, crab, front only and rear only - all joystick controlled 48 gallon (182 L) Hydraulic tank 300 gallon (1135 L) fuel capacity CAN Bus controls Fully enclosed cab with positive pressure heat & air conditioning system Variable speed, demand driven cooling fan			
		SX-6e Cab Only - Tier 4 Final QSX-15 rated at 675 hp - Does not Include Cutter		**$ 607,305**	**$ -**
		SX-6 OPTIONS:			
		Additive Systems			
		Automated Water and Emulsion Additive System 500 GPM, fully automatic controls with manual override, includes pump, flow meter, spray system manifold, push bar, nurse line, and nozzles for flow rates from 30 GPM up to 500 GPM. Automatic mode modulates flow based on cut depth, number of nozzles open and machine speed.	08-0006-02-0001	**$ 41,755**	**$ -**
		Hydraulically Lifting Push Bar for Additive System	08-0006-02-0010	**$ 3,630**	**$ -**
		Miscellaneous			
		Rear Tow Hitch Assembly to pull tanker behind machine	08-0006-02-0003	**$ 2,875**	**$ -**
		Air System Includes air compressor, hose reel, air hammer, and rear tow hitch for mounting system between rear legs	08-0006-02-0005	**$ 10,455**	**$ -**
		2 Camera Package Includes 2 additional cameras, 7" monitor, mounts, and necessary electrical components	08-0006-02-0006	**$ 3,355**	**$ -**
		4 Camera Package Includes 4 additional cameras, 12" monitor, mounts, and necessary electrical components	08-0006-02-0007	**$ 6,395**	**$ -**
		CUTTER HOUSINGS			
		100" (2.54 m) Cutter Housing - CHX6-100B			
		CHX6-100B STANDARD FEATURES:			
		8'4" (100") (2.54 m) width cutter drum			

	Bolt-On Cutter Assembly With Mechanical V-Belt Drive Automatic Drive Belt Tensioning W-50 Fairfield Cutter Gear Box with 16:1 gear ratio Depth of cut depends on drum option chosen					
	CHX6-100B 100" Housing (CUTTER HOUSING ONLY)	08-0006-03-0001	**$**	**85,415**	**$**	**-**
	CHX6-100B OPTIONS					
	Drum Options					
	50" Diameter - 0.6" Spaced Welded Drum	08-0006-03-0002	**$**	**46,155**	**$**	**-**
	50" Diameter - 0.6" Spaced QX1	08-0006-03-0003	**$**	**55,875**	**$**	**-**
	50" Diameter - 0.6" Spaced Kennametal 301 Quick Change	08-0006-03-0004	**$**	**57,500**	**$**	**-**
	50" Diameter - 0.853" Spaced QX1	08-0006-03-0005	**$**	**52,825**	**$**	**-**
	50" Diameter - 0.853" Spaced Kennametal 301 Quick Change	08-0006-03-0006	**$**	**53,930**	**$**	**-**
	58" Diameter - 0.6" Spaced Welded Drum	08-0006-03-0007	**$**	**50,305**	**$**	**-**
	58" Diameter - 0.6" Spaced QX1	08-0006-03-0008	**$**	**55,920**	**$**	**-**
	58" Diameter - 0.6" Spaced Kennametal 301 Quick Change	08-0006-03-0009	**$**	**56,840**	**$**	**-**
	58" Diameter - 0.853" Spaced QX1	08-0006-03-0010	**$**	**56,985**	**$**	**-**
	58" Diameter - 0.853" Spaced Kennametal 301 Quick Change	08-0006-03-0011	**$**	**58,090**	**$**	**-**
	Warranties					
	Roadtec Edge Extended Warrranty - SX-6e (3 yr / 3000 hr Total)	08-0006-50-0001	**$**	**14,105**	**$**	**-**
	Manufacturer's Engine Extended Warranty - SX-6e (5 yr / 6000 hr Total)	08-0006-50-0002	**$**	**9,515**	**$**	**-**

Roadtec Pricing Effective 7/1/2021

Quoted Item	Option Not Included		Price Code	List Price	Customer Configuration
SX-8 SOIL STABILIZER / RECLAIMER					
		SX-8 STANDARD FEATURES:			
		24 Volt Electrical System Hyrdaulically tensioned mechanical belt drive to planetary unit to drive cutter drum RH Flush Cut Hydraulic actuated clutch for transmission of power to cutter from engine 4 Speed transmission for drum rotation speed Four cutting speeds 92 rpm, 118 rpm, 146 rpm and 181 rpm Two speed fully hydrostatic propel system Four wheel drive - Four individual drive pumps 250 fpm (76 mpm) working speed and 6 mph (10 kph) travel speed Four heavy duty 3 piece wheels prevent rim slippage and tire failure High flotation, deep tread 23.5x25 tires Low profile operator station located on front of machine Seat and console swivel 90 degrees for operation from either side of machine in either direction Backup Camera to provide additional visibility while operating the machine in reverse Four wheel steering with four modes – coordinated, crab, front only and rear only - all joystick controlled 85 gallon (322 L) Hydraulic tank 320 gallon (1211 L) fuel capacity CAN Bus controls Fully enclosed cab with positive pressure heat & air conditioning system Variable speed, demand driven cooling fan			
		SX-8e Cab Only - Tier 4 Final Cat C18 rated at 755hp - Does not Include Cutter	08-0008-01-0001	**$ 778,510**	**$ -**
		SX-8 OPTIONS:			
		Additive Systems			
		Automated Water and Emulsion Additive System 500 GPM, fully automatic controls with manual override, includes pump, flow meter, spray system manifold, push bar, nurse line, and nozzles for flow rates from 30 GPM up to 500 GPM. Automatic mode modulates flow based on cut depth, number of nozzles open and machine speed.	08-0008-02-0001	**$ 48,865**	**$ -**
		Hydraulically Lifting Push Bar for Additive System	08-0008-02-0010	**$ 3,630**	**$ -**
		Miscellaneous			
		Rear Tow Hitch Assembly to pull tanker behind machine	08-0008-02-0003	**$ 2,995**	**$ -**
		Power Ladder to Operator Station		**$ 2,780**	**$ -**
		Air System	08-0008-02-0005	**$ 10,890**	**$ -**
		2 Camera Package Includes 2 additional cameras, 7" monitor, mounts, and necessary electrical components	08-0008-02-0006	**$ 3,495**	**$ -**
		4 Camera Package Includes 4 additional cameras, 12" monitor, mounts, and necessary electrical components	08-0008-02-0007	**$ 6,655**	**$ -**
		CUTTER HOUSINGS			
		100" (2.54 m) Cutter Housing - CHX8-100			
		CHX8-100 STANDARD FEATURES:			
		8'4" (100") (2.54 m) width cutter drum Bolt-On Cutter Assembly With Mechanical V-Belt Drive			

Automatic Drive Belt Tensioning
O&K FA130 Cutter Gear Box with 16:1 gear ratio
Depth of cut depends on drum option chosen

CHX8-100 100" Housing (CUTTER HOUSING ONLY)	08-0008-03-0001	**$**	**90,715**	**$**	**-**
Endgate Smart Cylinder Package	08-0008-04-0016	**$**	**8,320**	**$**	**-**
Breaker Bar (Only compatible with 50" drum diameter)	08-0008-04-0013	**$**	**5,705**	**$**	**-**

CHX8-100 OPTIONS

Drum Options					
50" Diameter - 0.6" Spaced Welded Drum	08-0008-03-0002	**$**	**49,020**	**$**	**-**
50" Diameter - 0.6" Spaced QX1	08-0008-03-0005	**$**	**59,350**	**$**	**-**
50" Diameter - 0.6" Spaced Kennametal 301 Quick Change	08-0008-03-0004	**$**	**61,070**	**$**	**-**
50" Diameter - 0.853" Spaced QX1	08-0008-03-0007	**$**	**56,110**	**$**	**-**
50" Diameter - 0.853" Spaced Kennametal 301 Quick Change	08-0008-03-0006	**$**	**57,280**	**$**	**-**
58" Diameter - 0.6" Spaced Welded Drum	08-0008-03-0012	**$**	**53,435**	**$**	**-**
58" Diameter - 0.6" Spaced QX1	08-0008-03-0008	**$**	**62,420**	**$**	**-**
58" Diameter - 0.6" Spaced Kennametal 301 Quick Change	08-0008-03-0009	**$**	**62,420**	**$**	**-**
58" Diameter - 0.853" Spaced QX1	08-0008-03-0010	**$**	**60,525**	**$**	**-**
58" Diameter - 0.853" Spaced Kennametal 301 Quick Change	08-0008-03-0011	**$**	**61,695**	**$**	**-**

120" (3.05 m) Cutter Housing - CHX8-120

CHX8-120 STANDARD FEATURES:

10' (120") (3.05 m) width cutter drum
Bolt-On Cutter Assembly With Mechanical V-Belt Drive
Automatic Drive Belt Tensioning
O&K FA130 Cutter Gear Box with 16:1 gear ratio
Depth of cut depends on drum option chosen

CHX8-120 120" Housing (CUTTER HOUSING ONLY)	08-0008-04-0001	**$**	**117,765**	**$**	**-**

CHX8-120 OPTIONS

Drum Options					
50" Diameter - 0.6" Spaced Welded Drum	08-0008-04-0002	**$**	**58,825**	**$**	**-**
50" Diameter - 0.6" Spaced QX1	08-0008-04-0012	**$**	**71,220**	**$**	**-**
50" Diameter - 0.6" Spaced Kennametal 301 Quick Change	08-0008-04-0004	**$**	**73,285**	**$**	**-**
50" Diameter - 0.875" Spaced QX1	08-0008-04-0013	**$**	**67,330**	**$**	**-**
50" Diameter - 0.875" Spaced Kennametal 301 Quick Change	08-0008-04-0006	**$**	**68,740**	**$**	**-**
58" Diameter - 0.6" Spaced Welded Drum	08-0008-04-0007	**$**	**64,120**	**$**	**-**
58" Diameter - 0.6" Spaced QX1	08-0008-04-0014	**$**	**76,515**	**$**	**-**
58" Diameter - 0.6" Spaced Kennametal 301 Quick Change	08-0008-04-0009	**$**	**78,585**	**$**	**-**
58" Diameter - 0.875" Spaced QX1	08-0008-04-0015	**$**	**72,630**	**$**	**-**
58" Diameter - 0.875" Spaced Kennametal 301 Quick Change	08-0008-04-0011	**$**	**74,040**	**$**	**-**

Warranties					
Roadtec Edge Extended Warrranty for SX-8e (3 yr / 3000 hr Total)	08-0008-50-0001	**$**	**18,085**	**$**	**-**
Manufacturer's Engine Extended Warranty for SX-8e (5 yr / 6000 hr Total)	08-0008-50-0002	**$**	**14,885**	**$**	**-**