FORM D - OFFERED ITEMS PRICING

INSTRUCTIONS: Fill in unshaded areas. Complete one line for each product code. Add lines as needed. Shaded columns for H-GAC use only.

Offeror Name:						
Contract	Manufacturer	Vendor	Product Code	Description	Price	Discount Percentage
	Aspen		TR18Z001	Aspen Lowboy Trailers pricing catalog		
	Aspen		TR18Z002	Aspen Specialized/Heavy Haul Trailers pricing catalog		
	Continental Cargo		TR18B014	Continental Cargo trailers: enclosed cargo trailers pricing catalog		
	Cargo		TR18B015	Continental Cargo trailers: enclosed car trailers pricing catalog		
	Cargo		TR18B016	Continental Cargo trailers: enclosed living quarters package pricing catalog		
	Continental Cargo		TR18B017	Continental Cargo trailers: enclosed motorcycle trailers with living quarters		
	Continental		TR18B018	Continental Cargo trailers: enclosed snowmobile trailers pricing catalog		
	Continental Cargo		TR18B019	Continental Cargo trailers: open aluminum utility trailers pricing catalog		
	Continental Cargo		TR18B020	Continental Cargo trailers: multi-purpose trailers pricing catalog		
	CPS		TR18Z004	CPS End and Bottom Dump Trailers pricing catalog		
	CPS		TR18CC01	Standard Belly Dump pricing catalog		
	CPS		TR18CC02	Lifgtweight Belly Dump pricing catalog		
	CPS		TR18CC03	Standard Belly Dump Spread axle air ride pricing catalog		
	CPS		TR18CC05	Low Profile Belly Dump Lightweight Belly Dump pricing catalog		
	CPS		TR18CC06	TR18CC06 Half Round End Dump pricing catalog		
	CPS		TR18CC07	TR18CC07 Grain Hopper pricing catalog		
	Doonan		TR18Z007	TR18Z007 Doonan Lowboy Trailers pricing catalog		

											2%												
ers pricing catalog	pricing catalog	utalog	ng catalog	ssion pricing	ailers pricing	e gooseneck pricing	cing catalog	ricing catalog	er: Hydraulic og	ler: Hydraulic alog	oup trailers pricing	ricing catalog	/Heavy Haul	ailers pricing	alog	ed cargo trailers	ed car trailers	ed motorcycle	ed adventure	ed specialty trailers	eu stacker traniers	ag-along trailers	iltbed trailers
23 Doonan Drop Deck Trailers pricing catalog	9 Doonan Flatbed Trailers pricing catalog	24 Dynasty Cargo pricing catalog	_	Dynasty Specialty/Concession pricing catalog	Bager Beaver Lowboy Trailers pricing catalog	Etnyre trailers: detachable gooseneck pricing catalog	10 Falcon Utility Trailer pricing catalog	11 Falcon Flatbed Trailers pricing catalog	Fontaine Heavy haul trailer: Hydraulic Beaver Tail pricing catalog	Pontaine Heavy Haul trailer: Hydraulic detach tri axle pricing catalog	Galbreath trailers: open pup trailers pricing catalog			_	15 Dump trailers pricing catalog	17 Haulmark trailers: enclosed cargo trailers	Haulmark trailers: enclosed car trailers pricing catalog			Haulmark trailers: enclosed specialty trailers pricing catalog			
TR18E023	TR18E099	TR18E024	TR18E025	TR18Z008	TR18Z009	TR18DD01	TR18Z010	TR18Z011	TR18AA01	TR18AA02	TR181041	TR18Z012	TR18Z013	TR18Z014	TR18Z015	TR18K047	TR18K048	TR18K049	TR18K050	TR18K051	TR18K052	TR18L053	TR18L054
									aul	aul	B & C Body Co.												
Doonan	Doonan	Dynasty	Dynasty	Dynasty	Eager Beaver	Etnyre	Falcon	Falcon	Fontaine Heavy Haul	Fontaine Heavy Haul	Galbreath	Gallegos	Globe trailer	Globe trailer	Globe trailer	Haulmark	Haulmark	Haulmark	Haulmark	Haulmark	Haulmark	Interstate	Interstate
											TR11-18												

	TR18L055	Interstate Trailers: open lowboy/gooseneck trailers pricing catalog
B & C Body Co.	TR18M056	J&J trailers: aluminum live walking floor trailers pricing catalog
	TR180058	Magnum trailers: open boat trailers pricing catalog
	TR180059	Magnum trailers: open car haulers pricing catalog
	TR180060	Magnum trailers: concession trailers pricing catalog
	TR180061	Magnum trailers: bumper/gooseneck dump trailers pricing catalog
	TR180062	Magnum trailers: enclosed trailers pricing catalog
	TR180063	Magnum trailers: open gooseneck trailers pricing catalog
	TR180064	Magnum trailers: enclosed horse/stock trailers pricing catalog
	TR180065	Magnum trailers: open utility trailers pricing catalog
	TR18Z015	Peerless Jeeps Trailers pricing catalog
	TR18P066	Performance trailers: open auto & motorcycle trailers pricing catalog
	TR18P067	Performance trailers: dump trailers pricing catalog
	TR18P068	Performance trailers: open equipment trailers pricing catalog
	TR18P069	Performance trailers: open gooseneck trailers pricing catalog
	TR18P070	Performance trailers: horse & stock trailers pricing catalog
	TR18P071	Performance trailers: landscape & highster trailers pricing catalog
	TR18P072	Performance trailers: open single/taxle tag trailers pricing catalog
	TR18P073	Performance trailers: enclosed cargo trailers pricing catalog
	TR18Q074	PJ Trailers: open flatdeck trailers pricing catalog

PJ Trailers	TR18Q075	PJ Trailers: open tilt trailers pricing catalog
PJ Trailers	TR18Q076	PJ Trailers; dump trailers pricing catalog
PJ Trailers	TR18Q077	PJ Trailers: open carhauler trailers pricing catalog
PJ Trailers	TR18Q078	PJ Trailers: open utility trailers pricing catalog
Red River	TR18R079	Red River: continuous belt live bottom trailer pricing catalog
Safety Trailers Inc	TR18S080	Safety Trailers TTMA-100 pricing catalog
Stalker	TR18T081	MC360 Message Center (4' x 8') Trailer Catalog
Stalker	TR18T082	MC360 Message Center (3'x 6') Trailer Catalog
Stalker	TR18T083	SAM Speed Trailer Catalog
Stalker	TR18T084	SAM-R Rotatable Speed Trailer Catalog
Talbert	TR18Z017	TR18Z017 Talbert Lowboy Trailers pricing catalog
Titan	TR18U084	Titan trailers: enclosed horse trailers pricing catalog
Titan	TR18U085	Titan trailers: enclosed livestock trailers pricing catalog
Titan	TR18U086	Titan trailers: dump trailers pricing catalog
Titan	TR18U087	Titan trailers: open flatbed trailers pricing catalog
Titan	TR18U088	TR18U088 Titan trailers: open utility trailers pricing
Titan	TR18U089	TR18U089 Aluminum Tipper Trailer Pricing Catalog
Titan	TR18U090	TR18U090 Refuse Trailer Pricing Catalog
Titan	TR18U91	Titan Trailers THINWALL TM Aluminum Tipper Trailer with Bolt On Roof pricing
	TR18U92	Titan Trailers THINWALL TM Aluminum Refuse Trailer with Bolt On Roof pricing
Titan		catalog
Titan	TR18U93	Possum Belly Tipper Trailer pricing catalog
Titan	TR18U94	Titan Trailers THINWALL TM Aluminum Drop Deck Refuse Trailer pricing catalog

Titan Trailers THINWALL TM Aluminum Refuse Trailer with Hydraulic Opening Roof pricing catalog	Top Hat trailers: open utility trailers pricing catalog	Top Hat trailers: open atv/motorcycle trailers pricing catalog	Top Hat trailers: open car hauler trailers pricing catalog	Top Hat trailers: open landscaper trailers pricing catalog	Top Hat uailers, open specially nailers	Top Hat trailers: open heavy duty utility and equipment trailers pricing catalog	Top Hat trailers: open gooseneck utility and equipment trailers pricing catalog	Top Hat trailers: dump trailers pricing catalog	TOP TAL HAIJETS. UCCK OVET HOARS, OVET UIE	-	Top Hat trailers: hay equipment pricing catalog	Top Hat trailers: enclosed cargo trailers pricing catalog	Towmaster trailers: open drop-deck trailers pricing catalog	Towmaster trailers: open drop-deck tilt trailers pricing catalog	Towmaster trailers: hydraulic dump trailers pricing catalog		Towmaster trailers: open deck-over tilt trailers pricing catalog	Towmaster trailers: open rigid gooseneck trailers pricing catalog
TR18U95	TR18V091	TR18V092	TR18V093	TR18V094	TR18V095	TR18V096	TR18V097	TR18V098	TR18V099	TR18V100	TR18V101	TR18V102	TR18W103	TR18W104	TR18W105	TR18W106	TR18W107	TR18W108
Titan	Top Hat	Top Hat	Top Hat	Top Hat	Top Hat	Top Hat	Top Hat	Top Hat	Top Hat	Top Hat	Top Hat	Top Hat	Towmaster	Towmaster	Towmaster	Towmaster	Towmaster	Towmaster

													96					
Towmaster trailers: open detachable gooseneck trailers pricing catalog	Towmaster trailers: open hydraulic tail trailers pricing catalog	Trail King trailers: open utility deck between fenders pricing catalog	Trail King trailers: open tilt deck utility pricing catalog	Trail King trailers: tag open deck over axle pricing catalog	Trail King trailers: open industrial/construction tilt deck over axle pricing catalog	Trail King trailers: open rigid gooseneck pricing catalog	Trail King trailers: Advantage Plus open hydraulic tail pricing catalog	Trail King trailers: Advantage Plus open hydraulic detach gooseneck pricing catalog	Trail King trailers: open mechanical detachable gooseneck pricing catalog	Trail King trailers: open folding gooseneck pricing catalog	Trail King trailers: Advantage Plus open sliding axle pricing catalog	Trail King trailers: open aluminum walking floor pricing catalog	Trail King trailers: open sliding tail pricing catalog	Trail King trailers: open aluminum tipper	Trail King trailers: open live bottom pricing catalog	Trail King trailers: steel half round end dump pricing catalog	Trail King trailers: tube length steel side dump pricing catalog	Trail King trailers: over fifth wheel live bottom pricing catalog
TR18W109	TRI8W110	TR18X111	TRI8X112	TR18X113	TR18X114	TR18X115	TR18X116	TR18X117	TR18X118	TR18X119	TR18X120	TR18X121	TR18X122	TR18X123	TR18X124	TR18X125	TR18X126	TR18X127
	1																	
Towmaster	Towmaster	Trail King	Trail King	Trail King	Trail King	Trail King	Trail King	Trail King	Trail King	Trail King	Trail King	Trail King	Trail King	Trail King	Trail King	Trail King	Trail King	Trail King

dwn	talog	italog	ති	pricing	oricing	cycle	mobile	ssion	and and	alty	purpose	cape	neck	5	le	e	сар
Trail King trailers: open Steel Side dump pricing catalog		TR18Z018 Viking Equipment Trailers pricing catalog	TR18Z019 Wade Lowboy Trailers pricing catalog	Wells Cargo enclosed trailers: cargo pricing catalog	Wells Cargo enclosed trailers: auto pricing catalog	Wells Cargo enclosed trailers: motorcycle catalog	Wells Cargo enclosed trailers: snowmobile pricing catalog	Wells Cargo enclosed trailers: concession pricing catalog	Wells Cargo enclosed trailers: office and storage pricing catalog	Wells Cargo enclosed trailers: specialty pricing catalog	Wells Cargo enclosed trailers: multi purpose pricing catalog	Wells Cargo enclosed trailers: landscape pricing catalog	TR18Y138 Wells Cargo enclosed trailers: gooseneck	Wells Cargo enclosed trailers: racing catalog	Wells Cargo enclosed trailers: mobile restrooms pricing catalog	Wells Cargo enclosed trailers: mobile showers pricing catalog	Wells Cargo enclosed trailers: handicap accessible pricing catalog
TR18X128	TR18BB01	TR18Z018	TR18Z019	TR18Y129	TR18Y130	TR18Y131	TR18Y132	TR18Y133	TR18Y134	TR18Y135	TR18Y136	TR18Y137	TR18Y138	TR18Y139	TR18Y140	TR18Y141	TR18Y142
Trail King	Travis	Viking	Wade	Wells Cargo	Wells Cargo	Wells Cargo	Wells Cargo	Wells Cargo	Wells Cargo	Wells Cargo	Wells Cargo	Wells Cargo	Wells Cargo	Wells Cargo	Wells Cargo	Wells Cargo	Wells Cargo

PRICE GUDE Cable Hoists, Hook Hoists & Trailers June 2015



S. Ibreath

PUP TRAILERS - NON-HYDRAULIC

45" Deck Height

2 Container Hold-downs Per Side

2 Ratchet Chain Restrains on Front

Poly Fenders Over Front and Rear Wheels

Primed & Painted with Two Part Baked on Epoxy

ABS Brakes

Air Powered Dolly Lockout

225 70R 22.5 16 Ply Low Profile Tires

Hot Phosphatized Wash

Non-Hydraulic Trailer

10' Tongue with Ratchet & Spring Assist Raise/Lower

Operation / Service / Parts Manual

25,000 lb. Front & Rear Axle 10 Hole Hub Piloted Wheels Neway Suspension

Pintle Hitch

DOT Approved LED Lighting

		Raulic pup trailers - no hoist	Rated	Can	List
Model	Holst Type	Description	lbs.	Size**	Price
	Two (2) Axle Spring Suspension	7,160lbs - 279° Deck Length - IS1841	40K	18'-22'	\$36,181
SP2A AP2A	Two (2) Axle Air Ride	7,670lbs - 279" Deck Length - Deck Lowers 4" - IS1840	40K	18'-22'	\$42,509
SP3A	Two (2) Rear	9,010lbs - 279" Deck Length - IS1841	50K	18'-22'	\$45,68
АРЗА	Three (3) Axle Air Ride-One (1) Front: Two (2) Rear	9,390lbs - 279" Deck Length - Deck Lowers 4" - IS1840	50K	18'-22'	\$51,97

Water Street Street Street	CANADA NON	HYDRAULIC PUP TRAILERS - NO HOIST			
Model	Holst Type	Description	Rated (6s.	Can 5ize**	List Price
AP3A-379	Three (3) Axle Air Ride-One (1) Front: Two (2) Rear	9,390lbs - 379" Length - Deck Lowers 4"	40K	18'-22'	\$57,332

Warning: Air powered dolly lockout pin must be engaged when backing empty PUP trailer in straight line with truck. Always have pin disengaged when driving over road or backing up with loaded container. Failure to do so could result in damage to equipment and/or injury to persons.

PUP TRAILERS - TT LIVE HYDRAULICS

15,000 lb. Maximum Vertical Tongue Load 2 Spool Control Valve (3 spool on EX models) Traller Frame 26 lb. I Beam Construction

Trailer Tongue T1 Fabricated Assembly

All GVWR Rated at 40K LBS

Primed & Painted with 2 Part Baked on Epoxy

Full Steel Fenders

DOT Approved LED Lighting Turn Lock Quick Disconnect

Auxiliary Front Stops (Optional)

Landing Gear

Seven (7) Wire Electric Connection

Hot Phosphatized Wash

7/8" Cable

Outside Controls

Single stage Lift Cylinder

1 1/4" Return Line

1" Pressure Line

Hoist Maintenance Props

Jack Knifeable Tongue

	Till the state of	IVE HYDRAULICS - HOIST INCLUDED	GVWR	Can	List
	It-let Time	Description	lbs.	Size**	Price
Model	Hoist Type	1 426" W 12 970 lbs	40K	18'-22'	\$59,955
TT-OR-176	Outside Rail	Overall Trailer Length 426" Wt 13,970 lbs	40K	18'-22'	\$61,860
TT-EX-176	Extendable Tail (Retracted)	Overall Trailer Length 384" - Wt 14,808 lbs	40K	18'-22'	\$61,491
TT-10-176	Inside/Outside Rall	Overall Trailer Length 426" - Wt 14,690 lbs	MARKAGO PARA PARA PARA PARA PARA PARA PARA PAR	MANAGEMENT DE	

MINIMUM TRACTOR SPECIFICATIONS

Adding a Lift Axie will NOT Change Trailer Capacity

Minimum tractor specifications are as follows:

Front Axle Rating 12,000lbs minimum

Rear Axle Rating 44,000lbs minimum

Chassis Frame Section Modulus 24 cu.in.

50 GPM @ 1500 running 2200 PSI or greater Wet Kit capable

Recommend using similar size hoses or larger to match system. Hoses from tractor need to support the following ends:

1" Female Quick Disconnect (Pressure Line) connections must be screw type

1 1/4" Male Quick Disconnect (Return Line) connections must be screw type

^{**}Maximum Container Lengths for this Configuration are Based on Wastequip Z245-type Containers and are Considered Part of the Load. Therefore, the Maximum Container Overhang at the Rear of all Extendable Tall Hoist Models is up to Four (4) Feet.

\$54,715

ROLL-OFF TRAILERS

50,000 lb. Single Point Suspension ICC Bumper (except for EX models) 2 Spool Control Valve (3 Spool on EX Models) Ratchet strap rear hold-downs (2) Lift Cylinders- 2 stage Telescopic (2) 7" Winch Cylinder

Trailer Brake at Street Side Front Brake control spring loaded

Hot Phosphatized Wash

M6-OR-200CA

Primed & Painted with 2 Part Baked on Epoxy

10 Hole Hub Piloted Steel Rims 50,000 lb. Two Speed Landing Gear Turn Lock Quick Disconnects 16" X 36 lb. W. F. Frame Mid Body LED Turn Signals **DOT Approved LED Lighting** Heavy Duty Swivel Eye ABS Braking System

Seven (7) Wire Electric Connection

Operation / Service / Parts Manual

11R/22.5 Tires 25,000 lb. Axles 1/4 Poly Rear Fenders 1 1/4" Return Line 1" Pressure Line Cable Hook Holder 7/8º Cable Hoist Maintenance Props M6-200CA Has 10" Main Frame

and 34.5" Rail Width

18'-26'

*68K

Model	Holst Rall Type	Hoist Capacity	AILER: - M6-200 Mighty Description	GVW Outer Bridge	Can Size**	List Price
Minate		60,000 lbs.	13,500 lbs - 27'5" Length	*68K	18'-26'	\$55,03
M6-OR-200	Outside Rail - Tandem Suspension		TBD lbs - 27'5" Length	*68K	18'-26'	\$58,10
VI6-10-200	Inside/Outside Tandem			*68K	18'-24'	\$58,20
M6-EX-200	Extendable Tall - Tandem	0.07	13,300 lbs - 23'4" Length	*68K	18-22'	\$58,40
M6-HH-200	Deadlift-Tandem	50,000 lbs.	TBD LBS - 22'8" Length			
	CALIFRONIA TAI	IDEM ROLL-O	FF TRAILER - MG-200CA MI	GVW		Service Control of the
COMPANS TO STREET	Hoist Rail Type	Hoist Capacity	Description	Outer Bridge	Çan Size**	List Price

Outside Rail - Tandem Suspension MINIMUM TRACTOR SPECIFICATIONS

10" Frame 34.5" Rall Width

Minimum tractor specifications are as follows:

Front Axle Rating 12,000lbs minimum

Rear Axle Rating 44,000lbs minimum

Chassis Frame Section Modulus 24 cu.in.

50 GPM @ 1500 running 2200 PSI or greater Wet Kit capable

50 Gallon Reservoir - A5-200, A5-250, ALC-392, AC-416, AC2-470/510 M6-200/250

65 Gallon Reservoir - A5-330, A5-366, A5-402

Recommend using similar size hoses or larger to match system. Hoses from tractor need to support the following ends:

60,000 lbs.

- 1" Female Quick Disconnect (Pressure Line) connections must be screw type
- 1 1/4" Male Quick Disconnect (Return Line) connections must be screw type

Trailer length does not allow for lift axies.

If a tire carrier is added there will be no room for a tool box. 48" tool box is compatible on this model Reference A5 series options for this trailer where applicable.

- * GVWR can vary based on Tractor wheel base For Models 200 330
- ** Maximum container lengths for this configuration are based on Wastequip 2245-type containers and are considered part of the load. Therefore, the maximum container overhang at the rear of all extendable tall hoists is up to 4'.

ROLL-OFF TRAILERS

50,000 lb. Single Point Suspension

ICC Bumper (except for EX models) 2 Spool Control Valve (3 Spool on EX Models)

Ratchet strap rear hold-downs

(2) Lift Cylinders- 2 stage Telescopic

(2) 7" Winch Cylinder

Trailer Brake at Street Side Front

Brake control spring loaded

Hot Phosphatized Wash

Primed & Painted with 2 Part Baked on Epoxy

10 Hole Hub Piloted Steel Rims

50,000 lb. Two Speed Landing Gear

Turn Lock Quick Disconnects

16" X 36 lb. W. F. Frame

Mid Body LED Turn Signals

DOT Approved LED Lighting

Heavy Duty Swivel Eye

ABS Braking System

Seven (7) Wire Electric Connection Operation / Service / Parts Manual 11R/22.5 Tires

25,000 lb. Axles

1/4 Poly Rear Fenders

1 1/4" Return Line

1" Pressure Line

Cable Hook Holder

7/8" Cable

Hoist Maintenance Props

	TANBL		AILER HOISTS - M6-250	GVW	Can	List Price
Model	Hoist Rail Type	Holst Capacity	Description	Outer Bridge	Size**	100000000000000000000000000000000000000
			15,650 lbs - 32' length	72,500	22'-30'	\$59,914
M6-OR-250	Outside Rail -Tandem	007		72,500	22'-30'	\$62,984
M6-10-250	Inside/Outside Rail -Tandem		16,900 lbs - 32' length	72,500	22'-28'	\$63,085
	Extendable Tail -Tandem		16,250 lbs - 28' length		-	\$63,283
M6-EX-250	Deadlift- Tandem	50,000 lbs.	15,650 lbs - 28' length	72,500	22'-26'	303,203

MINIMUM TRACTOR SPECIFICATIONS

Minimum tractor specifications are as follows:

Front Axle Rating 12,000lbs minimum

Rear Axle Rating 44,000lbs minimum

Chassis Frame Section Modulus 24 cu.in.

50 GPM @ 1500 running 2200 PSI or greater Wet Kit capable

50 Gallon Reservoir - A5-200, A5-250, ALC-392, AC-416, AC2-470/510 M6-200/250

65 Gallon Reservoir - A5-330, A5-366, A5-402

Recommend using similar size hoses or larger to match system. Hoses from tractor need

to support the following ends:

1" Female Quick Disconnect (Pressure Line) connections must be screw type

1 1/4" Male Quick Disconnect (Return Line) connections must be screw type

^{**}Maximum Container Lengths for this Configuration are Based on Wastequip Z245-type Containers and are Considered Part of the Load. Therefore, the Maximum Container Overhang at the Rear of all Extendable Tail Hoist Models is up to Four (4) Feet.

GVWR can vary based on Tractor wheel base - For Models 200 - 330

TANDEM AXLE ROLL-OFF TRAILER HOIST

50,000 lb. Single Point Suspension Bumper with recessed LED lights

2 Spool Control Valve (3 Spool on EX Models)

Energy Absorbing ICC Bumper DOT Approved LED Lighting Telescopic Lift Cylinders 7" X 4" X 108" Winch Cylinder

Trailer Brake at Street Side Front Fender Seven (7) Wire Electric Connection

Primed & Painted with 2 Part Baked on Epoxy

10 Hole Hub Piloted Steel Rims 50,000 lb. Two Speed Landing Gear

1" Pressure Line

Turn Lock Quick Disconnects 16" X 36 lb. W. F. Frame Mid Body LED Turn Signals

ABS Braking System Heavy Duty Swivel Eye Hot Phosphatized Wash

Operation / Service / Parts Manual

11R/22.5 Tires 25,000 lb. Axles Full Steel Fenders 1 1/4" Return Line Cable Hook Holder **Tractor Fenders** 7/8" Cable

Hoist Maintenance Props Ratchet rear Hold-downs

TANDEM ROLL-OFF TRAILER HOISTS - (A5 HEAVY DUTY SERI					Can	List Price
Model	Holst Rail Type	Hoist Capacity	Description	Outer Bridge	Size**	
11000			16,550 lbs - 32' length	*72,500	22'-30'	\$62,91
A5-OR-250	Outside Rail -Tandem	3075		*72,500	22'-30'	\$65,98
	Inside/Outside Rail -Tandem		17,800 lbs - 32' length		22'-28'	\$66,08
A5-IO-250		60,000 ibs.	17,150 lbs - 28' length	*72,500		
A5-EX-250	Extendable Tail -Tandem		17,800 lbs - 32' length	*72,500	22'-30'	\$66,88
A5-OX-250	Outside Rail/Ext. Tall -Tandem			*72.500	22'-26'	\$66,28
A5-HH-250	Deadlift- Tandem	00,000	16,550 lbs - 28' length			

MINIMUM TRACTOR SPECIFICATIONS

Minimum tractor specifications are as follows:

Front Axle Rating 12,000lbs minimum

Rear Axle Rating 44,000lbs minimum

Chassis Frame Section Modulus 24 cu.in.

50 GPM @ 1500 running 2200 PSI or greater Wet Kit capable

50 Gallon Reservoir - A5-200, A5-250, ALC-392, AC-416, AC2-470/510 M6-200/250

65 Gallon Reservoir - A5-330, A5-366, A5-402

Recommend using similar size hoses or larger to match system. Hoses from tractor need

to support the following ends:

- 1" Female Quick Disconnect (Pressure Line) connections must be screw type
- 1 1/4" Male Quick Disconnect (Return Line) connections must be screw type

^{**}Maximum Container Lengths for this Configuration are Based on Wastequip Z245-type Containers and are Considered Part of the Load. Therefore, the Maximum Container Overhang at the Rear of all Extendable Tall Hoist Models is up to Four (4) Feet.

^{*} GVWR can vary based on Tractor wheel base - For Models 200 - 330

TRI-AXLE ROLL-OFF TRAILER HOIST

50,000 lb. Single Point Suspension

25,000 lb. Tandem Axles

3rd Axle is a Single Point Non Steer Lift Axle Energy Absorbing ICC Bumper where applicable

1/4" A514 Web Section

Trailer Brake at Street Side Front Fender

6.5" X 4.5" X 144" Winch Cyllnder

Heavy Duty Swivel Eye

Seven (7) Wire Electric Connection

Hot Phosphatized Wash

Operation / Service / Parts Manual

10 Hole Hub Plloted Steel Rims

50,000 lb. Two Speed Landing Gear

Turn Lock Quick Disconnects

1 1/4" Return Line

1º Pressure Line

Telescopic Lift Cylinders

DOT Approved LED Lighting

ABS Braking System

10" x 4" x 1/2" Hoist Main Frame

2 Spool Control Valve (3 Spool on EX Models)

Primed & painted with 2 part baked on epoxy

11R/22.5 Tires

Full Steel Fenders

Tractor Fenders

Mid Body LED Turn Signals

Cable Hook Holder

Hoist Maintenance Props

7/8" Cable

Ratchet rear Hold-downs

Single Point Non Steer Lift Axle

Auto Suspension Lowering Valve

Bumper with Recessed LED Lights

	TRI-AXLE ROLL-OF	Holet Capacity	S - (A5 HEAVY DUTY SERIE	GVW Outer	Can Size**	List Price
Model	Holst Rall Type	Hoist Capacity	Description	Bridge		
		60,000 lbs.	20,875lbs - 37' length	*80K	20'-33'	\$83,014
A5-OR-330	Outside Rall / Tri-axle	90/000	21,567lbs - 37' length	*80K	20'-33'	\$86,25
A5-10-330	Inside/Outside Rall- Tri-axle	60,000 lbs.		80K	24'-36'	\$84,63
A5-OR-366	Outside Rail -Trl-axle		17,878lbs - 40' length	SOK	24'-36'	\$87,87
	Inside-Outside Rall -Tri-axle	60,000 lbs.	17,878lbs - 40' length		30'-39'	\$86,39
A5-10-366		60,000 lbs.	21,730lbs - 43' length	80K	-	
A5-OR-402	Outside Rail- Tri-axle	60,000 lbs.	23,908lbs - 43' length	80K	30,-39,	\$89,63
A5-10-402	Inside-Outside Rail- Tri-axie	50,000 lbs.	22,460lbs - 38' length	80K	30'-34'	\$89,63
A5-HH-402	Outside Rail -Tri-exie	1 30,000 103.		recommendation of the second	es au time de la	SAMPLE SA

MINIMUM TRACTOR SPECIFICATIONS

Minimum tractor specifications are as follows:

Front Axle Rating 12,000lbs minimum

Rear Axle Rating 44,000ibs minimum

Chassis Frame Section Modulus 24 cu.ln.

50 GPM @ 1500 running 2200 PSI or greater Wet Kit capable

50 Gallon Reservoir - A5-200, A5-250, ALC-392, AC-416, AC2-470/510 M6-200/250

65 Gallon Reservoir - A5-330, A5-366, A5-402

Recommend using similar size hoses or larger to match system. Hoses from tractor need

to support the following ends:

1° Female Quick Disconnect (Pressure Line) connections must be screw type

1 1/4" Male Quick Disconnect (Return Line) connections must be screw type

A5-330,366 and 402 - All are Tri Axle Standard with Tandem Axle and a Lift Axle, Some States Require a Fixed Tri Axle Set Up. Fixed Tri Axle Must be Specified when Ordering Trailers

A5-402 Trailers have a wider axle track compared to the other trailers.

^{**}Maximum Container Lengths for this Configuration are Based on Wastequip Z245-type Containers and are Considered Part of the Load. Therefore, the Maximum Container Overhang at the Rear of all Extendable Tail Hoist Models is up to Four (4) Feet.

^{*} GVWR can vary based on Tractor wheel base - For Models 200 - 330

SPECIALTY ROLL OFF TRAILER HOISTS

Closed Tandem Suspension Operation/Service/Parts Manual **Bumper with Recessed LED Lights** DOT Approved LED Lighting **Outboard Supported Side Rollers** Air Operated Front Locking Pins Mid Body LED Turn Signals 1 1/4" Return Line **Tractor Fenders**

Nylon Ratchet Hold Downs Heavy Duty Swivel Eye

Auto Suspension Lowering Valve

10 Hole Hub Piloted Steel Rims Aluminum Tread Plate Fenders 50,000 lb. Two Speed Landing Gear Turn Lock Quick Disconnects

Energy Absorbing ICC Bumper

3 Spool Control Valve (4 spool on EX models) Trailer Brake at Street Side Front Fender

10" x 4" Holst Main Frame Hoist Maintenance Props Hot Phosphatized Wash

Primed & Painted with Two Part Baked on Epoxy

11R/22.5 Tires 25,000 lb. Axles 11R/22.5 Tires

6" x 4.5" x 72" Lift Cylinders 6" x 3" x 90" Winch Cylinder

Cable Hook Holder **ABS Braking System** 1" Pressure Line 7/8" Cable

Seven (7) Wire Electric Connection

Model	Holst Rail Type	Hoist Capacity	CARRIAGE TO MAXIMIZE WEIGHT DISTRIBUTED	GVW Outer Bridge	Can Size**	List Price
AC-OR-416	Outside	60,000 lbs.	16,440lbs - 44' length - movable carriage for weight distribution - closed tandem	80K	20'-24'	\$89,758
AC-IO-416	Inside/Outside	60,000 lbs.	17,780lbs - 44' length - movable carriage for weight	80K	20'-24'	\$101,022
AC-EX-416	Extendable Tail	60,000 lbs.	17,320lbs - 40' length - movable carriage for weight	80K	20'-24'	\$95,008
AC-HH-416	Deadlift	50,000 lbs.	18,010lbs - 39' length - movable carriage for weight distribution	80K	20'-24'	\$92,62
			SCALES			
TRSCLE	IOn Board Scales	- Air Ride Suspensi	on Only - A3649			\$72

MINIMUM TRACTOR SPECIFICATIONS

Minimum tractor specifications are as follows:

Front Axle Rating 12,000lbs minimum

Rear Axle Rating 44,000lbs minimum

Chassis Frame Section Modulus 24 cu.in.

50 GPM @ 1500 running 2200 PSI or greater Wet Kit capable

50 Gallon Reservoir - A5-200, A5-250, ALC-392, AC-416, AC2-470/S10 M6-200/250

65 Gallon Reservoir - A5-330, A5-366, A5-402

Recommend using similar size hoses or larger to match system. Hoses from tractor need to support the following ends:

1" Female Quick Disconnect (Pressure Line) connections must be screw type

1 1/4" Male Quick Disconnect (Return Line) connections must be screw type

SPECIALTY ROLL OFF TRAILER HOISTS

Bumper with Recessed LED Lights
10 Hole Hub Piloted Rims
Two Speed Landing Gear
6" x 5" x 4" x 118" Lift Cylinders
6" x 3" x 90" Main Winch Cylinder
Mid Body LED Turn Signals
Holst Maintenance Props
Nylon Ratchet Hold Downs
5/8" Secondary Lift Cable on AC2
Hot Phosphatized Wash
Auto Suspension Lowering Valve
Operation, Installation, Service and Parts Manual

AC2 is a Air Ride Suspension on 10-2 spread
ACH is a fixed Tri Axle Trailer
Trailer Frame T-1 Fabricated I Beam
Outboard Supported Side Rollers
Air Operated Front Locking Pins
Energy Absorbing ICC Bumper - on OR model ONLY
Aluminum Tread Plate Tractor Fenders
4 Spool control valve (5 spool on EX models)
4" x 2.5" x 80" Secondary Winch Cylinder
Seven (7) Wire Electric Connection
Trailer Brake at Street Side Front Fender
10" x 4" x 3/8" Holst Main Frame
Primed & Painted with Two Part Baked on Epoxy

25,000 lb. Axles
11R/22.5 Tires
DOT Approved LEO Lighting
Turn Lock Quick Disconnects
1 1/4" Return Line
1" Pressure Line
Aluminum Rear Fenders
Cable Hook Holder
ABS Braking System
Heavy Duty Swivel Eye
7/8" Main Lift Cable
AC2H is a Fixed Tri Axle Trailer

THE DOUBLE UP TRAILER (TWO CONTAINERS)

Model	Holst Rail Type	Hoist Capacity	E TO MOVE CONTAINER TO FRONT OF HOIS	GVW Outer Bridge	Can Size**	List Price
AC2-OR-470	Outside	50,000 lbs. Main 20,000 (bs Secondary	19,180lbs - 49' length - 2 containers - 1 loaded/1 empty - or one single loaded 10 - 2 spread axie - air ride suspension	80K	18'-22'	\$109,720
AC2H-OR-470	Outside	The Cocondant	19,180lbs - 49' length - 2 containers - both loaded Fixed Tri Axle Trailer	80K	18'-22'	\$114,94
AC2-HH-510	Deadlift	50,000 lbs. Main 20,000	19,500lbs - 48' length - 2 containers - 1 loaded/1empty - or one single loaded 10 - 2 spread axle - air ride suspension - IS4344	80K	18'-22'*	\$114,50

Main Hoist is Located at the Rear of the Trailer, Secondary Hoist is located at the Front of the Trailer Nearest the Cab of the Tractor

MINIMUM TRACTOR SPECIFICATIONS

Minimum tractor specifications are as follows:

Front Axle Rating 12,000lbs minimum

Rear Axle Rating 44,000lbs minimum

Chassis Frame Section Modulus 24 cu.in.

50 GPM @ 1500 running 2200 PSI or greater Wet Kit capable

50 Gallon Reservoir - A5-200, AS-250, ALC-392, AC-416, AC2-470/510 M6-200/250

65 Gallon Reservoir - A5-330, A5-366, A5-402

Recommend using similar size hoses or larger to match system. Hoses from tractor need to support the following ends:

- 1" Female Quick Disconnect (Pressure Line) connections must be screw type
- 1 1/4" Male Quick Disconnect (Return Line) connections must be screw type

^{*} The combination of two (2) 22' containers may work depending on the container design. A maximum of a 20' container on the front and a 22' container on the rear is standard for this trailer model.



FRAME:

Somerset Welding & Steel, Inc. 10558 Somerset Pike

Somerset, PA 15501 Phone: (814) 444-3400 Fax: (814) 443-2621

Customer **B & C BODY COMPANY** 4400 BLUE MOUND RD FORTWORTH TX 76106 Attn: JIM LEWIS Phone: 817-624-3848 Fax: 903-212-3041 Cell: 501-454-1007 End User: HGAC

Stock: N **Brief Description**

Quote: 85578 Type: ALF

Order: PO No:

Alum Live Floor MODEL 45-102-STD Warranty Yrs:

Eng/Auth 06/24/18 15:31

Page 1

JAJ

1. Entered By: Number of Units: Jerry Johnson (814) 233-7868 Sales Rep:

Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

45' 0" DIMENSIONS: LENGTH

102.000" WIDTH

100" CU. YD. = 108 HEIGHT

36" KING PIN SETTING

50" Overall Trailer Height: 12' 10.625" 5TH WHEEL HEIGHT 33' 8" From Back Of Gate

LANDING GEAR LOCATION 12" CROSSMEMBER SPACING

24" SIDE POST SPACING

5/32" Alum Sheet BODY MATERIAL: SIDE FRONT

5/32" Alum Shee LENGTH: .00 " IF MATERIAL VARIES 3/16" ALUM BRITE SIDE REAR

BULKHEAD

Heavy Side Post Extrusion SIDE POSTS 9" 5/8" Top Rail-Grooved Top Rear Roller Brace TOP RAIL REAR BRACE

Intermediate top Roller Brace Ot KEITH 24 SLAT 2295-3.5" 45' CYL 3.0 Qty: 1 INTERMEDIATE BRACE

WALKING MECHINISM

FLOOR: Powered by Customers Wetline HYDRAULICS

5100 couplers, Bulkhead HOOK UP

Barndoor HARDWARE TYPE TAILGATE:

Horizontal paneled barndoor STYLE 5/32" Alum Sheet

SHEET 100" HEIGHT

NUMBER OF PANELS

CONTROLS

Latch ass'y, Barndoor gate Slop Latches On Gate 26" From Bottom of Gate SLOP LATCH

Rubber Gate Seal Z-Rail Extrusion 3/8" RUBBER SEAL LONGMEMBERS

4" I-Beam @2.70# 12" Formed Steel CROSSMEMBERS SUSPENSION SUB-FRAME

Holland Mark V Landing Gear LANDING GEAR

Laminated center pin grab BUMPER Hutch H9600 50K 3-Leaf
Dana D22 #25000 .58 Wall 102" wide trailer SUSPENSION RUNNING GEAR:

AXLES

Walther Hub piloted short stud HUBS AND DRUMS DUAL TIRE STYLE Wheel 22.5x8.25 10H Pilot Stl Wheel 22.5x8.25 10H Pilot Stl WHEELS OUTSIDE

WHEELS INSIDE Goodyear Marathon LHT 11R22.5 14PL TIRES

Air Brake System 2S/1M BRAKES

LADDERS FRONT LADDERS BACK Bulkhead Mounted ACCESSORIES: Tailgate Mounted

Grooved Tarp Rail, Both Sides TARP RAIL

Stripe, Black, 1,73002 STRIPE

Front & Rear TARP HOOKS

LED Light Pkg., In Gate MISCELLANEOUS: ELECTRICAL J & J Mudflaps (Std) MUDFLAPS

None MUDSHIELD Acid Clean BODY PAINT:

As Specified Silver STEEL ATTACHMENTS

Ouote: 85578 # 2

Eng/Auth

Somerset Welding & Steel, Inc. 10558 Somerset Pike

Order: PO No:

Page 2

Somerset, PA 15501

Stock: N

Phone: (814) 444-3400 Fax: (814) 443-2621

Brief Description

Alum Live Floor MODEL 45-102-STD

Warranty Yrs: 1 Entered By: JAJ

Number of Units: 1 Sales Rep: Jerry Johnson Inside Sales: Jerry Johnson

E-Mail: JIM.LEWIS@BANDCBODY.COM

Cell: 501-454-1007 End User: HGAC

Customer

B & C BODY COMPANY

4400 BLUE MOUND RD

FORTWORTH TX 76106

Phone: 817-624-3848

Fax: 903-212-3041

Attn: JIM LEWIS

----- (Optional Equipment Is Included) ----

BULKHEAD 45'MERLOT, MESH, REAR CONTR., PASS.

Price / Unit Including Options:

\$84,811.00

Total Due:

\$84,811.00

Appx. Weight: 16,325 lbs

Terms: NET 30 DAYS

Special Remarks: ************************************

WARNING: The "Overall Height" of this unit was calculated using a standard 5th wheel height, if your 5th wheel is different from that shown, please ask your sales representative to adjust this dimension, or recalculate the difference for an accurate "Overall Height".

Unless indicated above, F.E.T., and sales tax are NOT included in price.

NOTE: If a purchase order is required for payment, the purchase order must be provided before we enter this quote as an order and order any material for this job.

Please review carefully. If you have any questions, contact this office or your sales representative. If there are no questions, please sign and return one of the enclosed copies. We must have a signed copy of this quotation before we process and fabricate your order.

Terms: NET 30 DAYS

PRICE SUBJECT TO CHANGE AFTER 30 DAYS



Somerset Welding & Steel, Inc. 10558 Somerset Pike

Somerset, PA 15501 Phone: (814) 444-3400 Fax: (814) 443-2621

Customer **B & C BODY COMPANY** 4400 BLUE MOUND RD FORTWORTH TX 76106 Attn: JIM LEWIS Phone: 817-624-3848

Fax: 903-212-3041 Cell: 501-454-1007 End User: HGAC

Quote: 85897 Type: ALF Order:

Eng/Auth 06/24/18 15:34 Page 1

PO No: Stock: N

Brief Description
Alum Live Floor FAIRFAX COUNTY

SPEC.w/v-floor

Warranty Yrs: 1. Entered By: JAJ

Number of Units:

Qty: 1

Sales Rep: Jerry Johnson (814) 233-7868

Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

DIMENSIONS:

LENGTH WIDTH

HEIGHT

KING PIN SETTING

5TH WHEEL HEIGHT LANDING GEAR LOCATION

CROSSMEMBER SPACING SIDE POST SPACING

BODY MATERIAL: SIDE FRONT

SIDE REAR

BULKHEAD SIDE POSTS

TOP RAIL REAR BRACE

FLOOR:

FRAME:

INTERMEDIATE BRACE WALKING MECHINISM

HYDRAULICS HOOK UP

TAILGATE:

HARDWARE TYPE

STYLE SHEET HEIGHT

NUMBER OF PANELS

CONTROLS

SLOP LATCH LONGMEMBERS CROSSMEMBERS

SUSPENSION SUB-FRAME

LANDING GEAR BUMPER

RUNNING GEAR:

SUSPENSION AXLES

HUBS AND DRUMS TIRE STYLE

WHEELS OUTSIDE WHEELS INSIDE TIRES

BRAKES

ACCESSORIES:

LADDERS FRONT LADDERS BACK

TARP RAIL STRIPE ELECTRICAL

MUDFLAPS

MISCELLANEOUS:

PAINT:

MUDSHIELD BODY

STEEL ATTACHMENTS

45' 0" 96.000"

96" CU. YD. = 97

42"

50" Overall Trailer Height: 12' 6.625" 33' 8" From Back Of Gate

12"

24"

3/16" ALUM BRITE 3/16" ALUM BRIT LENGTH: .00 " IF MATERIAL VARIES

1/4" ALUM BRITE

Heavy Side Post Extrusion 9" 5/8" Top Rail-Grooved Top Rear Roller Brace

Intermediate top Roller Brace Keith 8 slat 5760401 45 cyl 3"

Powered by Customers Wetline

5100 couplers, Bulkhead Barndoor

Horizontal paneled barndoor

1/4" ALUM BRITE

96 "

Latch ass'y, Barndoor gate
*** NONE ***

Z-Rail Extrusion 3/8"

4" I-Beam @2.70# 12" Formed Steel

Holland Mark V Landing Gear Laminated center pin grab Hend HT300-15-001 30K 96"

Dana P23 #25000 .58 wall 96" wide trailer

Walther Hub Piloted short stud DUAL

Wheel 22.5x8.25 10H Pilot Stl Wheel 22.5x8.25 10H Pilot Stl TIRE, GOODYEAR, G316, 11R22.5 Air Brake System 4S/2M

*** NONE *** Tailgate Mounted SEE PHOTOS

*** NONE *** *** NONE ***

LED Light Pkg., In Gate J & J Mudflaps (Std)

None Acid Clean

As Specified Silver

----- (Optional Equipment Is Included) ----

Page 2

Somerset Welding & Steel, Inc.

10558 Somerset Pike

Order: PO No: Stock: N

Somerset, PA 15501

Phone: (814) 444-3400 Fax: (814) 443-2621

Brief Description

Alum Live Floor FAIRFAX COUNTY SPEC.w/v-floor

Warranty Yrs: 1 Entered By: JAJ Number of Units: 1

Sales Rep: Jerry Johnson Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

Cell: 501-454-1007 End User: HGAC

PIANO HINGE--12 PANEL W/AIR CONTROL AND DOOR AJAR LIGHT--1/4" ALUM TATLGATE 1 FACE SHEET. 3"-1/4"WALL TUBE HORZ.BRACES W/3/8"SHEDDER.&1/4" VERTICAL BRACES

3/16" 5454-H34 1 SIDES

Customer

B & C BODY COMPANY

4400 BLUE MOUND RD

FORTWORTH TX 76106

Phone: 817-624-3848 Fax: 903-212-3041

Attn: JIM LEWIS

9" W/HALF ROUND EXTRUSION OLD STYLE TOPRAIL

LAND. GEAR LANDING GEAR TO HAVE CURBSIDE CRANK 7

SOLID 1" X 1" SUBDECK REAR 20" W/ INTERLOCK FLOOR

DANA DISC BRAKES, INSTALL DIAGNOS- TIC CABLE #S449-364-143-0 BRAKES 1

PULL LANYARDS ON AIR ANK DRAIN VALVES

HYDRAULIC FLIP ROOF-INST. VERSITEX. DOUBLE ANGLES IN LIEU OF Z, 1

ALUM STRIPS IN LIEU OF FENDER WASHERS....VERSITEX IS .085 THICK.

12' CONTROL CABLE COIL TYPE MALE ENDS MOUNTED ON TRAILER 14' HYDRAULIC HOSES ON TRAILER W/ HOSE HANGER OTHER 1

OTHER

HYDRAULICS AEROQUIP 5100-16 ON PRESSURE AND 5100-20 ON RETURN-BOTH FEMALE 1

FITTINGS

MUD FLAPS--AERODYNAMIC FULL WIDTH AT REAR. QUARTER SPLASH GUARDS FLAPS IN FRONT OF TANDEM--VORTEX BRAND

REG. HOLD. BETTS MODEL PS-1 REGISTRATION HOLD- ER P/S FRONT

INCLUDE WIRING TO REAR. ELECTRONIC BACKUP ALARM REAR 1

CHANGE INSIDE SHEDDER PLATE TO 1/4" SIDE

BULKHEAD VISION WINDOW, EXP METAL WELDED TO STEEL ANGLE FRAME-USE PERFORAT 1

STEEL. 12 VOLT TRUCKLITE, LIGHTS IN GATE LIGHTS 1

, EXTRA 7 PIN PLUG FOR ABS

SIDE MARKER LIGHTS BETWEEN POSTS.

NON SMUDGE ALUMINUM (INCLUDING WHEELS) PAINT 1

STATE INSPECTION -- VA. SAFETY INSP. OTHER 1

INSTALL CENTER TAILGATE MOUNTED 6000 SERIES LIGHT@ 3RD STEP 1. OTHER FROM BOTTOM ON GATE.

OTHER

ADD SPECIAL STEPS REF; 03W/5193 INSTALL ALLIGATER V2B DOUBLE CHECK VALVE CAPS ON WHEELS OTHER 1 STEEL, AND REAR TURN SIGNALS

REAR HINGE PIN TO BE STAINLESS 1 OTHER TO BE AMBER

PREFERRED CUSTOMER DISCOUNT 1 SPECIAL AIR DISC BRAKES, BENDIX ADB-22X

BRAKES 1 INSTALL CUSTOMER SUPPLIED ONBOARD AIRWEIGH SYSTEM 1 SCALE

INCLUDES 50' POWER & SENSOR CABLE

OTHER INCLUDE ABS LINE 1

STAINLESS STEEL HYDRAULIC TUBING NOTE

FOR WALKING FLOOR HYDRAULICS.

\$135,464,41

Price / Unit Including Options:

\$135,464.41 Total Due:

Appx. Weight: 22,714 lbs

Terms: NET 30 DAYS

Special Remarks:

Ouote: 85897 # 1

Eng/Auth

Somerset Welding & Steel, Inc. 10558 Somerset Pike

Order: PO No:

Page 3

Stock: N

Somerset, PA 15501 Phone: (814) 444-3400 Fax: (814) 443-2621

Brief Description

Customer B & C BODY COMPANY 4400 BLUE MOUND RD

Alum Live Floor FAIRFAX COUNTY SPEC.w/v-floor

FORTWORTH TX 76106 Attn: JIM LEWIS Phone: 817-624-3848

Warranty Yrs: 1 Entered By: JAJ Number of Units: 1

Fax: 903-212-3041 Cell: 501-454-1007 End User: HGAC

Sales Rep: Jerry Johnson Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

WARNING: The "Overall Height" of this unit was calculated using a standard 5th wheel height, if your 5th wheel is different from that shown, please ask your sales representative to adjust this dimension, or recalculate the difference for an accurate "Overall Height".

NOTES: ITEM #1-INCLUDE 2ND GREASE FITTING @180 DEGREE APART ON THE FRONT SPROCKETS. CANNOT RELOCATE GREASE FITTING TO THE FRONT SIDE AT

BOTTOM AT THIS TIME. ITEM#2--RELOCATE GREASE FITTINGS ON TOP DOORS AS DISCUSSED.

ITEM#3--ELECTRICAL BOXES BETTER SEAL, & WEEP HOLES IN BOTTOMS.

ITEM#4--HYDRAULIC TUBING TO STAINLESS STEEL INCLUDED.

Unless indicated above, F.E.T., and sales tax are NOT included in price.

NOTE: If a purchase order is required for payment, the purchase order must be provided before we enter this quote as an order and order any material for this job.

NOTICE: Standard 5/8" wall axles used with the air ride suspension can only be rated for 22,500 pounds maximum load.

Please review carefully. If you have any questions, contact this office or your sales representative. If there are no questions, please sign and return one of the enclosed copies. We must have a signed copy of this quotation before we process and fabricate your order.

Terms: NET 30 DAYS

PRICE SUBJECT TO CHANGE AFTER 30 DAYS



Somerset Welding & Steel, Inc. 10558 Somerset Pike

Somerset, PA 15501 Phone: (814) 444-3400 Fax: (814) 443-2621

Customer **B & C BODY COMPANY** 4400 BLUE MOUND RD FORTWORTH TX 76106 Attn: JIM LEWIS

Phone: 817-624-3848 Fax: 903-212-3041 Cell: 501-454-1007 End User: HGAC

Quote: 85577 Type: ATTR Order:

Eng/Auth 06/24/18 15:30 Page 1

PO No: Stock: N

Brief Description Alum Tipper Trailer ATTR-NTWD

Warranty Yrs: 1. JAJ Entered By: Number of Units: Sales Rep:

Jerry Johnson (814) 233-7868

Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

DIMENSIONS:

FRAME:

LENGTH HTOTH

102.000" 100" CU. YD. = 115 HEIGHT

36" KING PIN SETTING

5TH WHEEL HEIGHT

48' 0"

50" Overall Trailer Height: 12' 10.625" 34' 6" From Back Of Gate LANDING GEAR LOCATION

16" CROSSMEMBER SPACING 24" SIDE POST SPACING

BODY MATERIAL: SIDE FRONT 5/32" Alum Sheet

3/16" ALUM BRIT LENGTH: 180.00 " IF MATERIAL VARIES SIDE REAR

3/16" Alum Sheet BULKHEAD

SIDE POSTS

TOP RAIL

Heavy Side Post Extrusion
9" 5/8" Top Rail-Grooved
Intermediate top Roller Brace Qty: 1
3/8" Alum Plate
3/8" Alum Plate LENGTH: .00 " IF MATERIAL VARIES INTERMEDIATE BRACE

FLOOR: FRONT

REAR

TAILGATE: HARDWARE TYPE

Top Offset Hardware Horizontal panel Gate 5/32" Alum Sheet STYLE SHEET

HEIGHT 100"

NUMBER OF PANELS Air T-Gate Latch, Bulkhead Mounted CONTROLS

Slop Latches On Gate 26" From Bottom of Gate SLOP LATCH

Rubber Gate Seal Z-Rail Extrusion 3/8" RUBBER SEAL

LONGMEMBERS

4" Boxed CROSSMEMBERS 12" Formed Steel

SUSPENSION SUB-FRAME Holland Mark V 102" LANDING GEAR

BUMPER Laminated center pin grab Hendrickson HT300 Tandem SUSPENSION RUNNING GEAR:

Dana P23 #25000 .58 wall 102" wide trailer AXLES

Haldex Auto-Slack Adjusters
Walther Hub Pilot SLACK ADJUSTERS HUBS AND DRUMS Walther Hub Piloted short stud DUAL TIRE STYLE

Wheel 22.5x8.25 10H Pilot Stl Wheel 22.5x8.25 10H Pilot Stl WHEELS OUTSIDE WHEELS INSIDE MICHELIN Xline, 11R22.5 14 PLY TIRES

Air Brake System 2S/1M BRAKES

Bulkhead Mounted WIDEN RUNGS, BEEF LADDERS FRONT ACCESSORIES:

*** NONE *** NOTHING ON GATE LADDERS BACK Grooved Tarp Rail, Both Sides TARP RAIL

*** NONE *** STRIPE Front & Rear TARP HOOKS

LED Light Pkg., Rear Pan ELECTRICAL MISCELLANEOUS:

J & J Mudflaps (Std) MUDFLAPS

None MUDSHIELD Acid Clean PAINT: BODY

As Specified BLACK STEEL ATTACHMENTS

(Continued on Next Page)

1

Eng/Auth

Somerset Welding & Steel, Inc. 10558 Somerset Pike

Order: PO No:

Page 2

Somerset, PA 15501

Stock: N

Phone: (814) 444-3400 Fax: (814) 443-2621

Customer B & C BODY COMPANY 4400 BLUE MOUND RD FORTWORTH TX 76106 Attn: JIM LEWIS Phone: 817-624-3848 Fax: 903-212-3041

Cell: 501-454-1007

End User: HGAC

Brief Description Alum Tipper Trailer ATTR-NTWD

Warranty Yrs: 1 Entered By: JAJ Number of Units: 1 Sales Rep: Jerry Johnson

Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

---- (Optional Equipment Is Included) ----

SUSPENSION SUBSTITUTE HENDRICKSON AAT250 INTRAX IN LIEU OF HT300, AIR-1 BAGS TO DUMP WHEN BRAKES ARE SET.

SUSPENSION FRONT AXLE AAL250 W/LIFT, REAR AXLE TO BE AAT250 W/AIR GAUGE FOR

BAGS, LOCATED ON BULKHEAD SUSPENSION FRONT AXLE TO LIFT--LIFT KIT TO

RAISE AXLE APPROX 5" IN FULL 1 UP POSITION. SPECIAL LIFT KIT W/DUMP. SAME AS 03W-8815.

CONSPICUITY TAPE BOTTOM RAIL BOTH SIDES FULL LENGTH & ON THE 1 TAILGATE DOWN SIDES AND ACROSS BOTTOM

REINFORCE TOP RAIL FOR TARP SYSTEM SAME AS 03W-8815. BODY

FLOOR TO BE 1/2" MATERIAL FULL LENGTH 1 BODY

LOWER BUMPER PADS ON REAR APPROX 10". SEE PHOTOS FROM NTWD NOTE

CUSTOMER HAS LOWERED ALL PREVIOUS UNITS DELETE METAL STEP AT REAR, BUMPER 1 NOTE

5 TARP HOOKS ABOVE TARP RAIL EVENLY SPACED ON CLOSED SIDE OF TARP 1 SIDE

HINGE BOLTS ON FRONT OF TARP SYS. HAVE WORKED LOOSE IN PAST. 1 NOTE NEED LOCK WASHERS OR SOMETHING BETTER TO PREVENT BOLTS FROM COMING LOOSE.

DONOVAN SIDEWINDER CS MOUNT HD MESH DRIVER SIDE MT. FLIPS TO 1 TARPER DRIVER SIDE.LADDER CENTERED. W/CONTROLS DS. MATERIAL #1906, ORANGE MESH.

> \$84,200.00 Price / Unit Including Options:

> > \$84,200.00 Total Due:

Appx. Weight: 15,461 lbs Terms: NET 30 DAYS

Special Remarks:

WARNING: The "Overall Height" of this unit was calculated using a standard 5th wheel height, if your 5th wheel is different from that shown, please ask your sales representative to adjust this dimension, or recalculate the difference for an accurate "Overall Height".

Unless indicated above, F.E.T., and sales tax are NOT included in price.

NOTE: If a purchase order is required for payment, the purchase order must be provided before we enter this quote as an order and order any material for this job.

NOTICE: Standard 5/8" wall axles used with the air ride suspension can only be rated for 22,500 pounds maximum load.

Please review carefully. If you have any questions, contact this office or your sales representative. If there are no questions, please sign and return one of the enclosed copies. We must have a signed copy of this quotation before we process and fabricate your order.

Terms: NET 30 DAYS

PRICE SUBJECT TO CHANGE AFTER 30 DAYS



FRAME:

RUNNING GEAR:

Somerset Welding & Steel, Inc. 10558 Somerset Pike

Somerset, PA 15501 Phone: (814) 444-3400 Fax: (814) 443-2621

Customer B & C BODY COMPANY 4400 BLUE MOUND RD FORTWORTH TX 76106 Attn: JIM LEWIS Phone: 817-624-3848 Fax: 903-212-3041 Cell: 501-454-1007 End User: HGAC

Quote: 85576 Type: ATTR Order: PO No:

Eng/Auth 06/24/18 15:30 Page 1

Stock: N

Brief DescriptionAlum Tipper Trailer ATTR-STD

Warranty Yrs: 1 Entered By: JAJ Number of Units: Sales Rep:

Jerry Johnson (814) 233-7868 Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

48' 0" DIMENSIONS: LENGTH 102.000" 100" CU. YD. = 115 HEIGHT 36" KING PIN SETTING 50" Overall Trailer Height: 12' 10.625" 34' 6" From Back Of Gate 5TH WHEEL HEIGHT LANDING GEAR LOCATION 16" CROSSMEMBER SPACING 24" SIDE POST SPACING 5/32" Alum Sheet BODY MATERIAL: SIDE FRONT 3/16" ALUM BRIT LENGTH: 180.00 " IF MATERIAL VARIES 3/16" Alum Sheet SIDE REAR BULKHEAD Heavy Side Post Extrusion SIDE POSTS 9" 5/8" Top Rail-Grooved TOP RAIL Intermediate Top Spring Brace Qty: 1 INTERMEDIATE BRACE 1/4" Alum Plate FRONT FLOOR: 3/8" Alum Plate LENGTH: 120.00 " IF MATERIAL VARIES REAR Top Offset Hardware Horizontal panel Gate HARDWARE TYPE TAILGATE: STYLE

5/32" Alum Sheet SHEET 100" HEIGHT

NUMBER OF PANELS

Air T-Gate Latch, Bulkhead Mounted CONTROLS

Slop Latches On Gate 26" From Bottom of Gate SLOP LATCH Rubber Gate Seal

RUBBER SEAL LONGMEMBERS None

4" Boxed CROSSMEMBERS 12" Aluminum Channel SUSPENSION SUB-FRAME

Holland Contender w/elephant feet LANDING GEAR

Center Pin Grab w/Laminated BUMPER Reyco 21B 50K Single Leaf SUSPENSION Dana D22 #22500 1/2" wall 102" AXLES

Haldex Auto-Slack Adjusters SLACK ADJUSTERS Walther Hub piloted short stud HUBS AND DRUMS TIRE STYLE DUAL

Wheel 22.5x8.25 10H Pilot Stl Wheel 22.5x8.25 10H Pilot Stl WHEELS OUTSIDE WHEELS INSIDE Goodyear Marathon LHT 11R22.5 14PL TIRES

Air Brake System 2S/1M BRAKES

Bulkhead Mounted Tailgate Mounted LADDERS FRONT ACCESSORIES: LADDERS BACK Grooved Tarp Rail, Both Sides TARP RAIL Stripe, Black, 1,73002

STRIPE Front & Rear TARP HOOKS LED Light Pkg., Rear Pan

MISCELLANEOUS: ELECTRICAL J & J Mudflaps (Std) MUDFLAPS ***None*** MUDSHIELD

Acid Clean PAINT: YCOR As Specified Silver STEEL ATTACHMENTS

Quote: 85576 # 2

Enq/Auth

Somerset Welding & Steel, Inc.

10558 Somerset Pike

Order: PO No: Page 2

Somerset, PA 15501

Stock: N

Phone: (814) 444-3400 Fax: (814) 443-2621

Brief Description Alum Tipper Trailer ATTR-STD

B & C BODY COMPANY 4400 BLUE MOUND RD FORTWORTH TX 76106 Attn: JIM LEWIS

Customer

Warranty Yrs: 1 Entered By: JAJ Number of Units: 1

Phone: 817-624-3848 Fax: 903-212-3041 Cell: 501-454-1007 Sales Rep: Jerry Johnson Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

End User: HGAC

---- (Optional Equipment Is Included) ----

TARPER

DONOVAN SIDEWINDER CS MOUNT MESH

Price / Unit Including Options:

\$72,800.00

Total Due:

\$72,800.00

Appx. Weight: 13,719 lbs

Terms: NET 30 DAYS

Special Remarks: *************************

WARNING: The "Overall Height" of this unit was calculated using a standard 5th wheel height, if your 5th wheel is different from that shown, please ask your sales representative to adjust this dimension, or recalculate the difference for an accurate "Overall Height".

Unless indicated above, F.E.T., and sales tax are NOT included in price.

NOTE: If a purchase order is required for payment, the purchase order must be provided before we enter this quote as an order and order any material for this job.

Please review carefully. If you have any questions, contact this office or your sales representative. If there are no questions, please sign and return one of the enclosed copies. We must have a signed copy of this quotation before we process and fabricate your order.

Terms: NET 30 DAYS

PRICE SUBJECT TO CHANGE AFTER 30 DAYS



Somerset Welding & Steel, Inc. 10558 Somerset Pike

Somerset, PA 15501 Phone: (814) 444-3400 Fax: (814) 443-2621

Customer B & C BODY COMPANY 4400 BLUE MOUND RD **FORTWORTH TX 76106** Attn: JIM LEWIS

Phone: 817-624-3848 Fax: 903-212-3041 Cell: 501-454-1007 End User: HGAC

Quote: 85575 APO Type: Order:

Eng/Auth 06/24/18 15:29 Page 1

PO No: Stock: N

Brief DescriptionAluminum Pushout Trailer HGAC, APO45

Warranty Yrs: 1. Number of Units: Entered By:

Sales Rep: Jerry Johnson (814) 233-7868

Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

BODY:

LENGTH

WIDTH HEIGHT

STYLE

SIDES:

SIDE MATERIAL SIDE POSTS POST SPACING

TOP RAIL SIDE LADDERS

TARP RAIL ROOF: MATERIAL

ROOF MATERIAL FLOOR:

CROSSMEMBER FLOOR DRAIN

TAILGATE:

HARDWARE TYPE STYLE SHEET

> HEIGHT CONTROLS SLOP LATCHES LEAK TEST

RUBBER SEAL APRON

RUNNING GEAR:

SUSPENSION AXLES

SLACK ADJUSTERS

HUBS AND DRUMS TIRE STYLE WHEELS OUTSIDE

WHEELS INSIDE TTRES

HYD FUNCTIONS

Quick Couplers Coupler size

HYD CONTROLS

GUIDE SHOES LANDING GEAR

KING PIN

MUDSHIELD

BRAKES SUSPENSION SUB-FRAME

HOOK UP

TANK

MODEL MATERIAL

HYDRAULICS:

EJECTOR:

FRAME:

MISC:

KING PIN SETTING DOCUMENT HOLDER MUDFLAPS

TELESCOPIC CYLINDERS

96" Wide 60"

45'

Open Top 3/16" ALUM BRITE

Tapered Side Post Extrusion

24" Full Length

9" Extruded Top Rail-Grooved

Drivers Side Front
NONE

3/16" Aluminum

Bolt-on section over Ejector

1/4" Alum Plate

4" Boxed

Two 3" drains, forward/ejector Hyd. Hi-Lift Tailgate

Horizontal Panel Tailgate 3/16" ALUM BRITE

60 "

Air operated T-Gate Latch 4 Slop Latches on Gate No Test Required

Rubber Gate Seal 4" EYEBROW APRON

Reyco #52,000 9-leaf susp.

Dana D22 #25000 .58 Wall 96" wide trailer Haldex Auto-Slack Adjusters

Walther Hub Pilot Short Stud 10-00011-132 Dura

DUAL Wheel 22.5x8.25 10H Pilot Stl Wheel 22.5x8.25 10H Pilot Stl Goodyear Marathon LHT 11R22.5 14PL 4S/2M Tandem Air Brake System

Standard for Tandem Push-out, Hyd. Lift Gate

DAT95-103-438 Manual on Trailer

3 Line, Tank & valve Tractor 5100 Series Quick Couplers 1"P,1-1/4"R,1-1/4"R

Customer Supplied (On Chassis) For 45' Push-out 1/4" Alum Plate

WMHU

Holland MK V w/Skid Foot Standard King Pin

24"

Betts Document Holder J & J Mudflaps (Std) Standard Mudshield

(Continued on Next Page)

Quote: 85575 # 2

Eng/Auth

Somerset Welding & Steel, Inc.

10558 Somerset Pike

Order: PO No: Page 2

Somerset, PA 15501

Stock: N

Phone: (814) 444-3400 Fax: (814) 443-2621

Brief Description

B & C BODY COMPANY 4400 BLUE MOUND RD

Customer

Aluminum Pushout Trailer HGAC, APO45

FORTWORTH TX 76106 Attn: JIM LEWIS

Phone: 817-624-3848 Fax: 903-212-3041 Cell: 501-454-1007

End User: HGAC

Warranty Yrs: 1 Entered By: JAJ Number of Units: 1

Sales Rep: Jerry Johnson Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

LIGHTS:

LIGHT PACKAGE

LED Light Pkg., Rear Pan

MID TURN SIGNALS

LED Amber Mid-Turns

PAINT:

STEEL ATTACHMENTS

BODY

Non-Smudge Aluminum Silver

Acid Clean

----- (Optional Equipment Is Included) ----

Price / Unit Including Options:

\$104,738.00

Total Due:

\$104,738.00

========== Appx. Weight: 16,175 lbs

Terms: NET 30 DAYS

Special Remarks:

Unless indicated above, F.E.T., and sales tax are NOT included in price.

NOTE: If a purchase order is required for payment, the purchase order must be provided before we enter this quote as an order and order any material for this job.

Please review carefully. If you have any questions, contact this office or your sales representative. If there are no questions, please sign and return one of the enclosed copies. We must have a signed copy of this quotation before we process and fabricate your order.

Terms: NET 30 DAYS

PRICE SUBJECT TO CHANGE AFTER 30 DAYS



Somerset Welding & Steel, Inc. 10558 Somerset Pike

Somerset, PA 15501 Phone: (814) 444-3400 Fax: (814) 443-2621

Customer
B & C BODY COMPANY
4400 BLUE MOUND RD
FORTWORTH TX 76106
Attn: JIM LEWIS
Phone: 817-624-3848

Fax: 903-212-3041 Cell: 501-454-1007 End User: HGAC Quote: 85574 # Type: SPO Order:

Order: PO No: Stock: N

Brief Description Steel Pushout Trailer SPO-Monmouth

Warranty Yrs: 1
Number of Units: 1 Entered By: JAJ
Sales Rep: Jerry Johnson

Eng/Auth

Page 1

06/24/18 15:28

Jerry Johnson (814) 233-7868 nside Sales: Jerry Johnson

Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

45' LENGTH BODY: 96" Wide WIDTH 78" HEIGHT Open Top STYLE 10 gauge HT SIDE FRONT SIDES: 10 gauge HT 12 gauge HT 18" REAR 1/3, 24" FRONT 2/3's SIDE REAR SIDE POSTS POST SPACING 3 ROWS LAST 1/3 6" x 3" x 1/4" Tube HORIZONTAL BRACING TOP RAIL Drivers Side Front SIDE LADDERS * * None * *
* * None * * MATERIAL ROOF: POST MATERIAL * * None * * POST SPACING ROOF BRACES * * None * * * * None * * ROOF OPENING 1/4"Hardox 450 MATERIAL FLOOR: 4" (7.7 LB/FT) "I" BEAM CROSSMEMBER Barndoor (P.S. Hinge) HARDWARE TYPE TAILGATE: H.D.Barndoor STYLE 10 gauge HT 78 " SHEET HEIGHT * * None * * LADDER Manual Gate Latch CONTROLS * * None * * COMPACTOR Rubber seal RUBBER SEAL Reyco 21B 52K 9 Leaf 96" SUSPENSION RUNNING GEAR: Dana D22 #25000 .58 Wall 96" wide trailer AXLES Haldex Auto-Slack Adjusters
Walther Hub piloted short stud SLACK ADJUSTERS HUBS AND DRUMS DUAL TIRE STYLE Wheel 22.5x8.25 10H Pilot Stl Wheel 22.5x8.25 10H Pilot Stl WHEELS OUTSIDE WHEELS INSIDE DUNLOP SP160 11R22.5 16 PLY TIRES 4S/2M Tandem Air Brake System BRAKES BRAKES SUSPENSION SUB-FRAME 1/4" Formed Channel (Tandem) * * None * * ENGINE (POWER SOURCE) HYDRAULICS: PUMP Push Out HYD FUNCTIONS CUSTOM DAT96-83-438TRUNION TELESCOPIC CYLINDERS Electric in Chassis Cab HYD CONTROLS Tank on Tractor, Valve on Trlr HOOK UP 5100 Series Quick Couplers 1"P,1-1/4"R,1-1/4"R Quick Couplers Coupler size Customer Supplied (On Chassis) TANK For 45' Push-out MODEL **EJECTOR:** 1/4 HT MATERIAL Standard Steel GUIDE SHOES

(Continued on Next Page)

Standard King Pin

LANDING GEAR

KING PIN

FRAME:

Holland MK V w/Wheel/Skid Foot

Customer B & C BODY COMPANY

4400 BLUE MOUND RD

FORTWORTH TX 76106

Phone: 817-624-3848 Fax: 903-212-3041 Cell: 501-454-1007

Attn: JIM LEWIS

Eng/Auth

Somerset Welding & Steel, Inc.

10558 Somerset Pike

Order: PO No: Stock: N Page 2

Somerset, PA 15501

Phone: (814) 444-3400 Fax: (814) 443-2621

Brief Description Steel Pushout Trailer

SPO-Monmouth

Warranty Yrs: 1 Entered By: JAJ

Number of Units: 1 Sales Rep: Jerry Johnson Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

End User: HGAC

MISC:

KING PIN SETTING

36"

DOCUMENT HOLDER MUDFLAPS

Betts Document Holder J & J Mudflaps (Std) Standard Mudshield

LIGHTS:

MUDSHIELD LIGHT PACKAGE MID TURN SIGNALS

LED Light Pkg., In Gate LED Amber Mid-Turns

BODY PAINT:

One Color Genesis Paint

---- (Optional Equipment Is Included) ----

- SUSPENSION USE SINGLE POINT SUSPENSION IN LIEU OF REYCO 9 LEAF SPRING SUSP. 1 60K SUSPENSION.
 - SIDE ACCESS DOOR 36" X 36" OPENING SIDE

1 TOW HOOKS, PAIR 1 REAR

DONOVAN SIDEWINDER DRIVER SIDE MNT. TARP TO STOP AT REAR JUST 1 TARPER

FORWARD OF HYDRAULIC TAILGATE HARDWARE. HEAVY DUTY PUSH BUMPER W/CENTER

GRAB PIN REAR TANDEMS, FRAME TO BOTTOM RAIL PLATE COVERING CROSSMEMBERS OVER COVER 7

INSIDE AND OUTSIDE. MGM BRAKE CHAMBERS, EPOXY COATED OTHER DOOR STYLE

TAILGATE HI LIFT TAILGATE IN LIEU OF BARN 1

- UNDERCOAT FRAME RAILS, CROSSMEMBERS FULL LENGTH OF TRAILER 1 PAINT
- WIRELESS CAMERA TOP OF TRAILER IN FRONT FACING TOWARD GATE 1 CAMERA IN CAB SCREEN TO BE INSTALLED AT J&J PRIOR TO SHIPPING
- CONTROLS 3 FUNCTION, EJECTOR, TARP SYSTEM, AND HIGH LIFT GATE, PLUMBED 1 FOR CAB CONTROLS -- REQUIRES SAUER DANFOSS VALVE

PREFERRED CUSTOMER DISCOUNT 1 SPECIAL

CONTROLS, HIGH LIFT, AND SEQUENCING ENSURE SEQUENCING FOR TARP, GATE 1

HIGH LIFT STYLE GATE. 1

EJECTOR. COORDINATE W/JJTE TO MAKE SURE UNITS MESH.
TAILGATE MANUAL GATE LATCHES NOT USED, WITH HIGH
ADJUST BODY LENGTH TO BE 41' OVERALL, INCL INCLUDE PROPER STROKE CYLINDER

ACTUAL CUBIC CAPACITY WATER LEVEL, APPROX 68.5 SEQUENCE SO TARP MUST OPEN, GATE MUST OPEN BEFORE EJECTOR CAN PLUMBING

ENGAGE. Price / Unit Including Options: \$117,148.41

-----\$117,148.41 Total Due:

============== Appx. Weight: 29,909 lbs Terms: NET 30 DAYS

Special Remarks: OPTION; FOAM FILL 8 TIRES ADD \$2900.00 TO BASE PRICE. *************

Unless indicated above, F.E.T., and sales tax are NOT included in price.

NOTE: If a purchase order is required for payment, the purchase order must be provided before we enter this quote as an order and order any material for this job.

(Continued on Next Page)

06/24/18 15:28

Ouote: 85574 # 2 Somerset Welding & Steel, Inc.

Order:

Eng/Auth Page 3

10558 Somerset Pike

PO No: Stock: N

Somerset, PA 15501

Phone: (814) 444-3400 Fax: (814) 443-2621

Brief Description Steel Pushout Trailer

SPO-Monmouth

Warranty Yrs: 1 Entered By: JAJ

Number of Units: 1 Sales Rep: Jerry Johnson Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

Fax: 903-212-3041 Cell: 501-454-1007

End User: HGAC

Attn: JIM LEWIS

Customer

B & C BODY COMPANY

4400 BLUE MOUND RD

FORTWORTH TX 76106

Phone: 817-624-3848

Please review carefully. If you have any questions, contact this office or your sales representative. If there are no questions, please sign and return one of the enclosed copies. We must have a signed copy of this quotation before we process and fabricate your order.

Terms: NET 30 DAYS

PRICE SUBJECT TO CHANGE AFTER 30 DAYS



Somerset Welding & Steel, Inc. 10558 Somerset Pike

Somerset, PA 15501 Phone: (814) 444-3400 Fax: (814) 443-2621

Customer **B & C BODY COMPANY** 4400 BLUE MOUND RD **FORTWORTH TX 76106** Attn: JIM LEWIS Phone: 817-624-3848

Fax: 903-212-3041 Cell: 501-454-1007

End User: HGAC--STEEL EJECTOR TRAILER

LANDING GEAR

KING PIN

FRAME:

Quote: 85573 SPO Type:

Order: PO No: Stock: N

Brief Description Steel Pushout Trailer

Warranty Yrs: Number of Units: 1 Entere Sales Rep: Jerry Johnson (814) 233-7868 Entered By: JAJ

Eng/Auth

Page 1

06/24/18 15:27

Inside Sales: Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

451 LENGTH BODY: WIDTH 96" Wide 96" HEIGHT Closed Top STYLE 12 gauge HT SIDE FRONT SIDES: SIDE FRONT
SIDE REAR
SIDE POSTS
12 gauge HT
10 gauge HT
12 gauge HT
12 gauge HT
12 gauge HT
13 gauge HT
14 gauge HT
15 gauge HT
16 gauge HT
17 gauge HT
18 REAR 1/3, 24 FRONT 2/3's
18 REAR 1/3, 24 FRONT 2/3's
18 REAR 1/3, 24 FRONT 2/3'S
19 Gauge HT
10 gauge HT
11 gauge HT
12 gauge HT
13 gauge HT
14 gauge HT
15 gauge HT
16 gauge HT
17 gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3, 24 FRONT 2/3'S
18 Gauge HT
18 REAR 1/3 FRONT 2/3' SIDE REAR SIDE POSTS Drivers Side Front SIDE LADDERS 12 Ga. Hi-Ten MATERIAL ROOF: 12 Ga. Hi-Ten Same as Sides POST MATERIAL POST SPACING ROOF BRACES Same as Sides * * None * * 3/16 HT ROOF OPENING MATERIAL FLOOR: CROSSMEMBER 4" (7.7 LB/FT) "I" BEAM Barndoor (P.S. Hinge) HARDWARE TYPE TAILGATE: Dutch Door STYLE 10 gauge HT 96 " SHEET HEIGHT * * None * * LADDER Manual Gate Latch CONTROLS Side Grab Hook-up COMPACTOR Rubber seal RUBBER SEAL Reyco 21B 52K 9 Leaf 96" RUNNING GEAR: SUSPENSION Dana D22 #25000 .58 Wall 96" wide trailer Haldex Auto-Slack Adjusters Walther Hub piloted short stud AXLES SLACK ADJUSTERS HUBS AND DRUMS DUAL TIRE STYLE WHEELS OUTSIDE WHEELS INSIDE Wheel 22.5x8.25 10H Pilot Stl Wheel 22.5x8.25 10H Pilot Stl Goodyear Marathon LHT 11R22.5 14PL TIRES 4S/2M Tandem Air Brake System SUSPENSION SUB-FRAME ENGINE (POWER SOURCE) BRAKES 1/4" Formed Channel (Tandem)
* * None * * HYDRAULICS: PUMP HYD FUNCTIONS Push Out TELESCOPIC CYLINDERS DAT95-103-438 Manual on Trailer HYD CONTROLS Tank on Tractor, Valve on Trlr 5100 Series Quick Couplers 1"P,1-1/4"R,1-1/4"R HOOK UP Quick Couplers Coupler size Customer Supplied (On Chassis) TANK For 45' Push-out EJECTOR: MODEL 1/4 HT MATERIAL GUIDE SHOES Standard Steel

Holland MK V w/Wheel/Skid Foot

Standard King Pin

MISC:

Quote: 85573 # 2

Eng/Auth

Somerset Welding & Steel, Inc. 10558 Somerset Pike

Order: PO No: Page 2

Somerset, PA 15501

Stock: N

Phone: (814) 444-3400 Fax: (814) 443-2621

Customer B & C BODY COMPANY

Steel Pushout Trailer

4400 BLUE MOUND RD FORTWORTH TX 76106 Attn: JIM LEWIS Phone: 817-624-3848

Warranty Yrs: 1 Entered By: JAJ Number of Units: 1 Sales Rep: Jerry Johnson

Brief Description

Fax: 903-212-3041 Cell: 501-454-1007 Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

End User: HGAC--STEEL EJECTOR TRAILER

30" KING PIN SETTING

Betts Document Holder DOCUMENT HOLDER J & J Mudflaps (Std) MUDFLAPS Standard Mudshield

MUDSHIELD LED Light Pkg., In Gate LED Amber Mid-Turns LIGHT PACKAGE LIGHTS: MID TURN SIGNALS One Color Genesis Paint BODY PAINT:

----- (Optional Equipment Is Included) ----

Price / Unit Including Options: \$89,669.00

_____ \$89,669.00 Total Due: ===========

Appx. Weight: 28,628 lbs

Terms: NET 30 DAYS

Special Remarks: **********************************

Unless indicated above, F.E.T., and sales tax are NOT included in price.

NOTE: If a purchase order is required for payment, the purchase order must be provided before we enter this quote as an order and order any material for this job.

Please review carefully. If you have any questions, contact this office or your sales representative. If there are no questions, please sign and return one of the enclosed copies. We must have a signed copy of this quotation before we process and fabricate your order.

Terms: NET 30 DAYS

PRICE SUBJECT TO CHANGE AFTER 30 DAYS



Somerset Welding & Steel, Inc. 10558 Somerset Pike

Somerset, PA 15501 Phone: (814) 444-3400 Fax: (814) 443-2621

Customer **B & C BODY COMPANY** 4400 BLUE MOUND RD **FORTWORTH TX 76106** Attn: JIM LEWIS Phone: 817-624-3848 Fax: 903-212-3041 Cell: 501-454-1007

Quote: 85587 ALF Type: Order: PO No:

Eng/Auth 06/24/18 15:27 Page 1

Stock: N **Brief Description**

Alum Live Floor Smooth Side ALF-FAIRFAX-EVO

Warranty Yrs 1 Entered By: JAJ Number of Units:

Sales Rep: Jerry Johnson (814) 233-7868 Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

End User: HGAC 48' 0" LENGTH DIMENSIONS: 96.000" WIDTH 100" CU. YD. = 108 HEIGHT 42" KING PIN SETTING 50" Overall Trailer Height: 12' 10.625" 5TH WHEEL HEIGHT 36' 8" From Back Of Gate LANDING GEAR LOCATION 12" CROSSMEMBER SPACING Alum EVO Side Panel Extrusion Alum EVO Top Rail Alum EVO LW Bottom Rail SIDE EXTRUSION BODY MATERIAL: TOP RAIL BOTTOM RAIL 1/4" ALUM BRITE BULKHEAD Top Rear Roller Brace REAR BRACE Intermediate Top Spring Brace Qty Keith 22 Slat #2299-3.5" 48' CYL 3.0 Qty: 1 INTERMEDIATE BRACE WALKING MECHANISM FLOOR: Powered by Customers Wetline HYDRAULICS 5100 couplers, Bulkhead HOOK UP HARDWARE TYPE Barndoor TAILGATE: Horizontal Panel Gate STYLE 1/4" ALUM BRITE SHEET 100" HEIGHT NUMBER OF PANELS Air Control Latch
*** NONE *** CONTROLS SLOP LATCH Rubber Gate Seal Z-Rail Extrusion 3/8" RUBBER SEAL LONGMEMBERS FRAME: 4" I-Beam @2.70# CROSSMEMBERS 12" Formed Steel SUSPENSION SUB-FRAME Holland Mark V Landing Gear LANDING GEAR Laminated center pin grab Intraax Tandem 25K w/Air Disc BUMPER SUSPENSION RUNNING GEAR: Axles included w/Suspension AXLES Included with Axle HUBS AND DRUMS DUAL TIRE STYLE Wheel 22.5x8.25 10H Pilot Stl WHEELS OUTSIDE Wheel 22.5x8.25 10H Pilot Stl TIRE,GOODYEAR,G316,11R22.5 WHEELS INSIDE TIRES Air Brake System 4S/2M BRAKES *** NONE *** ACCESSORIES: LADDERS FRONT Tailgate Mounted per previous orders LED Light Pkg., In Gate LADDERS BACK ELECTRICAL MISCELLANEOUS: J & J Mudflaps (Std) MUDFLAPS ***None*** MUDSHIELD Acid Clean BODY PAINT: As Specified Silver STEEL ATTACHMENTS ---- (Optional Equipment Is Included) ----

PIANO HINGE-12 PANEL W/AIR CONTROL AND DOOR AJAR LIGHT. 1/4" ALUM TAILGATE FACE SHEET. 3"-1/4" WALL TUBE HORIZ. BRACES. W/3/8" SHEDDER & 1/4" VERT

LANDING G LANDING GEAR TO HAVE CURBSIDE CRANK

(Continued on Next Page)

Order: PO No: Stock: N Page 2

Somerset, PA 15501

Phone: (814) 444-3400 Fax: (814) 443-2621

Brief Description Alum Live Floor Smooth Side

B & C BODY COMPANY 4400 BLUE MOUND RD FORTWORTH TX 76106 Attn: JIM LEWIS Phone: 817-624-3848 Fax: 903-212-3041

Cell: 501-454-1007 End User: HGAC

Customer

ALF-FAIRFAX-EVO Warranty Yrs: 1 Entered By: JAJ Number of Units: 1

Sales Rep: Jerry Johnson Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

SOLID 1" X 1" SUBDECK REAR 20" W/ INTERLOCK

FLOOR DANA DISC BRAKES, INSTLL DIAGNOSTIC CABLE #S449-364-143-0 W/PULL LANYARDS ON AIR TANK DRAIN VALVES

HYDRAULIC FLIP ROOF-INST. VERSITEX. DOUBLE ANGLES IN LIEU OF Z, ROOF ALUM. STRIPS IN LIEU OF FENDER WASHERS.... VERSITEX IS .085 THICK

OTHER 12' CONTROL CABLE COIL TYPE MALE. ENDS MOUNTED ON TRAILER OTHER 14' HYDRAULIC HOSES ON TRAILER W/ HOSE HANGER ٦

1 5100-20 ON RETURN-BOTH FEMALE HYDRAULICS AEROQUIP 5100-16 PRESSURE, AND 1

MUD FLAPS--AERODYNAMIC FULL WIDTH AT REAR. QUARTER SPLASH GUARDS 1 FLAPS IN FRONT OF TANDEM-VORTEX BRAND

REG. HOLD. BETTS MODEL PS-1 REGISTRATION HOLD- ER PASSENGER SIDE FRONT ELECTRONIC BACKUP ALARM INCLUDE WIRING TO REAR

INSIDE SHEDDER PLATE TO BE 1/4" FLOOR 1 BULKHEAD VISION WINDOW, EXP METAL WELDED TO STEEL ANGLE FRAME-USE

PERFORATED STEEL LIGHTS 12 VOLT TRUCKLITE, LIGHTS IN GATE. EXTRA 7 PIN PLUG FOR ABS SIDE MARKER LIGHTS EVENLY SPACED. 1

NONSMUDGE ALUMINUM INCLUDING WHEELS PAINT

OTHER STATE INSPEC, VIRGINIA 1

6000 SERIES LIGHT @ 3RD STEP INSTALL CENTER TAILGATE MOUNTED 1 OTHER

FROM BOTTOM ON GATE W/TAILGATE AIR CYLINDER UNDERNEATH BODY, CANNOT DO A PULL OUT STEPS 1

LADDER

INSTALL ALLIGATER V2B DOUBLE CHECK VALVE CAPS ON WHEELS OTHER 1 REAR HINGE PIN TO BE STAINLESS STEEL, AND REAR TURN SIGNALS OTHER

TO BE AMBER PREFERRED CUSTOMER DISCOUNT SPECIAL

AIR DISC BRAKES, BENDIX ADB-22X INSTALL CUSTOMER SUPPLIED ONBOARD BRAKES 1 AIRWEIGH SYSTEM-INCLUDES 50'

1 SCALE POWER & SENSOR CABLE.

INCLUDE ABS LINE 1 OTHER

STAINLESS STEEL HYDRAULIC TUBING FOR WALKING FLOOR HYDRAULICS 1 NOTE RAIL AND TOP OF GATE TO BE 96" OVERALL SIDE HEIGHT TO TOP OF TOP HEIGHT 1

NOT 100".

REMOVE HALF ROUND ON TOP OF TOPRAIL AS WAS ON ALL PREVIOUS TRLS. NOTE 1 TAILGATE LATCH CYLINDER IS UNDER-NEATH W/LATCHING ON OUTSIDE OF NOTE

POST. CROSSMEMB. REENFORCE EVERYOTHER CROSSMEMBER ON BOTH SIDES WITH GUSSETS, SAME

AS INSTALLED IN FIELD IN AUGUST 17. OTHER ON ROOF HINGES, POSITION GREASE ZERKS, SO THAT NONE OF THEM

POINT UPWARD WHEN ROOF IS CLOSED. REVIEW W/TIM SIMPSON.

Price / Unit Including Options: \$121,384.58

Total Due: \$121,384.58 Appx. Weight: 20,379 lbs

Terms: NET 30 DAYS

Ouote: 85587 # 2

Eng/Auth

Somerset Welding & Steel, Inc. 10558 Somerset Pike

Order: PO No: Page 3

Somerset, PA 15501

Stock: N

Phone: (814) 444-3400 Fax: (814) 443-2621

Brief Description

Customer B & C BODY COMPANY 4400 BLUE MOUND RD

Alum Live Floor Smooth Side ALF-FAIRFAX-EVO

FORTWORTH TX 76106 Attn: JIM LEWIS Phone: 817-624-3848 Warranty Yrs: 1 Entered By: JAJ

Fax: 903-212-3041 Cell: 501-454-1007 Number of Units: 1 Sales Rep: Jerry Johnson Inside Sales: Jerry Johnson E-Mail: JIM.LEWIS@BANDCBODY.COM

End User: HGAC

Special Remarks:

NOTES;

1) INCLUDE 2ND GREASE FITTING @180 DEGREE APART ON THE FRONT SPROCKETS. CANNOT RELOCATE GREASE FITTING TO THE FRONT SIDE AT BOTTOM AT THIS TIME.

2) RELOCATE GREASE FITTINGSON TOP DOORS AS DISCUSSED. 3) ELECTRICAL BOXES BEETTER SEAL, AND WEEP HOLES IN BOTTOMS.

4) HYDRAULIC TUBING TO BE STAINLESS STEEL.

NOTICE; STANDARD 5/8" WALL AXLES USED WITH THE AIR RIDE SUSPENSION CAN ONLY

BE RATED FOR 22,500 LB MAXIMUM LOAD RATING.

NOTE; OVERALL HEIGHT W/SIDE AND END ADJUSTMENT (96") WILL BE APPROX 12'7" ***************

Unless indicated above, F.E.T., and sales tax are NOT included in price.

NOTE: If a purchase order is required for payment, the purchase order must be provided before we enter this quote as an order and order any material for this job.

Please review carefully. If you have any questions, contact this office or your sales representative. If there are no questions, please sign and return one of the enclosed copies. We must have a signed copy of this quotation before we process and fabricate your order.

Terms: NET 30 DAYS

PRICE SUBJECT TO CHANGE AFTER 30 DAYS

J&J Dynahauler Model Popular Options List Price Option List Price

AlumInum IiveFloor Trailer

Base Mode! 45' Long X96" Wide ___\$84,811.00

HGAC CODE TR18MO56



TRUCK BODIES S: TRA!LERS'~'

ORM E - P	UBLISHED OPTIONS Procurement	No.:	TR11-18			
Offeror Name:						
	1) Use a single Form E for ALL Option/Accessory items and quote each on a single, separate line. DO NOT use multiple Form E's Add or insert additional lines as necessary. 2) Completely describe each item. Include the manufacturer's code or part number. Each item listed MUST have a					
Notes:	2) Completely describe each item. Include the manufacturer's code or part number. Each item listed MUST have a unique code or part number so that it can be identified in any subsequest contract. 3) Options which replace standard equipment on a Form D Item should be priced net of any credit due for the replaced item. 4) Options which are upgrades/downgrades of a Form D Item should be priced at the differential amount between the cost of the Form D Item and the upgrade/downgrade option.					
(Important)						
Code or Part No.	Option Description		Offered Price			
FAIRFAX ST	LE BASE MODEL	26	660.00			
48' ALF	48' LONG X 98" WIDE		3200.00			
45' ALF	45' LONG X 102" WIDE	56	00.00			
102' ALF	48' LONG X 102" WIDE	91	00.00			
HT300	HT300 AIR RIDE	56	00.00			
MRT	MOUNTAIN ROLL TARP W/ REAR G CONTROL & MESH COV	ER 35	500.00			
cw	CATWALK ON BULKHEAD	15	550.00			
STC-ALF	SPARE TIRE CARRIER	7	50.00			
HUB-ALF	HUB-O-METER	7:	50.00			
RGS-ALF	RUBBER GATE SEAL	9:	50.00			
ATT	ALUMINUM TIPPER TRAILER	-5	200.00			
STEEL LIVE	BASE MODEL (45' LONG X 96" WIDE	92	200.00			
	(45' LONG X 102" WIDE)	11	200.00			
	HT300 AIR RIDE	56	00.00			
	MOUNTAIN ROLL TARP	35	00.00			
***************************************	CATWALK ON BULKHEAD	15	550.00			
	SPARE TIRE CARRIER	7	50.00			
	RUBBER GATE SEAL	9:	50.00			
	REAR STOP	8	75.00			

6 :

Steel Push Out Trailer (SPO) Base Model (45' long X 96" wide - Open Top)	\$79,720
(45' long X 96" wide - Closed Top)	\$87,720
3/16" Hardox Floor	\$1,700
1/8" Hardox Sides	\$6,500
Spare Tire Carrier	\$750
Hub-O-Meter	\$750
Rubber Gate Seal	\$950
Rear Stop	\$875
DOFT / Donovan Double Flip Tarp	\$12,150
Consp / Conspiculty Tape	\$775
3568 / Ploneer RP4500SARG	\$10,295
19C8 / Manual Spool Additional for Compactors	\$550
16C / Tire Carrier Side Mounted	\$788
11D / Tri Axle Fenders	\$1,695
P/U / Pusher Axle w/ Wheels & Tires	\$9,200
AUX / Auxillary Fold Down Stops	\$466
WLK / Wet Line Kit added to existing Truck to mate to Trailer	\$6,225
PH / Pintle Hitch to existing Truck	\$2,500
HG03 / Hydraulic Landing Gear	\$2,483
OL56 / Rear Wings, Loading Ramps	\$798
29A / Rod Protector	\$886
SCLE / On Board Scales	\$1,475
HSTREF / Road Side Reflector Kit	\$325
TT9 / 7/8" Cable vs. ½" Cable	\$395
A5-OR-250 / A5-OR-250 Trailer from Base SP2A	\$28,350
A5-OR-330 / A5-OR-330 Trailer from Base SP2A	\$46,975
A5-OR-366 / A5-OR-366 Trailer from Base SP2A	\$47,339
FREIGHT / \$3.50 per mile	\$3.50/mile